

## Cisco MCS 7825-I5

Cisco® Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks, enabling easy collaboration every time from any workspace.

Cisco Unified Communications is a comprehensive IP communications system of voice, video, data, and mobility products and applications. It enables more effective, more secure, more personal communications that directly affect both sales and profitability. It brings people together by enabling a new way of communicating - where your business moves with you, security is everywhere, and information is always available whenever and wherever it is needed. Cisco Unified Communications is part of an integrated solution that includes network infrastructure, security, mobility, network management products, lifecycle services, flexible deployment and outsourced management options, end-user and partner financing packages, and third-party communications applications.

### Product Overview

The Cisco MCS 7825-I5 Media Convergence Server is an entry-level server platform used for Cisco Unified Communications Solutions. An integral part of a complete, scalable architecture for a new generation of high-quality IP voice solutions that run on enterprise data networks, the Cisco MCS 7825-I5 is an easily deployed, cost-effective solution that delivers the high performance and availability demanded by today's enterprise networks. At only 1 rack unit (1RU) high, the Cisco MCS 7825-I5 offers tremendous power in a low-profile chassis that minimizes rack space.

### Supported Cisco Applications

- Cisco Unified Application Environment
- Cisco Unified Communications Manager
- Cisco IP Interoperability and Collaboration System (IPICS)
- Cisco Emergency Responder
- Cisco Unified Contact Center Enterprise
- Cisco Unified Contact Center Express
- Cisco Unified Contact Center Hosted
- Cisco Unified Intelligent Contact Management Enterprise
- Cisco Unified Intelligent Contact Management Hosted
- Cisco Unified IP Interactive Voice Response (IP IVR)
- Cisco Unified Customer Voice Portal
- Cisco Unity® Connection

### Key Features and Benefits

#### Product Specifications

Table 1 gives information on the components of the Cisco MCS 7825-I5, and Table 2 gives information about equipment approvals and safety.

**Table 1.** Cisco MCS 7825-I5 Configuration

Component	Value
<b>Product part number</b>	MCS-7825-I5-CCX1 MCS-7825-I5-CCE1 MCS-7825-I5-IPC1 MCS7825I5-K9-CMD2 MCS7825I5-K9-CXA1 MCS7825I5-K9-UCC2
<b>Preload</b>	None
<b>OS included</b>	None
<b>Processor</b>	Single Intel x3430 quad-core 2.40-GHz; last level cache: 8 MB
<b>Memory included</b>	4-GB (two 2-GB DIMMs) dual-rank PC3-10600R-999 1333 MHz, fully buffered double data rate 3 (DDR3) registered DIMM (RDIMM)
<b>Memory maximum</b>	32 GB
<b>Memory bus clock</b>	Up to 1333 MHz
<b>Memory technology</b>	Registered PC3-10600 DDR3 1333-MHz dual-rank DIMM
<b>Multibit error mitigation</b>	Error Checking and Correcting (ECC)
<b>Total dual in-line memory module (DIMM) slots</b>	Six
<b>Basic input/output system (BIOS) type</b>	United Extensible Firmware Interface (UEFI)
<b>Hard disks</b>	Two 250-GB Serial Advanced Technology Attachment (SATA) 3.5-in. simple swap
<b>Simple swap bays</b>	Two
<b>Hard disk interface type</b>	SATA
<b>Hard disk spindle speed</b>	7200 rpm (revolutions per minute)
<b>Hard disk seek time</b>	11.9 ms (average)
<b>Hard disk latency</b>	4.2 ms (nominal)
<b>Data transfer rate</b>	Capable of 3 Gbps
<b>Hard Disk Form Size</b>	3.5-inch small form factor (SFF)
<b>Redundant Array of Independent Disks (RAID) controller model</b>	IBM ServeRAID BR10i SAS/SATA Controller v2
<b>RAID interface</b>	Connected to motherboard
<b>RAID cache</b>	0 MB
<b>Battery-backed write cache (BBWC)</b>	No
<b>RAID level</b>	Configured as a RAID 1
<b>Ethernet network interface card (NIC)</b>	Dual onboard 10/100/1000
<b>Ethernet connectors</b>	Two RJ-45 connectors on back of server
<b>10BASE-T cable support</b>	EIA Category 3, 4, or 5 unshielded twisted pair (UTP) (2 or 4 pair) up to 328 ft (100m)
<b>100BASE-TX cable support</b>	EIA Category 5 UTP (2 pair) up to 328 ft (100m)
<b>1000BASE-T cable support</b>	EIA Category 6 UTP (recommended), 5E UTP, 5 UTP (2 pair) up to 328 ft (100m)
<b>Serial ports</b>	1
<b>Parallel ports</b>	0
<b>USB 2.0 ports</b>	7 (2 front, 4 rear, and 1 internal)
<b>Keyboard ports</b>	Use one of the USB ports (PS/2 ports are not provided)
<b>Mouse ports</b>	Use one of the USB ports (PS/2 ports are not provided)
<b>Audio ports</b>	None
<b>Video Graphics Array (VGA) ports</b>	1 rear

Component	Value		
<b>System management ports</b>	Shared Ethernet port		
<b>Eight PCIe non-hot plug slots</b>	2		
<b>Dimensions (H x W x D)</b>	Height: 1.75 in. (1RU)	Height: 43 mm	
	Width: • 17.32 in.	Width: • 440 mm	
	Depth: • Overall: 22 in.	Depth: • Overall: 559 mm	
<b>Weight (maximum)</b>	28 lb	12.7 kg	
<b>Input requirements<sup>1</sup></b>	Rated line voltage: 100-127 VAC; 50 or 60 Hz		
	Input current (amps)	0.65 (idle) 1.74 (maximum measured) 6.0 (system rated) 40 (peak inrush current; 4 ms)	
	Leakage current (mA)	0.47 (idle; maximum measured; system rated)	
	Power (watts)	76 (idle) 196 (maximum measured) 351 (system rated)	
	VA rating (VA)	78 (idle) 201 (maximum measured) 351 (system rated)	
	BTU rating (BTU/hr)	259 (idle) 669 (maximum measured) 2047 (system rated)	
	Rated line voltage: 200-240 VAC; 50 or 60 Hz		
	Input current (amps)	0.37 (idle) 0.92 (maximum measured) 3.0 (system rated) 40 (peak inrush current; 4 ms)	
	Leakage current (mA)	0.47 (idle; maximum measured; system rated)	
	Power (watts)	75 (idle) 192 (maximum measured) 351 (system rated)	
	VA rating (VA)	77 (idle) 197 (maximum measured) 351 (system rated)	
	BTU rating (BTU/hr)	256 (idle) 656 (maximum measured) 2047 (system rated)	
	<b>Power supply output power</b>	Rated steady-state power	351W
	<b>Temperature range</b>	Operating	50 to 95°F (10 to 35°C) at 0-3000 ft (0-914.4m) with an altitude de-rating of 1.4°F (0.75°C) per 1000 ft (304.8m)
Nonoperating		50 to 109.4°F (10 to 43°C)	
Shipment		-104 to 140°F (-40 to 60°C)	

<sup>1</sup> Maximum measured values were determined with 77°F (25°C) ambient temperature, and your results may vary. Idle power: Power drawn with the machine(s) logged into the OS, and no other applications running. Memory, HDDs, optical drives, and tape drives are not being used. Measured maximum power: Maximum measured power is the power drawn by the machine with the CPUs 100-percent used and memory is used 10 percent more than base usage. The exerciser used is Prime95 (torture test); you can download it at <http://www.mersenne.org> Rated system maximum: The maximum power the machine can draw according to the system label rating.

Component	Value	
<b>Relative humidity (RH; noncondensing)</b>	Operating Shipment	8 to 80% 8 to 80%
<b>Maximum altitude</b>	7000 ft	2133m
<b>Acoustic noise</b>	Operating minimum	L WAd (bels) 6.5
<b>Airflow (cubic feet per minute [cfm])</b>	20 CFM minimum	31 cfm maximum
<b>Remote management</b>	IBM Integrated Management Module included (user-installable Virtual Media Key available) on a shared Ethernet connector	

**Table 2.** Equipment Approvals and Safety

Equipment Approvals and Safety
<ul style="list-style-type: none"> <li>• FCC - Verified to comply with Part 15 of the FCC Rules, Class A</li> <li>• ICES-003 Class A</li> <li>• AS/NZS CISPR22 Class A</li> <li>• CISPR22 Class A</li> <li>• CISPR24 Class A</li> <li>• EN55022 Class A</li> <li>• EN55024</li> <li>• IEC 61000-3-2</li> <li>• IEC 61000-3-3</li> <li>• KN22 Class A</li> <li>• CNS13438 Class A</li> <li>• GB9254 Class A</li> <li>• GB4943</li> <li>• VCCI-03 Class A</li> <li>• CSA C22.2 No. 60950-1-07</li> <li>• UL 60950-1 2nd Edition</li> <li>• IEC/EN 60950-1 2nd Edition</li> <li>• CE Mark (Low Voltage Directive 2006/95/EC, EMC Directive 2004/108/EC</li> <li>• KN24</li> </ul>

## Ordering Information

Tables 3 through 5 give ordering information for the Cisco MCS 7825-I5.

**Table 3.** Ordering Information

Product Name	Part Number
<b>Cisco Unified Application Environment</b>	See Cisco Unified Application Environment data sheet
<b>Cisco Unified Communications Manager 4.3</b>	See Cisco Unified Communications Solutions Ordering Guide
<b>Cisco Emergency Responder</b>	See Emergency Responder datasheet
<b>Cisco Unified Intelligent Contact Management Enterprise</b>	See Contact Center Ordering Guide
<b>Cisco Unified Intelligent Contact Management Hosted</b>	See Contact Center Ordering Guide
<b>Cisco Unified Contact Center Enterprise</b>	See Contact Center Ordering Guide
<b>Cisco Unified Contact Center Hosted</b>	See Contact Center Ordering Guide
<b>Cisco Unified Contact Center Express</b>	See Contact Center Ordering Guide
<b>Cisco Unified IP IVR</b>	See Contact Center Ordering Guide
<b>Cisco Unified Customer Voice Portal</b>	It is applicable for CVP Operation Server. Please check CCBU Ordering Guide for detail
<b>Cisco Unity Connection</b>	See the Unity Connection Ordering Guide

**Table 4.** Spare Server Ordering Information

Product Name	Part Number
Cisco MCS 7825-I5 for Cisco Unified Application Environment	MCS-7825-I5-IPC1
Cisco MCS 7825-I5 for Cisco Emergency Responder 1.3	MCS-7825-I5-IPC1
Cisco MCS 7825-I5 for Cisco Unified Communications Manager	MCS-7825-I5-IPC1 MCS7825I5-K9-CMD2
Cisco MCS 7825-I5 for Cisco IPCS	MCS-7825-I5-S31
Cisco MCS 7825-I5 for Cisco Unified Contact Center Enterprise	MCS-7825-I5-CCE1
Cisco MCS 7825-I5 for Cisco Contact Center Express	MCS-7825-I5-CCX1 MCS7825I5-K9-CXA1
Cisco MCS 7825-I5 for Cisco Unified Contact Center Hosted	MCS-7825-I5-CCE1
Cisco MCS 7825-I5 for Cisco Unified Intelligent Contact Manager Enterprise	MCS-7825-I5-CCE1
Cisco MCS 7825-I5 for Cisco Unified Intelligent Contact Manager Hosted	MCS-7825-I5-CCE1
Cisco MCS 7825-I5 for Cisco Unified IP IVR	MCS-7825-I5-CCX1 MCS7825I5-K9-CXA1
Cisco MCS 7825-I5 for Cisco Unified CVP Operation Server	MCS-7825-I5-CCE1
Cisco MCS 7825-I5 for Cisco Unity Connection	MCS-7825-K9-UCC2

**Table 5.** Spare Parts Ordering Information

Description	Spare Part Number
Spare 2GB DIMM for MCS 7816/25/28-I5	MEM-78xx-I5-2GB=
Spare 250GB Hard Disk Drive for MCS 7816/25/28-I5	HDD-78xx-I5-250=

## Warranty Information

Cisco offers a 1-year limited hardware warranty on Cisco Media Convergence Servers. For terms and conditions of this warranty, refer to [http://www.cisco.com/en/US/docs/general/warranty/English/1Y1DEN\\_.html](http://www.cisco.com/en/US/docs/general/warranty/English/1Y1DEN_.html).

## Cisco Unified Communications Services

Cisco Unified Communications Services allows you to accelerate cost savings and productivity gains associated with deploying a secure, resilient Cisco Unified Communications Solution. Delivered by Cisco and our certified partners, our portfolio of services is based on proven methodologies for unifying voice, video, data, and mobile applications on fixed and mobile networks. Our unique lifecycle approach to services can enhance your technology experience to accelerate true business advantage.



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)