



## Cisco MCS 7815-I1 Unified CallManager Appliance

**THIS PRODUCT IS NO LONGER BEING SOLD AND MIGHT NOT BE SUPPORTED. READ THE END-OF-LIFE NOTICE TO LEARN ABOUT POTENTIAL REPLACEMENT PRODUCTS AND INFORMATION ABOUT PRODUCT SUPPORT.**

The Cisco® Unified Communications system of voice and IP communications products and applications enables organizations to communicate more effectively—enabling them to streamline business processes, reach the right resource the first time and impact the top and bottom line. The Cisco Unified Communications portfolio is an integral part of the Cisco Business Communications Solution—an integrated solution for organizations of all sizes which also includes network infrastructure, security, and network management products, wireless connectivity, and a lifecycle services approach, along with flexible deployment and outsourced management options, end-user and partner financing packages, and third-party communications applications.

### PRODUCT OVERVIEW

The Cisco Media Convergence Server 7815-I1 (MCS-7815-I1) Unified CallManager Appliance is an entry-level appliance for Cisco Unified CallManager 5.0 and is an integral part of a complete, scalable architecture for a new generation of high-quality IP communications solutions for enterprise data networks. It delivers the high performance and availability that today's enterprise networks demand and represents a turnkey solution that is easy to deploy and highly cost-effective. The server appliance is preinstalled with an operating system and the Cisco Unified CallManager 5.0 application. The server appliance is fully operational upon startup, requiring entry of just a few configuration items such as IP address and domain. It includes the following features and components:

- Intel 3.06GHz or higher processors with 800 MHz front side bus (FSB) and 1 MB Layer 2 cache
- PC3200 CL3 error correction code (ECC) Double Data Rate (DDR) synchronous dynamic RAM (SDRAM) standard; 4GB SDRAM maximum
- Integrated Serial Advanced Technology Attachment (SATA) Controller
- 80GB SATA hard disk drive
- Single gigabit Ethernet port

### PRODUCT SPECIFICATIONS

Table 1 lists the product specifications for the Cisco MCS7815I1-K9-CM50.

**Table 1.** Product Specifications

Processor at Product Introduction	
Processor (CPU)	Intel Pentium 4
Processor Internal Clock Speed	3060MHz
Layer 2 Cache	1024KB
Maximum Processors	1
Processors Installed	1

Basic Input/Output System (BIOS) Type	Flash
<b>Memory</b>	
Memory Maximum	4GB
Memory Bus Clock	200MHz
Memory Technology	PC3200 DDR SDRAM
Total RAM Slots	4
Memory Installed	2GB
<b>Hard Disk</b>	
Hard Disk Installed	80GB SATA
Hard Disk RPM	7200
Hard Disk Average Seek Time	< 9 ms
Hard Disk Controller	I/O Controller Hub (ICH)-S SATA controller on motherboard
Hard Disk Type	Serial-ATA Easy Swap
<b>Network Connectivity</b>	
Network Interface Card (NIC)	Single onboard 10/100/1000
Connector	One RJ-45 connector on rear of server
10BASE-T Cable Support	Categories 3, 4, or 5 unshielded twisted-pair (UTP) (2 or 4 pair) up to 328 feet (100 meters)
100BASE-TX Cable Support	Category 5 UTP (2 pair) up to 328 feet (100 meters)
1000BASE-T Cable Support	Category 5 UTP, 5E UTP, 6 UTP (2 pair) up to 328 feet (100 meters)
<b>Interfaces</b>	
Serial Ports	2
Parallel Ports	1
Universal Serial Bus (USB) 2.0 Ports	4
Keyboard Ports	1 PS2
Mouse Ports	1 PS2
Audio Ports	None
<b>Interface Card Slots</b>	
Peripheral Component Interconnect (PCI) 2.2 Full Length Slots (32/33 MHz)	3
PCI-X Full Length Slots (64/66 MHz)	2
<b>Security</b>	
<ul style="list-style-type: none"> <li>• Power-on password</li> <li>• Selectable boot device security</li> <li>• U-Bolt tie-down security</li> <li>• Flash erasable programmable read-only memory (EPROM) write protection security</li> </ul>	

**Equipment Approvals and Safety**

- FCC—Verified to comply with Part 15 of the Federal Communications Commission (FCC) Rules, Class A
- Canada Information Collection and Evaluation Standard (ICES)-003, issue 3, Class A
- Underwriters Laboratories 1950
- CSA C22.2 No. 950
- NOM-018

**Power**

Maximum Input Power	340W
Auto-Ranging AC Mains Input	Yes
Power Factor Correction (PFC)	Yes
Mains Input Frequency Range	50 to 60 Hz
Input Voltage Low Range	<ul style="list-style-type: none"><li>• 90 VAC minimum</li><li>• 137 VAC maximum</li></ul>
Input Voltage High Range	<ul style="list-style-type: none"><li>• 180 VAC minimum</li><li>• 265 VAC maximum</li></ul>
Input Kilovolt-Amperes (kVA) Approximate	<ul style="list-style-type: none"><li>• 0.15 kVA minimum</li><li>• 0.80 kVA maximum</li></ul>

**Environmental**

Air Temperature—Server On	50.0 to 95.0°F (10 to 35°C )
Air Temperature—Server Off	50 to 109.4°F (10 to 43°C )
Humidity—Server On	8 to 80 percent
Humidity—Server Off	5 to 95 percent
British Thermal Unit (BTU) Rating Minimum	341 BTU per hour
BTU Rating Maximum	1604 BTU per hour
Sound Emissions Idle	5.1 bel
Sound Emissions Maximum	5.3 bel
Cooling System	2 fans installed

**Dimensions**

Form Factor	Tower
Rack-Mounting	4U standard rack-mount with optional rack-mount kit ordered
Weight—Maximum	24.58 lb (11.15 kg)
Height	18.5 in. (455 mm)
Width	6.5 in. (165 mm)
Depth	17.25 in. (498 mm)

## ORDERING INFORMATION

To order this product, visit the [Cisco Ordering Home Page](#) or visit <http://www.cisco.com/en/US/ordering/index.shtml>.

You may order the appliance in one of two ways. You can enter CALLMANAGER-5.0 into the Dynamic Configuration Tool on Cisco.com and view a list of Cisco MCS Unified CallManager Appliances and their associated licenses. You can also order the components individually using the following product IDs:

- MCS781511-K9-CM50
- LIC-CM5.0-K9-7815-I1=
- KEY-CCM-ADMIN-K9= (order a minimum quantity of 2)

## SERVER SPARES

To order spare servers, refer to Table 2.

**Table 2.** Ordering Information for Spare Server Appliance with Operating System and Cisco Unified CallManager 5.0

Application	Spare Part Number
Cisco Unified CallManager 5.0	MCS781511-K9-CM50

## FIELD REPLACEABLE SPARES

To order spare parts for the servers, refer to Table 3.

**Table 3.** Ordering Information for Server Appliance Spare Parts

Description	Spare Part Number
Spare 512 MB SDRAM Dual In-Line Memory Module (DIMM) for Cisco MCS 7815-I1 Server	MEM-7815-I1-512=
Spare 1GB SDRAM Dual In-Line Memory Module (DIMM) for Cisco MCS 7815-I1 Server	MEM-7815-I1-1GB=
Spare 80 GB SATA Easy Swap Hard Disk Drive	HDD-7815-I1-80=
Rack-Mounting Rail Kit for Cisco MCS 7815-I1	RAIL-7815-I1=

## IDENTIFYING CPU SPEED OF SERVER

As the Cisco MCS 781511-K9-CM50 matures and Intel replaces slower processors, the processor speeds will change. Table 4 provides the Cisco manufacturing part number that will be shown on the chassis to help identify any processor speed of any individual server appliance.

**Table 4.** Manufacturing Part Numbers by Processor Speed

Processor	Manufacturing Part Number Located on Server	Introduction
Intel Pentium 4 3.06GHz	74-4385-01	Initial production of server appliance

## CISCO UNIFIED COMMUNICATIONS SERVICES AND SUPPORT

Using the Cisco Lifecycle Services approach, Cisco Systems® and its partners offer a broad portfolio of end-to-end services to support the Cisco Unified Communications system. These services are based on proven methodologies for deploying, operating, and optimizing IP communications solutions. Upfront planning and design services, for example, can help you meet aggressive deployment schedules and minimize network disruption during implementation. Operate services reduce the risk of communications downtime with expert technical support. Optimize services enhance solution performance for operational excellence. Cisco and its partners offer a system-level service and support approach that can help you create and maintain a resilient, converged network that meets your business needs.

## WARRANTY INFORMATION

Cisco offers a one-year limited hardware warranty on Cisco Media Convergence Servers. For terms and conditions of this warranty, refer to [http://www.cisco.com/univercd/cc/td/doc/es\\_inpk/1y1cen.htm](http://www.cisco.com/univercd/cc/td/doc/es_inpk/1y1cen.htm).



**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

CCDE, CCENT, Cisco Eos, Cisco StadiumVision, the Cisco logo, DCE, and Welcome to the Human Network are trademarks. Changing the Way We Work, Live, Play, and Learn is a service mark, and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IQ Expertise, the IQ logo, IQ Net Readiness Scorecard, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0803R)

