

Cisco TelePresence Serial GW 3340

Product Overview

The Cisco TelePresence[®] Serial GW 3340 is part of the industry-leading Cisco TelePresence videoconferencing solution. It allows transparent integration between IP and serial videoconferencing networks (Figure 1). A easy to configure appliance with feature transparency plus powerful dial-plan capabilities, it allows organizations using networks attached through serial interfaces to gain all the benefits from IP-based high-definition (HD) videoconferencing solutions.

Figure 1. Cisco TelePresence Serial GW 3340




Features and Benefits

Table 1 summarizes the key features of the Cisco TelePresence Serial GW 3340, and Figure 2 shows an example of secure serial connectivity to a videoconferencing multipoint control unit (MCU).

Table 1. Cisco TelePresence Serial GW 3340 Feature Summary

Feature	Benefit
Design features	<ul style="list-style-type: none"> Standards-based and compatible with all major vendors' IP video endpoints and MCUs Pay as you grow - buy the capacity you need now and upgrade in the future with a software license Easily configurable unit Comprehensive remote web management Eight independently clocked ports Support for V.35, RS-449, and EIA-530 synchronous serial data interfaces and RS-366 dialing
Application features	<ul style="list-style-type: none"> Provides transparent integration between IP and serial devices Supports external serial encryption devices, including Loss of Synchronization (LOS) support Supports H.239 for content sharing Offers powerful dial plans to ensure that your calls get routed efficiently Fully integrated, with built-in gatekeeper Supports automatic load balancing in multiple gateway environments
Performance features	<ul style="list-style-type: none"> Offers video resolutions up to HD 720p at 30 fps Supports up to 8 serial ports in a single appliance Supports up to 8 video calls at 1920 kbps Supports bandwidth per call from 56 to 1920 kbps

Figure 2. Example of Serial Connectivity to a Video Conferencing MCU



Product Specifications

Table 2 lists the core gateway specification; Table 3 gives video and audio specifications; Table 4 gives network, security, and management specifications; and Table 5 lists the physical specifications for the Cisco TelePresence Serial GW 3340.

Table 2. Core Gateway Specifications

Endpoints and serial devices supported	<ul style="list-style-type: none"> • H.323 IP video endpoints • Synchronous serial interface devices
Serial interfaces supported	<ul style="list-style-type: none"> • V.35, RS-449, and EIA-530 (data terminal equipment [DTE] mode)
Serial dialing interface	<ul style="list-style-type: none"> • RS-366
Presentation and data collaboration	<ul style="list-style-type: none"> • Data from H.239 (dual video)-capable endpoints
Call routing from serial network	<ul style="list-style-type: none"> • Interactive voice response (IVR) and Auto Attendant • Default (operator) extension • Call routing to MCU (or bridge) • Flexible dial plan • Terminal Command String for extension address (TCS-4) support
Call routing from IP (H.323)	<ul style="list-style-type: none"> • IVR and Auto Attendant • Dial by E.164 address • Dialed number digit manipulation • Flexible dial plan • Dial from MCU with and without a gatekeeper
Embedded web server	<ul style="list-style-type: none"> • Complete configuration, control, and monitoring of the system
Built-in gatekeeper	<ul style="list-style-type: none"> • Resolution of E.164 numbers • Registration of endpoints and gateways • Ability for up to 25 devices to register
Embedded encryption	<ul style="list-style-type: none"> • Standards based on Advanced Encryption Standard (AES) 128-bit key • Automatic key generation and exchange • Transparent encryption
Software license	<ul style="list-style-type: none"> • Serial port licenses required to enable serial interface ports

Table 3. Video and Audio Specifications

Bandwidth	<ul style="list-style-type: none"> • Serial and H.323 calls supported up to 1920 kbps • Total bandwidth and number of sites supported limited only by serial capacity
Video standards	<ul style="list-style-type: none"> • H.261, H.263, H.263+, and H.264
Video resolution	<ul style="list-style-type: none"> • QCIF, QSIF, CIF, SIF, iCIF, iSIF, 288p, 384p, 400p, 448p, VGA, 4CIF, 4SIF, 480p, SVGA, 576p, XGA, and 720p
Frame rates	<ul style="list-style-type: none"> • Up to 30 frames per second and 60 fields per second
Audio standards	<ul style="list-style-type: none"> • G.711, G.722, G.728, and G.722.1 Annex C
Other standards	<ul style="list-style-type: none"> • H.323, H.320 (serial), H.233, H.234, H.235 (AES), H.239 (dual video), FTP, Real-Time Transport Protocol (RTP), HTTP, Secure HTTP (HTTPS), Dynamic Host Configuration Protocol (DHCP), Simple Network Management Protocol (SNMP), and Network Time Protocol (NTP)

Table 4. Network, Security, and Management Specifications

Protocols	<ul style="list-style-type: none"> • IPv4
Quality of service (QoS)	<ul style="list-style-type: none"> • Configurable differentiated services code point (DSCP) or type of service (ToS)/IP Precedence • H.323 flow control • Dynamic jitter buffers

Security features	<ul style="list-style-type: none"> • Two levels of access rights and privileges for users • Strong password policy • Secure management with HTTPS • Dial-plan system that controls which destinations are reachable • Ability to disable some services: HTTP, HTTPS, FTP, H.323, SNMP, and H.323 GK • H.235 authentication for gatekeeper registration • Secure non-PC hardware and operating system • AES encryption, 128-bit key, H.233, H.234, and H.235 • Transport Layer Security (TLS) certificate verification • Second Ethernet port • Audit log
Interfaces	<ul style="list-style-type: none"> • Up to 8 serial ports and 4 physical connections: <ul style="list-style-type: none"> ◦ Four 68-pin serial connectors: Compatible with Cisco TelePresence Serial GW 3340 Y-cable (one 68-pin connector to two 26-pin connectors); separate cables available to go from 26-pin to V.35, RS-449, or RS-530 • Two RJ-45 Ethernet, 10-/100-/1000-Mbps full or half duplex, manual or autosensing • RJ-45 serial port • CompactFlash socket • Up to 38 status LEDs
System management	<ul style="list-style-type: none"> • Management through embedded web server • XML application programming interface (API) • RS-232 for local control and diagnostics • Syslog for diagnostics • Configurable event logs and full H.323 decoding • Configuration backup to network • Secure upgrades through Ethernet or CompactFlash • Call detail records (CDRs) downloadable as XML • SNMP

Table 5. Physical Specifications

Chassis physical dimensions (H x W x D)	<ul style="list-style-type: none"> • Physical dimensions: 1.73 x 17.2 x 12.3 in. (310 x 437 x 312 mm) 19-in. rack-mountable (kit supplied)
Weight	<ul style="list-style-type: none"> • 10.25 lb (4.65 kg)
Power	<ul style="list-style-type: none"> • 100-240 VAC, 50 or 60 Hz, 380 BTU/hr (111W) maximum heat dissipation
Environmental data	<ul style="list-style-type: none"> • Operating temperature: 32 to 95°F (0 to 35°C) ambient • Relative humidity below 95% (noncondensing)
Approvals and compliance	<ul style="list-style-type: none"> • European safety: EN 60950-1:2001 • USA safety: UL 60950-1 First Edition • Canada safety: CSA 60950-1-03 • CE Marked • EMC: <ul style="list-style-type: none"> ◦ EN55022 class A ◦ EN61000-3-2, EN61000-3-3 ◦ EN55024: EN61000-4-2,-3,-4,-5,-6,-11 ◦ FCC Part 15 class A ◦ VCCI class A ◦ AS/NZS 3548 (C-Tick) • RoHS compliant

Warranty Information

Find warranty information on Cisco.com at the [Product Warranties](#) page.

Ordering Information

To place an order, visit the [Cisco Ordering Home Page](#) and refer to Table 6 or contact your local Cisco representative. To download software, visit the [Cisco Software Center](#).

Table 6. Ordering Information

Product Name	Part Number
Cisco TelePresence Serial GW 3340	CTI-3340-GWS-K9
Includes: Serial GW 3340 - Gateway and cables and four serial port licenses - included serial port licenses require optional Serial GW Y Cables to operate	
Software License Options	
4 additional serial ports on the Serial GW 3340	LIC-3300-GWS-4PL
AES and HTTPS Enable Option for Serial GW 3340	LIC-AESGW33-K9
Cisco TelePresence Serial GW 3340 license PAK (Product Authorization Key) for post sale upgrades	L-GW3300-UPG-PAK
Start with L-MCU5300-UPG-PAK in order to obtain post sales upgrades for the software options above apart from LIC-AESGW33-K9	
Cisco TelePresence Serial GW Y Cable to 2 DB26 connectors	CTI-GWS-CAB-2DB26=
Cisco TelePresence Serial GW 16 DB26 Rack Mount Bracket Kit	CTI-GWS-16DB-BRK=
AES and HTTPS Encryption Option for Serial GW 3340 post sales upgrade	L-AESGW33-K9=

Cisco Services

Cisco and our partners provide a broad portfolio of intelligent, personalized services and support that can help you realize the full value of your Cisco TelePresence investment by increasing business agility and network availability. This portfolio of services accelerates business innovation through a network-based collaboration platform that enables businesses to collaborate anywhere, anytime. For more information about these services, please visit: <http://www.cisco.com/go/telepresenceservices>.

For More Information

For more information about the Cisco TelePresence Serial GW 3340, please visit <http://www.cisco.com/go/telepresence> or contact your local Cisco account representative or authorized Cisco partner. Product specifications are estimates and subject to change without notice.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)