

Cisco Professional Series 47-inch LCD 110L

Product Overview

The Cisco® Professional Series 47-inch LCD 110L (Cisco LCD 110L PRO 47), shown in Figure 1, offers cutting-edge features along with visual appeal to emphasize your customer-facing communications. This 47-inch professional display complements the Cisco Digital Media Suite (DMS). It is fully compatible with Cisco Digital Media Players, and you can manage the display centrally from the Cisco Digital Media Manager platform, giving you a single-vendor solution for your Cisco Digital Media Suite deployment.

Figure 1. Cisco LCD 110L PRO 47



Features

Features of the Cisco LCD 110L PRO 47 include:

- High brightness and contrast ratio
- Landscape and portrait mode support
- HDMI inputs for real full HD content rendering
- Optional speakers for advanced audio applications
- Central management through the Cisco Digital Media Manager

Table 1 lists the features and benefits of the Cisco LCD 110L PRO 47.

Table 1. Cisco LCD 110L PRO 47 Features and Benefits

Feature	Benefit
Integrated with Cisco Digital Media Suite	Tested to work with Cisco Digital Media Suite products
Low total cost of ownership (TCO)	Single vendor for all requirements to reduce costs and save time and long-term operating expenses
Cisco Services (Cisco SMARTnet® Next Business Day [NBD] replacement)	Exceptional, dependable, and proven service from industry-renowned Cisco support organization
Cisco Capital® leasing and financing options	Easy availability of financing options

Product Specifications

Table 2 lists the product specifications for the Cisco LCD 110L PRO 47.

Table 2. Cisco LCD 110L PRO 47 Product Specifications

Feature	Specification
Diagonal size	47 in.
Native resolution	1920 x 1080 (HDMI)
Resolutions supported	1080p, 1080i, and 720p
Brightness (typical)	700 cd/m2
Contrast ratio (typical)	1300:1
Viewing angle (Horizontal/Vertical)	178/178 degrees
Response time	10 ms
Pixel pitch	0.5415 x 0.5415
Horizontal frequency	30 ~ 83k Hz (RGB, HDMI/DVI)
Vertical frequency	56 ~ 75 Hz (RGB), 60 Hz (HDMI/DVI)
Inputs	HDMI/DVI, RGB, Composite, and Component
Speaker	Optional (10W x 2)
Power consumption (maximum)	~260W
Power consumption at standby (maximum)	1W (RGB)/2W (HDMI/DVI)
Power supply	100~240V, 50/60 Hz
VESA mount	800 x 400 mm
Weight (set/package)	48.94lb/65.26 lb (22.2kg/29.6kg)
Dimensions (H x W x D)	42.50 x 24.59 x 4.83 in. (107.95 x 62.46 x 12.29 cm)
Bezel width	17.9 mm
Operating temperature	0-40°C
Humidity	10-80%
Mean time between failure (MTBF)	50,000 hours
Built-in TV tuner	No
Special features	<ul style="list-style-type: none"> • Lamp error detection • Temperature sensor • Built-in fan • Tile Mode (5x5) • RS-232C • Energy Star 5.0

Table 3 lists regulatory and compliance specifications for the Cisco LCD 110L PRO 47, in accordance with Commission Regulation (EC) 642/2009.

Table 3. Cisco LCD 110 PRO 47 Regulatory and Compliance Specifications

Parameter	Specification
Lab tested on-mode power consumption	236W
Lab tested standby mode power consumption	0.41W
Lab tested off-mode power consumption	NA
Forced menu	NA
Peak luminance ¹	90.5%
Mercury content	99.0mg
Lead content ²	Yes

Parameter	Specification
	Note 1: Defined as the ratio of the peak luminance of the on-mode condition of the television as delivered by the manufacturer and the peak luminance of the brightest on-mode condition provided by the television, expressed in percentage, rounded to the nearest integer.
	Note 2: Assembled with lead-free solder. This product contains lead only in certain parts or components where no technology alternatives exist in accordance with existing exemption clauses under the RoHS Directive.

System Requirements

The Cisco LCD 110L PRO 47 requires a stand (optional) or corresponding mount (not sold through Cisco) for suitable installation, depending on your deployment location and situation.

Warranty Information

Find warranty information on Cisco.com at the [Product Warranties](#) page.

Ordering Information

You can order the Cisco LCD 110L PRO 47 as part of a Cisco Digital Media Suite deployment or independently. Table 4 gives ordering information.

Table 4. Cisco LCD 110L PRO 47 Ordering Information

Product Name	Part Number
Cisco LCD L-Series 47" Display, 1080p, With Remote Control	LCD-110L-PRO-47

Service and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full value of your video investment, and increase business agility and network availability. This portfolio of services drives business transformation through a network-based collaboration platform that enables business to collaborate anywhere, anytime.

Specifically for Cisco LCD products, you can buy standard Cisco SMARTnet Next Business Day (NBD) replacement service and 24-hour phone support from the Cisco Technical Assistance Center (TAC) worldwide.

For more information about these services, visit: <http://www.cisco.com/go/services/digitalmedia>.

For More Information

For more information about the Cisco LCD 110L PRO 47, visit <http://www.cisco.com/go/dms> or contact your local Cisco account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)