

OSPF Routers Connected by a Point-to-Multipoint Link

Document ID: 47862

Contents

Introduction

Prerequisites

- Requirements
- Components Used
- Conventions

Configure

- Network Diagram
- Configurations

Verify

- Examine the OSPF Database
- Calculate the Shortest Path

Troubleshoot

Related Information

Introduction

This document shows two Open Shortest Path First (OSPF) routers connected by a point-to-multipoint link.

Prerequisites

Requirements

There are no specific requirements for this document.

Components Used

This document is not restricted to specific software and hardware versions.

Conventions

Refer to Cisco Technical Tips Conventions for more information on document conventions.


Configure

In this section, you are presented with the information to configure the features described in this document.

Note: Use the Command Lookup Tool (registered customers only) to find more information on the commands used in this document.

Network Diagram

This document uses this network setup:



Configurations

This document uses these configurations:

- Router 1.1.1.1
- Router 2.2.2.2

Router 1.1.1.1
<pre> Current configuration: hostname r1.1.1.1 interface Loopback0 ip address 1.1.1.1 255.0.0.0 interface Ethernet2/0/0 ip address 4.0.0.1 255.0.0.0 interface Serial2/1/0 ip address 5.0.0.1 255.0.0.0 ip ospf network point-to-multipoint router ospf 1 network 4.0.0.0 0.255.255.255 area 0 network 5.0.0.0 0.255.255.255 area 0 end </pre>

Router 2.2.2.2
<pre> Current configuration: hostname r2.2.2.2 interface Loopback0 ip address 2.2.2.2 255.0.0.0 interface Ethernet0/0/4 ip address 6.0.0.2 255.0.0.0 interface Serial2/1/0 ip address 5.0.0.2 255.0.0.0 ip ospf network point-to-multipoint router ospf 2 network 6.0.0.0 0.255.255.255 area 0 network 5.0.0.0 0.255.255.255 area 0 end </pre>

Verify

This section provides information you can use to confirm your configuration is working properly.

The Output Interpreter Tool (registered customers only) (OIT) supports certain **show** commands. Use the OIT to view an analysis of **show** command output.

- **show ip ospf database** Displays a list of the Link State Advertisements (LSAs) and types them into a link state database. This list shows only the information in the LSA header.
- **show ip ospf database [router] [link-state-id]** Displays a list of all of a router's LSAs in the database. LSAs are produced by every router. These fundamental LSAs list all of the routers' links or interfaces, along with the states and outgoing costs of the links. They are flooded only within the area in which they originate.

Examine the OSPF Database

In order to see how the OSPF database looks given this network environment, look at the output of the **show ip ospf database** command.

```
r2.2.2.2#show ip ospf database

      OSPF Router with ID (2.2.2.2) (Process ID 2)

          Router Link States (Area 0)

Link ID        ADV Router    Age      Seq#           Checksum      Link count
1.1.1.1        1.1.1.1        206     0x8000000A     0x158C         3
2.2.2.2        2.2.2.2        206     0x8000000B     0x791          3

r2.2.2.2#show ip ospf database router 1.1.1.1

      OSPF Router with ID (2.2.2.2) (Process ID 2)

          Router Link States (Area 0)

LS age: 224
Options: (No TOS-capability, DC)
LS Type: Router Links
Link State ID: 1.1.1.1

!--- For router links, Link State Id is always the same
!--- as the Advertising Router (next line).

Advertising Router: 1.1.1.1

!--- This is the router ID of the router that created
!--- this LSA.

LS Seq Number: 8000000A
Checksum: 0x158C
Length: 60
Number of Links: 3

Link connected to: another Router (point-to-point)

!--- This line shows that this router(1.1.1.1) is a
!--- neighbor with 2.2.2.2.

(Link ID) Neighboring Router ID: 2.2.2.2
(Link Data) Router Interface address: 5.0.0.1
```

*!--- This line shows the interface on this router
!--- (1.1.1.1) that connects the neighbor (2.2.2.2).*

Number of TOS metrics: 0
TOS 0 Metrics: 64

!--- The OSPF cost of the link is 64.

Link connected to: a Stub Network

*!--- This router's (1.1.1.1) interface on the
!--- point-to-multipoint network.*

(Link ID) Network/subnet number: 5.0.0.1
(Link Data) Network Mask: 255.255.255.255

*!--- Notice the mask. Only the interface is advertised,
!--- not the whole subnet.*

Number of TOS metrics: 0
TOS 0 Metrics: 0

*!--- The OSPF cost for this router to reach its
!--- own interface is zero.*

Link connected to: a Stub Network

!--- Represents the subnet of the Ethernet segment 4.0.0.0/8.

(Link ID) Network/subnet number: 4.0.0.0
(Link Data) Network Mask: 255.0.0.0
Number of TOS metrics: 0
TOS 0 Metrics: 10

!--- The cost of the link is 10.

r2.2.2.2#show ip ospf database router 2.2.2.2

OSPF Router with ID (2.2.2.2) (Process ID 2)

Router Link States (Area 0)

LS age: 253
Options: (No TOS-capability, DC)
LS Type: Router Links
Link State ID: 2.2.2.2
Advertising Router: 2.2.2.2
LS Seq Number: 8000000B
Checksum: 0x791
Length: 60
Number of Links: 3

Link connected to: another Router (point-to-point)
(Link ID) Neighboring Router ID: 1.1.1.1
(Link Data) Router Interface address: 5.0.0.2
Number of TOS metrics: 0
TOS 0 Metrics: 64

Link connected to: a Stub Network
(Link ID) Network/subnet number: 5.0.0.2
(Link Data) Network Mask: 255.255.255.255
Number of TOS metrics: 0
TOS 0 Metrics: 0

```
Link connected to: a Stub Network
(Link ID) Network/subnet number: 6.0.0.0
(Link Data) Network Mask: 255.0.0.0
Number of TOS metrics: 0
TOS 0 Metrics: 10
```

Calculate the Shortest Path

This section calculates the shortest path tree from the perspective of Router 2.2.2.2.

Router 2.2.2.2 looks in its own LSA and sees that Router 1.1.1.1 is a neighbor. Router 2.2.2.2 looks at 1.1.1.1's router LSA to verify that 1.1.1.1 sees 2.2.2.2 as a neighbor. If both routers see each other as neighbors, then they are considered reachable.

Each router also checks its local neighbor table (you can check it using the **show ip ospf neighbor** command) to verify that its interface and the neighbor's interface are on a common IP subnet. If they are, the routers install routes for any stub networks listed in their neighbor's router LSA.

In this example, Router 2.2.2.2 installs a route for 4.0.0.0/8 in its routing table because Router 1.1.1.1 listed 4.0.0.0/8 as a stub network in its own router LSA. Router 1.1.1.1 also listed 5.0.0.1/32 as a stub, which is its interface on the point-to-multipoint network. Therefore, Router 2.2.2.2 installs an OSPF route for 5.0.0.1/32 in its routing table.

```
Router 2.2.2.2#show ip route ospf
O    4.0.0.0/8 [110/74] via 5.0.0.1, 00:09:26, Serial0/1/0
O    5.0.0.1/32 [110/64] via 5.0.0.1, 00:09:26, Serial0/1/0

Router 1.1.1.1#show ip route ospf
O    6.0.0.0/8 [110/74] via 5.0.0.2, 00:00:49, Serial2/1/0
O    5.0.0.2/32 [110/64] via 5.0.0.2, 00:00:49, Serial2/1/0
```

Troubleshoot

There is currently no specific troubleshooting information available for this configuration.

Related Information

- [OSPF Database Explanation Guide](#)
- [OSPF Technology Support](#)
- [IP Routing Technology Support](#)
- [Technical Support & Documentation – Cisco Systems](#)

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2014 – 2015 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

Updated: Aug 10, 2005

Document ID: 47862
