

IOS Software Upgrade Procedure for Access Routers

Document ID: 49044

Contents

Introduction

Prerequisites

- Requirements
- Components Used
- Conventions

Background Information

- Install a TFTP Server
- Establish a Console Session with the Router
- Router Boot Problems

Software Installation and Upgrade Procedures

- Step 1: Select a Cisco IOS Software Image
- Step 2: Download the Cisco IOS Software Image to the TFTP Server
- Step 3: Identify the File System to Copy the Image
- Step 4: Prepare for the Upgrade
- Step 5: Verify that the TFTP Server has IP Connectivity to the Router
- Step 6: Copy IOS Image to the Router
- Step 7: Verify the Cisco IOS Image in the File System
- Step 8: Verify the Configuration Register
- Step 9: Verify the Boot Variable
- Step 10: Save the Configuration and Reload the Router
- Step 11: Verify the Cisco IOS Upgrade

Related Information

Introduction

This document explains how to upgrade a Cisco IOS® software image on Cisco Access Router platforms. The examples provided from the 2600 and 3600 Series Routers also apply to the list of router platforms mentioned. The Cisco IOS Software file names can vary, based on the Cisco IOS Software release, feature set, and platform.

These routers are addressed in this document:

- Cisco 1000 Series Routers
- Cisco 1400 Series Routers
- Cisco 1600-R Series Routers
- Cisco 1700 Series Routers
- Cisco 2600 Series Routers
- Cisco 2800 Series Routers
- Cisco 3600 Series Routers
- Cisco 3700 Series Routers
- Cisco 3800 Series Routers
- Cisco 4000 Series Routers
- Cisco 4700 Series Routers
- Cisco AS5300 Series Routers
- Cisco MC3810 Series Routers

Note: You must be a registered user and you must be logged in to the Cisco.com website in order to use the troubleshooting tools described in this document. In order to register for the Cisco.com website, visit the Cisco.com Registration page.

Prerequisites

Requirements

There are no specific requirements for this document.

Components Used

The information in this document is based on the Cisco IOS Software Release 12.0 or later.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Conventions

Refer to the Cisco Technical Tips Conventions for more information on document conventions.

Background Information

Several protocols are available to copy the Cisco IOS image into the Cisco routers. The most commonly used protocol is TFTP. Other protocols include ftp, http, https, scp, and rcp. If necessary, you can copy an image from one device to another. For more information, refer to the *Copying From One Router to Another* section of the How To Copy a System Image from One Device to Another document.

This section describes how to install a TFTP server, how to establish a console session with the router, and the router boot problems.

Install a TFTP Server

A Trivial File Transfer Protocol (TFTP) server application must be installed on a TCP/IP-ready workstation or PC. After the application is installed, you must perform a minimal level of configuration.

1. Download a TFTP server. Refer to TFTP Server Selection and Use for more information.
2. Configure the TFTP application to operate as a TFTP *server* instead of a TFTP *client*.
3. Specify the outbound file directory. This is the directory in which the Cisco IOS software images are stored. Most TFTP applications provide a setup routine in order to assist in these configuration tasks.

Establish a Console Session with the Router

Even if it is possible to connect to the router through a Telnet session, Cisco recommends that you connect directly to the router through the console port because, if something goes wrong during the upgrade, you might need to be physically present next to the router to power-cycle it. Moreover, the Telnet connection is lost while the router reboots during the upgrade procedure.

A rolled cable, usually a flat black cable, connects the console port of the router to one of the COM ports of the PC.

When the PC is connected to the console port of the router, open HyperTerminal on the PC, and use these settings:

```
Speed 9600 bits per second
8 databits
0 parity bits
1 stop bit
No Flow Control
```

If garbage characters appear in the HyperTerminal session, either you have not set the HyperTerminal properties properly or the config-register of the router is set to a non-standard value for which the console connection speed is higher than 9600 bps. In order to check the value of the config-register, issue the **show version** command. The config-register values appears in the last line of the output. Verify that this value is set to 0x2102 or 0x102.

Note: In order for a configuration register change to take effect, you must reload the router.

When you are sure that the console speed is set to 9600 bps on the router side, you should check the HyperTerminal properties. Refer to *Applying Correct Terminal Emulator Settings for Console Connections* for more information on how to set the HyperTerminal properties.

Router Boot Problems

When you are connected to the console port of the router, you might notice that the router is either in ROMmon or Boot mode. These two modes are used for recovery and diagnostic procedures. If you do not see the usual router prompt, you should use these recommendations in order to proceed with the upgrade procedure installation:

- The router boots in ROMmon mode, and this message appears when you issue the **dir flash:** command:

```
rommon 1 >dir flash:
device does not contain a valid magic number
dir: cannot open device "flash:"
rommon 2 >
```

This error message displays when the Flash is empty or the filesystem is corrupted. Refer to *Xmodem Console Download Procedure Using ROMmon* for more information.

Note: You might also need to consult the Boot Failure procedures specific to your platform. Choose your platform from the Product Support Selector in order to locate these procedures. Look in the Troubleshooting section of each document.

- The router boots in boot mode with these messages on the console:

```
router(boot)>
device does not contain a valid magic number
boot: cannot open "flash:"
boot: cannot determine first file name on device "flash:"
```

These error messages display in the console output when the Flash is empty or when the file system is corrupted. Copy a valid image on the Flash as described in the procedures provided in this document.

Note: You might also need to consult the Boot Failure procedures specific to your platform. Choose your platform from the Product Support Selector in order to locate these procedures. Look in the Troubleshooting section of each document.

Software Installation and Upgrade Procedures

This section covers these topics:

- Step 1: Select a Cisco IOS Software Image
- Step 2: Download the Cisco IOS Software Image to the TFTP Server
- Step 3: Identify the Router File System to Copy the Image
- Step 4: Prepare for the Upgrade
- Step 5: Verify that the TFTP Server has IP Connectivity to the Router
- Step 6: Copy the IOS image to the Router
- Step 7: Verify the Cisco IOS Image in the File System
- Step 8: Verify the Configuration Register
- Step 9: Verify the Boot Variable
- Step 10: Save the Configuration and Reload the Router
- Step 11: Verify the Cisco IOS Upgrade

Step 1: Select a Cisco IOS Software Image

Your first step in the upgrade procedure is to select the correct Cisco IOS software release and feature set. This step is very important, and these factors can affect the decision for which Cisco IOS you should select:

- **Memory requirement:** The router should have sufficient disk or flash memory to store the Cisco IOS. The router should also have sufficient memory (DRAM) to run the Cisco IOS. If the router does not have sufficient memory (DRAM), the router will have boot problems when it boots through the new Cisco IOS.
- **Interfaces and modules support:** You must ensure that the new Cisco IOS supports all the interfaces and modules in the router.
- **Software feature support:** You must ensure that the new Cisco IOS supports the features used with the old Cisco IOS.

Refer to How to Choose a Cisco IOS Software Release for information on how to select the correct software version and feature set.

Step 2: Download the Cisco IOS Software Image to the TFTP Server

Download the Cisco IOS Software image onto your workstation or PC from the Download Software Area (registered customers only) .

Step 3: Identify the File System to Copy the Image

The file system type "flash" or "disk" is used to store the Cisco IOS image. The **show file system** command output shows the list of file systems available on the router. The common "disk/flash" file systems supported in Cisco routers have prefixes such as flash:, slot0:, slot1:, disk0: and disk1:. It should have sufficient space to store the Cisco IOS image. You can use the **show file system** or the **dir file_system** command in order to find the free space.

```
2600#show file system
```

```
File Systems:
```

```
Size (b)      Free (b)      Type  Flags  Prefixes
```

```

-          -      opaque      rw      archive:
-          -      opaque      rw      system:
29688      20571      nvram      rw      nvram:
-          -      opaque      rw      null:
-          -      network     rw      tftp:
-          -      opaque      ro      xmodem:
-          -      opaque      ro      ymodem:
* 49807356 20152636      flash     rw      flash:
-          -      opaque      wo      syslog:

```

2800#show file system

File Systems:

```

      Size (b)      Free (b)      Type      Flags      Prefixes
-          -      opaque      rw      archive:
-          -      opaque      rw      system:
-          -      opaque      rw      null:
-          -      network     rw      tftp:
-          -      opaque      ro      xmodem:
-          -      opaque      ro      ymodem:
* 64016384 15470592      disk      rw      flash:#
      245752      239218      nvram     rw      nvram:
-          -      opaque      wo      syslog:

```

3600#show file system

File Systems:

```

      Size (b)      Free (b)      Type      Flags      Prefixes
-          -      opaque      rw      archive:
-          -      opaque      rw      system:
129016     126071      nvram     rw      nvram:
-          -      opaque      rw      null:
-          -      network     rw      tftp:
* 33030140 20511708      flash     rw      flash:
16777212 16777212      flash     rw      slot0:
16515068 8038516      flash     rw      slot1:
-          -      opaque      rw      xmodem:
-          -      opaque      rw      ymodem:

```

3700#show file system

File Systems:

```

      Size (b)      Free (b)      Type      Flags      Prefixes
-          -      opaque      rw      archive:
-          -      opaque      rw      system:
57336     51389      nvram     rw      nvram:
-          -      opaque      rw      null:
-          -      network     rw      tftp:
-          -      opaque      ro      xmodem:
-          -      opaque      ro      ymodem:
* 63881216 22765568      disk      rw      flash:#
31932416 31932416      disk      rw      slot0:#
-          -      opaque      wo      syslog:

```

Step 4: Prepare for the Upgrade

You should consider these items before you upgrade the Cisco IOS:

- If the router has sufficient memory (flash, slot or disk), you can store both the old Cisco IOS and the new Cisco IOS. You can boot the router in the ROMMON mode and boot the old Cisco IOS in case

The exclamation point "!" indicates that the copy process is in progress. Each exclamation point indicates that ten packets have transferred successfully. A checksum verification of the image occurs after the image is written to Flash memory.

Example 3: Copy the IOS image to flash: from another router

You can configure a router as TFTP server. If you choose the flash: file systems, use the **copy tftp: flash:** command in order to copy the image from TFTP server to flash.

```
Router-tftp(config)#tftp-server flash:c7200-a3js-mz.122-15.T16.bin

!--- Router-tftp is configured as the TFTP server.

7200#copy tftp: flash:
Address or name of remote host []? 172.22.1.84
Source filename []? c7200-a3js-mz.122-15.T16.bin
Destination filename [c7200-a3js-mz.122-15.T16.bin]?
Accessing tftp://172.22.1.84/c7200-a3js-mz.122-15.T16.bin...
Erase flash: before copying? [confirm]n
Loading c7200-a3js-mz.122-15.T16.bin from 172.22.1.84 (via GigabitEthernet0/1):
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
[OK - 19187152 bytes]

Verifying checksum... OK (0x15C1)
19187152 bytes copied in 482.920 secs (39732 bytes/sec)
```

Step 7: Verify the Cisco IOS Image in the File System

Verify the image in the file system.

```
2600#dir flash:

Directory of flash:/

   1  -rw-   29654656                   <no date>  c2600-adventerprisek9-mz.1
24-12.bin

49807356 bytes total (20152636 bytes free)

2600#verify flash:c2600-adventerprisek9-mz.124-12.bin

Verifying file integrity of flash:c2600-adventerprisek9-mz.124-12.bin.....
.....
.....Done!
Embedded Hash   MD5 : 1988B2EC9AFAF1EBD0631D4F6807C295
Computed Hash   MD5 : 1988B2EC9AFAF1EBD0631D4F6807C295
CCO Hash        MD5 : 141A677E6E172145245CCAC94674095A

Signature Verified
Verified flash:c2600-adventerprisek9-mz.124-12.bin
```

Refer to System Message Guide for information about different %SIGNATURE error messages and the necessary action to be taken.

Step 8: Verify the Configuration Register

config-register value—Use the **show version** command in order to check this value. The value is displayed in the last line of the **show version** output. It should be set to 0x2102.

```
2600#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
2600(config)#config-register 0x2102
2600(config)#^Z
```

Step 9: Verify the Boot Variable

IOS image in the flash—If the first file in the Flash is not the Cisco IOS Software image, but a configuration file, or something else, then you need to configure a **boot system** statement in order to boot the specified image. Otherwise, the router tries to boot with the configuration file or the first file in the Flash, which does not work. If there is only one file in the Flash and it is the Cisco IOS Software image, this step is not necessary.

```
2600#show run | include boot
boot system flash:c2600-adventerprisek9-mz.123-21.bin

2600#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
2600(config)#no boot system
2600(config)#boot system flash:c2600-adventerprisek9-mz.124-12.bin
2600(config)#^Z
```

IOS image in the slot1—The boot variable that points to the old Cisco IOS needs to be removed first, and then the router needs to be configured to boot through the new Cisco IOS.

```
3600# show run | include boot
boot system slot1:c3640-i-mz.120-22.bin

3600#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
3600(config)#no boot system
3600(config)#boot system slot1:c3640-i-mz.122-7b.bin
3600(config)#^Z
```

Step 10: Save the Configuration and Reload the Router

Save the configuration, and reload the Router.

```
2600# write memory
2610# reload
Proceed with reload? [confirm]
Jan 24 20:17:07.787: %SYS-5-RELOAD: Reload requested by console. Reload Reason:
Reload Command.
```

Step 11: Verify the Cisco IOS Upgrade

Verify that the router runs with the proper image.

After the reload is complete, the router should run the desired Cisco IOS Software image. Use the **show version** command in order to verify the Cisco IOS software.

```
2600#show version
00:22:25: %SYS-5-CONFIG_I: Configured from console by console
```

```
Cisco IOS Software, C2600 Software (C2600-ADVENTERPRISEK9-M), Version 12.4(12),  
RELEASE SOFTWARE (fc1)  
Technical Support: http://www.cisco.com/techsupport  
Copyright (c) 1986-2006 by Cisco Systems, Inc.  
Compiled Fri 17-Nov-06 11:18 by prod_rel_team  
  
ROM: System Bootstrap, Version 12.2(8r) [cmong 8r], RELEASE SOFTWARE (fc1)  
  
2610 uptime is 22 minutes  
System returned to ROM by reload  
System image file is "flash:c2600-adventerprisek9-mz.124-12.bin"
```

Here is the **show version** output of 3600 router that has Cisco IOS in the slot1:

```
3600#show version  
Cisco Internetwork Operating System Software  
IOS (tm) 3600 Software (C3640-I-M), Version 12.2(7b), RELEASE SOFTWARE (fc1)  
Copyright (c) 1986-2002 by cisco Systems, Inc.  
Compiled Mon 04-Mar-02 20:23 by pwade  
Image text-base: 0x600089A8, data-base: 0x60A6A000  
  
ROM: System Bootstrap, Version 11.1(19)AA, EARLY DEPLOYMENT RELEASE SOFTWARE (f)  
  
Router uptime is 2 minutes  
System returned to ROM by reload  
System image file is "slot1:c3640-i-mz.122-7b.bin"  
  
cisco 3640 (R4700) processor (revision 0x00) with 59392K/6144K bytes of memory.  
  
Processor board ID 10524422  
R4700 CPU at 100Mhz, Implementation 33, Rev 1.0  
Bridging software.  
X.25 software, Version 3.0.0.  
4 Ethernet/IEEE 802.3 interface(s)  
DRAM configuration is 64 bits wide with parity disabled.  
125K bytes of non-volatile configuration memory.  
4096K bytes of processor board System flash (Read/Write)  
20480K bytes of processor board PCMCIA Slot0 flash (Read/Write)  
20480K bytes of processor board PCMCIA Slot1 flash (Read/Write)  
  
Configuration register is 0x2102
```

Related Information

- [Download Software Area \(registered customers only\)](#)
- [Routers Product Support](#)
- [Software Advisor \(registered customers only\)](#)
- [How to Choose a Cisco IOS Software Release](#)
- [PCMCIA Flash Compatibility Matrix and Filesystem Information](#)
- [Field Notice: Cisco IOS TFTP Client Cannot Transfer Files Larger than 16MB in Size](#)
- [Technical Support & Documentation - Cisco Systems](#)

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2014 - 2015 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

Updated: Jul 31, 2015

Document ID: 49044
