



Document ID: 116942

Updated: Nov 24, 2015

Contributed by Scott Hills and Brad Magnani, Cisco TAC Engineers.



[Download PDF](#)



[Print](#)

[\[+\] Feedback](#)

Related Products

- [Cisco Unity Connection](#)

Contents

[Introduction](#)

[Problem](#)

[Enterprise Replication](#)

[Unity Connection Replication](#)

[Solution](#)

[Related Information](#)

[Related Cisco Support Community Discussions](#)

Introduction

This document describes steps to verify and attempt to address the issue when replication becomes out of sync or breaks entirely.

Problem

It is important to know that there are two types of replication that occur within Unity Connection (UC):

- Enterprise Replication (ER) - platform Cisco CallManager (CCM) related
- Unity Connection Replication

Enterprise Replication

It is important that ER is *always* Real Time Monitoring Tool (RTMT) state of (2)'s on both the Publisher and the Subscriber.

- In order to confirm this, enter the **utils dbreplication runtimestate** command.
- Another helpful command that can be used is **utils dbreplication status**.

Unity Connection Replication

Without the proper ER running, Unity Connection Replication does not work correctly. Commands used to troubleshoot UC replication are:

- **utils cuc cluster overwrittenb**
- **utils cuc cluster renegotiate**

Solution

If ER is down (RTMT does not = 2), complete these steps:

1. On the Subscriber, enter the **utils dbreplication stop** command. Wait for it to complete before you start the next step.
2. On the Publisher, enter the **utils dbreplication stop** command. Wait for it to complete before you start the next step.
3. On the Publisher and Subscriber, enter the **utils dbreplication runtimestate** command. Ensure that both servers are RPC reachable column = YES).
4. On the Publisher, enter the **utils dbreplication dropadmindb** command.
5. On the Subscriber, enter the **utils dbreplication dropadmindb** command. If you run Release 9.x, skip to step 8.
6. On the Publisher, enter the **utils dbreplication clusterreset** command. Wait for it to complete before you start the next step.
7. Restart the Subscriber. Wait for the Subscriber to come back up and services all start before you start the next step.
8. On the Publisher, enter the **utils dbreplication reset all** command.
9. On Publisher and Subscriber, periodically enter the **utils dbreplication runtimestate** command in order to monitor the RTMT state they each have for one another. They should progress and both ultimately end up at (2) if replication sets up properly. This can take some time.
10. If RTMT states do not go from 0's to 2's after you wait a good amount of time, collect this information from BOTH the Publisher and the Subscriber:**utils dbreplication runtimestatefile get activelog cm/trace/dbl/*.logfile get activelog cm/trace/dbl/sdi/dbmon*.txtfile get activelog cm/log/informix/dbl_repl*.logfile get activelog cm/log/informix/ccm*.log**
11. Open a case with the Technical Assistance Center (TAC) and provide the information collected in step 10.

Related Information

- [Command Line Interface Reference Guide for Cisco Unified Communications Solutions Release 8.6\(1\)](#)
- [Technical Support & Documentation - Cisco Systems](#)

Was this document helpful? [Yes](#) [No](#)

Thank you for your feedback.

[Open a Support Case](#) (Requires a [Cisco Service Contract](#).)

Related Cisco Support Community Discussions

The [Cisco Support Community](#) is a forum for you to ask and answer questions, share suggestions, and collaborate with your peers.

Refer to [Cisco Technical Tips Conventions](#) for information on conventions used in this document.