

# E&M Cable Pinouts Connecting Cisco 1750/2600/3600 E&M VIC to Lucent PBX G3R E&M Trunk

Document ID: 8635

## Contents

### Introduction

#### Prerequisites

- Requirements

- Components Used

- Conventions

#### Pinout

#### Related Information

## Introduction

This document describes the E&M Cable Pinouts connecting a Cisco 1750/2600/3600 E&M voice interface card (VIC) to a Lucent PBX G3R E&M Trunk.

## Prerequisites

## Requirements

There are no specific requirements for this document.

## Components Used

This document is not restricted to specific software and hardware versions.

## Conventions

For more information on document conventions, see the Cisco Technical Tips Conventions.

## Pinout

**Note:** Lucent G3R PBX ty1–stan and ty5 interoperate with Cisco 1750/2600/3600 E&M VIC.

Type 1 & 5; 4-wires; router to PBX -----Lucent-----

Router	Pins	PBX
	1 --	
M	2 -- 6	M
R	3 -- 4	TA
R1	4 -- 1	RA
T1	5 -- 2	RB
T	6 -- 5	TB
E	7 -- 3	E
	8 --	

## Related Information

- [Voice Technology Support](#)
  - [Voice and Unified Communications Product Support](#)
  - [Troubleshooting Cisco IP Telephony](#) 
  - [Technical Support – Cisco Systems](#)
- 

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2014 – 2015 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

---

Updated: Feb 02, 2006

Document ID: 8635

---