



Overlay:Distributed Anycast Gateway Routed

This feature enables distributed anycast gateway routing in overlay networks, allowing efficient traffic forwarding and gateway redundancy.

- [Distributed Anycast Gateway: routed overlay network overview, on page 1](#)
- [Restrictions for DAG routed overlay networks, on page 2](#)
- [Understanding DAG routed overlay networks, on page 2](#)
- [Configure DAG routed overlay networks, on page 4](#)
- [Verify the DAG routed overlay configuration, on page 13](#)
- [Reference configuration for DAG routed overlay networks, on page 16](#)

Distributed Anycast Gateway: routed overlay network overview


In modern enterprise campus environments, application traffic typically flows between wired and wireless users, and resources hosted either on-premises or across cloud environments. To manage this efficiently, network administrators implement a structured IP addressing plan with VLANs and subnets organized per distribution block. This approach enables segmentation through a routed overlay VXLAN fabric network, which provides scalable, flexible, and secure network segmentation.

In certain cases, the VLAN or subnet networks may require stretching beyond a single IP gateway boundary to support latency-sensitive or legacy enterprise applications. The Distributed Anycast Gateway (DAG) technology enables this by allowing secure and segmented communication between IP endpoints over a dynamic VXLAN tunnel.

With a Layer 2 flood-free network, the DAG-routed overlay network enables the stretching of IP subnets across switches implemented in EVPN multihoming fabric mode across targeted leaf switches. This approach supports scalable and secure network segmentation tailored to enterprise application requirements. Switches support the co-existence of routed and DAG routed overlay networks.

The following illustration shows a deployment scenario for an EVPN multihoming network with the co-existence of routed and DAG-routed overlay networks. The illustration also shows the stretching of a specific IP subnet, VLAN-111 between two targeted switches, one in network distribution Block 1 and the other in Block 2.

Figure 1: EVPN multihoming with DAG-routed overlay fabric network



Restrictions for DAG routed overlay networks

The following restrictions apply to the DAG Routed Overlay feature.

- Non-IP endpoint communication beyond local EVPN multihoming network devices is not supported.
- Silent-host endpoint communication beyond local EVPN multihoming network devices is not supported.


Understanding DAG routed overlay networks

Enterprise networks require flexibility to support unique per-VLAN overlay functions that are tailored to business requirements. Routed overlay is a proven and recommended approach for large-scale overlay networks, which can implement DAG-routed overlay to selectively stretch IP subnets without extending the Layer 2 flood boundary. Network administrators can implement the DAG-routed overlay to stretch an IP subnet across targeted leaf switches without extending the Layer 2 flood boundary.

Switches support the multiple flexible co-existence of routed and distributed Anycast gateway routed overlay networking options within the same macro-segmented IP VRF, and the micro-segmented VXLAN-GPO enabled environment.

The following figure displays the characteristics of an EVPN multihoming network with a DAG-routed overlay fabric.

Figure 2: Key network characteristics of a DAG-routed overlay fabric



Hierarchical BGP control plane

The recommended deployment consideration to support controlled route management between EVPN multihoming peers and spine switches in large-scale campus networks is the two-tier hierarchical BGP control plane. Each BGP peering layer manages domain-specific EVPN routes to enable downstream non-blocking and all-active Layer 2 multipath networks, and manages the advertising of fabric network prefixes to enable secure global network access connectivity in core networks.

EVPN multihoming

Layer 2 networks with EVPN multihoming functions independent of the fabric core EVPN fabric network. A pair of switches in each distribution layer builds and manages EVPN multihoming in each redundancy group.

The unified Layer 2 Ethernet Segment (ES) EtherChannel connection to downstream network device can carry VLANs that are mapped to routed, selective-stretched subnets with DAG-routed overlay and advertised in the fabric core or can continue to be traditional underlay IP networks.

Layer 2 broadcast network boundary

DAG routed overlay networks provide unified Layer 2 or Layer 3 network boundary as the routed overlay and the traditional underlay campus network. The Layer 2 bridge domain and the blast-radius remain contained between Layer 2 access and EVPN multihoming-enabled distribution layer systems.

A pair of switches in the distribution layer network dynamically builds the Layer 2 VXLAN tunnel using ingress replication mode to extend Broadcast, Unknown Unicast and Multicast (BUM) traffic. With built-in loop-detection and prevention techniques, EVPN multihoming-enabled networks support a secure and scalable Layer 2 network over traditional STP based networks.

IPv4 ARP and IPv6 proxy

Switches support IPv4 ARP and IPv6 Neighbor Discovery (ND) and Duplicate Address Detection (DAD) proxy functions on a per VLAN or subnet basis.

The intended, stretched IP subnet interface is configured with local proxy functions on anycast gateway switches. The incoming IPv4 ARP request and IPv6 ND/DAD messages are intercepted, processed, and responded to by the anycast gateway switch with the local anycast MAC address (00:00:5e:00:01:01). As a result, the IP subnet with IPv4 or IPv6 endpoints can be selectively stretched between EVPN multihoming network devices without extending the Layer 2 flood boundary that can impact scale, performance, and security in large scale environments.

Structured IP subnet with proxy and gateway redundancy

The DAG routed overlay network enables stretching an IP subnet between targeted EVPN multihoming network devices supporting scalable and secure overlay network. The selective group of switches in EVPN multihoming mode shares common IPv4/IPv6 subnet with IP proxy function enable to support intra-subnet host communication based on fabric host-routing table while providing load-sharing and gateway redundancy with anycast gateway as routed overlay.

Spine route policy

The IPv4 or IPv6 subnet stretch across multiple IP gateway systems demand a non-condensed host-level prefix announcement in fabric core to support end-to-end seamless data communication. Switches that stretch the IPv4 or IPv6 subnets require the advertisement of the host-route to the fabric.

The iBGP or eBGP prefix advertisement to spine switches in fabric core limits advertising the IPv4 or IPv6 RT-2-MAC-IP host prefixes along with RT-5 network prefixes. The switches in EVPN multihoming mode retain unfiltered routing with iBGP peering session with the remote ES switch for non-blocking the Layer 2 multipath EtherChannel.



Note EVPN multihoming-enabled networks support additional overlay network types to stretch IP subnets or Layer 2 flood-domain beyond a single distribution block using Distributed Anycast Gateway (DAG) bridged technology. For better scale, performance, and resiliency, we recommend the routed overlay network.

Configure DAG routed overlay networks

This section provides step-by-step configuration guidelines to implement DAG routed overlay networks.

Configure IP VRFs

This task shows how to configure a logically segmented virtual network with an IP VRF to exchange IPv4 or IPv6 network prefixes across all VTEPs in the fabric core network.

Procedure

	Command or Action	Purpose
Step 1	enable Example: Device> enable	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	configure terminal Example: Device# configure terminal	Enters global configuration mode.
Step 3	vrf definition vrf-name Example: Device(config)# vrf definition green	Configures a new virtual routing and forwarding (VRF) instance and enters VRF configuration mode.
Step 4	rd vpn-route-distinguisher Example: Device(config-vrf)# rd 10.200.255.101:101	Configures a route distinguisher with a distinct value across all fabric devices.
Step 5	address-family ipv4 [multicast unicast] Example: Device(config-vrf-af)# address-family ipv4 unicast	Enters IPv4 unicast address-family configuration mode.
Step 6	route-target [both export import] route-target-ext-community Example: Device(config- vrf-af)# route-target 65101:101	Configures an overlay IPv4 import and export routing policy that matches the extended community value. • The default is both and will auto-generate both import and export command line with the configured community value.
Step 7	route-target [both export import] route-target-ext-community stitching Example: Device(config- vrf-af)# route-target 65101:101 stitching	Configures an IPv4 routing import and export overlay policy that matches the extended community value and enables extended NLRI types for BGP EVPN VXLAN-enabled networks. • The default is both
Step 8	address-family ipv6 [multicast unicast] Example: Device(config- vrf-af)# address-family ipv6 unicast	Enters IPv6 unicast address-family configuration mode.

	Command or Action	Purpose
Step 9	route-target [both export import] <i>route-target-ext-community</i> Example: Device(config- vrf-af) # route-target 65101:101	Configures an IPv6 routing import and export overlay policy that matches the extended community value. The default is both and will auto-generate both import and export command line with the configured community value.
Step 10	route-target [both export import] <i>route-target-ext-community stitching</i> Example: Device(config- vrf-af) # route-target 65101:101 stitching	Configures an IPv6 routing import and export overlay policy that matches the extended community value and enables extended NLRI types for BGP EVPN VXLAN-enabled networks. The default is both.
Step 11	end Example: Device(config- vrf-af) # end	Exits IPv6 unicast address-family configuration mode and returns to privileged EXEC mode.

Configure core VLAN and SVI interfaces

This task shows how to configure core VLAN and SVI interfaces for each of the IP VRFs used for VXLAN encapsulation and decapsulation functions between the downstream non-VXLAN network and remote VXLAN-enabled VTEPs. The task also shows how to configure the NVE interface and bind the L3VNI ID to a logical interface.



Note Skip this task if you have already configured core VLAN and SVI interfaces as part of the routed overlay network configuration.

Procedure

	Command or Action	Purpose
Step 1	enable Example: Device> enable	Enables privileged EXEC mode. Enter your password if prompted.
Step 2	configure terminal Example: Device# configure terminal	Enters global configuration mode.
Step 3	vlan id Example:	Configures a dedicated VLAN ID for IP VRF core routing. This VLAN must not be used for

	Command or Action	Purpose
	Device(config)# vlan 101	any other purpose, and it is recommended to be pruned from Layer 2 trunk ports.
Step 4	vlan configuration id Example: Device(config)# vlan configuration 101	Configures a core VLAN to assign the Layer 3 VNI ID and enters VLAN configuration mode.
Step 5	member vni l3vni-id Example: Device(config-vlan)# member vni 11101	Configures a unique Layer 3 VNI ID for a specific IP VRF. For example, VRF green has the dedicated VLAN 101 and Layer 3 VNI, and these IDs must not be shared with other IP VRFs on the same system. All other VTEPs are recommended to have a Layer 3 VNI ID for the same IP VRF.
Step 6	exit Example: Device(config-vlan)# exit	Exits VLAN configuration mode and returns to global configuration mode
Step 7	interface vlan id Example: Device(config)# interface vlan 101	Configures a core VLAN SVI interface and assigns it to an IP VRF. The core VLAN SVI MAC address supports routed MAC (RMAC) for Layer 3 overlays.
Step 8	vrf forwarding vrf-name Example: Device(config-if)# vrf forwarding green	Maps the IP VRF to a core VLAN SVI interface.
Step 9	ip unnumbered id Example: Device(config-if)# ip unnumbered Loopback0	Configures an unnumbered IPv4 address from an underlay logical interface, for example, Loopback0.
Step 10	no autostate Example: Device(config-if)# no autostate	Disables autostate on the interface. In EVPN deployments, a VLAN used for a core-facing SVI, should not be allowed in any trunks. For a core-facing SVI to function correctly, the no autostate command must be configured for the SVI.
Step 11	exit Example: Device(config-if)# exit	Exits interface configuration mode and returns to global configuration mode.

	Command or Action	Purpose
Step 12	interface nve id Example: Device(config)# interface nve	Configures a virtual NVE interface to bind one or more L2VNIs and enables system-wide VXLAN forwarding function from the L3VNIs. Enters interface configuration mode.
Step 13	source-interface id Example: Device(config-if)# source-interface Loopback0	Configures a Loopback interface as the source to enable data communication over a VXLAN tunnel.
Step 14	host-reachability protocol bgp Example: Device(config-if)# host-reachability protocol bgp	Configures BGP as the host-reachability control plane protocol on this interface.
Step 15	member vni l3vni-id vrf vrf-name Example: Device(config-if)# member vni 11101 vrf green	Binds the L3VNI to the IP VRF under the NVE interface.
Step 16	end Example: Device(config-if)# end	Exits interface configuration mode and returns to privileged EXEC mode.

Configure DAG routed MAC VRFs

This task shows how to configure a MAC VRF and route-target policy to selectively exchange prefixes between a pair of EVPN multihoming-enabled switches in a single cluster.

Procedure

	Command or Action	Purpose
Step 1	enable Example: Device> enable	Enables privileged EXEC mode. Enter your password if prompted.
Step 2	configure terminal Example: Device# configure terminal	Enters global configuration mode.
Step 3	l2vpn evpn instance id vlan-based Example:	Configures a L2VPN EVPN virtual instance with a unique ID. Typically, the ID value is the

	Command or Action	Purpose
	Device(config)# l2vpn evpn instance 111 vlan-based	same as the VLAN ID, for example, data VLAN ID 111. • Enters EVPN instance configuration mode.
Step 4	encapsulation vxlan Example: Device(config-evpn-evi)# encapsulation vxlan	Enables VXLAN encapsulation to bridge inter-ES data between two systems.
Step 5	route-target {export import both} <i>route-target-ext-community</i> Example: Device(config-evpn-evi)# route-target both 1.1.1.1:111	Configures a MAC or IP routing import and export policy that matches the extended community value. • The recommended format for EVPN multihoming cluster VLAN ID is Cluster-1 ID with 1.1.1.1 and DAG-routed VLAN ID 111 can result in the MAC VRF route-target 1.1.1.1:111. The default is both and it auto-generates the import and export command-line with the configured community value.
Step 6	no auto-route-target Example: Device(config-evpn-evi)# no auto-route-target	Disables auto route-target with the manual route-target configured in Step-5 for the DAG-routed overlay MAC VRF. • The default is auto-generated route-target in ASN:L2VPN instance ID format.
Step 7	end Example: Device end	Exits EVPN instance configuration mode and returns to privileged EXEC mode.

Configure IPv4 ARP and IPv6 ND/DAD proxy

Configures IPv4 Address Resolution Protocol (ARP) and IPv6 Neighbor Discovery (ND) or Duplicate Address Detection (DAD) proxy on switches to provide local anycast interface MAC response after receiving requests or queries from local endpoints connected to the downstream Layer 2 network.

This configuration is required only on access-facing VLAN or SVI interfaces that are implemented in distributed anycast gateway routed overlay mode

Procedure

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.

	Command or Action	Purpose
	Example: Device> enable	• Enter your password if prompted
Step 2	configure terminal Example: Device# configure terminal	Enters global configuration mode.
Step 3	interface vlan id Example: Device (config)# interface vlan 111	Configures a Layer 3 SVI interface ID and enters interface configuration mode.
Step 4	ip address address mask Example: Device (config-if)# ip address 10.111.1.254 255.255.255.0	Assigns IPv4 gateway address and mask for selected VLANs. • Anycast gateway address is auto enabled with a common address between ES systems.
Step 5	ip local-proxy-arp Example: Device (config-if)# ip local-proxy-arp	Configures a gateway to send proxy responses with the local interface MAC address when receiving IPv4 ARP requests from local hosts.
Step 6	ipv6 address address mask Example: Device (config-if)# ipv6 address 2001:10:111:1::f/64	Assigns IPv6 gateway address and prefix for selected VLANs. • Anycast gateway address is auto-enabled with a common address between ES systems.
Step 7	exit Example: Device (config-if)# exit	Exits interfaced configuration mode and returns to privileged EXEC mode.
Step 8	vlan configuration id Example: Device (config)# vlan configuration 111	Enters VLAN configuration mode
Step 9	ipv6 nd routing proxy Example: Device (config-vlan)# ipv6 nd routing proxy	Configures a gateway switch to send proxy responses with the local interface MAC address when receiving IPv6 ND requests from local hosts.
Step 10	ipv6 nd dad-proxy Example: Device (config-vlan)# ipv6 nd dad-proxy	Configures the gateway switch to send DAD proxy response to local hosts with the local interface MAC address when receiving IPv6 ND DAD messages for the IPv6 address owned by another host.

	Command or Action	Purpose
Step 11	end Example: Device(config-vlan) # end	Exits VLAN configuration mode and returns to privileged EXEC mode.

Configure spine policies for DAG routed overlay networks

This task provides step-by-step instructions to configure a pair of ES switches with an outbound spine EVPN route policy. The route policy enables controlled EVPN route advertisement by the pair of ES switches, independent of iBGP or eBGP spine-peering session type.

The spine route-map policy to permit RT-5 prefix for routed overlay can be expanded with a new sequence to limit the switches advertising the RT-2 with combined MAC and IP (RT-2-MAC-IP) prefix for network-wide host route with IPv4 or IPv6 address propagation.

The iBGP peering with EVPN multihoming system unfiltered EVPN route exchange to build and maintain non-blocking Layer 2 multipath network.

Procedure

	Command or Action	Purpose
Step 1	enable Example: Device> enable	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	configure terminal Example: Device# configure terminal	Enters global configuration mode.
Step 3	route-map name [permit deny] sequence-number Example: Device(config) # route-map SPINE-ROUTE-POLICY-OUT permit 20	Creates a route-map rule with permit or deny match criteria and enters route-map configuration mode. • The optional <i>sequence-number</i> argument indicates the order of processing of the route-map rule.
Step 4	description description Example: Device(config-route-map) # description DAG ROUTED OVERLAY - VL111	(Optional) Adds a description for the route-map sequence.
Step 5	match evpn route-type [1-8 2-mac-ip 2-mac-only] Example: Device(config-route-map) # match evpn route-type 2-mac-ip	Configures an EVPN route-policy sequence to permit advertising the local IPv4 or IPv6 hosts prefixes (RT-2-MAC-IP) mapped to any IP VRF.

	Command or Action	Purpose
Step 6	exit Example: Device (config-route-map) # exit	Exits route-map configuration mode and returns to global configuration mode.
Step 7	router bgp <i>autonomous-system-number</i> Example: Device (config) # router bgp 65101	Configures BGP autonomous system numbers using 2-bytes or 4-bytes in asplain and asdot formats and enters router configuration mode.
Step 8	address-family <i>l2vpn evpn</i> Example: Device (config-router) # address-family l2vpn evpn	Enters BGP L2VPN address-family configuration mode.
Step 9	neighbor <i>spine-loopback-address</i> route-map <i>name out</i> Example: Device (config-router-af) # neighbor 10.200.255.3 route-map SPINE-ROUTE-POLICY-OUT out	Applies outbound route-map policy to each spine peer to limit the advertising of the RT-5 prefix.
Step 10	end Example: Device (config-router-af) # end	Exits router configuration mode and returns to privileged EXEC mode.

Configure IP VRF address family routing under BGP

This task shows how to advertise network prefixes in IPv4 and IPv6 address-family configuration.

Procedure

	Command or Action	Purpose
Step 1	enable Example: Device> enable	Enables privileged EXEC mode. • Enter your password if prompted.
Step 2	configure terminal Example: Device# configure terminal	Enters global configuration mode.
Step 3	router bgp <i>autonomous-system-number</i> Example: Device (config) # router bgp 65101	Configures BGP autonomous system numbers using 2-bytes or 4-bytes in asplain and asdot formats and enters router configuration mode.

	Command or Action	Purpose
Step 4	address-family ipv4 vrf vrf-name Example: Device(config-router) # address-family ipv4 vrf green	Enables IPv4 address-family for a VRF instance to enable IPv4 network prefix routing in overlay.
Step 5	advertise l2vpn evpn Example: Device(config-route-af) # advertise l2vpn evpn	Enables advertising the IPv4 network prefix routing between IPv4 VRF instances and EVPN fabric core networks.
Step 6	redistribute connected [metric route-map] name Example: Device(config-route-af) # redistribute connected	Configures IPv4 address-family to advertise all local connected IPv4 network prefixes in EVPN fabric network. The network prefix can be advertised with network command-line as an alternative.
Step 7	exit Example: Device(config-route-af) # exit	Exits IPv4 address-family configuration mode and returns to router configuration mode
Step 8	address-family ipv6 vrf vrf-name Example: Device(config-router) # address-family ipv6 vrf green	Enables IPv6 address-family for a VRF instance to enable IPv6 network prefix routing in overlay.
Step 9	advertise l2vpn evpn Example: Device(config-route-af) # advertise l2vpn evpn	Enables IPv6 network prefix routing between IPv6 VRF instances and EVPN fabric core networks.
Step 10	redistribute connected [metric route-map] name Example: Device(config-route-af) # redistribute connected	Configures an IPv6 address-family to advertise all local connected IPv6 network prefixes in EVPN fabric network. The network prefix can be advertised with network command-line as an alternative.
Step 11	end Example: Device(config-route-af) # end	Exits IPv6 address-family configuration mode and returns to privileged EXEC mode.

Verify the DAG routed overlay configuration

This section provides examples to verify the DAG routed overlay network configuration and states of VTEPs.

The command output may be truncated to focus on critical information for a Day-2 operation and troubleshooting.

IP VRF networks: Verifies the locally configured IP VRF and the associated physical or logical interface bindings to a virtual network on VTEPs including leaf and border devices. The interface binding includes the network edge VLANs connecting to endpoints, and network devices, along with a single core VLAN (VLAN 101) of an IP VRF.

ES-1# **show vrf green**

Name	Default RD	Protocols	Interfaces
green	10.200.255.101:101	ipv4 V111	V1111 V1101

BORDER-1# **show vrf green**

Name	Default RD	Protocols	Interfaces
green	10.200.255.1:101	ipv4 V1101	V11101

BGP L2VPN EVPN neighbors: Verifies that the two-tier hierarchical iBGP sessions between switches in EVPN multihoming mode and iBGP peering to a pair of spine systems are in operational state.

The following command output shows iBGP peering with a pair of spine switches, 10.100.255.3 and 10.100.255.4 and direct iBGP peering between ES-1, local 10.100.255.101 and ES-2, 10.100.255.102 switches in EVPN multihoming mode is operational.

ES-1# **show bgp l2vpn evpn all summary**

BGP router identifier 10.100.255.101, local AS number 65101
<snip>

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
10.100.255.3	4	65101	18	20	104	0	0	00:04:35	2
10.100.255.4	4	65101	23	25	106	0	0	00:05:19	2
10.100.255.102	4	65101	51	65	104	0	0	00:04:26	28

Spine policy: Verifies the VTEP in leaf or border roles implemented in EVPN multihoming mode is configured with a route-map and an outbound policy is applied to each spine, 10.200.255.3.

The spine policy configuration on border switches is optional and not required if the switches are not implemented in EVPN multihoming mode to connect to external network devices, such as firewalls.

ES-1# **show bgp l2vpn evpn neighbor 10.200.255.3 policy**

Neighbor: 10.200.255.3, Address-Family: L2VPN E-VPN
Locally configured policies:
 send-community extended
Inherited policies:
 route-map EVPN-SPINE-ROUTE-POLICY-OUT out

L2VPN advertised routes: Verifies the VTEP in leaf or border roles implemented in EVPN multihoming mode is advertising the EVPN prefixes to the spine, 10.200.255.3, based on the applied route-map policy.

The following command output from leaf and border switches confirms the advertising of RT-2-MAC-IP EVPN prefixes, and that no additional EVPN route-types are advertised to the spine switches.

```
ES-1# show bgp l2vpn evpn neighbor 10.200.255.3 advertised-route
```

```
BGP table version is 7179, local router ID is 10.200.255.101
<snip>
      Network          Next Hop          Metric  LocPrf  Weight  Path
Route Distinguisher: 10.200.255.101:111
*>   [2] [10.200.255.101:111] [0] [48] [00CCFC4ED1C3] [32] [10.111.1.1]/24
      0.0.0.0                      32768      ?
Route Distinguisher: 10.200.255.101:111
*>   [2] [10.200.255.101:111] [0] [48] [00CCFC4ED1C4] [32] [10.111.1.2]/24
      0.0.0.0                      32768      ?
```

```
Border-1# show bgp l2vpn evpn neighbors 10.200.255.3 advertised-routes
```

```
BGP table version is 2895, local router ID is 10.200.255.1
<snip>
      Network          Next Hop          Metric  LocPrf  Weight  Path
Route Distinguisher: 10.100.255.1:101 (default for vrf green)
*>   [5] [10.100.255.1:101] [0] [0] [0.0.0.0]/17
      21.1.1.1                      0          0      65001      ?
*>   [5] [10.100.255.1:101] [0] [16] [111.1.0.0]/17
      21.1.1.1                      0          0      65001      ?
```

MAC-VRF manual route-target: Verifies that the stretched IP-subnet VLAN is limited to import and export of the MAC or IP route matching the local cluster EVPN multihoming peer switch. With auto-route-target disabled, the import and export route-target only lists the manual configuration settings.

The following command output confirms that the bidirectional MAC route policy with route-target 1.1.1.1:111 and the default auto-generated ASN:Instance ID 65101:111 is not listed along with the manual configuration.

```
ES-1# show l2vpn evpn evi 111 detail
```

```
EVPN instance:          111 (VLAN Based)
RD:                     10.200.255.101:111 (auto)
Import-RTs:             1.1.1.1:111
Export-RTs:             1.1.1.1:111
Per-EVI Label:          none
State:                  Established
Replication Type:       Ingress (global)
<snip>
```

IP local proxy: Verifies the stretched IP-subnet SVI interface configured to support the IPv4 ARP local proxy function.

Use the **show ip interface vlan** command to verify the Anycast Gateway SVI interface. Network administrators can verify the ARP entries on local hosts to confirm the common IP gateway and the remote host IP-to-MAC binding entries.

```
ES-1# show ip interface vlan111
```

```
Vlan111 is up, line protocol is up
Internet address is 10.111.1.254/24
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
```

```

    MTU is 9100 bytes
<snip>
    Proxy ARP is enabled
    Local Proxy ARP is enabled
<snip>

```

VRF IP routing table: Verifies that the leaf implemented in EVPN multihoming mode is advertising the EVPN prefixes to the spine switch 10.200.255.3 based on the applied route-map policy.

The following command output from the border switch confirms that the pair of EVPN multihoming leaf systems configured in DAG routed overlay, each with two hosts are advertising RT2-MAC-IP. Border switches have a dual-path ECMP for each host to support load-sharing and redundancy for overlay network prefixes. And leaf switches receive RT-5 network prefix from the IP routing table of IP VRFs in the border systems that confirm the advertising of RT-5 EVPN prefixes.

```
ES-1# show ip route vrf green bgp
```

```

Routing Table: green
<snip>

```

```

Gateway of last resort is 10.200.255.2 to network 0.0.0.0
B*    0.0.0.0/0 [200/0] via 10.200.255.1, 00:00:32, Vlan101
      [200/0] via 10.200.255.2, 00:00:32, Vlan101

```

```
Border-1# show ip route vrf green bgp
```

```

Routing Table: green
<snip>

```

```
Gateway of last resort is 21.1.1.1 to network 0.0.0.0
```

```

B*    0.0.0.0/0 [20/0] via 21.1.1.1, 6w0d
      10.0.0.0/24 is subnetted, 95 subnets
B      10.111.1.1/32 [200/0] via 10.200.255.102, 00:01:33, Vlan1101
                        [200/0] via 10.200.255.101, 00:01:33, Vlan1101
B      10.111.1.2/32 [200/0] via 10.200.255.102, 00:01:33, Vlan1101
                        [200/0] via 10.200.255.101, 00:01:33, Vlan1101
B      10.111.1.3/32 [200/0] via 10.200.255.104, 00:01:33, Vlan1101
                        [200/0] via 10.200.255.103, 00:01:33, Vlan1101
B      10.111.1.4/32 [200/0] via 10.200.255.104, 00:01:33, Vlan1101
                        [200/0] via 10.200.255.103, 00:01:33, Vlan1101


```

Reference configuration for DAG routed overlay networks

This section provides a reference network design and configuration to implement end-to-end Layer 2 flood-free DAG routed overlay fabric network.

This following figure illustrates a reference network design to support scalable EVPN multihoming and fabric core with hierarchical BGP peering, control-plane peering, and selective stretching of an IP subnet between a pair of switches deployed in the distribution block with overlay fabric network.

Figure 3: EVPN multihoming: DAG routed overlay fabric network



This reference configuration shows a three-step process, from the initial network setup to the successful fabric deployment. Network administrators can follow these steps sequentially for initial deployment and to increment the overlay network configuration as the network demands increase.

Layer 2 EVPN multihoming

The base configuration to build a fabric begins with Layer 2 campus networks using EVPN multihoming technology. This section provides the step-by-step configuration on a pair of switches to successfully build a non-blocking all-active Layer 2 network with EVPN multihoming.

Step	ES-1 and ES-2	ES-3 and ES-4
1: Inter-ES Layer 3 EtherChannel	<pre> ES-1 ! interface Port-Channel 128 description CONNECTED TO EVPN MH SW-2 no switchport ip address 10.0.0.0 255.255.255.254 ip ospf network point-to-point ip ospf multi-area 0 ip ospf 100 area 101 ip ospf cost 10 carrier-delay msec 0 hold-queue 4094 in hold-queue 4094 out evpn multihoming core-tracking ! ES-2 ! interface Port-Channel 128 description CONNECTED TO EVPN MH SW-2 no switchport ip address 10.0.0.1 255.255.255.254 ip ospf network point-to-point ip ospf multi-area 0 ip ospf 100 area 101 ip ospf cost 10 carrier-delay msec 0 hold-queue 4094 in hold-queue 4094 out evpn multihoming core-tracking ! </pre>	<pre> ES-3 ! interface Port-Channel 128 description CONNECTED TO EVPN MH SW-1 no switchport ip address 10.0.0.2 255.255.255.254 ip ospf network point-to-point ip ospf multi-area 0 ip ospf 100 area 102 ip ospf cost 10 carrier-delay msec 0 hold-queue 4094 in hold-queue 4094 out evpn multihoming core-tracking ! ES-4 ! interface Port-Channel 128 description CONNECTED TO EVPN MH SW-1 no switchport ip address 10.0.0.3 255.255.255.254 ip ospf network point-to-point ip ospf multi-area 0 ip ospf 100 area 102 ip ospf cost 10 carrier-delay msec 0 hold-queue 4094 in hold-queue 4094 out evpn multihoming core-tracking ! </pre>

Step	ES-1 and ES-2	ES-3 and ES-4
2: IGP routing and core interface	<pre> ES-1 ! router ospf 100 router-id 10.200.255.101 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low area 101 stub no-summary passive-interface default no passive-interface Port-Channel 128 no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! interface Loopback 0 ip address 10.100.255.101 255.255.255.255 ip ospf 100 area 0 ! ES-2 ! router ospf 100 router-id 10.200.255.102 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low area 101 stub no-summary passive-interface default no passive-interface Port-Channel 128 no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! interface Loopback 0 ip address 10.100.255.102 255.255.255.255 ip ospf 100 area 0 ! </pre>	<pre> ES-3 ! router ospf 100 router-id 10.200.255.103 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low area 102 stub no-summary passive-interface default no passive-interface Port-Channel 128 no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! interface Loopback 0 ip address 10.100.255.103 255.255.255.255 ip ospf 100 area 0 ! ES-4 ! router ospf 100 router-id 10.200.255.104 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low area 102 stub no-summary passive-interface default no passive-interface Port-Channel 128 no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! interface Loopback 0 ip address 10.100.255.104 255.255.255.255 ip ospf 100 area 0 ! </pre>

Step	ES-1 and ES-2	ES-3 and ES-4
3: iBGP routing		

Step	ES-1 and ES-2	ES-3 and ES-4
	<pre> ES-1 ! router bgp 65101 template peer-policy ES-PEER-POLICY send-community both ! template peer-session ES-PEER-SESSION-POLICY remote-as 65101 description EVPN-MH-DIST-2-PEER update-source Loopback0 fall-over host-route ! bgp router-id interface Loopback0 bgp log-neighbor-changes bgp graceful-restart no bgp default ipv4-unicast neighbor 10.100.255.102 inherit peer-session ES-PEER-SESSION-POLICY ! address-family l2vpn evpn bgp nexthop trigger critical-delay 0 neighbor 10.100.255.102 activate neighbor 10.100.255.102 send-community both neighbor 10.100.255.102 inherit peer-policy ES-PEER-POLICY ! ES-2 ! router bgp 65101 template peer-policy ES-PEER-POLICY send-community both ! template peer-session ES-PEER-SESSION-POLICY remote-as 65101 description EVPN-MH-DIST-2-PEER update-source Loopback0 fall-over host-route ! bgp router-id interface Loopback0 bgp log-neighbor-changes bgp graceful-restart no bgp default ipv4-unicast neighbor 10.100.255.101 inherit peer-session ES-PEER-SESSION-POLICY ! address-family l2vpn evpn bgp nexthop trigger critical-delay 0 neighbor 10.100.255.101 activate neighbor 10.100.255.101 send-community both neighbor 10.100.255.101 inherit peer-policy ES-PEER-POLICY ! </pre>	<pre> ES-3 ! router bgp 65101 template peer-policy ES-PEER-POLICY send-community both ! template peer-session ES-PEER-SESSION-POLICY remote-as 65101 description EVPN-MH-DIST-1-PEER update-source Loopback0 fall-over host-route ! bgp router-id interface Loopback0 bgp log-neighbor-changes bgp graceful-restart no bgp default ipv4-unicast neighbor 10.100.255.104 inherit peer-session ES-PEER-SESSION-POLICY ! address-family l2vpn evpn bgp nexthop trigger critical-delay 0 neighbor 10.100.255.104 activate neighbor 10.100.255.104 send-community both neighbor 10.100.255.104 inherit peer-policy ES-PEER-POLICY ! ES-4 ! router bgp 65101 template peer-policy ES-PEER-POLICY send-community both ! template peer-session ES-PEER-SESSION-POLICY remote-as 65101 description EVPN-MH-DIST-1-PEER update-source Loopback0 fall-over host-route ! bgp router-id interface Loopback0 bgp log-neighbor-changes bgp graceful-restart no bgp default ipv4-unicast neighbor 10.100.255.103 inherit peer-session ES-PEER-SESSION-POLICY ! address-family l2vpn evpn bgp nexthop trigger critical-delay 0 neighbor 10.100.255.103 activate neighbor 10.100.255.103 send-community both neighbor 10.100.255.103 inherit peer-policy </pre>

Step	ES-1 and ES-2	ES-3 and ES-4
		<pre> ES-PEER-POLICY !</pre>
4: Global L2VPN	<pre> !</pre> l2vpn evpn advertise mac disable anycast-gateway mac auto multicast advertise sync-only multihoming aliasing disable multihoming peering adjacent replication-type ingress router-id Loopback 0 !	<pre> !</pre> l2vpn evpn advertise mac disable anycast-gateway mac auto multicast advertise sync-only multihoming aliasing disable multihoming peering adjacent replication-type ingress router-id Loopback 0 !
5: Routed VLAN and MAC VRF	<pre> !</pre> vlan 11 name ROUTED_DATA_VLAN ! l2vpn evpn instance 11 vlan-based encapsulation vxlan ! vlan configuration 11 member evpn-instance 11 vni 11011 ! interface nve 1 source-interface Loopback 0 host-reachability protocol bgp member vni 11011 ingress-replication !	<pre> !</pre> vlan 11 name ROUTED_DATA_VLAN ! l2vpn evpn instance 11 vlan-based encapsulation vxlan ! vlan configuration 11 member evpn-instance 11 vni 11011 ! interface nve 1 source-interface Loopback 0 host-reachability protocol bgp member vni 11011 ingress-replication !
6: DAG-routed VLAN and MAC VRF	<pre> !</pre> vlan 111 name DAG_ROUTED_DATA_VLAN ! l2vpn evpn instance 111 vlan-based encapsulation vxlan route-target 1.1.1.1:111 no auto-route-target ! vlan configuration 111 member evpn-instance 111 vni 11111 ! interface nve 1 member vni 11111 ingress-replication !	<pre> !</pre> vlan 111 name DAG_ROUTED_DATA_VLAN ! l2vpn evpn instance 111 vlan-based encapsulation vxlan route-target 1.1.1.1:111 no auto-route-target ! vlan configuration 111 member evpn-instance 111 vni 11111 ! interface nve 1 member vni 11111 ingress-replication !
7: ES EtherChannel	<pre> !</pre> interface Port-Channel 1 description CONNECTED TO L2 ACCESS switchport trunk allowed vlan 11,111 evpn ethernet-segment auto lacp df-election wait-time 1 !	<pre> !</pre> interface Port-Channel 1 description CONNECTED TO L2 ACCESS switchport trunk allowed vlan 11,111 evpn ethernet-segment auto lacp df-election wait-time 1 !

Underlay: fabric core and BGP peering

Enterprise campus core networks with solid underlay network foundation are the key for highly scalable, resilient BGP EVPN VXLAN fabric networks. This section is the second step to build a reliable underlay core network for fabric and hierarchical BGP peering on targeted network devices with specific roles.



Note The table is subdivided into two fabric roles with each step either sharing common configuration or a unique per-device with a common role.

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
1: Global best practices	<pre>! system mtu 9100 ! port-channel load-balance vlan-src-dst-mixed-ip-port ! ip cef load-sharing algorithm include-ports source destination protocol ! ip tcp mss 8000 ip tcp window-size 262144 ip tcp path-mtu-discovery !</pre>	<pre>! system mtu 9100 ! port-channel load-balance ! vlan-src-dst-mixed-ip-port ! ip cef load-sharing algorithm include-ports source destination protocol ! ip tcp mss 8000 ip tcp window-size 262144 ip tcp path-mtu-discovery !</pre>	<pre>! system mtu 9100 ! port-channel load-balance ! vlan-src-dst-mixed-ip-port ! ip cef load-sharing algorithm include-ports source destination protocol ! ip tcp mss 8000 ip tcp window-size 262144 ip tcp path-mtu-discovery !</pre>
2: Underlay interface configuration and best practices	<pre>! interface range HundredGig1/0/49-50 description CONNECTED TO SPINE ip ospf 100 area 0 ip ospf network point-to-point carrier-delay msec 0 hold-queue 4094 in hold-queue 4094 out evpn multihoming core-tracking !</pre>	<pre>! interface range HundredGig1/0/1-4 description CONNECTED TO CAMPUS CORE NETWORK ip ospf 100 area 0 ip ospf network point-to-point carrier-delay msec 0 hold-queue 4094 in hold-queue 4094 out !</pre>	<pre>! interface range HundredGig1/0/49-50 description CONNECTED TO SPINE ip ospf 100 area 0 ip ospf network point-to-point carrier-delay msec 0 hold-queue 4094 in hold-queue 4094 out !</pre>

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
3: OSPF routing configuration and best practices	<pre> ES-1 and ES-2 ! router ospf 100 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low area 101 stub no-summary passive-interface default no passive-interface Port-Channel 128 no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! ES-3 and ES-4 ! router ospf 100 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low area 102 stub no-summary passive-interface default no passive-interface Port-Channel 128 no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! </pre>	<pre> SPINE-1 ! router ospf 100 router-id 10.200.255.3 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low passive-interface default no passive-interface HundredGig1/0/1 no passive-interface HundredGig1/0/2 no passive-interface HundredGig1/0/3 no passive-interface HundredGig1/0/4 ! SPINE-2 ! router ospf 100 router-id 10.200.255.4 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low passive-interface default no passive-interface HundredGig1/0/1 no passive-interface HundredGig1/0/2 no passive-interface HundredGig1/0/3 no passive-interface HundredGig1/0/4 ! </pre>	<pre> BORDER-1 ! router ospf 100 router-id 10.200.255.1 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low passive-interface default no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! BORDER-2 ! router ospf 100 router-id 10.200.255.2 max-metric router-lsa include-stub summary-lsa external-lsa on-startup wait-for-bgp nsf cisco fast-reroute per-prefix enable prefix-priority low passive-interface default no passive-interface HundredGig1/0/49 no passive-interface HundredGig1/0/50 ! </pre>

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
4: BGP routing configuration and best practices	<pre>! router bgp 65101 ! bgp router-id interface Loopback0 bgp log-neighbor-changes bgp graceful-restart no bgp default ipv4-unicast !</pre>	<pre>! router bgp 65101 ! bgp router-id interface Loopback0 bgp log-neighbor-changes bgp graceful-restart no bgp default ipv4-unicast !</pre>	<pre>! router bgp 65101 ! bgp router-id interface Loopback0 bgp log-neighbor-changes bgp graceful-restart no bgp default ipv4-unicast !</pre>
5: Peer-session and peer-policy templates and parameters for leaf switches	<pre>! template peer-session EVPN-SPINE-PEER-SESSION-POLICY remote-as 65101 description EVPN-SPINE-PEER log-neighbor-changes update-source Loopback0 fall-over host-route ! template peer-policy EVPN-SPINE-PEER-POLICY send-community both !</pre>	<pre>! template peer-session EVPN-LEAF-PEER-SESSION-POLICY remote-as 65101 description EVPN-LEAF-PEER log-neighbor-changes update-source Loopback0 fall-over host-route ! template peer-policy EVPN-LEAF-PEER-POLICY route-reflector-client send-community both !</pre>	
6: Peer-session and policy templates and parameters for border switches		<pre>! template peer-session EVPN-BORDER-PEER-SESSION-POLICY remote-as 65101 description EVPN-BORDER-PEER log-neighbor-changes update-source Loopback0 fall-over host-route ! template peer-policy EVPN-BORDER-PEER-POLICY route-reflector-client send-community both !</pre>	<pre>! template peer-session EVPN-SPINE-PEER-SESSION-POLICY remote-as 65101 description EVPN-SPINE-PEER log-neighbor-changes update-source Loopback0 fall-over host-route ! template peer-policy EVPN-SPINE-PEER-POLICY send-community both !</pre>

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
7: Disable intra-cluster EVPN multihome leaf reflection		<pre>! no bgp client-to-client reflection intra-cluster cluster-id any</pre>	
8: Border-spine iBGP peering		<pre>! neighbor 10.200.255.1 inherit peer-session EVPN-BORDER-PEER-SESSION-POLICY ! neighbor 10.200.255.2 inherit peer-session EVPN-BORDER-PEER-SESSION-POLICY !</pre>	<pre>! neighbor 10.200.255.3 inherit peer-session EVPN-SPINE-PEER-SESSION-POLICY ! neighbor 10.200.255.4 inherit peer-session EVPN-SPINE-PEER-SESSION-POLICY !</pre>

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
9: Leaf iBGP peering	<pre> ! neighbor 10.200.255.3 inherit peer-session EVPN-SPINE-PEER-SESSION-POLICY ! neighbor 10.200.255.4 inherit peer-session EVPN-SPINE-PEER-SESSION-POLICY ! </pre>	<pre> ! neighbor 10.200.255.101 inherit peer-session EVPN-LEAF-PEER-SESSION-POLICY neighbor 10.200.255.101 cluster-id 1.1.1.1 ! neighbor 10.200.255.102 inherit peer-session EVPN-LEAF-PEER-SESSION-POLICY neighbor 10.200.255.102 cluster-id 1.1.1.1 ! neighbor 10.200.255.103 inherit peer-session EVPN-LEAF-PEER-SESSION-POLICY neighbor 10.200.255.101 cluster-id 1.1.1.2 ! neighbor 10.200.255.104 inherit peer-session EVPN-LEAF-PEER-SESSION-POLICY neighbor 10.200.255.102 cluster-id 1.1.1.2 ! </pre>	

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
10: Activate leaf and border iBGP peering under L2VPN EVPN address family	<pre> ! address-family l2vpn evpn bgp nexthop trigger critical-delay 0 neighbor 10.200.255.3 activate neighbor 10.200.255.3 send-community both neighbor 10.200.255.3 inherit peer-policy EVPN-SPINE-PEER-POLICY neighbor 10.200.255.4 activate neighbor 10.200.255.4 send-community both neighbor 10.200.255.4 inherit peer-policy EVPN-SPINE-PEER-POLICY ! </pre>		<pre> ! address-family l2vpn evpn bgp nexthop trigger critical-delay 0 neighbor 10.200.255.3 activate neighbor 10.200.255.3 send-community both neighbor 10.200.255.3 inherit peer-policy EVPN-SPINE-PEER-POLICY neighbor 10.200.255.4 activate neighbor 10.200.255.4 send-community both neighbor 10.200.255.4 inherit peer-policy EVPN-SPINE-PEER-POLICY ! </pre>

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
		<pre> ! address-family l2vpn evpn bgp nexthop trigger critical-delay 0 neighbor 10.200.255.1 activate neighbor 10.200.255.1 send-community both neighbor 10.200.255.1 inherit peer-policy EVPN-BORDER-PEER-POLICY neighbor 10.200.255.2 activate neighbor 10.200.255.2 send-community both neighbor 10.200.255.2 inherit peer-policy EVPN-BORDER-PEER-POLICY ! neighbor 10.200.255.101 activate neighbor 10.200.255.101 send-community both neighbor 10.200.255.101 inherit peer-policy EVPN-LEAF-PEER-POLICY neighbor 10.200.255.102 activate neighbor 10.200.255.102 send-community both neighbor 10.200.255.102 inherit peer-policy EVPN-LEAF-PEER-POLICY ! neighbor 10.200.255.103 activate neighbor 10.200.255.103 send-community both </pre>	

Step	ES-1, ES-2, ES-3 and ES-4	Spine-1 and Spine-2	Border-1 and Border-2
		<pre> neighbor 10.200.255.103 inherit peer-policy EVPN-LEAF-PEER-POLICY neighbor 10.200.255.104 activate neighbor 10.200.255.104 send-community both neighbor 10.200.255.104 inherit peer-policy EVPN-LEAF-PEER-POLICY !</pre>	

Overlay: DAG routed networks

The overlay network configuration is the final step to enable a fabric in the enterprise campus. This section provides step-by-step configuration procedures on VTEPs involved in a DAG routed overlay network that exchanges IP prefixes between external and internal network domains.

Step	ES-1, ES-2, ES-3 and ES-4	Border-1 and Border-2
1: IP VRF configuration	<pre> ES-1 ! vrf definition green rd 10.200.255.101:101 address-family ipv4 unicast route-target 65101:101 route-target 65101:101 stitching ! ES-2 ! vrf definition green rd 10.200.255.102:101 address-family ipv4 unicast route-target 65101:101 route-target 65101:101 stitching ! ES-3 ! vrf definition green rd 10.200.255.103:101 address-family ipv4 unicast route-target 65101:101 route-target 65101:101 stitching ! ES-4 ! vrf definition green rd 10.200.255.104:101 address-family ipv4 unicast route-target 65101:101 route-target 65101:101 stitching ! </pre>	<pre> BORDER-1 ! vrf definition green rd 10.200.255.1:101 address-family ipv4 unicast route-target 65101:101 route-target 65101:101 stitching ! BORDER-2 ! vrf definition green rd 10.200.255.2:101 address-family ipv4 unicast route-target 65101:101 route-target 65101:101 stitching ! </pre>
2: IP VRF core VLAN configuration	<pre> ! vlan 101 name VRF_GREEN_CORE_VLAN ! vlan configuration 101 member vni 10011 ! interface vlan 101 description CORE VLAN - VRF GREEN vrf forwarding green ip unnumbered Loopback0 no autostate ! </pre>	<pre> ! vlan 101 name VRF_GREEN_CORE_VLAN ! vlan configuration 101 member vni 10011 ! interface vlan 101 description CORE VLAN - VRF GREEN vrf forwarding green ip unnumbered Loopback0 no autostate ! </pre>
3: IP VRF L3VNI to NVE interface binding	<pre> ! interface nve 1 member vni 10011 vrf green ! </pre>	<pre> ! interface nve 1 member vni 10011 vrf green ! </pre>

Step	ES-1, ES-2, ES-3 and ES-4	Border-1 and Border-2
4: Network edge to access or external domain.	<pre> ES-1 and ES-2 ! interface Vlan 11 description ROUTED DATA VLAN - VRF GREEN vrf forwarding green ip address 10.11.1.254 255.255.255.0 ! interface Vlan 111 description DAG ROUTED DATA VLAN - VRF GREEN vrf forwarding green ip address 10.111.1.254 255.255.255.0 ! ES-3 and ES-4 ! interface Vlan 21 description ROUTED DATA VLAN - VRF GREEN vrf forwarding green ip address 10.21.1.254 255.255.255.0 ! interface Vlan 111 description DAG ROUTED DATA VLAN - VRF GREEN vrf forwarding green ip address 10.111.1.254 255.255.255.0 ! </pre>	<pre> BORDER-1 ! interface Vlan 2001 description FIREWALL HANDOFF - VRF GREEN vrf forwarding green ip address 21.1.1.0 255.255.255.254 ! BORDER-2 ! interface Vlan 2002 description FIREWALL HANDOFF - VRF GREEN vrf forwarding green ip address 21.1.1.2 255.255.255.254 ! </pre>
5: Route-map policy	<pre> ! route-map SPINE-ROUTE-POLICY-OUT permit 10 description ROUTED OVERLAY NETWORK POLICY match evpn route-type 5 ! route-map SPINE-ROUTE-POLICY-OUT permit 20 description DAG ROUTED OVERLAY NETWORK POLICY match evpn route-type 2-mac-ip ! </pre>	
6: Apply spine policy to BGP template	<pre> ! router bgp 65101 ! template peer-policy EVPN-SPINE-PEER-POLICY route-map SPINE-ROUTE-POLICY-OUT out ! </pre>	

Step	ES-1, ES-2, ES-3 and ES-4	Border-1 and Border-2
7: IP routing	<pre> ! router bgp 65101 ! address-family ipv4 vrf green advertise l2vpn evpn redistribute connected maximum-paths ibgp 2 ! </pre>	<pre> BORDER-1 ! router bgp 65101 ! address-family ipv4 vrf green advertise l2vpn evpn neighbor 21.1.1.1 remote-as 65001 neighbor 21.1.1.1 activate maximum-paths ibgp 2 ! BORDER-2 ! router bgp 65101 ! address-family ipv4 vrf green advertise l2vpn evpn neighbor 21.1.1.3 remote-as 65001 neighbor 21.1.1.3 activate maximum-paths ibgp 2 ! </pre>

