



Appendix A: Post-Upgrade Checklist

First Published: April 21, 2014

Revised: May 14, 2014

The following checklist is useful after you upgrade your software on a Cisco StadiumVision Director server.

List Item	Checkoff
1. Complete any specific verification steps documented for your particular upgrade.	<input type="checkbox"/>
2. Clear the browser cache.	<input type="checkbox"/>
 Caution Notify <i>all</i> Cisco StadiumVision Director users about the mandatory requirement to clear their browser cache before accessing the latest Cisco StadiumVision Director software.	
3. Verify that the Control Panel shows the Cisco StadiumVision Director version and build number that you installed.	<input type="checkbox"/>
4. If you are using phone control, verify that the phones work.	<input type="checkbox"/>
5. If using IP phones for local TV control, verify that channels can be successfully changed.	<input type="checkbox"/>
6. Verify that channel names and favorites are properly set.	<input type="checkbox"/>
7. If using suite commerce integration, verify that an order can be successfully placed using the IP phone.	<input type="checkbox"/>
8. Verify that all devices are properly in the nonevent_group.	<input type="checkbox"/>
9. Go to the Services Alert window in the Management Dashboard and make sure that all relevant services are green.	<input type="checkbox"/>
Tip You might need to click the refresh button to be sure that all services are re-pollled for status. If needed, you can Disable services that are not part of your installation	
10. Verify that all DMPs and TVs in the Management Dashboard are green.	<input type="checkbox"/>

List Item	Checkoff
11. Start an existing event script and validate that screens display the expected content.	<input type="checkbox"/>
12. Stop the event script and validate that screens are powered off.	<input type="checkbox"/>
13. Make a minor edit to the event script and make sure it can be saved.	<input type="checkbox"/>
14. Verify that you can push a new video file in the CMS to the DMPs.	<input type="checkbox"/>
15. If using dynamic menu boards, make a change to a menu item and verify that the change is reflected on the menu board.	<input type="checkbox"/>
16. If using external content integration, be sure to re-enable your data sources in the Control Panel and restart the External Content Integration application from the Management Dashboard.	<input type="checkbox"/>
17. Perform a server backup for the upgrade configuration.	<input type="checkbox"/>
18. After satisfying your site's testing and event requirements, failback to the primary server and upgrade it to the same version of software that you validated on your secondary server. For more information, see the “Configuring Failover Between Redundant Cisco StadiumVision Director Servers” module in the <i>Cisco StadiumVision Director Server Administration Guide</i> .	<input type="checkbox"/>
19. After you perform failback, be sure that you reconfigure your backup and restore environment using the Text Utility Interface (TUI).	<input type="checkbox"/>
20. (As needed for sites with a large volume of video content) Reduce the number of backups that are retained by the system. For more information, see the “Backing Up and Restoring Cisco StadiumVision Director Servers” module in the <i>Cisco StadiumVision Director Server Administration Guide</i> .	<input type="checkbox"/>