SSL Global Service Configuration Mode Commands

SSL global service lets you enable and configure basic SSL acceleration settings on your WAAS system. To configure global services on a WAAS device, use the **crypto ssl services global-settings** global configuration command. To delete a parameter use the **no** form of the command.

crypto ssl services global-settings

no crypto ssl services global-settings

Syntax Description This command has no arguments or keywords.

Defaults No default behavior or values.

Command Modes global configuration

Device Modes application-accelerator

central-manager

Usage Guidelines

Use the **crypto ssl services global-settings** command to configure basic SSL acceleration settings. The **crypto ssl services global-settings** command initiates SSL global service configuration mode, as indicated by the following prompt:

WAE(config-ssl-global)#

Within SSL global service configuration mode, you can use SSL global service configuration commands. To return to global configuration mode, enter **exit** at the SSL global service configuration mode prompt.

Examples

The following example shows how to enter SSL global service configuration mode:

WAE(config)# crypto ssl services global-settings WAE(config-ssl-global)# exit WAE(config)#

Related Commands

(config-ssl-global) cipher-list

(config-ssl-global) machine-cert-key

(config-ssl-global) version

(config-ssl-global) cipher-list

To configure secure socket layer (SSL) encryption cipher lists on a WAAS device, use the **cipher-list** command. To delete a cipher list use the **no** form of the command.

cipher-list cipher-list-name

no cipher-list cipher-list-name

Syntax Description	cipher-list-name	Name of the cipher list you want to create or edit. The cipher list name may contain up to 64 characters.
Defaults	No default behavior or values.	
Command Modes	SSL global service configuration	
Device Modes	application-accelerator central-manager	
Usage Guidelines	-	pher suites that you assign to an SSL connection. (See the SSL Cipher nds chapter for more information.)
Examples	edit a cipher list called myciphers	w to enter SSL global service configuration mode, and then create or i. If the cipher list is already established on the WAAS device, the ne cipher list does not exist, the cipher-list command creates it:
	WAE(config)# crypto ssl servi WAE(config-ssl-global)# ciphe	
Related Commands	(config) crypto ssl	

(config-ssl-global) machine-cert-key

To configure a certificate and private key, use the **machine-cert-key** command.

machine-cert-key filename

Syntax Description	filename	Filename of the certificate and key. Must be in PKCS#12 and have a ".p12" extension.
Defaults	No default behavior or values.	
Command Modes	SSL global service configuration	
Device Modes	application-accelerator central-manager	
Examples	The following example shows ho certificate and key: WAE(config)# crypto ssl servi WAE(config-ssl-global)# machi	
Related Commands	(config) crypto ssl	

(config-ssl-global) version

To specify the type of SSL protocol to use for global services, use the **version** command.

version {all | ssl3 | tls1}

Syntax Description	version {all ssl3 tls1}	Specifies SSL3 for the SSL version 3 protocol, TLS1 for the Transport Layer Security version 1 protocol, or All to use both SSL3 and TLS1 SSL protocols.
Defaults	No default behavior or values.	
Command Modes	SSL global service configuration	1
Device Modes	application-accelerator central-manager	
Examples	The following example shows he protocol to SSL version 3: WAE(config)# crypto ssl globe WAE(config-ssl-global)# versi	-
Related Commands	(config) crypto ssl	

(config-ssl-global) version