



Prepare to Configure

[Prerequisites and Restrictions](#) 2

[Prerequisites for Configuring the Cisco Remote-PHY Solution](#) 2

[Restrictions for Configuring the Cisco Remote-PHY Solution](#) 2

Revised: August 2, 2014,

Prerequisites and Restrictions

The following are the prerequisites and restrictions for Configuring the Cisco Remote-PHY Solution.

Prerequisites for Configuring the Cisco Remote-PHY Solution

- The Cisco CMTS must have at least one DOCSIS Timing, Communication, and Control (DTCC) card configured in the DOCSIS Timing Interface (DTI) mode for the Cisco uBR-MC3GX60V-RPHY line card to work with the CMC device.

Restrictions for Configuring the Cisco Remote-PHY Solution

- Adding or removing the upstream or downstream channels in the channel group may trigger the Cisco CMC to reset.
- The Cisco uBR-MC3GX60V-RPHY line card supports only static DEPI configuration.
- The Cisco uBR-MC3GX60V-RPHY line card does not support Spectrum Management, Inter Line Card RF Spanning, and High Availability.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA 95134-1706
USA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.