



DOCSIS Downstream Controllers

The table lists the features, the Cisco cBR version in which it was introduced, and also gives a short description of the feature.

Table 1: Feature History

Feature Name	Release Information	Feature Description
DOCSIS Downstream Controllers	Cisco IOS XE Bengaluru 17.6.1a	This release supports 32 DOCSIS controllers and 32 video controllers on the CBR-CCAP-LC-G2-R line card.

Cisco cBR-8 routers support DOCSIS with 32 DOCSIS controllers and 32 video controllers on the CBR-CCAP-LC-G2-R line card. The CBR-CCAP-LC-40G-R line card supports 32 downstream controllers. The 32 video SGs (downstream-video) are supported in addition to the existing 32 SGs (downstream-cable).

Downstream-cable supports both DOCSIS and video channels. If you want to increase the number of DOCSIS channels, move the video channels from downstream-cable to downstream-video so that you can avail all 32 downstream-cable controllers for DOCSIS.

Configure the DOCSIS channel in the legacy downstream-cable and the video channel in the new downstream-video.

You can choose downstream-video controllers option in the following two ways:

- The Service Distribution Group (SDG) configuration under cable video contains the option
 - The Core configuration in the cable RPD configuration
- The controller profile with the new video option helps to bind to the downstream-video controllers.
- [Configure Video Controllers, on page 1](#)
 - [Verify Video Controller-Profile, on page 2](#)
 - [Examples of Video Configuration, on page 5](#)

Configure Video Controllers

For Remote PHY line cards, SDG specifies the line card, bay, and downstream cable-controller where the video is destined. Use RPD `downstream-cable slot/bay/controller` command instead of `rf-port`

`integrated-cable slot/bay/port` command. You can specify only one downstream cable controller for an SDG. Hence, cBR-8 routers do not support.

So there are two types of controllers in RPHY:

`downstream-cable`: `rpd downstream-cable slot/bay/controller`

`downstream-video`: `rpd downstream-video slot/bay/controller`

Cisco RPD 1x2 can join up to 30 multicast streams simultaneously for video. The Cisco HA Shelf can join up to 30 multicast streams simultaneously for each RPD for video.

Configure Video Controller-Profile

Use the following sample command to configure the video controller profile.

Use different profile IDs for the cable downstream controller-profile video and cable downstream controller-profile.

```
Router(config)#cable downstream controller-profile 10 ?
  I-CMTS   Configure I-CMTS controller profile
  RPHY     Configure RPHY controller profile (default)
  Video    Configure Video controller profile
  copy     Copy configuration from exist controller profile
  <cr>    <cr>

Router(config)#cable downstream controller-profile 10 video
Router(config-controller-profile)#
```



Note

Add the keyword `video` to the controller profile. Otherwise, you cannot associate the profile to the `downstream-video` controller.

Configure RF Channel Type

You can configure only the video RF channels under the video controller-profile.

Use the following command to configure RF channel type:

```
Router(config-controller-profile)#rf 0 7
Router(config-prof-rf-chan)#type ?
  video  VIDEO (Asynchronous Mode)
```

Bind Video Controller to RPD DS Port

Use the following command to bind the video controller to an RPD DS port:

```
Router(config-rpd-core)#rpd-ds 0 downstream-video 1/0/?
  <0-31>  Controller port number
```

Verify Video Controller-Profile

Use the following command to verify the video controller-profile:

```

Router#show cable downstream controller-profile configured
Configured downstream controller-profiles:
I-CMTS
0    1

RPHY
99   101 134 195 197 199 200 221 223 225
227 249

VIDEO
2    10

```

Verify a Single Video Controller-Profile

Use the following command to verify a specific video controller-profile:

```

Router#show cable downstream controller-profile 2
Downstream controller-profile 2, type Video
Description:
Video controller-profile is being used by controller Downstream-Video:
  1/0/0, 1/0/3,
  Admin: UP
  MaxOfdmSpectrum: 0
  MaxCarrier: 158
  Mode: normal
  Free freq block list has 2 blocks:
    45000000 - 264999999
    271000000 - 1217999999
  DS Splitting: No
  OFDM frequency exclusion bands: None
Configured RF Channels:
Chan Admin Frequency Type Annex Mod srate Qam-profile dcid output
0    UP   268000000 VIDEO-ASYNC B   64   5057 0         -    NORMAL

```

Verify Video Controller-Profile Association

Use the following command to verify the video controller-profile association:

```

Router#show cable downstream controller-profile association
I-CMTS
Controller Integrated-Cable Downstream controller-profile id
None

RPHY
Controller Downstream-Cable Downstream controller-profile id
9/0/11                      223

Video
Controller Downstream-Video Downstream controller-profile id
1/0/0                       2
1/0/3                       2

```

Debug Video Controller-Profile

Use the following sample command to debug the video controller-profile.

```

Router#debug cable controller-profile ?
ds      Enable DS controller profile debug
us      Enable US controller profile debug
video   Enable Video controller profile debug

Router#debug cable controller-profile video
Video Controller Profile debugging is on

```

Show Details of All Video Controller Configurations

```
Router#show cable video downstream-video all
```

QAM	Port	TSID	ONID	Output	Physical	Admin	Operational	
Virtual-Carrier-Group				Service-Distribution-Group			Logical-Edge-Device	
Controller	Type	Encryption	Total	Port	QAM ID	State	State	Name
Capable	Sessions	Name				Name		
9/0/3:4	RPHY	-	-	0	160	ON	UP	-
clear	0	-				-		
9/0/3:5	RPHY	-	-	0	161	ON	UP	-
clear	0	-				-		
9/0/3:6	RPHY	-	-	0	162	ON	UP	-
clear	0	-				-		
9/0/3:7	RPHY	-	-	0	163	ON	UP	-
clear	0	-				-		
9/0/3:8	RPHY	-	-	0	164	ON	UP	-
clear	0	-				-		
--More--								

```
Router#show cable video downstream-video 9/0/3 rf-channel 20
```

```
Downstream-Cable: 9/0/35
RF Channel: 20
TSID: 20
ONID: 0
Physical QAM ID: 176
Admin State: ON
Operational State: UP
Virtual Carrier Group Name: vcg_R
Virtual Carrier Group ID: 8
Service Distribution Group Name: sdg-R
Service Distribution Group ID: 9
Logical Edge Device Name: led-R
Logical Edge Device ID: 2
Total Bandwidth: 38810700 bps
Available Bandwidth: 38810700 bps
Oversubscribed Bandwidth: 0 bps
Total Sessions: 1
```

```
show cable video session logical-edge-device id 2 downstream-video 9/0/3 summary
CHN3-RACK3-RPHY#$1-edge-device id 2 downstream-video 9/0/3 summary
Video Session Summary For Chassis:
```

```
Active      : 0          Init       : 0          Idle       : 0
Off         : 1          Blocked    : 0          PSI-Ready  : 0
UDP         : 1          ASM        : 0          SSM        : 0
Remap       : 1          Data       : 0          Passthru   : 0
Remux       : 0          Pending    : 0          Encrypted  : 0
Low Latency: 0
```

```
Total Sessions      : 1
Total Input Bitrate  : 0 BPS
Total Output Bitrate : 0 BPS
```

```
Router#$show cable video session logical-edge-device id 2 downstream-video 9/0/3
Total Sessions = 1
```

```

Session      Output Frequency Streaming Sess Session Source      UDP   Input
Output      Input      Output Input      Output Encrypt      Encrypt Low PMV
Session
Id           Port      Hz          Type          Type Ucast Dest IP/Mcast IP (S,G)  Port  Program
Program State      State      Bitrate      Bitrate      Type              Status      Lat NUM  Name
-----
2097152      20        221000000   Remap         UDP   171.113.2.21      -      49520 -
1            OFF        ON          0             0      CLEAR            -      N      -
test_video.9.0.2.20.49520

```

```

show cable video session logical-edge-device id 2 downstream-video 9/0/3 debug
Router#show logical-edge-device id 2 downstream-video 9/0/3 debug
Total Sessions = 1

```

```

Session      Output Output
|<-----Input----->|<-----Output----->|
Id           Port  Prog  Sync-Loss CC-Err  PCR-Jump UnderFlow OverFlow Block  Dropped
Overrun      Error  Block Overdue Inv-Rate  UnderFlow OverFlow Dropped
-----
2097152      20    1      0          0      0          0      0      0      0
0            0      0      0          0      0          0      0      0      0

```

Examples of Video Configuration

This section provides examples of the configuration.

```

Router(config)#cable downstream controller-profile 99 ?
I-CMTS  Configure I-CMTS controller profile
RPHY    Configure RPHY controller profile (default)
Video   Configure Video controller profile
copy    Copy configuration from exist controller profile
<cr>    <cr>

```

```

Router(config)#cable downstream controller-profile 99 video
Router(config-controller-profile)#

```

Video Profile

```

cable downstream controller-profile 99 Video
description Test_Downstream_Video_Controller
max-carrier 158
rf-chan 4 35
type VIDEO SYNC
qam-profile 1
frequency 125000000
rf-output NORMAL

```

SDG Configuration

```

cable video
service-distribution-group sdg-video id 9
rpd downstream-video 9/0/3

```

RPD Configuration

```

cable rpd LC9_RPD0_RACK5_6x12_SHF2
description RPD0_RACK5_6x12_SHF2
identifier f86b.d9ff.fafc
core-interface Te9/1/0
principal
rpd-ds 0 downstream-cable 9/0/4 profile 10

```

```
rpds 0 downstream-video 9/0/3 profile 99
rpds 0 upstream-cable 9/0/1 profile 1
core-interface Te9/1/2
rpds 0 downstream-cable 9/0/13 profile 32
r-dti 1
rpds-event profile 0
rpds-55d1-us-event profile
```