



Programming with the SCA BB Service Configuration API

Published: December 23, 2013, OL-30610-01

Introduction

This chapter is a reference for the main classes and methods of the Cisco SCA BB Service Configuration API. It also contains programming guidelines and code examples.

This chapter consists of these sections:

- [Service Configuration API Packages, page 3-1](#)
- [Package `com.cisco.scabb.servconf.mgmt`, page 3-2](#)
- [Class `SCABB`, page 3-2](#)
- [Class `ConnectionApi`, page 3-5](#)
- [Class `ImportExportApi`, page 3-5](#)
- [Class `ServiceConfigApi`, page 3-15](#)
- [Class `ServiceConfig`, page 3-21](#)
- [Service Configuration API Programming Guidelines, page 3-28](#)
- [Service Configuration API Code Examples, page 3-28](#)

Service Configuration API Packages

The Service Configuration API includes the following packages:

- Service Configuration Management API
 - `com.cisco.scabb.servconf.mgmt`
 - `com.pcube.apps.engage`
- Service Configuration Editing API
 - `com.cisco.scasbb.backend.classification`—Provides representation of the various model objects.

- `com.pcube.apps.engage.common`—Provides the classes that the Policy and Subscriber classes use.
- `com.pcube.apps.engage.policy`—Provides the classes that define service configurations.

Only `com.cisco.scabb.servconf.mgmt` is documented in this guide. For details of the other packages, see the Javadoc that is part of the Service Configuration API distribution (see the [“Distribution Content” section on page 2-2](#)).

Package `com.cisco.scabb.servconf.mgmt`

Package `com.cisco.scabb.servconf.mgmt` contains the following classes:

- `SCABB`—Provides methods for connecting to the SCE platform; these methods are used for apply and retrieve operations.
- `ConnectionApi`—Provides the connection handle to the SCE platform.
- `ImportExportApi`—Provides methods for saving service configurations to and reading service configurations from PQB files. This API also provides methods for importing and exporting parts of service configurations to and from CSV files.
- `ServiceConfigApi`—Provides methods for creating a new service configuration, and for applying service configurations to and retrieving service configurations from SCE platforms.
- `ServiceConfig`—Instances of this class are containers of configuration parameters that, when applied to the SCE platform, determine how the service control application performs classification, accounting and reporting, and control over network traffic.

Class `SCABB`

Class `SCABB` supplies login and logout methods to the SCE. The handle returned by the login serves all of the Service Configuration API and Subscriber API methods that directly affect the SCE. See the [“Class `SCABB` Methods” section on page 3-2](#) for details.

Class `SCABB` Methods

Class `SCABB` methods are explained in the following sections:

- [login, page 3-2](#)
- [login, page 3-3](#)
- [logout, page 3-3](#)
- [addNotificationListener, page 3-4](#)
- [removeNotificationListener, page 3-4](#)
- [getDefaultProtocolFamilies, page 3-4](#)

login

Syntax

```
public static ConnectionApi login(String hostName,
```

```

        String userName,
        String password,
        byte deviceType)
throws ConnectionFailedException

```

Description

Connects to the SCE platform; the method returns a handle that all the API methods that affect the device use.

Every login operation must be closed with a *logout* (*ConnectionApi*) operation.

Parameters

- *hostName*—SCE host address.
- *userName*—Username.
- *password*—Password.
- *deviceType*—Device type. Use the *Connection.SE_DEVICE* device type to connect to an SCE platform.

Return Value

The connection, which is a handle passed to all the API methods.

Exceptions

This method throws the *ConnectionFailedException* if the login fails; you can recover the reason for the failure from the exception.

login

Syntax

```

public static ConnectionApi login(com.pcube.management.framework.client.SessionObject
sessionObject)

```

Description

Connects to a device by using an existing *SessionObject*; the method returns a handle that all the API methods which affect the device use.

Every login operation must be closed with a *logout* (*ConnectionApi*) operation.

Parameters

sessionObject—Existing *SessionObject* of the device

Return Value

The connection, which is a handle passed to all the API methods.

logout

Syntax

```

public static void logout(ConnectionApi connectionApi)

```

Description

Disconnects from the SCE; the connection cannot be used after this method is called.

Parameters

connection—Connection that keeps a handle to the connection to the SCE

addNotificationListener**Syntax**

```
public static void addNotificationListener(NotificationListener listener)
```

Description

Subscribes the specified Cisco SCA BB notification listener to receive notifications about all the operations performed by the Cisco SCA BB API.

The listener must implement the NotificationListener interface.

Parameters

- listener—Notification listener

removeNotificationListener**Syntax**

```
public static void removeNotificationListener(NotificationListener listener)
```

Description

Unsubscribes the SCABB listener from receiving notifications about Cisco SCABB API operations.

The removed listener does not receive any more notifications.

Parameters

listener—NotificationListener to be removed

Exceptions

This method throws the IllegalArgumentException if the listener was never subscribed to listen to Cisco SCABB notifications

getDefaultProtocolFamilies**Syntax**

```
public static InputStream getDefaultProtocolFamilies()
```

Description

Gets the default protocol families for this class.

Return Value

An InputStream of the protocol families.

See Also

Class.getResourceAsStream(java.lang.String)

Class ConnectionApi

Class ConnectionApi is a connection handle to the SCE that all the Service Configuration API and Subscriber API methods use.

Class ConnectionApi Methods

Class ConnectionApi contains one method, which is explained in the following section:

isConnected

Syntax

```
public boolean isConnected()
```

Description

Checks if the connection is valid.

Return Value

`true` if connected to the device, `false` otherwise.

Class ImportExportApi

Class ImportExportApi is an API for import and export operations. Service configuration elements are imported and exported in CSV formats. Service configuration is imported and exported in XML format.

This section consists of these topics:

- [Class ImportExportApi Constructor, page 3-5](#)
- [Class ImportExportApi Methods, page 3-5](#)

Class ImportExportApi Constructor

The Class ImportExportApi constructor is explained in this section:

ImportExportApi

Syntax

```
public ImportExportApi()
```

Description

The ImportExportApi constructor.

Class ImportExportApi Methods

Class ImportExportApi methods are explained in these sections:

- [exportServiceConfiguration](#), page 3-6
- [importServiceConfiguration](#), page 3-7
- [importFlavors](#), page 3-7
- [importFlavors](#), page 3-8
- [importFlavorsFromEasyFormat](#), page 3-8
- [importHttpRefererFlavorsFromEasyFormat](#), page 3-8
- [importZones](#), page 3-9
- [importZones](#), page 3-9
- [importZonesFromEasyFormat](#), page 3-9
- [importProtocols](#), page 3-10
- [importProtocols](#), page 3-10
- [importServices](#), page 3-10
- [importServices](#), page 3-11
- [exportProtocols](#), page 3-11
- [exportProtocols](#), page 3-12
- [exportZones](#), page 3-12
- [exportZones](#), page 3-12
- [exportZonesToEasyFormat](#), page 3-13
- [exportFlavors](#), page 3-13
- [exportFlavors](#), page 3-13
- [exportFlavorsToEasyFormat](#), page 3-14
- [exportServices](#), page 3-14
- [exportServices](#), page 3-15
- [loadListArray](#), page 3-15

exportServiceConfiguration

Syntax

```
public static void exportServiceConfiguration(ServiceConfig servConf,
                                             File f)
throws FileNotFoundException,
       ImportExportException
```

Description

Exports a service configuration to a file.

Parameters

- `servConf`—Service configuration to export
- `f`—File to which to export the service configuration

Exceptions

This method may throw the following exceptions:

- FileNotFoundException
- ImportExportException—If an error occurs during the export.

importServiceConfiguration

Syntax

```
public static ServiceConfig importServiceConfiguration(File f)
throws ImportExportException,
      IOException
```

Description

Imports a service configuration from the specified file.

Parameters

- f—File containing the service configuration to import.

Return Value

The imported service configuration.

Exceptions

This method may throw the following exceptions:

- ImportExportException—If an error occurs during the import.
- IOException

importFlavors

Syntax

```
public static void importFlavors(ServiceConfig servConf,
                                FlavorType flavorType,
                                File file)
throws ImportExportException
```

Description

Imports flavors of a specified type from a specified CSV file.

Parameters

- servConf—Service configuration into which to import the flavors
- flavorType—Type of the imported flavors
- file—CSV file from which to import

Exceptions

This method may throw the following exception:

- ImportExportException—If an error occurs during the import.

importFlavors

Syntax

```
public static void importFlavors(ServiceConfig servConf,
                                FlavorType flavorType,
                                InputStream inStream)
throws ImportErrorException
```

Description

Imports flavors of a specified type from a given input stream.

Parameters

- servConf—Service configuration into which to import the flavors.
- flavorType—Type of the imported flavors.
- inStream—Input stream from which to import.

Exceptions

This method may throw the ImportErrorException if an error occurs during the import.

importFlavorsFromEasyFormat

Syntax

```
public static void importFlavorsFromEasyFormat(ServiceConfig servConf,
                                                File file)
throws ImportErrorException
```

Description

Imports flavors of a specified type from a specified CSV file in an Easy Format.

Parameters

- servConf—Service configuration into which to import the flavors.
- file—CSV file from which to import.

Exceptions

This method may throw the ImportErrorException if an error occurs during the import.

importHttpRefererFlavorsFromEasyFormat

Syntax

```
public static void importHttpRefererFlavorsFromEasyFormat(ServiceConfig servConf,
                                                           File file)
throws ImportErrorException
```

Description

Imports flavors of an HTTP Referer from a specified CSV file in Easy format.

Parameters

- servConf—Service configuration into which to import the flavors.

- file—CSV file from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the import.

importZones**Syntax**

```
public static void importZones(ServiceConfig servConf,
                             File file)
throws ImportExportException
```

Description

Imports zones from a specified CSV file.

Parameters

- servConf—Service configuration into which to import the zones.
- file—CSV file from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the import.

importZones**Syntax**

```
public static void importZones(ServiceConfig servConf,
                             InputStream inStream)
throws ImportExportException
```

Description

Imports zones from a given input stream.

Parameters

- servConf—Service configuration into which to import the zones.
- inStream—Input stream from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during import.

importZonesFromEasyFormat**Syntax**

```
public static void importZonesFromEasyFormat(ServiceConfig servConf,
                                             File file)
throws ImportExportException
```

Description

Imports zones from a specified CSV file in Easy format.

Parameters

- servConf—Service configuration into which to import the zones.
- file—CSV file from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the import.

importProtocols**Syntax**

```
public static void importProtocols(ServiceConfig servConf,
                                  File file)
throws ImportExportException
```

Description

Imports protocols from a specified CSV file.

Parameters

- servConf—Service configuration into which to import the protocols.
- file—CSV file from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the import.

importProtocols**Syntax**

```
public static void importProtocols(ServiceConfig servConf,
                                  InputStream inStream)
throws ImportExportException
```

Description

Imports protocols from a given input stream.

Parameters

- servConf—Service configuration into which to import the protocols.
- inStream—Input stream from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the import.

importServices**Syntax**

```
public static void importServices(ServiceConfig servConf,
                                  File file)
throws ImportExportException
```

Description

Imports services from a specified CSV file.

Parameters

- servConf—Service configuration into which to import the services.
- file—CSV file from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the import.

importServices

Syntax

```
public static void importServices(ServiceConfig servConf,  
                                InputStream inStream)  
throws ImportExportException
```

Description

Imports services from a given input stream.

Parameters

- servConf—Service configuration into which to import the services.
- inStream—Input stream from which to import.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the import.

exportProtocols

Syntax

```
public static void exportProtocols(List protocols,  
                                   File file)  
throws ImportExportException
```

Description

Exports protocols to a specified file in a CSV format.

Parameters

- protocols—List of protocols to export.
- file—File to which to export.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the export.

exportProtocols

Syntax

```
public static void exportProtocols(List protocols,
                                   OutputStream outputStream)
    throws ImportErrorException
```

Description

Exports protocols to a given output stream in a CSV format.

Parameters

- protocols—List of protocols to export.
- outputStream—Output stream to which to export.

Exceptions

This method may throw the ImportErrorException if an error occurs during the export.

exportZones

Syntax

```
public static void exportZones(List zones,
                                File file)
    throws ImportErrorException
```

Description

Exports zones to a specified file in a CSV format.

Parameters

- zones—List of zones to export.
- file—File to which to export.

Exceptions

This method may throw the ImportErrorException if an error occurs during the export.

exportZones

Syntax

```
public static void exportZones(List zones,
                                OutputStream outputStream)
    throws ImportErrorException
```

Description

Exports zones to a given output stream in a CSV format.

Parameters

- zones—List of zones to export.
- outputStream—Output stream to which to export.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the export.

exportZonesToEasyFormat

Syntax

```
public static void exportZonesToEasyFormat(List zones,
                                           File file)
throws ImportExportException
```

Description

Exports zones to a specified CSV file in Easy format.

Parameters

- `zones`—List of zones to export.
- `file`—File to which to export.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the export.

exportFlavors

Syntax

```
public static void exportFlavors(List flavors,
                                 FlavorType flavorType,
                                 File file)
throws ImportExportException
```

Description

Exports flavors of a specified type to a specified file in a CSV format.

Parameters

- `flavors`—List of flavors to export.
- `flavorType`—Type of the exported flavors.
- `file`—File to which to export.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the export.

exportFlavors

Syntax

```
public static void exportFlavors(List flavors,
                                 FlavorType flavorType,
                                 OutputStream outputStream)
throws ImportExportException
```

Description

Exports flavors of a specified type to a given output stream in a CSV format.

Parameters

- flavors—List of flavors to export.
- flavorType—Type of the exported flavors.
- outputStream—Output stream to which to export.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the export.

exportFlavorsToEasyFormat

Syntax

```
public static void exportFlavorsToEasyFormat(List flavors,  
                                             File file)  
throws ImportExportException
```

Description

Exports flavors of a specified type to a specified file in an Easy CSV format

Parameters

- flavors—List of flavors to export.
- file—File to which to export.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the export.

exportServices

Syntax

```
public static void exportServices(ServiceConfig servConf,  
                                 File file)  
throws ImportExportException
```

Description

Exports services from a service configuration to a file in CSV format.

Parameters

- servConf—Service configuration from which to export the services.
- file—File to which to export.

Exceptions

This method may throw the `ImportExportException` if an error occurs during the export.

exportServices

Syntax

```
public static void exportServices(ServiceConfig servConf,  
                                OutputStream outputStream)  
throws IOException
```

Description

Exports services from a service configuration to an output stream in CSV format.

Parameters

- servConf—Service configuration from which to export the services.
- outputStream—Output stream to which to export.

Exceptions

This method may throw the IOException if an error occurs during the export.

loadListArray

Syntax

```
public static void loadListArray(ServiceConfig servConf,  
                                InputStream inputStream)  
throws IOException
```

Description

Deprecated—Used only for 2.57 host list and IP list:

- It converts 2.57 CSV host-list files into 3.0 CSV HTTP URL flavor files.
- It converts 2.57 CSV IP-list files into 3.0 CSV zone files.

For loading 3.0 CSV files, use the methods importFlavors(ServiceConfig, FlavorType, File) and importZones(ServiceConfig, File).

Parameters

- servConf—Service configuration into which to import the services.
- inputStream—Input stream to import to.

Exceptions

- This method may throw the IOException.

Class ServiceConfigApi

Class ServiceConfigApi exposes Service Configuration API methods. All of these methods get or set data located in the SCE, and therefore, require a connection to the SCE platform.

Class ServiceConfigApi Methods

Class ServiceConfigApi methods are explained in these sections:

- [applyServiceConfiguration](#), page 3-16
- [applyServiceConfiguration](#), page 3-16
- [applyServiceConfiguration](#), page 3-17
- [retrieveServiceConfiguration](#), page 3-18
- [updateValuesIni](#), page 3-18
- [updateValuesIni](#), page 3-19
- [validateServiceConfiguration](#), page 3-19
- [importServConf](#), page 3-19
- [exportServConf](#), page 3-20
- [importDefaultServConf](#), page 3-20

applyServiceConfiguration

Syntax

```
public static long applyServiceConfiguration(ConnectionApi connectionApi,
                                           ServiceConfig servConf)
throws ElementManagementException,
       ApplyException
```

Description

Applies a service configuration to the specified SCE.

Parameters

- `connectionApi`—Connection API that keeps a handle to the connection to the SCE.
- `servConf`—Service configuration to apply.

Return Value

The operation time stamp.

Exceptions

This method may throw the following exceptions:

- `ElementManagementException`
- `ApplyException`

applyServiceConfiguration

Syntax

```
public static long applyServiceConfiguration(ConnectionApi connectionApi,
                                           ServiceConfig servConf,
                                           Properties applySettings)
throws ElementManagementException,
       ApplyException
```

Description

Applies a service configuration to the specified SCE.

Parameters

- connectionApi—Connection API that keeps a handle to the connection to the SCE.
- servConf—Service configuration to apply.
- applySettings—Properties.

Return Value

The operation time stamp.

Exceptions

This method may throw the following exceptions:

- ElementManagementException
- ApplyException

applyServiceConfiguration**Syntax**

```
public static long applyServiceConfiguration(ConnectionApi connectionApi,
                                           ServiceConfig servConf,
                                           boolean updateCm,
                                           Properties cmIpRemap,
                                           int cmUpdateMethod,
                                           int rpcPort
                                           boolean forceTemplateVirtualLinksInVlMode)
throws ElementManagementException,
       ApplyException
```

Description

Applies a service configuration to the specified SCE.

Parameters

- connectionApi—Connection API that keeps a handle to the connection to the SCE.
- servConf—Service configuration to apply.
- updateCm—Whether the Collection Manager for the specified SCE will be updated with the specified service configuration values.
- cmIpRemap—Map from the Collection Manager IP address as configured in the SCE, to the actual CM addresses.
- cmUpdateMethod—Method to use to connect to the Collection Manager.
- rpcPort—Port number for the Collection Manager RPC connection
- forceTemplateVirtualLinksInVlMode

Return Value

The operation time stamp.

Exceptions

This method may throw the following exceptions:

- ElementManagementException

- ApplyException

See Also

PolicyAPI.DC_UPDATE_METHOD_RPC, PolicyAPI.DC_DEFAULT_RPC_PORT

retrieveServiceConfiguration**Syntax**

```
public static ServiceConfig retrieveServiceConfiguration(ConnectionApi connectionApi)
throws IOException,
        ElementManagementException,
        ApplyException
```

Description

Retrieves the service configuration loaded in the specified SCE.

Parameters

- connectionApi—ConnectionApi that keeps a handle to the connection to the SCE.

Return Value

The service configuration in the SCE platform.

Exceptions

This method may throw the following exceptions:

- IOException
- ElementManagementException
- ApplyException

updateValuesIni**Syntax**

```
public static void updateValuesIni(String cmAddress,
                                  String sceAddress,
                                  ServiceConfig servConf)
throws ApplyException
```

Description

Updates the CM with data from the SCE platform service configuration.

Parameters

- cmAddress—Address of the CM to update.
- sceAddress—Address of the SCE platform that enforces the given service configuration.
- servConf—Service configuration.

Exceptions

This method may throw the ApplyException.

updateValuesIni

Syntax

```
public static void updateValuesIni(String cmAddress,
                                  String sceAddress,
                                  ServiceConfig servConf,
                                  int cmUpdateMethod,
                                  int rpcPort)

throws ApplyException
```

Description

Updates the CM with data from the SCE platform service configuration.

Parameters

- cmAddress—Address of the CM to update.
- sceAddress—Address of the SCE platform that enforces the given service configuration.
- servConf—Service configuration.
- cmUpdateMethod
- rpcPort

Exceptions

This method may throw the ApplyException.

validateServiceConfiguration

Syntax

```
public static ArrayList validateServiceConfiguration(ServiceConfig servConf)
```

Description

Validates a service configuration.

Parameters

servConf—The service configuration to validate.

Return Value

A vector with warning messages about rules that might have undesirable results.

See Also

PolicyValidator.validatePolicy(com.pcube.apps.engage.policy.Policy)

importServConf

Syntax

```
public static ServiceConfig importServConf(File pqbfile)
throws ImportExportException,
      IOException
```

Description

Loads the service configuration from a PQB file.

Parameters

- pqbfile—PQB file to load.

Return Value

The resulting service configuration.

Exceptions

This method may throw the following exceptions:

- ImportErrorException
- IOException

exportServConf**Syntax**

```
public static void exportServConf(ServiceConfig servConf,
                                 File pqbfile)
throws FileNotFoundException,
    ImportErrorException
```

Description

Saves a service configuration to a PQB file.

Parameters

- servConf—Service configuration to save.
- pqbfile—PQB file into which to save the service configuration.

Exceptions

This method may throw the following exceptions:

- FileNotFoundException
- ImportErrorException

importDefaultServConf**Syntax**

```
public static ServiceConfig importDefaultServConf()
throws ImportErrorException
```

Description

Loads the default service configuration.

Return Value

The default service configuration

Exceptions

This method may throw the `ImportExportException`.

Class ServiceConfig

Class `ServiceConfig` is the whole set of lists, protocols, services, and packages that an ISP has defined. The service configuration is applied to the ServiceConfig Domain SCE platforms and sets their application parameters to regulate subscriber flows.

Class ServiceConfig Methods

Class `ServiceConfig` methods are explained in these sections:

- [getCalendarList](#), page 3-21
- [getClassificationCfg](#), page 3-22
- [getDynamicSignatureScript](#), page 3-22
- [getPackageList](#), page 3-22
- [getPolicySettings](#), page 3-22
- [getProtocolList](#), page 3-23
- [getProtocolRedirectIndexNameArray](#), page 3-23
- [getProtocolRedirectString](#), page 3-23
- [getRealTimeFrameName](#), page 3-24
- [getServiceList](#), page 3-24
- [getSubNotifications](#), page 3-24
- [getTimeFrameNames](#), page 3-24
- [getProtocolRedirectString](#), page 3-25
- [getZoneList](#), page 3-25
- [isProtocolRedirectable](#), page 3-25
- [setProtocolRedirectString](#), page 3-26
- [setProtocolRedirectString](#), page 3-26
- [setTimeFrameName](#), page 3-27
- [setTimeFrameName](#), page 3-27
- [setTimeFrameNames](#), page 3-28

getCalendarList

Syntax

```
public CalendarArray getCalendarList()
```

Description

Gets the calendar list.

Return Value

The list of calendars in the service configuration.

getClassificationCfg

Syntax

```
public ClassificationConfiguration getClassificationCfg()
```

Description

Gets the classification configuration.

Return Value

The classification-related configuration in the domain.

getDynamicSignatureScript

Syntax

```
public DynamicSignaturesScript getDynamicSignatureScript()
```

Description

Gets the dynamic-signature configuration.

Return Value

The dynamic-signature script.

getPackageList

Syntax

```
public PackageArray getPackageList()
```

Description

Gets the service configuration package list.

Return Value

The service configuration package list.

getPolicySettings

Syntax

```
public PolicySettings getPolicySettings()
```

Description

Gets the service configuration settings for this service. These settings are general system settings for the SCE platforms in this service configuration domain.

Return Value

The service configuration settings for this service.

getProtocolList

Syntax

```
public ProtocolList getProtocolList()
```

Description

Gets this service configuration protocol list. The protocols in this list are referred to by the service configuration services.

Return Value

This service configuration protocols list.

getProtocolRedirectIndexNameArray

Syntax

```
public ProtocolRedirectIndexNameArray getProtocolRedirectIndexNameArray()
```

Description

Gets the list of redirect index names of the protocols.

Return Value

The list of redirect index names of the protocols.

getProtocolRedirectString

Syntax

```
public String getProtocolRedirectString(String protocolName,  
                                       int redirectIndex)  
throws ItemNotFoundException
```

Description

Gets the redirect address for the protocol in a certain index in its redirect string array.

Redirection is part of the protocol specification, and exists for only a few predefined protocols.

Parameters

- protocolName—Queried protocol.
- redirectIndex—Index in the redirect String array.

Return Value

The redirect address.

Exceptions

This method may throw the `ItemNotFoundException` if there is no such predefined protocol in this service configuration `ProtocolArray`, or if the redirect index is out of bound

getRealTimeFrameName

Syntax

```
public String getRealTimeFrameName(String name)
throws ItemNotFoundException
```

Description

Gets the predefined API name for a certain TimeFrame.

Parameters

- name—This service configuration alias for the TimeFrame.

Return Value

The TimeFrame API name.

Exceptions

This method may throw the ItemNotFoundException if there is no such alias in this service configuration.

getServiceList

Syntax

```
public ServiceArray getServiceList()
```

Description

Gets this service configuration service list.

Return Value

This service configuration service list.

getSubNotifications

Syntax

```
public SubNotificationArray getSubNotifications()
```

Description

Gets the subscriber notifications as configured in the service configuration.

Return Value

The subscriber notifications.

getTimeFrameNames

Syntax

```
public String[] getTimeFrameNames()
```


Description

Gets the time frame names this service configuration has assigned to the different TimeFrames.

These aliases allow time frames to have meaningful names.

The returned String array keeps in index X, the alias of the TimeFrame index X.

Return Value

The String array of this service configuration time frame names.

getProtocolRedirectString

Syntax

```
public String getProtocolRedirectString(String protocolName)
throws ItemNotFoundException
```

Description

Gets the default redirect address for the protocol.

Redirection is part of the protocol specification, and exists for only a few predefined protocols.

Parameters

- protocolName—Queried protocol.

Return Value

The redirect address.

Exceptions

This method may throw the ItemNotFoundException if there is no such predefined protocol in this service configuration ProtocolArray.

getZoneList

Syntax

```
public ZoneList getZoneList()
```

Description

Gets this service configuration IP, IP ranges, and host lists array. These lists are referred to by the service configuration services of this service.

Return Value

This service configuration array of lists.

isProtocolRedirectable

Syntax

```
public boolean isProtocolRedirectable(String protocolName)
throws ItemNotFoundException
```

Description

Checks if a specified protocol supports redirecting.

Redirection is part of the protocol specification, and exists for only a few predefined protocols.

Parameters

- protocolName—Queried protocol name.

Return Value

`true` if the protocol support redirection, `false` otherwise.

Exceptions

This method may throw the `ItemNotFoundException` if there is no such predefined protocol in this service configuration `ProtocolArray`.

setProtocolRedirectString

Syntax

```
public void setProtocolRedirectString(String protocolName,
                                     int redirectIndex,
                                     String value)

throws ItemNotFoundException,
       MalformedURLException
```

Description

Sets the address to which to redirect a certain flow. The redirection occurs when a rule has an *ACCESS_BLOCK_AND_REDIRECT* access mode for a certain service that uses the desired protocol. The setting is done to a certain `String` in the redirect `String` array. The rule chooses which redirect `String` to use from the redirect `String` array.

Parameters

- protocolName—Redirects the activity of this protocol.
- redirectIndex—Redirect `String` index in the protocol redirect `String` array.
- value—Protocol redirect address.

Exceptions

This method may throw the following exceptions:

- `ItemNotFoundException`—If there is no such predefined protocol in this service configuration `ProtocolArray`, or if the redirect index is out of bound.
- `MalformedURLException`—If the `String` is an illegal URL name.

setProtocolRedirectString

Syntax

```
public void setProtocolRedirectString(String protocolName,
                                     String value)

throws ItemNotFoundException,
       MalformedURLException
```

Description

Sets the default address to which to redirect a certain flow. The redirection occurs when a rule has an *ACCESS_BLOCK_AND_REDIRECT* access mode for a certain service that uses the desired protocol.

Parameters

- `protocolName`—Redirects the activity of this protocol.
- `value`—Protocol redirect address.

Exceptions

This method may throw the following exceptions:

- `ItemNotFoundException`—If there is no such predefined protocol in this service configuration `ProtocolArray`.
- `MalformedURLException`—If the `String` is an illegal URL name.

setTimeFrameName**Syntax**

```
public void setTimeFrameName(int index,
                             String newName)
throws ItemNotFoundException,
       DuplicateItemException
```

Description

Sets an alias for the `TimeFrame` that has a given index.

The alias allows the time frame to have a meaningful name.

Parameters

- `index`—Index of the `TimeFrame` to which the alias is given.
- `newName`—Alias for the name.

Exceptions

This method may throw the following exceptions:

- `ItemNotFoundException`—If there is no such `TimeFrame`.
- `DuplicateItemException`

setTimeFrameName**Syntax**

```
public void setTimeFrameName(TimeFrame frame,
                             String newName)
throws ItemNotFoundException,
       DuplicateItemException
```

Description

Sets an alias for the specified `TimeFrame`.

The alias allows the time frame to have a meaningful name.

Parameters

- `frame`—`TimeFrame` to which the alias is given.
- `newName`—Alias for the name.

Exceptions

This method may throw the following exceptions:

- `ItemNotFoundException`—If there is no such `TimeFrame`.
- `DuplicateItemException`

setTimeFrameNames**Syntax**

```
public void setTimeFrameNames(String[] newNames)
```

Description

Sets the names of all time frames.

Parameters

- `newNames`—The names to set

Service Configuration API Programming Guidelines

Connections to the SCE Platform

Make sure that the connections you create by using any of the `login()` methods are properly closed by using `logout()` (see [“logout” section on page 3-3](#)).

Service Configuration API Code Examples

This section gives several code examples of Service Configuration API usage.

- [Applying a Service Configuration, page 3-28](#)
- [Updating Zones Automatically, page 3-30](#)
- [Listing Names of Services and Packages, page 3-33](#)

Applying a Service Configuration

The following example applies a new service configuration to the SCE platform that is specified in the command line:

```
package examples;

import java.io.File;

import com.cisco.scabb.servconf.mgmt.ConnectionApi;
```

```

import com.cisco.scabb.servconf.mgmt.ImportExportApi;
import com.cisco.scabb.servconf.mgmt.SCABB;
import com.cisco.scabb.servconf.mgmt.ServiceConfig;
import com.cisco.scabb.servconf.mgmt.ServiceConfigApi;
import com.pcube.apps.engage.Connection;
import com.pcube.apps.engage.ConnectionFailedException;

/**
 * applies the service configuration in the PQB file to the SCE
 * specified in the command line. message is printed to standard error
 * in case of failure.
 * &lt;p&gt;
 * usage: java examples.SimpleApplyPqb &lt;sce-address&gt; &lt;password&gt;
 * &lt;pqb-filename&gt;
 */
public class SimpleApplyPqb {

    public static void main(String[] args) {

        if (args.length != 3) {
            System.err.println("usage: java examples.SimpleApplyPqb "
                + "&lt;sce-address&gt; &lt;password&gt; &lt;pqb-filename&gt;");
            System.exit(1);
        }

        String sceAddress = args[0];
        String password = args[1];
        String pqbFilename = args[2];

        ServiceConfig serviceConfig = openPqbFile(pqbFilename);

        if (serviceConfig == null) {
            return;
        }

        applyPqb(sceAddress, password, serviceConfig);
    }

    /**
     * apply the service configuration in the specified PQB file to the
     * specified SCE. message is printed to standard error in case of
     * failure.
     *
     * @param sceAddress
     * @param password
     * @param serviceConfig
     */
    private static void applyPqb(String sceAddress, String password,
        ServiceConfig serviceConfig) {
        ConnectionApi connection = null;
        try {

            System.out.println("connecting to SCE at " + sceAddress);
            connection = SCABB.login(sceAddress, "admin", password,
                Connection.SE_DEVICE);
            System.out.println("connected to SCE");

            System.out.println("applying service configuration");
            ServiceConfigApi.applyServiceConfiguration(connection,
                serviceConfig);
            System.out.println("service configuration applied");

        } catch (ConnectionFailedException e) {

```

```

        System.err.println("connection to SCE failed: "
            + e.getMessage());
        e.printStackTrace();

    } catch (Exception e) {

        System.err.println("apply operation failed: "
            + e.getMessage());
        e.printStackTrace();

    } finally {

        if (connection != null) {
            System.out.println("disconnecting from SCE");
            SCABB.logout(connection);
            System.out.println("disconnected");
        }

    }

}

/**
 * return the service configuration in the specified PQB file, or
 * null if reading the file has failed. message is printed to
 * standard error in case of failure.
 *
 * @param pqbFilename
 * @return
 */
private static ServiceConfig openPqbFile(String pqbFilename) {

    ServiceConfig serviceConfig = null;
    try {

        System.out.println("opening PQB file " + pqbFilename);
        serviceConfig = ImportExportApi
            .importServiceConfiguration(new File(pqbFilename));
        System.out.println("PQB file opened");

    } catch (Exception e) {

        System.err.println("opening PQB file failed: "
            + e.getMessage());
        e.printStackTrace();

    }

    return serviceConfig;
}
}

```

Updating Zones Automatically

The following example updates an SCE with zone IP addresses (specified in a CSV file):

```

package examples;

import java.io.File;

import com.cisco.scabb.servconf.mgmt.ConnectionApi;
import com.cisco.scabb.servconf.mgmt.ImportExportApi;

```

```

import com.cisco.scabb.servconf.mgmt.SCABB;
import com.cisco.scabb.servconf.mgmt.ServiceConfig;
import com.cisco.scabb.servconf.mgmt.ServiceConfigApi;
import com.cisco.scasbb.backend.classification.Zone;
import com.pcube.apps.engage.Connection;
import com.pcube.apps.engage.ConnectionFailedException;
import com.pcube.apps.engage.common.ImportExportException;

/**
 * updates an SCE with zone IP addresses. the zone IP address are
 * specified in a CSV file. the SCE address and CSV filename are taken
 * from the cmd-line argument.
 * <p>
 * usage: java examples.UpdateZoneFromCsv <sce-address> <password>
 * <zone-csv-file> <zone-name>
 *
 */
public class UpdateZoneFromCsv {

    public static void main(String[] args) {

        if (args.length != 4) {
            System.err.println("usage: java examples.UpdateZoneFromCsv"
                + " <sce-address> <password>"
                + " <zone-csv-file> <zone-name>");
            System.exit(1);
        }

        String sceAddress = args[0];
        String password = args[1];
        String csvFilename = args[2];
        String zoneName = args[3];

        ServiceConfig serviceConfig = retrievePqb(sceAddress, password);
        if (serviceConfig == null) {
            return;
        }

        ServiceConfig updatedServiceConfig = importZoneFromCsv(
            serviceConfig, csvFilename, zoneName);
        if (updatedServiceConfig == null) {
            return;
        }

        applyPqb(sceAddress, password, updatedServiceConfig);
    }

    /**
     * apply the service configuration in the specified PQB file to the
     * specified SCE. message is printed to standard error in case of
     * failure.
     *
     * @param sceAddress
     * @param password
     * @param serviceConfig
     */
    private static void applyPqb(String sceAddress, String password,
        ServiceConfig serviceConfig) {

        ConnectionApi connection = null;
        try {

            System.out.println("connecting to SCE at " + sceAddress);

```

```

        connection = SCABB.login(sceAddress, "admin", password,
            Connection.SE_DEVICE);
        System.out.println("connected to SCE");

        System.out.println("applying service configuration");
        ServiceConfigApi.applyServiceConfiguration(connection,
            serviceConfig);
        System.out.println("service configuration applied");
    } catch (ConnectionFailedException e) {

        System.err.println("connection to SCE failed: "
            + e.getMessage());
        e.printStackTrace();
    } catch (Exception e) {

        System.err.println("apply operation failed: "
            + e.getMessage());
        e.printStackTrace();
    } finally {

        if (connection != null) {
            System.out.println("disconnecting from SCE");
            SCABB.logout(connection);
            System.out.println("disconnected");
        }
    }
}

private static ServiceConfig importZoneFromCsv(
    ServiceConfig serviceConfig, String csvFilename,
    String zoneName) {

    // clear zone items
    Zone zone = (Zone) serviceConfig.getClassificationCfg()
        .getZoneList().findByName(zoneName);
    if (zone == null) {

        System.err.println("WARNING: zone not found: " + zoneName);
    } else {

        zone.getZoneItems().clear();
    }

    // import new zone items
    try {

        ImportExportApi.importZones(serviceConfig, new File(
            csvFilename));
    } catch (ImportExportException e) {

        System.err.println("importing zones failed: "
            + e.getMessage());
        e.printStackTrace();
        return null;
    }
}

```



```

        return serviceConfig;
    }

    private static ServiceConfig retrievePqb(String sceAddress,
        String password) {

        ServiceConfig retrievedServiceConfig = null;
        ConnectionApi connection = null;
        try {

            System.out.println("connecting to SCE at " + sceAddress);
            connection = SCABB.login(sceAddress, "admin", password,
                Connection.SE_DEVICE);
            System.out.println("connected to SCE");

            System.out.println("retrieving service configuration");
            retrievedServiceConfig = ServiceConfigApi
                .retrieveServiceConfiguration(connection);
            System.out.println("service configuration retrieved");

        } catch (ConnectionFailedException e) {

            System.err.println("connection to SCE failed: "
                + e.getMessage());
            e.printStackTrace();

        } catch (Exception e) {

            System.err.println("retrieve operation failed: "
                + e.getMessage());
            e.printStackTrace();

        } finally {

            if (connection != null) {
                System.out.println("disconnecting from SCE");
                SCABB.logout(connection);
                System.out.println("disconnected");
            }

        }

        return retrievedServiceConfig;
    }
}

```

Listing Names of Services and Packages

The following example prints the names of the services and packages that are in a service configuration:

```

package examples;

import java.io.File;
import java.io.IOException;
import java.util.Iterator;

import com.cisco.scabb.servconf.mgmt.ImportExportApi;
import com.cisco.scabb.servconf.mgmt.ServiceConfig;
import com.cisco.scabb.servconf.mgmt.ServiceConfigApi;
import com.pcube.apps.engage.common.ImportExportException;
import com.pcube.apps.engage.policy.Package;

```

```

import com.pcube.apps.engage.policy.Service;

public class IterateServiceConfig {

    public static void main(String[] args)
        throws ImportExportException, IOException {

        // take the PQB filename from the cmd-line, or use the default
        // service configuration instead
        ServiceConfig serviceConfig = null;
        if (args.length > 0) {
            serviceConfig = ImportExportApi
                .importServiceConfiguration(new File(args[0]));
        } else {
            serviceConfig = ServiceConfigApi.importDefaultServConf();
        }

        System.out.println("----- package names -----");
        Iterator pkgIter = serviceConfig.getPackageList().iterator();
        while (pkgIter.hasNext()) {

            Package pkg = (Package) pkgIter.next();
            System.out.println(pkg.getNumericId() + ": "
                + pkg.getName());

        }

        System.out.println("----- service names -----");
        Iterator svcIter = serviceConfig.getServiceList().iterator();
        while (svcIter.hasNext()) {

            Service svc = (Service) svcIter.next();
            System.out.println(svc.getNumericId() + ": "
                + svc.getName());

        }
    }
}

```