

Release Notes for Cisco Business Dashboard, Version 2.2.0

First Published: 2020-07-30

Introduction

These release notes describe the recommended practices and known issues that apply to software version 2.2.0 of Cisco Business Dashboard.

System Requirements for Cisco Business Dashboard

Cisco Business Dashboard is distributed as a virtual machine image, as an installer for use with the Ubuntu Linux distribution, and is available for Amazon Web Services (AWS) through the AWS Marketplace (https://aws.amazon.com/marketplace).

When running Cisco Business Dashboard on a virtual machine, your hypervisor must be one of the following:

- Microsoft Hyper-V version 10.0 or above
- Oracle VirtualBox version 6.1 or above
- VMWare—It can be one of the following:
 - · ESXi version 6.0 or above
 - Fusion version 11.5 or above
 - Workstation version 15.1 or above

To run Cisco Business Dashboard under Ubuntu Linux, your environment must be running Ubuntu version 16.04.x (Xenial Xerus) on a 64-bit Intel architecture platform. Cisco recommends using the Ubuntu server distribution and only installing packages required by Cisco Business Dashboard.

Table 1 lists the compute resources required for Cisco Business Dashboard based on the number of devices under management.

Table 1: Cisco Business Dashboard Compute Resource Requirements

#Device Supported	# vCPU	RAM	Disk Space
Up to 300	2	4GB	60GB
Up to 2500	12	24GB	60GB

To run Cisco Business Dashboard in AWS, you will need an AWS account. The following AWS instances types are supported:

• c5.large—up to 300 devices under management

• c5.4xlarge—up to 2500 devices under management

Cisco Business Dashboard is administered through a web user interface. To use this interface, your browser must be one of the following:

- Apple Safari (macOS only)—2 most recent major versions
- Google Chrome version—Latest version
- Microsoft Edge version—2 most recent major versions
- · Mozilla Firefox version—Latest version



Note

When using Safari, check that the certificate from Cisco Business Dashboard is set to **Always Trust**. Otherwise, certain functions that depend on the use of secure websockets are expected to fail. This is a limitation of the Safari web browser.

Your network must allow all instances of Cisco Business Dashboard Probe and directly managed network devices to establish TCP connectivity with Cisco Business Dashboard. For more details on the ports and protocols used, see *Frequently Asked Questions*, in the Cisco Business Dashboard Quick Start Guide.

System Requirements for Cisco Business Dashboard Probe

Cisco Business Dashboard Probe is distributed as a virtual machine image, and as installers for use with the following operating systems:

- Ubuntu Linux distribution running on a PC
- Raspbian Linux distribution running on a Raspberry Pi

Cisco Business Dashboard is also available as an embedded feature of select Cisco Business products.

To run Cisco Business Dashboard as a virtual machine, your environment must meet the following requirements:

- Hypervisor:
 - Microsoft Hyper-V version 10.0 or above
 - Oracle VirtualBox version 6.1 or above
 - VMWare—It can be one of the following:
 - ESXi version 6.0 or above
 - Fusion version 11.5 or above
 - Workstation version 15.1 or above
 - Virtual machine resource requirements:
 - CPU: 1x 64-bit Intel architecture
 - Memory: 512MB
 - Disk space: 5GB

To run Cisco Business Dashboard Probe under Ubuntu Linux operating system, your environment must meet the following requirements:

• Ubuntu version 16.04.x (Xenial Xerus)

• CPU: 1x 64-bit Intel architecture

Memory: 512MBDisk space: 5GB

To run the Cisco Business Dashboard Probe on a Raspberry Pi operating system, your environment must meet the following requirements:

• Hardware: Raspberry Pi 3 Model B/B+ or Raspberry Pi 4 Model B

• Disk space: 5GB

OS: Raspbian Buster

To run the Cisco Business Dashboard Probe as an embedded application on a Cisco Business product, you must have a supported product running a firmware version that supports the Cisco Business Dashboard Probe feature. Consult the Cisco Business Dashboard – Device Support List for details of hardware and version requirements. Also consult the administration guide for the product to determine any additional platform-specific requirements.

Cisco Business Dashboard Probe is administered through a web user interface. To use this interface, your browser must be one of the following:

- Apple Safari (macOS only)—2 most recent major versions
- Google Chrome—Latest version
- Microsoft Edge—2 most recent major versions
- Mozilla Firefox—Latest version

Cisco Business Dashboard Probe monitors and accesses the network devices that meet the following requirements:

- Must be in the same subnet as the PC that is running the Cisco Business Dashboard Probe, or be directly attached to a managed device and reachable via TCP/IP
- Must be a Cisco Business or Cisco Small Business 100 to 500 series device

Cisco Supported Devices

Cisco Business Dashboard supports Cisco Business and the Cisco Small Business 100 to 500 series products. For a detailed list of devices and features supported, please refer to the Cisco Business Dashboard - Device Support List.

License Requirements

Cisco Business Dashboard is a licensed application. Device licenses are required for each Cisco Business and Cisco Small Business product being managed. For more information, please refer to the Cisco Business Dashboard Datasheet.

Cisco Business Dashboard and Cisco FindIT Network Manager

Cisco Business Dashboard is derived from, upgrades, and replaces FindIT Network Manager. Cisco Business Dashboard provides all the functionality offered by FindIT Network Manager and more. FindIT Network Manager can be directly upgraded to Cisco Business Dashboard.

Difference between Cisco Business Dashboard and FindIT Network Manager

There are a number of differences between Cisco Business Dashboard and FindIT Network Manager. Cisco Business Dashboard adds support for the Cisco Business portfolio of products, and presents a new theme on the user interface. In addition, Cisco Business Dashboard includes the following functionality:

- Each installation of Cisco Business Dashboard includes 25 device licenses free of charge.
- Selected devices may be managed directly by Cisco Business Dashboard without requiring a probe to be present on the network.
- User configurable monitoring profiles that allow the monitoring of devices to be customized
- Access to the Cisco Business Dashboard application may be restricted based on IP Address ranges.
- Select PnP system variables may be manually set to accommodate complex deployments
- Sample PnP configuration templates have been provided
- PnP images and configuration files that have not yet been applied to a device will be applied to the device without waiting for a PnP connection if the device is active and reachable via a probe or direct management
- An Application Programming Interface (API) has been provided allowing the integration of third party applications with Cisco Business Dashboard. See https://cisco.com/go/cbd-api for details.

Upgrading to Cisco Business Dashboard from FindIT Network Manager

To upgrade from FindIT Network Manager or Probe version 2.1.x to Cisco Business Dashboard, do the following:

- 1. On the Manager, click **About FindIT**
- 2. Select the radio button next to the Manager update and click **Upgrade**. The Manager will download and apply the Cisco Business Dashboard upgrade package and then restart
- 3. Log on to the newly upgraded Dashboard, click the **About** icon
- **4.** Select the radio button next to the Probe update and click **Upgrade**. Each Probe will download and apply the Cisco Business Dashboard Probe upgrade package and then restart



Note

Upgrading to Cisco Business Dashboard from FindIT Network Manager version 2.0.x or 1.x is not supported. To upgrade FindIT Network Manager version 2.0.x or 1.x to Cisco Business Dashboard, first upgrade to FindIT Network Manager 2.1.1.

For more details on each step of this process, refer to the corresponding sections of the Cisco FindIT Network Management Administration Guide and the Cisco Business Dashboard Administration Guide.

Limitations and Restrictions

The Cisco Business Dashboard limitations and restrictions are described in the following sections:

- General Limitations
- System Backup and Restore

General Limitations

- The web interface on Cisco Business Dashboard takes a few minutes to become operational after the application is started
- Depending on the size of the network, it may take the Probe several minutes to discover all devices and calculate the network topology
- Up to 50 network devices can be managed by single virtual machine or Raspberry Pi Probe instance. Refer the documentation for the product in question to identify the maximum number of devices supported by an embedded probe running on a Cisco Business network device.
- Up to 2500 devices can be managed by a single Dashboard instance
- SNMPv3 authentication keys and privacy keys must be at least 8 characters in length
- When using Safari, ensure that the certificate presented by the Cisco Business Dashboard Probe is set to Always Trust

System Backup and Restore

- When performing a system backup or restore, Cisco Business Dashboard will prevent you from doing any further configuration actions
- Prior to beginning a system backup or restore, the idle timeout value in **Administration** > **Users** > **User Settings** should be set to at least 30 minutes (default is 60 minutes)

Caveats

Open Caveats

The following table lists the open caveats for Cisco Business Dashboard version 2.2.0

Table 2: Open Caveats

Caveat ID Number	Headline	
CSCvc02341	Roaming devices connect to multiple APs on topology.	
	Workaround	
	There is no workaround at this time.	

Caveat ID Number	Headline
CSCvc04204	Getting the duplicated entry in the credentials table for switch stack after power off the master.
	Workaround
	When the stack is stable, reboot Probe.
CSCvf49309	FindIT displays outside WAN IP instead of device IP on Network Plug and Play - Unclaimed Devices page.
	Workaround
	None
CSCvf49332	FindIT responses are slow when display is over 300 hosts on topology page.
	Workaround
	Don't try displaying hosts when there are many.
CSCvq25771	System does not sync time from the host on VirtualBox.
	Workaround
	Install VirtualBox Guest additions in the virtual machine with the command 'sudo apt-get install -y virtualbox-guest-utils' and reboot the virtual machine.
	Note The presence of VirtualBox Guest Additions in the virtual machine will prevent timesyncd from running and NTP will not function.
CSCvq25807	Stack switch unit configuration is missing after master recovery from offline.
	Workaround
	Manually read and accept current config or wait for the daily schedule job.
CSCvq25817	It doesn't show real VLAN setting info on a LAG port.
	Workaround
	Review the VLAN configuration for the LAG on the device administration GUI.
CSCvu45355	Fail to online upgrade SMB WAP devices by Tesla probe.
	Workaround
	Upgrade the WAP using Network Plug and Play or manually through the Administration GUI.
CSCvv18280	CBD doesn't support "same SSID name" case for CBW.
	Workaround
	Change the SSID names on the CBW access point to keep it unique.
	I

Resolved Caveats

The following table lists caveats present in FindIT Network Manager 2.1.1 that have been resolved in Cisco Business Dashboard 2.2.0

Table 3: Resolved Caveats

Caveat ID Number	Headline
CSCvc03176	System configurations and network settings don't apply on devices when restoring configurations.
CSCvq25755	Probe does NOT update ca-bundle periodically.
CSCvq25794	Profile with duplicated name is allowed to create in Network Configuration.

Where to Find Support

For current support information, visit the following URLs:

Table 4: Where to Find Support

Support				
Cisco Business Dashboard Support Forums	http://www.cisco.com/go/cbd-support			
Cisco Business Phone Support	http://www.cisco.com/go/cbphone			
Product Documentation				
Cisco Business Dashboard Support and Documentation Resources	https://cisco.com/go/cbd-docs			
Cisco Business				
Cisco Business Home	http://www.cisco.com/go/ciscobusiness			
Cisco Business Support Community	http://www.cisco.com/go/cbcommunity			

