



U Commands

- [ui-idle-timeout-seconds](#), on page 2
- [unicast](#), on page 3
- [update-source ethernet](#), on page 4
- [update-source loopback](#), on page 5
- [update-source vlan](#), on page 6
- [uplink-order](#), on page 7
- [uplink](#), on page 8
- [usage](#), on page 9
- [use-bia](#), on page 10
- [use-keyring](#), on page 11
- [use-vrf](#), on page 12
- [user](#), on page 13
- [username](#), on page 14

ui-idle-timeout-seconds

ui-idle-timeout-seconds <NUMBER>

Description: Set maximum GUI idle duration before requiring login refresh

Syntax:

<60-65525>	Set maximum GUI idle duration before requiring login refresh. Number range from=60 to=65525
------------	---

Command Mode: crypto webtoken : The cryptographic data used for generating and verifying web tokens.

Command Path:

```
# configure [['terminal', 't']]
(config)# crypto webtoken
(config-webtoken)# ui-idle-timeout-seconds <NUMBER>
```

unicast

unicast routing

Description: Instruct the fabric to route based on IP

Syntax:

routing	Unicast routing setting
---------	-------------------------

Command Mode: bridge-domain : Configuration for bridge-domain

Command Path:

```
# configure [['terminal', 't']]
(config)# tenant <WORD>
(config-tenant)# bridge-domain <WORD>
(config-tenant-bd)# unicast routing
```

update-source ethernet

update-source ethernet <interfaceRange>

Description: Source Ethernet Interface

Syntax:

<interfaceRange>	<interfaceRange>
------------------	------------------

Command Mode: neighbor : Configure a BGP neighbor

Command Path:

```
# configure [['terminal', 't']]
(config)# leaf <101-4000>
(config-leaf)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out
<WORD>]
(config-leaf-bgp-vrf-neighbor)# update-source ethernet <interfaceRange>
```

update-source ethernet <interfaceRange>

Description: Source Ethernet Interface

Syntax:

<interfaceRange>	<interfaceRange>
------------------	------------------

Command Mode: neighbor : Configure a BGP neighbor

Command Path:

```
# configure [['terminal', 't']]
(config)# spine <101-4000>
(config-spine)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out
<WORD>]
(config-leaf-bgp-vrf-neighbor)# update-source ethernet <interfaceRange>
```

update-source loopback

update-source loopback <A.B.C.D>

Description: Source Loopback Interface

Syntax:

<i>A.B.C.D</i>	IPv4 or IPv6 Address without mask
----------------	-----------------------------------

Command Mode: neighbor : Configure a BGP neighbor

Command Path:

```
# configure [['terminal', 't']]
(config)# leaf <101-4000>
(config-leaf)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out
<WORD>]
(config-leaf-bgp-vrf-neighbor)# update-source loopback <A.B.C.D>
```

update-source loopback <A.B.C.D>

Description: Source Loopback Interface

Syntax:

<i>A.B.C.D</i>	IPv4 or IPv6 Address without mask
----------------	-----------------------------------

Command Mode: neighbor : Configure a BGP neighbor

Command Path:

```
# configure [['terminal', 't']]
(config)# spine <101-4000>
(config-spine)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out
<WORD>]
(config-leaf-bgp-vrf-neighbor)# update-source loopback <A.B.C.D>
```

update-source vlan

update-source vlan <vlan>

Description: Source Vlan Interface

Syntax:

<vlan>	Vlan ID
--------	---------

Command Mode: neighbor : Configure a BGP neighbor

Command Path:

```
# configure [['terminal', 't']]
(config)# leaf <101-4000>
(config-leaf)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out
<WORD>]
(config-leaf-bgp-vrf-neighbor)# update-source vlan <vlan>
```

update-source vlan <vlan>

Description: Source Vlan Interface

Syntax:

<vlan>	Vlan ID
--------	---------

Command Mode: neighbor : Configure a BGP neighbor

Command Path:

```
# configure [['terminal', 't']]
(config)# spine <101-4000>
(config-spine)# router bgp <fabric-ASN>
(config-leaf-bgp)# vrf member tenant <WORD> vrf <WORD>
(config-leaf-bgp-vrf)# neighbor A.B.C.D|A.B.C.D/LEN|A:B::C:D|A:B::C:D/LEN [evpn] [l3out
<WORD>]
(config-leaf-bgp-vrf-neighbor)# update-source vlan <vlan>
```

uplink-order

uplink-order activeUplink <active_uplink> [standbyUplink <standby_uplink>]

Description: Configure Uplinks Failover Order for EPGs in Native mode

Syntax:

activeUplink	List the active uplink ids in the desired
<active_uplink>	List of active uplinks in the desired order
<standby_uplink>	(Optional) List of standby uplinks in the desired order

Command Mode: vmware-domain : Associate EPG to a VMWare Domain

Command Path:

```
# configure [['terminal', 't']]
(config)# tenant <WORD>
(config-tenant)# application <WORD>
(config-tenant-app)# epg <WORD> [type <WORD>]
(config-tenant-app-epg)# vmware-domain member <WORD> [encap <WORD>] [primary-encap <WORD>]
[allow-micro-segmentation] [deploy <WORD>] [push <WORD>] [binding-type
staticBinding|dynamicBinding|ephemeral] [port-allocation fixed|elastic] [num-ports <WORD>]
[untagged-access-pg] [custom-epg-name "<custom_name>"] [delimiter <WORD>]
(config-tenant-app-epg-domain)# uplink-order activeUplink <active_uplink> [standbyUplink
<standby_uplink>]
```

uplink

uplink <uplink-id> <uplink-name>

Description: Configure uplinks on DVS

Syntax:

<i>uplink-id</i>	The (integer) ID of the uplink to be configured
<i>uplink-name</i>	Configure the name of the uplink

Command Mode: vmware-domain : Create a VMM VMWare Domain

Command Path:

```
# configure [['terminal', 't']]
(config)# vmware-domain <WORD> [delimiter <WORD>] [access-mode <access-mode>]
[number-of-uplinks <number-of-uplinks>]
(config-vmware)# uplink <uplink-id> <uplink-name>
```

usage

usage <resource-type>

Description: Show deployment usage

Syntax:

<i>resource-type</i>	Resource type consuming the policy
----------------------	------------------------------------

Command Mode: configure : Configuration Mode

Command Path:

```
# configure [['terminal', 't']]
(config)# usage <resource-type>
```

use-bia

use-bia

Description: HSRP uses interfaces burned in address

Command Mode: template hsrp interface-policy : Configure HSRP Interface policy templates

Command Path:

```
# configure [['terminal', 't']]
(config)# leaf <101-4000>
(config-leaf)# template hsrp interface-policy <WORD> tenant <WORD>
(config-template-hsrp-if-pol)# use-bia
```

use-bia

Description: HSRP uses interfaces burned in address

Command Mode: template hsrp interface-policy : Configure HSRP Interface policy templates

Command Path:

```
# configure [['terminal', 't']]
(config)# spine <101-4000>
(config-spine)# template hsrp interface-policy <WORD> tenant <WORD>
(config-template-hsrp-if-pol)# use-bia
```

use-keyring

use-keyring <keyring-name>

Description: Use specified keyring for the HTTPS Server SSL certificate

Syntax:

<i>keyring-name</i>	Keyring name (Max Size 64)
---------------------	----------------------------

Command Mode: https : HTTPS communication policy group

Command Path:

```
# configure [['terminal', 't']]
(config)# comm-policy <WORD>
(config-comm-policy)# https
(config-https)# use-keyring <keyring-name>
```

use-vrf

use-vrf <arg>

Description: Configure the management vrf for dns servers

Syntax:

<i>arg</i>	Configure management vrf
------------	--------------------------

Command Mode: dns : Configure default dns policy

Command Path:

```
# configure [['terminal', 't']]
(config)# dns
(config-dns)# use-vrf <>
```

user

user <WORD>

Description: Set the remote path user name and password

Syntax:

<i>WORD</i>	User name
-------------	-----------

Command Mode: remote : Remote path configuration mode

Command Path:

```
# configure [['terminal', 't']]
(config)# remote path <WORD>
(config-remote)# user <WORD>
```

user <user-name>

Description: User Name

Syntax:

<i>user-name</i>	User Name
------------------	-----------

Command Mode: integrations-mgr : Integrations Manager

Command Path:

```
# configure [['terminal', 't']]
(config)# integrations-group <WORD>
(config-integrations-group)# integrations-mgr <WORD> <type>
(config-integrations-mgr)# user <user-name>
```

username

username <WORD>

Description: Create a locally-authenticated user account

Syntax:

<i>WORD</i>	User name (Max Size 32)
-------------	-------------------------

Command Mode: configure : Configuration Mode

Command Path:

```
# configure [['terminal', 't']]
(config)# username <WORD>
```

username <WORD>

Description: Configure a user account for the vCenter

Syntax:

<i>WORD</i>	Username for the account
-------------	--------------------------

Command Mode: vcenter : Configure a vCenter in the VMware domain

Command Path:

```
# configure [['terminal', 't']]
(config)# vmware-domain <WORD> [delimiter <WORD>] [access-mode <access-mode>]
[number-of-uplinks <number-of-uplinks>]
(config-vmware)# vcenter <> datacenter <WORD> [dvs-version <>]
(config-vmware-vc)# username <WORD>
```

username <WORD>

Description: Configure a user account for the nsx

Syntax:

<i>WORD</i>	Username for the account
-------------	--------------------------

Command Mode: nsx : Configure Nsx Manager in the VMware domain

Command Path:

```
# configure [['terminal', 't']]
(config)# vmware-domain <WORD> [delimiter <WORD>] [access-mode <access-mode>]
[number-of-uplinks <number-of-uplinks>]
(config-vmware)# nsx <>
(config-vmware-nsx)# username <WORD>
```

username <WORD>

Description: Configure a user account for the RHEV controller

Syntax:

<i>WORD</i>	Username for the account
-------------	--------------------------

Command Mode: rhev : Configure an RHEV controller in the Redhat domain

Command Path:

```
# configure [['terminal', 't']]
(config)# rhev-domain <WORD> [delimiter <WORD>]
(config-redhat)# rhev <> datacenter <WORD>
(config-redhat-rhev)# username <WORD>
```

