S Commands

- schedule, on page 19
- scheduler, on page 20
- show aaa authentication, on page 21
- show aaa groups, on page 22
- show aaa sessions, on page 23
- show access-list, on page 24
- show accounting log, on page 25
- show acllog deny l2 flow, on page 26
- show acllog deny l2 flow tenant vrf, on page 27
- show acllog deny l2 flow tenant vrf detail, on page 28
- show acllog deny l2 pkt, on page 29
- show acllog deny l2 pkt tenant vrf, on page 30
- show acllog deny l2 pkt tenant vrf detail, on page 31
- show acllog deny l3 flow, on page 32
- show acllog deny l3 flow tenant vrf, on page 33
- show acllog deny l3 flow tenant vrf detail, on page 34
- show acllog deny l3 pkt, on page 36
- show acllog deny l3 pkt tenant vrf, on page 37
- show acllog deny l3 pkt tenant vrf detail, on page 38
- show acllog permit l2 flow tenant vrf, on page 40
- show acllog permit l2 flow tenant vrf detail, on page 41
- show acllog permit l2 pkt tenant vrf, on page 42
- show acllog permit l2 pkt tenant vrf detail, on page 43
- show acllog permit l3 flow tenant vrf, on page 44
- show acllog permit l3 flow tenant vrf detail, on page 45
- show acllog permit l3 pkt tenant vrf, on page 47
- show acllog permit l3 pkt tenant vrf detail, on page 48
- show analytics, on page 50
- show application, on page 51
- show audits, on page 52
- show audits tenant, on page 53
- show audits tenant application, on page 54
- show audits tenant application epg, on page 55

- show audits tenant application esg, on page 56
- show audits tenant bridge-domain, on page 57
- show audits tenant bridge-domain detail, on page 58
- show audits tenant bridge-domain first-hop-security binding-table, on page 59
- show audits tenant bridge-domain first-hop-security statistics arp, on page 60
- show audits tenant bridge-domain first-hop-security statistics dhcpv4, on page 61
- show audits tenant bridge-domain first-hop-security statistics dhcpv6, on page 62
- show audits tenant bridge-domain first-hop-security statistics neighbor-discovery, on page 63
- show audits tenant dnsservergroup, on page 64
- show audits tenant dnsservergroup server, on page 65
- show audits tenant dnsservergroup server domain, on page 66
- show audits tenant interface bridge-domain, on page 67
- show audits tenant interface bridge-domain detail, on page 68
- show audits tenant interface bridge-domain first-hop-security binding-table, on page 69
- show audits tenant interface bridge-domain first-hop-security statistics arp, on page 70
- show audits tenant interface bridge-domain first-hop-security statistics dhcpv4, on page 71
- show audits tenant interface bridge-domain first-hop-security statistics dhcpv6, on page 72
- show audits tenant interface bridge-domain first-hop-security statistics neighbor-discovery, on page 73
- show audits tenant multicast-route-maps, on page 74
- show audits tenant vrf, on page 75
- show audits tenant vrf acllog l2, on page 76
- show audits tenant vrf acllog l3, on page 77
- show audits tenant vrf detail, on page 79
- show audits tenant vrf external-l3 bgp, on page 80
- show audits tenant vrf external-l3 bgp node, on page 81
- show audits tenant vrf external-l3 eigrp, on page 82
- show audits tenant vrf external-l3 eigrp detail, on page 83
- show audits tenant vrf external-l3 epg, on page 84
- show audits tenant vrf external-l3 epg detail, on page 85
- show audits tenant vrf external-l3 interfaces, on page 86
- show audits tenant vrf external-l3 interfaces detail, on page 87
- show audits tenant vrf external-l3 ospf, on page 88
- show audits tenant vrf external-l3 ospf detail, on page 89
- show audits tenant vrf external-l3 scale, on page 90
- show audits tenant vrf external-l3 scale detail, on page 91
- show audits tenant vrf external-l3 static-route, on page 92
- show audits tenant vrf external-l3 static-route detail, on page 93
- show audits tenant vrf external-l3 static-route node, on page 94
- show audits tenant vrf external-l3 static-route node detail, on page 95
- show audits tenant vrf ipv6multicast, on page 96
- show audits tenant vrf multicast, on page 97
- show bridge-domain, on page 98
- show bridge-domain detail, on page 99
- show bridge-domain first-hop-security binding-table, on page 100
- show bridge-domain first-hop-security statistics arp, on page 101
- show bridge-domain first-hop-security statistics dhcpv4, on page 102

- show bridge-domain first-hop-security statistics dhcpv6, on page 103
- show bridge-domain first-hop-security statistics neighbor-discovery, on page 104
- show callhome, on page 105
- show callhome common destination-profile, on page 106
- show callhome common query-profile, on page 107
- show callhome common transport-email, on page 108
- show catalog, on page 109
- show cli command, on page 110
- show cli list, on page 111
- show cli manpage, on page 112
- show cli path, on page 113
- show clock, on page 114
- show cloudave, on page 115
- show cloudsec summary, on page 116
- show communication ciphers, on page 117
- show communication controller, on page 118
- show communication http, on page 119
- show communication https, on page 120
- show communication performance, on page 121
- show communication performance config, on page 122
- show communication performance results, on page 123
- show communication shellinabox, on page 124
- show communication ssh-service, on page 125
- show communication telnet, on page 126
- show communication web-requests, on page 127
- show contract-type, on page 128
- show contract, on page 129
- show controller, on page 130
- show controller detail, on page 131
- show cores, on page 132
- show cores status, on page 133
- show debug counter, on page 134
- show debug log, on page 135
- show deployment endpoint node, on page 136
- show discoveryissues, on page 137
- show discoveryissues node, on page 138
- show dns-address, on page 139
- show dns-domain, on page 140
- show dot1q-tunnel, on page 141
- show dwdm interface, on page 142
- show endpoints, on page 143
- show endpoints leaf interface ethernet, on page 144
- show endpoints leaf interface port-channel, on page 145
- show endpoints vpc, on page 146
- show epg, on page 147
- show epg detail, on page 148

- show esg, on page 149
- show esg detail, on page 150
- show events, on page 151
- show events controller, on page 152
- show events controller detail, on page 153
- show events leaf, on page 154
- show events leaf fex, on page 155
- show events leaf fex module, on page 156
- show events leaf interface ethernet, on page 157
- show events leaf interface fc, on page 158
- show events leaf interface fcportchannel, on page 159
- show events leaf interface l3instance, on page 160
- show events leaf interface mgmt, on page 161
- show events leaf interface portchannel, on page 162
- show events leaf interface tunnel, on page 163
- show events leaf interface vethernet, on page 164
- show events leaf inventory chassis, on page 165
- show events leaf inventory fans, on page 166
- show events leaf inventory module, on page 167
- show events leaf inventory module fabricport, on page 168
- show events leaf inventory module leafport, on page 169
- show events leaf inventory powersupply, on page 170
- show events leaf inventory supervisor, on page 171
- show events leaf protocol, on page 172
- show events leaf vpc, on page 173
- show events leaf vrf, on page 174
- show events spine, on page 175
- show events spine interface ethernet, on page 176
- show events spine interface l3instance, on page 177
- show events spine interface mgmt, on page 178
- show events spine interface tunnel, on page 179
- show events spine inventory chassis, on page 180
- show events spine inventory fabric, on page 181
- show events spine inventory fans, on page 182
- show events spine inventory module, on page 183
- show events spine inventory module fabricport, on page 184
- show events spine inventory powersupply, on page 185
- show events spine inventory supervisor, on page 186
- show events spine inventory system, on page 187
- show events spine protocol, on page 188
- show events spine vrf, on page 189
- show events tenant, on page 190
- show events tenant application, on page 191
- show events tenant application epg, on page 192
- show events tenant application esg, on page 193
- show events tenant bridge-domain, on page 194

- show events tenant bridge-domain detail, on page 195
- show events tenant bridge-domain first-hop-security binding-table, on page 196
- show events tenant bridge-domain first-hop-security statistics arp, on page 197
- show events tenant bridge-domain first-hop-security statistics dhcpv4, on page 198
- show events tenant bridge-domain first-hop-security statistics dhcpv6, on page 199
- show events tenant bridge-domain first-hop-security statistics neighbor-discovery, on page 200
- show events tenant dnsservergroup, on page 201
- show events tenant dnsservergroup server, on page 202
- show events tenant dnsservergroup server domain, on page 203
- show events tenant endpoints, on page 204
- show events tenant endpoints leaf interface ethernet, on page 205
- show events tenant endpoints leaf interface port-channel, on page 206
- show events tenant endpoints vpc, on page 207
- show events tenant interface bridge-domain, on page 208
- show events tenant interface bridge-domain detail, on page 209
- show events tenant interface bridge-domain first-hop-security binding-table, on page 210
- show events tenant interface bridge-domain first-hop-security statistics arp, on page 211
- show events tenant interface bridge-domain first-hop-security statistics dhcpv4, on page 212
- show events tenant interface bridge-domain first-hop-security statistics dhcpv6, on page 213
- show events tenant interface bridge-domain first-hop-security statistics neighbor-discovery, on page 214
- show events tenant multicast-route-maps, on page 215
- show events tenant vrf, on page 216
- show events tenant vrf acllog l2, on page 217
- show events tenant vrf acllog l3, on page 218
- show events tenant vrf detail, on page 220
- show events tenant vrf external-l3 bgp, on page 221
- show events tenant vrf external-l3 bgp node, on page 222
- show events tenant vrf external-l3 eigrp, on page 223
- show events tenant vrf external-l3 eigrp detail, on page 224
- show events tenant vrf external-l3 epg, on page 225
- show events tenant vrf external-l3 epg detail, on page 226
- show events tenant vrf external-l3 interfaces, on page 227
- show events tenant vrf external-l3 interfaces detail, on page 228
- show events tenant vrf external-l3 ospf, on page 229
- show events tenant vrf external-l3 ospf detail, on page 230
- show events tenant vrf external-l3 route-map, on page 231
- show events tenant vrf external-l3 route-map detail, on page 232
- show events tenant vrf external-l3 scale, on page 233
- show events tenant vrf external-l3 scale detail, on page 234
- show events tenant vrf external-l3 static-route, on page 235
- show events tenant vrf external-l3 static-route detail, on page 236
- show events tenant vrf external-l3 static-route node, on page 237
- show events tenant vrf external-l3 static-route node detail, on page 238
- show events tenant vrf ipv6multicast, on page 239
- show events tenant vrf multicast, on page 240
- show external-l2 epg, on page 241

- show external-l2 epg name, on page 242
- show external-l2 epg tenant, on page 243
- show external-l3 bgp, on page 244
- show external-l3 bgp tenant, on page 245
- show external-l3 bgp tenant vrf, on page 246
- show external-l3 bgp tenant vrf node, on page 247
- show external-l3 eigrp, on page 248
- show external-l3 eigrp detail, on page 249
- show external-l3 eigrp node, on page 250
- show external-l3 eigrp node detail, on page 251
- show external-l3 eigrp tenant, on page 252
- show external-l3 eigrp tenant detail, on page 253
- show external-l3 eigrp tenant vrf, on page 254
- show external-l3 eigrp tenant vrf detail, on page 255
- show external-l3 eigrp tenant vrf node, on page 256
- show external-l3 eigrp tenant vrf node detail, on page 257
- show external-l3 epg, on page 258
- show external-l3 epg detail, on page 259
- show external-l3 epg name, on page 260
- show external-l3 epg name detail, on page 261
- show external-l3 epg tenant, on page 262
- show external-l3 epg tenant detail, on page 263
- show external-l3 epg tenant vrf, on page 264
- show external-l3 epg tenant vrf detail, on page 265
- show external-l3 interfaces, on page 266
- show external-l3 interfaces detail, on page 267
- show external-l3 interfaces node, on page 268
- show external-l3 interfaces node detail, on page 269
- show external-l3 interfaces tenant, on page 270
- show external-l3 interfaces tenant detail, on page 271
- show external-l3 interfaces tenant vrf, on page 272
- show external-l3 interfaces tenant vrf detail, on page 273
- show external-l3 interfaces tenant vrf node, on page 274
- show external-l3 interfaces tenant vrf node detail, on page 275
- show external-l3 ospf, on page 276
- show external-l3 ospf detail, on page 277
- show external-l3 ospf node, on page 278
- show external-l3 ospf node detail, on page 279
- show external-l3 ospf tenant, on page 280
- show external-l3 ospf tenant detail, on page 281
- show external-l3 ospf tenant vrf, on page 282
- show external-l3 ospf tenant vrf detail, on page 283
- show external-l3 ospf tenant vrf node, on page 284
- show external-l3 ospf tenant vrf node detail, on page 285
- show external-l3 route-map, on page 286
- show external-l3 route-map detail, on page 287

- show external-l3 route-map name, on page 288
- show external-l3 route-map name detail, on page 289
- show external-l3 route-map tenant, on page 290
- show external-l3 route-map tenant detail, on page 291
- show external-l3 route-map tenant vrf, on page 292
- show external-l3 route-map tenant vrf detail, on page 293
- show external-l3 route-map tenant vrf node, on page 294
- show external-l3 route-map tenant vrf node detail, on page 295
- show external-l3 scale, on page 296
- show external-l3 scale detail, on page 297
- show external-l3 scale node, on page 298
- show external-l3 scale node detail, on page 299
- show external-l3 scale tenant, on page 300
- show external-l3 scale tenant detail, on page 301
- show external-l3 scale tenant vrf, on page 302
- show external-l3 scale tenant vrf detail, on page 303
- show external-l3 scale tenant vrf node, on page 304
- show external-l3 scale tenant vrf node detail, on page 305
- show external-l3 static-route, on page 306
- show external-l3 static-route detail, on page 307
- show external-l3 static-route node, on page 308
- show external-l3 static-route node detail, on page 309
- show external-l3 static-route tenant, on page 310
- show external-l3 static-route tenant detail, on page 311
- show external-l3 static-route tenant vrf, on page 312
- show external-l3 static-route tenant vrf detail, on page 313
- show external-l3 static-route tenant vrf node, on page 314
- show external-l3 static-route tenant vrf node detail, on page 315
- show fabric-discovery-health, on page 316
- show fabric-recovery checker, on page 317
- show fabric-recovery status, on page 318
- show faults, on page 319
- show faults controller, on page 320
- show faults controller detail, on page 321
- show faults l4l7-cluster, on page 322
- show faults l4l7-graph, on page 323
- show faults leaf, on page 324
- show faults leaf fex, on page 325
- show faults leaf fex module, on page 326
- show faults leaf interface ethernet, on page 327
- show faults leaf interface fc, on page 328
- show faults leaf interface fcportchannel, on page 329
- show faults leaf interface l3instance, on page 330
- show faults leaf interface mgmt, on page 331
- show faults leaf interface portchannel, on page 332
- show faults leaf interface tunnel, on page 333

- show faults leaf interface vethernet, on page 334
- show faults leaf inventory chassis, on page 335
- show faults leaf inventory fans, on page 336
- show faults leaf inventory module, on page 337
- show faults leaf inventory module fabricport, on page 338
- show faults leaf inventory module leafport, on page 339
- show faults leaf inventory powersupply, on page 340
- show faults leaf inventory supervisor, on page 341
- show faults leaf protocol, on page 342
- show faults leaf vpc, on page 343
- show faults leaf vrf, on page 344
- show faults microsoft domain, on page 345
- show faults microsoft domain name, on page 346
- show faults microsoft domain name hyperv, on page 347
- show faults microsoft domain name port-group, on page 348
- show faults microsoft domain name scvmm, on page 349
- show faults microsoft domain name vm, on page 350
- show faults microsoft domain name vm name, on page 351
- show faults quota, on page 352
- show faults redhat domain, on page 353
- show faults redhat domain name, on page 354
- show faults redhat domain name epg, on page 355
- show faults redhat domain name rhev, on page 356
- show faults spine, on page 357
- show faults spine interface ethernet, on page 358
- show faults spine interface l3instance, on page 359
- show faults spine interface mgmt, on page 360
- show faults spine interface tunnel, on page 361
- show faults spine inventory chassis, on page 362
- show faults spine inventory fabric, on page 363
- show faults spine inventory fans, on page 364
- show faults spine inventory module, on page 365
- show faults spine inventory module fabricport, on page 366
- show faults spine inventory powersupply, on page 367
- show faults spine inventory supervisor, on page 368
- show faults spine inventory system, on page 369
- show faults spine protocol, on page 370
- show faults spine vrf, on page 371
- show faults tenant, on page 372
- show faults tenant application, on page 373
- show faults tenant application epg, on page 374
- show faults tenant application esg, on page 375
- show faults tenant bridge-domain, on page 376
- show faults tenant bridge-domain detail, on page 377
- show faults tenant bridge-domain first-hop-security binding-table, on page 378
- show faults tenant bridge-domain first-hop-security statistics arp, on page 379

- show faults tenant bridge-domain first-hop-security statistics dhcpv4, on page 380
- show faults tenant bridge-domain first-hop-security statistics dhcpv6, on page 381
- show faults tenant bridge-domain first-hop-security statistics neighbor-discovery, on page 382
- show faults tenant dnsservergroup, on page 383
- show faults tenant dnsservergroup server, on page 384
- show faults tenant dnsservergroup server domain, on page 385
- show faults tenant interface bridge-domain, on page 386
- show faults tenant interface bridge-domain detail, on page 387
- show faults tenant interface bridge-domain first-hop-security binding-table, on page 388
- show faults tenant interface bridge-domain first-hop-security statistics arp, on page 389
- show faults tenant interface bridge-domain first-hop-security statistics dhcpv4, on page 390
- show faults tenant interface bridge-domain first-hop-security statistics dhcpv6, on page 391
- show faults tenant interface bridge-domain first-hop-security statistics neighbor-discovery, on page 392
- show faults tenant multicast-route-maps, on page 393
- show faults tenant vrf, on page 394
- show faults tenant vrf acllog l2, on page 395
- show faults tenant vrf acllog l3, on page 396
- show faults tenant vrf detail, on page 398
- show faults tenant vrf external-l3 bgp, on page 399
- show faults tenant vrf external-l3 bgp node, on page 400
- show faults tenant vrf external-l3 eigrp, on page 401
- show faults tenant vrf external-l3 eigrp detail, on page 402
- show faults tenant vrf external-l3 epg, on page 403
- show faults tenant vrf external-l3 epg detail, on page 404
- show faults tenant vrf external-l3 interfaces, on page 405
- show faults tenant vrf external-l3 interfaces detail, on page 406
- show faults tenant vrf external-l3 ospf, on page 407
- show faults tenant vrf external-l3 ospf detail, on page 408
- show faults tenant vrf external-l3 scale, on page 409
- show faults tenant vrf external-l3 scale detail, on page 410
- show faults tenant vrf external-l3 static-route, on page 411
- show faults tenant vrf external-l3 static-route detail, on page 412
- show faults tenant vrf external-l3 static-route node, on page 413
- show faults tenant vrf external-l3 static-route node detail, on page 414
- show faults tenant vrf ipv6multicast, on page 415
- show faults tenant vrf multicast, on page 416
- show faults vmware domain, on page 417
- show faults vmware domain name, on page 418
- show faults vmware domain name epg, on page 419
- show faults vmware domain name esx, on page 420
- show faults vmware domain name port-group, on page 421
- show faults vmware domain name trunk-portgroup, on page 422
- show faults vmware domain name vcenter, on page 423
- show faults vmware domain name vm, on page 424
- show faults vmware domain name vm name, on page 425
- show fips, on page 426

- show fips status, on page 427
- show firmware compat matrix, on page 428
- show firmware repository, on page 429
- show firmware repository detail, on page 430
- show firmware upgrade scheduler-status, on page 431
- show firmware upgrade scheduler-status switch-group, on page 432
- show firmware upgrade status, on page 433
- show firmware upgrade status controller-group, on page 434
- show firmware upgrade status controller-group detail, on page 435
- show firmware upgrade status detail, on page 436
- show firmware upgrade status standby-apic, on page 437
- show firmware upgrade status standby-apic detail, on page 438
- show firmware upgrade status switch-group, on page 439
- show firmware upgrade status switch-group detail, on page 440
- show flow exporter, on page 441
- show flow exporter infra, on page 442
- show flow exporter tenant, on page 443
- show flow monitor, on page 444
- show flow monitor infra, on page 445
- show flow monitor tenant, on page 446
- show flow node-policy, on page 447
- show flow node-policy detail, on page 448
- show flow record, on page 449
- show flow record infra, on page 450
- show flow record tenant, on page 451
- show flow vm-exporter, on page 452
- show health, on page 453
- show health leaf, on page 454
- show health leaf fex, on page 455
- show health leaf fex module, on page 456
- show health leaf interface ethernet, on page 457
- show health leaf interface fc, on page 458
- show health leaf interface fcportchannel, on page 459
- show health leaf interface l3instance, on page 460
- show health leaf interface mgmt, on page 461
- show health leaf interface portchannel, on page 462
- show health leaf interface tunnel, on page 463
- show health leaf interface vethernet, on page 464
- show health leaf inventory chassis, on page 465
- show health leaf inventory fans, on page 466
- show health leaf inventory module, on page 467
- show health leaf inventory module fabricport, on page 468
- show health leaf inventory module leafport, on page 469
- show health leaf inventory powersupply, on page 470
- show health leaf inventory supervisor, on page 471
- show health leaf protocol, on page 472

- show health leaf vpc, on page 473
- show health leaf vrf, on page 474
- show health spine, on page 475
- show health spine interface ethernet, on page 476
- show health spine interface l3instance, on page 477
- show health spine interface mgmt, on page 478
- show health spine interface tunnel, on page 479
- show health spine inventory chassis, on page 480
- show health spine inventory fabric, on page 481
- show health spine inventory fans, on page 482
- show health spine inventory module, on page 483
- show health spine inventory module fabricport, on page 484
- show health spine inventory powersupply, on page 485
- show health spine inventory supervisor, on page 486
- show health spine inventory system, on page 487
- show health spine protocol, on page 488
- show health spine vrf, on page 489
- show health tenant, on page 490
- show health tenant application, on page 491
- show health tenant application epg, on page 492
- show health tenant application esg, on page 493
- show health tenant bridge-domain, on page 494
- show health tenant bridge-domain detail, on page 495
- show health tenant bridge-domain first-hop-security binding-table, on page 496
- show health tenant bridge-domain first-hop-security statistics arp, on page 497
- show health tenant bridge-domain first-hop-security statistics dhcpv4, on page 498
- show health tenant bridge-domain first-hop-security statistics dhcpv6, on page 499
- show health tenant bridge-domain first-hop-security statistics neighbor-discovery, on page 500
- show health tenant dnsservergroup, on page 501
- show health tenant dnsservergroup server, on page 502
- show health tenant dnsservergroup server domain, on page 503
- show health tenant interface bridge-domain, on page 504
- show health tenant interface bridge-domain detail, on page 505
- show health tenant interface bridge-domain first-hop-security binding-table, on page 506
- show health tenant interface bridge-domain first-hop-security statistics arp, on page 507
- show health tenant interface bridge-domain first-hop-security statistics dhcpv4, on page 508
- show health tenant interface bridge-domain first-hop-security statistics dhcpv6, on page 509
- show health tenant interface bridge-domain first-hop-security statistics neighbor-discovery, on page 510
- show health tenant multicast-route-maps, on page 511
- show health tenant vrf, on page 512
- show health tenant vrf acllog l2, on page 513
- show health tenant vrf acllog l3, on page 514
- show health tenant vrf detail, on page 516
- show health tenant vrf external-l3 bgp, on page 517
- show health tenant vrf external-l3 bgp node, on page 518
- show health tenant vrf external-l3 eigrp, on page 519

- show health tenant vrf external-l3 eigrp detail, on page 520
- show health tenant vrf external-l3 epg, on page 521
- show health tenant vrf external-l3 epg detail, on page 522
- show health tenant vrf external-l3 interfaces, on page 523
- show health tenant vrf external-l3 interfaces detail, on page 524
- show health tenant vrf external-l3 ospf, on page 525
- show health tenant vrf external-l3 ospf detail, on page 526
- show health tenant vrf external-l3 scale, on page 527
- show health tenant vrf external-l3 scale detail, on page 528
- show health tenant vrf external-l3 static-route, on page 529
- show health tenant vrf external-l3 static-route detail, on page 530
- show health tenant vrf external-l3 static-route node, on page 531
- show health tenant vrf external-l3 static-route node detail, on page 532
- show health tenant vrf ipv6multicast, on page 533
- show health tenant vrf multicast, on page 534
- show inband-mgmt, on page 535
- show inband-mgmt controller, on page 536
- show inband-mgmt switch, on page 537
- show interface bridge-domain, on page 538
- show interface bridge-domain detail, on page 539
- show interface bridge-domain first-hop-security binding-table, on page 540
- show interface bridge-domain first-hop-security statistics arp, on page 541
- show interface bridge-domain first-hop-security statistics dhcpv4, on page 542
- show interface bridge-domain first-hop-security statistics dhcpv6, on page 543
- show interface bridge-domain first-hop-security statistics neighbor-discovery, on page 544
- show ip interface bridge-domain, on page 545
- show ipv6 interface bridge-domain, on page 546
- show l4l7-cluster, on page 547
- show l4l7-graph, on page 548
- show l4l7-package, on page 549
- show ldap-server, on page 550
- show license all, on page 551
- show license catalog, on page 552
- show license hostname, on page 553
- show license interval, on page 554
- show license status, on page 555
- show license summary, on page 556
- show license tech, on page 557
- show license transport-mode, on page 558
- show license udi, on page 559
- show license usage, on page 560
- show lldp, on page 561
- show locator-led, on page 562
- show locator-led status leaf, on page 563
- show locator-led status spine, on page 564
- show macsec interface, on page 565

- show macsec policy, on page 566
- show microsoft domain, on page 567
- show microsoft domain name, on page 568
- show microsoft domain name hyperv, on page 569
- show microsoft domain name port-group, on page 570
- show microsoft domain name scvmm, on page 571
- show microsoft domain name vm, on page 572
- show microsoft domain name vm name, on page 573
- show microsoft vm, on page 574
- show monitor access, on page 575
- show monitor access filter-group, on page 576
- show monitor access session, on page 577
- show monitor fabric, on page 578
- show monitor fabric filter-group, on page 579
- show monitor fabric session, on page 580
- show monitor summary, on page 581
- show monitor tenant, on page 582
- show monitor virtual, on page 583
- show name-alias tenant, on page 584
- show name-alias tenant acl, on page 585
- show name-alias tenant application, on page 586
- show name-alias tenant application epg, on page 587
- show name-alias tenant bridge-domain, on page 588
- show name-alias tenant contract, on page 589
- show name-alias tenant contract subject, on page 590
- show name-alias tenant l3out, on page 591
- show name-alias tenant vrf, on page 592
- show ntpq, on page 593
- show oob-mgmt, on page 594
- show oob-mgmt controller, on page 595
- show oob-mgmt switch, on page 596
- show pd-recovery status, on page 597
- show policy-map, on page 598
- show policy-map type data-plane, on page 599
- show policy-map type qos, on page 600
- show port-channel leaf, on page 601
- show port-channel map, on page 602
- show port-channel map leaf, on page 603
- show pwd-rules, on page 604
- show quota, on page 605
- show radius-server, on page 606
- show redhat domain, on page 607
- show redhat domain name, on page 608
- show redhat domain name epg, on page 609
- show redhat domain name rhev, on page 610
- show resource, on page 611

- show resource conflict encap-vlan epg, on page 612
- show resource conflict encap-vlan epg node, on page 613
- show role, on page 614
- show rsa-server, on page 615
- show running-config, on page 616
- show sessions, on page 617
- show sessions controller, on page 618
- show sessions controller detail, on page 619
- show sessions leaf, on page 620
- show sessions spine, on page 621
- show snapshot active, on page 622
- show snapshot files, on page 623
- show snapshot jobs, on page 624
- show snmp, on page 625
- show snmp clientgroups, on page 626
- show snmp community, on page 627
- show snmp engineid, on page 628
- show snmp hosts, on page 629
- show snmp summary, on page 630
- show snmp users, on page 631
- show stats, on page 632
- show stats granularity communication controller, on page 633
- show stats granularity leaf, on page 634
- show stats granularity leaf fex, on page 635
- show stats granularity leaf fex module, on page 636
- show stats granularity leaf interface ethernet, on page 637
- show stats granularity leaf interface fc, on page 638
- show stats granularity leaf interface fcportchannel, on page 639
- show stats granularity leaf interface mgmt, on page 640
- show stats granularity leaf interface portchannel, on page 641
- show stats granularity leaf interface vethernet, on page 642
- show stats granularity leaf inventory chassis, on page 643
- show stats granularity leaf inventory fans, on page 644
- show stats granularity leaf inventory powersupply, on page 645
- show stats granularity leaf inventory supervisor, on page 646
- show stats granularity spine, on page 647
- show stats granularity spine interface ethernet, on page 648
- show stats granularity spine interface mgmt, on page 649
- show stats granularity spine inventory chassis, on page 650
- show stats granularity spine inventory fabric, on page 651
- show stats granularity spine inventory fans, on page 652
- show stats granularity spine inventory module, on page 653
- show stats granularity spine inventory powersupply, on page 654
- show stats granularity spine inventory supervisor, on page 655
- show stats granularity spine inventory system, on page 656
- show stats granularity tenant, on page 657

- show stats granularity tenant application, on page 658
- show stats granularity tenant application epg, on page 659
- show stats granularity tenant application esg, on page 660
- show stats granularity tenant dnsservergroup, on page 661
- show stats granularity tenant dnsservergroup server, on page 662
- show stats granularity tenant dnsservergroup server domain, on page 663
- show stats granularity tenant dot1q-tunnel, on page 664
- show stats granularity tenant multicast-route-maps, on page 665
- show stats granularity tenant vrf, on page 666
- show stats granularity tenant vrf acllog l2, on page 667
- show stats granularity tenant vrf acllog l3, on page 668
- show stats granularity tenant vrf detail, on page 670
- show stats granularity tenant vrf external-l3 bgp, on page 671
- show stats granularity tenant vrf external-l3 bgp node, on page 672
- show stats granularity tenant vrf external-l3 eigrp, on page 673
- show stats granularity tenant vrf external-l3 eigrp detail, on page 674
- show stats granularity tenant vrf external-l3 epg, on page 675
- show stats granularity tenant vrf external-l3 epg detail, on page 676
- show stats granularity tenant vrf external-l3 interfaces, on page 677
- show stats granularity tenant vrf external-l3 interfaces detail, on page 678
- show stats granularity tenant vrf external-l3 ospf, on page 679
- show stats granularity tenant vrf external-l3 ospf detail, on page 680
- show stats granularity tenant vrf external-l3 scale, on page 681
- show stats granularity tenant vrf external-l3 scale detail, on page 682
- show stats granularity tenant vrf external-l3 static-route, on page 683
- show stats granularity tenant vrf external-l3 static-route detail, on page 684
- show stats granularity tenant vrf external-l3 static-route node, on page 685
- show stats granularity tenant vrf external-l3 static-route node detail, on page 686
- show stats granularity tenant vrf ipv6multicast, on page 687
- show stats granularity tenant vrf multicast, on page 688
- show switch, on page 689
- show switch detail, on page 690
- show tacacs-server, on page 691
- show techsupport all, on page 692
- show techsupport controllers, on page 693
- show techsupport host, on page 694
- show techsupport switch, on page 695
- show tenant, on page 696
- show tenant access-list, on page 697
- show tenant application, on page 698
- show tenant application endpoints, on page 699
- show tenant application endpoints leaf interface ethernet, on page 700
- show tenant application endpoints leaf interface port-channel, on page 701
- show tenant application endpoints vpc, on page 702
- show tenant application epg, on page 703
- show tenant application epg detail, on page 704

- show tenant application epg endpoints, on page 705
- show tenant application epg endpoints leaf interface ethernet, on page 706
- show tenant application epg endpoints leaf interface port-channel, on page 707
- show tenant application epg endpoints vpc, on page 708
- show tenant application esg, on page 709
- show tenant application esg detail, on page 710
- show tenant application esg endpoints, on page 711
- show tenant bridge-domain, on page 712
- show tenant bridge-domain detail, on page 713
- show tenant bridge-domain first-hop-security binding-table, on page 714
- show tenant bridge-domain first-hop-security statistics arp, on page 715
- show tenant bridge-domain first-hop-security statistics dhcpv4, on page 716
- show tenant bridge-domain first-hop-security statistics dhcpv6, on page 717
- show tenant bridge-domain first-hop-security statistics neighbor-discovery, on page 718
- show tenant contract-type, on page 719
- show tenant contract, on page 720
- show tenant detail, on page 721
- show tenant dnsservergroup, on page 722
- show tenant dnsservergroup server, on page 723
- show tenant dnsservergroup server domain, on page 724
- show tenant dot1q-tunnel, on page 725
- show tenant endpoints, on page 726
- show tenant endpoints leaf interface ethernet, on page 727
- show tenant endpoints leaf interface port-channel, on page 728
- show tenant endpoints vpc, on page 729
- show tenant epg, on page 730
- show tenant epg detail, on page 731
- show tenant esg, on page 732
- show tenant esg detail, on page 733
- show tenant external-l2 epg, on page 734
- show tenant interface bridge-domain, on page 735
- show tenant interface bridge-domain detail, on page 736
- show tenant interface bridge-domain first-hop-security binding-table, on page 737
- show tenant interface bridge-domain first-hop-security statistics arp, on page 738
- show tenant interface bridge-domain first-hop-security statistics dhcpv4, on page 739
- show tenant interface bridge-domain first-hop-security statistics dhcpv6, on page 740
- show tenant interface bridge-domain first-hop-security statistics neighbor-discovery, on page 741
- show tenant ip interface bridge-domain, on page 742
- show tenant ipv6 interface bridge-domain, on page 743
- show tenant multicast-route-maps, on page 744
- show tenant policy-map, on page 745
- show tenant policy-map type data-plane, on page 746
- show tenant policy-map type qos, on page 747
- show tenant vrf, on page 748
- show tenant vrf acllog l2, on page 749
- show tenant vrf acllog l3, on page 750

- show tenant vrf detail, on page 752
- show tenant vrf external-l3 bgp, on page 753
- show tenant vrf external-l3 bgp node, on page 754
- show tenant vrf external-l3 eigrp, on page 755
- show tenant vrf external-l3 eigrp detail, on page 756
- show tenant vrf external-l3 epg, on page 757
- show tenant vrf external-l3 epg detail, on page 758
- show tenant vrf external-l3 interfaces, on page 759
- show tenant vrf external-l3 interfaces detail, on page 760
- show tenant vrf external-l3 ospf, on page 761
- show tenant vrf external-l3 ospf detail, on page 762
- show tenant vrf external-l3 route-map, on page 763
- show tenant vrf external-l3 route-map detail, on page 764
- show tenant vrf external-l3 scale, on page 765
- show tenant vrf external-l3 scale detail, on page 766
- show tenant vrf external-l3 static-route, on page 767
- show tenant vrf external-l3 static-route detail, on page 768
- show tenant vrf external-l3 static-route node, on page 769
- show tenant vrf external-l3 static-route node detail, on page 770
- show tenant vrf ipv6multicast, on page 771
- show tenant vrf multicast, on page 772
- show track-ipsla, on page 773
- show track-objects, on page 774
- show troubleshoot session, on page 775
- show troubleshoot session atomiccounter, on page 776
- show troubleshoot session audit, on page 777
- show troubleshoot session contracts, on page 778
- show troubleshoot session deployments, on page 779
- show troubleshoot session events, on page 780
- show troubleshoot session faults, on page 781
- show troubleshoot session latency, on page 782
- show troubleshoot session monitor, on page 783
- show troubleshoot session reports, on page 784
- show troubleshoot session statistics, on page 785
- show troubleshoot session topology, on page 786
- show troubleshoot session traceroute, on page 787
- show troubleshoot sessions, on page 788
- show upgrade-timeline controller, on page 789
- show upgrade-timeline summary, on page 790
- show upgrade-timeline switch, on page 791
- show upgradeissues controller, on page 792
- show username, on page 793
- show username detail, on page 794
- show versions, on page 795
- show vlan-domain, on page 796
- show vmware domain, on page 797

- show vmware domain name, on page 798
- show vmware domain name epg, on page 799
- show vmware domain name esx, on page 800
- show vmware domain name port-group, on page 801
- show vmware domain name trunk-portgroup, on page 802
- show vmware domain name vcenter, on page 803
- show vmware domain name vm, on page 804
- show vmware domain name vm name, on page 805
- show vmware vm, on page 806
- show vpc, on page 807
- show vpc map leaf, on page 808
- show vrf, on page 809
- show vrf detail, on page 810
- show vsan-domain, on page 811
- sr-upgrade, on page 812
- sr-version, on page 813
- switch-group, on page 814
- switch, on page 815
- syslog, on page 816

schedule

schedule <WORD>

Description: Assign a scheduler

Syntax:

WORD	scheduler name (Max Size 64)

Command Mode: switch-group : Create switch firmware upgrade policy

Command Path:

```
# configure [['terminal', 't']]
(config)# firmware
(config-firmware)# switch-group <WORD>
(config-firmware-switch)# schedule <WORD>
```

scheduler

scheduler pause

Description: Pause maintenance policy scheduler

Syntax:

pause	Pause maintenance policy scheduler

Command Mode: switch-group : Create switch firmware upgrade policy

Command Path:

```
# configure [['terminal', 't']]
(config)# firmware
(config-firmware)# switch-group <WORD>
(config-firmware-switch)# scheduler pause
```

show aaa authentication

show aaa authentication

Description: Show AAA Authentication information

Command Mode: exec : Exec Mode

Command Path:

```
# show aaa authentication
```

show aaa groups

show aaa groups

Description: Show AAA group information

Command Mode: exec : Exec Mode

Command Path:

```
# show aaa groups
```

show aaa sessions

show aaa sessions

Description: Active User Sessions

Command Mode: exec : Exec Mode

Command Path:

```
# show aaa sessions
```

show access-list

show access-list WORD

Description: Show Access-list Information

Syntax:

WORD	Name of the Contract to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show access-list WORD
```

show accounting log

show accounting log

Description: CLI configuration command logs

Command Mode: exec : Exec Mode

Command Path:

```
# show accounting log
```

NOTE:

This command displays only those changes made using the command line interface (CLI). It does not display changes made using the GUI or the API. To view all changes made in the Management Information Tree, use the **show audit detail** command.

show acllog deny l2 flow

show acllog deny l2 flow

Description: l3 flow information

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l2 flow
```

show acllog deny l2 flow tenant vrf

show acllog deny l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcIntf <srcintf>] <WORD>

Description: tenant vrf information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) source Interface
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcIntf <srcintf>] <WORD>
```

show acllog deny l2 flow tenant vrf detail

show acllog deny l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcIntf <srcintf>] <WORD> detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) source Interface
WORD	Name of the VRF to filter on (Max Size 64)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcIntf <srcintf>] <WORD>
detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac
 <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE
 EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show acllog deny l2 pkt

show acllog deny l2 pkt

Description: Pkt command

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l2 pkt
```

show acllog deny l2 pkt tenant vrf

show acllog deny l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>]

Description: Vrf Name

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) Source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>]
[srcintf <srcintf>] [pktlen <NUMBER>]
```

show acllog deny l2 pkt tenant vrf detail

show acllog deny l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: Detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) Source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>]
[srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName
 <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE
 >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show acllog deny l3 flow

show acllog deny l3 flow

Description: l3 flow information

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l3 flow
```

show acllog deny l3 flow tenant vrf

show acllog deny l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf <srcintf>] <WORD>

Description: tenant vrf information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
Protocol	(Optional) Protocol
SrcPort	(Optional) source port
DstPort	(Optional) destination port
srcintf	(Optional) source interface
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D
 or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf
<srcintf>] <WORD>
```

show acllog deny l3 flow tenant vrf detail

show acllog deny l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf <srcintf>] <WORD> detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
Protocol	(Optional) Protocol
SrcPort	(Optional) source port
DstPort	(Optional) destination port
srcintf	(Optional) source interface
WORD	Name of the VRF to filter on (Max Size 64)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D
 or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf
<srcintf>] <WORD> detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName
 <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E
```

```
EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show acllog deny l3 pkt

show acllog deny l3 pkt

Description: Pkt command

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l3 pkt
```

show acllog deny l3 pkt tenant vrf

show acllog deny l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>] [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>]

Description: Vrf Name

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
protocol	(Optional) protocol
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
<0-65535>	(Optional) Source port. Number range from=0 to=65535
<0-65535>	(Optional) Destination port. Number range from=0 to=65535
srcintf	(Optional) source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>]
 [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport
<NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>]
```

show acllog deny l3 pkt tenant vrf detail

show acllog deny l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>] [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: Detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
protocol	(Optional) protocol
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
<0-65535>	(Optional) Source port. Number range from=0 to=65535
<0-65535>	(Optional) Destination port. Number range from=0 to=65535
srcintf	(Optional) source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog deny l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>]
 [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport
<NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>]
 [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE
 EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show acllog permit l2 flow tenant vrf

show acllog permit l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcintf <srcintf>] <WORD>

Description: tenant vrf information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) source interface
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcintf <srcintf>] <WORD>
```

show acllog permit l2 flow tenant vrf detail

show acllog permit l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcintf <srcintf>] <WORD> detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) source interface
WORD	Name of the VRF to filter on (Max Size 64)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l2 flow tenant <WORD> vrf [vlan <NUMBER>] [srcintf <srcintf>] <WORD>
detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac
 <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE
 EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show acllog permit l2 pkt tenant vrf

show acllog permit l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>]

Description: Vrf Name

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>]
[srcintf <srcintf>] [pktlen <NUMBER>]
```

show acllog permit l2 pkt tenant vrf detail

show acllog permit l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: Detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
srcintf	(Optional) source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l2 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [vlan <NUMBER>]
[srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName
 <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE
 >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show acllog permit l3 flow tenant vrf

show acllog permit l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf <srcintf>] <WORD>

Description: tenant vrf information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
Protocol	(Optional) Protocol
SrcPort	(Optional) source port
DstPort	(Optional) destination port
srcintf	(Optional) source interface
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D
 or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf
<srcintf>] <WORD>
```

show acllog permit l3 flow tenant vrf detail

show acllog permit l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf <srcintf>] <WORD> detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
Protocol	(Optional) Protocol
SrcPort	(Optional) source port
DstPort	(Optional) destination port
srcintf	(Optional) source interface
WORD	Name of the VRF to filter on (Max Size 64)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l3 flow tenant <WORD> vrf [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D
 or A:B::C:D>] [protocol <Protocol>] [srcport <SrcPort>] [dstport <DstPort>] [srcintf
<srcintf>] <WORD> detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName
 <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E
```

```
EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show acllog permit l3 pkt tenant vrf

show acllog permit l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>] [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>]

Description: Vrf Name

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
protocol	(Optional) protocol
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
<0-65535>	(Optional) Source port. Number range from=0 to=65535
<0-65535>	(Optional) Destination port. Number range from=0 to=65535
srcintf	(Optional) source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>]
 [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport
<NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>]
```

show acllog permit l3 pkt tenant vrf detail

show acllog permit l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>] [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport <NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>] [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: Detail information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the vrf to filter on (Max Size 64)
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
time-stamp <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Event activity in time interval
protocol	(Optional) protocol
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
A.B.C.D or A:B::C:D	(Optional) IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
<0-65535>	(Optional) Source port. Number range from=0 to=65535
<0-65535>	(Optional) Destination port. Number range from=0 to=65535
srcintf	(Optional) source Interface
<1-65535>	(Optional) packet length. Number range from=1 to=65535
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) PC Tag (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
WORD	(Optional) Epg Name (Max Size None)
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show acllog permit l3 pkt tenant <WORD> vrf <WORD> [start-time time-stamp
<YYYY-MM-DDTHR:MIN:SEC>] [end-time time-stamp <YYYY-MM-DDTHR:MIN:SEC>] [protocol <protocol>]
 [srcip <A.B.C.D or A:B::C:D>] [dstip <A.B.C.D or A:B::C:D>] [srcport <NUMBER>] [dstport
<NUMBER>] [srcintf <srcintf>] [pktlen <NUMBER>] detail [srcpctag <WORD>] [dstpctag <WORD>]
 [srcEpgName <WORD>] [dstEpgName <WORD>] [srcmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE
 EEEE.EEEE.EEEE >] [dstmac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]
```

show analytics

show analytics

Description: Show analytics cluster configuration

Command Mode: exec : Exec Mode

Command Path:

```
# show analytics
```

show application

show application WORD

Description: Show Application Profiles Information

Syntax:

WORD	Name of the application we eventually want to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show application WORD
```

show audits

show audits [id <log-id>] [action action<action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] <scope>

Description: Show audit-log information

Syntax:

<*log-id*>	(Optional) Log ID
action<*action-type*>	(Optional) Object action indicator
<*user-name*>	(Optional) Name of user
<*num-minutes*>	(Optional) Logs created in time interval. Number range from 1 to 59
<*num-hours*>	(Optional) Logs created in time interval. Number range from 1 to 23
<*num-days*>	(Optional) Logs created in time interval. Number range from 1 to 999
<*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Logs created in time interval
end-time <*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Logs created in time interval
detail	(Optional) Detailed audit-log information. Displays what was modified and displays the old and new settings.
<*scope*>	command scope

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action action<action-type>] [user <user-name>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] <scope>
```

show audits tenant

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD

Description: Show Tenants Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
```

show audits tenant application

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD

Description: Show Application Profiles Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD
```

show audits tenant application epg

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD epg WORD
```

show audits tenant application esg

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD esg WORD

Description: Show Show Endpoint Security Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD esg WORD
```

show audits tenant bridge-domain

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD
```

show audits tenant bridge-domain detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD detail
```

show audits tenant bridge-domain first-hop-security binding-table

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
binding-table
```

show audits tenant bridge-domain first-hop-security statistics arp

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
statistics arp
```

show audits tenant bridge-domain first-hop-security statistics dhcpv4

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
statistics dhcpv4
```

show audits tenant bridge-domain first-hop-security statistics dhcpv6

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
statistics dhcpv6
```

show audits tenant bridge-domain first-hop-security statistics neighbor-discovery

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
statistics neighbor-discovery
```

show audits tenant dnsservergroup

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD

Description: Show Dns Server Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD
```

show audits tenant dnsservergroup server

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD

Description: Show Dns Server Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD
```

show audits tenant dnsservergroup server domain

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD domain WORD

Description: Show Dns Domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)
WORD	Domain we eventually want to filter on (Max Size 512)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD domain WORD
```

show audits tenant interface bridge-domain

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD
```

show audits tenant interface bridge-domain detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD detail
```

show audits tenant interface bridge-domain first-hop-security binding-table

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security
 binding-table
```

show audits tenant interface bridge-domain first-hop-security statistics arp

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security
 statistics arp
```

show audits tenant interface bridge-domain first-hop-security statistics dhcpv4

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security
 statistics dhcpv4
```

show audits tenant interface bridge-domain first-hop-security statistics dhcpv6

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security
 statistics dhcpv6
```

show audits tenant interface bridge-domain first-hop-security statistics neighbor-discovery

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security
 statistics neighbor-discovery
```

show audits tenant multicast-route-maps

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD multicast-route-maps

Description: Show multicast route-maps per Tenant

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD multicast-route-maps
```

show audits tenant vrf

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD

Description: Show VRF Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
```

show audits tenant vrf acllog l2

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>

Description: L2 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flowi stats
vlan	vlan info
<*vlan*>	<vlan>. Number range from=0 to=9223372036854775807
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan
<NUMBER> srcintf <srcintf>
```

show audits tenant vrf acllog l3

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport <dstport> srcintf <srcintf>

Description: L3 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flow stats
srcpctag	source pc tag
<*srcpctag*>	<srcpctag>
dstpctag	destination pc tag
<*dstpctag*>	<dstpctag>
srcepgname	source epg name
<*srcepgname*>	<srcepgname>
dstepgname	destination epg name
<*dstepgname*>	<dstepgname>
srcip	source ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
dstip	destination ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
proto	protocol
<*proto*>	<proto>
srcport	source port
<*srcport*>	<srcport>
dstport	destination port

<*dstport*>	<dstport>
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag
 <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip
<A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport
<dstport> srcintf <srcintf>
```

show audits tenant vrf detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD detail

Description: Show detailed view of VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD detail
```

show audits tenant vrf external-l3 bgp

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp

Description: Show command for BGP peers

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp
```

show audits tenant vrf external-l3 bgp node

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp node <101-4000>

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<101-4000>	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp node <101-4000>
```

show audits tenant vrf external-l3 eigrp

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp

Description: Show external l3 EIGRP

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp
```

show audits tenant vrf external-l3 eigrp detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp detail
```

show audits tenant vrf external-l3 epg

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName>

Description: Show command for external-l3 epgs

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName>
```

show audits tenant vrf external-l3 epg detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName> detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName> detail
```

show audits tenant vrf external-l3 interfaces

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces

Description: Show tenant <tenant> vrf <vrf> external l3 interfaces

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces
```

show audits tenant vrf external-l3 interfaces detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces detail
```

show audits tenant vrf external-l3 ospf

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf

Description: Show command for IPv4 and IPv6 external l3 OSPF configuration

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf
```

show audits tenant vrf external-l3 ospf detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf detail
```

show audits tenant vrf external-l3 scale

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale

Description: scale command

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale
```

show audits tenant vrf external-l3 scale detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale detail
```

show audits tenant vrf external-l3 static-route

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route

Description: Show command for external-l3 static routes

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route
```

show audits tenant vrf external-l3 static-route detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route detail
```

show audits tenant vrf external-l3 static-route node

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node
```

show audits tenant vrf external-l3 static-route node detail

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node detail
```

show audits tenant vrf ipv6multicast

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD ipv6multicast

Description: Show ipv6 multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD ipv6multicast
```

show audits tenant vrf multicast

show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD multicast

Description: Show multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show audits [id <log-id>] [action <action-type>] [user <user-name>] [last-minutes <NUMBER>]
 [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time
 <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD multicast
```

show bridge-domain

show bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show bridge-domain WORD
```

show bridge-domain detail

show bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show bridge-domain WORD detail
```

show bridge-domain first-hop-security binding-table

show bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show bridge-domain WORD first-hop-security binding-table
```

show bridge-domain first-hop-security statistics arp

show bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show bridge-domain WORD first-hop-security statistics arp
```

show bridge-domain first-hop-security statistics dhcpv4

show bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show bridge-domain WORD first-hop-security statistics dhcpv4
```

show bridge-domain first-hop-security statistics dhcpv6

show bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show bridge-domain WORD first-hop-security statistics dhcpv6
```

show bridge-domain first-hop-security statistics neighbor-discovery

show bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show bridge-domain WORD first-hop-security statistics neighbor-discovery
```

show callhome

show callhome common

Description: Show command for callhome

Syntax:

common	Common

Command Mode: exec : Exec Mode

Command Path:

```
# show callhome common
```

show callhome common destination-profile

show callhome common destination-profile

Description: Show command for callhome destination-profile

Syntax:

common	Common

Command Mode: exec : Exec Mode

Command Path:

```
# show callhome common destination-profile
```

show callhome common query-profile

show callhome common query-profile

Description: Show command for callhome destination-profile

Syntax:

common	Common

Command Mode: exec : Exec Mode

Command Path:

```
# show callhome common query-profile
```

show callhome common transport-email

show callhome common transport-email

Description: Show command for callhome transport-email

Syntax:

common	Common

Command Mode: exec : Exec Mode

Command Path:

```
# show callhome common transport-email
```

show catalog

show catalog

Description: Show catalog information

Command Mode: exec : Exec Mode

Command Path:

```
# show catalog
```

show cli command

show cli command <WORD> [mode <mode-name>]

Description: Show Commands Syntax

Syntax:

WORD	Command Name pattern between single quotes
<*mode-name*>	(Optional) Mode name pattern between single quotes
details	(Optional) Show Command Details

Command Mode: exec : Exec Mode

Command Path:

```
# show cli command <WORD> [mode <mode-name>]
```

show cli list

show cli list [mode <mode-name>]

Description: Show all cli-related commands

Syntax:

<*mode-name*>	(Optional) Mode name pattern between single quotes
details	(Optional) Show Command Details

Command Mode: exec : Exec Mode

Command Path:

```
# show cli list [mode <mode-name>]
```

show cli manpage

show cli manpage <WORD> [mode <mode-name>]

Description: Show Commands ManPage

Syntax:

WORD	Command Name pattern between single quotes
<*mode-name*>	(Optional) Mode name pattern between single quotes
details	(Optional) Show Command Details

Command Mode: exec : Exec Mode

Command Path:

```
# show cli manpage <WORD> [mode <mode-name>]
```

show cli path

show cli path <WORD> [mode <mode-name>]

Description: Show Commands Path

Syntax:

WORD	Command Name pattern between single quotes
<*mode-name*>	(Optional) Mode name pattern between single quotes
details	(Optional) Show Command Details

Command Mode: exec : Exec Mode

Command Path:

```
# show cli path <WORD> [mode <mode-name>]
```

show clock

show clock

Description: Show clock information

Command Mode: exec : Exec Mode

Command Path:

```
# show clock
```

show cloudave

show cloudave

Description: Show cloud AVE information

Command Mode: exec : Exec Mode

Command Path:

```
# show cloudave
```

show cloudsec summary

show cloudsec summary

Description: Show brief summary of cloudsec policies

Command Mode: exec : Exec Mode

Command Path:

```
# show cloudsec summary
```

show communication ciphers

show communication ciphers

Description: HTTPS service cipher suite listings

Command Mode: exec : Exec Mode

Command Path:

```
# show communication ciphers
```

show communication controller

show communication controller node-id

Description: Show command for nginx web-requests

Syntax:

node-id	node-id

Command Mode: exec : Exec Mode

Command Path:

```
# show communication controller node-id
```

show communication http

show communication http

Description: HTTP service settings

Command Mode: exec : Exec Mode

Command Path:

```
# show communication http
```

show communication https

show communication https

Description: HTTPS service settings

Command Mode: exec : Exec Mode

Command Path:

```
# show communication https
```

show communication performance

show communication performance

Description: Show command for performance data

Command Mode: exec : Exec Mode

Command Path:

```
# show communication performance
```

show communication performance config

show communication performance config

Description: Show command for performance configuration

Command Mode: exec : Exec Mode

Command Path:

```
# show communication performance config
```

show communication performance results

show communication performance results

Description: Show command for performance results

Command Mode: exec : Exec Mode

Command Path:

```
# show communication performance results
```

show communication shellinabox

show communication shellinabox

Description: Shellinabox service settings

Command Mode: exec : Exec Mode

Command Path:

```
# show communication shellinabox
```

show communication ssh-service

show communication ssh-service

Description: SSH service settings

Command Mode: exec : Exec Mode

Command Path:

```
# show communication ssh-service
```

show communication telnet

show communication telnet

Description: Telnet service settings

Command Mode: exec : Exec Mode

Command Path:

```
# show communication telnet
```

show communication web-requests

show communication web-requests

Description: Status of last web requests

Command Mode: exec : Exec Mode

Command Path:

```
# show communication web-requests
```

show contract-type

show contract-type WORD

Description: Show Contracts Information Based on Type

Syntax:

WORD	whitelist (permit) or blacklist(deny) or oob-mgmt type of contract

Command Mode: exec : Exec Mode

Command Path:

```
# show contract-type WORD
```

show contract

show contract WORD

Description: Show Contracts Information

Syntax:

WORD	Name of the Contract to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show contract WORD
```

show controller

show controller

Description: Show controller information

Command Mode: exec : Exec Mode

Command Path:

```
# show controller
```

show controller detail

show controller detail [id <node-id>]

Description: Detailed controller information

Syntax:

node-id	(Optional) Optional Serial number

Command Mode: exec : Exec Mode

Command Path:

```
# show controller detail [id <node-id>]
```

show cores

show cores

Description: Show all core dumps

Command Mode: exec : Exec Mode

Command Path:

```
# show cores
```

show cores status

show cores status

Description: Show exported core status

Command Mode: exec : Exec Mode

Command Path:

```
# show cores status
```

show debug counter

show debug <node-name> <process> counter <counterTopics>

Description: Show Counter information

Syntax:

<*node-name*>	Node name
<*process*>	Process name
<*counterTopics*>	Counter Topics

Command Mode: exec : Exec Mode

Command Path:

```
# show debug <node-name> <process> counter <counterTopics>
```

show debug log

show debug <node-name> <process> log

Description: Show log level information

Syntax:

<*node-name*>	Node name
<*process*>	Process name

Command Mode: exec : Exec Mode

Command Path:

```
# show debug <node-name> <process> log
```

show deployment endpoint node

show deployment endpoint node <WORD>

Description: Node id

Syntax:

WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807

Command Mode: exec : Exec Mode

Command Path:

```
# show deployment endpoint node <WORD>
```

show discoveryissues

show discoveryissues

Description: Show fabric discovery issues

Command Mode: exec : Exec Mode

Command Path:

```
# show discoveryissues
```

show discoveryissues node

show discoveryissues node <NUMBER>

Description: Enter node Id

Syntax:

<*node-id*>	Enter node id. Number range from=0 to=9223372036854775807

Command Mode: exec : Exec Mode

Command Path:

```
# show discoveryissues node <NUMBER>
```

show dns-address

show dns-address

Description: Show dns address information

Command Mode: exec : Exec Mode

Command Path:

```
# show dns-address
```

show dns-domain

show dns-domain

Description: Show dns domain information

Command Mode: exec : Exec Mode

Command Path:

```
# show dns-domain
```

show dot1q-tunnel

show dot1q-tunnel WORD

Description: Show Dot1q-tunnel Information

Syntax:

WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show dot1q-tunnel WORD
```

show dwdm interface

show dwdm interface switch <101-4000>

Description: interface

Syntax:

switch	switch
<101-4000>	switch ID

Command Mode: exec : Exec Mode

Command Path:

```
# show dwdm interface switch <101-4000>
```

show endpoints

show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]

Description: Show IP endpoints

Syntax:

type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx

Command Mode: exec : Exec Mode

Command Path:

```
# show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE
 >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]
```

show endpoints leaf interface ethernet

show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface ethernet ethernet [<fex>/]<slot>/<port>

Description: Show IP endpoints on an interface ethernet

Syntax:

type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
ethernet [<fex>/]<slot>/<port>	Ethernet Range

Command Mode: exec : Exec Mode

Command Path:

```
# show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE
 >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface ethernet ethernet
 [<fex>/]<slot>/<port>
```

show endpoints leaf interface port-channel

show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface port-channel <WORD> [fex <NUMBER>]

Description: Show IP endpoints on an interface port-channel

Syntax:

type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Port Channel Name (Max Size 64)
<101-199>	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE
 >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface port-channel
<WORD> [fex <NUMBER>]
```

show endpoints vpc

show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc context <WORD> <WORD> interface vpc <WORD> [fex <fex>]

Description: Show IP endpoints on vpc

Syntax:

type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
context	VPC Context
WORD	First VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Second VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
interface	VPC Interface name
vpc	VPC Interface name
WORD	VPC Name (Max Size 64)
fex	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE
 >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc context <WORD> <WORD> interface
vpc <WORD> [fex <fex>]
```

show epg

show epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show epg WORD
```

show epg detail

show epg WORD detail

Description: Show detailed view of Application EPg

Syntax:

WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show epg WORD detail
```

show esg

show esg WORD

Description: Show Endpoint Security Group Information

Syntax:

WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show esg WORD
```

show esg detail

show esg WORD detail

Description: Show detailed view of Endpoint Security Group

Syntax:

WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show esg WORD detail
```

show events

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] <scope>

Description: Show event information

Syntax:

<*event-code*>	(Optional) Event code
<*event-ID*>	(Optional) Event ID
<*event-value*>	(Optional) Cause
last-minutes <*num-minutes*>	(Optional) Event activity in time interval. Number range from=1 to=59
last-hours <*num-hours*>	(Optional) Event activity in time interval. Number range from=1 to=23
last-days <*num-days*>	(Optional) Event activity in time interval. Number range from=1 to=999
start-time <*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Event activity in time interval
end-time <*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Event activity in time interval
detail	(Optional) Detailed event information
<*scope*>	command scope

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] <scope>
```

show events controller

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller

Description: Show controller information

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller
```

show events controller detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller detail [id <node-id>]

Description: Detailed controller information

Syntax:

node-id	(Optional) Optional Serial number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller detail [id <node-id>]
```

show events leaf

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId>

Description: Show command for leaf

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId>
```

show events leaf fex

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex <fexNum>

Description: Show extended chassis information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex <fexNum>
```

show events leaf fex module

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex <fexNum> module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex <fexNum> module <lcSlot>
```

show events leaf interface ethernet

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface ethernet <phyInt>
```

show events leaf interface fc

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface fc <phyInt>

Description: Fibre Channel Protocol

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface fc <phyInt>
```

show events leaf interface fcportchannel

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface fcportchannel <portChan>

Description: FC Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface fcportchannel <portChan>
```

show events leaf interface l3instance

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface l3instance <l3Inst>

Description: L3 instance

Syntax:

<*leafId*>	Leaf id
<*l3Inst*>	<L3 instance number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface l3instance <l3Inst>
```

show events leaf interface mgmt

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface mgmt <mgmtPort>
```

show events leaf interface portchannel

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface portchannel <portChan>

Description: Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface portchannel <portChan>
```

show events leaf interface tunnel

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface tunnel <tunnelPort>

Description: Tunnel Interface

Syntax:

<*leafId*>	Leaf id
<*tunnelPort*>	<Tunnel interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface tunnel <tunnelPort>
```

show events leaf interface vethernet

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface vethernet <phyInt>

Description: vethernet ID

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface vethernet <phyInt>
```

show events leaf inventory chassis

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory chassis
```

show events leaf inventory fans

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory fans <ftSlot>
```

show events leaf inventory module

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot>
```

show events leaf inventory module fabricport

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot> fabricport <fabPort>

Description: Show information for fabric port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*fabPort*>	pls enter the fabric port number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot> fabricport
 <fabPort>
```

show events leaf inventory module leafport

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot> leafport <leafPort>

Description: Show information for leaf port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*leafPort*>	pls enter the leaf port number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot> leafport
 <leafPort>
```

show events leaf inventory powersupply

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory powersupply <psuSlot>
```

show events leaf inventory supervisor

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory supervisor <supMod>
```

show events leaf protocol

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> protocol <protName>

Description: Show command for protocol

Syntax:

<*leafId*>	Leaf id
<*protName*>	Protocol name

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> protocol <protName>
```

show events leaf vpc

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vpc <vpcPort>

Description: Virtual port channel information

Syntax:

<*leafId*>	Leaf id
<*vpcPort*>	pls enter virtual port channel number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vpc <vpcPort>
```

show events leaf vrf

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vrf <vrfPort>

Description: Vrf information

Syntax:

<*leafId*>	Leaf id
<*vrfPort*>	pls enter vrf name

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vrf <vrfPort>
```

show events spine

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId>

Description: Show command for spine

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId>
```

show events spine interface ethernet

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface ethernet <phyInt>
```

show events spine interface l3instance

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface l3instance <l3Inst>

Description: L3 instance

Syntax:

<*leafId*>	Leaf id
<*l3Inst*>	<L3 instance number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface l3instance <l3Inst>
```

show events spine interface mgmt

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface mgmt <mgmtPort>
```

show events spine interface tunnel

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface tunnel <tunnelPort>

Description: Tunnel Interface

Syntax:

<*leafId*>	Leaf id
<*tunnelPort*>	<Tunnel interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface tunnel <tunnelPort>
```

show events spine inventory chassis

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory chassis
```

show events spine inventory fabric

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory fabric <fcMod>

Description: Show information for fabric module

Syntax:

<*leafId*>	Leaf id
<*fcMod*>	pls enter the fabric module number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory fabric <fcMod>
```

show events spine inventory fans

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory fans <ftSlot>
```

show events spine inventory module

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory module <lcSlot>
```

show events spine inventory module fabricport

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory module <lcSlot> fabricport <fabPort>

Description: Show information for fabric port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*fabPort*>	pls enter the fabric port number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory module <lcSlot>
fabricport <fabPort>
```

show events spine inventory powersupply

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory powersupply <psuSlot>
```

show events spine inventory supervisor

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory supervisor <supMod>
```

show events spine inventory system

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory system <sysMod>

Description: Show information for system module

Syntax:

<*leafId*>	Leaf id
<*sysMod*>	pls enter the system module number

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory system <sysMod>
```

show events spine protocol

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> protocol <protName>

Description: Show command for protocol

Syntax:

<*leafId*>	Leaf id
<*protName*>	Protocol name

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> protocol <protName>
```

show events spine vrf

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> vrf <vrfPort>

Description: Vrf information

Syntax:

<*leafId*>	Leaf id
<*vrfPort*>	pls enter vrf name

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> vrf <vrfPort>
```

show events tenant

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD

Description: Show Tenants Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
```

show events tenant application

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD

Description: Show Application Profiles Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD
```

show events tenant application epg

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD epg WORD
```

show events tenant application esg

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD esg WORD

Description: Show Show Endpoint Security Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD esg WORD
```

show events tenant bridge-domain

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD
```

show events tenant bridge-domain detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD detail
```

show events tenant bridge-domain first-hop-security binding-table

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
 binding-table
```

show events tenant bridge-domain first-hop-security statistics arp

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
 statistics arp
```

show events tenant bridge-domain first-hop-security statistics dhcpv4

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
 statistics dhcpv4
```

show events tenant bridge-domain first-hop-security statistics dhcpv6

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
 statistics dhcpv6
```

show events tenant bridge-domain first-hop-security statistics neighbor-discovery

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security
 statistics neighbor-discovery
```

show events tenant dnsservergroup

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD

Description: Show Dns Server Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD
```

show events tenant dnsservergroup server

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD

Description: Show Dns Server Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD
```

show events tenant dnsservergroup server domain

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD domain WORD

Description: Show Dns Domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)
WORD	Domain we eventually want to filter on (Max Size 512)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD
domain WORD
```

show events tenant endpoints

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]

Description: Show IP endpoints

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E
 EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>]
```

show events tenant endpoints leaf interface ethernet

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface ethernet ethernet [<fex>/]<slot>/<port>

Description: Show IP endpoints on an interface ethernet

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
ethernet [<fex>/]<slot>/<port>	Ethernet Range

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E
 EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>] leaf <WORD> interface ethernet ethernet [<fex>/]<slot>/<port>
```

show events tenant endpoints leaf interface port-channel

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface port-channel <WORD> [fex <NUMBER>]

Description: Show IP endpoints on an interface port-channel

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Port Channel Name (Max Size 64)
<101-199>	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E
 EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>] leaf <WORD> interface port-channel <WORD> [fex <NUMBER>]
```

show events tenant endpoints vpc

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc context <WORD> <WORD> interface vpc <WORD> [fex <fex>]

Description: Show IP endpoints on vpc

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
context	VPC Context
WORD	First VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Second VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
interface	VPC Interface name
vpc	VPC Interface name
WORD	VPC Name (Max Size 64)
fex	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD endpoints [type <type>] [mac <E.E.E
 EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>] vpc context <WORD> <WORD> interface vpc <WORD> [fex <fex>]
```

show events tenant interface bridge-domain

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD
```

show events tenant interface bridge-domain detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD detail
```

show events tenant interface bridge-domain first-hop-security binding-table

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD
first-hop-security binding-table
```

show events tenant interface bridge-domain first-hop-security statistics arp

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD
first-hop-security statistics arp
```

show events tenant interface bridge-domain first-hop-security statistics dhcpv4

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD
first-hop-security statistics dhcpv4
```

show events tenant interface bridge-domain first-hop-security statistics dhcpv6

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD
first-hop-security statistics dhcpv6
```

show events tenant interface bridge-domain first-hop-security statistics neighbor-discovery

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD
first-hop-security statistics neighbor-discovery
```

show events tenant multicast-route-maps

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD multicast-route-maps

Description: Show multicast route-maps per Tenant

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD multicast-route-maps
```

show events tenant vrf

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD

Description: Show VRF Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
```

show events tenant vrf acllog l2

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>

Description: L2 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flowi stats
vlan	vlan info
<*vlan*>	<vlan>. Number range from=0 to=9223372036854775807
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l2
flow vlan <NUMBER> srcintf <srcintf>
```

show events tenant vrf acllog l3

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport <dstport> srcintf <srcintf>

Description: L3 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flow stats
srcpctag	source pc tag
<*srcpctag*>	<srcpctag>
dstpctag	destination pc tag
<*dstpctag*>	<dstpctag>
srcepgname	source epg name
<*srcepgname*>	<srcepgname>
dstepgname	destination epg name
<*dstepgname*>	<dstepgname>
srcip	source ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
dstip	destination ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
proto	protocol
<*proto*>	<proto>
srcport	source port
<*srcport*>	<srcport>
dstport	destination port

<*dstport*>	<dstport>
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l3
flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname>
 srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport>
dstport <dstport> srcintf <srcintf>
```

show events tenant vrf detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD detail

Description: Show detailed view of VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD detail
```

show events tenant vrf external-l3 bgp

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp

Description: Show command for BGP peers

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp
```

show events tenant vrf external-l3 bgp node

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp node <101-4000>

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<101-4000>	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp node
<101-4000>
```

show events tenant vrf external-l3 eigrp

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp

Description: Show external l3 EIGRP

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp
```

show events tenant vrf external-l3 eigrp detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp detail
```

show events tenant vrf external-l3 epg

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName>

Description: Show command for external-l3 epgs

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName>
```

show events tenant vrf external-l3 epg detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName> detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName>
 detail
```

show events tenant vrf external-l3 interfaces

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces

Description: Show tenant <tenant> vrf <vrf> external l3 interfaces

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces
```

show events tenant vrf external-l3 interfaces detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces
detail
```

show events tenant vrf external-l3 ospf

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf

Description: Show command for IPv4 and IPv6 external l3 OSPF configuration

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf
```

show events tenant vrf external-l3 ospf detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf detail
```

show events tenant vrf external-l3 route-map

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 route-map [name <l3out name>]

Description: Show command for external-l3 route-map

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<l3out name>	(Optional) Name of the route-map to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 route-map [name
 <l3out name>]
```

show events tenant vrf external-l3 route-map detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 route-map [name <l3out name>] detail

Description: Show external-l3 route-map in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<l3out name>	(Optional) Name of the route-map to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 route-map [name
 <l3out name>] detail
```

show events tenant vrf external-l3 scale

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale

Description: scale command

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale
```

show events tenant vrf external-l3 scale detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale detail
```

show events tenant vrf external-l3 static-route

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route

Description: Show command for external-l3 static routes

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route
```

show events tenant vrf external-l3 static-route detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route
detail
```

show events tenant vrf external-l3 static-route node

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route
node
```

show events tenant vrf external-l3 static-route node detail

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route
node detail
```

show events tenant vrf ipv6multicast

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD ipv6multicast

Description: Show ipv6 multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD ipv6multicast
```

show events tenant vrf multicast

show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD multicast

Description: Show multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show events [code <event-code>] [id <event-ID>] [cause <event-value>] [last-minutes
<NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
[end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD multicast
```

show external-l2 epg

show external-l2 epg

Description: Show command for external-l2 epgs

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l2 epg
```

show external-l2 epg name

show external-l2 epg name WORD

Description: EPG name to filter on

Syntax:

WORD	Name of the EPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l2 epg name WORD
```

show external-l2 epg tenant

show external-l2 epg tenant WORD

Description: tenant to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l2 epg tenant WORD
```

show external-l3 bgp

show external-l3 bgp

Description: Show command for BGP peers

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 bgp
```

show external-l3 bgp tenant

show external-l3 bgp tenant <WORD>

Description: tenant to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 bgp tenant <WORD>
```

show external-l3 bgp tenant vrf

show external-l3 bgp tenant <WORD> vrf WORD

Description: vrf to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 bgp tenant <WORD> vrf WORD
```

show external-l3 bgp tenant vrf node

show external-l3 bgp tenant <WORD> vrf WORD node <101-4000>

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<101-4000>	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 bgp tenant <WORD> vrf WORD node <101-4000>
```

show external-l3 eigrp

show external-l3 eigrp

Description: Show command for external-l3 eigrp

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp
```

show external-l3 eigrp detail

show external-l3 eigrp detail

Description: Show interanl details

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp detail
```

show external-l3 eigrp node

show external-l3 eigrp node <101-4000>

Description: Node(s) to filter on

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp node <101-4000>
```

show external-l3 eigrp node detail

show external-l3 eigrp node <101-4000> detail

Description: Show interanl details

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp node <101-4000> detail
```

show external-l3 eigrp tenant

show external-l3 eigrp tenant <WORD>

Description: Tenant(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp tenant <WORD>
```

show external-l3 eigrp tenant detail

show external-l3 eigrp tenant <WORD> detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp tenant <WORD> detail
```

show external-l3 eigrp tenant vrf

show external-l3 eigrp tenant <WORD> vrf WORD

Description: Vrf(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp tenant <WORD> vrf WORD
```

show external-l3 eigrp tenant vrf detail

show external-l3 eigrp tenant <WORD> vrf WORD detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp tenant <WORD> vrf WORD detail
```

show external-l3 eigrp tenant vrf node

show external-l3 eigrp tenant <WORD> vrf WORD node <101-4000>

Description: Node(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp tenant <WORD> vrf WORD node <101-4000>
```

show external-l3 eigrp tenant vrf node detail

show external-l3 eigrp tenant <WORD> vrf WORD node <101-4000> detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 eigrp tenant <WORD> vrf WORD node <101-4000> detail
```

show external-l3 epg

show external-l3 epg

Description: Show command for external-l3 epgs

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg
```

show external-l3 epg detail

show external-l3 epg detail

Description: external-l3 epg in detail with operational status

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg detail
```

show external-l3 epg name

show external-l3 epg name <epgName>

Description: EPG name to filter on

Syntax:

<*epgName*>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg name <epgName>
```

show external-l3 epg name detail

show external-l3 epg name <epgName> detail

Description: external-l3 epg in detail with operational status

Syntax:

<*epgName*>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg name <epgName> detail
```

show external-l3 epg tenant

show external-l3 epg tenant <WORD>

Description: tenant to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg tenant <WORD>
```

show external-l3 epg tenant detail

show external-l3 epg tenant <WORD> detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg tenant <WORD> detail
```

show external-l3 epg tenant vrf

show external-l3 epg tenant <WORD> vrf WORD

Description: vrf to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg tenant <WORD> vrf WORD
```

show external-l3 epg tenant vrf detail

show external-l3 epg tenant <WORD> vrf WORD detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 epg tenant <WORD> vrf WORD detail
```

show external-l3 interfaces

show external-l3 interfaces

Description: Show command for external-l3 interfaces

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces
```

show external-l3 interfaces detail

show external-l3 interfaces detail

Description: Show interfaces details

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces detail
```

show external-l3 interfaces node

show external-l3 interfaces node <101-4000>

Description: Node(s) to filter on

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces node <101-4000>
```

show external-l3 interfaces node detail

show external-l3 interfaces node <101-4000> detail

Description: Show interfaces details

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces node <101-4000> detail
```

show external-l3 interfaces tenant

show external-l3 interfaces tenant <WORD>

Description: Tenant(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces tenant <WORD>
```

show external-l3 interfaces tenant detail

show external-l3 interfaces tenant <WORD> detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces tenant <WORD> detail
```

show external-l3 interfaces tenant vrf

show external-l3 interfaces tenant <WORD> vrf WORD

Description: Vrf(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces tenant <WORD> vrf WORD
```

show external-l3 interfaces tenant vrf detail

show external-l3 interfaces tenant <WORD> vrf WORD detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces tenant <WORD> vrf WORD detail
```

show external-l3 interfaces tenant vrf node

show external-l3 interfaces tenant <WORD> vrf WORD node <101-4000>

Description: Node(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces tenant <WORD> vrf WORD node <101-4000>
```

show external-l3 interfaces tenant vrf node detail

show external-l3 interfaces tenant <WORD> vrf WORD node <101-4000> detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 interfaces tenant <WORD> vrf WORD node <101-4000> detail
```

show external-l3 ospf

show external-l3 ospf

Description: Show command for external-l3 ospf

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf
```

show external-l3 ospf detail

show external-l3 ospf detail

Description: Show internal details

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf detail
```

show external-l3 ospf node

show external-l3 ospf node <101-4000>

Description: Node(s) to filter on

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf node <101-4000>
```

show external-l3 ospf node detail

show external-l3 ospf node <101-4000> detail

Description: Show internal details

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf node <101-4000> detail
```

show external-l3 ospf tenant

show external-l3 ospf tenant <WORD>

Description: Tenant(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf tenant <WORD>
```

show external-l3 ospf tenant detail

show external-l3 ospf tenant <WORD> detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf tenant <WORD> detail
```

show external-l3 ospf tenant vrf

show external-l3 ospf tenant <WORD> vrf WORD

Description: Vrf(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf tenant <WORD> vrf WORD
```

show external-l3 ospf tenant vrf detail

show external-l3 ospf tenant <WORD> vrf WORD detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf tenant <WORD> vrf WORD detail
```

show external-l3 ospf tenant vrf node

show external-l3 ospf tenant <WORD> vrf WORD node <101-4000>

Description: Node(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf tenant <WORD> vrf WORD node <101-4000>
```

show external-l3 ospf tenant vrf node detail

show external-l3 ospf tenant <WORD> vrf WORD node <101-4000> detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 ospf tenant <WORD> vrf WORD node <101-4000> detail
```

show external-l3 route-map

show external-l3 route-map

Description: Show command for external-l3 route-map

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map
```

show external-l3 route-map detail

show external-l3 route-map detail

Description: Route-map in detail with operational status

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map detail
```

show external-l3 route-map name

show external-l3 route-map name <l3out name>

Description: Route-map name to filter on

Syntax:

<l3out name>	Name of the route-map to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map name <l3out name>
```

show external-l3 route-map name detail

show external-l3 route-map name <l3out name> detail

Description: Route-map in detail with operational status

Syntax:

<l3out name>	Name of the route-map to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map name <l3out name> detail
```

show external-l3 route-map tenant

show external-l3 route-map tenant <WORD>

Description: tenant to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map tenant <WORD>
```

show external-l3 route-map tenant detail

show external-l3 route-map tenant <WORD> detail

Description: Route-map in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map tenant <WORD> detail
```

show external-l3 route-map tenant vrf

show external-l3 route-map tenant <WORD> vrf WORD

Description: vrf to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map tenant <WORD> vrf WORD
```

show external-l3 route-map tenant vrf detail

show external-l3 route-map tenant <WORD> vrf WORD detail

Description: Route-map in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map tenant <WORD> vrf WORD detail
```

show external-l3 route-map tenant vrf node

show external-l3 route-map tenant <WORD> vrf WORD node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map tenant <WORD> vrf WORD node
```

show external-l3 route-map tenant vrf node detail

show external-l3 route-map tenant <WORD> vrf WORD node detail

Description: Route-map in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 route-map tenant <WORD> vrf WORD node detail
```

show external-l3 scale

show external-l3 scale

Description: Show command for external-l3 scale

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale
```

show external-l3 scale detail

show external-l3 scale detail

Description: Show scale details

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale detail
```

show external-l3 scale node

show external-l3 scale node <101-4000>

Description: Node(s) to filter on

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale node <101-4000>
```

show external-l3 scale node detail

show external-l3 scale node <101-4000> detail

Description: Show scale details

Syntax:

<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale node <101-4000> detail
```

show external-l3 scale tenant

show external-l3 scale tenant <WORD>

Description: Tenant(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale tenant <WORD>
```

show external-l3 scale tenant detail

show external-l3 scale tenant <WORD> detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale tenant <WORD> detail
```

show external-l3 scale tenant vrf

show external-l3 scale tenant <WORD> vrf WORD

Description: Vrf(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale tenant <WORD> vrf WORD
```

show external-l3 scale tenant vrf detail

show external-l3 scale tenant <WORD> vrf WORD detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale tenant <WORD> vrf WORD detail
```

show external-l3 scale tenant vrf node

show external-l3 scale tenant <WORD> vrf WORD node <101-4000>

Description: Node(s) to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale tenant <WORD> vrf WORD node <101-4000>
```

show external-l3 scale tenant vrf node detail

show external-l3 scale tenant <WORD> vrf WORD node <101-4000> detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF(s) to filter on (Max Size 64)
<101-4000>	Node Range or Node Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 scale tenant <WORD> vrf WORD node <101-4000> detail
```

show external-l3 static-route

show external-l3 static-route

Description: Show command for external-l3 static routes

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route
```

show external-l3 static-route detail

show external-l3 static-route detail

Description: static-route in detail with operational status

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route detail
```

show external-l3 static-route node

show external-l3 static-route node

Description: node to filter on

Syntax:

arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route node
```

show external-l3 static-route node detail

show external-l3 static-route node detail

Description: static-route in detail with operational status

Syntax:

arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route node detail
```

show external-l3 static-route tenant

show external-l3 static-route tenant <WORD>

Description: tenant to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route tenant <WORD>
```

show external-l3 static-route tenant detail

show external-l3 static-route tenant <WORD> detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route tenant <WORD> detail
```

show external-l3 static-route tenant vrf

show external-l3 static-route tenant <WORD> vrf WORD

Description: vrf to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route tenant <WORD> vrf WORD
```

show external-l3 static-route tenant vrf detail

show external-l3 static-route tenant <WORD> vrf WORD detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route tenant <WORD> vrf WORD detail
```

show external-l3 static-route tenant vrf node

show external-l3 static-route tenant <WORD> vrf WORD node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route tenant <WORD> vrf WORD node
```

show external-l3 static-route tenant vrf node detail

show external-l3 static-route tenant <WORD> vrf WORD node detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show external-l3 static-route tenant <WORD> vrf WORD node detail
```

show fabric-discovery-health

show fabric-discovery-health

Description: Show health of fabric discovery

Command Mode: exec : Exec Mode

Command Path:

```
# show fabric-discovery-health
```

show fabric-recovery checker

show fabric-recovery checker moDn [detail]

Description: To show the recovery checker status

Syntax:

moDn	Optional Dn
detail	(Optional) detail

Command Mode: exec : Exec Mode

Command Path:

```
# show fabric-recovery checker moDn [detail]
```

show fabric-recovery status

show fabric-recovery status

Description: Show fabric recovery status

Command Mode: exec : Exec Mode

Command Path:

```
# show fabric-recovery status
```

show faults

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes/no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] <scope>

Description: Show fault information

Syntax:

history	(Optional) Historical information
<*fault-code*>	(Optional) Fault code
<*fault-ID*>	(Optional) Fault ID
<*yes/no*>	(Optional) Acknowledgment status
<*lc-state*>	(Optional) Lifecycle state
<*severity-value*>	(Optional) Severity
<*severity-value*>	(Optional) Minimum severity
<*fault-type*>	(Optional) Type
<*fault-value*>	(Optional) Cause
last-minutes <*num-minutes*>	(Optional) Fault activity in time interval. Number range from=1 to=59
last-hours <*num-hours*>	(Optional) Fault activity in time interval. Number range from=1 to=23
last-days <*num-days*>	(Optional) Fault activity in time interval. Number range from=1 to=999
start-time <*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Fault activity in time interval
end-time <*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Fault activity in time interval
detail	(Optional) Detailed faults information
<*scope*>	command scope

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes/no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail]
<scope>
```

show faults controller

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller

Description: Show controller information

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller
```

show faults controller detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller detail [id <node-id>]

Description: Detailed controller information

Syntax:

node-id	(Optional) Optional Serial number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller detail [id
 <node-id>]
```

show faults l4l7-cluster

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] l4l7-cluster [tenant <Tenant Name>] [cluster <Device Cluster Name>]

Description: Show L4 L7 Device information

Syntax:

Tenant Name	(Optional) Name of Tenant
Device Cluster Name	(Optional) Name of Device

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] l4l7-cluster [tenant
 <Tenant Name>] [cluster <Device Cluster Name>]
```

show faults l4l7-graph

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] l4l7-graph [tenant <Tenant Name>] [graph <Graph Name>]

Description: Show L4 L7 Graph information

Syntax:

<Tenant Name>	(Optional) Name of Tenant
<Graph Name>	(Optional) Name of Graph

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] l4l7-graph [tenant
<Tenant Name>] [graph <Graph Name>]
```

show faults leaf

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId>

Description: Show command for leaf

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId>
```

show faults leaf fex

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex <fexNum>

Description: Show extended chassis information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex
<fexNum>
```

show faults leaf fex module

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex <fexNum> module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> fex
<fexNum> module <lcSlot>
```

show faults leaf interface ethernet

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 ethernet <phyInt>
```

show faults leaf interface fc

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface fc <phyInt>

Description: Fibre Channel Protocol

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 fc <phyInt>
```

show faults leaf interface fcportchannel

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface fcportchannel <portChan>

Description: FC Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 fcportchannel <portChan>
```

show faults leaf interface l3instance

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface l3instance <l3Inst>

Description: L3 instance

Syntax:

<*leafId*>	Leaf id
<*l3Inst*>	<L3 instance number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 l3instance <l3Inst>
```

show faults leaf interface mgmt

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 mgmt <mgmtPort>
```

show faults leaf interface portchannel

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface portchannel <portChan>

Description: Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 portchannel <portChan>
```

show faults leaf interface tunnel

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface tunnel <tunnelPort>

Description: Tunnel Interface

Syntax:

<*leafId*>	Leaf id
<*tunnelPort*>	<Tunnel interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 tunnel <tunnelPort>
```

show faults leaf interface vethernet

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface vethernet <phyInt>

Description: vethernet ID

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> interface
 vethernet <phyInt>
```

show faults leaf inventory chassis

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<leafId>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory
 chassis
```

show faults leaf inventory fans

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory
 fans <ftSlot>
```

show faults leaf inventory module

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory
 module <lcSlot>
```

show faults leaf inventory module fabricport

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot> fabricport <fabPort>

Description: Show information for fabric port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*fabPort*>	pls enter the fabric port number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory
 module <lcSlot> fabricport <fabPort>
```

show faults leaf inventory module leafport

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory module <lcSlot> leafport <leafPort>

Description: Show information for leaf port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*leafPort*>	pls enter the leaf port number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory
 module <lcSlot> leafport <leafPort>
```

show faults leaf inventory powersupply

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory
 powersupply <psuSlot>
```

show faults leaf inventory supervisor

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> inventory
 supervisor <supMod>
```

show faults leaf protocol

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> protocol <protName>

Description: Show command for protocol

Syntax:

<*leafId*>	Leaf id
<*protName*>	Protocol name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> protocol
 <protName>
```

show faults leaf vpc

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vpc <vpcPort>

Description: Virtual port channel information

Syntax:

<*leafId*>	Leaf id
<*vpcPort*>	pls enter virtual port channel number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vpc
<vpcPort>
```

show faults leaf vrf

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vrf <vrfPort>

Description: Vrf information

Syntax:

<*leafId*>	Leaf id
<*vrfPort*>	pls enter vrf name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId> vrf
<vrfPort>
```

show faults microsoft domain

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain

Description: Show Microsoft domain information

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain
```

show faults microsoft domain name

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name <WORD>

Description: Microsoft domain name

Syntax:

WORD	Microsoft domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name
 <WORD>
```

show faults microsoft domain name hyperv

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name <WORD> hyperv <WORD>

Description: Show Microsoft Hypervisor information

Syntax:

WORD	Microsoft domain name
WORD	HyperV hostname

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name
 <WORD> hyperv <WORD>
```

show faults microsoft domain name port-group

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name <WORD> port-group

Description: Show Microsoft port group information

Syntax:

WORD	Microsoft domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name
 <WORD> port-group
```

show faults microsoft domain name scvmm

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name <WORD> scvmm <hostname|ip>

Description: Show Microsoft SCVMM information

Syntax:

WORD	Microsoft domain name
<hostname|ip>	SCVMM hostname or IP

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name
 <WORD> scvmm <hostname|ip>
```

show faults microsoft domain name vm

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name <WORD> vm

Description: Show Microsoft VM information

Syntax:

WORD	Microsoft domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name
 <WORD> vm
```

show faults microsoft domain name vm name

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name <WORD> vm name <WORD>

Description: Show detailed Microsoft VM information

Syntax:

WORD	Microsoft domain name
WORD	VM Name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] microsoft domain name
 <WORD> vm name <WORD>
```

show faults quota

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] quota

Description: Show Quotas Information

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] quota
```

show faults redhat domain

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain

Description: Show Redhat domain information

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain
```

show faults redhat domain name

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain name <name>

Description: Redhat domain name

Syntax:

<name>	Redhat domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain name
<name>
```

show faults redhat domain name epg

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain name <name> epg

Description: Show Redhat domain EPG details

Syntax:

<*name*>	Redhat domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain name
<name> epg
```

show faults redhat domain name rhev

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain name <name> rhev <hostname|ip>

Description: RHEV ip or hostname

Syntax:

<*name*>	Redhat domain name
<*hostname*|*ip*>	rhev hostname or IP

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] redhat domain name
<name> rhev <hostname|ip>
```

show faults spine

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId>

Description: Show command for spine

Syntax:

<leafId>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId>
```

show faults spine interface ethernet

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface
 ethernet <phyInt>
```

show faults spine interface l3instance

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface l3instance <l3Inst>

Description: L3 instance

Syntax:

<*leafId*>	Leaf id
<*l3Inst*>	<L3 instance number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface
 l3instance <l3Inst>
```

show faults spine interface mgmt

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface
 mgmt <mgmtPort>
```

show faults spine interface tunnel

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface tunnel <tunnelPort>

Description: Tunnel Interface

Syntax:

<*leafId*>	Leaf id
<*tunnelPort*>	<Tunnel interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> interface
 tunnel <tunnelPort>
```

show faults spine inventory chassis

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 chassis
```

show faults spine inventory fabric

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory fabric <fcMod>

Description: Show information for fabric module

Syntax:

<*leafId*>	Leaf id
<*fcMod*>	pls enter the fabric module number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 fabric <fcMod>
```

show faults spine inventory fans

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 fans <ftSlot>
```

show faults spine inventory module

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 module <lcSlot>
```

show faults spine inventory module fabricport

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory module <lcSlot> fabricport <fabPort>

Description: Show information for fabric port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*fabPort*>	pls enter the fabric port number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 module <lcSlot> fabricport <fabPort>
```

show faults spine inventory powersupply

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 powersupply <psuSlot>
```

show faults spine inventory supervisor

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 supervisor <supMod>
```

show faults spine inventory system

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory system <sysMod>

Description: Show information for system module

Syntax:

<*leafId*>	Leaf id
<*sysMod*>	pls enter the system module number

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> inventory
 system <sysMod>
```

show faults spine protocol

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> protocol <protName>

Description: Show command for protocol

Syntax:

<*leafId*>	Leaf id
<*protName*>	Protocol name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> protocol
 <protName>
```

show faults spine vrf

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> vrf <vrfPort>

Description: Vrf information

Syntax:

<leafId>	Leaf id
<vrfPort>	pls enter vrf name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId> vrf
<vrfPort>
```

show faults tenant

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD

Description: Show Tenants Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
```

show faults tenant application

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD

Description: Show Application Profiles Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application
 WORD
```

show faults tenant application epg

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application
 WORD epg WORD
```

show faults tenant application esg

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application WORD esg WORD

Description: Show Show Endpoint Security Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD application
 WORD esg WORD
```

show faults tenant bridge-domain

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
bridge-domain WORD
```

show faults tenant bridge-domain detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
bridge-domain WORD detail
```

show faults tenant bridge-domain first-hop-security binding-table

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
bridge-domain WORD first-hop-security binding-table
```

show faults tenant bridge-domain first-hop-security statistics arp

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
bridge-domain WORD first-hop-security statistics arp
```

show faults tenant bridge-domain first-hop-security statistics dhcpv4

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
bridge-domain WORD first-hop-security statistics dhcpv4
```

show faults tenant bridge-domain first-hop-security statistics dhcpv6

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
bridge-domain WORD first-hop-security statistics dhcpv6
```

show faults tenant bridge-domain first-hop-security statistics neighbor-discovery

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
bridge-domain WORD first-hop-security statistics neighbor-discovery
```

show faults tenant dnsservergroup

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD

Description: Show Dns Server Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
dnsservergroup WORD
```

show faults tenant dnsservergroup server

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD

Description: Show Dns Server Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
dnsservergroup WORD server WORD
```

show faults tenant dnsservergroup server domain

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD dnsservergroup WORD server WORD domain WORD

Description: Show Dns Domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)
WORD	Domain we eventually want to filter on (Max Size 512)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
dnsservergroup WORD server WORD domain WORD
```

show faults tenant interface bridge-domain

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface
 bridge-domain WORD
```

show faults tenant interface bridge-domain detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface
 bridge-domain WORD detail
```

show faults tenant interface bridge-domain first-hop-security binding-table

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface
 bridge-domain WORD first-hop-security binding-table
```

show faults tenant interface bridge-domain first-hop-security statistics arp

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface
 bridge-domain WORD first-hop-security statistics arp
```

show faults tenant interface bridge-domain first-hop-security statistics dhcpv4

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface
 bridge-domain WORD first-hop-security statistics dhcpv4
```

show faults tenant interface bridge-domain first-hop-security statistics dhcpv6

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface
 bridge-domain WORD first-hop-security statistics dhcpv6
```

show faults tenant interface bridge-domain first-hop-security statistics neighbor-discovery

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD interface
 bridge-domain WORD first-hop-security statistics neighbor-discovery
```

show faults tenant multicast-route-maps

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD multicast-route-maps

Description: Show multicast route-maps per Tenant

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD
multicast-route-maps
```

show faults tenant vrf

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD

Description: Show VRF Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
```

show faults tenant vrf acllog l2

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>

Description: L2 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flowi stats
vlan	vlan info
<*vlan*>	<vlan>. Number range from=0 to=9223372036854775807
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>
```

show faults tenant vrf acllog l3

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport <dstport> srcintf <srcintf>

Description: L3 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flow stats
srcpctag	source pc tag
<*srcpctag*>	<srcpctag>
dstpctag	destination pc tag
<*dstpctag*>	<dstpctag>
srcepgname	source epg name
<*srcepgname*>	<srcepgname>
dstepgname	destination epg name
<*dstepgname*>	<dstepgname>
srcip	source ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
dstip	destination ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
proto	protocol
<*proto*>	<proto>
srcport	source port
<*srcport*>	<srcport>
dstport	destination port

<*dstport*>	<dstport>
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname>
 dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto
<proto> srcport <srcport> dstport <dstport> srcintf <srcintf>
```

show faults tenant vrf detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD detail

Description: Show detailed view of VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 detail
```

show faults tenant vrf external-l3 bgp

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp

Description: Show command for BGP peers

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 bgp
```

show faults tenant vrf external-l3 bgp node

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 bgp node <101-4000>

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<101-4000>	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 bgp node <101-4000>
```

show faults tenant vrf external-l3 eigrp

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp

Description: Show external l3 EIGRP

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 eigrp
```

show faults tenant vrf external-l3 eigrp detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 eigrp detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 eigrp detail
```

show faults tenant vrf external-l3 epg

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName>

Description: Show command for external-l3 epgs

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<*epgName*>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 epg <epgName>
```

show faults tenant vrf external-l3 epg detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 epg <epgName> detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 epg <epgName> detail
```

show faults tenant vrf external-l3 interfaces

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces

Description: Show tenant <tenant> vrf <vrf> external l3 interfaces

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 interfaces
```

show faults tenant vrf external-l3 interfaces detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 interfaces detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 interfaces detail
```

show faults tenant vrf external-l3 ospf

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf

Description: Show command for IPv4 and IPv6 external l3 OSPF configuration

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 ospf
```

show faults tenant vrf external-l3 ospf detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 ospf detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 ospf detail
```

show faults tenant vrf external-l3 scale

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale

Description: scale command

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 scale
```

show faults tenant vrf external-l3 scale detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 scale detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 scale detail
```

show faults tenant vrf external-l3 static-route

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route

Description: Show command for external-l3 static routes

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 static-route
```

show faults tenant vrf external-l3 static-route detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 static-route detail
```

show faults tenant vrf external-l3 static-route node

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 static-route node
```

show faults tenant vrf external-l3 static-route node detail

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD external-l3 static-route node detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 external-l3 static-route node detail
```

show faults tenant vrf ipv6multicast

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD ipv6multicast

Description: Show ipv6 multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 ipv6multicast
```

show faults tenant vrf multicast

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD multicast

Description: Show multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] tenant WORD vrf WORD
 multicast
```

show faults vmware domain

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain

Description: Show VMware domain information

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain
```

show faults vmware domain name

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name>

Description: VMware domain name

Syntax:

<*name*>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name>
```

show faults vmware domain name epg

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name> epg

Description: Show VMware domain EPG details

Syntax:

<*name*>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name> epg
```

show faults vmware domain name esx

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name> esx <esx-ip>

Description: Show VMware ESX information

Syntax:

<*name*>	VMware domain name
<*esx-ip*>	ESX IP

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name> esx <esx-ip>
```

show faults vmware domain name port-group

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name> port-group

Description: Show VMware port group information

Syntax:

<*name*>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name> port-group
```

show faults vmware domain name trunk-portgroup

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name> trunk-portgroup [name <name>]

Description: Show VMware domain trunk portgroup details

Syntax:

<*name*>	VMware domain name
<*name*>	(Optional) trunk portgroup name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name> trunk-portgroup [name <name>]
```

show faults vmware domain name vcenter

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name> vcenter <hostname|ip>

Description: VMware vCenter ip or hostname

Syntax:

<*name*>	VMware domain name
<*hostname*|*ip*>	vCenter hostname or IP

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name> vcenter <hostname|ip>
```

show faults vmware domain name vm

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name> vm

Description: Show VMware VM information

Syntax:

<name>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name> vm
```

show faults vmware domain name vm name

show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>] [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause <fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name <name> vm name <vm-name>

Description: Show detailed VMware VM information

Syntax:

<*name*>	VMware domain name
<*vm-name*>	VM Name

Command Mode: exec : Exec Mode

Command Path:

```
# show faults [history] [code <fault-code>] [id <fault-ID>] [ack <yes|no>] [lc <lc-state>]
 [severity <severity-value>] [min-severity <severity-value>] [type <fault-type>] [cause
<fault-value>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time
 <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] vmware domain name
<name> vm name <vm-name>
```

show fips

show fips

Description: Show FIPS information

Command Mode: exec : Exec Mode

Command Path:

```
# show fips
```

show fips status

show fips status

Description: Show FIPS status

Command Mode: exec : Exec Mode

Command Path:

```
# show fips status
```

show firmware compat matrix

show firmware compat matrix <WORD>

Description: compatibility matrix for desired version

Syntax:

WORD	Desired Controller Version

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware compat matrix <WORD>
```

show firmware repository

show firmware repository

Description: Show firmware images present in repository

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware repository
```

show firmware repository detail

show firmware repository detail

Description: Detailed repository information

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware repository detail
```

show firmware upgrade scheduler-status

show firmware upgrade scheduler-status

Description: scheduler status information

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade scheduler-status
```

show firmware upgrade scheduler-status switch-group

show firmware upgrade scheduler-status switch-group <WORD>

Description: Scheduler status for desired switch group

Syntax:

WORD	Scheduler status for desired switch group

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade scheduler-status switch-group <WORD>
```

show firmware upgrade status

show firmware upgrade status

Description: Upgrade status of all controllers and switches

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status
```

show firmware upgrade status controller-group

show firmware upgrade status controller-group

Description: Controller-group upgrade status

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status controller-group
```

show firmware upgrade status controller-group detail

show firmware upgrade status controller-group detail

Description: Detailed upgrade status

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status controller-group detail
```

show firmware upgrade status detail

show firmware upgrade status detail

Description: Detailed upgrade status information

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status detail
```

show firmware upgrade status standby-apic

show firmware upgrade status standby-apic

Description: standby-apic upgrade status

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status standby-apic
```

show firmware upgrade status standby-apic detail

show firmware upgrade status standby-apic detail

Description: Detailed standby-apic upgrade status

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status standby-apic detail
```

show firmware upgrade status switch-group

show firmware upgrade status switch-group <WORD>

Description: Switch-group upgrade status

Syntax:

WORD	switch-group name (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status switch-group <WORD>
```

show firmware upgrade status switch-group detail

show firmware upgrade status switch-group <WORD> detail

Description: Detailed upgrade status

Syntax:

WORD	switch-group name (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show firmware upgrade status switch-group <WORD> detail
```

show flow exporter

show flow exporter

Description: Show Netflow exporter information

Command Mode: exec : Exec Mode

Command Path:

```
# show flow exporter
```

show flow exporter infra

show flow exporter infra WORD [detail]

Description: Show flow exporter infra information

Syntax:

WORD	Exporter Name
detail	(Optional) detail

Command Mode: exec : Exec Mode

Command Path:

```
# show flow exporter infra WORD [detail]
```

show flow exporter tenant

show flow exporter tenant <WORD> WORD [detail]

Description: Show flow exporter tenant information

Syntax:

WORD	Optional tenant name
WORD	Exporter Name
detail	(Optional) detail

Command Mode: exec : Exec Mode

Command Path:

```
# show flow exporter tenant <WORD> WORD [detail]
```

show flow monitor

show flow monitor

Description: Show Netflow Monitor Information

Command Mode: exec : Exec Mode

Command Path:

```
# show flow monitor
```

show flow monitor infra

show flow monitor infra WORD [detail]

Description: Show Netflow Monitor Information for infra

Syntax:

WORD	Optional Monitor Name
detail	(Optional) detail

Command Mode: exec : Exec Mode

Command Path:

```
# show flow monitor infra WORD [detail]
```

show flow monitor tenant

show flow monitor tenant <WORD> WORD [detail]

Description: Show Netflow Monitor Information for the specified tenant

Syntax:

WORD	Specify tenant name
WORD	Optional Monitor Name
detail	(Optional) detail

Command Mode: exec : Exec Mode

Command Path:

```
# show flow monitor tenant <WORD> WORD [detail]
```

show flow node-policy

show flow node-policy [name <WORD>]

Description: Show Netflow Node Policy Information

Syntax:

WORD	(Optional) Optional Node Policy Name

Command Mode: exec : Exec Mode

Command Path:

```
# show flow node-policy [name <WORD>]
```

show flow node-policy detail

show flow node-policy [name <WORD>] detail

Description: Show Netflow Node Policy Detailed Information

Syntax:

WORD	(Optional) Optional Node Policy Name

Command Mode: exec : Exec Mode

Command Path:

```
# show flow node-policy [name <WORD>] detail
```

show flow record

show flow record

Description: Show Netflow record information

Command Mode: exec : Exec Mode

Command Path:

```
# show flow record
```

show flow record infra

show flow record infra WORD [detail]

Description: Show flow record infra information

Syntax:

WORD	Record Name
detail	(Optional) detail

Command Mode: exec : Exec Mode

Command Path:

```
# show flow record infra WORD [detail]
```

show flow record tenant

show flow record tenant [record-name <recordName>] <tenantName> WORD [detail]

Description: Show flow record tenant information

Syntax:

recordName	(Optional) Optional record name
tenantName	Optional tenant name
WORD	Record Name
detail	(Optional) detail

Command Mode: exec : Exec Mode

Command Path:

```
# show flow record tenant [record-name <recordName>] <tenantName> WORD [detail]
```

show flow vm-exporter

show flow vm-exporter WORD

Description: Show NetFlow Exporter information for VM Networking

Syntax:

WORD	NetFlow Exporter Name

Command Mode: exec : Exec Mode

Command Path:

```
# show flow vm-exporter WORD
```

show health

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] <scope>

Description: Show health score information

Syntax:

history	(Optional) Historical information
min-change <percentage change>	(Optional) Minimum change in health score percentage. Number range from=-100 to=9999
max-hs <maximum health-score>	(Optional) Maximum health score. Number range from=0 to=100
start-time <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Health activity in time interval
end-time <YYYY-MM-DDTHR:MIN:SEC>	(Optional) Health activity in time interval
<scope>	command scope

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] <scope>
```

show health leaf

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId>

Description: Show command for leaf

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId>
```

show health leaf fex

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> fex <fexNum>

Description: Show extended chassis information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> fex <fexNum>
```

show health leaf fex module

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> fex <fexNum> module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> fex <fexNum>
module <lcSlot>
```

show health leaf interface ethernet

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface ethernet
 <phyInt>
```

show health leaf interface fc

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface fc <phyInt>

Description: Fibre Channel Protocol

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface fc
<phyInt>
```

show health leaf interface fcportchannel

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface fcportchannel <portChan>

Description: FC Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface
fcportchannel <portChan>
```

show health leaf interface l3instance

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface l3instance <l3Inst>

Description: L3 instance

Syntax:

<*leafId*>	Leaf id
<*l3Inst*>	<L3 instance number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface l3instance
 <l3Inst>
```

show health leaf interface mgmt

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface mgmt
<mgmtPort>
```

show health leaf interface portchannel

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface portchannel <portChan>

Description: Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface
portchannel <portChan>
```

show health leaf interface tunnel

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface tunnel <tunnelPort>

Description: Tunnel Interface

Syntax:

<*leafId*>	Leaf id
<*tunnelPort*>	<Tunnel interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface tunnel
 <tunnelPort>
```

show health leaf interface vethernet

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface vethernet <phyInt>

Description: vethernet ID

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> interface vethernet
 <phyInt>
```

show health leaf inventory chassis

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<leafId>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory chassis
```

show health leaf inventory fans

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory fans
<ftSlot>
```

show health leaf inventory module

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory module
 <lcSlot>
```

show health leaf inventory module fabricport

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory module <lcSlot> fabricport <fabPort>

Description: Show information for fabric port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*fabPort*>	pls enter the fabric port number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory module
 <lcSlot> fabricport <fabPort>
```

show health leaf inventory module leafport

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory module <lcSlot> leafport <leafPort>

Description: Show information for leaf port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*leafPort*>	pls enter the leaf port number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory module
 <lcSlot> leafport <leafPort>
```

show health leaf inventory powersupply

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory
powersupply <psuSlot>
```

show health leaf inventory supervisor

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> inventory supervisor
 <supMod>
```

show health leaf protocol

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> protocol <protName>

Description: Show command for protocol

Syntax:

<*leafId*>	Leaf id
<*protName*>	Protocol name

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> protocol <protName>
```

show health leaf vpc

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> vpc <vpcPort>

Description: Virtual port channel information

Syntax:

<*leafId*>	Leaf id
<*vpcPort*>	pls enter virtual port channel number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> vpc <vpcPort>
```

show health leaf vrf

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> vrf <vrfPort>

Description: Vrf information

Syntax:

<*leafId*>	Leaf id
<*vrfPort*>	pls enter vrf name

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] leaf <leafId> vrf <vrfPort>
```

show health spine

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId>

Description: Show command for spine

Syntax:

<leafId>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId>
```

show health spine interface ethernet

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface ethernet
 <phyInt>
```

show health spine interface l3instance

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface l3instance <l3Inst>

Description: L3 instance

Syntax:

<*leafId*>	Leaf id
<*l3Inst*>	<L3 instance number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface
l3instance <l3Inst>
```

show health spine interface mgmt

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface mgmt
<mgmtPort>
```

show health spine interface tunnel

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface tunnel <tunnelPort>

Description: Tunnel Interface

Syntax:

<*leafId*>	Leaf id
<*tunnelPort*>	<Tunnel interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> interface tunnel
 <tunnelPort>
```

show health spine inventory chassis

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory chassis
```

show health spine inventory fabric

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory fabric <fcMod>

Description: Show information for fabric module

Syntax:

<*leafId*>	Leaf id
<*fcMod*>	pls enter the fabric module number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory fabric
 <fcMod>
```

show health spine inventory fans

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory fans
<ftSlot>
```

show health spine inventory module

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory module
 <lcSlot>
```

show health spine inventory module fabricport

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory module <lcSlot> fabricport <fabPort>

Description: Show information for fabric port

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number
<*fabPort*>	pls enter the fabric port number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory module
 <lcSlot> fabricport <fabPort>
```

show health spine inventory powersupply

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory
powersupply <psuSlot>
```

show health spine inventory supervisor

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory
supervisor <supMod>
```

show health spine inventory system

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory system <sysMod>

Description: Show information for system module

Syntax:

<*leafId*>	Leaf id
<*sysMod*>	pls enter the system module number

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> inventory system
 <sysMod>
```

show health spine protocol

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> protocol <protName>

Description: Show command for protocol

Syntax:

<*leafId*>	Leaf id
<*protName*>	Protocol name

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> protocol <protName>
```

show health spine vrf

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> vrf <vrfPort>

Description: Vrf information

Syntax:

<*leafId*>	Leaf id
<*vrfPort*>	pls enter vrf name

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] spine <leafId> vrf <vrfPort>
```

show health tenant

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD

Description: Show Tenants Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD
```

show health tenant application

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD application WORD

Description: Show Application Profiles Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD application WORD
```

show health tenant application epg

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD application WORD epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD application WORD
epg WORD
```

show health tenant application esg

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD application WORD esg WORD

Description: Show Show Endpoint Security Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD application WORD
esg WORD
```

show health tenant bridge-domain

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD
```

show health tenant bridge-domain detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD
 detail
```

show health tenant bridge-domain first-hop-security binding-table

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD
 first-hop-security binding-table
```

show health tenant bridge-domain first-hop-security statistics arp

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD
 first-hop-security statistics arp
```

show health tenant bridge-domain first-hop-security statistics dhcpv4

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD
 first-hop-security statistics dhcpv4
```

show health tenant bridge-domain first-hop-security statistics dhcpv6

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD
 first-hop-security statistics dhcpv6
```

show health tenant bridge-domain first-hop-security statistics neighbor-discovery

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD bridge-domain WORD
 first-hop-security statistics neighbor-discovery
```

show health tenant dnsservergroup

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD dnsservergroup WORD

Description: Show Dns Server Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD dnsservergroup WORD
```

show health tenant dnsservergroup server

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD dnsservergroup WORD server WORD

Description: Show Dns Server Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD dnsservergroup WORD
 server WORD
```

show health tenant dnsservergroup server domain

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD dnsservergroup WORD server WORD domain WORD

Description: Show Dns Domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)
WORD	Domain we eventually want to filter on (Max Size 512)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD dnsservergroup WORD
 server WORD domain WORD
```

show health tenant interface bridge-domain

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface
bridge-domain WORD
```

show health tenant interface bridge-domain detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface
bridge-domain WORD detail
```

show health tenant interface bridge-domain first-hop-security binding-table

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface
bridge-domain WORD first-hop-security binding-table
```

show health tenant interface bridge-domain first-hop-security statistics arp

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface
bridge-domain WORD first-hop-security statistics arp
```

show health tenant interface bridge-domain first-hop-security statistics dhcpv4

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface
bridge-domain WORD first-hop-security statistics dhcpv4
```

show health tenant interface bridge-domain first-hop-security statistics dhcpv6

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface
bridge-domain WORD first-hop-security statistics dhcpv6
```

show health tenant interface bridge-domain first-hop-security statistics neighbor-discovery

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD interface
bridge-domain WORD first-hop-security statistics neighbor-discovery
```

show health tenant multicast-route-maps

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD multicast-route-maps

Description: Show multicast route-maps per Tenant

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD multicast-route-maps
```

show health tenant vrf

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD

Description: Show VRF Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD
```

show health tenant vrf acllog l2

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>

Description: L2 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flowi stats
vlan	vlan info
<*vlan*>	<vlan>. Number range from=0 to=9223372036854775807
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD acllog
<permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>
```

show health tenant vrf acllog l3

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport <dstport> srcintf <srcintf>

Description: L3 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flow stats
srcpctag	source pc tag
<*srcpctag*>	<srcpctag>
dstpctag	destination pc tag
<*dstpctag*>	<dstpctag>
srcepgname	source epg name
<*srcepgname*>	<srcepgname>
dstepgname	destination epg name
<*dstepgname*>	<dstepgname>
srcip	source ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
dstip	destination ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
proto	protocol
<*proto*>	<proto>
srcport	source port
<*srcport*>	<srcport>
dstport	destination port
<*dstport*>	<dstport>

srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD acllog
<permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname>
dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto>
 srcport <srcport> dstport <dstport> srcintf <srcintf>
```

show health tenant vrf detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD detail

Description: Show detailed view of VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD detail
```

show health tenant vrf external-l3 bgp

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 bgp

Description: Show command for BGP peers

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 bgp
```

show health tenant vrf external-l3 bgp node

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 bgp node <101-4000>

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<101-4000>	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 bgp node <101-4000>
```

show health tenant vrf external-l3 eigrp

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 eigrp

Description: Show external l3 EIGRP

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 eigrp
```

show health tenant vrf external-l3 eigrp detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 eigrp detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 eigrp detail
```

show health tenant vrf external-l3 epg

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 epg <epgName>

Description: Show command for external-l3 epgs

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<*epgName*>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 epg <epgName>
```

show health tenant vrf external-l3 epg detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 epg <epgName> detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 epg <epgName> detail
```

show health tenant vrf external-l3 interfaces

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 interfaces

Description: Show tenant <tenant> vrf <vrf> external l3 interfaces

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 interfaces
```

show health tenant vrf external-l3 interfaces detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 interfaces detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 interfaces detail
```

show health tenant vrf external-l3 ospf

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 ospf

Description: Show command for IPv4 and IPv6 external l3 OSPF configuration

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 ospf
```

show health tenant vrf external-l3 ospf detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 ospf detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 ospf detail
```

show health tenant vrf external-l3 scale

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 scale

Description: scale command

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 scale
```

show health tenant vrf external-l3 scale detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 scale detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 scale detail
```

show health tenant vrf external-l3 static-route

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 static-route

Description: Show command for external-l3 static routes

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 static-route
```

show health tenant vrf external-l3 static-route detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 static-route detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 static-route detail
```

show health tenant vrf external-l3 static-route node

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 static-route node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 static-route node
```

show health tenant vrf external-l3 static-route node detail

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3 static-route node detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD external-l3
 static-route node detail
```

show health tenant vrf ipv6multicast

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD ipv6multicast

Description: Show ipv6 multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD ipv6multicast
```

show health tenant vrf multicast

show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD multicast

Description: Show multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show health [history] [min-change <NUMBER>] [max-hs <NUMBER>] [start-time
<YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] tenant WORD vrf WORD multicast
```

show inband-mgmt

show inband-mgmt

Description: Show inband mgmt epgs on all the nodes

Command Mode: exec : Exec Mode

Command Path:

```
# show inband-mgmt
```

show inband-mgmt controller

show inband-mgmt controller <controller-id> [epg <WORD>]

Description: show inband mgmt epgs on the controller

Syntax:

<controller-id>	
WORD	(Optional) Epg Name of conusmer epg

Command Mode: exec : Exec Mode

Command Path:

```
# show inband-mgmt controller <controller-id> [epg <WORD>]
```

show inband-mgmt switch

show inband-mgmt switch <switch-id> [epg <WORD>]

Description: Show inband mgmt epgs on the node

Syntax:

<switch-id>	
WORD	(Optional) Epg Name

Command Mode: exec : Exec Mode

Command Path:

```
# show inband-mgmt switch <switch-id> [epg <WORD>]
```

show interface bridge-domain

show interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show interface bridge-domain WORD
```

show interface bridge-domain detail

show interface bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show interface bridge-domain WORD detail
```

show interface bridge-domain first-hop-security binding-table

show interface bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show interface bridge-domain WORD first-hop-security binding-table
```

show interface bridge-domain first-hop-security statistics arp

show interface bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show interface bridge-domain WORD first-hop-security statistics arp
```

show interface bridge-domain first-hop-security statistics dhcpv4

show interface bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show interface bridge-domain WORD first-hop-security statistics dhcpv4
```

show interface bridge-domain first-hop-security statistics dhcpv6

show interface bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show interface bridge-domain WORD first-hop-security statistics dhcpv6
```

show interface bridge-domain first-hop-security statistics neighbor-discovery

show interface bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show interface bridge-domain WORD first-hop-security statistics neighbor-discovery
```

show ip interface bridge-domain

show ip interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show ip interface bridge-domain WORD
```

show ipv6 interface bridge-domain

show ipv6 interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show ipv6 interface bridge-domain WORD
```

show l4l7-cluster

show l4l7-cluster [tenant <Tenant Name>] [cluster <Device Cluster Name>]

Description: Show L4 L7 Device information

Syntax:

Tenant Name	(Optional) Name of Tenant
Device Cluster Name	(Optional) Name of Device

Command Mode: exec : Exec Mode

Command Path:

```
# show l4l7-cluster [tenant <Tenant Name>] [cluster <Device Cluster Name>]
```

show l4l7-graph

show l4l7-graph [tenant <Tenant Name>] [graph <Graph Name>]

Description: Show L4 L7 Graph information

Syntax:

<*Tenant Name*>	(Optional) Name of Tenant
<*Graph Name*>	(Optional) Name of Graph

Command Mode: exec : Exec Mode

Command Path:

```
# show l4l7-graph [tenant <Tenant Name>] [graph <Graph Name>]
```

show l4l7-package

show l4l7-package

Description: Show L4-L7 package information

Command Mode: exec : Exec Mode

Command Path:

```
# show l4l7-package
```

show ldap-server

show ldap-server

Description: Show LDAP server information

Command Mode: exec : Exec Mode

Command Path:

```
# show ldap-server
```

show license all

show license all

Description: Show license all

Command Mode: exec : Exec Mode

Command Path:

```
# show license all
```

show license catalog

show license catalog

Description: Show license catalog

Command Mode: exec : Exec Mode

Command Path:

```
# show license catalog
```

show license hostname

show license hostname privacy

Description: Show license hostname

Syntax:

privacy	privacy

Command Mode: exec : Exec Mode

Command Path:

```
# show license hostname privacy
```

show license interval

show license interval

Description: Display the license interval

Command Mode: exec : Exec Mode

Command Path:

```
# show license interval
```

show license status

show license status

Description: Show license status

Command Mode: exec : Exec Mode

Command Path:

```
# show license status
```

show license summary

show license summary

Description: Show license summary

Command Mode: exec : Exec Mode

Command Path:

```
# show license summary
```

show license tech

show license tech support

Description: Show license tech support

Syntax:

support	techsupport

Command Mode: exec : Exec Mode

Command Path:

```
# show license tech support
```

show license transport-mode

show license transport-mode

Description: Displaying smart licensing transport mode

Command Mode: exec : Exec Mode

Command Path:

```
# show license transport-mode
```

show license udi

show license udi

Description: Display device udi

Command Mode: exec : Exec Mode

Command Path:

```
# show license udi
```

show license usage

show license usage

Description: Show license usage

Command Mode: exec : Exec Mode

Command Path:

```
# show license usage
```

show lldp

show lldp

Description: Show lldp neighbor information

Command Mode: exec : Exec Mode

Command Path:

```
# show lldp
```

show locator-led

show locator-led status

Description: Show command for locator-led

Syntax:

status	locator-led status

Command Mode: exec : Exec Mode

Command Path:

```
# show locator-led status
```

show locator-led status leaf

show locator-led status leaf

Description: Leaf to filter on

Syntax:

status	locator-led status
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show locator-led status leaf
```

show locator-led status spine

show locator-led status spine

Description: Spine to filter on

Syntax:

status	locator-led status
arg	Spine Range or Spine Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show locator-led status spine
```

show macsec interface

show macsec interface switch <101-4000>

Description: interface

Syntax:

switch	switch
<101-4000>	switch ID

Command Mode: exec : Exec Mode

Command Path:

```
# show macsec interface switch <101-4000>
```

show macsec policy

show macsec policy <WORD>

Description: Show macsec policies

Syntax:

WORD	Node Number (Max Size 4000). Number range from=0 to=9223372036854775807

Command Mode: exec : Exec Mode

Command Path:

```
# show macsec policy <WORD>
```

show microsoft domain

show microsoft domain

Description: Show Microsoft domain information

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft domain
```

show microsoft domain name

show microsoft domain name <WORD>

Description: Microsoft domain name

Syntax:

WORD	Microsoft domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft domain name <WORD>
```

show microsoft domain name hyperv

show microsoft domain name <WORD> hyperv <WORD>

Description: Show Microsoft Hypervisor information

Syntax:

WORD	Microsoft domain name
WORD	HyperV hostname

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft domain name <WORD> hyperv <WORD>
```

show microsoft domain name port-group

show microsoft domain name <WORD> port-group

Description: Show Microsoft port group information

Syntax:

WORD	Microsoft domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft domain name <WORD> port-group
```

show microsoft domain name scvmm

show microsoft domain name <WORD> scvmm <hostname|ip>

Description: Show Microsoft SCVMM information

Syntax:

WORD	Microsoft domain name
<hostname|ip>	SCVMM hostname or IP

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft domain name <WORD> scvmm <hostname|ip>
```

show microsoft domain name vm

show microsoft domain name <WORD> vm

Description: Show Microsoft VM information

Syntax:

WORD	Microsoft domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft domain name <WORD> vm
```

show microsoft domain name vm name

show microsoft domain name <WORD> vm name <WORD>

Description: Show detailed Microsoft VM information

Syntax:

WORD	Microsoft domain name
WORD	VM Name

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft domain name <WORD> vm name <WORD>
```

show microsoft vm

show microsoft vm [name <WORD>] [ip <A.B.C.D>] [mac <AA:BB:CC:DD:EE:FF>]

Description: Show Microsoft VM information

Syntax:

WORD	(Optional) Specify a VM name
A.B.C.D	(Optional) Specify a VM IP address
AA:BB:CC:DD:EE:FF	(Optional) Specify a VM MAC address

Command Mode: exec : Exec Mode

Command Path:

```
# show microsoft vm [name <WORD>] [ip <A.B.C.D>] [mac <AA:BB:CC:DD:EE:FF>]
```

show monitor access

show monitor access

Description: Show monitor session/filter-group for access interfaces

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor access
```

show monitor access filter-group

show monitor access filter-group filter-group_name

Description: Show monitor filter-group for access interfaces

Syntax:

filter-group_name	filter-group name

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor access filter-group filter-group_name
```

show monitor access session

show monitor access session session_name

Description: Show monitor session for access interfaces

Syntax:

session_name	session name

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor access session session_name
```

show monitor fabric

show monitor fabric

Description: Show monitor session/filter-group for fabric interfaces

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor fabric
```

show monitor fabric filter-group

show monitor fabric filter-group filter-group_name

Description: Show monitor filter-group for fabric interfaces

Syntax:

filter-group_name	filter-group name

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor fabric filter-group filter-group_name
```

show monitor fabric session

show monitor fabric session session_name

Description: Show monitor session for fabric interfaces

Syntax:

session_name	session name

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor fabric session session_name
```

show monitor summary

show monitor summary

Description: Show brief summary of all non-virtual monitor sessions

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor summary
```

show monitor tenant

show monitor tenant <tenant_name> session session_name

Description: Show monitor session for tenant

Syntax:

tenant_name	tenant
session	session
session_name	session name

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor tenant <tenant_name> session session_name
```

show monitor virtual

show monitor virtual session WORD

Description: Show monitor session for virtual switches

Syntax:

session	session
WORD	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show monitor virtual session WORD
```

show name-alias tenant

show name-alias tenant WORD

Description: Show corresponding tenants for Alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD
```

show name-alias tenant acl

show name-alias tenant WORD acl WORD

Description: Show Acl Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the Acl Alias to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD acl WORD
```

show name-alias tenant application

show name-alias tenant WORD application WORD

Description: Show Application Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the application Alias to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD application WORD
```

show name-alias tenant application epg

show name-alias tenant WORD application WORD epg WORD

Description: Show EndPoint Group Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the application Alias to filter on (Max Size 64)
WORD	Name of the epg Alias to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD application WORD epg WORD
```

show name-alias tenant bridge-domain

show name-alias tenant WORD bridge-domain WORD

Description: Show Bridge-Domain Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the bridge-domain Alias to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD bridge-domain WORD
```

show name-alias tenant contract

show name-alias tenant WORD contract WORD

Description: Show Contract Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the contract Alias to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD contract WORD
```

show name-alias tenant contract subject

show name-alias tenant WORD contract WORD subject WORD

Description: Show Subject Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the contract Alias to filter on (Max Size 64)
WORD	Name of the Subject Alias to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD contract WORD subject WORD
```

show name-alias tenant l3out

show name-alias tenant WORD l3out WORD

Description: Show L3out Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the L3out Alias to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD l3out WORD
```

show name-alias tenant vrf

show name-alias tenant WORD vrf WORD

Description: Show Vrf Name for alias

Syntax:

WORD	Name of the tenant Alias to filter on (Max Size 63)
WORD	Name of the vrf Alias to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show name-alias tenant WORD vrf WORD
```

show ntpq

show ntpq

Description: Show ntpq information

Command Mode: exec : Exec Mode

Command Path:

```
# show ntpq
```

show oob-mgmt

show oob-mgmt

Description: Show Out of band Information

Command Mode: exec : Exec Mode

Command Path:

```
# show oob-mgmt
```

show oob-mgmt controller

show oob-mgmt controller <controller-id> [epg <WORD>]

Description: Show oob mgmt epgs on the controller, enter one

Syntax:

<controller-id>	
WORD	(Optional) Epg Name of conusmer epg

Command Mode: exec : Exec Mode

Command Path:

```
# show oob-mgmt controller <controller-id> [epg <WORD>]
```

show oob-mgmt switch

show oob-mgmt switch <switch-id> [epg <WORD>]

Description: Show oob mgmt epgs on the node, enter one

Syntax:

<switch-id>	
WORD	(Optional) Epg Name of conusmer epg

Command Mode: exec : Exec Mode

Command Path:

```
# show oob-mgmt switch <switch-id> [epg <WORD>]
```

show pd-recovery status

show pd-recovery status

Description: Show policydist shard recovery from policymgr shards status

Command Mode: exec : Exec Mode

Command Path:

```
# show pd-recovery status
```

show policy-map

show policy-map

Description: Show policy maps

Command Mode: exec : Exec Mode

Command Path:

```
# show policy-map
```

show policy-map type data-plane

show policy-map type data-plane infra WORD [stats]

Description: Data-plane type policy-map(s)

Syntax:

infra	Global data-plane policy-map(s)
WORD	data-plane type policy-map(s) (Max Size 64)
stats	(Optional) Data-Plane Policer Statistics, where available

Command Mode: exec : Exec Mode

Command Path:

```
# show policy-map type data-plane infra WORD [stats]
```

show policy-map type qos

show policy-map type qos WORD

Description: QOS type policy-map(s)

Syntax:

WORD	QOS type policy-map(s) (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show policy-map type qos WORD
```

show port-channel leaf

show port-channel leaf WORD <port-channel-list>

Description: Show leaf port-channel info

Syntax:

WORD	Leaf Range or Leaf Name List
<*port-channel-list*>	port channel names

Command Mode: exec : Exec Mode

Command Path:

```
# show port-channel leaf WORD <port-channel-list>
```

show port-channel map

show port-channel map <port-channel-list>

Description: Show port-channel mapping

Syntax:

<*port-channel-list*>	port channel names

Command Mode: exec : Exec Mode

Command Path:

```
# show port-channel map <port-channel-list>
```

show port-channel map leaf

show port-channel map <port-channel-list> leaf WORD [fex <101-199>]

Description: Leaf

Syntax:

<port-channel-list>	port channel names
WORD	Leaf Range or Leaf Name List
<101-199>	(Optional) Fex ID

Command Mode: exec : Exec Mode

Command Path:

```
# show port-channel map <port-channel-list> leaf WORD [fex <101-199>]
```

show pwd-rules

show pwd-rules

Description: Show Password Rules

Command Mode: exec : Exec Mode

Command Path:

```
# show pwd-rules
```

show quota

show quota

Description: Show Quotas Information

Command Mode: exec : Exec Mode

Command Path:

```
# show quota
```

show radius-server

show radius-server

Description: Show RADIUS server information

Command Mode: exec : Exec Mode

Command Path:

```
# show radius-server
```

show redhat domain

show redhat domain

Description: Show Redhat domain information

Command Mode: exec : Exec Mode

Command Path:

```
# show redhat domain
```

show redhat domain name

show redhat domain name <name>

Description: Redhat domain name

Syntax:

<*name*>	Redhat domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show redhat domain name <name>
```

show redhat domain name epg

show redhat domain name <name> epg

Description: Show Redhat domain EPG details

Syntax:

<*name*>	Redhat domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show redhat domain name <name> epg
```

show redhat domain name rhev

show redhat domain name <name> rhev <hostname|ip>

Description: RHEV ip or hostname

Syntax:

<*name*>	Redhat domain name
<*hostname*|*ip*>	rhev hostname or IP

Command Mode: exec : Exec Mode

Command Path:

```
# show redhat domain name <name> rhev <hostname|ip>
```

show resource

show resource conflict encap-vlan

Description: Show resource information

Syntax:

conflict	show resource conflicts in APIC
encap-vlan	show resource conflicts of encap-vlan in APIC

Command Mode: exec : Exec Mode

Command Path:

```
# show resource conflict encap-vlan
```

show resource conflict encap-vlan epg

show resource conflict encap-vlan epg <WORD>

Description: Epg Name

Syntax:

conflict	show resource conflicts in APIC
encap-vlan	show resource conflicts of encap-vlan in APIC
WORD	Epg Name

Command Mode: exec : Exec Mode

Command Path:

```
# show resource conflict encap-vlan epg <WORD>
```

show resource conflict encap-vlan epg node

show resource conflict encap-vlan epg <WORD> node <101-4000>

Description: Node ID

Syntax:

conflict	show resource conflicts in APIC
encap-vlan	show resource conflicts of encap-vlan in APIC
WORD	Epg Name
<101-4000>	Leaf ID

Command Mode: exec : Exec Mode

Command Path:

```
# show resource conflict encap-vlan epg <WORD> node <101-4000>
```

show role

show role

Description: Show information about AAA Roles

Command Mode: exec : Exec Mode

Command Path:

```
# show role
```

show rsa-server

show rsa-server

Description: Show RSA server information

Command Mode: exec : Exec Mode

Command Path:

```
# show rsa-server
```

show running-config

show running-config [all] <scope>

Description: Show running configuration

Syntax:

all	(Optional) Show running-config with defaults
<*scope*>	command scope

Command Mode: exec : Exec Mode

Command Path:

```
# show running-config [all] <scope>
```

show sessions

show sessions [id <log-id>] [action action<action-type>] [user <user-name>] [last-minutes <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] <scope>

Description: Show session-log information

Syntax:

<*log-id*>	(Optional) Log ID
action<*action-type*>	(Optional) Object action indicator
<*user-name*>	(Optional) Name of user
<*num-minutes*>	(Optional) Logs created in time interval. Number range from 1 to 59
<*num-hours*>	(Optional) Logs created in time interval. Number range from 1 to 23
<*num-days*>	(Optional) Logs created in time interval. Number range from 1 to 999
<*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Logs created in time interval
end-time <*YYYY-MM-DDTHR:MIN:SEC*>	(Optional) Logs created in time interval
detail	(Optional) Detailed session-log information. Displays the action trigger that shows why a login occurred.
<*scope*>	command scope

Command Mode: exec : Exec Mode

Command Path:

```
# show sessions [id <log-id>] [action action<action-type>] [user <user-name>] [last-minutes
 <NUMBER>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>]
 [end-time end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] <scope>
```

show sessions controller

show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller

Description: Show controller information

Command Mode: exec : Exec Mode

Command Path:

```
# show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>]
 [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>]
 [detail] controller
```

show sessions controller detail

show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] controller detail [id <node-id>]

Description: Detailed controller information

Syntax:

node-id	(Optional) Optional Serial number

Command Mode: exec : Exec Mode

Command Path:

```
# show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>]
 [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>]
 [detail] controller detail [id <node-id>]
```

show sessions leaf

show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] leaf <leafId>

Description: Show command for leaf

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>]
 [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>]
 [detail] leaf <leafId>
```

show sessions spine

show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>] [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>] [detail] spine <leafId>

Description: Show command for spine

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show sessions [id <log-id>] [action <action-type>] [user <user-name>] [last-hours <NUMBER>]
 [last-days <NUMBER>] [start-time <YYYY-MM-DDTHR:MIN:SEC>] [end-time <YYYY-MM-DDTHR:MIN:SEC>]
 [detail] spine <leafId>
```

show snapshot active

show snapshot active job

Description: Show command for active snapshot job

Syntax:

job	View active snapshot job

Command Mode: exec : Exec Mode

Command Path:

```
# show snapshot active job
```

show snapshot files

show snapshot files

Description: Show command for snapshot files

Command Mode: exec : Exec Mode

Command Path:

```
# show snapshot files
```

show snapshot jobs

show snapshot jobs <WORD>

Description: Show command for snapshot jobs

Syntax:

WORD	Snapshot policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snapshot jobs <WORD>
```

show snmp

show snmp [policy <policy>]

Description: Show snmp policy information

Syntax:

policy	(Optional) SNMP policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snmp [policy <policy>]
```

show snmp clientgroups

show snmp [policy <policy>] clientgroups

Description: Show snmp client group policies

Syntax:

policy	(Optional) SNMP policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snmp [policy <policy>] clientgroups
```

show snmp community

show snmp [policy <policy>] community

Description: Show snmp community information

Syntax:

policy	(Optional) SNMP policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snmp [policy <policy>] community
```

show snmp engineid

show snmp [policy <policy>] engineid

Description: Show snmp v3 engine-id

Syntax:

policy	(Optional) SNMP policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snmp [policy <policy>] engineid
```

show snmp hosts

show snmp [policy <policy>] hosts

Description: Show snmp trap hosts

Syntax:

policy	(Optional) SNMP policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snmp [policy <policy>] hosts
```

show snmp summary

show snmp [policy <policy>] summary

Description: Show snmp summary

Syntax:

policy	(Optional) SNMP policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snmp [policy <policy>] summary
```

show snmp users

show snmp [policy <policy>] users

Description: Show snmp v3 users

Syntax:

policy	(Optional) SNMP policy name

Command Mode: exec : Exec Mode

Command Path:

```
# show snmp [policy <policy>] users
```

show stats

show stats granularity <granularity-value> [history] [cumulative] tenant|leaf|spine

Description: Show statistics

Syntax:

granularity	Choose granularity value
<granularity-value>	<granularity-value>
history	(Optional) historical stats information
cumulative	(Optional) cumulative stats information
tenant	command scope
leaf	command scope
spine	command scope

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant|leaf|spine
```

show stats granularity communication controller

show stats granularity <granularity-value> [history] [cumulative] communication controller node-id

Description: Show command for nginx web-requests

Syntax:

node-id	node-id

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] communication controller
 node-id
```

show stats granularity leaf

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId>

Description: Show command for leaf

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId>
```

show stats granularity leaf fex

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> fex <fexNum>

Description: Show extended chassis information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> fex
<fexNum>
```

show stats granularity leaf fex module

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> fex <fexNum> module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*fexNum*>	pls enter fex number
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> fex
<fexNum> module <lcSlot>
```

show stats granularity leaf interface ethernet

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface
 ethernet <phyInt>
```

show stats granularity leaf interface fc

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface fc <phyInt>

Description: Fibre Channel Protocol

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface
 fc <phyInt>
```

show stats granularity leaf interface fcportchannel

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface fcportchannel <portChan>

Description: FC Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface
 fcportchannel <portChan>
```

show stats granularity leaf interface mgmt

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface
 mgmt <mgmtPort>
```

show stats granularity leaf interface portchannel

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface portchannel <portChan>

Description: Port channel interface

Syntax:

<*leafId*>	Leaf id
<*portChan*>	<Port channel number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface
 portchannel <portChan>
```

show stats granularity leaf interface vethernet

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface vethernet <phyInt>

Description: vethernet ID

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> interface
 vethernet <phyInt>
```

show stats granularity leaf inventory chassis

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory
 chassis
```

show stats granularity leaf inventory fans

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory
 fans <ftSlot>
```

show stats granularity leaf inventory powersupply

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory
 powersupply <psuSlot>
```

show stats granularity leaf inventory supervisor

show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] leaf <leafId> inventory
 supervisor <supMod>
```

show stats granularity spine

show stats granularity <granularity-value> [history] [cumulative] spine <leafId>

Description: Show command for spine

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId>
```

show stats granularity spine interface ethernet

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> interface ethernet <phyInt>

Description: Ethernet IEEE 802.3z

Syntax:

<*leafId*>	Leaf id
<*phyInt*>	<slot or chassis-number/port or slot number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> interface
 ethernet <phyInt>
```

show stats granularity spine interface mgmt

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> interface mgmt <mgmtPort>

Description: Management interface

Syntax:

<*leafId*>	Leaf id
<*mgmtPort*>	<Management interface number>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> interface
 mgmt <mgmtPort>
```

show stats granularity spine inventory chassis

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory chassis

Description: Show inventory chassis information

Syntax:

<*leafId*>	Leaf id

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory
 chassis
```

show stats granularity spine inventory fabric

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory fabric <fcMod>

Description: Show information for fabric module

Syntax:

<*leafId*>	Leaf id
<*fcMod*>	pls enter the fabric module number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory
 fabric <fcMod>
```

show stats granularity spine inventory fans

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory fans <ftSlot>

Description: Show inventory fan information

Syntax:

<*leafId*>	Leaf id
<*ftSlot*>	pls enter fan tray number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory
 fans <ftSlot>
```

show stats granularity spine inventory module

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory module <lcSlot>

Description: Show inventory module information

Syntax:

<*leafId*>	Leaf id
<*lcSlot*>	please enter the module number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory
 module <lcSlot>
```

show stats granularity spine inventory powersupply

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory powersupply <psuSlot>

Description: Show inventory power supply information

Syntax:

<*leafId*>	Leaf id
<*psuSlot*>	pls enter the powersupply number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory
 powersupply <psuSlot>
```

show stats granularity spine inventory supervisor

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory supervisor <supMod>

Description: Show information for supervisor module

Syntax:

<*leafId*>	Leaf id
<*supMod*>	pls enter the supervisor module number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory
 supervisor <supMod>
```

show stats granularity spine inventory system

show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory system <sysMod>

Description: Show information for system module

Syntax:

<*leafId*>	Leaf id
<*sysMod*>	pls enter the system module number

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] spine <leafId> inventory
 system <sysMod>
```

show stats granularity tenant

show stats granularity <granularity-value> [history] [cumulative] tenant WORD

Description: Show Tenants Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD
```

show stats granularity tenant application

show stats granularity <granularity-value> [history] [cumulative] tenant WORD application WORD

Description: Show Application Profiles Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD application
 WORD
```

show stats granularity tenant application epg

show stats granularity <granularity-value> [history] [cumulative] tenant WORD application WORD epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD application
 WORD epg WORD
```

show stats granularity tenant application esg

show stats granularity <granularity-value> [history] [cumulative] tenant WORD application WORD esg WORD

Description: Show Show Endpoint Security Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD application
 WORD esg WORD
```

show stats granularity tenant dnsservergroup

show stats granularity <granularity-value> [history] [cumulative] tenant WORD dnsservergroup WORD

Description: Show Dns Server Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD dnsservergroup
 WORD
```

show stats granularity tenant dnsservergroup server

show stats granularity <granularity-value> [history] [cumulative] tenant WORD dnsservergroup WORD server WORD

Description: Show Dns Server Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD dnsservergroup
 WORD server WORD
```

show stats granularity tenant dnsservergroup server domain

show stats granularity <granularity-value> [history] [cumulative] tenant WORD dnsservergroup WORD server WORD domain WORD

Description: Show Dns Domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)
WORD	Domain we eventually want to filter on (Max Size 512)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD dnsservergroup
 WORD server WORD domain WORD
```

show stats granularity tenant dot1q-tunnel

show stats granularity <granularity-value> [history] [cumulative] tenant WORD dot1q-tunnel WORD

Description: Show Dot1q-tunnel Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the TnlEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD dot1q-tunnel
 WORD
```

show stats granularity tenant multicast-route-maps

show stats granularity <granularity-value> [history] [cumulative] tenant WORD multicast-route-maps

Description: Show multicast route-maps per Tenant

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD
multicast-route-maps
```

show stats granularity tenant vrf

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD

Description: Show VRF Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
```

show stats granularity tenant vrf acllog l2

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>

Description: L2 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flowi stats
vlan	vlan info
<*vlan*>	<vlan>. Number range from=0 to=9223372036854775807
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>
```

show stats granularity tenant vrf acllog l3

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport <dstport> srcintf <srcintf>

Description: L3 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flow stats
srcpctag	source pc tag
<*srcpctag*>	<srcpctag>
dstpctag	destination pc tag
<*dstpctag*>	<dstpctag>
srcepgname	source epg name
<*srcepgname*>	<srcepgname>
dstepgname	destination epg name
<*dstepgname*>	<dstepgname>
srcip	source ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
dstip	destination ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
proto	protocol
<*proto*>	<proto>
srcport	source port
<*srcport*>	<srcport>
dstport	destination port
<*dstport*>	<dstport>

srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname>
 dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto
<proto> srcport <srcport> dstport <dstport> srcintf <srcintf>
```

show stats granularity tenant vrf detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD detail

Description: Show detailed view of VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
detail
```

show stats granularity tenant vrf external-l3 bgp

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 bgp

Description: Show command for BGP peers

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 bgp
```

show stats granularity tenant vrf external-l3 bgp node

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 bgp node <101-4000>

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<101-4000>	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 bgp node <101-4000>
```

show stats granularity tenant vrf external-l3 eigrp

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 eigrp

Description: Show external l3 EIGRP

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 eigrp
```

show stats granularity tenant vrf external-l3 eigrp detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 eigrp detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 eigrp detail
```

show stats granularity tenant vrf external-l3 epg

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 epg <epgName>

Description: Show command for external-l3 epgs

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 epg <epgName>
```

show stats granularity tenant vrf external-l3 epg detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 epg <epgName> detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 epg <epgName> detail
```

show stats granularity tenant vrf external-l3 interfaces

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 interfaces

Description: Show tenant <tenant> vrf <vrf> external l3 interfaces

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 interfaces
```

show stats granularity tenant vrf external-l3 interfaces detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 interfaces detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 interfaces detail
```

show stats granularity tenant vrf external-l3 ospf

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 ospf

Description: Show command for IPv4 and IPv6 external l3 OSPF configuration

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 ospf
```

show stats granularity tenant vrf external-l3 ospf detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 ospf detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 ospf detail
```

show stats granularity tenant vrf external-l3 scale

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 scale

Description: scale command

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 scale
```

show stats granularity tenant vrf external-l3 scale detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 scale detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 scale detail
```

show stats granularity tenant vrf external-l3 static-route

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 static-route

Description: Show command for external-l3 static routes

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 static-route
```

show stats granularity tenant vrf external-l3 static-route detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 static-route detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 static-route detail
```

show stats granularity tenant vrf external-l3 static-route node

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 static-route node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 static-route node
```

show stats granularity tenant vrf external-l3 static-route node detail

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD external-l3 static-route node detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
external-l3 static-route node detail
```

show stats granularity tenant vrf ipv6multicast

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD ipv6multicast

Description: Show ipv6 multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
ipv6multicast
```

show stats granularity tenant vrf multicast

show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD multicast

Description: Show multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show stats granularity <granularity-value> [history] [cumulative] tenant WORD vrf WORD
multicast
```

show switch

show switch

Description: Show switch information

Command Mode: exec : Exec Mode

Command Path:

```
# show switch
```

show switch detail

show switch detail [id <switch-id>]

Description: Show switch detailed information

Syntax:

switch-id	(Optional) Optional switch id. Number range from=0 to=9223372036854775807

Command Mode: exec : Exec Mode

Command Path:

```
# show switch detail [id <switch-id>]
```

show tacacs-server

show tacacs-server

Description: Show tacacs server information

Command Mode: exec : Exec Mode

Command Path:

```
# show tacacs-server
```

show techsupport all

show techsupport all status

Description: Techsupport status for all

Syntax:

status	Status

Command Mode: exec : Exec Mode

Command Path:

```
# show techsupport all status
```

show techsupport controllers

show techsupport controllers status

Description: Techsupport status for controllers

Syntax:

status	Status

Command Mode: exec : Exec Mode

Command Path:

```
# show techsupport controllers status
```

show techsupport host

show techsupport host <NUMBER> status

Description: Techsupport status for host

Syntax:

<*Odevid*>	Specify the host Odev ID. Number range from=0 to=9223372036854775807
status	Status

Command Mode: exec : Exec Mode

Command Path:

```
# show techsupport host <NUMBER> status
```

show techsupport switch

show techsupport switch switchId <switchId> status

Description: Techsupport status for switch

Syntax:

switchId <switchId>	switch id 101-4000 or range(s): 101-103,104
status	Status

Command Mode: exec : Exec Mode

Command Path:

```
# show techsupport switch switchId <switchId> status
```

show tenant

show tenant WORD

Description: Show Tenants Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD
```

show tenant access-list

show tenant WORD access-list WORD

Description: Show Access-list Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the Contract to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD access-list WORD
```

show tenant application

show tenant WORD application WORD

Description: Show Application Profiles Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD
```

show tenant application endpoints

show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]

Description: Show IP endpoints

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE
EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]
```

show tenant application endpoints leaf interface ethernet

show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface ethernet ethernet [<fex>/]<slot>/<port>

Description: Show IP endpoints on an interface ethernet

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
ethernet [<fex>/]<slot>/<port>	Ethernet Range

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE
EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf
<WORD> interface ethernet ethernet [<fex>/]<slot>/<port>
```

show tenant application endpoints leaf interface port-channel

show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface port-channel <WORD> [fex <NUMBER>]

Description: Show IP endpoints on an interface port-channel

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Port Channel Name (Max Size 64)
<101-199>	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE
EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf
<WORD> interface port-channel <WORD> [fex <NUMBER>]
```

show tenant application endpoints vpc

show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc context <WORD> <WORD> interface vpc <WORD> [fex <fex>]

Description: Show IP endpoints on vpc

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
context	VPC Context
WORD	First VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Second VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
interface	VPC Interface name
vpc	VPC Interface name
WORD	VPC Name (Max Size 64)
fex	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE
EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc
context <WORD> <WORD> interface vpc <WORD> [fex <fex>]
```

show tenant application epg

show tenant WORD application WORD epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD epg WORD
```

show tenant application epg detail

show tenant WORD application WORD epg WORD detail

Description: Show detailed view of Application EPg

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD epg WORD detail
```

show tenant application epg endpoints

show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]

Description: Show IP endpoints

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E
EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>]
```

show tenant application epg endpoints leaf interface ethernet

show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface ethernet ethernet [<fex>/]<slot>/<port>

Description: Show IP endpoints on an interface ethernet

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
ethernet [<fex>/]<slot>/<port>	Ethernet Range

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E
EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>] leaf <WORD> interface ethernet ethernet [<fex>/]<slot>/<port>
```

show tenant application epg endpoints leaf interface port-channel

show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface port-channel <WORD> [fex <NUMBER>]

Description: Show IP endpoints on an interface port-channel

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Port Channel Name (Max Size 64)
<101-199>	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E
EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>] leaf <WORD> interface port-channel <WORD> [fex <NUMBER>]
```

show tenant application epg endpoints vpc

show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc context <WORD> <WORD> interface vpc <WORD> [fex <fex>]

Description: Show IP endpoints on vpc

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the AEPG to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
context	VPC Context
WORD	First VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Second VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
interface	VPC Interface name
vpc	VPC Interface name
WORD	VPC Name (Max Size 64)
fex	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD epg WORD endpoints [type <type>] [mac <E.E.E
EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>] vpc context <WORD> <WORD> interface vpc <WORD> [fex <fex>]
```

show tenant application esg

show tenant WORD application WORD esg WORD

Description: Show Show Endpoint Security Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD esg WORD
```

show tenant application esg detail

show tenant WORD application WORD esg WORD detail

Description: Show detailed view of Endpoint Security Group

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD esg WORD detail
```

show tenant application esg endpoints

show tenant WORD application WORD esg WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]

Description: Show IP endpoints

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the application we eventually want to filter on (Max Size 64)
WORD	Name of the ESG to filter on (Max Size 64)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD application WORD esg WORD endpoints [type <type>] [mac <E.E.E
EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6
 <A:B::C:D>]
```

show tenant bridge-domain

show tenant WORD bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD bridge-domain WORD
```

show tenant bridge-domain detail

show tenant WORD bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD bridge-domain WORD detail
```

show tenant bridge-domain first-hop-security binding-table

show tenant WORD bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD bridge-domain WORD first-hop-security binding-table
```

show tenant bridge-domain first-hop-security statistics arp

show tenant WORD bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD bridge-domain WORD first-hop-security statistics arp
```

show tenant bridge-domain first-hop-security statistics dhcpv4

show tenant WORD bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD bridge-domain WORD first-hop-security statistics dhcpv4
```

show tenant bridge-domain first-hop-security statistics dhcpv6

show tenant WORD bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD bridge-domain WORD first-hop-security statistics dhcpv6
```

show tenant bridge-domain first-hop-security statistics neighbor-discovery

show tenant WORD bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD bridge-domain WORD first-hop-security statistics neighbor-discovery
```

show tenant contract-type

show tenant WORD contract-type WORD

Description: Show Contracts Information Based on Type

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	whitelist (permit) or blacklist(deny) or oob-mgmt type of contract

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD contract-type WORD
```

show tenant contract

show tenant WORD contract WORD

Description: Show Contracts Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the Contract to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD contract WORD
```

show tenant detail

show tenant WORD detail

Description: Show detailed view of tenant

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD detail
```

show tenant dnsservergroup

show tenant WORD dnsservergroup WORD

Description: Show Dns Server Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD dnsservergroup WORD
```

show tenant dnsservergroup server

show tenant WORD dnsservergroup WORD server WORD

Description: Show Dns Server Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD dnsservergroup WORD server WORD
```

show tenant dnsservergroup server domain

show tenant WORD dnsservergroup WORD server WORD domain WORD

Description: Show Dns Domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the dns server group we eventually want to filter on (Max Size 16)
WORD	IP of server we eventually want to filter on (Max Size None)
WORD	Domain we eventually want to filter on (Max Size 512)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD dnsservergroup WORD server WORD domain WORD
```

show tenant dot1q-tunnel

show tenant WORD dot1q-tunnel WORD

Description: Show Dot1q-tunnel Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the TnlEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD dot1q-tunnel WORD
```

show tenant endpoints

show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]

Description: Show IP endpoints

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE
 EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>]
```

show tenant endpoints leaf interface ethernet

show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface ethernet ethernet [<fex>/]<slot>/<port>

Description: Show IP endpoints on an interface ethernet

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
ethernet [<fex>/]<slot>/<port>	Ethernet Range

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE
 EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface
ethernet ethernet [<fex>/]<slot>/<port>
```

show tenant endpoints leaf interface port-channel

show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface port-channel <WORD> [fex <NUMBER>]

Description: Show IP endpoints on an interface port-channel

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
WORD	Leaf Number (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Port Channel Name (Max Size 64)
<101-199>	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE
 EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] leaf <WORD> interface
port-channel <WORD> [fex <NUMBER>]
```

show tenant endpoints vpc

show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc context <WORD> <WORD> interface vpc <WORD> [fex <fex>]

Description: Show IP endpoints on vpc

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
type	(Optional) Endpoint Type
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)
<1-4094>	(Optional) Encapsulation Vlan. Number range from=1 to=4094
A.B.C.D	(Optional) IP Unicast address in format i.i.i.i
A:B::C:D	(Optional) IPv6 address in format xxxx:xxxx, xxxx::xx
context	VPC Context
WORD	First VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
WORD	Second VPC leaf (Max Size 4000). Number range from=0 to=9223372036854775807
interface	VPC Interface name
vpc	VPC Interface name
WORD	VPC Name (Max Size 64)
fex	(Optional) Fex Id. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD endpoints [type <type>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE
 EEEE.EEEE.EEEE >] [vlan <NUMBER>] [ip <A.B.C.D>] [ipv6 <A:B::C:D>] vpc context <WORD>
<WORD> interface vpc <WORD> [fex <fex>]
```

show tenant epg

show tenant WORD epg WORD

Description: Show Application EPG Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD epg WORD
```

show tenant epg detail

show tenant WORD epg WORD detail

Description: Show detailed view of Application EPg

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the AEPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD epg WORD detail
```

show tenant esg

show tenant WORD esg WORD

Description: Show Endpoint Security Group Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD esg WORD
```

show tenant esg detail

show tenant WORD esg WORD detail

Description: Show detailed view of Endpoint Security Group

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the ESG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD esg WORD detail
```

show tenant external-l2 epg

show tenant WORD external-l2 epg WORD

Description: Show command for external-l2 epgs

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the EPG to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD external-l2 epg WORD
```

show tenant interface bridge-domain

show tenant WORD interface bridge-domain WORD

Description: Show Bridge-domain Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD interface bridge-domain WORD
```

show tenant interface bridge-domain detail

show tenant WORD interface bridge-domain WORD detail

Description: Show Bridge-domain Detailed Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD interface bridge-domain WORD detail
```

show tenant interface bridge-domain first-hop-security binding-table

show tenant WORD interface bridge-domain WORD first-hop-security binding-table

Description: Show Bridge-domain Binding Table Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD interface bridge-domain WORD first-hop-security binding-table
```

show tenant interface bridge-domain first-hop-security statistics arp

show tenant WORD interface bridge-domain WORD first-hop-security statistics arp

Description: Show Bridge-domain First Hop Security ARP Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD interface bridge-domain WORD first-hop-security statistics arp
```

show tenant interface bridge-domain first-hop-security statistics dhcpv4

show tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv4

Description: Show Bridge-domain First Hop Security DHCPv4 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv4
```

show tenant interface bridge-domain first-hop-security statistics dhcpv6

show tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv6

Description: Show Bridge-domain First Hop Security DHCPv6 Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD interface bridge-domain WORD first-hop-security statistics dhcpv6
```

show tenant interface bridge-domain first-hop-security statistics neighbor-discovery

show tenant WORD interface bridge-domain WORD first-hop-security statistics neighbor-discovery

Description: Show Bridge-domain First Hop Security Neighbor Discovery Statistics

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD interface bridge-domain WORD first-hop-security statistics
neighbor-discovery
```

show tenant ip interface bridge-domain

show tenant WORD ip interface bridge-domain WORD

Description: Show command for IP properties on interface BD

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD ip interface bridge-domain WORD
```

show tenant ipv6 interface bridge-domain

show tenant WORD ipv6 interface bridge-domain WORD

Description: Show command for IP properties on interface BD

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the bridge-domain (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD ipv6 interface bridge-domain WORD
```

show tenant multicast-route-maps

show tenant WORD multicast-route-maps

Description: Show multicast route-maps per Tenant

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD multicast-route-maps
```

show tenant policy-map

show tenant WORD policy-map

Description: Show policy maps

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD policy-map
```

show tenant policy-map type data-plane

show tenant WORD policy-map type data-plane WORD [stats]

Description: Data-plane type policy-map(s)

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	data-plane type policy-map(s) (Max Size 64)
stats	(Optional) Data-Plane Policer Statistics, where available

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD policy-map type data-plane WORD [stats]
```

show tenant policy-map type qos

show tenant WORD policy-map type qos WORD

Description: QOS type policy-map(s)

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	QOS type policy-map(s) (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD policy-map type qos WORD
```

show tenant vrf

show tenant WORD vrf WORD

Description: Show VRF Information

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD
```

show tenant vrf acllog l2

show tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>

Description: L2 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flowi stats
vlan	vlan info
<*vlan*>	<vlan>. Number range from=0 to=9223372036854775807
srcintf	source interface
<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD acllog <permitDrop> l2 flow vlan <NUMBER> srcintf <srcintf>
```

show tenant vrf acllog l3

show tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag <dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport <dstport> srcintf <srcintf>

Description: L3 flow stats

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
permitDrop	permitDrop
flow	flow stats
srcpctag	source pc tag
<*srcpctag*>	<srcpctag>
dstpctag	destination pc tag
<*dstpctag*>	<dstpctag>
srcepgname	source epg name
<*srcepgname*>	<srcepgname>
dstepgname	destination epg name
<*dstepgname*>	<dstepgname>
srcip	source ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
dstip	destination ip
A.B.C.D or A:B::C:D	IP address in format i.i.i.i or IPv6 address in format xxxx:xxxx, xxxx::xx
proto	protocol
<*proto*>	<proto>
srcport	source port
<*srcport*>	<srcport>
dstport	destination port
<*dstport*>	<dstport>
srcintf	source interface

<*srcintf*>	<srcintf>

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD acllog <permitDrop> l3 flow srcpctag <srcpctag> dstpctag
<dstpctag> srcepgname <srcepgname> dstepgname <dstepgname> srcip <A.B.C.D or A:B::C:D> dstip
 <A.B.C.D or A:B::C:D> proto <proto> srcport <srcport> dstport <dstport> srcintf <srcintf>
```

show tenant vrf detail

show tenant WORD vrf WORD detail

Description: Show detailed view of VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD detail
```

show tenant vrf external-l3 bgp

show tenant WORD vrf WORD external-l3 bgp

Description: Show command for BGP peers

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 bgp
```

show tenant vrf external-l3 bgp node

show tenant WORD vrf WORD external-l3 bgp node <101-4000>

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<101-4000>	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 bgp node <101-4000>
```

show tenant vrf external-l3 eigrp

show tenant WORD vrf WORD external-l3 eigrp

Description: Show external l3 EIGRP

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 eigrp
```

show tenant vrf external-l3 eigrp detail

show tenant WORD vrf WORD external-l3 eigrp detail

Description: Show interanl details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 eigrp detail
```

show tenant vrf external-l3 epg

show tenant WORD vrf WORD external-l3 epg <epgName>

Description: Show command for external-l3 epgs

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<*epgName*>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 epg <epgName>
```

show tenant vrf external-l3 epg detail

show tenant WORD vrf WORD external-l3 epg <epgName> detail

Description: external-l3 epg in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<epgName>	Name of the EPG to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 epg <epgName> detail
```

show tenant vrf external-l3 interfaces

show tenant WORD vrf WORD external-l3 interfaces

Description: Show tenant <tenant> vrf <vrf> external l3 interfaces

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 interfaces
```

show tenant vrf external-l3 interfaces detail

show tenant WORD vrf WORD external-l3 interfaces detail

Description: Show interfaces details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 interfaces detail
```

show tenant vrf external-l3 ospf

show tenant WORD vrf WORD external-l3 ospf

Description: Show command for IPv4 and IPv6 external l3 OSPF configuration

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 ospf
```

show tenant vrf external-l3 ospf detail

show tenant WORD vrf WORD external-l3 ospf detail

Description: Show internal details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 ospf detail
```

show tenant vrf external-l3 route-map

show tenant WORD vrf WORD external-l3 route-map [name <l3out name>]

Description: Show command for external-l3 route-map

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<l3out name>	(Optional) Name of the route-map to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 route-map [name <l3out name>]
```

show tenant vrf external-l3 route-map detail

show tenant WORD vrf WORD external-l3 route-map [name <l3out name>] detail

Description: Show external-l3 route-map in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
<l3out name>	(Optional) Name of the route-map to filter on

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 route-map [name <l3out name>] detail
```

show tenant vrf external-l3 scale

show tenant WORD vrf WORD external-l3 scale

Description: scale command

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 scale
```

show tenant vrf external-l3 scale detail

show tenant WORD vrf WORD external-l3 scale detail

Description: Show scale details

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 scale detail
```

show tenant vrf external-l3 static-route

show tenant WORD vrf WORD external-l3 static-route

Description: Show command for external-l3 static routes

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 static-route
```

show tenant vrf external-l3 static-route detail

show tenant WORD vrf WORD external-l3 static-route detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 static-route detail
```

show tenant vrf external-l3 static-route node

show tenant WORD vrf WORD external-l3 static-route node

Description: node to filter on

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 static-route node
```

show tenant vrf external-l3 static-route node detail

show tenant WORD vrf WORD external-l3 static-route node detail

Description: static-route in detail with operational status

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)
arg	Leaf Range or Leaf Name List

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD external-l3 static-route node detail
```

show tenant vrf ipv6multicast

show tenant WORD vrf WORD ipv6multicast

Description: Show ipv6 multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD ipv6multicast
```

show tenant vrf multicast

show tenant WORD vrf WORD multicast

Description: Show multicast configuration per VRF

Syntax:

WORD	Name of the tenant to filter on (Max Size 63)
WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show tenant WORD vrf WORD multicast
```

show track-ipsla

show track-ipsla

Description: Show ipsla object ID details

Command Mode: exec : Exec Mode

Command Path:

```
# show track-ipsla
```

show track-objects

show track-objects

Description: Show track object ID details

Command Mode: exec : Exec Mode

Command Path:

```
# show track-objects
```

show troubleshoot session

show troubleshoot session <session_name>

Description: Show session

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name>
```

show troubleshoot session atomiccounter

show troubleshoot session <session_name> atomiccounter

Description: Show atomic counters

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> atomiccounter
```

show troubleshoot session audit

show troubleshoot session <session_name> audit

Description: Show audit

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> audit
```

show troubleshoot session contracts

show troubleshoot session <session_name> contracts

Description: Show contracts

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> contracts
```

show troubleshoot session deployments

show troubleshoot session <session_name> deployments

Description: Show deployment changes

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> deployments
```

show troubleshoot session events

show troubleshoot session <session_name> events

Description: Show events

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> events
```

show troubleshoot session faults

show troubleshoot session <session_name> faults

Description: Show faults

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> faults
```

show troubleshoot session latency

show troubleshoot session <session_name> latency

Description: Show latency stats

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> latency
```

show troubleshoot session monitor

show troubleshoot session <session_name> monitor

Description: Show monitor

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> monitor
```

show troubleshoot session reports

show troubleshoot session <session_name> reports

Description: Show reports

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> reports
```

show troubleshoot session statistics

show troubleshoot session <session_name> statistics

Description: Show statistics

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> statistics
```

show troubleshoot session topology

show troubleshoot session <session_name> topology

Description: Show topology

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> topology
```

show troubleshoot session traceroute

show troubleshoot session <session_name> traceroute

Description: Show traceroute

Syntax:

session_name	Session name

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot session <session_name> traceroute
```

show troubleshoot sessions

show troubleshoot sessions

Description: Show sessions

Command Mode: exec : Exec Mode

Command Path:

```
# show troubleshoot sessions
```

show upgrade-timeline controller

show upgrade-timeline controller

Description: show upgrade-timeline for controller

Command Mode: exec : Exec Mode

Command Path:

```
# show upgrade-timeline controller
```

show upgrade-timeline summary

show upgrade-timeline summary

Description: show upgrade-timeline summary

Command Mode: exec : Exec Mode

Command Path:

```
# show upgrade-timeline summary
```

show upgrade-timeline switch

show upgrade-timeline switch <NUMBER>

Description: show upgrade-timeline for a switch

Syntax:

switchId <switchId>	switch id. Number range from=101 to=4000

Command Mode: exec : Exec Mode

Command Path:

```
# show upgrade-timeline switch <NUMBER>
```

show upgradeissues controller

show upgradeissues controller

Description: Show APIC controller upgrade information.

Command Mode: exec : Exec Mode

Command Path:

```
# show upgradeissues controller
```

show username

show username <WORD>

Description: Show user information

Syntax:

WORD	User name

Command Mode: exec : Exec Mode

Command Path:

```
# show username <WORD>
```

show username detail

show username <WORD> detail

Description: Show user information

Syntax:

WORD	User name

Command Mode: exec : Exec Mode

Command Path:

```
# show username <WORD> detail
```

show versions

show versions

Description: Show version information

Command Mode: exec : Exec Mode

Command Path:

```
# show versions
```

show vlan-domain

show vlan-domain [name <arg>] [vlan] [leaf <arg>] [detail]

Description: Show command for vlan-domain

Syntax:

arg	(Optional) Vlan-domain name
<*vlan-range*>	(Optional) VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
arg	(Optional) Leaf id. Number range from=101 to=4000
detail	(Optional) vlan-domain in detail with concrete MOs

Command Mode: exec : Exec Mode

Command Path:

```
# show vlan-domain [name <>] [vlan] [leaf <>] [detail]
```

show vmware domain

show vmware domain

Description: Show VMware domain information

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain
```

show vmware domain name

show vmware domain name <name>

Description: VMware domain name

Syntax:

<*name*>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name>
```

show vmware domain name epg

show vmware domain name <name> epg

Description: Show VMware domain EPG details

Syntax:

<*name*>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name> epg
```

show vmware domain name esx

show vmware domain name <name> esx <esx-ip>

Description: Show VMware ESX information

Syntax:

<*name*>	VMware domain name
<*esx-ip*>	ESX IP

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name> esx <esx-ip>
```

show vmware domain name port-group

show vmware domain name <name> port-group

Description: Show VMware port group information

Syntax:

<*name*>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name> port-group
```

show vmware domain name trunk-portgroup

show vmware domain name <name> trunk-portgroup [name <name>]

Description: Show VMware domain trunk portgroup details

Syntax:

<*name*>	VMware domain name
<*name*>	(Optional) trunk portgroup name

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name> trunk-portgroup [name <name>]
```

show vmware domain name vcenter

show vmware domain name <name> vcenter <hostname|ip>

Description: VMware vCenter ip or hostname

Syntax:

<*name*>	VMware domain name
<*hostname*|*ip*>	vCenter hostname or IP

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name> vcenter <hostname|ip>
```

show vmware domain name vm

show vmware domain name <name> vm

Description: Show VMware VM information

Syntax:

<*name*>	VMware domain name

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name> vm
```

show vmware domain name vm name

show vmware domain name <name> vm name <vm-name>

Description: Show detailed VMware VM information

Syntax:

<*name*>	VMware domain name
<*vm-name*>	VM Name

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware domain name <name> vm name <vm-name>
```

show vmware vm

show vmware vm [name <WORD>] [ip <A.B.C.D>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE >]

Description: Show VMware VM information

Syntax:

WORD	(Optional) Specify a VM name
A.B.C.D	(Optional) IP address in format i.i.i.i
E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE EEEE.EEEE.EEEE	(Optional) MAC address (Option 1) MAC address (Option 2) MAC address (Option 3) MAC address (Option 4)

Command Mode: exec : Exec Mode

Command Path:

```
# show vmware vm [name <WORD>] [ip <A.B.C.D>] [mac <E.E.E EE-EE-EE-EE-EE-EE EE:EE:EE:EE:EE:EE
 EEEE.EEEE.EEEE >]
```

show vpc

show vpc map <vpc-list>

Description: Show vpc mapping

Syntax:

map	Map by name
<*vpc-list*>	vpc names

Command Mode: exec : Exec Mode

Command Path:

```
# show vpc map <vpc-list>
```

show vpc map leaf

show vpc map <vpc-list> leaf WORD [fex <NUMBER>]

Description: Leaf

Syntax:

map	Map by name
<vpc-list>	vpc names
WORD	Leaf Range or Leaf Name List
<101-199>	(Optional) Fex ID. Number range from=101 to=199

Command Mode: exec : Exec Mode

Command Path:

```
# show vpc map <vpc-list> leaf WORD [fex <NUMBER>]
```

show vrf

show vrf WORD

Description: Show VRF Information

Syntax:

WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show vrf WORD
```

show vrf detail

show vrf WORD detail

Description: Show detailed view of VRF

Syntax:

WORD	Name of the VRF to filter on (Max Size 64)

Command Mode: exec : Exec Mode

Command Path:

```
# show vrf WORD detail
```

show vsan-domain

show vsan-domain [name <arg>] [detail]

Description: Show command for vsan-domain

Syntax:

arg	(Optional) Vsan-domain name
detail	(Optional) Vsan-domain detailed information

Command Mode: exec : Exec Mode

Command Path:

```
# show vsan-domain [name <>] [detail]
```

sr-upgrade

sr-upgrade

Description: Check for SR Upgrade

Command Mode: switch-group : Create switch firmware upgrade policy

Command Path:

```
# configure [['terminal', 't']]
(config)# firmware
(config-firmware)# switch-group <WORD>
(config-firmware-switch)# sr-upgrade
```

sr-version

sr-version <version>

Description: Set target SR version

Syntax:

<*version*>	SR version

Command Mode: switch-group : Create switch firmware upgrade policy

Command Path:

```
# configure [['terminal', 't']]
(config)# firmware
(config-firmware)# switch-group <WORD>
(config-firmware-switch)# sr-version <version>
```

switch-group

switch-group <WORD>

Description: Create switch firmware upgrade policy

Syntax:

WORD	switch-group name (Max Size 64)

Command Mode: firmware : Firmware upgrade configuration Mode

Command Path:

```
# configure [['terminal', 't']]
(config)# firmware
(config-firmware)# switch-group <WORD>
```

switch

switch

Description: Add switches to switch group

Syntax:

arg	

Command Mode: switch-group : Create switch firmware upgrade policy

Command Path:

```
# configure [['terminal', 't']]
(config)# firmware
(config-firmware)# switch-group <WORD>
(config-firmware-switch)# switch
```

syslog

syslog <common>

Description: Syslog policy configuration mode

Syntax:

common	Syslog Src Policy Name

Command Mode: configure : Configuration Mode

Command Path:

```
# configure [['terminal', 't']]
(config)# syslog <common>
```