

Cisco Nexus 9364E-SG2 Switches

READ ME FIRST

May 6, 2025

Contents

- Introduction 2
- Scope 2
- Positioning 2
- Supported Features 2
- Cisco Nexus Dashboard Support 4
- Software Releases 4
- Platform Hardware 4
- Additional Resources 5
- Blogs 5
- Documentation Feedback 5
- Legal Information 5

Introduction

The Cisco Nexus 9364E-SG2-O and Cisco Nexus 9364E-SG2-Q switches support 64 OSFP ports and QSFP-DD ports, respectively, and use Cisco Silicon One™ ASIC. Based on Silicon One ASIC in a 2-RU form factor, these new platforms empower customers with advanced network solutions specifically tailored for AI and ML applications.

Scope

This document summarizes the current capabilities of the Cisco Nexus 9364E-SG2-O and 9364E-SG2-Q, including the current software features and hardware products.

Positioning

The next generation Nexus 9300 switches are designed to deliver high-density 64-port 800G (51.2T) aggregation. Leveraging Cisco's cutting-edge technology, users can seamlessly build both front-end and back-end networks to support a variety of AI use cases such as training and inference. This demonstrates our commitment to advancing Ethernet-based AI/ML infrastructures and addressing the evolving needs of enterprises in this domain. The switches are Ultra Ethernet Consortium (UEC) ready.

Supported Features

Beginning with the NX-OS Release 10.5(3)F, the Cisco Nexus 9364E-SG2-O and Cisco Nexus 9364E-SG2-Q switches support these software features:

Feature Type	Description
--------------	-------------

Network Interfaces and Speeds	<ul style="list-style-type: none"> • 800G, 400G, 200G, 100G • Breakouts: 8 x 100G, 2 x 400G, 4 x 100G
Network Protocols and Serviceability	<ul style="list-style-type: none"> • L2 support • Port Channaels (PC) • SVI support • L3 subinterface support • HSRP, VRRP, EIGRP, and ISIS supported • Static routes supported
Layer3 Unicast and Routing (IPv4 and IPv6)	<ul style="list-style-type: none"> • BGP, OSPF, BFD, VRF
VXLAN	<ul style="list-style-type: none"> • Spine/Leaf/Borderleaf roles • Multisite anycast BGW with L3 stretch • VXLAN with IR underlay support • ARP Suppression • Flowlet load balancing (FLLB) on VXLAN fabric
Load Balancing	<ul style="list-style-type: none"> • ECMP, DLB(Flowlet Load balancing (FLLB) and Packet Spraying) • 512 ECMP groups, 128-way ECMP • RDMA- Opcode, q-pair, PSN • Configurable flow-let aging timer • DSCP-based FLLB • WCMP + FLLB • Policy-based FLLB multiple profile support
Network Security	<ul style="list-style-type: none"> • AAA, RADIUS, TACACS+ • ACL • Ingress and egress RACL (IPV4/V6) • SSH Protocol Version 2 • SNMPv3 • PBR
Quality of Service	<ul style="list-style-type: none"> • RoCEv2 (PFC +WRED ECN) • Classification and Marking • Queuing and Scheduling

	<ul style="list-style-type: none"> • CoPP, Custom CoPP
Telemetry and Monitoring	<ul style="list-style-type: none"> • SNMPv2 • Software Telemetry <ul style="list-style-type: none"> • DME data collection • NX-API data sources • Google protocol buffer (GPB) encoding over Google Remote Procedure Call (gRPC) transport • JSON encoding over HTTP • sFlow • gNMI support • SPAN, SPAN on Drop, ERSPAN
Programmability	<ul style="list-style-type: none"> • Open NX-OS automation • Open and Native YANG Models <ul style="list-style-type: none"> • NETCONF, RESTCONF, gNMI • Python API • Tcl • Cisco NX-API
Licensing	<ul style="list-style-type: none"> • Premier, Advantage and Essentials License for appropriate features

Cisco Nexus Dashboard Support

Nexus Dashboard (ND) can provide management and automation for Cisco Nexus 9364E-SG2-Q in external fabrics in ND 3.2(2).

Software Releases

Table 1. Software Releases

NX-OS Release	Description
10.5(3)F	Release 10.5(3) was the first release to enable 800G support on Silicon One ASIC in Cisco Nexus 9364E-SG2 switches.

Platform Hardware

The Nexus 9300 Series includes many switch chassis. For a complete list of 9300 series switches, see [Cisco Nexus 9000 Series Switches Install and Upgrade Guides](#).

The site lists the currently available Nexus 93xxx Series switches, line cards, and accessories. For expanded details about these hardware products, see:

- [Cisco Nexus 9364E-SG2 Data Sheet](#)

Additional Resources

- [Cisco Nexus 9000 Series Switches Install and Upgrade Guides](#)
- [Cisco Nexus 9000 Series Switches Configuration Guides](#)
- [Cisco Nexus 9000 Series NX-OS Verified Scalability Guides](#)
- [Cisco DataCenter Networking Blueprint](#)
- [Cisco Addressing AI/ML Network Challenges-Whitepaper](#)
- [Cisco Validated Design for Data Center Networking](#)
- [Cisco Optics-to-Device Compatibility Matrix](#)

Blogs

- <https://blogs.cisco.com/datacenter/building-data-center-infrastructure-for-the-ai-revolution>
- <https://blogs.cisco.com/datacenter/unlock-the-potential-of-ai-ml-workloads-with-cisco-data-center-networks>
- <https://blogs.cisco.com/datacenter/nexus-improves-load-balancing-and-brings-uec-closer-to-adoption>

Documentation Feedback

To provide technical feedback on this document, or to report an error or omission, send your comments to nexus9k-docfeedback@cisco.com. We appreciate your feedback.

Legal Information

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL:

<http://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.