



# Cisco Nexus 3000 Series NX-OS Release Notes

Release 10.5(3)F

**Note:** The documentation set for this product strives to use bias-free language. For the purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

## Introduction

The Cisco Nexus 3000 Series NX-OS Release Notes document describes the features, issues, and exceptions of Cisco NX-OS Release 10.5(3)F software for use on Cisco Nexus 3500 and 3600 Series switches.

Date	Description
April 23, 2025	Release 10.5(3)F became available.

## New and Enhanced Software Features

### New Software Features

Cisco NX-OS Release 10.5(3)F does not include any new software features for the Cisco Nexus 3000 Series.

Product Impact	Feature	Description
Feature set	Bundle NX-OS image with EPLD Image	<p>Starting from NX-OS Release 10.5(3)F, we no longer provide a separate EPLD image. Instead, we have bundled the EPLD image with the NX-OS software images. This allows you to upgrade both NX-OS and EPLD images at the same time and decreases the installation time. We also provide you the option to skip the EPLD image and install only the NX-OS image.</p> <p>For more information, see Cisco Nexus 3600 Series NX-OS Software Upgrade and Downgrade Guide, Release 10.5(x).</p>

### New Enhanced Features

Cisco NX-OS Release 10.5(3)F does not include any new enhanced features for the Cisco Nexus 3000 Series.

## Hardware Features

Cisco NX-OS Release 10.5(3)F does not include any new hardware features for the Cisco Nexus 3000 Series.

## Release Image

Cisco Nexus 3000 Series platforms support only 64-bit image. The 64-bit Cisco NX-OS image filename begins with "nxos64-msll" (for example, nxos64-msll.10.5.1.F.bin) and this image is supported on Cisco Nexus 3600 series fixed switches and Cisco Nexus 3500-XL series switches. 32-bit image is no longer supported.

Note: Nexus 3600 supports EPLD image. Starting from 10.5(3)F, Cisco NX-OS no longer provides a separate EPLD image for Nexus 3600 series switches. Instead, the EPLD image is bundled with the NX-OS image and so the image size is correspondingly larger.

## Open Issues

There are no open issues for Cisco Nexus 3000 Series in Cisco NX-OS Release 10.5(3)F.

## Resolved Issues

Bug ID	Description
<a href="#">CSCwn87179</a>	NBM interfaces attributes missing in telemetry data streamed from N9K in 10.3(6)
<a href="#">CSCwo57693</a>	N3500XL 'show tshoot' cli provides incorrect information
<a href="#">CSCwmm60818</a>	N3500 may report 18 minutes PTP correction
<a href="#">CSCwo66309</a>	N3500XL may fail to send erspan packet after erspan egress intf changes
<a href="#">CSCwn52434</a>	N3500 aclqos hap reset causing booting loop
<a href="#">CSCwn27011</a>	NxOS IPv6 Static Route remains valid when interface to reach next-hop is down
<a href="#">CSCwn24462</a>	Error "Incorrect /dev/sda1 partition size detected" on N3K-C3524P-XL/N3K-C3548P-XL
<a href="#">CSCwn65052</a>	N3500 hardware program incorrect SG L2 ltl-index, I2 multicast not forwarded out on OIL port
<a href="#">CSCwn26391</a>	When configure "service-policy type qos input" under "system qos" the process "policyelem" crashes
<a href="#">CSCwn61776</a>	N3500 may be sending NAT untranslated packet within translated NAT flow
<a href="#">CSCwmm62915</a>	N3500 SPAN IP filter does not work with vlan source allowing all traffic to be SPAN-ed
<a href="#">CSCwmm61956</a>	n9k: Incorrect static route after NH move between VPC peers in VPC fabric peering
<a href="#">CSCwmm48004</a>	N9K: IPv6 ra trigger doesn't work as documented
<a href="#">CSCwn61112</a>	SNMP user ACL can't be removed after upgrade
<a href="#">CSCwo67684</a>	Secure Erase feature for 3548XL on 10.4 not working
<a href="#">CSCwo26549</a>	N3K-C3548P-XL / N3K-C3548P-10GX crashed unexpectedly with mtc_usd hap reset
<a href="#">CSCwo02994</a>	Print the src mac address in ipv6 DAD syslog messages

## Device Hardware

The following tables list the Cisco Nexus 3500 and Cisco Nexus 3600 Series hardware that Cisco NX-OS Release 10.5(3)F supports. For additional information about the supported hardware, see the Hardware Installation Guide for your Cisco Nexus 3500 and Cisco Nexus 3600 Series devices.

## Cisco Nexus 3500 Switches

Product ID	Description
N3K-C3524P-XL	Cisco Nexus 3524-XL switch
N3K-C3548P-XL	Cisco Nexus 3548-XL switch

## Cisco Nexus 3500 Series Fans, Fan Trays, and Power Supplies

Product ID	Description
N2200-PAC-400W	Cisco Nexus 2000 or 3000 400W AC power supply, forward airflow (port side exhaust)
N2200-PAC-400W-B	Cisco Nexus 2000 or 3000 400W AC power supply, reverse airflow (port side intake)
N2200-PDC-400W	Cisco Nexus 2000 or 3000 400W DC power supply, forward airflow (port side exhaust)
N3K-PDC-350W-B	Cisco Nexus 2000 or 3000 350W DC power supply, reverse airflow (port side intake)
NXA-FAN-30CFM-B	Cisco Nexus 2000 or 3000 individual fan, reverse airflow (port side intake)
NXA-FAN-30CFM-F	Cisco Nexus 2000 or 3000 individual fan, forward airflow (port side exhaust)

## Cisco Nexus 3550-T Switches

Product ID	Description
N35-T-48X	Cisco Nexus 3550-T switch features a console port, a Micro USB port, and a 1G RJ45 port, which can be used as management interfaces.

## Cisco Nexus 3550-T Switches Fans, Fan Trays, and Power Supplies

Product ID	Description
N35-T-FAN-PE	Fan module with port-side exhaust airflow
N35-T-FAN-PI	Fan module with port-side intake airflow
N35-T-PAC-PE	Cisco Nexus 2000 or 3000 400W AC power supply, forward airflow (port side exhaust)
N35-T-PAC-PI	Cisco Nexus 2000 or 3000 350W AC power supply, reverse airflow (port side intake)

## Cisco Nexus 3550-T Switches Fans, Fan Trays, and Power Supplies

Product ID	Description	Country
CP-PWR-CORD-AU N35-T-48X	Standard Power Cord	Australia
CAB-AC-10A-BRZ	Power Cord 10A NBR 14136 plug 3 pins	Brazil
CAB-9K12A-NA	Power Cord, 125VAC 13A NEMA 5-15 Plug, 8.2-Ft	North America
CAB-ACC	AC Power Cord, C13, NEMA 5-15P, 2.1m	

Product ID	Description	Country
CAB-C13-C14-2M	Standard Power Cable, 240 Volts, 0.02 Pounds, Length: 6.6 ft., Connectors: 1 x power IEC 320 EN 60320 C13	
CAB-N35-AC-EU	AC Power Supply Cord	Europe
CP-PWR-CORD-UK	Cisco CP-PWR-CORD-UK Transformer Power Cord, Cisco VOIP phones	United Kingdom
CAB-IND-10A	Standard Power Cord, Second End Connector Type: IEC 320 EN 60320 C13, Current Rating: 10 A	India
CAB-C13-C14-3M-IN	This is a 10ft C13 to C14 18AWG 100-250V power cable that can be used to extend the lengths of 3-pin devices that utilize a shrouded power connector.	
CAB-3P-JPN	Standard AC Power Supply Cord Nema 5-15P to C13. Length: 6 Feet/19.6 Meters	Japan
CAB-C13-C14-2M-JP	Power cable - IEC 60320 C13 to IEC 60320 C14 - 6.6 ft	
CP-PWR-CORD-SA	AC Power Supply Cord	South Africa
CP-PWR-CORD-TW	AC Power Supply Cord	Taiwan

## Cisco Nexus 3600 Switches

Product ID	Description
N3K-C3636C-R	The Cisco Nexus 3636C-R is a 1 rack unit (RU) switch with 36 100-Gigabit QSFP28 ports, 40-Gigabit QSFP, 2 management ports, 1 console port, and 1 USB port. The switch supports both port-side exhaust and port-side intake airflow schemes. The switch has two power supplies, one for operations and the other for redundancy. Both power supplies must be either AC power supplies or DC power supplies.
N3K-C36180YC-R	<p>The Cisco Nexus 36180YC-R is a 1 rack unit (RU) switch with 48 1/10/25-Gigabit SFP ports and 6 40Gigabit QSFP/100-Gigabit QSFP28 ports, 1 management port, 1 console port, and 1 USB port. The switch supports both port-side exhaust and port-side intake airflow schemes. The switch has two power supplies, one for operations and the other for redundancy. Both power supplies must be either AC power supplies or DC power supplies.</p> <p>From Cisco NX-OS Release 10.3(3)F, the following AC ports are supported on Cisco Nexus 36180YC-R (N3K-C36180YC-R):</p> <ul style="list-style-type: none"> <li>• AC port-side exhaust (NXA-PAC-750W-PE)</li> <li>• AC port-side intake (NXA-PAC-750W-PI)</li> </ul> <p>The following table provides information about spares support:</p> <ul style="list-style-type: none"> <li>• The Typical/Minimum port-side intake and fan speed percentage is 50% and the maximum port-side intake and fan speed percentage is 100%.</li> <li>• The Typical/Minimum port-side exhaust and fan speed percentage is 70% and the maximum port-side exhaust and fan speed percentage is 100%.</li> </ul> <p>For information about N3K-C36180YC-R, see <a href="#">Cisco Nexus 3600 Hardware Installation Guide</a>.</p>

## Upgrade and Downgrade

To perform a software upgrade or downgrade, follow the instructions in the [Cisco Nexus 3500 Series NX-OS Software Upgrade and Downgrade Guide](#) and [Cisco Nexus 3600 Series NX-OS Software Upgrade and Downgrade Guide](#).

For information about an In Service Software Upgrade (ISSU), see the [Cisco NX-OS ISSU Support Matrix](#).

## MIB Support

The Cisco Management Information Base (MIB) list includes Cisco proprietary MIBs and many other Internet Engineering Task Force (IETF) standard MIBs. These standard MIBs are defined in Requests for Comments (RFCs). To find specific MIB information, you must examine the Cisco proprietary MIB structure and related IETF-standard MIBs supported by the Cisco Nexus 3000 Series switch. The MIB Support List is available at the following FTP sites:

<https://cisco.github.io/cisco-mibs/supportlists/nexus3000/Nexus3000MIBSupportList.html>

## Optics

To determine which transceivers and cables are supported by Cisco Nexus 3000 Series switches, see the [Transceiver Module \(TMG\) Compatibility Matrix](#).

To see the transceiver specifications and installation information, see [Install and Upgrade Guides](#)<https://www.cisco.com/c/en/us/support/interfaces-modules/transceiver-modules/products-installation-guides-list.html>.

## Related Content

This document describes and provides links to the user documentation available for Cisco Nexus 3000 Series documentation. To find a document online, use one of the links in this section.

Document Title	Description
<a href="#">Cisco Nexus 3000 Series switch documentation</a>	Cisco Nexus 3000 Series documentation
<a href="#">Cisco NX-OS Software Strategy and Lifecycle Guide</a>	Cisco NX-OS Software Release and Image-naming Convention
<a href="https://developer.cisco.com/site/nx-os/docs/n3k-n9k-api-ref/API%20REST%20SDK%20User%20Guide%20and%20API%20Reference">Cisco Nexus 3000 and 9000 Series NX-OS/docs/n3k-n9k-api-ref/API REST SDK User Guide and API Reference</a>	Cisco Nexus 3000 and 9000 Series NX-API REST SDK User Guide and API Reference
<a href="#">Cisco NX-OS Licensing Guide</a> <a href="#">Cisco Nexus 9000 and 3000 Series NX-OS Switch License Navigator</a> <a href="#">Cisco Nexus Smart Licensing Using Policy User Guide</a>	Licensing Information

## Documentation Feedback

To provide technical feedback on this document, or to report an error or omission, please send your comments to [nexus9k-docfeedback@cisco.com](mailto:nexus9k-docfeedback@cisco.com). We appreciate your feedback.

---

## Legal Information

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL:

<https://www.cisco.com/c/en/us/about/legal/trademarks.html>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2025 Cisco Systems, Inc. All rights reserved.