G Show Commands

- show guestshell, on page 2

show guestshell

show guestshell [{ detail }] [__readonly__ [TABLE_detail <name> <state> <package_name> <ova_path> <application_name> <application_version> <application_description> <key_type> <signing_method> <licensing_name> <licensing_version> <disk_reservation> <memory_reservation> <cpu_reservation> TABLE_attached_devices <type> <name> <alias>]]

Syntax Description

show	Show running system information
guestshell	Display guest shell service information
detail	(Optional) Detailed guest shell service information
__readonly__	(Optional) Read Only
TABLE_detail	(Optional) Virtual service detail table
name	(Optional) Virtual service name
package_name	(Optional) Virtual service package name
application_name	(Optional) Name of the application
application_version	(Optional) Version of the application
application_description	(Optional) Description of the application
key_type	(Optional) Virtual service key type
signing_method	(Optional) Method used to sign the package
licensing_name	(Optional) Name of the license
licensing_version	(Optional) Version of the license
ova_path	(Optional) Virtual service OVA path
state	(Optional) Virtual service state
disk_reservation	(Optional) Virtual service disk reservation
memory_reservation	(Optional) Virtual service memory reservation
cpu_reservation	(Optional) Virtual service CPU reservation
TABLE_attached_devices	(Optional) Attached devices table
type	(Optional) Type of the attached device
name	(Optional) Name of the attached device
alias	(Optional) Alias for the attached device

Command Mode

- /exec