



## H Show Commands

---

- [show hardware](#), on page 3
- [show hardware access-list lou resource threshold](#), on page 6
- [show hardware access-list resource pooling](#), on page 7
- [show hardware access-list tcam](#), on page 8
- [show hardware capacity](#), on page 9
- [show hardware capacity eobc](#), on page 10
- [show hardware capacity fabric-utilization](#), on page 11
- [show hardware capacity forwarding](#), on page 12
- [show hardware capacity interface](#), on page 13
- [show hardware capacity module](#), on page 14
- [show hardware capacity power](#), on page 16
- [show hardware fabricpath mac-learning module](#), on page 17
- [show hardware feature-capability](#), on page 18
- [show hardware flow aging](#), on page 19
- [show hardware flow entry address type](#), on page 20
- [show hardware flow ip](#), on page 21
- [show hardware flow ipv6](#), on page 22
- [show hardware flow l2](#), on page 23
- [show hardware flow mpls](#), on page 24
- [show hardware flow sampler](#), on page 25
- [show hardware flow tah-etrap](#), on page 26
- [show hardware flow utilization](#), on page 27
- [show hardware forwarding interface statistics mode](#), on page 28
- [show hardware forwarding memory health detail](#), on page 29
- [show hardware forwarding memory health summary](#), on page 32
- [show hardware ip verify](#), on page 34
- [show hardware profile forwarding-mode](#), on page 35
- [show hardware profile module](#), on page 36
- [show hardware profile packet-drop](#), on page 37
- [show hardware profile portmode](#), on page 38
- [show hardware profile status](#), on page 39
- [show hardware profile tcam region](#), on page 41
- [show hardware qos afd profile](#), on page 42

- [show hardware qos burst-detect max-records](#), on page 43
- [show hardware qos eoq stats-class](#), on page 44
- [show hardware qos include ipg](#), on page 45
- [show hardware qos ing-pg-hdrm-reserve](#), on page 46
- [show hardware qos ing-pg-no-min](#), on page 47
- [show hardware qos ing-pg-share](#), on page 48
- [show hardware qos min-buffer](#), on page 49
- [show hardware qos ns-buffer-profile](#), on page 50
- [show hardware qos ns-mcq3-alias](#), on page 51
- [show hardware rate-limiter](#), on page 52
- [show hardware rate-limiter](#), on page 54
- [show hardware rate-limiter span-egress](#), on page 56
- [show hardware vxlan storm-control](#), on page 57
- [show hostname](#), on page 58
- [show hosts](#), on page 59
- [show hsrp](#), on page 61
- [show hsrp anycast](#), on page 65
- [show hsrp anycast interface vlan](#), on page 66
- [show hsrp anycast remote-db](#), on page 67
- [show hsrp anycast summary](#), on page 68
- [show hsrp bfd-sessions](#), on page 69
- [show hsrp delay](#), on page 71
- [show hsrp mgo](#), on page 72
- [show hsrp summary](#), on page 73

# show hardware

```
show hardware [ __readonly__ <header_str> <bios_ver_str> [ <loader_ver_str> ] <kickstart_ver_str>
<nxos_ver_str> [ <sys_ver_str> ] <bios_cmpl_time> <kick_file_name> <nxos_file_name> <kick_cmpl_time>
<nxos_cmpl_time> <kick_tmstamp> <nxos_tmstamp> [ <isan_file_name> ] [ <isan_cmpl_time> ] [
<isan_tmstamp> ] <chassis_id> [ <module_id> ] <cpu_name> <memory> <mem_type> <proc_board_id> [
<host_name> ] <bootflash_size> [ <slot0_size> ] [ <slot1_size> ] <kern_uptm_days> <kern_uptm_hrs>
<kern_uptm_mins> <kern_uptm_secs> [ <rr_usecs> ] [ <rr_ctime> ] <rr_reason> [ <rr_sys_ver> ] [
<rr_service> ] <plugins> [ <manufacturer> ] { TABLE_slot [ TABLE_slot_info [ [ <num_slot_str> ] [
<status_ok_empty> ] [ [ <type> [ <num_submods> ] ] <model_num> <hw_ver> <part_num> <part_revision>
<manuf_date> <serial_num> <CLEI_code> [ <num_slot_str> ] ] ] ] }
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
<i>__readonly__</i>	(Optional)
<i>header_str</i>	(Optional)
<i>bios_ver_str</i>	(Optional)
<i>loader_ver_str</i>	(Optional)
<i>kickstart_ver_str</i>	(Optional)
<i>nxos_ver_str</i>	(Optional)
<i>sys_ver_str</i>	(Optional)
<i>bios_cmpl_time</i>	(Optional)
<i>kick_file_name</i>	(Optional)
<i>nxos_file_name</i>	(Optional)
<i>kick_cmpl_time</i>	(Optional)
<i>nxos_cmpl_time</i>	(Optional)
<i>kick_tmstamp</i>	(Optional)
<i>nxos_tmstamp</i>	(Optional)
<i>isan_file_name</i>	(Optional)
<i>isan_cmpl_time</i>	(Optional)
<i>isan_tmstamp</i>	(Optional)
<i>chassis_id</i>	(Optional)

<i>module_id</i>	(Optional)
<i>cpu_name</i>	(Optional)
<i>memory</i>	(Optional)
<i>mem_type</i>	(Optional)
<i>proc_board_id</i>	(Optional)
<i>bootflash_size</i>	(Optional)
<i>slot0_size</i>	(Optional)
<i>slot1_size</i>	(Optional)
<i>host_name</i>	(Optional)
<i>kern_uptm_days</i>	(Optional)
<i>kern_uptm_hrs</i>	(Optional)
<i>kern_uptm_mins</i>	(Optional)
<i>kern_uptm_secs</i>	(Optional)
<i>rr_usec</i>	(Optional)
<i>rr_ctime</i>	(Optional)
<i>rr_reason</i>	(Optional)
<i>rr_sys_ver</i>	(Optional)
<i>rr_service</i>	(Optional)
<i>plugins</i>	(Optional)
<i>manufacturer</i>	(Optional)
TABLE_slot	(Optional) Slot
<i>num_slot_str</i>	(Optional) Number of elements
TABLE_slot_info	(Optional) Slot Info
<i>status_ok_empty</i>	(Optional) Status (Present or Absent)
<i>type</i>	(Optional) Description of the element
<i>num_submods</i>	(Optional) Number of Submodules
<i>model_num</i>	(Optional) Model Number
<i>hw_ver</i>	(Optional) Hardware version
<i>part_num</i>	(Optional) Part Number

<i>part_revision</i>	(Optional) Part revision
<i>manuf_date</i>	(Optional) Manufacturing date
<i>serial_num</i>	(Optional) Serial Number
<i>CLEI_code</i>	(Optional) CLEI code

**Command Mode**

- /exec

## show hardware access-list lou resource threshold

```
show hardware access-list lou resource threshold [ __readonly__ { current [ { lou [ { resource [ { threshold [
{ <threshold_value> } ] } ] } ] } ] }
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
access-list	Access Control List
lou	LOU
resource	hardware resource
threshold	port expansion threshold
__readonly__	(Optional)
current	(Optional)
lou	(Optional)
resource	(Optional)
threshold	(Optional)
<i>threshold_value</i>	(Optional)

### Command Mode

- /exec

# show hardware access-list resource pooling

show hardware access-list resource pooling [ *\_\_readonly\_\_* <mod-num> <status> ]

## Syntax Description

show	Show running system information
hardware	Show hardware information
access-list	Access Control List
resource	Hardware resource
pooling	ACL programming across TCAM banks
<i>__readonly__</i>	(Optional)
<i>mod-num</i>	(Optional) module number
<i>status</i>	(Optional) Banchaining status

## Command Mode

- /exec

## show hardware access-list tcam

```
show hardware access-list tcam { { template { nfe | nfe2 | l2-l3 | l3 | <name> | all } } | { region } } [
__readonly__ { TCAM_Region [ { TABLE_Sizes <type> <tcam_size> <tcam_width> } ] } ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
access-list	Access Control List
tcam	Show tcam parameters
region	Show tcam region sizes
__readonly__	(Optional)
TCAM_Region	(Optional)
TABLE_Sizes	(Optional)
<i>type</i>	(Optional)
<i>tcam_size</i>	(Optional)
<i>tcam_width</i>	(Optional)
template	Specify template name
nfe	NFE (Trident2) TCAM template
nfe2	NFE2 (Tomahawk) tcam template
l2-l3	L2-L3 default tcam template
l3	L3 default tcam template
<i>name</i>	Name of custom template to be displayed
all	Display all custom templates

### Command Mode

- /exec



# show hardware capacity

show hardware capacity

## Syntax Description

show	Show running system information
hardware	Hardware related
capacity	Hardware usage levels for Power, Switching Fabric, Flash, etc

## Command Mode

- /exec

# show hardware capacity eobc

```
show hardware capacity eobc [ __readonly__ { eobc_usage [ <eobc_tx_pps> ] [ <eobc_tx_packets> ] [ <eobc_tx_dropped> ] [ <eobc_rx_pps> ] [ <eobc_rx_packets> ] [ <eobc_rx_dropped> ] } ]
```

## Syntax Description

show	Show running system information
hardware	Hardware related
capacity	resource inventory and/or usage level
eobc	EOBC resources
__readonly__	(Optional)
eobc_usage	(Optional)
<i>eobc_tx_packets</i>	(Optional)
<i>eobc_tx_dropped</i>	(Optional)
<i>eobc_tx_pps</i>	(Optional)
<i>eobc_rx_packets</i>	(Optional)
<i>eobc_rx_dropped</i>	(Optional)
<i>eobc_rx_pps</i>	(Optional)

## Command Mode

- /exec

# show hardware capacity fabric-utilization

```
show hardware capacity fabric-utilization [ __readonly__ { TABLE_fabutl <mod> <bandwidth> <ingress>
<egress> } ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
capacity	resource inventory and/or usage level
fabric-utilization	Show per module Fabric utilization
__readonly__	(Optional)
TABLE_fabutl	(Optional) fabric utilization table
<i>mod</i>	(Optional)
<i>bandwidth</i>	(Optional)
<i>ingress</i>	(Optional)
<i>egress</i>	(Optional)

## Command Mode

- /exec

# show hardware capacity forwarding

show hardware capacity forwarding

## Syntax Description

show	Show running system information
hardware	Hardware related
capacity	Hardware usage levels for Power, Switching Fabric, Flash, etc
forwarding	L2/L3 Forwarding resources

## Command Mode

- /exec

# show hardware capacity interface

```
show hardware capacity interface [ __readonly__ { TABLE_moddrops <mod_num_drops> <tx_drops>
<rx_drops> <max_tx_port> <max_rx_port> } { TABLE_modbuffers <mod_num_buffers> <tx_buffers>
<rx_buffers> } ]
```

## Syntax Description

show	Show running system information
hardware	Hardware related
capacity	Usage levels
interface	Interface Resources - Tx/Rx drops and Tx/Rx buffers
<i>__readonly__</i>	(Optional) Read Only
<i>mod_num_drops</i>	(Optional) Module number for Tx/Rx drops
TABLE_moddrops	(Optional) show module
<i>tx_drops</i>	(Optional) Tx drops
<i>rx_drops</i>	(Optional) Rx drops
<i>max_tx_port</i>	(Optional) Port with max Tx drops
<i>max_rx_port</i>	(Optional) Port with max Rx drops
<i>mod_num_buffers</i>	(Optional) Module number for Tx/Rx buffers
TABLE_modbuffers	(Optional) show module
<i>tx_buffers</i>	(Optional) Tx buffers
<i>rx_buffers</i>	(Optional) Rx buffers

## Command Mode

- /exec

## show hardware capacity module

```
show hardware capacity module [ __readonly__ { sup_ha_status [ <sup_ha_admin_status> ] [
<sup_ha_oper_status> ] [ <dual_sup_hw_state> ] [ <redundancy_state> ] } { switch_resouces { TABLE_lcinfo
<mod_num> <model_num> <part_num> <serial_num> } [ { TABLE_xbarinfo <mod_num1> <model_num1>
<part_num1> <serial_num1> } ] } { TABLE_flash_nvram_info <mod_num2> <dev_name> <total_bytes>
<free_bytes> <percent_used> } ]
```

### Syntax Description

show	Show running system information
hardware	Hardware related
capacity	resource inventory and/or usage level
module	SUP, LC, XBAR
<i>__readonly__</i>	(Optional)
<i>sup_ha_status</i>	(Optional)
<i>sup_ha_admin_status</i>	(Optional)
<i>sup_ha_oper_status</i>	(Optional)
<i>dual_sup_hw_state</i>	(Optional)
<i>redundancy_state</i>	(Optional)
<i>switch_resouces</i>	(Optional)
TABLE_lcinfo	(Optional)
<i>mod_num</i>	(Optional)
<i>model_num</i>	(Optional)
<i>part_num</i>	(Optional)
<i>serial_num</i>	(Optional)
TABLE_xbarinfo	(Optional)
<i>mod_num1</i>	(Optional)
<i>model_num1</i>	(Optional)
<i>part_num1</i>	(Optional)
<i>serial_num1</i>	(Optional)
TABLE_flash_nvram_info	(Optional)
<i>mod_num2</i>	(Optional)

<i>dev_name</i>	(Optional)
<i>total_bytes</i>	(Optional)
<i>free_bytes</i>	(Optional)
<i>percent_used</i>	(Optional)

**Command Mode**

- /exec

# show hardware capacity power

```
show hardware capacity power [ __readonly__ { power_summary <ps_redun_mode_admin>
<ps_redun_mode_oper> <power_total> <power_rsvd> <power_rsvd_percent> <power_given_mod>
<power_given_mod_percent> <power_avail> <power_avail_percent> <power_out_actual_draw>
<power_input_actual_draw> } ]
```

## Syntax Description

show	Show running system information
hardware	Hardware related
capacity	resource inventory and/or usage level
power	power summary
__readonly__	(Optional)
power_summary	(Optional)
<i>ps_redun_mode_admin</i>	(Optional) Mode: Redundant or Non-redundant
<i>ps_redun_mode_oper</i>	(Optional) Mode: Redundant or Non-redundant
<i>power_total</i>	(Optional)
<i>power_rsvd</i>	(Optional)
<i>power_rsvd_percent</i>	(Optional)
<i>power_given_mod</i>	(Optional)
<i>power_given_mod_percent</i>	(Optional)
<i>power_avail</i>	(Optional)
<i>power_avail_percent</i>	(Optional)
<i>power_out_actual_draw</i>	(Optional) Total Power Output, Actuals
<i>power_input_actual_draw</i>	(Optional) Total Power Input, Actuals

## Command Mode

- /exec



# show hardware fabricpath mac-learning module

```
show hardware fabricpath mac-learning module <module> [ __readonly__ { [ { TABLE_module
<module_num> <port_group> <mac_learning> } ] } ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
fabricpath	Fabric Path
mac-learning	MAC Learning
module	Specify a module number
<i>module</i>	Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_module	(Optional)
<i>module_num</i>	(Optional) Specify a module number
<i>port_group</i>	(Optional)
<i>mac_learning</i>	(Optional)

## Command Mode

- /exec

# show hardware feature-capability

```
show hardware feature-capability [ detailed ] [ __readonly__ [ { TABLE_feature_support <feature_name> [
{ TABLE_mod_support <mod_inst> <support> } ] } ] ] ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
feature-capability	show registered features supported
detailed	(Optional) detailed
__readonly__	(Optional) Read_Only
TABLE_feature_support	(Optional) show features supported
<i>feature_name</i>	(Optional) feature name
TABLE_mod_support	(Optional) show registered features supported
<i>mod_inst</i>	(Optional) module instance
<i>support</i>	(Optional) support details

## Command Mode

- /exec

# show hardware flow aging

show hardware flow aging [ instance <inst> ] [ module <num> ]

## Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
aging	Aging Info
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

## Command Mode

- /exec

## show hardware flow entry address type

show hardware flow entry address <addr> type { ip | ipv6 | l2 | mpls } [ instance <inst> ] [ module <num> ]

### Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
entry	Netflow Table Entry
address	Netflow Table Address
<i>addr</i>	Netflow Table Address
type	Flow Type
ip	Internet Protocol Version 4
ipv6	Internet Protocol Version 6
l2	Layer 2 Protocol
mpls	MPLS Protocol
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

### Command Mode

- /exec

# show hardware flow ip

```
show hardware flow ip [ { { monitor <mname> } | { profile <prof_id> } | { vlan <vlan_id> } | { interface
<interface> } } ] [ instance <inst> ] [ detail ] [ module <num> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
ip	Internet Protocol Version 4
monitor	(Optional) Netflow Flow Monitor
<i>mname</i>	(Optional) Netflow Flow Monitor Name
profile	(Optional) Flow Profile
<i>prof_id</i>	(Optional) Netflow Profile ID
vlan	(Optional) Vlan commands
<i>vlan_id</i>	(Optional) VLAN ID 1-4094
interface	(Optional) Interface
<i>interface</i>	(Optional) Interface Name
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
detail	(Optional) Detailed Output Display
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

## Command Mode

- /exec

# show hardware flow ipv6

```
show hardware flow ipv6 [ { { monitor <mname> } | { profile <prof_id> } | { vlan <vlan_id> } | { interface
<interface> } } ] [ instance <inst> ] [ detail ] [ module <num> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
ipv6	Internet Protocol Version 6
monitor	(Optional) Netflow Flow Monitor
<i>mname</i>	(Optional) Netflow Flow Monitor Name
profile	(Optional) Flow Profile
<i>prof_id</i>	(Optional) Netflow Profile ID
vlan	(Optional) Vlan commands
<i>vlan_id</i>	(Optional) VLAN ID 1-4094
interface	(Optional) Interface
<i>interface</i>	(Optional) Interface Name
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
detail	(Optional) Detailed Output Display
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

## Command Mode

- /exec

## show hardware flow l2

```
show hardware flow l2 [ { { monitor <mname> } | { profile <prof_id> } | { vlan <vlan_id> } } ] [ instance
<inst> ] [ detail ] [ module <num> ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
l2	Layer 2 Protocol
monitor	(Optional) Netflow Flow Monitor
<i>mname</i>	(Optional) Netflow Flow Monitor Name
profile	(Optional) Flow Profile
<i>prof_id</i>	(Optional) Netflow Profile ID
vlan	(Optional) Vlan commands
<i>vlan_id</i>	(Optional) VLAN ID 1-4094
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
detail	(Optional) Detailed Output Display
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

### Command Mode

- /exec

# show hardware flow mpls

```
show hardware flow mpls [ { { monitor <mname> } | { profile <prof_id> } | { vlan <vlan_id> } | { interface
<interface> } } ] [ instance <inst> ] [ detail ] [ module <num> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
mpls	MPLS Protocol
monitor	(Optional) Netflow Flow Monitor
<i>mname</i>	(Optional) Netflow Flow Monitor Name
profile	(Optional) Flow Profile
<i>prof_id</i>	(Optional) Netflow Profile ID
vlan	(Optional) Vlan commands
<i>vlan_id</i>	(Optional) VLAN ID 1-4094
interface	(Optional) Interface
<i>interface</i>	(Optional) Interface Name
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
detail	(Optional) Detailed Output Display
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

## Command Mode

- /exec



# show hardware flow sampler

```
show hardware flow sampler { all | count | index <index> | name <sname> } [ detail ] [ instance <inst> ] [ module <num> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
sampler	Flow Sampler
all	Netflow Sampler Usage
count	Netflow Sampler Utilization
index	Netflow Sampler Index
<i>index</i>	Netflow Sampler Index
name	Netflow Sampler Name
<i>sname</i>	Netflow Sampler Name
detail	(Optional) Detailed Output Display
instance	(Optional) Instance
<i>inst</i>	(Optional) Clipper Instance
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

## Command Mode

- /exec

# show hardware flow tah-etrap

```
show hardware flow tah-etrap [ module <module> ] [ { unit <unit> slice <slice> } ] [ __readonly__ [ {
TABLE_etrap_flows <unit> <slice> <index> <keytype> <src_addr> <dst_addr> <src_port> <dst_port>
<proto> <rate> } ] ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Traffic flow information
tah-etrap	Elephant Trap information
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number
unit	(Optional) Asic Number
<i>unit</i>	(Optional) Asic Number on the module
slice	(Optional) slice num on asic
<i>slice</i>	(Optional) slice number on asic
__readonly__	(Optional) Read Only
TABLE_etrap_flows	(Optional) Elephant trap flows
<i>unit</i>	(Optional) ASIC number on the module
<i>slice</i>	(Optional) Slice number on the ASIC
<i>index</i>	(Optional) Elephant trap table index
<i>keytype</i>	(Optional) Elephant trap table key type
<i>src_addr</i>	(Optional) Elephant trap flow src address
<i>dst_addr</i>	(Optional) Elephant trap flow dst address
<i>src_port</i>	(Optional) Elephant trap flow src port
<i>dst_port</i>	(Optional) Elephant trap flow src port
<i>proto</i>	(Optional) Elephant trap flow protocol
<i>rate</i>	(Optional) Elephant trap flow protocol

## Command Mode

- /exec

# show hardware flow utilization

show hardware flow utilization [ instance <inst> ] [ module <num> ]

## Syntax Description

show	Show running system information
hardware	Show hardware information
flow	Netflow Module
utilization	NT Table Utilization
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

## Command Mode

- /exec

# show hardware forwarding interface statistics mode

```
show hardware forwarding interface statistics mode [ __readonly__ { system [ { <sysmode> } ] [ {
TABLE_module <module> <modmode> } ] ] ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
forwarding	Show hardware information for forwarding path
interface	Interface
statistics	Statistics
mode	Statistics mode
__readonly__	(Optional)
system	(Optional)
<i>sysmode</i>	(Optional)
TABLE_module	(Optional)
<i>module</i>	(Optional) Specify a module number
<i>modmode</i>	(Optional)

## Command Mode

- /exec

## show hardware forwarding memory health detail

```
show hardware forwarding memory health detail [ __readonly__ { memscan_interval <mscan_interval> } {
memscan_rate <mscan_rate> } [ TABLE_ser <table_name> <entry_count> <table_head> <table_tail> [
TABLE_ser_entry_new <n_entry_index> [ <reg_id> ] [ <reg_port> ] [ <reg_index> ] [ <table_id> ] [
<table_index> ] <detections> <corrections> [ <last_detection_ts> ] [ <last_correction_ts> ] ] [
TABLE_ser_entry_old <o_entry_index> <mem_addr> <cause_bits> <event_type> <last_event> <last_time>
] ] [ { parity_detect_counter <parity_detect_cnt> } ] [ { parity_correct_counter <parity_correct_cnt> } ] [ {
reg_parity_detect_counter <reg_parity_detect_cnt> } ] [ { reg_parity_correct_counter <reg_parity_correct_cnt>
} ] [ { tcam_parity_detect_counter <tcam_parity_detect_cnt> } ] [ { tcam_parity_correct_counter
<tcam_parity_correct_cnt> } ] [ { sram_parity_detect_counter <sram_parity_detect_cnt> } ] [ {
sram_parity_correct_counter <sram_parity_correct_cnt> } ] [ { TABLE_ser_tbl_parity <table_id> <detections>
<corrections> } ] ] ] ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
forwarding	forwarding information
memory	memory information
health	memory health information
detail	show the detail
__readonly__	(Optional) Read Only
memscan_interval	(Optional) memory scan interval value
<i>mscan_interval</i>	(Optional) mem scan interval
memscan_rate	(Optional) memory scan rate value
<i>mscan_rate</i>	(Optional) mem scan rate
TABLE_ser	(Optional) ser table list
<i>table_name</i>	(Optional) table name
<i>entry_count</i>	(Optional) total entries in table
<i>table_head</i>	(Optional) start of entry index
<i>table_tail</i>	(Optional) end of entry index
TABLE_ser_entry_new	(Optional) ser table entry with new format
<i>n_entry_index</i>	(Optional) entry index
<i>reg_id</i>	(Optional) register id

<i>reg_port</i>	(Optional) port
<i>reg_index</i>	(Optional) register index
<i>table_id</i>	(Optional) table id
<i>table_index</i>	(Optional) table_index
<i>detections</i>	(Optional) parity detetction count
<i>corrections</i>	(Optional) parity correction count
<i>last_detection_ts</i>	(Optional) last detetction timestamp
<i>last_correction_ts</i>	(Optional) last correction timestamp
TABLE_ser_entry_old	(Optional) ser table entry with new format
<i>o_entry_index</i>	(Optional) table entry index
<i>mem_addr</i>	(Optional) memory address
<i>cause_bits</i>	(Optional) cause bit
<i>event_type</i>	(Optional) type of event
<i>last_event</i>	(Optional) last event that occurred
<i>last_time</i>	(Optional) last time of event
parity_detect_counter	(Optional) parity detect count
<i>parity_detect_cnt</i>	(Optional) count of parity detect
parity_correct_counter	(Optional) parity correct count
<i>parity_correct_cnt</i>	(Optional) count of parity correct
reg_parity_detect_counter	(Optional) reg parity detect count
<i>reg_parity_detect_cnt</i>	(Optional) count of reg parity detect
reg_parity_correct_counter	(Optional) reg parity correct count
<i>reg_parity_correct_cnt</i>	(Optional) count of reg parity correct
tcam_parity_detect_counter	(Optional) tcam parity detect count
<i>tcam_parity_detect_cnt</i>	(Optional) count of tcam parity detect
tcam_parity_correct_counter	(Optional) tcam parity correct count
<i>tcam_parity_correct_cnt</i>	(Optional) count of tcam parity correct
sram_parity_detect_counter	(Optional) sram parity detect count
<i>sram_parity_detect_cnt</i>	(Optional) count of sram parity detect

<i>sram_parity_correct_counter</i>	(Optional) sram parity correct count
<i>sram_parity_correct_cnt</i>	(Optional) count of sram parity correct
<i>TABLE_ser_tbl_parity</i>	(Optional) all ser tables
<i>table_id</i>	(Optional) table name
<i>detections</i>	(Optional) parity detection count for ser table
<i>corrections</i>	(Optional) parity correction count for ser table

**Command Mode**

- /exec

## show hardware forwarding memory health summary

```
show hardware forwarding memory health summary [ __readonly__ [ { parity_detect_counter
<parity_detect_cnt> } ] [ { parity_correct_counter <parity_correct_cnt> } ] [ { reg_parity_detect_counter
<reg_parity_detect_cnt> } ] [ { reg_parity_correct_counter <reg_parity_correct_cnt> } ] [ {
tcam_parity_detect_counter <tcam_parity_detect_cnt> } ] [ { tcam_parity_correct_counter
<tcam_parity_correct_cnt> } ] [ { sram_parity_detect_counter <sram_parity_detect_cnt> } ] [ {
sram_parity_correct_counter <sram_parity_correct_cnt> } ] [ { TABLE_ser_tbl_parity <table_id> <detections>
<corrections> } ] ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
forwarding	forwarding information
memory	memory information
health	memory health information
summary	show the summary
<code>__readonly__</code>	(Optional) Read Only
<code>parity_detect_counter</code>	(Optional) parity detect count
<i>parity_detect_cnt</i>	(Optional) count of parity detect
<code>parity_correct_counter</code>	(Optional) parity correct count
<i>parity_correct_cnt</i>	(Optional) count of parity correct
<code>reg_parity_detect_counter</code>	(Optional) reg parity detect count
<i>reg_parity_detect_cnt</i>	(Optional) count of reg parity detect
<code>reg_parity_correct_counter</code>	(Optional) reg parity correct count
<i>reg_parity_correct_cnt</i>	(Optional) count of reg parity correct
<code>tcam_parity_detect_counter</code>	(Optional) tcam parity detect count
<i>tcam_parity_detect_cnt</i>	(Optional) count of tcam parity detect
<code>tcam_parity_correct_counter</code>	(Optional) tcam parity correct count
<i>tcam_parity_correct_cnt</i>	(Optional) count of tcam parity correct
<code>sram_parity_detect_counter</code>	(Optional) sram parity detect count
<i>sram_parity_detect_cnt</i>	(Optional) count of sram parity detect
<code>sram_parity_correct_counter</code>	(Optional) sram parity correct count



<i>sram_parity_correct_cnt</i>	(Optional) count of sram parity correct
TABLE_ser_tbl_parity	(Optional) all ser tables
<i>table_id</i>	(Optional) table name
<i>detections</i>	(Optional) parity detection count for ser table
<i>corrections</i>	(Optional) parity correction count for ser table

**Command Mode**

- /exec

# show hardware ip verify

show hardware [ forwarding ] ip verify [ module <module> ] [ \_\_readonly\_\_ <info\_str> ]

## Syntax Description

show	Show running system information
hardware	Show hardware information
forwarding	(Optional) Show hardware information for forwarding path
ip	IP
verify	Show IP packet verification checks enabled in hardware
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
<i>info_str</i>	(Optional) IDS Check Stats

## Command Mode

- /exec

# show hardware profile forwarding-mode

```
show hardware profile forwarding-mode [ __readonly__ <forwarding-mode> [ <host-size> ] [ <unicast-size>
] [ <unicast-rpf-size> ] [ <unicast-ipv4-size> ] [ <unicast-ipv4-rpf-size> ] [ <unicast-ipv6-size> ] [
<multicast-size> ] [ <l2-size> ] [ <unified-size> ] ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware profile forwarding-mode
profile	profile forwarding-mode
forwarding-mode	forwarding-mode
<i>__readonly__</i>	(Optional)
<i>forwarding-mode</i>	(Optional)
<i>host-size</i>	(Optional)
<i>unicast-size</i>	(Optional)
<i>unicast-rpf-size</i>	(Optional)
<i>unicast-ipv4-size</i>	(Optional)
<i>l2-size</i>	(Optional)
<i>unified-size</i>	(Optional)
<i>unicast-ipv4-rpf-size</i>	(Optional)
<i>unicast-ipv6-size</i>	(Optional)
<i>multicast-size</i>	(Optional)

## Command Mode

- /exec

# show hardware profile module

show hardware profile module <module> [ \_\_readonly\_\_ { TABLE\_profile <slot> <type> } ]

## Syntax Description

show	Show running system information
hardware	Show hardware profile
profile	Profile settings
module	Enter module number
<i>module</i>	
<i>__readonly__</i>	(Optional)
TABLE_profile	(Optional) Show version info
<i>slot</i>	(Optional) Slot
<i>type</i>	(Optional) Profile type

## Command Mode

- /exec

# show hardware profile packet-drop

```
show hardware profile packet-drop { status | data [ instance <cap_instance> ] | event [ instance <cap_instance>
] } [ __readonly__ [ <enable><state> <cap-scope><drop-trigger> <cap-count><cap-time> <file-inst> ] [
TABLE_hardware_packet_drop_status <profile-name><start-thres><stop-thres> ] [
TABLE_hardware_packet_drop_data <src-port><dst-port> <qos-grp><que-depth> <payload> ] [
TABLE_hardware_packet_drop_event <src-port><dst-port> <qos-grp><que-depth> <drop-reason> ] ]
```

## Syntax Description

show	Show running system information
hardware	Change hardware usage settings
profile	Profile settings
packet-drop	Packet Drop parameters
status	Packet Drop status
data	Packet Drop circular-buffer data
instance	(Optional) Packet Drop captured instance
<i>cap_instance</i>	(Optional) Value 1-5
event	Packet Drop event-buffer data
instance	(Optional) Packet Drop captured instance
<i>cap_instance</i>	(Optional) Value 1-5
<i>__readonly__</i>	(Optional)
<i>file-inst</i>	(Optional) Packet-Drop file instance
TABLE_hardware_packet_drop_status	(Optional) XML Packet-drop stats
TABLE_hardware_packet_drop_data	(Optional) XML Packet-drop data
<i>payload</i>	(Optional) Packet-Drop Data Packet Payload (80bytes)
TABLE_hardware_packet_drop_event	(Optional) XML Packet-drop event
<i>drop-reason</i>	(Optional) PacketDrop Event Drop trigger

## Command Mode

- /exec

# show hardware profile portmode

{ show hardware profile portmode }

## Syntax Description

show	Show running system information
hardware	Change hardware usage settings
profile	profile settings
portmode	QSFP port mode setting

## Command Mode

- /exec

## show hardware profile status

```
show hardware profile status [ module <module> ] [ detail ] [ __readonly__ { <total_lpm> <total_host>
<reserved_lpm> <max_host4_limit> <max_host6_limit> <max_mcast_limit> <max_mcast6_limit> [
<max_mcast_transit_route_limit> ] [ <max_v6_lpm_limit> ] [ <max_v6_lpm_65_to_127_limit> ] [
<used_lpm_total> ] <used_v4_lpm> <used_v6_lpm> [ <used_v6_lpm_128> ] <used_host_lpm_total>
<used_host_v4_lpm> <used_host_v6_lpm> <used_mcast> <used_mcast6> [ <used_mcast_transit_routes> ]
<used_mcast_oifl> <used_host_in_host_total> <used_host4_in_host> <used_host6_in_host>
<max_ecmp_table_limit> <used_ecmp_table> <max_ecmp_nh_table_limit> <used_ecmp_nh_table> [
<mfib_fd_status> ] [ <mfib_fd_maxroute> ] [ <mfib_fd_count> ] [ <lpm_to_host_migrate_table> ] [
<host_to_lpm_migrate_table> ] }
```

### Syntax Description

show	Show running system information
hardware	Show hardware usage settings
profile	Show current table usage
status	Show status of dynamic resource allocation
module	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
<i>module</i>	(Optional) Slot/module number
detail	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
<u>__readonly__</u>	(Optional) Read only
<i>total_lpm</i>	(Optional) Total LPM Entries
<i>total_host</i>	(Optional) Total Host Entries
<i>reserved_lpm</i>	(Optional) Reserved LPM Entries
<i>max_host4_limit</i>	(Optional) Max Host4 Limit Entries
<i>max_host6_limit</i>	(Optional) Max Host6 Limit Entries
<i>max_mcast_limit</i>	(Optional) Max Mcast Limit Entries
<i>max_mcast6_limit</i>	(Optional) Max IPv6 Mcast Limit Entries
<i>max_v6_lpm_limit</i>	(Optional) Max Ucast IPv6 LPM Limit Entries
<i>max_v6_lpm_65_to_127_limit</i>	(Optional) Max Ucast IPv6 LPM_65_to_127 Limit Entries
<i>used_lpm_total</i>	(Optional) Used LPM Entries (Total)
<i>used_v4_lpm</i>	(Optional) Used IPv4 LPM Entries
<i>used_v6_lpm</i>	(Optional) Used IPv6 LPM Entries

<i>used_v6_lpm_128</i>	(Optional) Used IPv6 LPM_128 Entries
<i>used_host_lpm_total</i>	(Optional) Used Host Entries in LPM (Total)
<i>used_host_v4_lpm</i>	(Optional) Used Host4 Entries in LPM
<i>used_host_v6_lpm</i>	(Optional) Used Host6 Entries in LPM
<i>used_mcast</i>	(Optional) Used Mcast Entries
<i>used_mcast6</i>	(Optional) Used IPv6 Mcast Entries
<i>used_mcast_oifl</i>	(Optional) Used Mcast OIFL Entries
<i>used_host_in_host_total</i>	(Optional) Used Host Entries in Host (Total)
<i>used_host4_in_host</i>	(Optional) Used Host4 Entries in Host
<i>used_host6_in_host</i>	(Optional) Used Host6 Entries in Host
<i>max_ecmp_table_limit</i>	(Optional) Max ECMP table Limit Entries
<i>used_ecmp_table</i>	(Optional) Used ECMP Table Entries
<i>max_ecmp_nh_table_limit</i>	(Optional) Max ECMP NH table Limit Entries
<i>used_ecmp_nh_table</i>	(Optional) Used ECMP NH Table Entries
<i>mfib_fd_status</i>	(Optional) MFIB fd status
<i>mfib_fd_maxroute</i>	(Optional) MFIB fd maxroute
<i>mfib_fd_count</i>	(Optional) MFIB fd count
<i>lpm_to_host_migrate_table</i>	(Optional) Times Route Migrated from LPM to Host Table
<i>host_to_lpm_migrate_table</i>	(Optional) Times Route Migrated from Host to LPM Table
<i>max_mcast_transit_route_limit</i>	(Optional) Max Mcast Transit Route Limit Entries
<i>used_mcast_transit_routes</i>	(Optional) Used Mcast Transit Routes

**Command Mode**

- /exec



# show hardware profile tcam region

```
show hardware profile tcam region [ __readonly__ { TCAM_Region [ { TABLE_Sizes <tcam_compat_type>
<tcam_compat_size> <tcam_compat_width> } ] } ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
profile	profile
tcam	Show tcam parameters
region	Show tcam region sizes
<i>__readonly__</i>	(Optional)
TCAM_Region	(Optional)
TABLE_Sizes	(Optional)
<i>tcam_compat_type</i>	(Optional)
<i>tcam_compat_size</i>	(Optional)
<i>tcam_compat_width</i>	(Optional)

## Command Mode

- /exec

# show hardware qos afd profile

```
show hardware qos afd profile [ module <module> ] [ __readonly__ TABLE_qos_afd_profile [ <module> ]
<prof-desc> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
afd	Show Approximate Fair Dropping config
profile	Show AFD profile config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_afd_profile	(Optional) the xml qos_afd_profile configuration
<i>prof-desc</i>	(Optional) profile description

## Command Mode

- /exec

# show hardware qos burst-detect max-records

show hardware qos burst-detect max-records [ *\_\_readonly\_\_* <*max\_records*> ]

## Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
burst-detect	Show oobst burst-detect info
max-records	Show oobst burst-detect max-records
<i>__readonly__</i>	(Optional)
<i>max_records</i>	(Optional) max number of burst records configured

## Command Mode

- /exec

# show hardware qos eoq stats-class

```
show hardware qos eoq stats-class [ module <module> ] [ __readonly__ TABLE_qos_eoq_stats_class [
<module> ] <eoq-stats-class-desc> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show QoS related information
eoq	Show Extended Output Queue(EOQ) related information
stats-class	Show EOQ Statistics class selection config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_eoq_stats_class	(Optional) the xml qos_eoq_stats_class configuration
<i>eoq-stats-class-desc</i>	(Optional) selected class description

## Command Mode

- /exec

# show hardware qos include ipg

show hardware qos include ipg [ module <module> ] [ \_\_readonly\_\_ TABLE\_qos\_include\_ipg <module> ]

## Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
include	Show include config
ipg	Show whether to include IPG in Shaping/Policing config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_include_ipg	(Optional) the xml qos_include_ipg configuration

## Command Mode

- /exec

# show hardware qos ing-pg-hdrm-reserve

```
show hardware qos ing-pg-hdrm-reserve [ module <module> ] [ __readonly__
TABLE_qos_ing_pg_hdrm_reserve <module> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
ing-pg-hdrm-reserve	Show ing-pg-hdrm-reserve config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_ing_pg_hdrm_reserve	(Optional) the xml qos_ing_pg_hdrm_reserve configuration

## Command Mode

- /exec

## show hardware qos ing-pg-no-min

```
show hardware qos ing-pg-no-min [ module <module> ] [ __readonly__ TABLE_qos_ing_pg_no_min [
<module> ] <ingress_pg_min> <pg_min_value> ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
ing-pg-no-min	Show ing-pg-no-min config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_ing_pg_no_min	(Optional) the xml qos_ing_pg_no_min configuration
<i>ingress_pg_min</i>	(Optional) Enable/Disable PG Min
<i>pg_min_value</i>	(Optional) PG Min Value

### Command Mode

- /exec

# show hardware qos ing-pg-share

```
show hardware qos ing-pg-share [ module <module> ] [ __readonly__ TABLE_qos_ing_pg_share <module> ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
ing-pg-share	Show ing-pg-share config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_ing_pg_share	(Optional) the xml qos_ing_pg_share configuration

## Command Mode

- /exec



## show hardware qos min-buffer

```
show hardware qos min-buffer [ module <module> ] [ __readonly__ TABLE_qos_min_buffer_profile [
<module> ] <buff-prof-desc> ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
min-buffer	Show min-buffer config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_min_buffer_profile	(Optional) the xml qos_min_buffer_profile configuration
<i>buff-prof-desc</i>	(Optional) buffer profile description

### Command Mode

- /exec

# show hardware qos ns-buffer-profile

show hardware qos ns-buffer-profile [ module <module> ] [ \_\_readonly\_\_ TABLE\_qos\_ns\_buffer\_profile <module> <buff-prof-desc> ]

## Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show qos related information
ns-buffer-profile	Show ns-buffer-profile config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_ns_buffer_profile	(Optional) the xml qos_ns_buffer_profile configuration
<i>buff-prof-desc</i>	(Optional) buffer profile description

## Command Mode

- /exec

## show hardware qos ns-mcq3-alias

```
show hardware qos ns-mcq3-alias [ module <module> ][ __readonly__ TABLE_qos_ns_mcq3_alias <module>
<ns-mcq3-alias-desc> ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
qos	Show QoS related information
ns-mcq3-alias	Show NS mc-queue-3 alias class selection config
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE_qos_ns_mcq3_alias	(Optional) the xml qos_ns_mcq3_alias configuration
<i>ns-mcq3-alias-desc</i>	(Optional) selected class description

### Command Mode

- /exec

# show hardware rate-limiter

```
show hardware rate-limiter [ module <module> ] [ layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2
<l2-opts> | <opts> | fl <fl-opts> | span-egress | urpf-fail ] [ __readonly__ TABLE hardware_rate_limiter
<rate-limit-class> <class-descr> <module> <rate-limit-configured> [ <rate-limit-allowed> ] [
<rate-limit-dropped> ] [ <rate-limit-total> ] ]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
rate-limiter	Show Rate-Limiter configs and statistics
layer-3	(Optional) Layer-3 control and Routed packets
<i>l3-opts</i>	(Optional)
multicast	(Optional) Multicast data packets
<i>mcast-opts</i>	(Optional)
layer-2	(Optional) Layer-2 control and Bridged packets
<i>l2-opts</i>	(Optional)
<i>opts</i>	(Optional)
fl	(Optional) Control packets from F1 modules to supervisor
<i>fl-opts</i>	(Optional)
span-egress	(Optional) SPAN/ERSPAN egress packets
urpf-fail	(Optional) URPF fail packets
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE hardware_rate_limiter	(Optional) the xml Rate-Limiter configuration and statistics
<i>rate-limit-class</i>	(Optional) the xml rate limiter class
<i>class-descr</i>	(Optional) class description
<i>module</i>	(Optional) the xml module number
<i>rate-limit-configured</i>	(Optional) the xml rate-limit-configured
<i>rate-limit-allowed</i>	(Optional) the xml rate-limit-allowed

<i>rate-limit-dropped</i>	(Optional) the xml rate-limit-dropped
<i>rate-limit-total</i>	(Optional) the xml rate-limit-total

**Command Mode**

- /exec

## show hardware rate-limiter

```
show hardware rate-limiter [ module <module> ] [ layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2
<l2-opts> | <opts> | fl <fl-opts> | span-egress | urpf-fail ] [ __readonly__ TABLE hardware_rate_limiter
<rate-limit-class> <class-descr> <module> <rate-limit-configured> [ <rate-limit-allowed> ] [
<rate-limit-dropped> ] [ <rate-limit-total> ] ]
```

### Syntax Description

show	Show running system information
hardware	Show hardware information
rate-limiter	Show Rate-Limiter configs and statistics
layer-3	(Optional) Layer-3 control and Routed packets
<i>l3-opts</i>	(Optional)
multicast	(Optional) Multicast data packets
<i>mcast-opts</i>	(Optional)
layer-2	(Optional) Layer-2 control and Bridged packets
<i>l2-opts</i>	(Optional)
<i>opts</i>	(Optional)
fl	(Optional) Control packets from F1 modules to supervisor
<i>fl-opts</i>	(Optional)
span-egress	(Optional) SPAN/ERSPAN egress packets
urpf-fail	(Optional) URPF fail packets
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>__readonly__</i>	(Optional)
TABLE hardware_rate_limiter	(Optional) the xml Rate-Limiter configuration and statistics
<i>rate-limit-class</i>	(Optional) the xml rate limiter class
<i>class-descr</i>	(Optional) class description
<i>module</i>	(Optional) the xml module number
<i>rate-limit-configured</i>	(Optional) the xml rate-limit-configured
<i>rate-limit-allowed</i>	(Optional) the xml rate-limit-allowed

<i>rate-limit-dropped</i>	(Optional) the xml rate-limit-dropped
<i>rate-limit-total</i>	(Optional) the xml rate-limit-total

**Command Mode**

- /exec

# show hardware rate-limiter span-egress

```
show hardware rate-limiter span-egress [ __readonly__ TABLE hardware_rate_limiter <rate-limit-class>
<class-descr> <module> <rate-limit-configured> <rate-limit-allowed> <rate-limit-dropped> <rate-limit-total>
]
```

## Syntax Description

show	Show running system information
hardware	Show hardware information
rate-limiter	Show Rate-Limiter configs and statistics
span-egress	SPAN/ERSPAN egress packets
<i>__readonly__</i>	(Optional)
<i>TABLE hardware_rate_limiter</i>	(Optional) the xml Rate-Limiter configuration and statistics
<i>rate-limit-class</i>	(Optional) the xml rate limiter class
<i>class-descr</i>	(Optional) class description
<i>module</i>	(Optional) the xml module number
<i>rate-limit-configured</i>	(Optional) the xml rate-limit-configured
<i>rate-limit-allowed</i>	(Optional) the xml rate-limit-allowed
<i>rate-limit-dropped</i>	(Optional) the xml rate-limit-dropped
<i>rate-limit-total</i>	(Optional) the xml rate-limit-total

## Command Mode

- /exec



# show hardware vxlan storm-control

show hardware vxlan storm-control

## Syntax Description

show	Show running system information
hardware	Show hardware information
vxlan	VxLAN Information
storm-control	Storm Control Information

## Command Mode

- /exec

# show hostname

```
show { hostname | switchname } [ __readonly__ { <hostname> } ]
```

## Syntax Description

show	Show running system information
hostname	show the system's hostname
switchname	show the system's hostname
__readonly__	(Optional) Read Only
<i>hostname</i>	(Optional)

## Command Mode

- /exec

# show hosts

```
show hosts [ __readonly__ [ <dnslookup> ] [ <dnsnameservice> ] [ { TABLE_vrf <vrfname> [
<defaultdomains> ] [ <additionaldomainserver> ] [ <domainservers> ] [ <nameservice> ] [ <dhcpdomains>
] [ <dhcpdomainservers> ] } ] [ { TABLE_dnsconfigvrf <dnsvrfname> [ <usevrf> ] [ <token> ] [ {
TABLE_dnsconfigvrfconfig <config> } ] } ] [ { TABLE_hosts <host> [ <address> } ] }
```

## Syntax Description

show	Show running system information
hosts	Show information about DNS
<i>__readonly__</i>	(Optional)
<i>dnslookup</i>	(Optional) dns lookup enable status
<i>dnsnameservice</i>	(Optional) name service
TABLE_vrf	(Optional) vrf domain servers
<i>vrfname</i>	(Optional) vrf name
<i>defaultdomains</i>	(Optional) default domain
<i>additionaldomainserver</i>	(Optional) additionaldomain
<i>domainservers</i>	(Optional) domain server
<i>nameservice</i>	(Optional) name service
<i>dhcpdomains</i>	(Optional) dhcp domains
<i>dhcpdomainservers</i>	(Optional) dhcpservers
TABLE_dnsconfigvrf	(Optional) dns config vrf
<i>dnsvrfname</i>	(Optional) vrfname
<i>usevrf</i>	(Optional) usevrf
<i>token</i>	(Optional) token
TABLE_dnsconfigvrfconfig	(Optional) dns config vrf config
<i>config</i>	(Optional) token
TABLE_hosts	(Optional) all configured dns hosts
<i>host</i>	(Optional) xml host information
<i>address</i>	(Optional) xml address information

## Command Mode

- /exec

# show hsrp

```
show hsrp [ interface <interface-id> ] [ group <group-number> ] [ active | init | learn | listen | speak | standby
] + [ all ] [ brief [ all ] | detail ] [ ipv4 | ipv6 ] [ _readonly_ <show_hsrp_start> { TABLE_grp_detail
<sh_if_index> <sh_group_num> <sh_group_type> <sh_group_version> <sh_group_state> [ <sh_state_reason>
] <sh_prio> <sh_cfg_prio> <sh_fwd_lower_threshold> <sh_fwd_upper_threshold> <sh_can_forward>
<sh_preempt> [ <sh_preempt_min_delay> ] [ <sh_preempt_min_delay_active> ] [ <sh_preempt_reload_delay>
] [ <sh_preempt_reload_delay_active> ] [ <sh_preempt_sync_delay> ] [ <sh_preempt_sync_delay_active> ]
<sh_cur_hello> <sh_cur_hello_attr> [ <sh_cfg_hello> ] [ <sh_cfg_hello_attr> ] [ <sh_active_hello> ]
<sh_cur_hold> <sh_cur_hold_attr> [ <sh_cfg_hold> ] [ <sh_cfg_hold_attr> ] [ <sh_vip> | <sh_vip_v6> ]
<sh_vip_attr> <sh_num_vip_sec> { [ TABLE_grp_vip_sec <sh_vip_sec> } } [ <sh_active_router_addr> |
<sh_active_router_addr_v6> ] <sh_active_router_prio> [ <sh_active_router_timer> ] [
<sh_standby_router_addr> | <sh_standby_router_addr_v6> ] <sh_standby_router_prio>
<sh_authentication_type> <sh_authentication_data> [ <sh_keystring_attr> ] [ <sh_keystring_timeout> ] [
<sh_keystring_cur_valid> ] <sh_vmac> <sh_vmac_attr> <sh_num_of_state_changes> [ <sh_last_state_change>
] <sh_num_of_total_state_changes> [ <sh_last_total_state_change> ] { [ TABLE_grp_track_obj <sh_track_obj>
<sh_track_obj_state> <sh_track_obj_prio> ] } <sh_num_track_obj> <sh_ip_redund_name>
<sh_ip_redund_name_attr> } <show_hsrp_end> ]
```

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
interface	(Optional) Groups on this interface
<i>interface-id</i>	(Optional) Interface
active	(Optional) Groups in active state
init	(Optional) Groups in init state
listen	(Optional) Groups in listen state
standby	(Optional) Groups in standby state
learn	(Optional) Groups in learn state
speak	(Optional) Groups in speak state
group	(Optional) Group number
<i>group-number</i>	(Optional) Group Number
all	(Optional) Include groups in disabled state
brief	(Optional) Brief output
detail	(Optional) Detailed output
ipv4	(Optional) HSRP V4 Groups
ipv6	(Optional) HSRP V6 Groups

all	(Optional) Display all VIPs
__readonly__	(Optional) Read only
show_hsrp_start	(Optional) Show hsrp start
TABLE_grp_detail	(Optional) Group table detail
sh_if_index	(Optional) Interface type and number
sh_group_num	(Optional) Group number
sh_group_state	(Optional) HSRP state
sh_state_reason	(Optional) Reason
sh_group_type	(Optional) Group type
sh_group_version	(Optional) Group version
sh_prio	(Optional) Priority
sh_cfg_prio	(Optional) Configured priority
sh_fwd_lower_threshold	(Optional) Lower threshold value
sh_fwd_upper_threshold	(Optional) Upper threshold value
sh_can_forward	(Optional) Current forwarding status
sh_preempt	(Optional) Preemption enabled/not
sh_preempt_min_delay	(Optional) Preemption min delay
sh_preempt_min_delay_active	(Optional) Active preemption min delay
sh_preempt_reload_delay	(Optional) Preemption reload delay
sh_preempt_reload_delay_active	(Optional) Active preemption reload delay
sh_preempt_sync_delay	(Optional) Preemption sync delay
sh_preempt_sync_delay_active	(Optional) Active preemption sync delay
sh_cur_hello	(Optional) Current hello time
sh_cur_hello_attr	(Optional) Hello time in ms/not
sh_cfg_hello	(Optional) Configured hello time
sh_cfg_hello_attr	(Optional) Hello time in ms/not
sh_active_hello	(Optional) Active hello time
sh_cur_hold	(Optional) Current hold time
sh_cur_hold_attr	(Optional) Hello time in ms/not

<i>sh_cfg_hold</i>	(Optional) Configured hold time
<i>sh_cfg_hold_attr</i>	(Optional) Hello time in ms/not
<i>sh_vip</i>	(Optional) Virtual IP address
<i>sh_vip_attr</i>	(Optional) Virtual IP address attribute
<i>sh_num_vip_sec</i>	(Optional) Number of Secondary virtual IP address
TABLE_grp_vip_sec	(Optional) Group secondary ip address
<i>sh_vip_sec</i>	(Optional) Secondary virtual IP address
<i>sh_active_router_addr</i>	(Optional) Active router address
<i>sh_active_router_prio</i>	(Optional) Active router priority
<i>sh_active_router_timer</i>	(Optional) Active router expiry timer
<i>sh_standby_router_addr</i>	(Optional) Standby router address
<i>sh_standby_router_prio</i>	(Optional) Standby router priority
<i>sh_authentication_type</i>	(Optional) Authentication type
<i>sh_authentication_data</i>	(Optional) Authentication data
<i>sh_keystring_attr</i>	(Optional) Keystring attribute
<i>sh_keystring_timeout</i>	(Optional) Keystring timeout
<i>sh_keystring_cur_valid</i>	(Optional) Keystring current valid time
<i>sh_vmac</i>	(Optional) Virtual MAC
<i>sh_vmac_attr</i>	(Optional) Virtual MAC attribute
<i>sh_num_of_state_changes</i>	(Optional) Number of state changes
<i>sh_last_state_change</i>	(Optional) Last state change time
<i>sh_num_of_total_state_changes</i>	(Optional) Number of total state changes
<i>sh_last_total_state_change</i>	(Optional) Last total state change time
<i>sh_num_track_obj</i>	(Optional) Number of tracked objects
TABLE_grp_track_obj	(Optional) Group tracked objects
<i>sh_track_obj</i>	(Optional) Tracked object
<i>sh_track_obj_state</i>	(Optional) State of tracked object
<i>sh_track_obj_prio</i>	(Optional) Tracked object priority decrement
<i>sh_ip_redund_name</i>	(Optional) IP redundancy name

<i>sh_ip_redund_name_attr</i>	(Optional) IP redundancy name attribute
<i>show_hsrp_end</i>	(Optional) End of Group

**Command Mode**

- /exec



# show hsrp anycast

```
show hsrp anycast [ <id> { ipv4 | ipv6 | both } ] [ brief ]
```

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
anycast	Anycast related commands
<i>id</i>	(Optional) Bundle number
ipv4	(Optional) Associate IP Version 4 for the bundle
ipv6	(Optional) Associate IP Version 6 for the bundle
both	(Optional) Associate IP Version 4 and 6 for the bundle
brief	(Optional) Brief output

## Command Mode

- /exec

# show hsrp anycast interface vlan

show hsrp anycast interface { vlan | bdi } <id>

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
anycast	Anycast related commands
interface	Bundle on this interface Interface
vlan	VLAN interface
bdi	Bridge-Domain interface
<i>id</i>	VLAN number

## Command Mode

- /exec

# show hsrp anycast remote-db

```
show hsrp anycast remote-db [ <id> { ipv4 | ipv6 | both } ]
```

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
anycast	Anycast related commands
remote-db	Remote data base for the bundle
<i>id</i>	(Optional) Bundle number
ipv4	(Optional) Associate IP Version 4 for the bundle
ipv6	(Optional) Associate IP Version 6 for the bundle
both	(Optional) Associate IP Version 4 and 6 for the bundle

## Command Mode

- /exec

# show hsrp anycast summary

show hsrp anycast summary

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
anycast	Anycast related commands
summary	Show HSRP summary

## Command Mode

- /exec

# show hsrp bfd-sessions

```
show hsrp bfd-sessions [ interface <interface-id> [ to <ipaddress> ] ] [ __readonly__ [ TABLE_bfd_sess [
<interface> ] [ <list_size> ] { [ <src_addr> ] } { [ <dst_addr> ] } [ <ref_count> ] { [ TABLE_ref_groups [
<ref_group_id> ] } ] } { [ TABLE_hist_groups [ <hist_group_id> ] [ <hist_operation> ] [ <hist_rel_time> ] [
<hist_abs_time> ] [ <hist_ref_count> ] [ <hist_group_state> ] [ <hist_status> ] [ <hist_op_reason> ] ] } ] ]
```

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
bfd-sessions	BFD sessions
interface	(Optional) Groups on this interface
<i>interface-id</i>	(Optional) Interface
to	(Optional) To IP address
<i>ipaddress</i>	(Optional) Sessions to IP address
<i>__readonly__</i>	(Optional)
TABLE_bfd_sess	(Optional)
<i>interface</i>	(Optional) Interface
<i>list_size</i>	(Optional) List size
<i>src_addr</i>	(Optional) IPv4 Source address
<i>dst_addr</i>	(Optional) IPv4 Destination address
<i>ref_count</i>	(Optional) Ref count
TABLE_ref_groups	(Optional)
<i>ref_group_id</i>	(Optional) Group id
TABLE_hist_groups	(Optional)
<i>hist_group_id</i>	(Optional) Group id
<i>hist_operation</i>	(Optional) Operation
<i>hist_rel_time</i>	(Optional) Relative time
<i>hist_abs_time</i>	(Optional) Absolute time
<i>hist_ref_count</i>	(Optional) Ref count
<i>hist_group_state</i>	(Optional) Group state

<i>hist_status</i>	(Optional) Status
<i>hist_op_reason</i>	(Optional) Op reason

**Command Mode**

- /exec

# show hsrp delay

```
show hsrp delay [ interface <interface-id> ] [ __readonly__ TABLE_delay <interface> <min_delay>
<reload_delay> ]
```

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
delay	Group initialisation delay
interface	(Optional) Groups on this interface
<i>interface-id</i>	(Optional) Interface
<i>__readonly__</i>	(Optional)
<i>TABLE_delay</i>	(Optional)
<i>interface</i>	(Optional) Interface
<i>min_delay</i>	(Optional) Min delay
<i>reload_delay</i>	(Optional) Reload delay

## Command Mode

- /exec

# show hsrp mgo

```
show hsrp mgo [ name <name> | brief ] [ __readonly__ TABLE_hsrp_mgo <master_name> <master_interface>
<master_address_family> <master_group_id> [ <master_version> ] <master_state> [ <master_down_reason>
] [ { TABLE_slave <slave_interface> <slave_group_id> <slave_state> [ <slave_down_reason> } ] [
<num_slave_group> ] ]
```

## Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
mgo	Show HSRP mgo details
name	(Optional) Redundancy name string
<i>name</i>	(Optional) name string
brief	(Optional) show HSPR mgo brief
<i>__readonly__</i>	(Optional)
TABLE_hsrp_mgo	(Optional)
<i>master_name</i>	(Optional) HSRP master name
<i>master_interface</i>	(Optional) HSRP master interface
<i>master_address_family</i>	(Optional) HSRP master AF
<i>master_group_id</i>	(Optional) HSRP master group ID
<i>master_version</i>	(Optional) HSRP master version
<i>master_state</i>	(Optional) HSRP master state
<i>master_down_reason</i>	(Optional) HSRP master down reason
TABLE_slave	(Optional) Slave table
<i>slave_interface</i>	(Optional) HSRP slave interface
<i>slave_group_id</i>	(Optional) HSRP slave group id
<i>slave_state</i>	(Optional) HSRP slave state
<i>slave_down_reason</i>	(Optional) HSRP slave down reason
<i>num_slave_group</i>	(Optional) HSRP number of slave groups

## Command Mode

- /exec



## show hsrp summary

```
show hsrp summary [ __readonly__ <switchover_notify_rxed> <bfd_enabled> <num_of_groups>
<num_of_v4_v1_groups> <num_of_v4_v2_groups> <num_of_v6_v2_groups> <num_of_active_groups>
<num_of_standby_groups> <num_of_listen_groups> <num_of_v6_active_groups>
<num_of_v6_standby_groups> <num_of_v6_listen_groups> <num_of_hsrp_enabled_ifs> <counter_pkts_tx>
<counter_pkts_tx_failure> <counter_pkts_in> <counter_pkts_bad_vr> <counter_mts_rx> ]
```

### Syntax Description

show	Show running system information
hsrp	Hot Standby Router Protocol (HSRP) information
summary	Show HSRP summary
<i>__readonly__</i>	(Optional)
<i>switchover_notify_rxed</i>	(Optional) Switchover notification received (1 => active)
<i>bfd_enabled</i>	(Optional) BFD status
<i>num_of_groups</i>	(Optional) Total number of groups
<i>num_of_v4_v1_groups</i>	(Optional) Number of IPv4 V1 groups
<i>num_of_v4_v2_groups</i>	(Optional) Number of IPv4 V2 groups
<i>num_of_v6_v2_groups</i>	(Optional) Number of IPv6 V2 groups
<i>num_of_active_groups</i>	(Optional) Number of active groups
<i>num_of_standby_groups</i>	(Optional) Number of standby groups
<i>num_of_listen_groups</i>	(Optional) Number of listen groups
<i>num_of_v6_active_groups</i>	(Optional) Number of IPv6 active groups
<i>num_of_v6_standby_groups</i>	(Optional) Number of IPv6 standby groups
<i>num_of_v6_listen_groups</i>	(Optional) Number of IPv6 listen groups
<i>num_of_hsrp_enabled_ifs</i>	(Optional) Number of HSRP enabled interfaces
<i>counter_pkts_tx</i>	(Optional) Number of packet transmission successes
<i>counter_pkts_tx_failure</i>	(Optional) Number of packet transmission failure
<i>counter_pkts_in</i>	(Optional) Number of packets received successfully
<i>counter_pkts_bad_vr</i>	(Optional) Number of packets for unknown groups
<i>counter_mts_rx</i>	(Optional) Number of MTS messages received

### Command Mode

- /exec