



## V Show Commands

---

- [show vdc](#), on page 3
- [show vdc current-vdc](#), on page 5
- [show vdc fcoe-vlan-range](#), on page 6
- [show vdc resource](#), on page 7
- [show vdc resource](#), on page 8
- [show vdc resource template](#), on page 9
- [show version](#), on page 10
- [show version epld](#), on page 13
- [show version image](#), on page 14
- [show version module](#), on page 15
- [show version module epld](#), on page 16
- [show virtual-service](#), on page 18
- [show virtual-service storage pool list](#), on page 21
- [show virtual-service tech-support](#), on page 22
- [show virtual-service utilization name](#), on page 23
- [show virtual-service version](#), on page 24
- [show vlan](#), on page 25
- [show vlan access-list](#), on page 27
- [show vlan access-map](#), on page 31
- [show vlan all-ports](#), on page 32
- [show vlan counters](#), on page 33
- [show vlan dot1Q tag native](#), on page 34
- [show vlan fcoe](#), on page 35
- [show vlan filter](#), on page 36
- [show vlan id](#), on page 37
- [show vlan id counters](#), on page 39
- [show vlan id vn-segment](#), on page 41
- [show vlan name](#), on page 42
- [show vlan private-vlan](#), on page 44
- [show vlan private-vlan type](#), on page 45
- [show vlan xbrief](#), on page 46
- [show vlan xsummary](#), on page 47
- [show vmtracker](#), on page 48

- [show vmtracker certificate](#), on page 50
- [show vmtracker fabric auto-config](#), on page 51
- [show vmtracker status](#), on page 52
- [show vpc](#), on page 53
- [show vpc](#), on page 56
- [show vpc consistency-parameters](#), on page 57
- [show vpc consistency-parameters vlans](#), on page 58
- [show vpc fabric-ports](#), on page 59
- [show vpc orphan-ports](#), on page 60
- [show vpc peer-keepalive](#), on page 61
- [show vpc role](#), on page 62
- [show vpc statistics peer-keepalive](#), on page 63
- [show vpc statistics vpc](#), on page 64
- [show vpc virtual-peerlink dest reachable](#), on page 65
- [show vpc virtual-peerlink vlan consistency](#), on page 66
- [show vrf](#), on page 67
- [show vrf](#), on page 68
- [show vrrp](#), on page 70
- [show vrrp bfd-sessions](#), on page 73
- [show vrrpv3](#), on page 74
- [show vrss client](#), on page 78
- [show vrss pathway](#), on page 79
- [show vrss server](#), on page 80
- [show vrss tag](#), on page 81
- [show vsan](#), on page 82
- [show vsan membership](#), on page 83
- [show vsan membership interface](#), on page 84
- [show vsan usage](#), on page 85
- [show vtp counters](#), on page 86
- [show vtp interface](#), on page 87
- [show vtp password](#), on page 88
- [show vtp status](#), on page 89

# show vdc

```
{ show vdc [ <e-vdc2> ] [ feature-set | detail | membership [ all | status | module <module> ] | shared membership ] [ __readonly__ [ detail2 ] [ <swmode> ] { TABLE_vdc <vdc_id> <vdc_name> <state> <mac> <hap> <sw> <boot_order> [ <prio> <prio_per> ] [ <create_time> ] [ <reload_count> ] [ <restart_count> ] [ <restart_time> ] [ <restart_reason> ] <vtype> <lc-support> [ TABLE_fs <fs_id> <fs_name> ] [ TABLE_port <port-list> ] } ] }
```

## Syntax Description

show	Show Virtual Device Contexts
vdc	Show Virtual Device Contexts
<i>e-vdc2</i>	(Optional) Enter Virtual Device Context <vdc-id>
detail	(Optional) Show detailed vdc information
membership	(Optional) Show vdc interface membership information
shared	(Optional) Show the shared interfaces in a vdc
membership	(Optional) Show the shared interfaces in a vdc
module	(Optional) Show vdc interface membership information for a specific module only
<i>module</i>	(Optional) Show vdc interface membership information for a specific module only
status	(Optional) Show vdc related port-status
feature-set	(Optional) Show vdc feature-set information
all	(Optional) Show offline modules as well
__readonly__	(Optional) Read Only
detail2	(Optional)
<i>swmode</i>	(Optional)
TABLE_vdc	(Optional)
<i>vdc_id</i>	(Optional) vdc-id
TABLE_port	(Optional)
<i>port-list</i>	(Optional) port membership for VDC
<i>vdc_name</i>	(Optional) vdc-name
<i>state</i>	(Optional) state
<i>mac</i>	(Optional) mac address for VDC

show vdc

<i>hap</i>	(Optional) hap policy
<i>sw</i>	(Optional) sw policy
<i>vtype</i>	(Optional)
<i>lc-support</i>	(Optional)
<i>create_time</i>	(Optional)
<i>reload_count</i>	(Optional)
<i>restart_count</i>	(Optional)
<i>restart_time</i>	(Optional)
<i>restart_reason</i>	(Optional)
TABLE_fs	(Optional)
<i>fs_id</i>	(Optional) fs id
<i>fs_name</i>	(Optional)
<i>boot_order</i>	(Optional)
<i>prio</i>	(Optional)
<i>prio_per</i>	(Optional)

**Command Mode**

- /exec

# show vdc current-vdc

show vdc current-vdc [ \_\_readonly\_\_ <mode> <name> ]

## Syntax Description

show	Show Virtual Device Contexts
vdc	Show Virtual Device Contexts
current-vdc	Show which vdc you are currently in
__readonly__	(Optional) Read Only
<i>mode</i>	(Optional) cli mode
<i>name</i>	(Optional) vdc name

## Command Mode

- /exec

show vdc fcoe-vlan-range

## show vdc fcoe-vlan-range

show vdc fcoe-vlan-range [ \_\_readonly\_\_ <fcoe-vdc> [ <fcoe-vlans> ] [ <sharing-vdcs> ] ]

### Syntax Description

show	Show Virtual Device Contexts
vdc	Show Virtual Device Contexts
fcoe-vlan-range	vlans reserved for FCoE
__readonly__	(Optional) Read Only
<i>fcoe-vdc</i>	(Optional)
<i>sharing-vdcs</i>	(Optional)
<i>fcoe-vlans</i>	(Optional)

### Command Mode

- /exec

# show vdc resource

```
show vdc <id> resource [ <res-mgr-res-known-name> ] [ __readonly__ { TABLE_vdc_resource_single_vdc
<res_name> <min> <max> <used> <unused> <free> } ]
```

## Syntax Description

show	Show running system information
vdc	Show Virtual Device Contexts
<i>id</i>	Enter Virtual Device Context <vdc-id>
resource	Show resource configuration for VDC
<i>res-mgr-res-known-name</i>	(Optional) Resource name
<u>__readonly__</u>	(Optional) Read Only
<i>res_name</i>	(Optional) Resource Name
<i>min</i>	(Optional) Resource min configuration
<i>max</i>	(Optional) Resource max configuration
<i>used</i>	(Optional) Resource current usage for this VDC
<i>unused</i>	(Optional) Resource reserved for this VDC but currently not used
<i>free</i>	(Optional) Resource current free for this VDC
TABLE_vdc_resource_single_vdc	(Optional)

## Command Mode

- /exec

show vdc resource

# show vdc resource

```
show vdc resource [ <res-mgr-res-known-name> ] [ detail | hidden-too | with-flags ] + [ __readonly__ {  
    TABLE_resource <resource_name> <total_used> <total_unused> <total_free> <total_avail> <total> [  
    TABLE_vdc_resource_across_vdcs <vdc_name> <min> <max> <used> <unused> <free> ] } ]
```

## Syntax Description

show	Show running system information
vdc	Show Virtual Device Contexts
resource	Show resource configuration across VDCs
<i>res-mgr-res-known-name</i>	(Optional) Resource name
detail	(Optional) Show detail resource configuration
hidden-too	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
with-flags	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
__readonly__	(Optional) Read Only
TABLE_resource	(Optional)
<i>resource_name</i>	(Optional) Resource Name
<i>total_used</i>	(Optional) Resource current usage for all VDC
<i>total_unused</i>	(Optional) Resources currently reserved but not used across all VDC
<i>total_free</i>	(Optional) Resource current free for all VDC
<i>total_avail</i>	(Optional) Resource current available across all VDC
<i>total</i>	(Optional) Resources grand total
TABLE_vdc_resource_across_vdcs	(Optional)
<i>vdc_name</i>	(Optional) VDC name
<i>min</i>	(Optional) Resource min configuration
<i>max</i>	(Optional) Resource max configuration
<i>used</i>	(Optional) Resource current usage for this VDC
<i>unused</i>	(Optional) Resource reserved for this VDC but currently not used
<i>free</i>	(Optional) Resource current free for this VDC

## Command Mode

- /exec

# show vdc resource template

show vdc resource template [ <res-mgr-template-known-name-all> ] [ \_\_readonly\_\_ TABLE\_template <template\_name> { TABLE\_resource <resource\_name> <min> <max> } ]

## Syntax Description

show	Show running system information
vdc	Show Virtual Device Contexts
resource	Show resource configuration for VDC
template	Resource template configuration
<i>res-mgr-template-known-name-all</i>	(Optional) Resource template name
<u>__readonly__</u>	(Optional) Read Only
TABLE_template	(Optional)
<i>template_name</i>	(Optional) Resource Template Name
TABLE_resource	(Optional)
<i>resource_name</i>	(Optional) Resource Name
<i>min</i>	(Optional) Resource min configuration
<i>max</i>	(Optional) Resource max configuration

## Command Mode

- /exec

show version

# show version

```
show version [ __readonly__ <header_str> <bios_ver_str> [ <epld_ver_str> ] [ <loader_ver_str> ]
<kickstart_ver_str> <release_type> <nxos_ver_str> [ <host_nxos_ver_str> ] [ <sys_ver_str> ]
<bios_cmpl_time> <kick_file_name> <nxos_file_name> <kick_cmpl_time> <nxos_cmpl_time>
<kick_tmstmp> <nxos_tmstmp> [ <isan_file_name> ] [ <isan_cmpl_time> ] [ <isan_tmstmp> ] [
<boot_lxc_mode> ] <chassis_id> [ <module_id> ] <cpu_name> <memory> <mem_type> <proc_board_id>
<host_name> <bootflash_size> [ <slot0_size> ] [ <slot1_size> ] <kern_uptm_days> <kern_uptm_hrs>
<kern_uptm_mins> <kern_uptm_secs> [ <rr_usecs> ] [ <rr_ctime> ] <rr_reason> <rr_sys_ver> <rr_service>
<plugins> <manufacturer> [ TABLE_smu_list <install_smu_id> + ] [ TABLE_package_list <package_id>
+ ] ]
```

## Syntax Description

show	
version	Show the software version
__readonly__	(Optional)
header_str	(Optional)
bios_ver_str	(Optional)
epld_ver_str	(Optional)
loader_ver_str	(Optional)
kickstart_ver_str	(Optional)
nxos_ver_str	(Optional)
host_nxos_ver_str	(Optional)
release_type	(Optional)
sys_ver_str	(Optional)
bios_cmpl_time	(Optional)
kick_file_name	(Optional)
nxos_file_name	(Optional)
kick_cmpl_time	(Optional)
nxos_cmpl_time	(Optional)
kick_tmstmp	(Optional)
nxos_tmstmp	(Optional)
isan_file_name	(Optional)

<i>isan_cmpl_time</i>	(Optional)
<i>isan_tmstmp</i>	(Optional)
<i>boot_lxc_mode</i>	(Optional)
<i>chassis_id</i>	(Optional)
<i>module_id</i>	(Optional)
<i>cpu_name</i>	(Optional)
<i>memory</i>	(Optional)
<i>mem_type</i>	(Optional)
<i>proc_board_id</i>	(Optional)
<i>host_name</i>	(Optional)
<i>bootflash_size</i>	(Optional)
<i>slot0_size</i>	(Optional)
<i>slot1_size</i>	(Optional)
<i>kern_uptm_days</i>	(Optional)
<i>kern_uptm_hrs</i>	(Optional)
<i>kern_uptm_mins</i>	(Optional)
<i>kern_uptm_secs</i>	(Optional)
<i>rr_usecs</i>	(Optional)
<i>rr_ctime</i>	(Optional)
<i>rr_reason</i>	(Optional)
<i>rr_sys_ver</i>	(Optional)
<i>rr_service</i>	(Optional)
<i>plugins</i>	(Optional)
<i>manufacturer</i>	(Optional)
<i>TABLE_smu_list</i>	(Optional)
<i>install_smu_id</i>	(Optional)
<i>TABLE_package_list</i>	(Optional)
<i>package_id</i>	(Optional) Package name

**Command Mode**

show version

- /exec

# show version epld

show version epld <uri0> [ \_\_readonly\_\_ <image-info> [ { TABLE\_module\_info <module-type> <model> <epld-device> <version> } ] ]

## Syntax Description

show	Show running system information
version	Show the software version
epld	Show CPLD versions available in CPLD image
<i>uri0</i>	Local URI containing CPLD Image
<u>__readonly__</u>	(Optional)
<i>image-info</i>	(Optional) image file info
TABLE_module_info	(Optional)
<i>module-type</i>	(Optional) module type
<i>model</i>	(Optional) model
<i>epld-device</i>	(Optional) epld device
<i>version</i>	(Optional) version

## Command Mode

- /exec

show version image

## show version image

```
show version image <uri0> [ __readonly__ <md5_str> <img_file_name> [ <bios_ver_str> ] <sys_ver_str>
<img_cmpl_time> [ <img_tmstmp> ] ]
```

### Syntax Description

show	Show running system information
version	Show the software version
image	Show the software version of a given image
<i>uri0</i>	Enter URI
<i>__readonly__</i>	(Optional)
<i>md5_str</i>	(Optional)
<i>img_file_name</i>	(Optional)
<i>bios_ver_str</i>	(Optional)
<i>sys_ver_str</i>	(Optional)
<i>img_cmpl_time</i>	(Optional)
<i>img_tmstmp</i>	(Optional)

### Command Mode

- /exec

# show version module

```
show version module <module> [ __readonly__ { TABLE_version <slot> <type> <sw> <interim> <bios> } ]
```

## Syntax Description

show	Show running system information
version	Show the software version
module	Show the software version of a Module
<i>module</i>	Enter module number
<u>__readonly__</u>	(Optional)
TABLE_version	(Optional) Show version info
<i>slot</i>	(Optional) Slot
<i>type</i>	(Optional) image type
<i>sw</i>	(Optional) SW version
<i>interim</i>	(Optional) SW interim version
<i>bios</i>	(Optional) BIOS version

## Command Mode

- /exec

show version module epld

## show version module epld

```
show version module <module> epld [ __readonly__ { [ <header_info> ] [ <module> ] [ <mi_iofpga><version> ]
] [ <io_fpga><version> ] [ <mi_iofpga2><version> ] [ <mi_iofpga3><version> ] [ <mi_iofpga4><version>
] [ <mi_iofpga5><version> ] [ <mi_iofpga6><version> ] [ <mi_iofpga7><version> ] [ <mi_iofpga8>
<version> ] [ <mi_iofpga9><version> ] [ <mi_iofpga10><version> ] [ <cpu_iofpga><version> ] [ <db_fpga>
<version> ] } ]
```

### Syntax Description

show	Show running system information
version	Show the software version
module	Show the software version of a Module
<i>module</i>	Enter module number
epld	Show a module's current EPLD versions
<i>__readonly__</i>	(Optional)
<i>header_info</i>	(Optional)
<i>module</i>	(Optional)
<i>mi_iofpga</i>	(Optional)
<i>io_fpga</i>	(Optional)
<i>mi_iofpga2</i>	(Optional)
<i>mi_iofpga3</i>	(Optional)
<i>mi_iofpga4</i>	(Optional)
<i>mi_iofpga5</i>	(Optional)
<i>mi_iofpga6</i>	(Optional)
<i>mi_iofpga7</i>	(Optional)
<i>mi_iofpga8</i>	(Optional)
<i>mi_iofpga9</i>	(Optional)
<i>mi_iofpga10</i>	(Optional)
<i>cpu_iofpga</i>	(Optional)
<i>db_fpga</i>	(Optional)
<i>version</i>	(Optional)

### Command Mode

- /exec

show virtual-service

# show virtual-service

```
show virtual-service [ { list } | { global } | { detail [ name <virt_serv_name> ] } | { core [ name <virt_serv_name_core> ] } ][ __readonly__ [ <infrastructure_major_version><infrastructure_minor_version> <total_virtual_services_installed><total_virtual_services_activated><machine_types_supported><machine_types_disabled><maximum_vcpus_per_virtual_service> TABLE_resource_limits <media_name><quota><committed><available> ] [ TABLE_list <name><status><package_name> ] [ TABLE_detail <name><state><package_name><ova_path><application_name><application_version><application_description><key_type><signing_method><licensing_name><licensing_version><disk_reservation><memory_reservation><cpu_reservation> TABLE_attached_devices <type><name><alias> ] [ TABLE_core <name><name_core> ] ]
```

## Syntax Description

show	Show running system information
virtual-service	Display virtualization service information
global	(Optional) Virtual service global information
list	(Optional) List virtual services
detail	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
core	(Optional) Core information
name	(Optional) Information for a specific virtual service
<i>virt_serv_name</i>	(Optional) Name of a virtual service
<i>virt_serv_name_core</i>	(Optional) Name of a virtual service
<u>__readonly__</u>	(Optional) Read Only
<i>infrastructure_major_version</i>	(Optional) Infrastructure major version
<i>infrastructure_minor_version</i>	(Optional) Infrastructure minor version
<i>total_virtual_services_installed</i>	(Optional) Total virtual services installed
<i>total_virtual_services_activated</i>	(Optional) Total virtual services activated
<i>maximum_vcpus_per_virtual_service</i>	(Optional) Maximum VCPUs per virtual service
<i>machine_types_supported</i>	(Optional) Machine types supported
<i>machine_types_disabled</i>	(Optional) Machine types disabled
TABLE_resource_limits	(Optional) Virtual service global resource limits
<i>media_name</i>	(Optional) Resource name
<i>quota</i>	(Optional) Resource Virtualization quota

<i>committed</i>	(Optional) Resource Virtualization committed
<i>available</i>	(Optional) Resource Virtualization available
TABLE_list	(Optional) Virtual service list table
<i>name</i>	(Optional) Virtual service name
<i>status</i>	(Optional) Virtual service status
<i>package_name</i>	(Optional) Virtual service package name
TABLE_detail	(Optional) Virtual service detail table
<i>name</i>	(Optional) Virtual service name
<i>package_name</i>	(Optional) Virtual service package name
<i>application_name</i>	(Optional) Name of the application
<i>application_version</i>	(Optional) Version of the application
<i>application_description</i>	(Optional) Description of the application
<i>key_type</i>	(Optional) Virtual service key type
<i>signing_method</i>	(Optional) Method used to sign the package
<i>licensing_name</i>	(Optional) Name of the license
<i>licensing_version</i>	(Optional) Version of the license
<i>ova_path</i>	(Optional) Virtual service OVA path
<i>state</i>	(Optional) Virtual service state
<i>disk_reservation</i>	(Optional) Virtual service disk reservation
<i>memory_reservation</i>	(Optional) Virtual service memory reservation
<i>cpu_reservation</i>	(Optional) Virtual service CPU reservation
TABLE_attached_devices	(Optional) Attached devices table
<i>type</i>	(Optional) Type of the attached device
<i>name</i>	(Optional) Name of the attached device
<i>alias</i>	(Optional) Alias for the attached device
TABLE_core	(Optional) Virtual service core table
<i>name</i>	(Optional) Virtual service name
<i>name_core</i>	(Optional) Name of core

**Command Mode**

show virtual-service

- /exec

# show virtual-service storage pool list

```
show virtual-service storage pool list [ __readonly__ [ TABLE_storage <pool_name> <pool_type> <pool_path> ] ]
```

## Syntax Description

show	Show running system information
virtual-service	Display virtualization service storage pool information
storage	Storage information about virtual service
pool	Storage pool information about virtual service
list	List storage pool for virtual service
__readonly__	(Optional) Read Only
TABLE_storage	(Optional) Virtual service storage pool list table
<i>pool_name</i>	(Optional) Virtual service storage pool name
<i>pool_type</i>	(Optional) Virtual service storage pool type
<i>pool_path</i>	(Optional) Virtual service storage pool path

## Command Mode

- /exec

```
show virtual-service tech-support
```

# show virtual-service tech-support

show virtual-service tech-support

## Syntax Description

show	Show running system information
virtual-service	Gather information for virtualization services trouble shooting
tech-support	Gather information for trouble shooting

## Command Mode

- /exec

# show virtual-service utilization name

```
show virtual-service utilization name <virt_serv_name> [ __readonly__ [ TABLE_cpu <request> <actual> <state> ] [ TABLE_memory <allocation> <used> ] [ TABLE_storage <name> <alias> <capacity> <used> <available> <usage> ] ]
```

## Syntax Description

show	Show running system information
virtual-service	Display virtualization service utilization information
utilization	Utilization information about virtual service
name	Utilization of a virtual service
<i>virt_serv_name</i>	Name of a virtual service
<u>__readonly__</u>	(Optional) Read Only
TABLE_storage	(Optional) Virtual service storage utilization
<i>name</i>	(Optional) storage device name
<i>alias</i>	(Optional) storage device alias
<i>capacity</i>	(Optional) Capacity 1k blocks
<i>used</i>	(Optional) Used 1k blocks
<i>available</i>	(Optional) Available 1k blocks
<i>usage</i>	(Optional) Usage
TABLE_memory	(Optional) Virtual service memory utilization
<i>allocation</i>	(Optional) Memory allocation
<i>used</i>	(Optional) Memory used
TABLE_cpu	(Optional) Virtual service cpu utilization
<i>request</i>	(Optional) Requested Application Utilization
<i>actual</i>	(Optional) Actual Application Utilization
<i>state</i>	(Optional) CPU state

## Command Mode

- /exec

show virtual-service version

# show virtual-service version

```
show virtual-service version { { installed } | { name <virt_serv_name> installed } } [ __readonly__
<virt_service_name><application_name><application_version> ]
```

## Syntax Description

show	Show running system information
virtual-service	Display virtualization service version information
version	Version information about virtual service
installed	Installed version
name	Version of a virtual service
<i>virt_serv_name</i>	Name of a virtual service
<u>__readonly__</u>	(Optional) Read Only
<i>virt_service_name</i>	(Optional) Virtual service name
<i>application_name</i>	(Optional) Application name
<i>application_version</i>	(Optional) Application version

## Command Mode

- /exec

# show vlan

```
show vlan [ controller ] [ __readonly__ <vlanshowbr-hdr> { TABLE_vlanbrief <vlanshowbr-vlanid>
<vlanshowbr-vlanid-utf> <vlanshowbr-vlanname> <vlanshowbr-vlanstate> <vlanshowbr-shutstate> [
<vlanshowplist-ifidx> + ] } <vlanshowinfo-mtu-hdr> { TABLE_mtuinfo <vlanshowinfo-vlanid>
<vlanshowinfo-media-type> <vlanshowinfo-vlanmode> } [ <vlanshowrspan-hdr1> ] [
<vlanshowrspan-vlantype> ] [ <vlanshowrspan-hdr2> ] [ <vlanshowrspan-vlanbitmap> ] [ <pvlan-hdr> ] [
<pvlan-section> ] [ <pvlan-stby> ] <show-end> [ <true-end> ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
controller	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
__readonly__	(Optional) Read Only
TABLE_vlanbrief	(Optional) VLAN brief table format
TABLE_mtuinfo	(Optional) MTU information table format
vlanshowbr-hdr	(Optional) VLAN brief header
vlanshowbr-vlanid	(Optional) VLAN brief VLAN ID
vlanshowbr-vlanid-utf	(Optional) VLAN brief VLAN ID
vlanshowbr-vlanname	(Optional) VLAN brief VLAN name
vlanshowbr-vlanstate	(Optional) VLAN brief VLAN state
vlanshowbr-shutstate	(Optional) VLAN brief shutdown state
vlanshowplist-ifidx	(Optional) Port list ifindex
vlanshowinfo-mtu-hdr	(Optional) Vlan info mtu header
vlanshowinfo-vlanid	(Optional) Vlan info VLAN ID
vlanshowinfo-media-type	(Optional) Select media type
vlanshowinfo-vlanmode	(Optional) VLAN brief VLAN mode
vlanshowrspan-hdr1	(Optional) RSPAN VLAN header for one VLAN
vlanshowrspan-hdr2	(Optional) RSPAN VLAN header for multiple VLANs
vlanshowrspan-vlantype	(Optional) RSPAN VLAN one VLAN rspan or non-rspan
vlanshowrspan-vlanbitmap	(Optional) RSPAN VLAN multiple VLANs
show-end	(Optional) Show vlan end marker

**show vlan**

<i>true-end</i>	(Optional) Show vlan end marker
<i>pvlan-hdr</i>	(Optional) private vlan section
<i>pvlan-section</i>	(Optional) private vlan section
<i>pvlan-stby</i>	(Optional) private vlan section on standby

**Command Mode**

- /exec

# show vlan access-list

```
show vlan access-list <name> [ <inp_seqno> ] [ __readonly__ TABLE_vacl <vacl_name> [ <vacl_seqno> ]
[ TABLE_list<ip_ipv6_mac><acl_name> [ TABLE_seqno <seqno> { <permitdeny> [ <proto_str> | <proto>
| <ip> | <ipv6> ] { <src_any> | <src_ip_prefix> | <src_ip_addr> <src_ip_mask> | <src_ipv6_prefix> |
<src_ipv6_addr> <src_ipv6_mask> | <mac_src> <mac_src_wild> | <src_addrgrp> } [ <src_port_op> [
<src_port1_str> ] { <src_port1_num> } [ <src_port2_str> | <src_port2_num> ] | <src_portgrp> ] { <dest_any>
| <dest_ip_prefix> | <dest_ip_addr> <dest_ip_mask> | <dest_ipv6_prefix> | <dest_ipv6_addr>
<dest_ipv6_mask> | <mac_dest> <mac_dest_wild> | <dest_addrgrp> } [ <dest_port_op> [ <dest_port1_str>
] { <dest_port1_num> } [ <dest_port2_str> | <dest_port2_num> ] | <dest_portgrp> ] [ { <icmp_type> [
<icmp_code> ] | <icmp_str> } | { <icmpv6_type> [ <icmpv6_code> ] | <icmpv6_str> } ] [ <igmp_type> |
<igmp_type_str> ] [ [ <precedence> | <precedence_str> ] [ <tos> | <tos_str> ] | <dscp> [ <dscp_mask> ] |
<dscp_str> ] | [ <ttl> ] [ <log> ] [ <telemetry_queue> ] [ <telemetry_path> ] [ <udfs> ] [ <capture_session>
] [ <fragments> ] [ <plen_op> <plen1> [ <plen2> ] ] [ <urg> ] [ <ack> ] [ <psh> ] [ <rst> ] [ <syn> ] [ <fin>
] [ <established> ] [ <http-method> | <http_opt_str> ] [ <tcp-option-length> ] [ <tcp-flags-mask> ] [
<flow_label> ] [ <timerange> ] [ <eth_proto> | <eth_proto_str> ] [ <vlan> ] [ <cos> ] [ <match_count> ] | [
TABLE_match <module> <module_match_count> ] | [ <nve_vni> ] | [ <nve_vni> ] | [ <label1> [ <label2>
<label3> <label4> ] <remark> } ] [ <action> <actionid> ] ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
access-list	Vlan access list
<i>name</i>	List name
<i>inp_seqno</i>	(Optional) Sequence number
<i>vacl_name</i>	(Optional) List name
<i>__readonly__</i>	(Optional)
<i>vacl_seqno</i>	(Optional) Sequence number
TABLE_vacl	(Optional)
TABLE_list	(Optional)
<i>ip_ipv6_mac</i>	(Optional) IP/iIPV6/MAC
<i>acl_name</i>	(Optional) Access list name
<i>seqno</i>	(Optional) Sequence number
<i>permitdeny</i>	(Optional) Permit/deny
<i>proto</i>	(Optional) A protocol number
TABLE_seqno	(Optional)
<i>proto_str</i>	(Optional) Protocol name

show vlan access-list

<i>ip</i>	(Optional) IP
<i>ipv6</i>	(Optional) IPV6
<i>src_any</i>	(Optional) SRCAny
<i>dest_any</i>	(Optional) DESTAny
<i>src_ip_prefix</i>	(Optional) Source IP prefix
<i>src_ip_addr</i>	(Optional) Source IP address
<i>src_ip_mask</i>	(Optional) Source IP mask
<i>mac_src</i>	(Optional) Source MAC address
<i>mac_src_wild</i>	(Optional) Source MAC mask
<i>dest_ip_prefix</i>	(Optional) Destination IP prefix
<i>dest_ip_addr</i>	(Optional) Destination IP address
<i>dest_ip_mask</i>	(Optional) Destination IP mask
<i>mac_dest</i>	(Optional) Destination MAC address
<i>mac_dest_wild</i>	(Optional) Destination MAC mask
<i>src_port_op</i>	(Optional) Source Port operator
<i>dest_port_op</i>	(Optional) Destination Port operator
<i>src_port1_str</i>	(Optional) Source port name
<i>src_port1_num</i>	(Optional) Source port number
<i>src_port2_str</i>	(Optional) Source port name
<i>src_port2_num</i>	(Optional) Source port number
<i>dest_port1_str</i>	(Optional) Destination port name
<i>dest_port1_num</i>	(Optional) Destination port number
<i>dest_port2_str</i>	(Optional) Destination port name
<i>dest_port2_num</i>	(Optional) Destination port number
<i>icmp_type</i>	(Optional) ICMP type
<i>icmp_code</i>	(Optional) ICMP code
<i>icmp_str</i>	(Optional) ICMP message
<i>icmpv6_type</i>	(Optional) ICMP type
<i>icmpv6_code</i>	(Optional) ICMP code

<i>icmpv6_str</i>	(Optional) ICMP message
<i>igmp_type</i>	(Optional) IGMP type
<i>igmp_type_str</i>	(Optional) IGMP type String
<i>precedence</i>	(Optional) precedence
<i>precedence_str</i>	(Optional) precedence string
<itos< i=""></itos<>	(Optional) tos
<i>tos_str</i>	(Optional) tos string
<i>dscp</i>	(Optional) dscp
<i>dscp_mask</i>	(Optional) dscp mask
<i>dscp_str</i>	(Optional) dscp string
<i>udfs</i>	(Optional) udfs string
<i>ttl</i>	(Optional) ttl
<i>capture_session</i>	(Optional) capture session
<i>log</i>	(Optional) Log
<i>telemetry_queue</i>	(Optional) telemetry_queue
<i>telemetry_path</i>	(Optional) telemetry_path
<i>fragments</i>	(Optional) Fragments
<i>urg</i>	(Optional) URG
<i>ack</i>	(Optional) ACK
<i>psh</i>	(Optional) PSH
<i>rst</i>	(Optional) RST
<i>syn</i>	(Optional) SYN
<i>fin</i>	(Optional) FIN
<i>established</i>	(Optional) ESTABLISHED
<i>http-method</i>	(Optional) http-method
<i>http_opt_str</i>	(Optional) http_option string
<i>tcp-option-length</i>	(Optional) TCP Option size
<i>tcp-flags-mask</i>	(Optional) TCP Flags mask
<i>flow_label</i>	(Optional) IPv6 flow label

**show vlan access-list**

<i>timerange</i>	(Optional) Time-range
<i>eth_proto</i>	(Optional) MAC protocol number
<i>eth_proto_str</i>	(Optional) MAC protocol name
<i>vlan</i>	(Optional) VLAN number
<i>cos</i>	(Optional) CoS value
<i>match_count</i>	(Optional) Number of packets matching the ACL
<i>TABLE_match</i>	(Optional)
<i>module</i>	(Optional) Module name
<i>module_match_count</i>	(Optional) Number of packets matching the ACL
<i>nve_vni</i>	(Optional) nve vni
<i>remark</i>	(Optional) Remark String
<i>src_addrgrp</i>	(Optional) Source address group
<i>dest_addrgrp</i>	(Optional) Destination address group
<i>src_portgrp</i>	(Optional) Source port group
<i>dest_portgrp</i>	(Optional) Destination port group
<i>plen_op</i>	(Optional) Source Port operator
<i>plen1</i>	(Optional) Packet length minimum
<i>plen2</i>	(Optional) packet length maximum
<i>label1</i>	(Optional) mpls label one
<i>label2</i>	(Optional) mpls label two
<i>label3</i>	(Optional) mpls label three
<i>label4</i>	(Optional) mpls label four
<i>action</i>	(Optional) Action
<i>actionid</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535> redirect_all: Ethernet1/1,port-channel1

### Command Mode

- /exec

# show vlan access-map

```
show vlan access-map [ <name> ] [ __readonly__ [ TABLE_vacl <vacl_name> [ TABLE_seqno [ <seqno> ] [ <ip_ipv6_mac> { <match_name> } + [ <action_drop> ] [ <action_log> ] [ <action_telemetry_queue> ] [ <action_telemetry_path> ] [ <action_fwd> ] [ <action_capture> ] [ <action_redirect> <intf> ] ] [ <statistics> ] ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
access-map	List VLAN access maps
<i>name</i>	(Optional) List name
<i>vacl_name</i>	(Optional) List name
<i>__readonly__</i>	(Optional)
<i>seqno</i>	(Optional) Sequence number
TABLE_vacl	(Optional)
TABLE_seqno	(Optional)
<i>ip_ipv6_mac</i>	(Optional) IP/iIPV6/MAC
<i>match_name</i>	(Optional) Access list name
<i>action_drop</i>	(Optional) DROP
<i>action_log</i>	(Optional) LOG
<i>action_telemetry_queue</i>	(Optional) telemetry_queue
<i>action_telemetry_path</i>	(Optional) telemetry_path
<i>action_fwd</i>	(Optional) FWD
<i>action_capture</i>	(Optional) CAPTURE
<i>action_redirect</i>	(Optional) REDIRECT
<i>intf</i>	(Optional) Interface traffic is redirected to
<i>statistics</i>	(Optional) STATISTICS

## Command Mode

- /exec

show vlan all-ports

# show vlan all-ports

```
show vlan all-ports [ __readonly__ <vlanshowbr-hdr> { TABLE_vlanbriefallports <vlanshowbr-vlanid>
<vlanshowbr-vlanid-utf> <vlanshowbr-vlanname> <vlanshowbr-vlanstate> <vlanshowbr-shutstate> [
<vlanshowplist-ifidx> + ] } <show-end> [ <true-end> ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
all-ports	Show all ports on VLAN
<u>__readonly__</u>	(Optional) Read Only
TABLE_vlanbriefallports	(Optional) VLAN brief table format
<i>vlanshowbr-hdr</i>	(Optional) VLAN brief header
<i>vlanshowbr-vlanid</i>	(Optional) VLAN brief VLAN ID
<i>vlanshowbr-vlanid-utf</i>	(Optional) VLAN brief VLAN ID
<i>vlanshowbr-vlanname</i>	(Optional) VLAN brief VLAN name
<i>vlanshowbr-vlanstate</i>	(Optional) VLAN brief VLAN state
<i>vlanshowbr-shutstate</i>	(Optional) VLAN brief shutdown state
<i>vlanshowplist-ifidx</i>	(Optional) Port list ifindex
<i>show-end</i>	(Optional) Show vlan end marker
<i>true-end</i>	(Optional) Show vlan end marker

## Command Mode

- /exec

# show vlan counters

```
show vlan counters [ __readonly__ { TABLE_vlancounters <vlanshowbr-vlanid> [ <l2_ing_unicast_b> ] [ <l2_ing_unicast_p> ] [ <l2_ing_multicast_b> ] [ <l2_ing_multicast_p> ] [ <l2_ing_broadcast_b> ] [ <l2_ing_broadcast_p> ] [ <l2_egress_unicast_b> ] [ <l2_egress_unicast_p> ] [ <l3_unicast_recv_b> ] [ <l3_unicast_recv_p> ] [ <total_recv_b> ] [ <total_recv_p> ] [ <total_sent_b> ] [ <total_sent_p> ] } ]
```

## Syntax Description

show	Show running system information
vlan	Vlan commands
counters	display counters
<u>__readonly__</u>	(Optional) Read Only
TABLE_vlancounters	(Optional) vlan counters table format
vlanshowbr-vlanid	(Optional) VLAN brief VLAN ID
<i>l2_ing_unicast_b</i>	(Optional) L2 Ingress unicast octets
<i>l2_ing_unicast_p</i>	(Optional) L2 Ingress unicast packets
<i>l2_ing_multicast_b</i>	(Optional) L2 Ingress multicast octets
<i>l2_ing_multicast_p</i>	(Optional) L2 Ingress multicast packets
<i>l2_ing_broadcast_b</i>	(Optional) L2 Ingress broadcast octets
<i>l2_ing_broadcast_p</i>	(Optional) L2 Ingress broadcast packets
<i>l2_egress_unicast_b</i>	(Optional) L2 Egress unicast octets
<i>l2_egress_unicast_p</i>	(Optional) L2 Egress unicast packets
<i>l3_unicast_recv_b</i>	(Optional) L3 unicast octets in
<i>l3_unicast_recv_p</i>	(Optional) L3 unicast packets in
<i>total_recv_b</i>	(Optional) Total octets in
<i>total_recv_p</i>	(Optional) Total packets in
<i>total_sent_b</i>	(Optional) Total octets out
<i>total_sent_p</i>	(Optional) Total packets out

## Command Mode

- /exec

show vlan dot1Q tag native

## show vlan dot1Q tag native

show vlan dot1Q tag native [ \_\_readonly\_\_ <tag\_native\_mode> ]

### Syntax Description

show	Show running system information
vlan	VTP VLAN status
dot1Q	Display dot1q parameters
tag	Display tag parameters
native	Display native vlan tagging
__readonly__	(Optional) Read Only
<i>tag_native_mode</i>	(Optional) Native vlan tagging mode

### Command Mode

- /exec

# show vlan fcoe

`show vlan fcoe [ <vlan-id> ] [ __readonly__ { TABLE_assoc <orig-id> <tran-id> <assoc-state> } ]`

## Syntax Description

show	Show running system information
fcoe	FCOE Congiguration
vlan	Original VLAN Status
__readonly__	(Optional) Read Only
TABLE_assoc	(Optional) Association Table Format
<i>vlan-id</i>	(Optional) VLAN ID <1-4094>
<i>orig-id</i>	(Optional) Enter original VLAN-ID being associated with translated ID
<i>tran-id</i>	(Optional) Enter VSAN-ID being associated with VLAN-ID
<i>assoc-state</i>	(Optional) Show Association Status

## Command Mode

- /exec

**show vlan filter**

# show vlan filter

```
show vlan filter [ access-map <name> | vlan <vlan> ] [ __readonly__ TABLE_vlan_filter <vacl_name> <configured_vlans> ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
filter	Information about VLAN filters
access-map	(Optional) Show the VLANs where an access-map is applied
<i>name</i>	(Optional) List name
vlan	(Optional) Show the access-map applied to a VLAN
<i>vlan</i>	(Optional) VLAN number
<u>__readonly__</u>	(Optional)
TABLE_vlan_filter	(Optional)
<i>vacl_name</i>	(Optional) List name
<i>configured_vlans</i>	(Optional) VLAN numbers

## Command Mode

- /exec

# show vlan id

```
show vlan id <vlan-id> [ __readonly__ <vlanshowbr-hdr> { TABLE_vlanbriefid <vlanshowbr-vlanid>
<vlanshowbr-vlanid-utf> <vlanshowbr-vlanname> <vlanshowbr-vlanstate> <vlanshowbr-shutstate> [
<vlanshowplist-ifidx> + ] } <vlanshowinfo-mtu-hdr> { TABLE_mtuinfoid <vlanshowinfo-vlanid>
<vlanshowinfo-media-type> <vlanshowinfo-vlanmode> } [ <vlanshow-vlanerrbitmap> ] [
<vlanshowrspan-hdr1> ] [ <vlanshowrspan-vlantype> ] [ <vlanshowrspan-hdr2> ] [
<vlanshowrspan-vlanbitmap> ] [ <pvlan-hdr> ] [ <pvlan-id-section> ] [ <pvlan-stby> ] [ <is-vtp-manageable>
] [ <is-internal> ] [ <is-reserved> ] [ <is-rspan> ] [ <is-dynamic-gvrp> ] <show-end> [ <true-end> ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
id	VLAN status by VLAN id
<i>vlan-id</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
<u>__readonly__</u>	(Optional) Read Only
TABLE_vlanbriefid	(Optional) VLAN brief table format
TABLE_mtuinfoid	(Optional) MTU information table format
<i>vlanshowbr-hdr</i>	(Optional) VLAN brief header
<i>vlanshowbr-vlanid</i>	(Optional) VLAN brief VLAN ID
<i>vlanshowbr-vlanid-utf</i>	(Optional) VLAN brief VLAN ID
<i>vlanshowbr-vlanname</i>	(Optional) VLAN brief VLAN name
<i>vlanshowbr-vlanstate</i>	(Optional) VLAN brief VLAN state
<i>vlanshowbr-shutstate</i>	(Optional) VLAN brief shutdown state
<i>vlanshowplist-ifidx</i>	(Optional) Port list ifindex
<i>vlanshowinfo-mtu-hdr</i>	(Optional) Vlan info mtu header
<i>vlanshowinfo-vlanid</i>	(Optional) Vlan info VLAN ID
<i>vlanshowinfo-media-type</i>	(Optional) Select media type
<i>vlanshowinfo-vlanmode</i>	(Optional) VLAN brief VLAN mode
<i>vlanshow-vlanerrbitmap</i>	(Optional) VLAN error bitmap
<i>vlanshowrspan-hdr1</i>	(Optional) RSPAN VLAN header for one VLAN
<i>vlanshowrspan-hdr2</i>	(Optional) RSPAN VLAN header for multiple VLANs
<i>vlanshowrspan-vlantype</i>	(Optional) RSPAN VLAN one VLAN rspan or non-rspan

**show vlan id**

<i>vlanshowrspan-vlanbitmap</i>	(Optional) RSPAN VLAN multiple VLANs
<i>show-end</i>	(Optional) Show vlan end marker
<i>true-end</i>	(Optional) Show vlan end marker
<i>pvlan-hdr</i>	(Optional) private vlan section
<i>pvlan-id-section</i>	(Optional) private id vlan section
<i>pvlan-stby</i>	(Optional) private vlan section on standby
<i>is-vtp-manageable</i>	(Optional) VTP Manageable VLAN flag
<i>is-internal</i>	(Optional) Internal VLAN flag
<i>is-reserved</i>	(Optional) Reserved VLAN flag
<i>is-rspan</i>	(Optional) RSPAN VLAN flag
<i>is-dynamic-gvrp</i>	(Optional) Dynamic GVRP VLAN flag

#### Command Mode

- /exec

# show vlan id counters

```
show vlan id <vlan-id> counters [ __readonly__ { TABLE_vlancounters <vlanshowbr-vlanid> [
<l2_ing_unicast_b> ] [ <l2_ing_unicast_p> ] [ <l2_ing_multicast_b> ] [ <l2_ing_multicast_p> ] [ <l2_ing_broadcast_b> ]
[ <l2_ing_broadcast_p> ] [ <l2_egress_unicast_b> ] [ <l2_egress_unicast_p> ] [ <l3_unicast_recv_b> ] [ <l3_unicast_recv_p> ]
[ <total_recv_b> ] [ <total_recv_p> ] [ <total_sent_b> ] [ <total_sent_p> ] } ]
```

## Syntax Description

show	Show running system information
vlan	Vlan commands
id	VLAN status by VLAN id
counters	display counters
<i>vlan-id</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
<u>__readonly__</u>	(Optional) Read Only
TABLE_vlancounters	(Optional) vlan counters table format
<i>vlanshowbr-vlanid</i>	(Optional) VLAN brief VLAN ID
<i>l2_ing_unicast_b</i>	(Optional) L2 Ingress unicast octets
<i>l2_ing_unicast_p</i>	(Optional) L2 Ingress unicast packets
<i>l2_ing_multicast_b</i>	(Optional) L2 Ingress multicast octets
<i>l2_ing_multicast_p</i>	(Optional) L2 Ingress multicast packets
<i>l2_ing_broadcast_b</i>	(Optional) L2 Ingress broadcast octets
<i>l2_ing_broadcast_p</i>	(Optional) L2 Ingress broadcast packets
<i>l2_egress_unicast_b</i>	(Optional) L2 Egress unicast octets
<i>l2_egress_unicast_p</i>	(Optional) L2 Egress unicast packets
<i>l3_unicast_recv_b</i>	(Optional) L3 unicast octets in
<i>l3_unicast_recv_p</i>	(Optional) L3 unicast packets in
<i>total_recv_b</i>	(Optional) Total octets in
<i>total_recv_p</i>	(Optional) Total packets in
<i>total_sent_b</i>	(Optional) Total octets out
<i>total_sent_p</i>	(Optional) Total packets out

## Command Mode

show vlan id counters

- /exec

# show vlan id vn-segment

```
show vlan id <vlan-id> vn-segment [ __readonly__ <vlanshowinfo-segid-hdr> { TABLE_seginfoid
<vlanshowinfo-seg-vlanid> <vlanshowinfo-segment-id> } <show-end> [ <true-end> ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
id	VLAN status by VLAN id
vn-segment	Show vn-segment mapping
<i>vlan-id</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
<u>__readonly__</u>	(Optional) Read Only
TABLE_seginfoid	(Optional) Segment id information table format
<i>vlanshowinfo-segid-hdr</i>	(Optional) Vlan info segment id header
<i>vlanshowinfo-seg-vlanid</i>	(Optional) Vlan info VLAN ID
<i>vlanshowinfo-segment-id</i>	(Optional) Vlan info SEGMENT ID
<i>show-end</i>	(Optional) Show vlan end marker
<i>true-end</i>	(Optional) Show vlan end marker

## Command Mode

- /exec

show vlan name

# show vlan name

```
show vlan name <vname> [ __readonly__ <vlanshowbr-hdr> { TABLE_vlanbriefname <vlanshowbr-vlanid>
<vlanshowbr-vlanid-utf> <vlanshowbr-vlanname> <vlanshowbr-vlanstate> <vlanshowbr-shutstate> [
<vlanshowplist-ifidx> + ] } <vlanshowinfo-mtu-hdr> { TABLE_mtuinfoname <vlanshowinfo-vlanid>
<vlanshowinfo-media-type> <vlanshowinfo-vlanmode> } [ <vlanshowrspan-hdr1> ] [
<vlanshowrspan-vlantype> ] [ <vlanshowrspan-hdr2> ] [ <vlanshowrspan-vlanbitmap> ] <show-end> [
<true-end> ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
name	VLAN status by VLAN name
<i>vname</i>	A vlan name with size 32 (128 if long vlan name enabled)
<u>__readonly__</u>	(Optional) Read Only
TABLE_vlanbriefname	(Optional) VLAN brief table format
TABLE_mtuinfoname	(Optional) MTU information table format
<i>vlanshowbr-hdr</i>	(Optional) VLAN brief header
<i>vlanshowbr-vlanid</i>	(Optional) VLAN brief VLAN ID
<i>vlanshowbr-vlanid-utf</i>	(Optional) VLAN brief VLAN ID
<i>vlanshowbr-vlanname</i>	(Optional) VLAN brief VLAN name
<i>vlanshowbr-vlanstate</i>	(Optional) VLAN brief VLAN state
<i>vlanshowbr-shutstate</i>	(Optional) VLAN brief shutdown state
<i>vlanshowplist-ifidx</i>	(Optional) Port list ifindex
<i>vlanshowinfo-mtu-hdr</i>	(Optional) Vlan info mtu header
<i>vlanshowinfo-vlanid</i>	(Optional) Vlan info VLAN ID
<i>vlanshowinfo-media-type</i>	(Optional) Select media type
<i>vlanshowinfo-vlanmode</i>	(Optional) VLAN brief VLAN mode
<i>vlanshowrspan-hdr1</i>	(Optional) RSPAN VLAN header for one VLAN
<i>vlanshowrspan-hdr2</i>	(Optional) RSPAN VLAN header for multiple VLANs
<i>vlanshowrspan-vlantype</i>	(Optional) RSPAN VLAN one VLAN rspan or non-rspan
<i>vlanshowrspan-vlanbitmap</i>	(Optional) RSPAN VLAN multiple VLANs

<i>show-end</i>	(Optional) Show vlan end marker
<i>true-end</i>	(Optional) Show vlan end marker

**Command Mode**

- /exec

show vlan private-vlan

## show vlan private-vlan

```
show vlan [ id <vlan-id> ] private-vlan [ __readonly__ [ { TABLE_pvlan_primary <vlan-key> [ <primary> ] [ <secondary> ] <pvlan-type> [ <ports> + ] } ] ]
```

### Syntax Description

show	Show running system information
vlan	VLAN status
id	(Optional) VLAN status by VLAN id
<i>vlan-id</i>	(Optional) VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
private-vlan	Private VLAN information
<u>__readonly__</u>	(Optional) Read Only
TABLE_pvlan_primary	(Optional) Pvlan primary vlan table
<i>vlan-key</i>	(Optional) Vlan key
<i>primary</i>	(Optional) Primary VLAN
<i>secondary</i>	(Optional) Secondary VLAN
<i>pvlan-type</i>	(Optional) PVLAN Type
<i>ports</i>	(Optional) Port list

### Command Mode

- /exec

# show vlan private-vlan type

show vlan [ id<vlan-id> ] private-vlan type [ \_\_readonly\_\_ [ { TABLE\_pvlantype <vlan-num><pvlan-type> } ] ]

## Syntax Description

show	Show running system information
vlan	VLAN status
id	(Optional) VLAN status by VLAN id
<i>vlan-id</i>	(Optional) VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
private-vlan	Private VLAN information
type	Private VLAN type information
__readonly__	(Optional) Read Only
TABLE_pvlantype	(Optional) Pvlan type table
<i>vlan-num</i>	(Optional) vlan
<i>pvlan-type</i>	(Optional) PVLAN Type

## Command Mode

- /exec

show vlan xbrief

# show vlan xbrief

```
show vlan xbrief [ controller | cli ] [ __readonly__ <vlanshowbr-hdr> { TABLE_vlanbriefxbrief
<vlanshowbr-vlanid><vlanshowbr-vlanid-utf><vlanshowbr-vlanname><vlanshowbr-vlanstate>
<vlanshowbr-shutstate> [ <vlanshowplist-ifidx> + ] } <show-end> [ <true-end> ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
xbrief	All VLAN status in brief
controller	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
cli	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
__readonly__	(Optional) Read Only
TABLE_vlanbriefxbrief	(Optional) VLAN brief table format
vlanshowbr-hdr	(Optional) VLAN brief header
vlanshowbr-vlanid	(Optional) VLAN brief VLAN ID
vlanshowbr-vlanid-utf	(Optional) VLAN brief VLAN ID
vlanshowbr-vlanname	(Optional) VLAN brief VLAN name
vlanshowbr-vlanstate	(Optional) VLAN brief VLAN state
vlanshowbr-shutstate	(Optional) VLAN brief shutdown state
vlanshowplist-ifidx	(Optional) Port list ifindex
show-end	(Optional) Show vlan end marker
true-end	(Optional) Show vlan end marker

## Command Mode

- /exec

# show vlan xsummary

```
show vlan xsummary [ __readonly__ <vlansum-all-vlan> <vlansum-vtp-vlan> <vlansum-ext-vlan>
<vlansum-max-supported-vlan> <vlansum-carved-vlan> <show-end> [ <true-end> ] ]
```

## Syntax Description

show	Show running system information
vlan	VLAN status
xsummary	VLAN summary information
<u>__readonly__</u>	(Optional) Read Only
<i>vlansum-all-vlan</i>	(Optional) Show vlan summary Total
<i>vlansum-vtp-vlan</i>	(Optional) Show vlan summary Number of normal vlans
<i>vlansum-ext-vlan</i>	(Optional) Show vlan summary Number of extended vlans
<i>vlansum-max-supported-vlan</i>	(Optional) Show vlan summary Max supported vlans
<i>vlansum-carved-vlan</i>	(Optional) Show vlan summary Number of carved sdn vlans
<i>show-end</i>	(Optional) Show vlan end marker
<i>true-end</i>	(Optional) Show vlan end marker

## Command Mode

- /exec

show vmtracker

# show vmtracker

```
show vmtracker [ connection <conn_name> ] { { info { { [ interface <intf_id> ] { summary | detail | host |
vm | port-group } } | { vxlan-segment | vxlan-vms } } } | event-history } [ __readonly__ [ TABLE_info
<intf_name> <host_or_ip> <vmnic> <vm_name> <vm_state> <port_group> <pg_type> <vlan_range>
<virt_wire_name> <multicast_ip> <vdn_id> <vtep_ip> <event_time> <event_msg> ] [ TABLE_evt <event_id>
<event_time> <event_msg> ] ]
```

## Syntax Description

<code>__readonly__</code>	(Optional)
<code>TABLE_info</code>	(Optional)
<code>intf_name</code>	(Optional)
<code>host_or_ip</code>	(Optional)
<code>vmnic</code>	(Optional)
<code>vm_name</code>	(Optional)
<code>vm_state</code>	(Optional)
<code>port_group</code>	(Optional)
<code>pg_type</code>	(Optional)
<code>vlan_range</code>	(Optional)
<code>virt_wire_name</code>	(Optional)
<code>multicast_ip</code>	(Optional)
<code>vdn_id</code>	(Optional)
<code>vtep_ip</code>	(Optional)
<code>event_time</code>	(Optional)
<code>event_msg</code>	(Optional)
<code>TABLE_evt</code>	(Optional)
<code>event_id</code>	(Optional)
<code>event_time</code>	(Optional)
<code>event_msg</code>	(Optional)
<code>show</code>	Show running system information
<code>vmtracker</code>	Show vmtracker info
<code>connection</code>	(Optional) Show vmtracker configured connections

<i>conn_name</i>	(Optional) Show vmtracker Connection name
info	Display vmtracker information
interface	(Optional) Display vmtracker interface information
<i>intf_id</i>	(Optional) Interface name to display
summary	Display a summary of vmtracker information
detail	Display vmtracker information details
host	Display vmtracker host information
vm	Display vmtracker related Virtual Machine information
port-group	Display vmtracker related port-group information
vxlan-segment	Print all segment info
vxlan-vms	Print all vm info
event-history	Display vmtracker related event-history

**Command Mode**

- /exec

**show vmtracker certificate**

## show vmtracker certificate

show vmtracker certificate [ \_\_readonly\_\_ TABLE\_cert <certificate> ]

### Syntax Description

__readonly__	(Optional)
TABLE_cert	(Optional) The entire certificate, line by line
<i>certificate</i>	(Optional) A line of the certificate in xml
show	Show running system information
vmtracker	VMTRACKER commands
certificate	Show the default certificate used

### Command Mode

- /exec

# show vmtracker fabric auto-config

```
show vmtracker fabric auto-config [ interface <intf_id> ] [ vlan <vlan_id> ] [ status { success | pending | failure | skipped } ] [ __readonly__ { <oper_status> } [ TABLE_autoconfig <interface_name> <port_group_name> <vlan_range> <config_status> ] ]
```

## Syntax Description

<code>__readonly__</code>	(Optional)
<code>oper_status</code>	(Optional) fabric auto-config enabled or disabled
<code>TABLE_autoconfig</code>	(Optional)
<code>interface_name</code>	(Optional) interface to the UCS
<code>port_group_name</code>	(Optional) port-channel of this interface
<code>vlan_range</code>	(Optional) vlans learned
<code>config_status</code>	(Optional) status of auto-config over this interface
<code>show</code>	Show running system information
<code>vmtracker</code>	VMTRACKER commands
<code>fabric</code>	VM Tracker Fabric paramters
<code>auto-config</code>	VM Tracker Fabric AutoConfiguration
<code>interface</code>	(Optional) Display vmtracker interface information
<code>intf_id</code>	(Optional) Interface name to display
<code>vlan</code>	(Optional) vlan to display
<code>vlan_id</code>	(Optional) VLAN ID 1-4094 or range(s) like: 1-5, 10 or 2-5,7-19
<code>status</code>	(Optional) Auto-config status
<code>success</code>	(Optional) Success
<code>pending</code>	(Optional) Pending
<code>failure</code>	(Optional) Failure
<code>skipped</code>	(Optional) Skipped

## Command Mode

- /exec

show vmtracker status

## show vmtracker status

show vmtracker [ connection <conn\_name> ] status [ \_\_readonly\_\_ { TABLE\_connection <name> <host\_or\_ip> <conn\_status> } ]

### Syntax Description

<code>__readonly__</code>	(Optional)
<code>TABLE_connection</code>	(Optional)
<code>name</code>	(Optional)
<code>host_or_ip</code>	(Optional)
<code>conn_status</code>	(Optional)
<code>show</code>	Show running system information
<code>vmtracker</code>	Show vmtracker info
<code>connection</code>	(Optional) Show vmtracker configured connections
<code>conn_name</code>	(Optional) Show vmtracker Connection name
<code>status</code>	Show vmtracker connection status

### Command Mode

- /exec

# show vpc

```
show vpc [ brief ] [ __readonly__ <vpc-domain-id> [ <vpc-l2mp-switch-id> ] <vpc-peer-status>
<vpc-peer-status-reason> <vpc-peer-keepalive-status> [ <vpc-peer-l2mp-status> ] <vpc-peer-consistency>
[ <vpc-peer-consistency-reason> ] [ <vpc-peer-vlan-peer-consistency> ] <vpc-peer-consistency-status> }
<vpc-type-2-consistency> { [ <vpc-type-2-consistency-reason> ] <vpc-type-2-consistency-status> } <vpc-role>
<num-of-vpcs> [ <track-obj> ] [ <peer-gateway> ] [ <peer-gateway-excluded-vlans> ]
<dual-active-excluded-vlans> <vpc-graceful-consistency-check-status> [ <vpc-auto-recovery-status> ] [
<vpc-delay-restore-status> ] [ <vpc-delay-restore-svi-status> ] [ <vpc-delay-restore-orphan-port-status> ] [
<vpc-delay-peer-link-status> ] <operational-l3-peer> [ <vpc-scale-high-status> ] [
<fp-enhanced-load-balancing> ] [ <vpc-peer-vlan-peer-consistency> ] [ <virtual-peerlink> ] [
<vpc-peer-link-hdr> [ { TABLE_peerlink <peer-link-id> <peerlink-ifindex> <peer-link-port-state>
<peer-up-vlan-bitset> } ] <vpc-end> ] [ <vpc-hdr> [ <vpc-is-es> ] [ <vpc-not-es> ] [ { TABLE_vpc <vpc-id>
<vpc-ifindex> <vpc-port-state> <phy-port-if-removed><vpc-thru-peerlink> <vpc-consistency> { [
<vpc-consistency-reason> ] [ <vpc-consistency-status> ] } <up-vlan-bitset> <es-attr> } ] <vpc-end> ] ]
```

## Syntax Description

vpc	Virtual Port Channel configuration
brief	(Optional) Brief display of vPC status
__readonly__	(Optional) Read Only
TABLE_peerlink	(Optional) vPC peerlink table
TABLE_vpc	(Optional) vPC table
vpc-domain-id	(Optional) vPC domain id
vpc-l2mp-switch-id	(Optional) vPC+ switch ID
vpc-peer-status	(Optional) vPC peer status
vpc-peer-status-reason	(Optional) vPC peer status reason
vpc-peer-keepalive-status	(Optional) vpc peer keepalive status
vpc-peer-l2mp-status	(Optional) vPC fabricpath status
vpc-role	(Optional) vPC role
peer-gateway	(Optional) Peer gateway status
peer-gateway-excluded-vlans	(Optional) peer-gateway excluded VLANs
dual-active-excluded-vlans	(Optional) dual-active excluded VLANs
fp-enhanced-load-balancing	(Optional) Fabricpath enhanced load balancing status
num-of-vpcs	(Optional) Number of vPCs configured
track-obj	(Optional) Track object for vPC

show vpc

<i>vpc-graceful-consistency-check-status</i>	(Optional) vPC graceful consistency check
<i>vpc-consistency</i>	(Optional) vPC global configuration consistency
<i>vpc-consistency-reason</i>	(Optional) vPC consistency reason
<i>vpc-consistency-status</i>	(Optional) vPC consistency reason
<i>vpc-peer-consistency</i>	(Optional) vPC global configuration consistency
<i>vpc-peer-consistency-reason</i>	(Optional) vPC consistency reason
<i>vpc-peer-consistency-status</i>	(Optional) vPC consistency reason
<i>vpc-per-vlan-peer-consistency</i>	(Optional) vPC per-vlan global configuration consistency
<i>vpc-type-2-consistency</i>	(Optional) vPC type-2 configuration consistency status
<i>vpc-type-2-consistency-reason</i>	(Optional) vPC type-2 configuration consistency reason
<i>vpc-type-2-consistency-status</i>	(Optional) vPC type-2 configuration consistency status
<i>operational-l3-peer</i>	(Optional) Operational Layer 3 peer status
<i>virtual-peerlink</i>	(Optional) Virtual peerlink status
<i>vpc-scale-high-status</i>	(Optional) vPC scale high status
<i>vpc-hdr</i>	(Optional) Start of vPC table
<i>vpc-is-es</i>	(Optional) Flag to indicate vPC+ complex
<i>vpc-not-es</i>	(Optional) Flag to indicate vPC complex
<i>vpc-peer-link-hdr</i>	(Optional) Start of vPC peer-link table
<i>vpc-port-state</i>	(Optional) vPC port state
<i>vpc-end</i>	(Optional) End of table
<i>vpc-id</i>	(Optional) vPC id
<i>vpc-ifindex</i>	(Optional) vPC ifindex
<i>peer-link-id</i>	(Optional) peer link id
<i>peerlink-ifindex</i>	(Optional) peer link ifindex
<i>peer-link-port-state</i>	(Optional) peer-link port state
<i>peer-up-vlan-bitset</i>	(Optional) peer link UP VLAN bitset
<i>up-vlan-bitset</i>	(Optional) vPC UP VLAN bitset
<i>es-attr</i>	(Optional) vPC+ attributes
<i>vpc-auto-recovery-status</i>	(Optional) Auto-recovery status

<i>vpc-delay-restore-status</i>	(Optional) Delay-resotre status
<i>vpc-delay-restore-svi-status</i>	(Optional) Delay-restore-svi status
<i>vpc-delay-restore-orphan-port-status</i>	(Optional) Delay-restore-orphan-port status
<i>vpc-delay-peer-link-status</i>	(Optional) Delay-peer-link status

**Command Mode**

- /exec

show vpc

# show vpc

```
show vpc { <vpc-number> | brief vpc <vpc-number> } [ __readonly__ [ <vpc-hdr> ] [ <vpc-is-es> ] [ <vpc-not-es> ] [ TABLE_vpc <vpc-id><vpc-ifindex><vpc-port-state><phy-port-if-removed><vpc-thru-peerlink><vpc-consistency> { [ <vpc-consistency-reason> ] [ <vpc-consistency-status> ] } <up-vlan-bitset> <es-attr> ] <vpc-end> ]
```

## Syntax Description

vpc	Virtual Port Channel configuration
brief	Brief display of vPC status
<i>vpc-number</i>	Enter a Virtual Port Channel number
<u>__readonly__</u>	(Optional) Read Only
<i>vpc-hdr</i>	(Optional) Start of vPC table
<i>vpc-is-es</i>	(Optional) Flag to indicate vPC+ complex
<i>vpc-not-es</i>	(Optional) Flag to indicate vPC complex
TABLE_vpc	(Optional) vPC table
<i>vpc-id</i>	(Optional) vPC id
<i>vpc-ifindex</i>	(Optional) vPC ifindex
<i>vpc-port-state</i>	(Optional) vPC port state
<i>vpc-consistency</i>	(Optional) vPC global configuration consistency
<i>vpc-consistency-reason</i>	(Optional) vPC consistency reason
<i>vpc-consistency-status</i>	(Optional) vPC consistency reason
<i>up-vlan-bitset</i>	(Optional) vPC UP VLAN bitset
<i>es-attr</i>	(Optional) vPC+ attributes
<i>vpc-end</i>	(Optional) End of table

## Command Mode

- /exec

# show vpc consistency-parameters

```
show vpc consistency-parameters { global | vni | interface <if> | vpc <vpc-num> } [ __readonly__  
TABLE_vpc_consistency<vpc-param-name><vpc-param-type><vpc-param-local-val><vpc-param-peer-val>  
]
```

## Syntax Description

vpc	Virtual Port Channel configuration
consistency-parameters	Show vPC Consistency Parameters
global	Global Parameters
vni	Show vPC Consistency Parameters vni
<i>if</i>	
<i>vpc-num</i>	Enter a Virtual Port Channel number
<i>__readonly__</i>	(Optional) Read Only
TABLE_vpc_consistency	(Optional) vPC table
<i>vpc-param-name</i>	(Optional)
<i>vpc-param-type</i>	(Optional)
<i>vpc-param-local-val</i>	(Optional)
<i>vpc-param-peer-val</i>	(Optional)

## Command Mode

- /exec

show vpc consistency-parameters vlans

## show vpc consistency-parameters vlans

```
show vpc consistency-parameters vlans [ vnseg ] [ __readonly__ TABLE_vpc_consistency <vpc-param-name>
<vpc-param-type> [ <reason_code> ] [ <syserr> ] <vpc-pass-vlans> [ <reason_code> ] ]
```

### Syntax Description

vpc	Virtual Port Channel configuration
consistency-parameters	Show vPC Consistency Parameters
vlans	vlans
vnseg	(Optional) Display vlan to vn-segment map
__readonly__	(Optional) Read Only
TABLE_vpc_consistency	(Optional) vPC table
<i>vpc-param-name</i>	(Optional)
<i>vpc-param-type</i>	(Optional)
<i>vpc-pass-vlans</i>	(Optional)
<i>syserr</i>	(Optional) vPC consistency reason
<i>reason_code</i>	(Optional) vPC consistency reason

### Command Mode

- /exec

# show vpc fabric-ports

show vpc fabric-ports [ \_\_readonly\_\_ [ { TABLE\_fabric\_ports <vpc-fabric-ports> } ] ]

## Syntax Description

vpc	Virtual Port Channel configuration
fabric-ports	Show ports that are part of uplink virtual-peerlink
__readonly__	(Optional) Read Only
TABLE_fabric_ports	(Optional) vPC fabric ports table
<i>vpc-fabric-ports</i>	(Optional) description of the port

## Command Mode

- /exec

show vpc orphan-ports

## show vpc orphan-ports

show vpc orphan-ports [ \_\_readonly\_\_ [ { TABLE\_orphan\_ports <vpc-vlan> <vpc-orphan-ports> } ] ]

### Syntax Description

vpc	Virtual Port Channel configuration
orphan-ports	Show ports that are not part of vPC but have common VLANs
__readonly__	(Optional) Read Only
TABLE_orphan_ports	(Optional) vPC orphan ports table
<i>vpc-vlan</i>	(Optional) port vlan
<i>vpc-orphan-ports</i>	(Optional) description of the port

### Command Mode

- /exec

# show vpc peer-keepalive

```
show vpc peer-keepalive [ __readonly__ <vpc-peer-keepalive-status> <vpc-keepalive-dest>
<vpc-keepalive-send-interface> <vpc-keepalive-receive-interface> <vpc-keepalive-send-tstamp>
<vpc-keepalive-receive-tstamp> <vpc-peer-keepalive-up-time> <vpc-keepalive-send-status>
<vpc-keepalive-receive-status> <vpc-keepalive-lastupdate> [ <vpc-keepalive-dest> ] <vpc-keepalive-interval>
<vpc-keepalive-timeout> <vpc-keepalive-hold-timeout> <vpc-keepalive-vrf> <vpc-keepalive-udp-port>
<vpc-keepalive-tos> ]
```

## Syntax Description

vpc	Virtual Port Channel configuration
peer-keepalive	vPC keepalive status
__readonly__	(Optional) Read Only
<i>vpc-peer-keepalive-status</i>	(Optional) vpc peer keepalive status
<i>vpc-keepalive-dest</i>	(Optional) vPC keepalive destination ip address
<i>vpc-keepalive-send-status</i>	(Optional) vPC keepalive send status
<i>vpc-keepalive-receive-status</i>	(Optional) vPC keepalive receive status
<i>vpc-peer-keepalive-up-time</i>	(Optional) keepalive- alive time
<i>vpc-keepalive-send-tstamp</i>	(Optional) vPC keepalive last send timestamp
<i>vpc-keepalive-send-interface</i>	(Optional) vPC keepalive send interface
<i>vpc-keepalive-receive-tstamp</i>	(Optional) vPC keepalive last receive timestamp
<i>vpc-keepalive-receive-interface</i>	(Optional) vPC keepalive receive interface
<i>vpc-keepalive-lastupdate</i>	(Optional) vPC keepalive last update from peer
<i>vpc-keepalive-interval</i>	(Optional) vPC keepalive timeout
<i>vpc-keepalive-timeout</i>	(Optional) vPC keepalive interval
<i>vpc-keepalive-hold-timeout</i>	(Optional) hold timeout
<i>vpc-keepalive-vrf</i>	(Optional) vrf name
<i>vpc-keepalive-udp-port</i>	(Optional) udp port
<i>vpc-keepalive-tos</i>	(Optional) tos value

## Command Mode

- /exec

show vpc role

# show vpc role

```
show vpc role [ __readonly__ <vpc-peer-status> <vpc-peer-status-reason> [ <vpc-current-role> ] [ <vpc-es-current-role> ] <dual-active-detected> <vpc-system-mac> <vpc-system-prio> <vpc-local-system-mac> <vpc-local-system-prio> <vpc-local-role-prio> <vpc-peer-system-mac> <vpc-peer-system-prio> <vpc-peer-role-prio> ]
```

## Syntax Description

vpc	Virtual Port Channel configuration
role	vPC role status
__readonly__	(Optional) Read Only
<i>vpc-peer-status</i>	(Optional) vPC peer status
<i>vpc-peer-status-reason</i>	(Optional) vPC peer status reason
<i>vpc-current-role</i>	(Optional) vPC role
<i>vpc-es-current-role</i>	(Optional) vPC role
<i>dual-active-detected</i>	(Optional) Dual active detection status
<i>vpc-system-mac</i>	(Optional) vPC system mac
<i>vpc-local-system-mac</i>	(Optional) vPC local system mac
<i>vpc-peer-system-mac</i>	(Optional) vPC peer system mac
<i>vpc-system-prio</i>	(Optional) vPC system priority

## Command Mode

- /exec

# show vpc statistics peer-keepalive

show vpc statistics peer-keepalive [ \_\_readonly\_\_ <vpc-peer-keepalive-status> <vpc-keepalive-counters-tx> <vpc-keepalive-counters-rx> <vpc-keepalive-avg-rx-interval> <vpc-keepalive-peer-state-changes> ]

## Syntax Description

vpc	Virtual Port Channel configuration
statistics	Statistics
peer-keepalive	peer keepalive module related statistics
__readonly__	(Optional) Read Only
<i>vpc-peer-keepalive-status</i>	(Optional) vpc peer keepalive status
<i>vpc-keepalive-counters-tx</i>	(Optional) tx counters
<i>vpc-keepalive-counters-rx</i>	(Optional) rx counters
<i>vpc-keepalive-avg-rx-interval</i>	(Optional) avg rx interval in ms
<i>vpc-keepalive-peer-state-changes</i>	(Optional) peer state changes

## Command Mode

- /exec

```
show vpc statistics vpc
```

## show vpc statistics vpc

```
show vpc statistics { vpc <vpc_num> | peer-link }
```

### Syntax Description

vpc	Virtual Port Channel configuration
statistics	Statistics
<i>vpc_num</i>	Virtual Port Channel number
peer-link	stats for peer-link

### Command Mode

- /exec

# show vpc virtual-peerlink dest reachable

show vpc virtual-peerlink dest reachable

## Syntax Description

show	Show running system information
vpc	vPC related information
virtual-peerlink	virtual-peerlink Related show commands
dest	dest info
reachable	dest reachability

## Command Mode

- /exec

```
show vpc virtual-peerlink vlan consistency
```

## show vpc virtual-peerlink vlan consistency

show vpc virtual-peerlink vlan consistency

### Syntax Description

show	Show running system information
vpc	vPC related information
virtual-peerlink	virtual-peerlink Related show commands
vlan	vlan info for vPC
consistency	vlan vni consistency

### Command Mode

- /exec

# show vrf

show vrf [ <vrf-name> | <vrf-known-name> | all ]

## Syntax Description

show	Show running system information
vrf	Display VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display VRF information for all VRFs

## Command Mode

- /exec

show vrf

# show vrf

```
show vrf [<vrf-name> | <vrf-known-name> | all ] [ order id ] [ detail ] [ passive ] [ __readonly__ TABLE_vrf
<vrf_name><vrf_id><vrf_state> [ <vrf_reason> ] [ <vrf_pend> ] [ <vpnid><rd> [ <vni> ] <max_routes>
<mid_threshold> ] [ { TABLE_tib <tib_id><tib_af><tib_nonce><tib_state> [ <tib_reason> ] [ <tib_pend>
] } ] ]
```

## Syntax Description

show	Show running system information
vrf	Display VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display VRF information for all VRFs
order	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
id	(Optional) Order by ID
detail	(Optional) Display VRF detail information
passive	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
__readonly__	(Optional)
TABLE_vrf	(Optional)
TABLE_tib	(Optional)
<i>vrf_name</i>	(Optional)
<i>vrf_id</i>	(Optional)
<i>vrf_state</i>	(Optional)
<i>vrf_reason</i>	(Optional)
<i>vrf_pend</i>	(Optional)
<i>vpnid</i>	(Optional)
<i>rd</i>	(Optional)
<i>max_routes</i>	(Optional)
<i>mid_threshold</i>	(Optional)
<i>tib_id</i>	(Optional)
<i>tib_af</i>	(Optional)

<i>tib_nonce</i>	(Optional)
<i>tib_state</i>	(Optional)
<i>tib_reason</i>	(Optional)
<i>tib_pend</i>	(Optional)
<i>vni</i>	(Optional)

**Command Mode**

- /exec

show vrrp

# show vrrp

```
show vrrp [ [ summary ] | { [ statistics | detail ] [ interface <interface_id> ] [ vr <vr_id> ] [ master | backup | init ] + } ] [ __readonly__ [ [ TABLE_vrrp_group <sh_if_index><sh_group_id><sh_group_type><sh_group_state><sh_group_preempt><sh_vip_addr> { [ TABLE_sec_vip_addr <sh_sec_vip_addr> ] } <sh_priority> [ <sh_cfg_priority><sh_fwd_thr_lower><sh_fwd_thr_upper> ] <sh_adv_interval> [ <sh_auth_text> ] [ <sh_vmac> ] [ <sh_master_router> ] [ <sh_native_track_intf><sh_native_track_priotiry> ] { [ TABLE_vrrp_track <sh_track_object_id><sh_decrement_priority><sh_track_object_state> ] } [ <sh_bfd_status><sh_bfd_session> ] ] [ { TABLE_vrrp_statistics [ <if_index> ] [ <grp_id> ] [ <grp_type> ] [ <master_cnt> ] [ <adv_pkts> ] [ <adv_intv_mismatch> ] [ <auth_failure> ] [ <ttl_err> ] [ <zero_pri_adv_rcvd> ] [ <zero_pri_adv_sent> ] [ <type_fl_mismatch> ] [ <addr_mismatch> ] [ <inv_auth> ] [ <auth_mismatch> ] [ <inv_pkt_len> ] } ] [ <total_num_of_grp> ] [ <init_grps> ] [ <backup_grps> ] [ <master_grps> ] [ <vrrp_enabled_ifs> ] [ <mts_rx> ] [ <mts_tx> ] [ <pkt_rx> ] [ <pkt_tx> ] ] + ]
```

## Syntax Description

show	Show running system information
vrrp	Show vrrp information
summary	(Optional) Show vrrp summary
statistics	(Optional) Show vrrp statistics
detail	(Optional) Show detailed information
interface	(Optional) Show vrrp info for the interface
<i>interface_id</i>	(Optional)
vr	(Optional) Show vrrp info for the group
<i>vr_id</i>	(Optional) [1-255] enter IPv4 vr group
master	(Optional) Groups in Master state
backup	(Optional) Groups in Backup state
init	(Optional) Groups in Init state
<u>__readonly__</u>	(Optional) Read only
TABLE_vrrp_group	(Optional) Group detail table
<i>sh_if_index</i>	(Optional) Interface type and number
<i>sh_group_id</i>	(Optional) Group number
<i>sh_group_type</i>	(Optional) Group type
<i>sh_group_state</i>	(Optional) VRRP group state
<i>sh_group_preempt</i>	(Optional) Group preemption statue

<i>sh_vip_addr</i>	(Optional) Virtual IP Address
<i>TABLE_sec_vip_addr</i>	(Optional) Secondary virtual ip address table
<i>sh_sec_vip_addr</i>	(Optional) Secondary virtual ip address
<i>sh_priority</i>	(Optional) Priority of VRRP group
<i>sh_auth_text</i>	(Optional) Authentication text
<i>sh_cfg_priority</i>	(Optional) Configured priority of VRRP group
<i>sh_fwd_thr_lower</i>	(Optional) Lower forwarding threshold
<i>sh_fwd_thr_upper</i>	(Optional) Upper forwarding threshold
<i>sh_adv_interval</i>	(Optional) Advertisement interval
<i>sh_vmac</i>	(Optional) Virtual MAC
<i>sh_master_router</i>	(Optional) Master router
<i>sh_native_track_intf</i>	(Optional) Native tracked interface
<i>sh_native_track_priotiry</i>	(Optional) Decrement priority for Native tracking
<i>TABLE_vrrp_track</i>	(Optional) VRRP tracking table
<i>sh_track_object_id</i>	(Optional) Object id of tracking object
<i>sh_decrement_priority</i>	(Optional) Decrement priority
<i>sh_track_object_state</i>	(Optional) Tracking object state
<i>sh_bfd_status</i>	(Optional) BFD status
<i>sh_bfd_session</i>	(Optional) BFD session status
<i>TABLE_vrrp_statistics</i>	(Optional) VRRP statistics table
<i>if_index</i>	(Optional) Interface type and number
<i>grp_id</i>	(Optional) Group number
<i>grp_type</i>	(Optional) Group type
<i>master_cnt</i>	(Optional) VRRP Master
<i>adv_pkts</i>	(Optional) Advertisement pkts
<i>adv_intv_mismatch</i>	(Optional) Advertisement interval mismatch
<i>auth_failure</i>	(Optional) Auth failure
<i>ttl_err</i>	(Optional) TTL error
<i>zero_pri_adv_rcvd</i>	(Optional) Zero pri adv received

show vrrp

<i>zero_pri_adv_sent</i>	(Optional) Zero pri adv sent
<i>type_fl_mismatch</i>	(Optional) Invalid type field
<i>addr_mismatch</i>	(Optional) Address mismatch
<i>inv_auth</i>	(Optional) Invalid auth type
<i>auth_mismatch</i>	(Optional) Authentication mismatch
<i>inv_pkt_len</i>	(Optional) Invalid pkt length
<i>total_num_of_grp</i>	(Optional) Total Number of Groups Configured
<i>init_grps</i>	(Optional) Init groups
<i>backup_grps</i>	(Optional) Backup groups
<i>master_grps</i>	(Optional) Master groups
<i>vrrp_enabled_ifs</i>	(Optional) Number of VRRP enabled interfaces
<i>mts_rx</i>	(Optional) Total MTS Rx
<i>mts_tx</i>	(Optional) Total MTS Tx
<i>pkt_rx</i>	(Optional) Total Pkt Rx
<i>pkt_tx</i>	(Optional) Total Pkt Tx

**Command Mode**

- /exec

# show vrrp bfd-sessions

```
show vrrp bfd-sessions [ interface <interface-id> [ to <ipaddress> ] ] [ __readonly__ TABLE_bfd_sess
<interface> { <src_addr> | <src_addr_v6> } { <dst_addr> | <dst_addr_v6> } <session_state> <ref_count>
<displayed_interface> { TABLE_groups <group_id> <vrrp_state> <bfd_status> <operation> <time> } ]
```

## Syntax Description

show	Show running system information
vrrp	Show vrrp information
bfd-sessions	BFD sessions
interface	(Optional) Groups on this interface
<i>interface-id</i>	(Optional) Interface
to	(Optional) To IP address
<i>ipaddress</i>	(Optional) Sessions to IP address
__readonly__	(Optional)
TABLE_bfd_sess	(Optional)
<i>interface</i>	(Optional) Interface
<i>src_addr</i>	(Optional) IPv4 Source address
<i>dst_addr</i>	(Optional) IPv4 Destination address
<i>session_state</i>	(Optional) Session state
<i>ref_count</i>	(Optional) Ref count
<i>displayed_interface</i>	(Optional) Displayed interface
TABLE_groups	(Optional)
<i>group_id</i>	(Optional) Group id
<i>vrrp_state</i>	(Optional) VRRP STATE
<i>bfd_status</i>	(Optional) BFD STATE
<i>operation</i>	(Optional) Operation
<i>time</i>	(Optional) Time

## Command Mode

- /exec

show vrrpv3

## show vrrpv3

```
show vrrpv3 [ brief | detail | statistics ] [ <intf> [ <group_num> ] ] [ <opt_v4_or_v6> ] [ all ] [ __readonly__ [ <global_drops> ] [ [ { TABLE_istats [ <i_intf> ] [ <i_drops> ] [ <ttl> ] [ <checksum> ] [ <version> ] [ <type> ] [ <length> ] [ <badid> ] [ <other> ] } ] [ { TABLE_grp [ <intf> ] [ <id> ] [ <af> ] [ <desc> ] [ <state> ] [ <duration> ] [ <vip> ] ] [ { TABLE_sec [ <addr> ] [ <prefix> ] } ] [ <vmac> ] [ <adv> ] [ <owner> ] [ <preempt> ] [ <delay> ] [ <delay_rem> ] [ <priority> ] [ <cfg_priority> ] [ <m_addr> ] [ <m_priority> ] [ <m_adv> ] [ <m_expire> ] [ <down> ] [ <down_expire> ] [ <t_id> ] [ <t_dec_prio> ] [ <t_state> ] [ <adv_sent> ] [ <adv_err> ] [ <adv_recv> ] [ <v2adv_sent> ] [ <v2adv_err> ] [ <v2adv_recv> ] [ <drops> ] [ <incompat> ] [ <conflict> ] [ <bad_count> ] [ <bad_addr> ] [ <bad_config> ] [ <bad_advert> ] [ <bad_state> ] [ <bad_other> ] [ <init_master> ] [ <init_master_time> ] [ <init_backup> ] [ <init_backup_time> ] [ <back_master> ] [ <back_master_time> ] [ <master_back> ] [ <master_back_time> ] [ <mast_init> ] [ <mast_init_time> ] [ <back_init> ] [ <back_init_time> ] } ] ] + [ { TABLE_vbrief [ <intf_b> ] [ <id_b> ] [ <af_b> ] [ <priority_b> ] [ <down_b> ] [ <owner_b> ] [ <preempt_b> ] [ <state_b> ] [ <m_addr_b> ] [ <vip_b> ] } ] ]
```

### Syntax Description

show	Show running system information
vrrpv3	VRRPv3 Show commands
all	(Optional) All VRRPV3 information
brief	(Optional) Brief output
detail	(Optional) Detail output
statistics	(Optional) Statistics output
<i>opt_v4_or_v6</i>	(Optional) Enter ipv4 or ipv6
<i>intf</i>	(Optional) Interface
<i>group_num</i>	(Optional) Group Number
<i>__readonly__</i>	(Optional)
TABLE_istats	(Optional) Interface-level VRRPv3 statistics
TABLE_grp	(Optional) VRRP Groups
TABLE_sec	(Optional) Secondary Addresses
TABLE_vbrief	(Optional) VRRP Brief
<i>global_drops</i>	(Optional) Total dropped packets
<i>i_intf</i>	(Optional) Interface
<i>i_drops</i>	(Optional) Total dropped packets
<i>ttl</i>	(Optional) Invalid TTL/Hop limit
<i>checksum</i>	(Optional) Invalid checksum

<i>version</i>	(Optional) Invalid version
<i>type</i>	(Optional) Invalid message type
<i>length</i>	(Optional) Invalid length
<i>baid</i>	(Optional) Invalid group ID
<i>other</i>	(Optional) Other
<i>intf</i>	(Optional) Interface
<i>id</i>	(Optional) Group ID
<i>af</i>	(Optional) Address family
<i>desc</i>	(Optional) Description
<i>state</i>	(Optional) Group state
<i>duration</i>	(Optional) Time in current state
<i>vip</i>	(Optional) Primary virtual IP address
<i>addr</i>	(Optional) Secondary virtual IP address
<i>prefix</i>	(Optional) Secondary VIP prefix
<i>vmac</i>	(Optional) Virtual MAC address
<i>adv</i>	(Optional) Advertisement interval
<i>preempt</i>	(Optional) Preemption status
<i>owner</i>	(Optional) Owner mode
<i>delay</i>	(Optional) Preemption delay
<i>delay_rem</i>	(Optional) Preemption delay remaining
<i>priority</i>	(Optional) Priority
<i>cfg_priority</i>	(Optional) Configured priority
<i>m_addr</i>	(Optional) Group master router address
<i>m_priority</i>	(Optional) Group master priority
<i>m_adv</i>	(Optional) Master advertisement interval
<i>m_expire</i>	(Optional) Master expiration
<i>down</i>	(Optional) Master down interval
<i>down_expire</i>	(Optional) Master down expiration
<i>t_id</i>	(Optional) Tracking object ID

show vrrpv3

<i>t_dec_prio</i>	(Optional) Priority to decrement
<i>t_state</i>	(Optional) Tracking object state
<i>adv_sent</i>	(Optional) Advertisements sent
<i>adv_err</i>	(Optional) Advertisement errors
<i>adv_recv</i>	(Optional) Advertisements received
<i>v2adv_sent</i>	(Optional) Advertisements sent (v2)
<i>v2adv_err</i>	(Optional) Advertisement errors (v2)
<i>v2adv_recv</i>	(Optional) Advertisements received (v2)
<i>drops</i>	(Optional) Total dropped packets
<i>incompat</i>	(Optional) v2, Incompatible
<i>conflict</i>	(Optional) Address owner conflicts
<i>bad_count</i>	(Optional) Invalid address count
<i>bad_addr</i>	(Optional) Invalid IP address
<i>bad_config</i>	(Optional) Invalid IP address config
<i>bad_advert</i>	(Optional) Invalid advertisement interval
<i>bad_state</i>	(Optional) Invalid group state
<i>bad_other</i>	(Optional) Other
<i>init_master</i>	(Optional) Init to Master
<i>init_master_time</i>	(Optional) Last Occurrence
<i>init_backup</i>	(Optional) Init to Backup
<i>init_backup_time</i>	(Optional) Last Occurrence
<i>back_master</i>	(Optional) Backup to Master
<i>back_master_time</i>	(Optional) Last Occurrence
<i>master_back</i>	(Optional) Master to Backup
<i>master_back_time</i>	(Optional) Last Occurrence
<i>mast_init</i>	(Optional) Master to Init
<i>mast_init_time</i>	(Optional) Last Occurrence
<i>back_init</i>	(Optional) Backup to Init
<i>back_init_time</i>	(Optional) Last Occurrence

<i>intf_b</i>	(Optional) Interface
<i>id_b</i>	(Optional) Group ID
<i>af_b</i>	(Optional) Address family
<i>priority_b</i>	(Optional) Priority
<i>down_b</i>	(Optional) Master down interval
<i>owner_b</i>	(Optional) Owner mode
<i>preempt_b</i>	(Optional) Preemption status
<i>state_b</i>	(Optional) Group state
<i>m_addr_b</i>	(Optional) Group master router address
<i>vip_b</i>	(Optional) Primary virtual IP address

**Command Mode**

- /exec

**show vrrs client**

## show vrrs client

```
show vrrs client [ <cname> ] [ __readonly__ { TABLE_client <name> <id> <all> <priority> { TABLE_tags <tname> } } ]
```

### Syntax Description

vrrs	VRRS Show commands
show	Show running system information
client	Information about VRRS clients
<i>cname</i>	(Optional) VRRS client name
<u>__readonly__</u>	(Optional)
TABLE_client	(Optional) VRRS clients
TABLE_tags	(Optional) VRRS tags
<i>name</i>	(Optional) VRRS client name
<i>id</i>	(Optional) VRRS client id
<i>priority</i>	(Optional) Priority
<i>all</i>	(Optional) Client follows all tags
<i>tname</i>	(Optional) VRRS tag name

### Command Mode

- /exec

# show vrrs pathway

```
show vrrs pathway [ <intf> ] [ __readonly__ { TABLE_pws <name> <state> <vrrs_push_state> <vmac>
<vmac_state> <vmac_dbg> [ <pvmac> ] [ <pvmac_state> ] [ <pvmac_dbg> ] <af> [ <desc> ] <opt> <eval>
[ { TABLE_vips <addr> [ <flags> ] } ] } ]
```

## Syntax Description

vrrs	VRRS Show commands
show	Show running system information
pathway	Information about VRRS pathways
<i>intf</i>	(Optional) Interface
<i>__readonly__</i>	(Optional)
TABLE_pws	(Optional) Show VRRS pathways
TABLE_vips	(Optional) Pathway vIP addresses
<i>name</i>	(Optional) Pathway name
<i>state</i>	(Optional) Pathway state
<i>vrrs_push_state</i>	(Optional) VRRS push state
<i>vmac</i>	(Optional) Virtual MAC address
<i>vmac_state</i>	(Optional) Virtual MAC state
<i>vmac_dbg</i>	(Optional) Virtual MAC debug flags
<i>pvmac</i>	(Optional) Previous Virtual MAC address
<i>pvmac_state</i>	(Optional) Previous MAC state
<i>pvmac_dbg</i>	(Optional) Previous MAC debug flags
<i>af</i>	(Optional) Pathway address-family
<i>desc</i>	(Optional) Pathway description
<i>opt</i>	(Optional) Option flags
<i>eval</i>	(Optional) Eval flags
<i>addr</i>	(Optional) Virtual IP address
<i>flags</i>	(Optional) Virtual IP address flags

## Command Mode

- /exec

show vrrs server

## show vrrs server

```
show vrrs server [ __readonly__ { TABLE_srv <name> <af> <intf> <state> <vmac> <vip> [ { TABLE_tag <tag> } ] } ]
```

### Syntax Description

vrrs	VRRS Show commands
show	Show running system information
server	Information about VRRS servers
__readonly__	(Optional)
TABLE_srv	(Optional) VRRS Servers
TABLE_tag	(Optional) VRRS tags associated with each server
<i>name</i>	(Optional) VRRS server name
<i>af</i>	(Optional) Address-family
<i>intf</i>	(Optional) Interface
<i>state</i>	(Optional) VRRS server state
<i>vmac</i>	(Optional) Virtual MAC address
<i>vip</i>	(Optional) Virtual IP address
<i>tag</i>	(Optional) VRRS tag

### Command Mode

- /exec

# show vrrs tag

```
show vrrs tag [ <tagname> ] [ __readonly__ { TABLE_tag <name> <server> [ { TABLE_client <id> <client> <all> } ] } ]
```

## Syntax Description

vrrs	VRRS Show commands
show	Show running system information
tag	Information about VRRS tags
<i>tagname</i>	(Optional) VRRS tag
<u>__readonly__</u>	(Optional)
TABLE_tag	(Optional) Known VRRS tags
TABLE_client	(Optional) VRRS clients listening
<i>name</i>	(Optional) VRRS tag name
<i>server</i>	(Optional) VRRS server name
<i>id</i>	(Optional) VRRS client id
<i>client</i>	(Optional) VRRS client name
<i>all</i>	(Optional) Client follows all tags

## Command Mode

- /exec

**show vsan**

# show vsan

```
show vsan [ <id_in> ] [ __readonly__ { TABLE_vsan <id> { [ <name> <state> <interop_mode>
<load_balancing> <operational_state> ] | <inactive_vsan_name> | <evfp_control_vsan_name> } } ]
```

## Syntax Description

show	Show running system information
vsan	Vsan commands
<i>id_in</i>	(Optional) VSAN ID range
<u>__readonly__</u>	(Optional) Read Only
TABLE_vsan	(Optional) Table of VSAN's
<i>id</i>	(Optional) VSAN ID
<i>name</i>	(Optional) VSAN name
<i>state</i>	(Optional) VSAN state
<i>interop_mode</i>	(Optional) Interoperability mode
<i>load_balancing</i>	(Optional) Load balancing
<i>operational_state</i>	(Optional) Operational state
<i>inactive_vsan_name</i>	(Optional) Isolated VSAN
<i>evfp_control_vsan_name</i>	(Optional) EVFP isolated VSAN

## Command Mode

- /exec

# show vsan membership

```
show vsan [ <id_in> ] membership [ __readonly__ { TABLE_vsan <id> [ <inactive_vsan_name> ] [ <evfp_control_vsan_name> ] [ TABLE_interface <name> ] } ]
```

## Syntax Description

show	Show running system information
vsan	Vsan commands
<i>id_in</i>	(Optional) VSAN ID range
membership	VSAN membership information
__readonly__	(Optional) Read Only
TABLE_vsan	(Optional) VSAN table
<i>id</i>	(Optional) VSAN ID
<i>inactive_vsan_name</i>	(Optional) Isolated VSAN
<i>evfp_control_vsan_name</i>	(Optional) EVFP isolated VSAN
TABLE_interface	(Optional) List of interface members
<i>name</i>	(Optional) Interface name

## Command Mode

- /exec

show vsan membership interface

## show vsan membership interface

show vsan membership interface <if\_in> [ \_\_readonly\_\_ { TABLE\_interface <name> <vsan\_id\_memb> [ <inactive\_vsan\_name> | <evfp\_control\_vsan\_name> ] <allowed\_vsan\_list> } ]

### Syntax Description

show	Show running system information
vsan	Vsan commands
membership	VSAN membership information
interface	Show interface status and information
<i>if_in</i>	Interface range
<u>__readonly__</u>	(Optional) Read Only
TABLE_interface	(Optional) Interface VSAN table
<i>name</i>	(Optional) Interface Name
<i>vsan_id_memb</i>	(Optional) VSAN ID to which interface belongs
<i>inactive_vsan_name</i>	(Optional) Isolated VSAN
<i>evfp_control_vsan_name</i>	(Optional) EVFP isolated VSAN
<i>allowed_vsan_list</i>	(Optional) Allowed VSAN list

### Command Mode

- /exec

# show vsan usage

```
show vsan usage [ __readonly__ { <num_vsans_configured><configured_range_of_vsans><vsans_available_to_configure> } ]
```

## Syntax Description

show	Show running system information
vsan	Vsan commands
usage	show VSAN usage in the system
__readonly__	(Optional) Read Only
<i>num_vsans_configured</i>	(Optional) Total VSAN's configured
<i>configured_range_of_vsans</i>	(Optional) Range of VSAN's configured
<i>vsans_available_to_configure</i>	(Optional) VSAN range available to configure

## Command Mode

- /exec

show vtp counters

## show vtp counters

```
show vtp counters [ __readonly__ <start> <summary_rx> <subset_rx> <request_rx> <summary_tx>
<subset_tx> <request_tx> <num_config_rev_error> <num_config_digest_error> <num_v1_summary_error>
[ { TABLE_pruning_counters <if_index> <join_tx> <join_rx> <summary_adv_v1_rx> } ] ]
```

### Syntax Description

show	Show running system information
vtp	VTP information
counters	VTP statistics
<u>__readonly__</u>	(Optional) Read Only
<i>start</i>	(Optional) Start
<i>summary_rx</i>	(Optional) Summary advertisements received
<i>subset_rx</i>	(Optional) Subset advertisements received
<i>request_rx</i>	(Optional) Request advertisements received
<i>summary_tx</i>	(Optional) Summary advertisements transmitted
<i>subset_tx</i>	(Optional) Subset advertisements transmitted
<i>request_tx</i>	(Optional) Request advertisements transmitted
<i>num_config_rev_error</i>	(Optional) Number of config revision errors
<i>num_config_digest_error</i>	(Optional) Number of config digest errors
<i>num_v1_summary_error</i>	(Optional) Number of V1 summary errors
TABLE_pruning_counters	(Optional) Pruning counters in table format
<i>if_index</i>	(Optional) Trunk
<i>join_tx</i>	(Optional) Join Transmitted
<i>join_rx</i>	(Optional) Join Received
<i>summary_adv_v1_rx</i>	(Optional) Summary advts received from non-pruning-capable device

### Command Mode

- /exec

# show vtp interface

```
show vtp interface [ <interface_range> ] [ __readonly__ [ <start> ] { TABLE_vtp_interface <if_index> <status> } ]
```

## Syntax Description

show	Show running system information
vtp	VTP information
interface	VTP interface status and configuration
<i>interface_range</i>	(Optional) Enter interfaces
<u>__readonly__</u>	(Optional) Read Only
<i>start</i>	(Optional) Start
TABLE_vtp_interface	(Optional) VTP interface configuration in table format
<i>if_index</i>	(Optional) Trunk
<i>status</i>	(Optional) VTP interface status

## Command Mode

- /exec

show vtp password

## show vtp password

show vtp password [ domain <domain-id> ] [ \_\_readonly\_\_ <start> <passwd> <password-type> <secret-key> ]

### Syntax Description

show	Show running system information
vtp	VTP information
password	VTP password
domain	(Optional) VTP administrative domain
<i>domain-id</i>	(Optional) Domian index(Domain-id)
<u>__readonly__</u>	(Optional) Read Only
<i>start</i>	(Optional) Start
<i>passwd</i>	(Optional) VTP Domain Password
<i>password-type</i>	(Optional) Password Type (1=plaintext, 2=hidden)
<i>secret-key</i>	(Optional) Secret Key for the password

### Command Mode

- /exec

# show vtp status

```
show vtp status [ __readonly__ <start> <version> <config_rev> <max_vlan_supported_local>
<num_current_vlans> <oper_mode> <domain_name> <pruning_mode> <oper_pruning_mode> <v2_mode>
<trap_enabled> <md5_digest> <last_modified_ip> <last_modified_time> <running-version> <updater_id>
<updater_reason> ]
```

## Syntax Description

show	Show running system information
vtp	VTP information
status	VTP domain status
<u>__readonly__</u>	(Optional) Read Only
<i>start</i>	(Optional) Start
<i>version</i>	(Optional) VTP version
<i>config_rev</i>	(Optional) Configuration Revision
<i>max_vlan_supported_local</i>	(Optional) Maximum VLANs supported locally
<i>num_current_vlans</i>	(Optional) Number of existing VLANs
<i>oper_mode</i>	(Optional) VTP Mode
<i>domain_name</i>	(Optional) VTP Domain Name
<i>pruning_mode</i>	(Optional) Pruning Mode
<i>oper_pruning_mode</i>	(Optional) Operational Pruning Mode
<i>v2_mode</i>	(Optional) VTP v2 Mode
<i>trap_enabled</i>	(Optional) trap enabled
<i>md5_digest</i>	(Optional) MD5 Digest
<i>last_modified_ip</i>	(Optional) Configuration last modified by
<i>last_modified_time</i>	(Optional) Configuration last modified at
<i>running-version</i>	(Optional) VTP Version Running
<i>updater_id</i>	(Optional) Local Updater id
<i>updater_reason</i>	(Optional) Local Updater id reason

## Command Mode

- /exec

show vtp status