



## New and Changed Information

- [New and Changed Information](#), on page 1

### New and Changed Information

This table summarizes the new and changed features for the *Cisco Nexus 9000 Series NX-OS IP Fabric for Media Solution Guide, Release 10.3(x)*.

**Table 1: New and Changed Features**

Feature	Description	Changed in Release	Where Documented
Flexible NBM modes with Multi-tenancy VRF	The pim-active and pim-passive modes can coexist on the same switch.	10.3(2)F	<a href="#">Guidelines and Limitations</a>
NBM support on sub-interfaces	NBM subinterface type is supported in NBM pim-active and pim-passive modes on Layer 3 sub-interfaces.	10.3(2)F	<a href="#">Guidelines and Limitations</a> <a href="#">Configuring NBM Subinterface Type</a>
Multicast NAT support on sub-interfaces for IPFM flows	Multicast NAT is supported on all host and fabric ports for NBM pim-active and pim-passive modes on Layer 3 sub-interfaces.	10.3(2)F	<a href="#">Guidelines and Limitations</a> <a href="#">Configuring NBM Subinterface Type</a>
NAT Enhancement	Egress service reflection (egress multicast NAT, and multicast to unicast NAT) supports Post-NAT Source IP to be IP Address of an egress interface.	10.3(2)F	<a href="#">NAT Guidelines and Limitations</a>

<b>Feature</b>	<b>Description</b>	<b>Changed in Release</b>	<b>Where Documented</b>
vPC Support for IPFM Endpoints	vPC is supported with feature NBM.	10.3(1)F	<a href="#">vPC Support</a>
PMN Support	Added support for PMN on Cisco Nexus 9808 platform switches.	10.3(1)F	<a href="#">Prerequisites</a> <a href="#">Guidelines and Limitations</a>