



## New and Changed Information

---

- New and Changed Information, on page 1

## New and Changed Information

**Table 1: New and Changed Features for Cisco NX-OS Release 10.5(x)**

| Feature                                    | Description   | Changed in Release | Where Documented   |
|--|---|--------------------|--|
| Service Chaining with service threshold    | Added support for service chaining with service threshold.  | 10.5(3)F           | <a href="#">Guidelines and Limitations</a><br><a href="#">Configuring ePBR Service</a>   |
| Support for Layer 3 ePBR policies          | Added the set-vrf option to redirect packets through a specified VRF instance for ePBR inter-VRF deployments. | 10.5(2)F           | <a href="#">Guidelines and Limitations for ePBR L3</a><br><a href="#">Configuring ePBR Set-VRF for an ePBR Policy</a>  |
| Multi-Node and Multi-Site Service Chaining | Added support for multi node and multi site ePBR service chaining   | 10.5(2)F           | <a href="#">ePBR Service and Service-chain</a><br><a href="#">ePBR and GPO Multi-Site</a><br><a href="#">Guidelines and Limitations</a><br><a href="#">Configuring ePBR Service-chain</a><br><a href="#">Configuring Failover Group</a><br><a href="#">Configuration Examples for SGACL service-chaining Configuration</a> |
| ePBR IPACL one-arm endpoints               | Configuring a reverse IP address for one-arm service devices is not necessary.                                | 10.5(1)F           | <a href="#">Guidelines and Limitations for ePBR L3</a><br><a href="#">Configuring ePBR Service, Policy, and Associating to an Interface</a>  |

**New and Changed Information**