



# EEM Library Debug Command Extensions

---

**Last Updated: November 7, 2011**

- [cli\\_debug, page 1](#)
- [smtp\\_debug, page 1](#)

## cli\_debug

Prints a command-line interface (CLI) debug statement to syslog. This Tcl command extension is used to print a CLI debug statement to syslog if the **debug event manager tcl cli\_library** Cisco IOS CLI command is in effect.

### Syntax

```
cli_debug spec_string debug_string
```

### Arguments

---

spec_string	(Mandatory) The spec_string argument is used to indicate the type of debug statement.
debug_string	(Mandatory) The debug_string argument is used to indicate the debugging text.

---

### Result String

None

### Set \_cerrno

No

## smtp\_debug



---

**Americas Headquarters:**  
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Prints a Simple Mail Transfer Protocol (SMTP) debug statement to syslog. This Tcl command extension prints a SMTP debug statement to syslog if the **debug event manager tcl smtp\_library** Cisco IOS command-line interface (CLI) command is in effect.

### Syntax

```
smtp_debug spec_string debug_string
```

### Arguments

spec_string	(Mandatory) The spec_string argument is used to indicate the type of debug statement.
debug_string	(Mandatory) The debug_string argument is used to indicate the debugging text.

### Result String

None

### Set\_cerrno

No

© 2011 Cisco Systems, Inc. All rights reserved.