



EEM Library Debug Command Extensions

Last Updated: October 16, 2012

- [cli_debug](#), page 1
- [smtp_debug](#), page 1

cli_debug

Prints a command-line interface (CLI) debug statement to syslog. This Tcl command extension is used to print a CLI debug statement to syslog if the **debug event manager tcl cli_library** Cisco IOS CLI command is in effect.

Syntax

```
cli_debug spec_string debug_string
```

Arguments

| | |
|--------------|---|
| spec_string | (Mandatory) The spec_string argument is used to indicate the type of debug statement. |
| debug_string | (Mandatory) The debug_string argument is used to indicate the debugging text. |

Result String

None

Set_cerrno

No

smtp_debug



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Prints a Simple Mail Transfer Protocol (SMTP) debug statement to syslog. This Tcl command extension prints a SMTP debug statement to syslog if the **debug event manager tcl smtp_library Cisco IOS** command-line interface (CLI) command is in effect.

Syntax

```
smtp_debug spec_string debug_string
```

Arguments

| | |
|--------------|---|
| spec_string | (Mandatory) The spec_string argument is used to indicate the type of debug statement. |
| debug_string | (Mandatory) The debug_string argument is used to indicate the debugging text. |

Result String

None

Set _errno

No

© 2012 Cisco Systems, Inc. All rights reserved.