



## EIGRP Support for Route Map Filtering

---

**Last Updated: April 21, 2011**

The EIGRP Support for Route Map Filtering feature enables Enhanced Interior Gateway Routing Protocol (EIGRP) to interoperate with other protocols to leverage additional routing functionality by filtering inbound and outbound traffic based on complex route map options. Several extended filtering options are introduced to provide EIGRP-specific match choices.

- [Finding Feature Information, page 1](#)
- [Information About EIGRP Support for Route Map Filtering, page 1](#)
- [How to Configure EIGRP Support for Route Map Filtering, page 2](#)
- [Configuration Examples for EIGRP Support for Route Map Filtering, page 8](#)
- [Additional References, page 9](#)
- [Feature Information for EIGRP Support for Route Map Filtering, page 10](#)
- [, page 11](#)

### Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the Feature Information Table at the end of this document.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.

### Information About EIGRP Support for Route Map Filtering

- [EIGRP Route Map Support, page 2](#)

## EIGRP Route Map Support

EIGRP support for route map filtering enables EIGRP to interoperate with other protocols by filtering inbound and outbound traffic based on route map options. Additional EIGRP-specific match choices are available to allow flexibility in fine-tuning EIGRP network operations.

EIGRP supports the route map filtering capability that exists for other routing protocols to filter routes being redistributed into their protocol. For more details about understanding and configuring route maps, see the Enabling Policy Routing section of the Configuring IP Routing Protocol-Independent Features module of the *Cisco IOS XE IP Routing: Protocol-Independent Configuration Guide*, Release 2.

Match options allow EIGRP to filter internal and external routes based on source protocols, to match a metric against a range, and to match on an external protocol metric.

EIGRP can be configured to filter traffic using a route map and the **redistribute** or **distribute-list** command. Using a route map with the **redistribute** command allows routes that are redistributed from the routing table to be filtered with a route map before being admitted into an EIGRP topology table. Routes that are dynamically received from, or advertised to, EIGRP peers can be filtered by adding a route map option to the **distribute-list** command.

A route map may be configured with both the **redistribute** and the **distribute-list** commands in the same routing process. When a route map is used with a **distribute-list** command that is configured for inbound or outbound filtering, route packets that are learned from or advertised to EIGRP peers can be processed with the route map to provide better control of route selection during the route exchange process. Redistribution serves as a mechanism to import routes into the EIGRP topology table from a routing table. A route map configured with the **redistribute** command adds flexibility to the redistribution capability and results in a more specific redistributed route selection.

The use of route maps to filter traffic is the same for both autonomous-system configurations and named configurations. See the Configuring EIGRP module for more information about autonomous system and named configurations.

Demands for EIGRP to interoperate with other protocols and flexibility in fine-tuning network operation necessitate the capability to filter traffic using a route map.

## How to Configure EIGRP Support for Route Map Filtering

- [Setting EIGRP Tags Using a Route Map for Autonomous System Configurations](#), page 2
- [Setting EIGRP Tags Using a Route Map for Named Configurations](#), page 4

## Setting EIGRP Tags Using a Route Map for Autonomous System Configurations

Perform this task to set EIGRP tags for autonomous system configurations using a route map. The EIGRP metrics used for filtering are configured within a route map. The first match clause defines EIGRP routes that contain an external protocol metric between 400 and 600 inclusive; the second match clause defines EIGRP external routes that match a source protocol of BGP and the autonomous system 45000. When the two match clauses are true, a tag value of the destination routing protocol is set to 5. This route map can be used with the **distribute-list** command, see the [Example Setting EIGRP Tags Using a Route Map--Autonomous System Configuration Examples](#), page 8 for an example configuration.

**SUMMARY STEPS**

1. **enable**
2. **configure terminal**
3. **route-map** *map-tag* [**permit** | **deny**] [*sequence-number*]
4. **match metric** {*metric-value*| **external** *metric-value*} [**+-** *deviation-number*]
5. **match source-protocol** *source-protocol* [*autonomous-system-number*]
6. **set tag** *tag-value*
7. **exit**
8. **router eigrp** *as-number*
9. **network** *ip-address*
10. **distribute-list route-map** *map-tag* **in**

**DETAILED STEPS**

	Command or Action	Purpose
<b>Step 1</b>	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
<b>Step 2</b>	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
<b>Step 3</b>	<b>route-map</b> <i>map-tag</i> [ <b>permit</b>   <b>deny</b> ] [ <i>sequence-number</i> ]  <b>Example:</b> Router(config)# route-map metric-range	Enters route-map configuration mode.
<b>Step 4</b>	<b>match metric</b> { <i>metric-value</i>   <b>external</b> <i>metric-value</i> } [ <b>+-</b> <i>deviation-number</i> ]  <b>Example:</b> Router(config-route-map)# match metric external 500 +- 100	Specifies a match clause that filters inbound updates that match an internal or external protocol metric. <ul style="list-style-type: none"> <li>• <i>metric-value</i> --Internal protocol metric, which can be an EIGRP five-part metric. The range is from 1 to 4294967295.</li> <li>• <b>external</b> --External protocol metric. The range is from 1 to 4294967295.</li> <li>• <b>+-</b> <i>deviation-number</i> --(Optional) Represents a standard deviation. The deviation can be any number. There is no default.</li> </ul> <p><b>Note</b>When you specify a metric deviation with the + and - keywords, the router will match any metric that falls inclusively in that range.</p> <p><b>Note</b>The external protocol metric is not the same as the EIGRP assigned route metric, which is a figure computed from EIGRP vectorized metric components (delay, bandwidth, reliability, load, and MTU).</p>

	Command or Action	Purpose
Step 5	<p><b>match source-protocol</b> <i>source-protocol</i> [<i>autonomous-system-number</i>]</p> <p><b>Example:</b></p> <pre>Router(config-route-map)# match source-protocol bgp 45000</pre>	<p>Specifies a match clause that matches external routes from sources that match the source protocol.</p> <ul style="list-style-type: none"> <li><i>source-protocol</i> --Protocol to match. The valid keywords are <b>bgp</b>, <b>connected</b>, <b>eigrp</b>, <b>isis</b>, <b>ospf</b>, <b>rip</b>, and <b>static</b>. There is no default.</li> <li><i>autonomous-system-number</i> --(Optional) Autonomous system number. The <i>autonomous-system-number</i> argument is not applicable to the <b>connected</b>, <b>static</b>, and <b>rip</b> keywords. The range is from 1 to 65535. There is no default.</li> </ul>
Step 6	<p><b>set tag</b> <i>tag-value</i></p> <p><b>Example:</b></p> <pre>Router(config-route-map)# set tag 5</pre>	<p>Sets a tag value on the route in the destination routing protocol when all the match criteria of a route map are met.</p>
Step 7	<p><b>exit</b></p> <p><b>Example:</b></p> <pre>Router(config-route-map)# exit</pre>	<p>Exits route-map configuration mode and returns to global configuration mode.</p>
Step 8	<p><b>router eigrp</b> <i>as-number</i></p> <p><b>Example:</b></p> <pre>Router(config)# router eigrp 1</pre>	<p>Configures the EIGRP routing process and enters router configuration mode.</p>
Step 9	<p><b>network</b> <i>ip-address</i></p> <p><b>Example:</b></p> <pre>Router(config-router)# network 172.16.0.0</pre>	<p>Specifies a network for the EIGRP routing process.</p>
Step 10	<p><b>distribute-list route-map</b> <i>map-tag in</i></p> <p><b>Example:</b></p> <pre>Router(config-router)# distribute-list route-map metric-range in</pre>	<p>Filters networks received in updates.</p>

## Setting EIGRP Tags Using a Route Map for Named Configurations

Perform this task to set EIGRP tags for named configurations using a route map. The EIGRP metrics used for filtering are configured within a route map. The first match clause defines EIGRP routes that contain an external protocol metric between 400 and 600 inclusive; the second match clause defines EIGRP external routes that match a source protocol of BGP and the autonomous system 45000. When the two match clauses are true, a tag value of the destination routing protocol is set to 5. This route map can be used with the **distribute-list** command, see the [Example Setting EIGRP Tags Using a Route Map--Named Configuration Examples](#), page 9 for an example configuration.

**SUMMARY STEPS**

1. **enable**
2. **configure terminal**
3. **route-map** *map-tag* [**permit** | **deny**] [*sequence-number*]
4. **set metric** *bandwidth delay reliability loading mtu*
5. **match ip route-source** {*access-list-number* | *access-list-name*} [...*access-list-number* | ...*access-list-name*]
6. **match metric** {*metric-value* | **external** *metric-value*} [+ *deviation-number*]
7. **match source-protocol** *source-protocol* [*autonomous-system-number*]
8. **set tag** *tag-value*
9. **exit**
10. **router eigrp** *virtual-instance-name*
11. Do one of the following:
  - **address-family ipv4** [**multicast**] [**unicast**] [**vrf** *vrf-name*] **autonomous-system** *autonomous-system-number*
  - 
  - 
  - **address-family ipv6** [**unicast**] [**vrf** *vrf-name*] **autonomous-system** *autonomous-system-number*
12. **network** *ip-address* [*wildcard-mask*]
13. **af-interface** {**default** | *interface-type interface-number*}
14. **next-hop-self**
15. **exit-af-interface**
16. **topology** {**base** | *topology-name* **tid** *number*}
17. **distribute-list route-map** *map-tag* **in**

**DETAILED STEPS**

	<b>Command or Action</b>	<b>Purpose</b>
<b>Step 1</b>	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
<b>Step 2</b>	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
<b>Step 3</b>	<b>route-map</b> <i>map-tag</i> [ <b>permit</b>   <b>deny</b> ] [ <i>sequence-number</i> ]	Enters route-map configuration mode.

	Command or Action	Purpose
	<p><b>Example:</b></p> <pre>Router(config)# route-map metric-range</pre>	
<b>Step 4</b>	<p><b>set metric</b> <i>bandwidth delay reliability loading mtu</i></p> <p><b>Example:</b></p> <pre>Router(config-route-map)# set metric 10000 10 255 1 1500</pre>	(Optional) Sets the metric value for EIGRP in a route map.
<b>Step 5</b>	<p><b>match ip route-source</b> {<i>access-list-number</i> <i>access-list-name</i>} [<i>...access-list-number</i>   <i>...access-list-name</i>]</p> <p><b>Example:</b></p> <pre>Router(config-route-map)# match ip route- source 5 80</pre>	Redistributes routes that have been advertised by routers and access servers at the address specified by the access lists.
<b>Step 6</b>	<p><b>match metric</b> {<i>metric-value</i> <b>external</b> <i>metric-value</i>} [<i>+/- deviation-number</i>]</p> <p><b>Example:</b></p> <pre>Router(config-route-map)# match metric external 500 +/- 100</pre>	<p>Specifies a match clause that includes EIGRP routes that match an internal or external protocol metric.</p> <ul style="list-style-type: none"> <li><i>metric-value</i> --Internal protocol metric, which can be an EIGRP five-part metric. The range is from 1 to 4294967295.</li> <li><b>external</b> --External protocol metric. The range is from 1 to 4294967295.</li> <li><i>+/- deviation-number</i> --(Optional) Represents a standard deviation. The deviation can be any number. There is no default.</li> </ul> <p><b>Note</b>When you specify a metric deviation with the + and - keywords, the router will match any metric that falls inclusively in that range.</p> <p><b>Note</b>The external protocol metric is not the same as the EIGRP assigned route metric, which is a figure computed from EIGRP vectorized metric components (delay, bandwidth, reliability, load, and MTU).</p>
<b>Step 7</b>	<p><b>match source-protocol</b> <i>source-protocol</i> [<i>autonomous-system-number</i>]</p> <p><b>Example:</b></p> <pre>Router(config-route-map)# match source- protocol bgp 45000</pre>	<p>Specifies a match clause that includes EIGRP external routes that match a source protocol.</p> <ul style="list-style-type: none"> <li><i>source-protocol</i> --Protocol to match. The valid keywords are <b>bgp</b>, <b>connected</b>, <b>eigrp</b>, <b>isis</b>, <b>ospf</b>, <b>rip</b>, and <b>static</b>. There is no default.</li> <li><i>autonomous-system-number</i> --(Optional) Autonomous system number. The <i>autonomous-system-number</i> argument is not applicable to the <b>connected</b>, <b>static</b>, and <b>rip</b> keywords. The range is from 1 to 65535. There is no default.</li> </ul>
<b>Step 8</b>	<b>set tag</b> <i>tag-value</i>	Sets a tag value on the route in the destination routing protocol when all the match criteria of a route map are met.

	Command or Action	Purpose
	<p><b>Example:</b></p> <pre>Router(config-route-map)# set tag 5</pre>	
<b>Step 9</b>	<p><b>exit</b></p> <p><b>Example:</b></p> <pre>Router(config-route-map)# exit</pre>	Exits route-map configuration mode and returns to global configuration mode.
<b>Step 10</b>	<p><b>router eigrp</b> <i>virtual-instance-name</i></p> <p><b>Example:</b></p> <pre>Router(config)# router eigrp virtual-name1</pre>	Configures the EIGRP routing process and enters router configuration mode.
<b>Step 11</b>	<p>Do one of the following:</p> <ul style="list-style-type: none"> <li>• <b>address-family ipv4</b> [<b>multicast</b>] [<b>unicast</b>] [<b>vrf vrf-name</b>] <b>autonomous-system</b> <i>autonomous-system-number</i></li> <li>•</li> <li>•</li> <li>• <b>address-family ipv6</b> [<b>unicast</b>] [<b>vrf vrf-name</b>] <b>autonomous-system</b> <i>autonomous-system-number</i></li> </ul> <p><b>Example:</b></p> <pre>Router(config-router)# address-family ipv4 autonomous-system 45000</pre>	Enters address family configuration mode to configure an EIGRP IPv4 or IPv6 routing instance.
<b>Step 12</b>	<p><b>network</b> <i>ip-address</i> [<i>wildcard-mask</i>]</p> <p><b>Example:</b></p> <pre>Router(config-router-af)# network 172.16.0.0</pre>	Specifies a network for the EIGRP routing process.
<b>Step 13</b>	<p><b>af-interface</b> {<b>default</b>   <i>interface-type interface-number</i>}</p> <p><b>Example:</b></p> <pre>Router(config-router-af)# af-interface default</pre>	Enters address family interface configuration mode to configure interface-specific EIGRP commands.
<b>Step 14</b>	<p><b>next-hop-self</b></p> <p><b>Example:</b></p> <pre>Router(config-router-af-interface)# next-hop-self</pre>	Enables EIGRP to advertise routes with the local outbound interface address as the next hop.
<b>Step 15</b>	<p><b>exit-af-interface</b></p>	Exits address-family interface configuration mode.

	Command or Action	Purpose
	<b>Example:</b> Router(config-router-af-interface)# exit-af-interface	
<b>Step 16</b>	<b>topology</b> {base   <i>topology-name</i> tid number}  <b>Example:</b> Router(config-router-af)# topology base	Configures an EIGRP process to route IP traffic under the specified topology instance and enters address family topology configuration mode.
<b>Step 17</b>	<b>distribute-list route-map</b> map-tag in  <b>Example:</b> Router(config-router-af-topology)# distribute-list route-map metric-range in	Filters networks received in updates.

## Configuration Examples for EIGRP Support for Route Map Filtering

- [Example Setting EIGRP Tags Using a Route Map--Autonomous System Configuration Examples, page 8](#)
- [Example Setting EIGRP Tags Using a Route Map--Named Configuration Examples, page 9](#)

## Example Setting EIGRP Tags Using a Route Map--Autonomous System Configuration Examples

The following example shows how to configure a route map to match an EIGRP external protocol metric route with an allowable deviation of 100, a source protocol of BGP, and an autonomous system 45000. When the two match clauses are true, the tag value of the destination routing protocol is set to 5. The route map is used to distribute incoming packets for an EIGRP process.

```
Router(config)# route-map metric-range
Router(config-route-map)# match metric external 500 +- 100
Router(config-route-map)# match source-protocol bgp 45000
Router(config-route-map)# set tag 5
Router(config-route-map)# exit
Router(config)# router eigrp 1
Router(config-router)# network 172.16.0.0
Router(config-router)# distribute-list route-map metric_range in
```

The following example shows how to configure a route map to match EIGRP routes with a metric of 110, 200, or an inclusive range of 700 to 800. When the match clause is true, the tag value of the destination routing protocol is set to 10. The route map is used to redistribute EIGRP packets.

```
Router(config)# route-map metric-eigrp
Router(config-route-map)# match metric 110 200 750 +- 50
Router(config-route-map)# set tag 10
```



```
Router(config-route-map)# exit
Router(config)# router eigrp 1
Router(config-router)# network 172.21.1.0/24
Router(config-router)# redistribute eigrp route-map metric-eigrp
```

## Example Setting EIGRP Tags Using a Route Map--Named Configuration Examples

The following example shows how to configure a route map to match an EIGRP external protocol metric route with an allowable deviation of 100, a source protocol of BGP, and an autonomous system 45000. When the two match clauses are true, the tag value of the destination routing protocol is set to 5. The route map is used to distribute incoming packets for an EIGRP process.

```
Router(config)# route-map metric_range
Router(config-route-map)# match metric external 500 +- 100
Router(config-route-map)# match source-protocol bgp 45000
Router(config-route-map)# set tag 5
Router(config-route-map)# exit
Router(config)# router eigrp virtual-name
Router(config-router)# address-family ipv4 autonomous-system 45000
Router(config-router-af)# network 172.21.1.0/24
Router(config-router-af)# topology base
Router(config-router-af-topology)# distribute-list route-map metric_range in
```

The following example shows how to configure a route map to match EIGRP routes with a metric of 110, 200, or an inclusive range of 700 to 800. When the match clause is true, the tag value of the destination routing protocol is set to 10. The route map is used to redistribute EIGRP packets.

```
Router(config)# route-map metric_eigrp
Router(config-route-map)# match metric 110 200 750 +- 50
Router(config-route-map)# set tag 10
Router(config-route-map)# exit
Router(config)# router eigrp virtual-name
Router(config-router)# address-family ipv4 autonomous-system 45000
Router(config-router-af)# network 172.21.1.0/24
Router(config-router-af)# topology base
Router(config-router-af-topology)# distribute-list route-map metric-range in
```

## Additional References

### Related Documents

Related Topic	Document Title
Cisco IOS commands	<a href="#">Cisco IOS Master Commands List, All Releases</a>
EIGRP overview and configuration	Configuring EIGRP
EIGRP commands including syntax, usage guidelines, and examples	<i>Cisco IOS IP Routing: EIGRP Command Reference</i>

**Standards**

Standard	Title
None	--

**MIBs**

MIB	MIBs Link
None	To locate and download MIBs for selected platforms, Cisco software releases, and feature sets, use Cisco MIB Locator found at the following URL:  <a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a>

**RFCs**

RFC	Title
None	--

**Technical Assistance**

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	<a href="http://www.cisco.com/cisco/web/support/index.html">http://www.cisco.com/cisco/web/support/index.html</a>

## Feature Information for EIGRP Support for Route Map Filtering

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.

**Table 1: Feature Information for EIGRP Support for Route Map Filtering**

Feature Name	Releases	Feature Information
EIGRP Support for Route Map Filtering	Cisco IOS XE Release 2.1	<p>The EIGRP Support for Route Map Filtering feature enables EIGRP to interoperate with other protocols by filtering inbound and outbound traffic based on complex route map options. Several extended filtering options are introduced to provide EIGRP-specific match choices.</p> <p>In Cisco IOS XE Release 2.1, this feature was introduced on the Cisco ASR 1000 Series Aggregation Services Routers.</p> <p>The following commands were introduced or modified by this feature: <b>match metric (IP)</b>, <b>match source-protocol</b>, <b>show ip eigrp topology</b>.</p> <p>In Cisco IOS XE Release 2.5, the following command was introduced or modified for this feature: <b>show eigrp address-family topology</b></p>

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.