

IPv6 CEF-Switched Tunnels

Cisco Express Forwarding switching can be used for IPv6 manually configured tunnels.

- Finding Feature Information, on page 1
- Information About IPv6 CEF-Switched Tunnels, on page 1
- Additional References, on page 2
- Feature Information for IPv6 CEF-Switched Tunnels, on page 3

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see Bug Search Tool and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About IPv6 CEF-Switched Tunnels

IPv6 Manually Configured Tunnels

A manually configured tunnel is equivalent to a permanent link between two IPv6 domains over an IPv4 backbone. The primary use is for stable connections that require regular secure communication between two edge devices or between an end system and an edge device, or for connection to remote IPv6 networks.

An IPv6 address is manually configured on a tunnel interface, and manually configured IPv4 addresses are assigned to the tunnel source and the tunnel destination. The host or device at each end of a configured tunnel must support both the IPv4 and IPv6 protocol stacks. Manually configured tunnels can be configured between border devices or between a border device and a host. Cisco Express Forwarding switching can be used for IPv6 manually configured tunnels, or Cisco Express Forwarding switching can be disabled if process switching is needed.

Additional References

Related Documents

Related Topic	Document Title
IPv6 addressing and connectivity	IPv6 Configuration Guide
Tunnels	Interface and Hardware Component Configuration Guide
Cisco IOS commands	Cisco IOS Master Commands List, All Releases
IPv6 commands	Cisco IOS IPv6 Command Reference
Cisco IOS IPv6 features	Cisco IOS IPv6 Feature Mapping

Standards and RFCs

Standard/RFC	Title
RFCs for IPv6	IPv6 RFCs

MIBs

MIB	MIBs Link
	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL:
	http://www.cisco.com/go/mibs

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	

Feature Information for IPv6 CEF-Switched Tunnels

Table 1: Feature Information for IPv6 CEF-Switched Tunnels

Feature Name	Releases	Feature Information
CEFv6 Switching for 6to4 Tunnels	12.2(28)SB	Cisco Express Forwarding switching can be used for IPv6 manually configured tunnels.
	12.2(25)SG	
	12.2(33)SRA	
	12.2(18)SXE	
	12.2(12)T	
	12.4	
	15.0(1)S	
	Cisco IOS XE 3.9(S)	
IPv6 Switching: CEFv6 Switched	12.2(2)T	IPv6 supports this feature.
Automatic IPv4-Compatible Tunnels	12.2(52)SG	
Tumicis	12.2(33)SRA	
	12.2(17a)SX1	
	Cisco IOS XE 3.9(S)	
IPv6 Switching: CEFv6 Switched	12.2(13)T	IPv6 supports this feature.
Configured IPv6 over IPv4 Tunnels	12.2(52)SG	
	12.2(33)SRA	
	12.2(17a)SX1	
	Cisco IOS XE 3.9(S)	
IPv6 Switching: CEFv6 Switched	12.2(15)T	IPv6 supports this feature.
ISATAP Tunnels	12.2(25)SG	
	3.2.0SG	
	15.0(2)SG	
	12.2(33)SRA	
	12.2(17a)SX1	
	Cisco IOS XE 3.9(S)	

Feature Information for IPv6 CEF-Switched Tunnels