

Quality of Service for VPNs

The QoS for VPNs feature provides a solution for making Cisco IOS QoS services operate in conjunction with tunneling and encryption on an interface. Cisco IOS software can classify packets and apply the appropriate QoS service before the data is encrypted and tunneled. The QoS for VPN feature allows users to look inside the packet so that packet classification can be done based on original port numbers and based on source and destination IP addresses. This allows the service provider to treat mission critical or multi-service traffic with higher priority across their network.

- Finding Feature Information, page 1
- Information About Quality of Service for Virtual Private Networks, page 2
- How to Configure QoS for VPNs, page 2
- Configuration Examples for QoS for VPNs, page 4
- Additional References for QoS for VPNs, page 4
- Feature Information for QoS for VPNs, page 5

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see Bug Search Tool and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About Quality of Service for Virtual Private Networks

QoS for VPNs

The QoS for VPNs feature provides a solution for making Cisco IOS QoS services operate in conjunction with tunneling and encryption on an interface. Cisco IOS software can classify packets and apply the appropriate QoS service before the data is encrypted and tunneled. The QoS for VPN feature allows users to look inside the packet so that packet classification can be done based on original port numbers and based on source and destination IP addresses. This allows the service provider to treat mission critical or multi-service traffic with higher priority across their network.

How to Configure QoS for VPNs

Configuring QoS When Using IPsec VPNs

This task uses the **qos pre-classify** command to enable QoS preclassification for the packet. QoS preclassification is not supported for all fragmented packets. If a packet is fragmented, each fragment might received different preclassifications.



This task is required only if you are using IPsec Virtual Private Networks (VPNs). Otherwise, this task is not necessary. For information about IPsec VPNs, see the "Configuring Security for VPNs with IPsec" module.

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- 3. crypto map map-name seq-num
- 4. exit
- 5. interface type number [name-tag]
- 6. qos pre-classify
- 7. end

DETAILED STEPS

	Command or Action	Purpose	
Step 1	enable	Enables privileged EXEC mode.	

QoS: Classification Configuration Guide, Cisco IOS XE Everest 16.6

ſ

	Command or Action	Purpose
		Enter your password if prompted.
	Example:	
	Router> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example:	
	Router# configure terminal	
Step 3	crypto map map-name seq-num	Enters crypto map configuration mode and creates or modifies a crypto map entry.
	Example:	• Enter the crypto map name and sequence number.
	Router(config)# crypto map mymap 10	
Step 4	exit	Returns to global configuration mode.
	Example:	
	Router(config-crypto-map)# exit	
Step 5	interface type number [name-tag]	Configures an interface type and enters interface configuration mode.
	Example:	• Enter the interface type and number.
	Router(config)# interface serial4/0/0	
Step 6	qos pre-classify	Enables QoS preclassification.
	Example:	
	Router(config-if)# qos pre-classify	
Step 7	end	(Optional) Exits interface configuration mode and returns to privileged EXEC mode.
	Example:	
	Router(config-if)# end	
	1	

Configuration Examples for QoS for VPNs

Example Configuring QoS When Using IPsec VPNs

The following is an example of configuring QoS when using IPsec VPNs. In this example, the **crypto map** command specifies the IPsec crypto map (mymap 10) to which the **qos pre-classify** command will be applied.

```
Router> enable
Router# configure terminal
Router(config)# crypto map mymap 10
Router(config-crypto-map)# qos pre-classify
Router(config-crypto-map)# exit
```

Additional References for QoS for VPNs

Related Documents

Related Topic	Document Title	
Cisco commands	Cisco IOS Master Command List, All Releases	
QoS commands: complete command syntax, command modes, command history, defaults, usage guidelines, and examples	Cisco IOS Quality of Service Solutions Command Reference	
Classifying network traffic	"Classifying Network Traffic" module	
MQC	"Applying QoS Features Using the MQC" module	
Marking network traffic	"Marking Network Traffic" module	

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	

I

Feature Information for QoS for VPNs

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Feature Name	Releases	Feature Information
Quality of Service for Virtual Private Networks	12.2(2)T Cisco IOS XE Release 3.9S	The QoS for VPNs feature provides a solution for making Cisco IOS QoS services operate in conjunction with tunneling and encryption on an interface. Cisco IOS software can classify packets and apply the appropriate QoS service before the data is encrypted and tunneled. The QoS for VPN feature allows users to look inside the packet so that packet classification can be done based on original port numbers and based on source and destination IP addresses. This allows the service provider to treat mission critical or multi-service traffic with higher priority across their network.
QoS: Traffic Pre-classification	Cisco IOS XE Release 2.1	This feature was introduced on Cisco ASR 1000 Series Routers.

Table 1: Feature Information for QoS for VPNs



٦