



QoS Match VLAN

The QoS: Match VLAN feature allows you to classify network traffic on the basis of the Layer 2 virtual local-area network (VLAN) identification number.

- [Finding Feature Information, on page 1](#)
- [Information About Match VLAN, on page 1](#)
- [How to Configure Match VLAN, on page 2](#)
- [Configuration Examples for Match VLAN, on page 4](#)
- [Additional References for QoS for Match VLAN, on page 5](#)
- [Feature Information for QoS for Match VLAN, on page 5](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About Match VLAN

QoS Match VLAN

The QoS: Match VLAN feature allows you to classify network traffic on the basis of the Layer 2 virtual local-area network (VLAN) identification number. To classify network traffic based on the VLAN identification number you create a class-map and specify the match criteria using the **match vlan** command. You then attach the class to a policy-map and use the policy map in a service policy that is attached to an interface.

How to Configure Match VLAN

Classifying Network Traffic per VLAN

To classify network traffic on a per VLAN basis, perform the following task.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **class-map** {**match-any** | **match-all**} *class-map-name*
4. **match vlan** *vlan-id-number*
5. **exit**
6. **policy-map** *policy-map-name*
7. **class** *class-map-name*
8. **bandwidth percent** *percent*
9. **exit**
10. **exit**
11. **policy-map** *policy-map-name*
12. **class** *class-map-name*
13. **shape** {**average** | **peak**} *cir*
14. **service-policy** {**input** | **output**} *policy-map-name*
15. **exit**
16. **exit**
17. **interface** *type number* [**name-tag**]
18. **service-policy** {**input** | **output**} *policy-map-name*
19. **end**

DETAILED STEPS

| | Command or Action | Purpose |
|---------------|---|--|
| Step 1 | enable Example: Router> enable | Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted. |
| Step 2 | configure terminal Example: Router# configure terminal | Enters global configuration mode. |
| Step 3 | class-map { match-any match-all } <i>class-map-name</i> Example: Router(config)# class-map match-any Blue_VRF | Creates a class map and enters class map configuration mode. |

| | Command or Action | Purpose |
|----------------|---|---|
| Step 4 | match vlan <i>vlan-id-number</i> Example: Router(config-cmap)# match vlan 101 | Matches traffic on the basis of the range of VLAN identification numbers specified. |
| Step 5 | exit Example: Router(config-cmap)# exit | Returns to global configuration mode. |
| Step 6 | policy-map <i>policy-map-name</i> Example: Router(config)# policy-map Shared_QoS | Creates a policy map that can be attached to an interface and enters policy-map configuration mode. |
| Step 7 | class <i>class-map-name</i> Example: Router(config-pmap)# class Blue_VRF | Specify the name of the class whose policy you want to create and enters policy-map class configuration mode. |
| Step 8 | bandwidth percent <i>percent</i> Example: Router(config-pmap-c)# bandwidth percent 30 | Specifies the bandwidth allocated for a class belonging to a policy map. |
| Step 9 | exit Example: Router(config-pmap-c)# exit | Returns to policy-map configuration mode. |
| Step 10 | exit Example: Router(config-pmap)# exit | Returns to global configuration mode. |
| Step 11 | policy-map <i>policy-map-name</i> Example: Router(config)# policy-map COS-OUT-SHAPED | Creates a policy map that can be attached to an interface and enters policy-map configuration mode. |
| Step 12 | class <i>class-map-name</i> Example: Router(config-pmap)# class FROM_WAN | Specify the name of the class whose policy you want to create and enters policy-map class configuration mode. |

| | Command or Action | Purpose |
|----------------|--|--|
| Step 13 | shape {average peak} <i>cir</i> Example: Router(config-pmap-c)# shape average 9000000000 | Specifies the average rate traffic shaping. • The Committed information rate (CIR), is specified in bits per second (bps). |
| Step 14 | service-policy {input output} <i>policy-map-name</i> Example: Router(config-pmap-c)# service-policy Shared_QoS | Specifies the name of the predefined policy map to be used as a QoS policy. |
| Step 15 | exit Example: Router(config-pmap-c)# exit | Returns to policy-map configuration mode. |
| Step 16 | exit Example: Router(config-pmap)# exit | Returns to global configuration mode. |
| Step 17 | interface <i>type number [name-tag]</i> Example: Router(config)# interface FastEthernet 0/0.1 | Configures an interface type and enters interface configuration mode. • Enter the interface type and number. |
| Step 18 | service-policy {input output} <i>policy-map-name</i> Example: Router(config-if)# service-policy output COS-OUT-SHAPED | Attaches a policy map to an input interface, a virtual circuit (VC), an output interface, or a VC that will be used as the service policy for the interface. |
| Step 19 | end Example: Router(config-if)# end | (Optional) Exits interface configuration mode and returns to privileged EXEC mode. |

Configuration Examples for Match VLAN

Example: Classifying Network Traffic per VLAN

The following example shows how to classify network traffic on a VLAN basis. The VLAN classified traffic is applied to the FastEthernet 0/0.1 subinterface.

```
interface FastEthernet0/0.1
service-policy output COS-OUT-SHAPED
```

```

policy-map COS-OUT-SHAPED
  class ADMIN
  class FROM_WAN
    shape average 900000000
    service-policy Shared_QoS
policy-map Shared_QoS
  ! description -- Bandwidth sharing between VRF --
  class Blue_VRF
    bandwidth percent 3
class-map match-any Blue_VRF
  ! description -- traffic belonging to the VRF Blue --
  match vlan 101

```

Additional References for QoS for Match VLAN

Related Documents

| Related Topic | Document Title |
|---|---|
| Cisco commands | Cisco IOS Master Command List, All Releases |
| QoS commands: complete command syntax, command modes, command history, defaults, usage guidelines, and examples | <i>Cisco IOS Quality of Service Solutions Command Reference</i> |
| Classifying network traffic | “Classifying Network Traffic” module |
| MQC | “Applying QoS Features Using the MQC” module |
| Marking network traffic | “Marking Network Traffic” module |

Technical Assistance

| Description | Link |
|---|---|
| The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password. | http://www.cisco.com/cisco/web/support/index.html |

Feature Information for QoS for Match VLAN

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for QoS for Match VLAN

| Feature Name | Releases | Feature Information |
|-----------------|---|--|
| QoS: Match VLAN | 12.2(31)SB2 Cisco IOS XE Release 2.1 15.0(1)S | The QoS: Match VLAN feature allows you to classify network traffic on the basis of the Layer 2 virtual local-area network (VLAN) identification number. The following commands were introduced or modified by this feature: match vlan (QoS), show policy-map interface This feature was introduced on Cisco ASR 1000 Series Routers. |