



Configuring and Managing a Cisco IOS Certificate Server for PKI Deployment

Last Updated: July 18, 2012

This module describes how to set up and manage a Cisco IOS certificate server for public key infrastructure (PKI) deployment. A certificate server embeds a simple certificate server, with limited certification authority (CA) functionality, into the Cisco IOS software. Thus, the following benefits are provided to the user:

- Easier PKI deployment by defining default behavior. The user interface is simpler because default behaviors are predefined. That is, you can leverage the scaling advantages of PKI without all of the certificate extensions that a CA provides, thereby allowing you to easily enable a basic PKI-secured network.
- Direct integration with Cisco IOS software.



Note

Security threats, as well as the cryptographic technologies to help protect against them, are constantly changing. For more information about the latest Cisco cryptographic recommendations, see the [Next Generation Encryption](#) (NGE) white paper.

- [Finding Feature Information](#), page 1
- [Prerequisites for Configuring a Cisco IOS Certificate Server](#), page 2
- [Restrictions for Configuring a Cisco IOS Certificate Server](#), page 3
- [Information About Cisco IOS Certificate Servers](#), page 3
- [How to Set Up and Deploy a Cisco IOS Certificate Server](#), page 11
- [Configuration Examples for Using a Certificate Server](#), page 42
- [Where to Go Next](#), page 51
- [Additional References](#), page 51
- [Feature Information for the Cisco IOS Certificate Server](#), page 53

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release.



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Prerequisites for Configuring a Cisco IOS Certificate Server

Planning Your PKI Before Configuring the Certificate Server

Before configuring a Cisco IOS certificate server, it is important that you have planned for and chosen appropriate values for the settings you intend to use within your PKI (such as certificate lifetimes and certificate revocation list (CRL) lifetimes). After the settings have been configured in the certificate server and certificates have been granted, settings cannot be changed without having to reconfigure the certificate server and reenrolling the peers. For information on certificate server default settings and recommended settings, see the section “[Certificate Server Default Values and Recommended Values](#), page 28.”

Enabling an HTTP Server

The certificate server supports Simple Certificate Enrollment Protocol (SCEP) over HTTP. The HTTP server must be enabled on the router for the certificate server to use SCEP. (To enable the HTTP server, use the **ip http server** command.) The certificate server automatically enables or disables SCEP services after the HTTP server is enabled or disabled. If the HTTP server is not enabled, only manual PKCS10 enrollment is supported.



Note

To take advantage of automatic CA certificate and key pair rollover functionality for all types of certificate servers, Cisco IOS Release 12.4(4)T or a later release must be used and SCEP must be used as the enrollment method.

Configuring Reliable Time Services

Time services must be running on the router because the certificate server must have reliable time knowledge. If a hardware clock is unavailable, the certificate server depends on manually configured clock settings, such as Network Time Protocol (NTP). If there is not a hardware clock or the clock is invalid, the following message is displayed at bootup:

```
% Time has not been set. Cannot start the Certificate server.
```

After the clock has been set, the certificate server automatically switches to running status.

For information on manually configuring clock settings, see the section “Setting Time and Calendar Services” in the chapter “Performing Basic System Management” of the *Cisco IOS Network Management Configuration Guide*.

“crypto ca” to “crypto pki” CLI Change

As of Cisco IOS Release 12.3(7)T, all commands that begin as “crypto ca” have been changed to begin as “crypto pki.” Although the router continues to accept crypto ca commands, all output is read back as crypto pki.

Restrictions for Configuring a Cisco IOS Certificate Server

The certificate server does not provide a mechanism for modifying the certificate request that is received from the client; that is, the certificate that is issued from the certificate server matches the requested certificate without modifications. If a specific certificate policy, such as name constraints, must be issued, the policy must be reflected in the certificate request.

Information About Cisco IOS Certificate Servers

- [RSA Key Pair and Certificate of the Certificate Server, page 3](#)
- [Certificate Server Database, page 4](#)
- [Trustpoint of the Certificate Server, page 6](#)
- [Certificate Revocation Lists \(CRLs\), page 6](#)
- [Certificate Server Error Conditions, page 7](#)
- [Certificate Enrollment Using a Certificate Server, page 7](#)
- [Types of CA Servers Subordinate and Registration Authorities \(RAs\), page 8](#)
- [Automatic CA Certificate and Key Rollover, page 9](#)
- [Support for Specifying a Cryptographic Hash Function, page 10](#)

RSA Key Pair and Certificate of the Certificate Server

The certificate server automatically generates a 1024-bit Rivest, Shamir, and Adelman (RSA) key pair. You must manually generate an RSA key pair if you prefer a different key pair modulus. For information on completing this task, see the section “[Generating a Certificate Server RSA Key Pair, page 11.](#)”

**Note**

The recommended modulus for a certificate server key pair is 2048 bits.

The certificate server uses a regular Cisco IOS RSA key pair as its CA key. This key pair must have the same name as the certificate server. If you do not generate the key pair before the certificate server is created on the router, a general-purpose key pair is automatically generated during the configuration of the certificate server.

As of Cisco IOS Release 12.3(11)T and later releases, the CA certificate and CA key can be backed up automatically one time after they are generated by the certificate server. As a result, it is not necessary to generate an exportable CA key for backup purposes.

What to Do with Automatically Generated Key Pairs in Cisco IOS Software Prior to Release 12.3(11)T

If the key pair is automatically generated, it is not marked as exportable. Thus, you must manually generate the key pair as exportable if you want to back up the CA key. For information on how to complete this task, see the section “[Generating a Certificate Server RSA Key Pair, page 11.](#)”

- [How the CA Certificate and CA Key Are Automatically Archived, page 3](#)

How the CA Certificate and CA Key Are Automatically Archived

At initial certificate server setup, you can enable the CA certificate and the CA key to be automatically archived so that they may be restored later if either the original copy or the original configuration is lost.

When the certificate server is turned on the first time, the CA certificate and CA key is generated. If automatic archive is also enabled, the CA certificate and the CA key is exported (archived) to the server database. The archive can be in PKCS12 or privacy-enhanced mail (PEM) format.

**Note**

This CA key backup file is extremely important and should be moved immediately to another secured place.

- This archiving action occurs only one time. Only the CA key that is (1) manually generated and marked exportable or (2) automatically generated by the certificate server is archived (this key is marked nonexportable).
- Autoarchiving does not occur if you generate the CA key manually and mark it “nonexportable.”
- In addition to the CA certificate and CA key archive file, you should also regularly back up the serial number file (.ser) and the CRL file (.crl). The serial file and the CRL file are both critical for CA operation if you need to restore your certificate server.
- It is not possible to manually back up a server that uses nonexportable RSA keys or manually generated, nonexportable RSA keys. Although automatically generated RSA keys are marked as nonexportable, they are automatically archived once.

Certificate Server Database

The Cisco IOS certificate server stores files for its own use and may publish files for other processes to use. Critical files generated by the certificate server that are needed for its ongoing operation are stored to only one location per file type for its exclusive use. The certificate server reads from and writes to these files. The critical certificate server files are the serial number file (.ser) and the CRL storage location file (.crl). Files that the certificate server writes to, but does not read from again, may be published and available for use by other processes. An example of a file that may be published is the issued certificates file (.crt).

Performance of your certificate server may be affected by the following factors, which should be considered when you choose storage options and publication options for your certificate server files.

- The storage or publish locations you choose may affect your certificate server performance. Reading from a network location takes more time than reading directly from a router’s local storage device.
- The number of files you choose to store or publish to a specific location may affect your certificate server performance. The local Cisco IOS file system may not always be suitable for a large number of files.
- The file types you choose to store or publish may affect your certificate server performance. Certain files, such as the .crl files, can become very large.

**Note**

It is recommended that you store .ser and .crl files to your local Cisco IOS file system and publish your .crt files to a remote file system.

- [Certificate Server Database File Storage, page 5](#)
- [Certificate Server Database File Publication, page 5](#)

Certificate Server Database File Storage

The certificate server allows the flexibility to store different critical file types to different storage locations depending on the database level set (see the **database level** command for more information). When choosing storage locations, consider the file security needed and server performance. For instance, serial number files and archive files (.p12 or .pem) might have greater security restrictions than the issued certificates file storage location (.crt) or the name file storage location (.cnm).

The table below shows the critical certificate server file types by file extension that may be stored to a specific location.

Table 1 **Certificate Server Storage Critical File Types**

File Extension	File Type
.ser	The main certificate server database file.
.crl	The CRL storage location.
.crt	The issued certificates storage location.
.cnm	The certificate name and expiration file storage location.
.p12	The certificate server certificate archive file location in PKCS12 format.
.pem	The certificate server certificate archive file location in PEM format.

Cisco IOS certificate server files may be stored to three levels of specificity:

- Default location, NVRAM
- Specified primary storage location for all critical files
- Specified storage location for specific critical file(s).

A more specific storage location setting overrides a more general storage location setting. For instance, if you have not specified any certificate server file storage locations, all certificate server files are stored to NVRAM. If you specify a storage location for the name file, only the name file is stored there; all other files continue to be stored to NVRAM. If you then specify a primary location, all files except the name file is now stored to this location, instead of NVRAM.



Note

You may specify either .p12 or .pem; you cannot specify both types of archive files.

Certificate Server Database File Publication

A publish file is a copy of the original file and is available for other processes to use or for your use. If the certificate server fails to publish a file, it does cause the server to shut down. You may specify one publish location for the issued certificates file and name file and multiple publish locations for the CRL file. See the table below for files types available for publication. You may publish files regardless of the database level that is set.

Table 2 **Certificate Server Publish File Types**

File Extension	File Type
.crl	The CRL publish location.
.crt	The issued certificates publish location.
.cnm	The certificate name and expiration file publish location.

Trustpoint of the Certificate Server

If the certificate server also has an automatically generated trustpoint of the same name, then the trustpoint stores the certificate of the certificate server. After the router detects that a trustpoint is being used to store the certificate of the certificate server, the trustpoint is locked so that it cannot be modified.

Before configuring the certificate server you can perform the following:

- Manually create and set up this trustpoint (using the **crypto pki trustpoint** command), which allows you to specify an alternative RSA key pair (using the **rsa keypair** command).
- Specify that the initial autoenrollment key pair is generated on a specific device, such as a configured and available USB token, using the **on** command.



Note

The automatically generated trustpoint and the certificate server certificate are not available for the certificate server device identity. Thus, any command-line interface (CLI) (such as the **ip http secure-trustpoint** command) that is used to specify the CA trustpoint to obtain certificates and authenticate the connecting client's certificate must point to an additional trustpoint configured on the certificate server device.

If the server is a root certificate server, it uses the RSA key pairs and several other attributes to generate a self-signed certificate. The associated CA certificate has the following key usage extensions--Digital Signature, Certificate Sign, and CRL Sign.

After the CA certificate is generated, attributes can be changed only if the certificate server is destroyed.



Note

A certificate server trustpoint must not be automatically enrolled using the **auto-enroll** command. Initial enrollment of the certificate server must be initiated manually and ongoing automatic rollover functionality may be configured with the **auto-rollover** command. For more information on automatic rollover functionality, see the section "[Automatic CA Certificate and Key Rollover, page 9.](#)"

Certificate Revocation Lists (CRLs)

By default, CRLs are issued once every 168 hours (1 calendar week). To specify a value other than the default value for issuing the CRL, execute the **lifetime crl** command. After the CRL is issued, it is written to the specified database location as *ca-label.crl*, where *ca-label* is the name of the certificate server.

CRLs can be distributed through SCEP, which is the default method, or a CRL distribution point (CDP), if configured and available. If you set up a CDP, use the **cdp-url** command to specify the CDP location. If the **cdp-url** command is not specified, the CDP certificate extension is not included in the certificates that are

issued by the certificate server. If the CDP location is not specified, Cisco IOS PKI clients automatically request a CRL from the certificate server with a SCEP GetCRL message. The CA then returns the CRL in a SCEP CertRep message to the client. Because all SCEP messages are enveloped and signed PKCS#7 data, the SCEP retrieval of the CRL from the certificate server is costly and not highly scalable. In very large networks, an HTTP CDP provides better scalability and is recommended if you have many peer devices that check CRLs. You may specify the CDP location by a simple HTTP URL string for example,

```
cdp-url http://my-cdp.company.com/filename.crl
```

The certificate server supports only one CDP; thus, all certificates that are issued include the same CDP.

If you have PKI clients that are not running Cisco IOS software and that do not support a SCEP GetCRL request and wish to use a CDP you may set up an external server to distribute CRLs and configure the CDP to point to that server. Or, you can specify a non-SCEP request for the retrieval of the CRL from the certificate server by specifying the **cdp-url** command with the URL in the following format where *cs-addr* is the location of the certificate server:

```
cdp-url http://cs-addr/cgi-bin/pkiclient.exe?operation=GetCRL
```

**Note**

If your Cisco IOS CA is also configured as your HTTP CDP server, specify your CDP with the **cdp-url**`http://cs-addr/cgi-bin/pkiclient.exe?operation=GetCRL` command syntax.

It is the responsibility of the network administrator to ensure that the CRL is available from the location that is specified through the **cdp-url** command.

In order to force the parser to retain the embedded question mark within the specified location, enter Ctrl-v prior to the question mark. If this action is not taken, CRL retrieval through HTTP returns an error message.

The CDP location may be changed after the certificate server is running through the **cdp-url** command. New certificates contain the updated CDP location, but existing certificates are not reissued with the newly specified CDP location. When a new CRL is issued, the certificate server uses its current cached CRL to generate a new CRL. (When the certificate server is rebooted, it reloads the current CRL from the database.) A new CRL cannot be issued unless the current CRL has expired. After the current CRL expires, a new CRL is issued only after a certificate is revoked from the CLI.

Certificate Server Error Conditions

At startup, the certificate server checks the current configuration before issuing any certificates. It reports the last known error conditions through the **show crypto pki server** command output. Example errors can include any of the following conditions:

- Storage inaccessible
- Waiting for HTTP server
- Waiting for time setting

If the certificate server experiences a critical failure at any time, such as failing to publish a CRL, the certificate server automatically enters a disabled state. This state allows the network administrator to fix the condition; thereafter, the certificate server returns to the previous normal state.

Certificate Enrollment Using a Certificate Server

A certificate enrollment request functions as follows:

- The certificate server receives the enrollment request from an end user, and the following actions occur:
 - A request entry is created in the enrollment request database with the initial state. (See the table below for a complete list of certificate enrollment request states.)
 - The certificate server refers to the CLI configuration (or the default behavior any time a parameter is not specified) to determine the authorization of the request. Thereafter, the state of the enrollment request is updated in the enrollment request database.
- At each SCEP query for a response, the certificate server examines the current request and performs one of the following actions:
 - Responds to the end user with a “pending” or “denied” state.
 - Generates and signs the appropriate certificate and stores the certificate in the enrollment request database.

If the connection of the client has closed, the certificate server waits for the client to request another certificate.

All enrollment requests transition through the certificate enrollment states that are defined in the table below. To see current enrollment requests, use the **crypto pki server request pkcs10** command.

Table 3 *Certificate Enrollment Request State Descriptions*

Certificate Enrollment State	Description
authorized	The certificate server has authorized the request.
denied	The certificate server has denied the request for policy reasons.
granted	The CA core has generated the appropriate certificate for the certificate request.
initial	The request has been created by the SCEP server.
malformed	The certificate server has determined that the request is invalid for cryptographic reasons.
pending	The enrollment request must be manually accepted by the network administrator.

- [SCEP Enrollment, page 8](#)

SCEP Enrollment

All SCEP requests are treated as new certificate enrollment requests, even if the request specifies a duplicate subject name or public key pair as a previous certificate request.

Types of CA Servers Subordinate and Registration Authorities (RAs)

CA servers have the flexibility to be configured as a subordinate certificate server or an RA-mode certificate server.

Why Configure a Subordinate CA?

A subordinate certificate server provides all the same features as a root certificate server. The root RSA key pairs are extremely important in a PKI hierarchy, and it is often advantageous to keep them offline or archived. To support this requirement, PKI hierarchies allow for subordinate CAs that have been signed by the root authority. In this way, the root authority can be kept offline (except to issue occasional CRL updates), and the subordinate CA can be used during normal operation.

Why Configure an RA-Mode Certificate Server?

A Cisco IOS certificate server can be configured to run in RA mode. An RA offloads authentication and authorization responsibilities from a CA. When the RA receives a SCEP or manual enrollment request, the administrator can either reject or grant it on the basis of local policy. If the request is granted, it is forwarded to the issuing CA, and the CA automatically generates the certificate and return it to the RA. The client can later retrieve the granted certificate from the RA.

An RA is the authority charged with recording or verifying some or all of the data required for the CA to issue certificates. In many cases the CA undertakes all of the RA functions itself, but where a CA operates over a wide geographical area or when there is security concern over exposing the CA to direct network access, it may be administratively advisable to delegate some of the tasks to an RA and leave the CA to concentrate on its primary tasks of signing certificates and CRLs.

CA Server Compatibility

In Cisco IOS Release 15.1(2)T, new functionality was introduced that allows the IOS CA server in RA mode to interoperate with more than one type of CA server. See [Configuring a Certificate Server to Run in RA Mode](#), page 24 for more information.

Automatic CA Certificate and Key Rollover

CAs--root CAs, subordinate CAs, and RA-mode CAs--like their clients, have certificates and key pairs with expiration dates that need to be reissued when the current certificate and key pair are about to expire. When a root CA's certificate and key pair are expiring it must generate a self-signed rollover certificate and key pair. If a subordinate CA or an RA-mode CA's certificate and key pair are expiring, it requests a rollover certificate and key pair from its superior CA, obtaining the superior CA's new self-signed rollover certificates at the same time. The CA must distribute the new CA rollover certificate and keys too all its peers. This process, called rollover, allows for continuous operation of the network while the CAs and their clients are switching from an expiring CA certificate and key pair to a new CA certificate and key pair.

Rollover relies on the PKI infrastructure requirements of trust relationships and synchronized clocks. The PKI trust relationships allow (1) the new CA certificate to be authenticated, and (2) the rollover to be accomplished automatically without the loss of security. Synchronized clocks allow the rollover to be coordinated throughout your network.

- [Automatic CA Certificate Rollover How It Works](#), page 9

Automatic CA Certificate Rollover How It Works

The CA server must have rollover configured. All levels of CAs must be automatically enrolled and have **auto-rollover** enabled. CA clients support rollover automatically when automatically enrolled. For more information about clients and automatic rollover, see the section "Automatic Certificate Enrollment" in the chapter "Configuring Certificate Enrollment for a PKI".

After CAs have rollover enabled and their clients are automatically enrolled, there are three stages to the automatic CA certificate rollover process.

Stage One: Active CA Certificate and Key Pair Only

In stage one, there is an active CA certificate and key pair only.

Stage Two: Rollover CA Certificate and Key Pair Generation and Distribution

In stage two, the rollover CA certificate and key pair are generated and distributed. The superior CA generates a rollover certificate and key pair. After the CA successfully saves its active configuration, the CA is ready to respond to client requests for the rollover certificate and key pair. When the superior CA receives a request for the new CA certificate and key pair from a client, the CA responds by sending the new rollover CA certificate and key pair to the requesting client. The clients store the rollover CA certificate and key pair.

**Note**

When a CA generates its rollover certificate and key pair, it must be able to save its active configuration. If the current configuration has been altered, saving of the rollover certificate and key pair does not happen automatically. In this case, the administrator must save the configuration manually or rollover information is lost.

Stage Three: Rollover CA Certificate and Key Pair Become the Active CA Certificate and Key Pair

In stage three, the rollover CA certificate and key pair become the active CA certificate and key pair. All devices that have stored a valid rollover CA certificate rename the rollover certificate to the active certificate and the once-active certificate and key pair are deleted.

After the CA certificate rollover, you may observe the following deviation from usual certificate lifetime and renewal time:

- The lifetime of the certificates issued during rollover is lower than the preconfigured value.
- In specific conditions, the renew time may be inferior to the configured percentage of the actual lifetime. The difference observed can be of up to 20% in cases where the certificate lifetime is less than one hour.

These differences are normal, and result from **jitter** (random time fluctuation) introduced by the algorithm on the Certificate server. This task is performed to avoid the hosts participating to the PKI synchronize their enrollment timer, which could result in congestion on the Certificate Server.

**Note**

The lifetime fluctuations that occur do not affect proper functioning of the PKI, since the differences always result in a shorter lifetime, thus remaining within maximum configured lifetime for certificates.

Support for Specifying a Cryptographic Hash Function

Secure Hash Algorithm (SHA) support allows a user to specify a cryptographic hash function for Cisco IOS certificate servers and clients. The cryptographic hash functions that can be specified are Message Digest algorithm 5 (MD5), SHA-1, SHA-256, SHA-384, or SHA-512.

**Note**

Cisco no longer recommends using MD5; instead, you should use SHA-256. For more information about the latest Cisco cryptographic recommendations, see the [Next Generation Encryption](#) (NGE) white paper.

See the “Configuring a Subordinate Certificate Server” task for more information on specifying the **hash** (ca-trustpoint) and **hash** (cs-server) commands that are used to implement this feature.

How to Set Up and Deploy a Cisco IOS Certificate Server

- [Generating a Certificate Server RSA Key Pair, page 11](#)
- [Configuring Certificate Servers, page 14](#)
- [Configuring Certificate Server Functionality, page 28](#)
- [Working with Automatic CA Certificate Rollover, page 32](#)
- [Maintaining Verifying and Troubleshooting the Certificate Server Certificates and the CA, page 35](#)

Generating a Certificate Server RSA Key Pair

Perform this task to manually generate an RSA key pair for the certificate server. Manually generating a certificate server RSA key pair allows you to specify the type of key pair you want to generate, to create an exportable key pair for backup purposes, to specify the key pair storage location, or to specify the key generation location.

If you are running Cisco IOS Release 12.3(8)T or earlier releases, you may want to create an exportable certificate server key pair for backup, or archive purposes. If this task is not performed, the certificate server automatically generates a key pair, which is not marked as exportable. Automatic CA certificate archiving was introduced in Cisco IOS Release 12.3(11)T.

As of Cisco IOS Release 12.4(11)T and later releases, if your router has a USB token configured and available, the USB token can be used as cryptographic device in addition to a storage device. Using a USB token as a cryptographic device allows RSA operations such as key generation, signing, and authentication of credentials to be performed on a USB token. The private key never leaves the USB token and is not exportable. The public key is exportable. For titles of specific documents about configuring a USB token and making it available to use as a cryptographic device, see the “Related Documents” section.



Note

It is recommended that the private key be kept in a secure location and that you regularly archive the certificate server database.



Note

Security threats, as well as the cryptographic technologies to help protect against them, are constantly changing. For more information about the latest Cisco cryptographic recommendations, see the [Next Generation Encryption \(NGE\)](#) white paper.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **crypto key generate rsa** [**general-keys** | **usage-keys** | **signature** | **encryption**] [**label** *key-label*] [**exportable**] [**modulus** *modulus-size*] [**storage** *devicename:*] [**on** *devicename:*]
4. **crypto key export rsa** *key-label* **pem** {**terminal** | **url** *url*} {**3des** | **des**} *passphrase*
5. **crypto key import rsa** *key-label* **pem** [**usage-keys** | **signature** | **encryption**] {**terminal** | **url** *url*} [**exportable**] [**on** *devicename:*] *passphrase*
6. **exit**
7. **show crypto key mypubkey rsa**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 configure terminal Example: Router# configure terminal	Enters global configuration mode.

Command or Action	Purpose
<p>Step 3 <code>crypto key generate rsa [general-keys usage-keys signature encryption] [label key-label] [exportable] [modulus modulus-size] [storage devicename:] [on devicename:]</code></p> <p>Example:</p> <pre>Router (config)# crypto key generate rsa label mycs exportable modulus 2048</pre>	<p>Generates the RSA key pair for the certificate server.</p> <ul style="list-style-type: none"> The storage keyword specifies the key storage location. When specifying a label name by specifying the <i>key-label</i> argument, you must use the same name for the label that you plan to use for the certificate server (through the crypto pki server cs-label command). If a <i>key-label</i> argument is not specified, the default value, which is the fully qualified domain name (FQDN) of the router, is used. <p>If the exportable RSA key pair is manually generated after the CA certificate has been generated, and before issuing the no shutdown command, then use the crypto ca export pkcs12 command to export a PKCS12 file that contains the certificate server certificate and the private key.</p> <ul style="list-style-type: none"> By default, the modulus size of a CA key is 1024 bits. The recommended modulus for a CA key is 2048 bits. The range for a modulus size of a CA key is from 350 to 4096 bits. The on keyword specifies that the RSA key pair is created on the specified device, including a Universal Serial Bus (USB) token, local disk, or NVRAM. The name of the device is followed by a colon (:). <p>Note Keys created on a USB token must be 2048 bits or less.</p>
<p>Step 4 <code>crypto key export rsa key-label pem {terminal url url} {3des des} passphrase</code></p> <p>Example:</p> <pre>Router (config)# crypto key export rsa mycs pem url nvram: 3des PASSWORD</pre>	<p>(Optional) Exports the generated RSA key pair.</p> <p>Allows you to export the generated keys.</p>
<p>Step 5 <code>crypto key import rsa key-label pem [usage-keys signature encryption] {terminal url url} [exportable] [on devicename:] passphrase</code></p> <p>Example:</p> <pre>Router (config)# crypto key import rsa mycs2 pem url nvram:mycs PASSWORD</pre>	<p>(Optional) Imports RSA key pair.</p> <p>To create the imported keys on a USB token, use the on keyword and specify the appropriate device location.</p> <p>If you exported the RSA keys using the exportable keyword and you want to change the RSA key pair to nonexportable, import the key back to the certificate server without the exportable keyword. The key cannot be exported again.</p>
<p>Step 6 <code>exit</code></p> <p>Example:</p> <pre>Router (config)# exit</pre>	<p>Exits global configuration.</p>

Command or Action	Purpose
Step 7 <code>show crypto key mypubkey rsa</code>	Displays the RSA public keys of your router.
Example: Router# <code>show crypto key mypubkey rsa</code>	

Example

The following example generates a general usage 1024-bit RSA key pair on a USB token with the label “ms2” with crypto engine debugging messages shown:

```
Router(config)# crypto key generate rsa on usbtoken0 label ms2 modulus 1024
The name for the keys will be: ms2
% The key modulus size is 1024 bits
% Generating 1024 bit RSA keys, keys will be on-token, non-exportable...
Jan 7 02:41:40.895: crypto_engine: Generate public/private keypair [OK]
Jan 7 02:44:09.623: crypto_engine: Create signature
Jan 7 02:44:10.467: crypto_engine: Verify signature
Jan 7 02:44:10.467: CryptoEngine0: CRYPTO_ISA_RSA_CREATE_PUBKEY(hw)(ipsec)
Jan 7 02:44:10.467: CryptoEngine0: CRYPTO_ISA_RSA_PUB_DECRYPT(hw)(ipsec)
```

Now, the on-token keys labeled “ms2” may be used for enrollment.

The following example shows the successful import of an encryption key to a configured and available USB tokens:

```
Router#
configure terminal

Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#
crypto key import rsa encryption on usbtoken0 url nvram:e password

% Importing public Encryption key or certificate PEM file...
filename [e-encr.pub]?
Reading file from nvram:e-encr.pub
% Importing private Encryption key PEM file...
Source filename [e-encr.prv]?
Reading file from nvram:e-encr.prv
% Key pair import succeeded.
```

Configuring Certificate Servers

- [Prerequisites for Automatic CA Certificate Rollover, page 14](#)
- [Restrictions for Automatic CA Certificate Rollover, page 15](#)
- [Configuring a Certificate Server, page 15](#)
- [Configuring a Subordinate Certificate Server, page 17](#)
- [Configuring a Certificate Server to Run in RA Mode, page 24](#)
- [Configuring the Root Certificate Server to Delegate Enrollment Tasks to the RA Mode Certificate Server, page 26](#)
- [What to Do Next, page 28](#)

Prerequisites for Automatic CA Certificate Rollover

When configuring a certificate server, for automatic CA certificate rollover to run successfully, the following prerequisites are applicable for your CA servers:

- You must be running Cisco IOS Release 12.4(2)T or a later release on your CA servers.
- Your CA server must be enabled and fully configured with a reliable time of day, an available key pair, a self-signed, valid CA certificate associated with the key pair, a CRL, an accessible storage device, and an active HTTP/SCEP server.
- CA clients must have successfully completed automatic enrollment and have autoenrollment enabled with the same certificate server.

**Note**

If you are running Cisco IOS 12.4(2)T or earlier releases, only your root CA supports automatic CA certificate rollover functionality. Cisco IOS 12.4(4)T or later releases support all CAs--root CAs, subordinate CAs, and RA-mode CAs.

Restrictions for Automatic CA Certificate Rollover

When configuring a certificate server, in order for automatic CA certificate rollover to run successfully, the following restrictions are applicable:

- SCEP must be used to support rollover. Any device that enrolls with the PKI using an alternative to SCEP as the certificate management protocol or mechanism (such as enrollment profiles, manual enrollment, or TFTP enrollment) is not be able to take advantage of the rollover functionality provided by SCEP.
- If you have automatic archive configured on your network and the archive fails, rollover does not occur because the certificate server does not enter the rollover state, and the rollover certificate and key pair is not automatically saved.

Configuring a Certificate Server

Perform this task to configure a Cisco IOS certificate server and enable automatic rollover.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip http server**
4. **crypto pki server** *cs-label*
5. **no shutdown**
6. **auto-rollover** [*time-period*]

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> Enter your password if prompted.
<p>Step 2 <code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 3 <code>ip http server</code></p> <p>Example:</p> <pre>Router(config)# ip http server</pre>	<p>Enables the HTTP server on your system.</p>
<p>Step 4 <code>crypto pki server <i>cs-label</i></code></p> <p>Example:</p> <pre>Router(config)# crypto pki server server-pki</pre>	<p>Defines a label for the certificate server and enters certificate server configuration mode.</p> <p>Note If you manually generated an RSA key pair, the <i>cs-label</i> argument must match the name of the key pair.</p>
<p>Step 5 <code>no shutdown</code></p> <p>Example:</p> <pre>Router(cs-server)# no shutdown</pre>	<p>(Optional) Enables the certificate server.</p> <p>Note Only use this command at this point if you want to use the preconfigured default functionality. That is, do not issue this command just yet if you plan to change any of the default settings as shown in the task “Configuring Certificate Server Functionality.”</p>
<p>Step 6 <code>auto-rollover [<i>time-period</i>]</code></p> <p>Example:</p> <pre>Router(cs-server)# auto-rollover 90</pre>	<p>(Optional) Enables the automated CA certificate rollover functionality.</p> <ul style="list-style-type: none"> <i>time-period</i> --default is 30 days.

Examples

The following example shows how to configure the certificate server “ca”:

```
Router(config)#
crypto pki server ca
Router(cs-server)#
no shutdown
% Once you start the server, you can no longer change some of
```

```

% the configuration.
Are you sure you want to do this? [yes/no]:
yes
% Generating 1024 bit RSA keys ...[OK]
% Certificate Server enabled.
Router(cs-server)#
end
!
Router#
show crypto pki server
Certificate Server ca:
  Status: enabled, configured
  CA cert fingerprint: 5A856122 4051347F 55E8C246 866D0AC3
  Granting mode is: manual
  Last certificate issued serial number: 0x1
  CA certificate expiration timer: 19:44:57 GMT Oct 14 2006

CRL NextUpdate timer: 19:45:25 GMT Oct 22 2003
Current storage dir: nvram:
Database Level: Complete - all issued certs written as <serialnum>.cer

```

The following example shows how to enable automated CA certificate rollover on the server mycs with the **auto-rollover** command. The **show crypto pki server** command shows that the automatic rollover has been configured on the server mycs with an overlap period of 25 days.

```

Router(config)# crypto pki server mycs
Router(cs-server)# auto-rollover 25
Router(cs-server)# no shut
%Some server settings cannot be changed after CA certificate generation.
% Generating 1024 bit RSA keys, keys will be non-exportable...[OK]
% Exporting Certificate Server signing certificate and keys...
% Certificate Server enabled.
Router(cs-server)#
Router# show crypto pki server
Certificate Server mycs:
  Status: enabled
  Server's configuration is locked (enter "shut" to unlock it)
  Issuer name: CN=mycs
  CA cert fingerprint: 70AFECA9 211CDDCC 6AA9D7FF 3ADB03AE
  Granting mode is: manual
  Last certificate issued serial number: 0x1
  CA certificate expiration timer: 00:49:26 PDT Jun 20 2008
  CRL NextUpdate timer: 00:49:29 PDT Jun 28 2005
  Current storage dir: nvram:
  Database Level: Minimum - no cert data written to storage
  Auto-Rollover configured, overlap period 25 days
  Autorollover timer: 00:49:26 PDT May 26 2008

```

Configuring a Subordinate Certificate Server

Perform this task to configure a subordinate certificate server to grant all or certain SCEP or manual certificate requests and to enable automatic rollover.



Note

- You must be running Cisco IOS Release 12.3(14)T or a later release. (Versions prior to Cisco IOS software Release 12.3(14)T support only one certificate server and no hierarchy; that is, subordinate certificate servers are not supported.)
- The root certificate server should be a Cisco IOS certificate server.

**Note**

Security threats, as well as the cryptographic technologies to help protect against them, are constantly changing. For more information about the latest Cisco cryptographic recommendations, see the [Next Generation Encryption \(NGE\)](#) white paper.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **crypto pki trustpoint** *name*
4. **enrollment** [**mode**] [**retry period** *minutes*] [**retry count** *number*] **url** *url* [**pem**]
5. **hash** {**md5** | **sha1** | **sha256** | **sha384** | **sha512**}
6. **exit**
7. **crypto pki server** *cs-label*
8. **issuer name** *DN-string*
9. **mode sub-cs**
10. **auto-rollover** [*time-period*]
11. **grant auto rollover** {**ca-cert** | **ra-cert**}
12. **hash** {**md5** | **sha1** | **sha256** | **sha384** | **sha512**}
13. **no shutdown**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3	crypto pki trustpoint <i>name</i> Example: <pre>Router (config)# crypto pki trustpoint sub</pre>	Declares the trustpoint that your subordinate certificate server should use and enters ca-trustpoint configuration mode.

Command or Action	Purpose
<p>Step 4 enrollment [mode] [retry period <i>minutes</i>] [retry count <i>number</i>] url <i>url</i> [pem]</p> <p>Example:</p> <pre>Router (ca-trustpoint)# enrollment url http://caserver.myexample.com - or- Router (ca-trustpoint)# enrollment url http://[2001:DB8:1:1::1]:80</pre>	<p>Specifies the following enrollment parameters of the CA:</p> <ul style="list-style-type: none"> • (Optional) The mode keyword specifies the registration authority (RA) mode, if your CA system provides an RA. By default, RA mode is disabled. • (Optional) The retry period keyword and <i>minutes</i> argument specifies the period, in minutes, in which the router waits before sending the CA another certificate request. Valid values are from 1 to 60. The default is 1. • (Optional) The retry count keyword and <i>number</i> argument specifies the number of times a router will resend a certificate request when it does not receive a response from the previous request. Valid values are from 1 to 100. The default is 10. • The <i>url</i> argument is the URL of the CA to which your router should send certificate requests. <ul style="list-style-type: none"> Note With the introduction of Cisco IOS Release 15.2(1)T, an IPv6 address can be added to the http: enrolment method. For example: <code>http://[ipv6-address]:80</code>. The IPv6 address must be enclosed in brackets in the URL. See the enrollment url (ca-trustpoint) command page for more information on the other enrollment methods that can be used. • (Optional) The pem keyword adds privacy-enhanced mail (PEM) boundaries to the certificate request.
<p>Step 5 hash {md5 sha1 sha256 sha384 sha512}</p> <p>Example:</p> <pre>Router (ca-trustpoint)# hash sha384</pre>	<p>(Optional) Specifies the hash function for the signature that the Cisco IOS client uses to sign its self-signed certificates. The Cisco IOS client uses the MD5 cryptographic hash function for self-signed certificates by default.</p> <p>Any of the following command algorithm keyword options can be specified to over-ride the default setting for the trustpoint. This setting then becomes the default cryptographic hash algorithm function for self-signed certificates by default.</p> <ul style="list-style-type: none"> • md5 —Specifies that MD5, the default hash function, is used. (No longer recommended). • sha1 —Specifies that the SHA-1 hash function is used as the default hash algorithm for RSA keys. (No longer recommended). • sha256 —Specifies that the SHA-256 hash function is used as the hash algorithm for Elliptic Curve (EC) 256 bit keys. • sha384 —Specifies that the SHA-384 hash function is used as the hash algorithm for EC 384 bit keys. • sha512 —Specifies that the SHA-512 hash function is used as the hash algorithm for EC 512 bit keys.

Command or Action	Purpose
<p>Step 6 <code>exit</code></p> <p>Example:</p> <pre>Router (ca-trustpoint)# exit</pre>	<p>Exits ca-trustpoint configuration mode.</p>
<p>Step 7 <code>crypto pki server <i>cs-label</i></code></p> <p>Example:</p> <pre>Router(config)# crypto pki server sub</pre>	<p>Enables a Cisco IOS certificate server and enters cs-server configuration mode.</p> <p>Note The subordinate server must have the same name as the trustpoint that was created in Step 3 above.</p>
<p>Step 8 <code>issuer name <i>DN-string</i></code></p> <p>Example:</p> <pre>Router(cs-server) # issuer-name CN=sub CA, O=Cisco, C=us</pre>	<p>(Optional) Specifies the DN as the CA issuer name for the certificate server.</p>
<p>Step 9 <code>mode sub-cs</code></p> <p>Example:</p> <pre>Router(cs-server)# mode sub-cs</pre>	<p>Places the PKI server into sub-certificate server mode.</p>
<p>Step 10 <code>auto-rollover [<i>time-period</i>]</code></p> <p>Example:</p> <pre>Router(cs-server)# auto-rollover 90</pre>	<p>(Optional) Enables the automated CA certificate rollover functionality.</p> <ul style="list-style-type: none"> <i>time-period</i> --default is 30 days.
<p>Step 11 <code>grant auto rollover {<i>ca-cert</i> <i>ra-cert</i>}</code></p> <p>Example:</p> <pre>Router(cs-server)# grant auto rollover ca-cert</pre>	<p>(Optional) Automatically grants reenrollment requests for subordinate CAs and RA-mode CAs without operator intervention.</p> <ul style="list-style-type: none"> ca-cert --Specifies that the subordinate CA rollover certificate is automatically granted. ra-cert --Specifies that the RA-mode CA rollover certificate is automatically granted. <p>Note If this is the first time that a subordinate certificate server is enabled and enrolled, the certificate request must be manually granted.</p>

Command or Action	Purpose
<p>Step 12 <code>hash {md5 sha1 sha256 sha384 sha512}</code></p> <p>Example:</p> <pre>Router(cs-server)# hash sha384</pre>	<p>(Optional) Sets the hash function for the signature that the Cisco IOS certificate authority (CA) uses to sign all of the certificates issued by the server.</p> <ul style="list-style-type: none"> • md5 —Specifies that MD5, the default hash function, is used. (No longer recommended). • sha1 —Specifies that the SHA-1 hash function is used. (No longer recommended). • sha256 —Specifies that the SHA-256 hash function is used. • sha384 —Specifies that the SHA-384 hash function is used. • sha512 —Specifies that the SHA-512 hash function is used.
<p>Step 13 <code>no shutdown</code></p> <p>Example:</p> <pre>Router(cs-server)# no shutdown</pre>	<p>Enables or reenables the certificate server.</p> <p>If this is the first time that a subordinate certificate server is enabled, the certificate server generates the key and obtain its signing certificate from the root certificate server.</p>

- [Examples, page 21](#)

Examples

If the certificate server fails to enable or if the certificate server has trouble handling the request that has been configured, you can use the **debug crypto pki server** command to troubleshoot your configuration as shown in the following examples (Clock Not Set and Trustpoint Not Configured):

```
Router# debug crypto pki server
```

Clock Not Set

```
Router(config)# crypto pki server sub
Router(cs-server)# mode sub-cs
Router(cs-server)# no shutdown
%Some server settings cannot be changed after CA certificate generation.
% Please enter a passphrase to protect the private key % or type Return to exit
Password:
*Jan 6 20:57:37.667: CRYPTO_CS: enter FSM: input state initial, input signal no shut
Re-enter password:
% Generating 1024 bit RSA keys ...
*Jan 6 20:57:45.303: CRYPTO_CS: starting enabling checks
*Jan 6 20:57:45.303: CRYPTO_CS: key 'sub' does not exist; generated automatically[OK]
% Time has not been set. Cannot start the Certificate server
```

Trustpoint Not Configured

```
Router(config)# crypto pki server sub
Router(cs-server)# mode sub-cs
Router(cs-server)# no shutdown
%Some server settings cannot be changed after CA certificate generation.
% Please enter a passphrase to protect the private key or type Return to exit
Password:
Jan 6 21:00:15.961: CRYPTO_CS: enter FSM: input state initial, input signal no shut.
Jan 6 21:03:34.309: CRYPTO_CS: enter FSM: input state initial, input signal time set.
Jan 6 21:03:34.313: CRYPTO_CS: exit FSM: new state initial.
```

```

Jan 6 21:03:34.313: CRYPTO_CS: cs config has been unlocked
Re-enter password:
% Generating 1024 bit RSA keys ...
Jan 6 21:03:44.413: CRYPTO_CS: starting enabling checks
Jan 6 21:03:44.413: CRYPTO_CS: associated trust point 'sub' does not exist; generated
automatically
Jan 6 21:03:44.417: CRYPTO_CS: key 'sub' does not exist; generated automatically[OK]
Jan 6 21:04:03.993: CRYPTO_CS: nvram filesystem
Jan 6 21:04:04.077: CRYPTO_CS: serial number 0x1 written.
You must specify an enrollment URL for this CA before you can authenticate it.
% Failed to authenticate the Certificate Authority

```

If the certificate server fails to obtain its signing certificate from the root certificate server, you can use the **debug crypto pki transactions** command to troubleshoot your configuration as shown in the following example:

```

Router# debug crypto pki transactions
Jan 6 21:07:00.311: CRYPTO_CS: enter FSM: input state initial, input signal time set
Jan 6 21:07:00.311: CRYPTO_CS: exit FSM: new state initial
Jan 6 21:07:00.311: CRYPTO_CS: cs config has been unlocked no sh
%Some server settings cannot be changed after CA certificate generation.
% Please enter a passphrase to protect the private key % or type Return to exit
Password:
Jan 6 21:07:03.535: CRYPTO_CS: enter FSM: input state initial, input signal no shut
Re-enter password:
% Generating 1024 bit RSA keys ...
Jan 6 21:07:10.619: CRYPTO_CS: starting enabling checks
Jan 6 21:07:10.619: CRYPTO_CS: key 'sub' does not exist; generated automatically[OK]
Jan 6 21:07:20.535: %SSH-5-ENABLED: SSH 1.99 has been enabled
Jan 6 21:07:25.883: CRYPTO_CS: nvram filesystem
Jan 6 21:07:25.991: CRYPTO_CS: serial number 0x1 written.
Jan 6 21:07:27.863: CRYPTO_CS: created a new serial file.
Jan 6 21:07:27.863: CRYPTO_CS: authenticating the CA 'sub'
Jan 6 21:07:27.867: CRYPTO_PKI: Sending CA Certificate Request:
GET /cgi-bin/pkiclient.exe?operation=GetCACert&message=sub HTTP/1.0
User-Agent: Mozilla/4.0 (compatible; MSIE 5.0; Cisco PKI)
Jan 6 21:07:27.867: CRYPTO_PKI: can not resolve server name/IP address
Jan 6 21:07:27.871: CRYPTO_PKI: Using unresolved IP Address 192.0.2.6 Certificate has the
following attributes:
    Fingerprint MD5: 328ACC02 52B25DB8 22F8F104 B6055B5B
    Fingerprint SHA1: 02FD799D DD40C7A8 61DC53AB 1E89A3EA 2A729EE2
% Do you accept this certificate? [yes/no]:
Jan 6 21:07:30.879: CRYPTO_PKI: http connection opened
Jan 6 21:07:30.903: CRYPTO_PKI: HTTP response header:
    HTTP/1.1 200 OK
Date: Thu, 06 Jan 2005 21:07:30 GMT
Server: server-IOS
Content-Type: application/x-x509-ca-cert
Expires: Thu, 06 Jan 2005 21:07:30 GMT
Last-Modified: Thu, 06 Jan 2005 21:07:30 GMT
Cache-Control: no-store, no-cache, must-revalidate
Pragma: no-cache
Accept-Ranges: none
Content-Type indicates we have received a CA certificate.
Jan 6 21:07:30.903: Received 507 bytes from server as CA certificate:
Jan 6 21:07:30.907: CRYPTO_PKI: transaction GetCACert completed
Jan 6 21:07:30.907: CRYPTO_PKI: CA certificate received.
Jan 6 21:07:30.907: CRYPTO_PKI: CA certificate received.
Jan 6 21:07:30.927: CRYPTO_PKI: crypto_pki_authenticate_tp_cert()
Jan 6 21:07:30.927: CRYPTO_PKI: trustpoint sub authentication status = 0 y Trustpoint CA
certificate accepted.%
% Certificate request sent to Certificate Authority
% Enrollment in progress...
Router (cs-server)#
Jan 6 21:07:51.772: CRYPTO_CA: certificate not found
Jan 6 21:07:51.772: CRYPTO_CA: certificate not found
Jan 6 21:07:52.460: CRYPTO_CS: Publishing 213 bytes to crl file nvram:sub.crl
Jan 6 21:07:54.348: CRYPTO_CS: enrolling the server's trustpoint 'sub'
Jan 6 21:07:54.352: CRYPTO_CS: exit FSM: new state check failed
Jan 6 21:07:54.352: CRYPTO_CS: cs config has been locked
Jan 6 21:07:54.356: CRYPTO_PKI: transaction PKCSReq completed
Jan 6 21:07:54.356: CRYPTO_PKI: status:

```

```

Jan 6 21:07:55.016: CRYPTO_PKI: Certificate Request Fingerprint MD5: 1BA027DB 1C7860C7
ECl88F65 64356C80
Jan 6 21:07:55.016: CRYPTO_PKI: Certificate Request Fingerprint SHA1: 840DB52C E17614CB
0C7BE187 0DFC884D D32CAA75
Jan 6 21:07:56.508: CRYPTO_PKI: can not resolve server name/IP address
Jan 6 21:07:56.508: CRYPTO_PKI: Using unresolved IP Address 192.0.2.6
Jan 6 21:07:56.516: CRYPTO_PKI: http connection opened
Jan 6 21:07:59.136: CRYPTO_PKI: received msg of 776 bytes
Jan 6 21:07:59.136: CRYPTO_PKI: HTTP response header:
  HTTP/1.1 200 OK
  Date: Thu, 06 Jan 2005 21:07:57 GMT
  Server: server-IOS
  Content-Type: application/x-pki-message
  Expires: Thu, 06 Jan 2005 21:07:57 GMT
  Last-Modified: Thu, 06 Jan 2005 21:07:57 GMT
  Cache-Control: no-store, no-cache, must-revalidate
  Pragma: no-cache
  Accept-Ranges: none
Jan 6 21:07:59.324: The PKCS #7 message has 1 verified signers.
Jan 6 21:07:59.324: signing cert: issuer=cn=root1
Jan 6 21:07:59.324: Signed Attributes:
Jan 6 21:07:59.328: CRYPTO_PKI: status = 102: certificate request pending
Jan 6 21:08:00.788: CRYPTO_PKI: can not resolve server name/IP address
Jan 6 21:08:00.788: CRYPTO_PKI: Using unresolved IP Address 192.0.2.6
Jan 6 21:08:00.796: CRYPTO_PKI: http connection opened
Jan 6 21:08:11.804: CRYPTO_PKI: received msg of 776 bytes
Jan 6 21:08:11.804: CRYPTO_PKI: HTTP response header: HTTP/1.1 200 OK
  Date: Thu, 06 Jan 2005 21:08:01 GMT
  Server: server-IOS
  Content-Type: application/x-pki-message
  Expires: Thu, 06 Jan 2005 21:08:01 GMT
  Last-Modified: Thu, 06 Jan 2005 21:08:01 GMT
  Cache-Control: no-store, no-cache, must-revalidate
  Pragma: no-cache
  Accept-Ranges: none
Jan 6 21:08:11.992: The PKCS #7 message has 1 verified signers.
Jan 6 21:08:11.992: signing cert: issuer=cn=root1
Jan 6 21:08:11.996: Signed Attributes:
Jan 6 21:08:11.996: CRYPTO_PKI: status = 102: certificate request pending
Jan 6 21:08:21.996: CRYPTO_PKI: All sockets are closed for trustpoint sub.
Jan 6 21:08:31.996: CRYPTO_PKI: All sockets are closed for trustpoint sub.
Jan 6 21:08:41.996: CRYPTO_PKI: All sockets are closed for trustpoint sub.
Jan 6 21:08:51.996: CRYPTO_PKI: All sockets are closed for trustpoint sub.
Jan 6 21:09:01.996: CRYPTO_PKI: All sockets are closed for trustpoint sub.
Jan 6 21:09:11.996: CRYPTO_PKI: resend GetCertInitial, 1
Jan 6 21:09:11.996: CRYPTO_PKI: All sockets are closed for trustpoint sub.
Jan 6 21:09:11.996: CRYPTO_PKI: resend GetCertInitial for session: 0
Jan 6 21:09:11.996: CRYPTO_PKI: can not resolve server name/IP address
Jan 6 21:09:11.996: CRYPTO_PKI: Using unresolved IP Address 192.0.2.6
Jan 6 21:09:12.024: CRYPTO_PKI: http connection opened% Exporting Certificate Server
signing certificate and keys...
Jan 6 21:09:14.784: CRYPTO_PKI: received msg of 1611 bytes
Jan 6 21:09:14.784: CRYPTO_PKI: HTTP response header:
  HTTP/1.1 200 OK
  Date: Thu, 06 Jan 2005 21:09:13 GMT
  Server: server-IOS
  Content-Type: application/x-pki-message
  Expires: Thu, 06 Jan 2005 21:09:13 GMT
  Last-Modified: Thu, 06 Jan 2005 21:09:13 GMT
  Cache-Control: no-store, no-cache, must-revalidate
  Pragma: no-cache
  Accept-Ranges: none
Jan 6 21:09:14.972: The PKCS #7 message has 1 verified signers.
Jan 6 21:09:14.972: signing cert: issuer=cn=root1
Jan 6 21:09:14.972: Signed Attributes:
Jan 6 21:09:14.976: CRYPTO_PKI: status = 100: certificate is granted
Jan 6 21:09:15.668: The PKCS #7 message contains 1 certs and 0 crls.
Jan 6 21:09:15.688: Newly-issued Router Cert: issuer=cn=root serial=2
Jan 6 21:09:15.688: start date: 21:08:03 GMT Jan 6 2005
Jan 6 21:09:15.688: end date: 21:08:03 GMT Jan 6 2006
Jan 6 21:09:15.688: Router date: 21:09:15 GMT Jan 6 2005
Jan 6 21:09:15.692: Received router cert from CA
Jan 6 21:09:15.740: CRYPTO_CA: certificate not found

```

```

Jan 6 21:09:15.744: CRYPTO_PKI: All enrollment requests completed for trustpoint sub.
Jan 6 21:09:15.744: %PKI-6-CERTRET: Certificate received from Certificate Authority
Jan 6 21:09:15.744: CRYPTO_PKI: All enrollment requests completed for trustpoint sub.
Jan 6 21:09:15.744: CRYPTO_PKI: All enrollment requests completed for trustpoint sub.
Jan 6 21:09:15.748: CRYPTO_CS: enter FSM: input state check failed, input signal cert
configured
Jan 6 21:09:15.748: CRYPTO_CS: starting enabling checks
Jan 6 21:09:15.748: CRYPTO_CS: nvram filesystem
Jan 6 21:09:15.796: CRYPTO_CS: found existing serial file.
Jan 6 21:09:15.820: CRYPTO_CS: old router cert flag 0x4
Jan 6 21:09:15.820: CRYPTO_CS: new router cert flag 0x44
Jan 6 21:09:18.432: CRYPTO_CS: DB version 1
Jan 6 21:09:18.432: CRYPTO_CS: last issued serial number is 0x1
Jan 6 21:09:18.480: CRYPTO_CS: CRL file sub.crl exists.
Jan 6 21:09:18.480: CRYPTO_CS: Read 213 bytes from crl file sub.crl.
Jan 6 21:09:18.532: CRYPTO_CS: SCEP server started
Jan 6 21:09:18.532: CRYPTO_CS: exit FSM: new state enabled
Jan 6 21:09:18.536: CRYPTO_CS: cs config has been locked
Jan 6 21:09:18.536: CRYPTO_PKI: All enrollment requests completed for trustpoint sub.

```

If the certificate server fails to enable or if the certificate server has trouble handling the request that has been configured, you can use the **debug crypto pki server** command to troubleshoot the progress of an enrollment. This command can also be used to debug the root CA (turn it on at the root CA).

Configuring a Certificate Server to Run in RA Mode

The Cisco IOS certificate server can act as an RA for a Cisco IOS CA or another third party CA. Read the details in Step 8 for more information about the **transparent** keyword option if a third-party CA is used.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **crypto pki trustpoint** *name*
4. **enrollment url** *url*
5. **subject-name** *x.500-name*
6. **exit**
7. **crypto pki server** *cs-label*
8. **mode ra** [**transparent**]
9. **auto-rollover** [*time-period*]
10. **grant auto rollover** {**ca-cert** | **ra-cert**}
11. **no shutdown**
12. **no shutdown**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.
	Example:	
	Router> enable	<ul style="list-style-type: none"> • Enter your password if prompted.

	Command or Action	Purpose
Step 2	<p>configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3	<p>crypto pki trustpoint <i>name</i></p> <p>Example:</p> <pre>Router (config)# crypto pki trustpoint ra-server</pre>	Declares the trustpoint that your RA mode certificate server should use and enters ca-trustpoint configuration mode.
Step 4	<p>enrollment url <i>url</i></p> <p>Example:</p> <pre>Router (ca-trustpoint)# enrollment url http://ca- server.company.com</pre>	Specifies the enrollment URL of the issuing CA certificate server (root certificate server).
Step 5	<p>subject-name <i>x.500-name</i></p> <p>Example:</p> <pre>Router (ca-trustpoint)# subject-name cn=ioscs RA</pre>	<p>(Optional) Specifies the subject name the RA uses.</p> <p>Note Include “cn=ioscs RA” or “ou=ioscs RA” in the subject name so that the issuing CA certificate server can recognize the RA (see Step 7 below).</p>
Step 6	<p>exit</p> <p>Example:</p> <pre>Router (ca-trustpoint)# exit</pre>	Exits ca-trustpoint configuration mode.
Step 7	<p>crypto pki server <i>cs-label</i></p> <p>Example:</p> <pre>Router(config)# crypto pki server ra- server</pre>	<p>Enables a Cisco IOS certificate server and enters cs-server configuration mode.</p> <p>Note The certificate server must have the same name as the trustpoint that was created in Step 3 above.</p>

Command or Action	Purpose
<p>Step 8 <code>mode ra [transparent]</code></p> <p>Example:</p> <pre>Router(cs-server)# mode ra</pre>	<p>Places the PKI server into RA certificate server mode.</p> <p>Use the transparent keyword to allow the CA server in RA mode to interoperate with more than one type of CA server. When the transparent keyword is used, the original PKCS#10 enrollment message is not re-signed and is forwarded unchanged. This enrollment message makes the IOS RA certificate server work with CA servers like the Microsoft CA server.</p>
<p>Step 9 <code>auto-rollover [time-period]</code></p> <p>Example:</p> <pre>Router(cs-server)# auto-rollover 90</pre>	<p>(Optional) Enables the automatic CA certificate rollover functionality.</p> <ul style="list-style-type: none"> <code>time-period</code> --default is 30 days.
<p>Step 10 <code>grant auto rollover {ca-cert ra-cert}</code></p> <p>Example:</p> <pre>Router(cs-server)# grant auto rollover ra-cert</pre>	<p>(Optional) Automatically grants reenrollment requests for subordinate CAs and RA-mode CAs without operator intervention.</p> <ul style="list-style-type: none"> ca-cert --Specifies that the subordinate CA rollover certificate is automatically granted. ra-cert --Specifies that the RA-mode CA rollover certificate is automatically granted. <p>If this is the first time that a subordinate certificate server is enabled and enrolled, the certificate request must be manually granted.</p>
<p>Step 11 <code>no shutdown</code></p> <p>Example:</p> <pre>Router(cs-server)# no shutdown</pre>	<p>Enables the certificate server.</p> <p>Note After this command is issued, the RA automatically enrolls with the root certificate server. After the RA certificate has been successfully received, you must issue the no shutdown command again, which reenables the certificate server.</p>
<p>Step 12 <code>no shutdown</code></p> <p>Example:</p> <pre>Router(cs-server)# no shutdown</pre>	<p>Reenables the certificate server.</p>

Configuring the Root Certificate Server to Delegate Enrollment Tasks to the RA Mode Certificate Server

Perform the following steps on the router that is running the issuing certificate server; that is, configure the root certificate server that is delegating enrollment tasks to the RA mode certificate server.

**Note**

Granting enrollment requests for an RA is essentially the same process as granting enrollment requests for client devices--except that enrollment requests for an RA are displayed in the section “RA certificate requests” of the command output for the **crypto pki server info-requests** command.

SUMMARY STEPS

1. **enable**
2. **crypto pki server *cs-label* info requests**
3. **crypto pki server *cs-label* grant *req-id***
4. **configure terminal**
5. **crypto pki server *cs-label***
6. **grant ra-auto**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: <pre>Router > enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 crypto pki server <i>cs-label</i> info requests Example: <pre>Router# crypto pki server root-server info requests</pre>	Displays the outstanding RA certificate request. Note This command is issued on the router that is running the issuing certificate server.
Step 3 crypto pki server <i>cs-label</i> grant <i>req-id</i> Example: <pre>Router# crypto pki server root-server grant 9</pre>	Grants the pending RA certificate request. Note Because the issuing certificate server delegates the enrollment request verification task to the RA, you must pay extra attention to the RA certificate request before granting it.
Step 4 configure terminal Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.

Command or Action	Purpose
Step 5 <code>crypto pki server cs-label</code> Example: <pre>Router (config)# crypto pki server root-server</pre>	Enables a Cisco IOS certificate server and enters cs-server configuration mode.
Step 6 <code>grant ra-auto</code> Example: <pre>Router(cs-server)# grant ra-auto</pre>	(Optional) Specifies that all enrollment requests from an RA are to be granted automatically. Note For the grant ra-auto command to work, you have to include “cn=ioscs RA” or “ou=ioscs RA” in the subject name of the RA certificate. (See Step 2 above.)

What to Do Next

After you have configured a certificate server, you can use the preconfigured default values or specify values through the CLI for the functionality of the certificate server. If you choose to specify values other than the defaults, see the following section, “[Configuring Certificate Server Functionality, page 28.](#)”

Configuring Certificate Server Functionality

After you have enabled a certificate server and are in certificate server configuration mode, use any of the steps in this task to configure basic certificate server functionality values other than the default values.

- [Certificate Server Default Values and Recommended Values, page 28](#)
- [Certificate Server File Storage and Publication Locations, page 28](#)

Certificate Server Default Values and Recommended Values

The default values for a certificate server are intended to address a relatively small network (of about ten devices). For example, the database settings are minimal (through the **database level minimal** command) and the certificate server handles all CRL requests through SCEP. For larger networks, it is recommended that you use either the database setting “names” or “complete” (as described in the **database level** command) for possible audit and revocation purposes. Depending on the CRL checking policy, you should also use an external CDP in a larger network.

Certificate Server File Storage and Publication Locations

You have the flexibility to store file types to different storage and publication locations.

SUMMARY STEPS

1. **database url** *root-url*
2. **database url** { *cnm* | *crl* | *crt* | *p12* | *pem* | *ser* } *root-url*
3. **database url** { *cnm* | *crl* | *crt* } **publish** *root-url*
4. **database level** { *minimal* | *names* | *complete* }
5. **database username** *username* [**password** *encr-type*] *password*]
6. **database archive** { *pkcs12* | *pem* } [**password** *encr-type*] *password*]
7. **issuer-name** *DN-string*
8. **lifetime** { *ca-certificate* | *certificate* } *time*
9. **lifetime crl** *time*
10. **lifetime enrollment-request** *time*
11. **cdp-url** *url*
12. **no shutdown**

DETAILED STEPS

	Command or Action	Purpose
Step 1	<p>database url <i>root-url</i></p> <p>Example:</p> <pre>Router (cs-server)# database url tftp://cert-svr-db.company.com</pre>	<p>Specifies the primary location where database entries for the certificate server are written.</p> <p>If this command is not specified, all database entries are written to NVRAM.</p>
Step 2	<p>database url { <i>cnm</i> <i>crl</i> <i>crt</i> <i>p12</i> <i>pem</i> <i>ser</i> } <i>root-url</i></p> <p>Example:</p> <pre>Router (cs-server)# database url ser nvram:</pre>	<p>Specifies certificate server critical file storage location by file type.</p> <p>Note If this command is not specified, all critical files are stored to the primary location if specified. If the primary location is not specified, all critical files are stored to NVRAM.</p>
Step 3	<p>database url { <i>cnm</i> <i>crl</i> <i>crt</i> } publish <i>root-url</i></p> <p>Example:</p> <pre>Router (cs-server)# database url crl publish tftp://csdb_specific_crl_files.company.com</pre>	<p>Specifies certificate server publish location by file type.</p> <p>Note If this command is not specified, all publish files are stored to the primary location if specified. If the primary location is not specified, all publish files are stored to NVRAM.</p>

Command or Action	Purpose
<p>Step 4 <code>database level {minimal names complete}</code></p> <p>Example:</p> <pre>Router (cs-server)# database level complete</pre>	<p>Controls what type of data is stored in the certificate enrollment database.</p> <ul style="list-style-type: none"> • minimal --Enough information is stored only to continue issuing new certificates without conflict; the default value. • names --In addition to the information given in the minimal level, the serial number and subject name of each certificate. • complete --In addition to the information given in the minimal and names levels, each issued certificate is written to the database. <p>Note The complete keyword produces a large amount of information; if it is issued, you should also specify an external TFTP server in which to store the data through the database url command.</p>
<p>Step 5 <code>database username <i>username</i> [password [<i>encr-type</i>] <i>password</i>]</code></p> <p>Example:</p> <pre>Router (cs-server)# database username user password PASSWORD</pre>	<p>(Optional) Sets a username and password when a user is required to access a primary certificate enrollment database storage location.</p>
<p>Step 6 <code>database archive {pkcs12 pem}[password <i>encr-type</i>] <i>password</i>]</code></p> <p>Example:</p> <pre>Router (cs-server)# database archive pem</pre>	<p>(Optional) Sets the CA key and CA certificate archive format and password to encrypt the file.</p> <p>The default value is pkcs12, so if this subcommand is not configured, autoarchiving continues, and the PKCS12 format is used.</p> <ul style="list-style-type: none"> • The password is optional. If it is not configured, you are prompted for the password when the server is turned on for the first time. <p>Note It is recommended that you remove the password from the configuration after the archive is finished.</p>
<p>Step 7 <code>issuer-name <i>DN-string</i></code></p> <p>Example:</p> <pre>Router (cs-server)# issuer-name my-server</pre>	<p>(Optional) Sets the CA issuer name to the specified distinguished name (<i>DN-string</i>). The default value is as follows: issuer-name cn={<i>cs-label</i> }.</p>

Command or Action	Purpose
<p>Step 8 <code>lifetime {ca-certificate certificate} time</code></p> <p>Example:</p> <pre>Router (cs-server)# lifetime certificate 888</pre>	<p>(Optional) Specifies the lifetime, in days, of a CA certificate or a certificate.</p> <p>Valid values range from 1 day to 1825 days. The default CA certificate lifetime is 3 years; the default certificate lifetime is 1 year. The maximum certificate lifetime is 1 month less than the lifetime of the CA certificate.</p>
<p>Step 9 <code>lifetime crl time</code></p> <p>Example:</p> <pre>Router (cs-server)# lifetime crl 333</pre>	<p>(Optional) Defines the lifetime, in hours, of the CRL that is used by the certificate server.</p> <p>Maximum lifetime value is 336 hours (2 weeks). The default value is 168 hours (1 week).</p>
<p>Step 10 <code>lifetime enrollment-request time</code></p> <p>Example:</p> <pre>Router (cs-server)# lifetime enrollment-request 888</pre>	<p>(Optional) Specifies how long an enrollment request should stay in the enrollment database before being removed.</p> <p>Maximum lifetime is 1000 hours.</p>
<p>Step 11 <code>cdp-url url</code></p> <p>Example:</p> <pre>Router (cs-server)# cdp-url http://my-cdp.company.com</pre>	<p>(Optional) Defines the CDP location to be used in the certificates that are issued by the certificate server.</p> <ul style="list-style-type: none"> The URL must be an HTTP URL. <p>If you have PKI clients that are not running Cisco IOS software and that do not support a SCEP GetCRL request, use the following URL format:</p> <pre>http://server.company.com/certEnroll/filename.crl</pre> <p>Or, if your Cisco IOS certificate server is also configured as your CDP, use the following URL format</p> <pre>http://cs-addr/cgi-bin/pkiclient.exe?operation=GetCRL</pre> <p>where <i>cs-addr</i> is the location of the certificate server.</p> <p>In order to force the parser to retain the embedded question mark within the specified location, enter Ctrl-v prior to the question mark. If this action is not taken, CRL retrieval through HTTP returns an error message.</p> <p>Note Although this command is optional, it is strongly recommended for any deployment scenario.</p>
<p>Step 12 <code>no shutdown</code></p> <p>Example:</p> <pre>Router (cs-server)# no shutdown</pre>	<p>Enables the certificate server.</p> <p>You should issue this command only after you have completely configured your certificate server.</p>

Examples

The following example shows how to configure a CDP location where the PKI clients do not support SCEP GetCRL requests:

```
Router(config)# crypto pki server aaa
Router(cs-server)# database level minimum
Router(cs-server)# database url tftp://10.1.1.1/username1/
Router(cs-server)# issuer-name CN=aaa

Router(cs-server)# cdp-url http://server.company.com/certEnroll/aaa.crl
```

After a certificate server has been enabled on a router, the `show crypto pki server` command displays the following output:

```
Router# show crypto pki server
Certificate Server status:enabled, configured
Granting mode is:manual
Last certificate issued serial number:0x1
CA certificate expiration timer:19:31:15 PST Nov 17 2006
CRL NextUpdate timer:19:31:15 PST Nov 25 2003
Current storage dir:nvram:
Database Level:Minimum - no cert data written to storage
```

Working with Automatic CA Certificate Rollover

- [Starting Automated CA Certificate Rollover Immediately, page 32](#)
- [Requesting a Certificate Server Client Rollover Certificate, page 33](#)
- [Exporting a CA Rollover Certificate, page 34](#)

Starting Automated CA Certificate Rollover Immediately

Use this task to initiate the automated CA certificate rollover process immediately on your root CA server.

SUMMARY STEPS

1. `enable`
2. `configure terminal`
3. `crypto pki server cs-label rollover cancel]]`

DETAILED STEPS

Command or Action	Purpose
Step 1 <code>enable</code> Example: Router> <code>enable</code>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.

Command or Action	Purpose
Step 2 <code>configure terminal</code> Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3 <code>crypto pki server <i>cs-label</i> rollover cancel []</code> Example: <pre>Router(config)# crypto pki server mycs rollover</pre>	Immediately starts the CA certificate rollover process by generating a shadow CA certificate. To delete the CA certificate rollover certificate and keys, use the cancel keyword.

Requesting a Certificate Server Client Rollover Certificate

Use this task to request a certificate server client's rollover certificate.

SUMMARY STEPS

1. `enable`
2. `configure terminal`
3. `crypto pki server cs-label rollover request pkcs10 terminal`

DETAILED STEPS

Command or Action	Purpose
Step 1 <code>enable</code> Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 <code>configure terminal</code> Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3 <code>crypto pki server <i>cs-label</i> rollover request pkcs10 terminal</code> Example: <pre>Router(config)# crypto pki server mycs rollover request pkcs10 terminal</pre>	Requests a client rollover certificate from the server.

Example

The following example shows a rollover certificate request being inputted into the server:

```
Router# crypto pki server mycs rollover request pkcs10 terminal

% Enter Base64 encoded or PEM formatted PKCS10 enrollment request.
% End with a blank line or "quit" on a line by itself.
-----BEGIN CERTIFICATE REQUEST-----
MIIBUTCBuwIBADASMRAwDgYDVQQDEwdOZXdsb290MIGfMA0GCSqGSIb3DQEBAQUA
A4GNADCBiQKBgQDMHeev1ERSs320zbLQQk+3lhv/R2HpYQ/im6uT1jkJf5iy0UPR
wF/Xl6yUNmG+ObiGiW9fsASF0nxZw+f07d2X2yh1PakfvF2wbP27C/sgJNOw9uPf
sBxEc40Xe0d5FMh0YKOSAShfZYKOflnyQR2Drmm2x/33QGol5QyRvjkeWQIDAQAB
oAAwDQYJKoZIhvcNAQEEBQADgYEALM90r4d79X6vxhd0qjuYJXfBCOvv4FNyFs jr
aBS/y6CnNVYySF8UBUohXYIGTWf4I4+s j6i8gYfoFUW1/L82djs18TLrUr6wpCOs
RqfAfps7HW1e4cizOfjAUU+C71NcobCAhwF1o6q2nIEjPQ/2yfk907sb3SCJZBfe
eW3tyCo=
-----END CERTIFICATE REQUEST-----
```

Exporting a CA Rollover Certificate

Use this task to export a CA rollover certificate.

SUMMARY STEPS

1. enable
2. configure terminal
3. `crypto pki export trustpoint pem {terminal | url url} [rollover]`

DETAILED STEPS

	Command or Action	Purpose
Step 1	<p><code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	<p><code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
Step 3	<p><code>crypto pki export trustpoint pem {terminal url url} [rollover]</code></p> <p>Example:</p> <pre>Router(config)# crypto pki export mycs pem terminal rollover</pre>	<p>Exports a CA shadow certificate.</p>

Maintaining Verifying and Troubleshooting the Certificate Server Certificates and the CA

- [Managing the Enrollment Request Database, page 35](#)
- [Removing Requests from the Enrollment Request Database, page 37](#)
- [Deleting a Certificate Server, page 37](#)
- [Verifying and Troubleshooting Certificate Server and CA Status, page 38](#)
- [Verifying CA Certificate Information, page 39](#)

Managing the Enrollment Request Database

SCEP supports two client authentication mechanisms--manual and preshared key. Manual enrollment requires the administrator at the CA server to specifically authorize the enrollment requests; enrollment using preshared keys allows the administrator to preauthorize enrollment requests by generating a one-time password (OTP).

Use any of the optional steps within this task to help manage the enrollment request database by performing functions such as specifying enrollment processing parameters that are to be used by SCEP and by controlling the run-time behavior or the certificate server.

SUMMARY STEPS

1. **enable**
2. **crypto pki server *cs-label* grant all *req-id***
3. **crypto pki server *cs-label* reject {all *req-id***
4. **crypto pki server *cs-label* password generate *minutes***
5. **crypto pki server *cs-label* revoke *certificate-serial-number***
6. **crypto pki server *cs-label* request pkcs10 {*url* | terminal} [*base64*| pem**
7. **crypto pki server *cs-label* info *crl***
8. **crypto pki server *cs-label* info requests**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 crypto pki server <i>cs-label</i> grant all <i>req-id</i></p> <p>Example:</p> <pre>Router# crypto pki server mycs grant all</pre>	<p>Grants all or specific SCEP requests.</p>

Command or Action	Purpose
<p>Step 3 <code>crypto pki server <i>cs-label</i> reject {all <i>req-id</i>}</code></p> <p>Example:</p> <p>Example:</p> <pre>Router# crypto pki server mycs reject all</pre>	<p>Rejects all or specific SCEP requests.</p>
<p>Step 4 <code>crypto pki server <i>cs-label</i> password generate <i>minutes</i></code></p> <p>Example:</p> <pre>Router# crypto pki server mycs password generate 75</pre>	<p>Generates a OTP for SCEP requests.</p> <ul style="list-style-type: none"> <i>minutes</i> --Length of time, in minutes, that the password is valid. Valid values range from 1 to 1440 minutes. The default is 60 minutes. <p>Note Only one OTP is valid at a time; if a second OTP is generated, the previous OTP is no longer valid.</p>
<p>Step 5 <code>crypto pki server <i>cs-label</i> revoke <i>certificate-serial-number</i></code></p> <p>Example:</p> <pre>Router# crypto pki server mycs revoke 3</pre>	<p>Revokes a certificate on the basis of its serial number.</p> <ul style="list-style-type: none"> <i>certificate-serial-number</i> --One of the following options: <ul style="list-style-type: none"> A string with a leading 0x, which is treated as a hexadecimal value A string with a leading 0 and no x, which is treated as octal All other strings, which are treated as decimal
<p>Step 6 <code>crypto pki server <i>cs-label</i> request pkcs10 {<i>url</i> terminal} [base64] pem</code></p> <p>Example:</p> <pre>Router# crypto pki server mycs request pkcs10 terminal pem</pre>	<p>Manually adds either a base64-encoded or PEM-formatted PKCS10 certificate enrollment request to the request database.</p> <p>After the certificate is granted, it is displayed on the console terminal using base64 encoding.</p> <ul style="list-style-type: none"> pem --Specifies the certificate that is returned with PEM headers automatically added to the certificate after the certificate is granted, regardless of whether PEM headers were used in the request. base64 --Specifies the certificate that is returned without privacy-enhanced mail (PEM) headers, regardless of whether PEM headers were used in the request.
<p>Step 7 <code>crypto pki server <i>cs-label</i> info crl</code></p> <p>Example:</p> <pre>Router# crypto pki server mycs info crl</pre>	<p>Displays information regarding the status of the current CRL.</p>

Command or Action	Purpose
Step 8 <code>crypto pki server <i>cs-label</i> info requests</code> Example: <pre>Router# crypto pki server mycs info requests</pre>	Displays all outstanding certificate enrollment requests.

Removing Requests from the Enrollment Request Database

After the certificate server receives an enrollment request, the server can leave the request in a pending state, reject it, or grant it. The request stays in the enrollment request database for 1 week until the client polls the certificate server for the result of the request. If the client exits and never polls the certificate server, you can remove either individual requests or all requests from the database.

Use this task to remove requests from the database and allow the server to be returned to a clean slate with respect to the keys and transaction IDs. Also, you can use this task to help troubleshoot a SCEP client that may not be behaving properly.

SUMMARY STEPS

1. `enable`
2. `crypto pki server cs-label remove {all | req-id}`

DETAILED STEPS

Command or Action	Purpose
Step 1 <code>enable</code> Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 <code>crypto pki server <i>cs-label</i> remove {all <i>req-id</i>}</code> Example: <pre>Router# crypto pki server mycs remove 15</pre>	Removes enrollment requests from the enrollment request database.

Deleting a Certificate Server

Users can delete a certificate server from the PKI configuration if they no longer want it on the configuration. Typically, a subordinate certificate server or an RA is being deleted. However, users may delete a root certificate server if they are moving it to another device through the archived RSA keys.

Perform this task to delete a certificate server from your PKI configuration.

**Note**

When a certificate server is deleted, the associated trustpoint and key are also deleted.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **no crypto pki server *cs-label***

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: <pre>Router > enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: <pre>Router # configure terminal</pre>	Enters global configuration mode.
Step 3	no crypto pki server <i>cs-label</i> Example: <pre>Router (config)# no crypto pki server mycs</pre>	Deletes a certificate server and associated trustpoint and key.

Verifying and Troubleshooting Certificate Server and CA Status

Use any of the following optional steps to verify the status of the certificate server or the CA.

SUMMARY STEPS

1. **enable**
2. **debug crypto pki server**
3. **dir filesystem :**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 <code>debug crypto pki server</code></p> <p>Example:</p> <pre>Router# debug crypto pki server</pre>	<p>Enables debugging for a crypto PKI certificate server.</p> <ul style="list-style-type: none"> • This command can be used for monitoring the progress of an enrollment and for troubleshooting if the certificate server fails to respond or if the certificate server has trouble handling the request that has been configured.
<p>Step 3 <code>dir filesystem :</code></p> <p>Example:</p> <pre>Router# dir slot0:</pre>	<p>Displays a list of files on a file system.</p> <ul style="list-style-type: none"> • This command can be used to verify the certificate server autoarchived file if the database url command was entered to point to a local file system. You should be able to at least see “<i>cs-label .ser</i>” and “<i>cs-label .crl</i>” files in the database.

Verifying CA Certificate Information

To obtain information relating to the CA certificates including the certificate server rollover process, rollover certificates, and timers, you may use any of the following commands.

**Note**

These commands are not exclusive to shadow certificate information. If no shadow certificate exists, the following commands display the active certificate information.

SUMMARY STEPS

1. The **crypto pki certificate chain** command can be used to view the certificate chain details and to distinguish the current active certificate from the rollover certificate in the certificate chain. The following example shows a certificate chain with an active CA certificate and a shadow, or rollover, certificate:
2. The **crypto pki server info requests** command displays all outstanding certificate enrollment requests. The following example shows the output for shadow PKI certificate information requests:
3. The **show crypto pki certificates** command displays information about your certificate, the certification authority certificate, shadow certificates, and any registration authority certificates. The following example displays the certificate of the router and the certificate of the CA. There is no shadow certificate available. A single, general-purpose RSA key pair was previously generated, and a certificate was requested but not received for that key pair. Note that the certificate status of the router shows “Pending.” After the router receives its certificate from the CA, the Status field changes to “Available” in the **show** output.
4. The **show crypto pki server** command displays the current state and configuration of the certificate server. The following example shows that the certificate server “routercs” has rollover configured. The CA auto-rollover time has occurred and the rollover, or shadow, PKI certificate is available. The status shows the rollover certificate fingerprint and rollover CA certificate expiration timer information.
5. The **show crypto pki trustpoints** command displays the trustpoints that are configured in the router. The following output shows that a shadow CA certificate is available and shows the SCEP capabilities reported during the last enrollment operation:

DETAILED STEPS

Step 1 The **crypto pki certificate chain** command can be used to view the certificate chain details and to distinguish the current active certificate from the rollover certificate in the certificate chain. The following example shows a certificate chain with an active CA certificate and a shadow, or rollover, certificate:

Example:

```
Router(config)# crypto pki certificate chain mica
certificate 06
certificate ca 01
! This is the peer's shadow PKI certificate.
certificate rollover 0B
! This is the CA shadow PKI certificate
certificate rollover ca 0A
```

Step 2 The **crypto pki server info requests** command displays all outstanding certificate enrollment requests. The following example shows the output for shadow PKI certificate information requests:

Example:

```
Router# crypto pki server myca info requests
Enrollment Request Database:
RA certificate requests:
  ReqID  State      Fingerprint                               SubjectName
-----
RA rollover certificate requests:
  ReqID  State      Fingerprint                               SubjectName
-----
Router certificates requests:
```

```

ReqID   State      Fingerprint                               SubjectName
-----
1       pending    A426AF07FE3A4BB69062E0E47198E5BF hostname=client
Router rollover certificates requests:
ReqID   State      Fingerprint                               SubjectName
-----
2       pending    B69062E0E47198E5BFA426AF07FE3A4B hostname=client

```

Step 3

The **show crypto pki certificates** command displays information about your certificate, the certification authority certificate, shadow certificates, and any registration authority certificates. The following example displays the certificate of the router and the certificate of the CA. There is no shadow certificate available. A single, general-purpose RSA key pair was previously generated, and a certificate was requested but not received for that key pair. Note that the certificate status of the router shows “Pending.” After the router receives its certificate from the CA, the Status field changes to “Available” in the **show** output.

Example:

```

Router# show crypto pki certificates
Certificate
  Subject Name
    Name: myrouter.example.com
    IP Address: 192.0.2.1
    Serial Number: 04806682
  Status: Pending
  Key Usage: General Purpose
  Fingerprint: 428125BD A3419600 3F6C7831 6CD8FA95 00000000
CA Certificate
  Status: Available
  Certificate Serial Number: 3051DF7123BEE31B8341DFE4B3A338E5F
  Key Usage: Not Set

```

Step 4

The **show crypto pki server** command displays the current state and configuration of the certificate server. The following example shows that the certificate server “routercs” has rollover configured. The CA auto-rollover time has occurred and the rollover, or shadow, PKI certificate is available. The status shows the rollover certificate fingerprint and rollover CA certificate expiration timer information.

Example:

```

Router# show crypto pki server
Certificate Server routercs:
  Status: enabled, configured
  Issuer name: CN=walnutcs
  CA cert fingerprint: 800F5944 74337E5B C2DF6C52 9A7B1BDB
  Granting mode is: auto
  Last certificate issued serial number: 0x7
  CA certificate expiration timer: 22:10:29 GMT Jan 29 2007
  CRL NextUpdate timer: 21:50:56 GMT Mar 5 2004
  Current storage dir: nvram:
  Database Level: Minimum - no cert data written to storage
  Rollover status: available for rollover
  Rollover CA cert fingerprint: 6AAF5944 74227A5B 23DF3E52 9A7F1FEF
  Rollover CA certificate expiration timer: 22:10:29 GMT Jan 29 2017

```

Step 5

The **show crypto pki trustpoints** command displays the trustpoints that are configured in the router. The following output shows that a shadow CA certificate is available and shows the SCEP capabilities reported during the last enrollment operation:

Example:

```

Router# show crypto pki trustpoints
Trustpoint vpn:

```

```

Subject Name:
cn=Cisco SSL CA
o=Cisco Systems
Serial Number: 0FFEBC1B6F6D9D0EA7875875E4C695
Certificate configured.
Rollover certificate configured.
Enrollment Protocol:
SCEPv1, PKI Rollover

```

Configuration Examples for Using a Certificate Server

Configuring Specific Storage and Publication Locations Examples

The following example shows the configuration of a minimal local file system, so that the certificate server can respond quickly to certificate requests. The .ser and .crl files are stored on the local Cisco IOS file system for fast access, and a copy of all of the .crt files are published to a remote location for long-term logging.

```

crypto pki server myserver
    !Pick your database level.
    database level minimum
    !Specify a location for the .crt files that is different than the default
local    !Cisco IOS file system.
    database url crt publish http://url username user1 password secret

```



Note

Free space on the local file system should be monitored, in case the .crl file becomes too large.

The following example shows the configuration of a primary storage location for critical files, a specific storage location for the critical file serial number file, the main certificate server database file, and a password protected file publication location for the CRL file:

```

Router(config)# crypto pki server mycs
Router(cs-server)# database url ftp://cs-db.company.com

!
% Server database url was changed. You need to move the
% existing database to the new location.
!
Router(cs-server)# database url ser nvram:
Router(cs-server)# database url crt publish ftp://crl.company.com username myname
password mypassword

Router(cs-server)# end

```

The following output displays the specified primary storage location and critical file storage locations specified:

```

Router# show
Sep  3 20:19:34.216: %SYS-5-CONFIG_I: Configured from console by user on console
Router# show crypto pki server
Certificate Server mycs:
  Status: disabled
  Server's configuration is unlocked (enter "no shut" to lock it)
  Issuer name: CN=mycs
  CA cert fingerprint: -Not found-

```

```

Granting mode is: manual
Last certificate issued serial number: 0x0
CA certificate expiration timer: 00:00:00 GMT Jan 1 1970
CRL not present.
Current primary storage dir: ftp://cs-db.company.com
Current storage dir for .ser files: nvram:
Database Level: Minimum - no cert data written to storage
The following output displays all storage and publication locations. The serial number file (.ser) is stored in NVRAM. The CRL file will be published to ftp://crl.company.com with a username and password. All other critical files will be stored to the primary location, ftp://cs-db.company.com.
Router# show running-config

section crypto pki server
crypto pki server mycs shutdown database url ftp://cs-db.company.com
database url crl publish ftp://crl.company.com username myname password 7
12141C0713181F13253920
database url ser nvram:
Router#

```

Removing Enrollment Requests from the Enrollment Request Database Examples

The following examples show both the enrollment requests that are currently in the enrollment request database and the result after one of the enrollment requests has been removed from the database.

Enrollment Request Currently in the Enrollment Request Database

The following example shows that the **crypto pki server info requests** command has been used to display the enrollment requests that are currently in the Enrollment Request Database:

```

Router# crypto pki server myserver info requests
Enrollment Request Database:
RA certificate requests:
ReqID   State   Fingerprint                               SubjectName
-----
Router certificates requests:
ReqID   State   Fingerprint                               SubjectName
-----
2       pending 1B07F3021DAAB0F19F35DA25D01D8567       hostname=host1.company.com
1       denied  5322459D2DC70B3F8EF3D03A795CF636       hostname=host2.company.com

```

crypto pki server remove Command Used to Remove One Enrollment Request

The following example shows that the **crypto pki server remove** command has been used to remove Enrollment Request 1:

```

Router# crypto pki server myserver remove 1

```

Enrollment Request Database After the Removal of One Enrollment Request

The following example shows the result of the removal of Enrollment Request 1 from the Enrollment Request Database:

```

Router# crypto pki server mycs info requests
Enrollment Request Database:
RA certificate requests:
ReqID   State   Fingerprint                               SubjectName
-----
Router certificates requests:
ReqID   State   Fingerprint                               SubjectName
-----
2       pending 1B07F3021DAAB0F19F35DA25D01D8567       hostname=host1.company.com

```

Autoarchiving the Certificate Server Root Keys Examples

The following output configurations and examples show what you might see if the **database archive** command has not been configured (that is, configured using the default value); if the **database archive** command has been configured to set the CA certificate and CA key archive format as PEM, without configuring a password; and if the **database archive** command has been configured to set the CA certificate and CA key archive format as PKCS12, with a password configured. The last example is sample content of a PEM-formatted archive file.

database archive Command Not Configured



Note

The default is PKCS12, and the prompt for the password appears after the **no shutdown** command has been issued.

```
Router (config)# crypto pki server myserver
Router (cs-server)# no shutdown
% Generating 1024 bit RSA keys ...[OK]
% Ready to generate the CA certificate.
%Some server settings cannot be changed after CA certificate generation.
Are you sure you want to do this? [yes/no]: y
% Exporting Certificate Server signing certificate and keys...
! Note the next two lines, which are asking for a password.
% Please enter a passphrase to protect the private key.
Password:
% Certificate Server enabled.
Router (cs-server)# end
Router# dir nvram:
Directory of nvram:/
 125  -rw-          1693          <no date>  startup-config
 126  ----           5          <no date>  private-config
   1  -rw-           32          <no date>  myserver.ser
   2  -rw-          214          <no date>  myserver.crl
! Note the next line, which indicates PKCS12 format.
   3  -rw-          1499          <no date>  myserver.p12
```

database archive Command and pem Keyword Configured



Note

The prompt for the password appears after the **no shutdown** command has been issued.

```
Router (config)# crypto pki server myserver
Router (cs-server)# database archive pem
Router (cs-server)# no shutdown
% Generating 1024 bit RSA keys ...[OK]
% Ready to generate the CA certificate.
%Some server settings cannot be changed after CA certificate generation.
Are you sure you want to do this? [yes/no]: y
% Exporting Certificate Server signing certificate and keys...
!Note the next two lines, which are asking for a password.
% Please enter a passphrase to protect the private key.
Password:
% Certificate Server enabled.
Router (cs-server)# end
Router# dir nvram:
Directory of nvram:/
 125  -rw-          1693          <no date>  startup-config
 126  ----           5          <no date>  private-config
   1  -rw-           32          <no date>  myserver.ser
   2  -rw-          214          <no date>  myserver.crl
```

```
! Note the next line showing that the format is PEM.
3 -rw-          1705          <no date> myserver.pem
```

database archive Command and pkcs12 Keyword (and Password) Configured



Note

When the password is entered, it is encrypted. However, it is recommended that you remove the password from the configuration after the archive has finished.

```
Router (config)# crypto pki server myserver
Router (cs-server)# database archive pkcs12 password cisco123
Router (cs-server)# no shutdown

% Generating 1024 bit RSA keys ...[OK]
% Ready to generate the CA certificate.
% Some server settings cannot be changed after CA certificate generation.
Are you sure you want to do this? [yes/no]: y
% Exporting Certificate Server signing certificate and keys...
! Note that you are not being prompted for a password.
% Certificate Server enabled.
Router (cs-server)# end
Router# dir nvram:
Directory of nvram:/
 125  -rw-          1693          <no date>  startup-config
 126  ----              5          <no date>  private-config
   1  -rw-           32          <no date>  myserver.ser
   2  -rw-          214          <no date>  myserver.crl
! Note that the next line indicates that the format is PKCS12.
   3  -rw-          1499          <no date>  myserver.pl2
```

PEM-Formatted Archive

The following sample output shows that autoarchiving has been configured in PEM file format. The archive consists of the CA certificate and the CA private key. To restore the certificate server using the backup, you would have to import the PEM-formatted CA certificate and CA key individually.



Note

In addition to the CA certificate and CA key archive files, you should also back up the serial file (.ser) and the CRL file (.crl) regularly. The serial file and the CRL file are both critical for CA operation if you need to restore your certificate server.

```
Router# more nvram:mycs.pem
-----BEGIN CERTIFICATE-----
MIIB9zCCAACgAwIBAgIBATANBgkqhkiG9w0BAQQFADAPMQ0wCwYDVQQDEwRteWNz
MB4XDTA0MDgyNzAyMzI0NloXDTA3MDgyNzAyMzI0NlowDzENMAsGAlUEAxMEbXlj
czCBnzANBgkqhkiG9w0BAQEFAAOBjQAwgYkCgYEA11ZpKP4nGDJHgPkpYSkix71D
nr23aMlZ9Kz5oo/qTBxeZ8mu j p j YcZ0T8AZvoOiCuDnYM1796ZwpkMg j z1aZzBL+
BtuVvllsEOfhC+u/Ol/vxfGG5xpshoz/F5J3xdg5ZZuWWuIDAUYu9+QbI5feuG04
Z/BiPIb4AmGTP4B2MM0CAwEAAnjMGEwDwYDVR0TAAQ/BAUwAwEB/zAOBgNVHQ8B
Af8EBAMCAYYwHwYDVR0jBBgwFoAUKi/cuK6wkz+ZswVtb06vUJboEeEwHQYDVR0O
BBYEFcov3LiusJM/mbMFbW9Or1CW6BHhMA0GCSqGSIb3DQEBAUAA4GBAKLOmoE2
4+NeOEXMCXG1jcohK702HrkFfl/vpK0+q92PTnMUFhxL0qI8pWIq5CCgC7heace
OrTv2zcUAoH4rzx3Rc2USIxkDokWWQMLujsMm/SLIeHit0G5uj/GCcbgK20MAW6
ymf7+Tmb1SFljWzstoUXC2hLnsJIMq/Kffad
-----END CERTIFICATE-----
```

```
!The private key is protected by the password that is
configured in "database archive pem password pwd" or that
is entered when you are prompted for the password.
```

```
-----BEGIN RSA PRIVATE KEY-----
Proc-Type: 4,ENCRYPTED
DEK-Info: DES-EDE3-CBC,106CE91FFD0A075E
```

```

zyiFC8rKv8Cs+IKsQG2QpsVpvDBHqZqBSM4D528bvZv7jzr6WuHj8E6zO+6G8R/A
zjsfTALo+e+ZDg7KMzbrYHARvjskbqFdOML1VIYBhCeSELKsskWB6chOuyPHJInW
JwC5YzZdZwOqcyLBP/xOYXcvjzZnFpAXZzN12VR8vWDNq/kHT+3Lplc8hY++ABMI
M+C9FB3dpNZzu501BZCJg46bqbkulaCCmScIDaVt0zDFZwWTSufiemmNxZBG4xS8
t5t+FEhmSfv8DAmwg4f/KVRFtm10phUarcLxQ038A10W5YHHORdACnuzVUvHgco7
VT4XUTjO7qMhmJgFNWylpu49fbdS2NnOn5IoIyAq51klKUPrz/WABWiCvLMy1GnZ
kyMCWoaMtgS/vdx74BBCj09yRZJnLMLi6SDofjCNTDHFmFEVg4LsSWCd41P9OP8
0MqhP1D5VIx6PbMNwkWWL2lpBbCCdesFRGHjZD2dOu96kHD7ItErX34CC8W04aG4
b7DLktUu6WNv6M8g3CAqJiC0V8ATlp+kvdHZVkXovgND5IU00Jpsj0HhGzKAGpOY
KTGTUekUboISjvVvKI6efp1vO6temVL3Txg3KGhzWMJGrq1snghE0KnV8tkddv/9N
d/t1l+we9mrccTq50WNDnkEi/cwHI/0PKXg+NDNH3k3QGpAprsqGQmMPdqc5ut0P
86i4cF9078QwWg4Tpay3uqNH1Zz6UN0tcarVVNmDupFESUxYw10qJrrEYVRadu74
rKAU4Ey4xkAftB2kuqvr21Av/L+jne4kkGIoZYdB+p/M98pQRgkYy==
-----END RSA PRIVATE KEY-----

```

Restoring a Certificate Server from Certificate Server Backup Files Examples

The following example shows that restoration is from a PKCS12 archive and that the database URL is NVRAM (the default).

```

Router# copy tftp://192.0.2.71/backup.ser nvram:myscs.ser
Destination filename [myscs.ser]?

32 bytes copied in 1.320 secs (24 bytes/sec)
Router# copy tftp://192.0.2.71/backup.crl nvram:myscs.crl
Destination filename [myscs.crl]?

214 bytes copied in 1.324 secs (162 bytes/sec)
Router# configure terminal
Router (config)# crypto pki import myscs pkcs12 tftp://192.0.2.71/backup.p12 cisco123
Source filename [backup.p12]?
CRYPTO_PKI: Imported PKCS12 file successfully.
Router (config)# crypto pki server myscs
! fill in any certificate server configuration here
Router (cs-server)# no shutdown
% Certificate Server enabled.
Router (cs-server)# end
Router# show crypto pki server

Certificate Server myscs:
  Status: enabled
  Server's current state: enabled
  Issuer name: CN=myscs
  CA cert fingerprint: 34885330 B13EAD45 196DA461 B43E813F
  Granting mode is: manual
  Last certificate issued serial number: 0x1
  CA certificate expiration timer: 01:49:13 GMT Aug 28 2007
  CRL NextUpdate timer: 01:49:16 GMT Sep 4 2004
  Current storage dir: nvram:
  Database Level: Minimum - no cert data written to storage

```

The following example shows that restoration is from a PEM archive and that the database URL is flash:

```

Router# copy tftp://192.0.2.71/backup.ser flash:myscs.ser
Destination filename [myscs.ser]?
32 bytes copied in 1.320 secs (24 bytes/sec)
Router# copy tftp://192.0.2.71/backup.crl flash:myscs.crl
Destination filename [myscs.crl]?
214 bytes copied in 1.324 secs (162 bytes/sec)
Router# configure terminal
! Because CA cert has Digital Signature usage, you need to import using the "usage-keys"
keyword
Router (config)# crypto ca import myscs pem usage-keys terminal cisco123
% Enter PEM-formatted CA certificate.
% End with a blank line or "quit" on a line by itself.
! Paste the CA cert from .pem archive.
-----BEGIN CERTIFICATE-----
MIIB9zCCAWCgAwIBAgIBATANBgkqhkiG9w0BAQQFADAPMQ0wCwYDVQQDEwRteWNz

```

```

MB4XDTA0MDkwmjIxMDI1NloXDTA3MDkwmjIxMDI1NlowDzENMASGA1UEAxMEbXlJ
czcBnzANBkgqhkiG9w0BAQEFAAOBjQAwGyKCGYEAuGnnDXJbDDQwCuKGS5Zg2rc
K7ZJauSUotTmWYQvNx+ZmWrUs5/j9Ee5FV2YonirGBQ9mc6ul63kNlrIPFck062L
GpahBhNmKDgodlo2PHTnRlZpEZNDIqU2D3hACgByxpjrY4vUnccV36ewLnQnYpp8
szEu7PYTJr5dU5ltAekCAwEAAAnjMGEwDwYDVR0TAQH/BAUwAwEB/zAObgNVHQ8B
Af8EBAMCAYYwHwYDVR0jBBgwFoAUaEEQwYKQC1dm9+wLYBKRTlzxADIWHQYDVR0
BBYEFghBEMGCgkNXZvfsC2ASKU5c8WgyMA0GCSqGSIB3DQEBBAUAA4GBAHyhiV2C
mH+vswkBJRAlFzZk8ttu9s5kwqG0dXp25QRUWsGlr9nsKPNdVKt3P7p0A/KochHe
eNiygiv+hDQ3FVnzsNv9831e605jvAPxc17R01BbfNhgqEWMsXdnjH0cUy7XerCo
+bdPcUf/eCiZueH/BEy/SzhD7yovzn2cdzBN
-----END CERTIFICATE-----
% Enter PEM-formatted encrypted private SIGNATURE key.
% End with "quit" on a line by itself.
! Paste the CA private key from .pem archive.
-----BEGIN RSA PRIVATE KEY-----
Proc-Type: 4, ENCRYPTED
DEK-Info: DES-EDE3-CBC, 5053DC842B04612A

1cNlF5Pqvd0zp2NLZ7iosxzTy6nDeXppNyJpxB5q+V29IuY8App6TlJCU7YrsEB/
nBTK7K76DCeGpLlpcuyEI171QmkQJ2gA0QhC0LrRo09WrINVH+b4So/y7nffzKvB
p2yDpZwqoJ8cmRH94Tie0YmzBtEh6ayOud11z53qbrsCnfSEwszt1xrWlMKrFZrk
/fTy6loHzGFz13BDj4r5gBecExwcPp74ldHO+Ld4Nc9egG8BYkeBCsZQOQNVhXLN
I0tOD0s6hP915zb6OrZFYv0NK6grTBO9D8hjNZ3U79jJzssP7UNzIYHNTzRjAiYu
i56Oy/iHvkCSNUIK6zeIJQnW4bSoM1BqrbVPwHU6QaXUqlNzZ8SDtw7ZRZ/rHuiD
RTJMPbKquAzeuBss11320aAUJRStjPXgyZTUbc+cWb6zATNws2yi jPDR6sRHoQL
47wHM2Yj80VZGgkCSLakL88ACz9TfUivFhtfl6xMC2yuFl+WRklXfF5VtWe5Zer
3Fn1DcBmlF7086XUkiSHP4EV0cI6n5ZMzVLx0XAUtdAllgD94ylV+6p9PcQHLYQA
pGRmj5i1SFw90aLafgCTbRbmC0ChIqHy91UFalub0130+yu7LsLGRlPmJ9NE61JR
bjRh1UXItRYWY7C4M3m/0wz6fmVQNSumJM08RHg61UB3olZlgGIZ1ZkoaESrLG0p
qq2AENFemCPF0uhyVS2humMHjWuRr+jedfc/IM17sLEgAdqCVCfV3RZVEaNXBud1
4QjkuTrwaTcrXVFbtrVioT/puyVULpA7+k7w+F5TZwUV08mwvUEqDw==
-----END RSA PRIVATE KEY-----
quit
% Enter PEM-formatted SIGNATURE certificate.
% End with a blank line or "quit" on a line by itself.
! Paste the CA cert from .pem archive again.
-----BEGIN CERTIFICATE-----
MIIB9zCCAACgAwIBAgIBATANBgkqhkiG9w0BAQQFADAPMQ0wCwYDVQQDEwRteWNz
MB4XDTA0MDkwmjIxMDI1NloXDTA3MDkwmjIxMDI1NlowDzENMASGA1UEAxMEbXlJ
czcBnzANBkgqhkiG9w0BAQEFAAOBjQAwGyKCGYEAuGnnDXJbDDQwCuKGS5Zg2rc
K7ZJauSUotTmWYQvNx+ZmWrUs5/j9Ee5FV2YonirGBQ9mc6ul63kNlrIPFck062L
GpahBhNmKDgodlo2PHTnRlZpEZNDIqU2D3hACgByxpjrY4vUnccV36ewLnQnYpp8
szEu7PYTJr5dU5ltAekCAwEAAAnjMGEwDwYDVR0TAQH/BAUwAwEB/zAObgNVHQ8B
Af8EBAMCAYYwHwYDVR0jBBgwFoAUaEEQwYKQC1dm9+wLYBKRTlzxADIWHQYDVR0
BBYEFghBEMGCgkNXZvfsC2ASKU5c8WgyMA0GCSqGSIB3DQEBBAUAA4GBAHyhiV2C
mH+vswkBJRAlFzZk8ttu9s5kwqG0dXp25QRUWsGlr9nsKPNdVKt3P7p0A/KochHe
eNiygiv+hDQ3FVnzsNv9831e605jvAPxc17R01BbfNhgqEWMsXdnjH0cUy7XerCo
+bdPcUf/eCiZueH/BEy/SzhD7yovzn2cdzBN
-----END CERTIFICATE-----

% Enter PEM-formatted encrypted private ENCRYPTION key.
% End with "quit" on a line by itself.
! Because the CA cert only has Digital Signature usage, skip the encryption part.
quit
% PEM files import succeeded.
Router (config)# crypto pki server mycs
Router (cs-server)# database url flash:
! Fill in any certificate server configuration here.
Router (cs-server)# no shutdown
% Certificate Server enabled.
Router (cs-server)# end
Router # show crypto pki server
Certificate Server mycs:
  Status: enabled
  Server's current state: enabled
  Issuer name: CN=mycs
  CA cert fingerprint: F04C2B75 E0243FBC 19806219 B1D77412
  Granting mode is: manual
  Last certificate issued serial number: 0x2
  CA certificate expiration timer: 21:02:55 GMT Sep 2 2007
  CRL NextUpdate timer: 21:02:58 GMT Sep 9 2004
  Current storage dir: flash:
  Database Level: Minimum - no cert data written to storage

```

Subordinate Certificate Server Example

The following configuration and output is typical of what you might see after configuring a subordinate certificate server:

```

Router (config)# crypto pki trustpoint sub
Router (ca-trustpoint)# enrollment url http://192.0.2.6
Router (ca-trustpoint)# exit
Router (config)# crypto pki server sub
Router (cs-server)# mode sub-cs
Router (ca-server)# no shutdown
%Some server settings cannot be changed after CA certificate generation.
% Please enter a passphrase to protect the private key
% or type Return to exit
Password:
Jan 6 22:32:22.698: CRYPTO_CS: enter FSM: input state initial, input signal no shut
Re-enter password:
% Generating 1024 bit RSA keys ...
Jan 6 22:32:30.302: CRYPTO_CS: starting enabling checks
Jan 6 22:32:30.306: CRYPTO_CS: key 'sub' does not exist; generated automatically [OK]
Jan 6 22:32:39.810: %SSH-5-ENABLED: SSH 1.99 has been enabled
Certificate has the following attributes:
    Fingerprint MD5: 328ACC02 52B25DB8 22F8F104 B6055B5B
    Fingerprint SHA1: 02FD799D DD40C7A8 61DC53AB 1E89A3EA 2A729EE2
% Do you accept this certificate? [yes/no]:
Jan 6 22:32:44.830: CRYPTO_CS: nvram filesystem
Jan 6 22:32:44.922: CRYPTO_CS: serial number 0x1 written.
Jan 6 22:32:46.798: CRYPTO_CS: created a new serial file.
Jan 6 22:32:46.798: CRYPTO_CS: authenticating the CA 'sub'y
Trustpoint CA certificate accepted.%
% Certificate request sent to Certificate Authority
% Enrollment in progress...
Router (cs-server)#
Jan 6 22:33:30.562: CRYPTO_CS: Publishing 213 bytes to crl file nvram:sub.crl
Jan 6 22:33:32.450: CRYPTO_CS: enrolling the server's trustpoint 'sub'
Jan 6 22:33:32.454: CRYPTO_CS: exit FSM: new state check failed
Jan 6 22:33:32.454: CRYPTO_CS: cs config has been locked
Jan 6 22:33:33.118: CRYPTO_PKI: Certificate Request Fingerprint MD5: CED89E5F 53B9C60E
> AA123413 CDDAD964
Jan 6 22:33:33.118: CRYPTO_PKI: Certificate Request Fingerprint SHA1: 70787C76 ACD7E67F
7D2C8B23 98CB10E7 718E84B1
% Exporting Certificate Server signing certificate and keys...
Jan 6 22:34:53.839: %PKI-6-CERTRET: Certificate received from Certificate Authority
Jan 6 22:34:53.843: CRYPTO_CS: enter FSM: input state check failed, input signal cert
configured
Jan 6 22:34:53.843: CRYPTO_CS: starting enabling checks
Jan 6 22:34:53.843: CRYPTO_CS: nvram filesystem
Jan 6 22:34:53.883: CRYPTO_CS: found existing serial file.
Jan 6 22:34:53.907: CRYPTO_CS: old router cert flag 0x4
Jan 6 22:34:53.907: CRYPTO_CS: new router cert flag 0x44
Jan 6 22:34:56.511: CRYPTO_CS: DB version
Jan 6 22:34:56.511: CRYPTO_CS: last issued serial number is 0x1
Jan 6 22:34:56.551: CRYPTO_CS: CRL file sub.crl exists.
Jan 6 22:34:56.551: CRYPTO_CS: Read 213 bytes from crl file sub.crl.
Jan 6 22:34:56.603: CRYPTO_CS: SCEP server started
Jan 6 22:34:56.603: CRYPTO_CS: exit FSM: new state enabled
Jan 6 22:34:56.603: CRYPTO_CS: cs config has been locked
Jan 6 22:35:02.359: CRYPTO_CS: enter FSM: input state enabled, input signal time set
Jan 6 22:35:02.359: CRYPTO_CS: exit FSM: new state enabled
Jan 6 22:35:02.359: CRYPTO_CS: cs config has been locked

```

Root Certificate Server Differentiation Example

When issuing certificates, the root certificate server (or parent subordinate certificate server) differentiates the certificate request from “Sub CA,” “RA,” and peer requests, as shown in the following sample output:

```

Router# crypto pki server server1 info req

```

```

Enrollment Request Database:
RA certificate requests:
ReqID      State      Fingerprint                               SubjectName
-----
Subordinate CS certificate requests:
ReqID      State      Fingerprint                               SubjectName
-----
1          pending    CB9977AD8A73B146D3221749999B0F66        hostname=host-subcs.company.com
RA certificate requests:
ReqID      State      Fingerprint                               SubjectName
-----
Router certificate requests:
ReqID      State      Fingerprint                               SubjectName
-----

```

Show Output for a Subordinate Certificate Server Example

The following **show crypto pki server** command output indicates that a subordinate certificate server has been configured:

```

Router# show crypto pki server
Certificate Server sub:
  Status: enabled
  Server's configuration is locked (enter "shut" to unlock it)
  Issuer name: CN=sub
  CA cert fingerprint: 11B586EE 3B354F33 14A25DDD 7BD39187
  Server configured in subordinate server mode
  Upper CA cert fingerprint: 328ACC02 52B25DB8 22F8F104 B6055B5B
  Granting mode is: manual
  Last certificate issued serial number: 0x1
  CA certificate expiration timer: 22:33:44 GMT Jan 6 2006
  CRL NextUpdate timer: 22:33:29 GMT Jan 13 2005
  Current storage dir: nvram:
  Database Level: Minimum - no cert data written to storage

```

RA Mode Certificate Server Example

The following output is typical of what you might see after having configured an RA mode certificate server:

```

Router-ra (config)# crypto pki trustpoint myra
Router-ra (ca-trustpoint)# enrollment url http://192.0.2.17
! Include "cn=ioscs RA" or "ou=ioscs RA" in the subject-name.
Router-ra (ca-trustpoint)# subject-name cn=myra, ou=ioscs RA, o=company, c=us
Router-ra (ca-trustpoint)# exit
Router-ra (config)# crypto pki server myra
Router-ra (cs-server)# mode ra
Router-ra (cs-server)# no shutdown
% Generating 1024 bit RSA keys ...[OK]
Certificate has the following attributes:
Fingerprint MD5: 32661452 0DDA3CE5 8723B469 09AB9E85
Fingerprint SHA1: 9785BBED 6C67D27C C950E8D0 718C7A14 C0FE9C38
% Do you accept this certificate? [yes/no]: yes
Trustpoint CA certificate accepted.
% Ready to request the CA certificate.
%Some server settings cannot be changed after the CA certificate has been requested.
Are you sure you want to do this? [yes/no]: yes
%
% Start certificate enrollment ..
% Create a challenge password. You will need to verbally provide this
password to the CA administrator in order to revoke your certificate.
For security reasons your password will not be saved in the configuration.
Please make a note of it.
Password:
Re-enter password:
% The subject name in the certificate will include: cn=myra, ou=ioscs RA, o=company, c=us
% The subject name in the certificate will include: Router-ra.company.com
% Include the router serial number in the subject name? [yes/no]: no

```

```

% Include an IP address in the subject name? [no]: no
Request certificate from CA? [yes/no]: yes
% Certificate request sent to Certificate Authority
% The certificate request fingerprint will be displayed.
% The 'show crypto pki certificate' command will also show the fingerprint.
% Enrollment in progress...
Router-ra (cs-server)#
Sep 15 22:32:40.197: CRYPTO_PKI: Certificate Request Fingerprint MD5: 82B41A76 AF4EC87D
AAF093CD 07747D3A
Sep 15 22:32:40.201: CRYPTO_PKI: Certificate Request Fingerprint SHA1: 897CDF40 C6563EAA
0FED05F7 0115FD3A 4FFC5231
Sep 15 22:34:00.366: %PKI-6-CERTRET: Certificate received from Certificate Authority
Router-ra (cs-server)#
Router-ra(cs-server)# end
Router-ra# show crypto pki server
Certificate Server myra:
  Status: enabled
  Issuer name: CN=myra
  CA cert fingerprint: 32661452 0DDA3CE5 8723B469 09AB9E85
  ! Note that the certificate server is running in RA mode
  Server configured in RA mode
  RA cert fingerprint: C65F5724 0E63B3CC BE7AE016 BE0D34FE
  Granting mode is: manual
  Current storage dir: nvram
  Database Level: Minimum - no cert data written to storage

```

The following output shows the enrollment request database of the issuing certificate server after the RA has been enabled:



Note

The RA certificate request is recognized by the issuing certificate server because "ou=ioscs RA" is listed in the subject name.

```

Router-ca# crypto pki server mycs info request
Enrollment Request Database:
Subordinate CA certificate requests:
ReqID  State      Fingerprint                               SubjectName
-----
! The request is identified as RA certificate request.
RA certificate requests:
ReqID  State      Fingerprint                               SubjectName
-----
12     pending   88F547A407FA0C90F97CDE8900A30CB0
hostname=Router-ra.company.com,cn=myra,ou=ioscs RA,o=company,c=us
Router certificates requests:
ReqID  State      Fingerprint                               SubjectName
-----
! Issue the RA certificate.
Router-ca# crypto pki server mycs grant 12

```

The following output shows that the issuing certificate server is configured to issue a certificate automatically if the request comes from an RA:

```

Router-ca(config)# crypto pki server mycs
Router-ca (cs-server)# grant ra-auto

% This will cause all certificate requests already authorized by known RAs to be
automatically granted.
Are you sure you want to do this? [yes/no]: yes
Router-ca (cs-server)# end
Router-ca# show crypto pki server
Certificate Server mycs:
  Status: enabled
  Server's current state: enabled
  Issuer name: CN=mycs
  CA cert fingerprint: 32661452 0DDA3CE5 8723B469 09AB9E85
  ! Note that the certificate server will issue certificate for requests from the RA.
  Granting mode is: auto for RA-authorized requests, manual otherwise
  Last certificate issued serial number: 0x2

```

```

CA certificate expiration timer: 22:29:37 GMT Sep 15 2007
CRL NextUpdate timer: 22:29:39 GMT Sep 22 2004
Current storage dir: nvram:
Database Level: Minimum - no cert data written to storage

```

The following example shows the configuration of “myra”, an RA server, configured to support automatic rollover from “myca”, the CA. After the RA server is configured, automatic granting of certificate reenrollment requests is enabled:

```

crypto pki trustpoint myra
  enrollment url
  http://myca
  subject-name ou=iosca RA
  rsakeypair myra
crypto pki server myra
  mode ra
  auto-rollover
crypto pki server mycs
  grant auto rollover ra-cert
  auto-rollover 25

```

Enabling CA Certificate Rollover to Start Immediately Example

The following example shows how to enable automated CA certificate rollover on the server mycs with the **crypto pki server** command. The **show crypto pki server** command then shows the current state of the mycs server and that the rollover certificate is currently available for rollover.

```

Router(config)# crypto pki server mycs rollover
Jun 20 23:51:21.211:%PKI-4-NOSHADOWAUTOSAVE:Configuration was
modified. Issue "write memory" to save new IOS CA certificate
! The config has not been automatically saved because the config has been changed.
Router# show crypto pki server
Certificate Server mycs:
  Status:enabled
  Server's configuration is locked (enter "shut" to unlock it)
  Issuer name:CN=mycs
  CA cert fingerprint:E7A5FABA 5D7AA26C F2A9F7B3 03CE229A
  Granting mode is:manual
  Last certificate issued serial number:0x2
  CA certificate expiration timer:00:49:26 PDT Jun 20 2008
  CRL NextUpdate timer:00:49:29 PDT Jun 28 2005
  Current storage dir:nvram:
  Database Level:Minimum - no cert data written to storage
  Rollover status:available for rollover
  ! Rollover certificate is available for rollover.
  Rollover CA certificate fingerprint:9BD7A443 00A6DD74 E4D9ED5F B7931BE0
  Rollover CA certificate expiration time:00:49:26 PDT Jun 20 2011
  Auto-Rollover configured, overlap period 25 days

```

Where to Go Next

After the certificate server is successfully running, you can either begin enrolling clients through manual mechanisms (as explained in the module “Configuring Certificate Enrollment for a PKI”) or begin configuring SDP, which is a web-based enrollment interface, (as explained in the module “Setting Up Secure Device Provisioning (SDP) for Enrollment in a PKI.”)

Additional References

Related Documents

Related Topic	Document Title
Cisco IOS commands	Cisco IOS Master Commands List, All Releases
PKI and security commands	Cisco IOS Security Command Reference
USB Token RSA Operations: Using the RSA keys on a USB token for initial autoenrollment	“Configuring Certificate Enrollment for a PKI” chapter in the Cisco IOS Security Configuration Guide: Secure Connectivity. See the “ Configuring Certificate Servers, page 14 ” section.
USB Token RSA Operations: Benefits of using USB tokens	“Storing PKI Credentials ” module in the Cisco IOS Security Configuration Guide: Secure Connectivity.
Certificate server client certificate enrollment, autoenrollment, and automatic rollover	“Configuring Certificate Enrollment for a PKI ” module in the Cisco IOS Security Configuration Guide: <i>Secure Connectivity</i> .
Setting up and logging into a USB token	“Storing PKI Credentials ” module in the Cisco IOS Security Configuration Guide: Secure Connectivity.
Web-based certificate enrollment	“ Setting Up Secure Device Provisioning (SDP) for Enrollment in a PKI ” module in the Cisco IOS Security Configuration Guide: <i>Secure Connectivity</i> .
RSA keys in PEM formatted files	“Deploying RSA Keys Within a PKI ” module in the Cisco IOS Security Configuration Guide: Secure Connectivity.
Choosing a certificate revocation mechanism	“Configuring Authorization and Revocation of Certificates in a PKI ” module in the Cisco IOS Security Configuration Guide: Secure Connectivity.
Recommended cryptographic algorithms	Next Generation Encryption

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for the Cisco IOS Certificate Server

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 4 Feature Information for the Cisco IOS Certificate Server

Feature Name	Releases	Feature Information
Cisco IOS USB Token PKI Enhancements-- Phase 2	12.4(11)T	<p>This feature enhances USB token functionality by using the USB token as a cryptographic device. USB tokens may be used for RSA operations such as key generation, signing, and authentication.</p> <p>The following sections in this document provide information about this feature:</p> <ul style="list-style-type: none"> • RSA Key Pair and Certificate of the Certificate Server, page 3 • Trustpoint of the Certificate Server, page 6 • Generating a Certificate Server RSA Key Pair, page 11 <p>Note This document covers the use of using USB tokens for RSA operations during certificate server configuration.</p>
IOS Certificate Server (CS) Split Database	12.4(4)T	<p>This feature allows the user to set storage locations and publish locations for specific certificate server file types.</p> <p>The following sections provide information about this feature:</p> <p>The following command was modified by this feature:</p> <p>database url</p>

Feature Name	Releases	Feature Information
Subordinate/RA Mode IOS Certificate Server (CS) Rollover	12.4(4)T	<p>This feature expands on Certificate Authority (CA) Key Rollover introduced in 12.4(2)T to allow CA certificate rollover for subordinate CAs and RA-mode CAs. This functionality allows the rollover expiring CA certificates and keys and to have these changes propagate through the PKI network without manual intervention.</p> <p>The following sections provide information about this feature:</p> <p>The following command was modified by this feature: grant auto rollover</p>
Certificate Authority (CA) Key Rollover	12.4(2)T	<p>This feature introduces the ability for root or subordinate CAs to roll over expiring CA certificates and keys and to have these changes propagate through the PKI network without manual intervention.</p> <p>The following sections provide information about this feature:</p> <p>The following commands were introduced or modified by this feature: auto-rollover, crypto pki certificate chain, crypto pki export pem, crypto pki server info request, crypto pki server, show crypto pki certificates, show crypto pki server, and show crypto pki trustpoint</p>
Cisco IOS Certificate Server	12.3(8)T	<p>This feature introduces support for the Cisco IOS certificate server, which offers users a CA that is directly integrated with Cisco IOS software to more easily deploy basic PKI networks.</p> <p>The following sections provide information about this feature:</p>

Feature Name	Releases	Feature Information
The Certificate Server Auto Archive Enhancement ¹	12.3(11)T	<p>This enhancement enables the CA certificate and CA key to be backed up automatically just once after they are generated by the certificate server. As a result, it is not necessary to generate an exportable CA key if CA backup is desirable.</p> <p>The following sections provide information about this feature:</p> <p>The following commands were introduced by this feature: crypto pki server remote, database archive</p>
The Certificate Server Registration Authority (RA) Mode enhancement	12.3(7)T	<p>A certificate server can be configured to run in RA mode.</p> <p>The following section provides information about this feature:</p> <p>The following commands were introduced by this feature: grant ra-auto, lifetime enrollment-requests</p>
PKI Status 1	12.3(11)T	<p>This enhancement provides a quick snapshot of current trustpoint status.</p> <p>The following section provides information about this enhancement:</p> <p>The following command was modified by this enhancement : show crypto pki trustpoints</p>

¹ This is a minor enhancement. Minor enhancements are not typically listed in Feature Navigator.

Feature Name	Releases	Feature Information
Subordinate Certificate Server 1	12.3(14)T	<p>This enhancement allows you to configure a subordinate certificate server to grant all or certain SCEP or manual certificate requests.</p> <p>The following section provides information about this enhancement:</p> <p>The following command was introduced by this enhancement : mode sub-cs</p>
RSA 4096-bit Key Generation in Software Crypto Engine Support	15.1(1)T	<p>The range value for the modulus keyword value for the crypto key generate rsa command is extended from 360 to 2048 bits to 360 to 4096 bits.</p>
IOS PKI Server RA Mode Support for Non-IOS CA Servers	15.1(2)T	<p>This enhancement allows the IOS CA server in RA mode to interoperate with more than one type of CA server.</p> <p>The following section provides information about this feature:</p> <p>The transparent keyword was added to the mode ra command to allow the CA server in RA mode to interoperate with more than one type of CA server.</p>
Public Key Infrastructure (PKI) IPv6 Support for VPN Solutions	15.2(1)T	<p>The enrollment url (ca-trustpoint) command was modified to allow the specification of an IPv6 address in the URL for the CA.</p>

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2012 Cisco Systems, Inc. All rights reserved.