



Fast Convergence Default Optimize

The fast convergence default optimize feature modifies the default settings of all the protocols to recommended defaults for fast convergence.

- [Information About Fast Convergence Default Optimize, on page 1](#)
- [Default Optimize Values for IS-IS, on page 2](#)
- [Default Optimize Values for OSPF, on page 2](#)
- [Additional References for Fast Convergence Default Optimize, on page 4](#)
- [Feature Information for Fast Convergence Default Optimize, on page 4](#)

Information About Fast Convergence Default Optimize

The fast convergence default optimize feature modifies the default settings of all the protocols to recommended defaults for fast convergence. To revert the defaults to pre-fast-convergence settings for both IS-IS and OSPF, **no routing-default-optimize** command is used. This command sends signals to IS-IS and OSPF and modifies the default configuration for these protocols.

By default, the fast convergence settings is enabled which means when you upgrade the software, you can automatically see the new behavior. This makes easier integration of the devices in a multi-vendor deployment and reduces support cases for poor convergence.

When default optimize is disabled, existing protocol default configuration is used. When default optimize is enabled, new protocol defaults are used. The show running configurations does not display configuration lines for default settings even when default settings are being used.

A configuration of a protocol overrides the default, but a change to default optimize does not override any configuration.

The following is the sample output of **spf-interval** command in IS-IS:

```
Device(config-if)# router isis
Device(config-router)# spf-interval 10 5500 5500
```

If a non-default value is configured, it will be displayed in show running configuration output:

```
Device(config-router)# spf-interval 5 50 200
Device(config-router)# do show run | inc spf-interval
spf-interval 5 50 200
```

You can revert to the default values by configuring the default values or by removing the non-default configuration.

Default Optimize Values for IS-IS

The following table summarizes the configuration impacted by default optimize:

| IS-IS command | Parameters | Default optimize disabled | Default optimize enabled |
|-----------------------|-----------------------------|---------------------------|--------------------------|
| fast-flood | | | |
| | # of lsps flooded back-back | Disabled | 10 |
| spf-interval | | | |
| | Initial (milliseconds) | 5500 | 50 |
| | Secondary (milliseconds) | 5500 | 200 |
| | max (seconds) | 10 | 5 |
| prc-interval | | | |
| | Initial (milliseconds) | 2000 | 50 |
| | Secondary (milliseconds) | 5000 | 200 |
| | max (seconds) | 5 | 5 |
| lsp-gen-interval | | | |
| | Initial (milliseconds) | 50 | 50 |
| | Secondary (milliseconds) | 5000 | 200 |
| | max (seconds) | 5 | 5 |
| log-adjacency-changes | | disabled | enabled |

Default Optimize Values for OSPF

The following table summarizes the configuration impacted by default optimize for OSPFv2/v3:

| OSPF command | Parameters | Default optimize disabled | Default optimize enabled |
|---------------------|--------------------------|---------------------------|--------------------------|
| timers throttle spf | | | |
| | Initial (milliseconds) | 5000 | 50 |
| | Secondary (milliseconds) | 10000 | 200 |

| OSPF command | Parameters | Default optimize disabled | Default optimize enabled |
|-------------------------|--------------------------|---------------------------|--------------------------|
| | max (milliseconds) | 10 | 5 |
| timers throttle lsa all | | | |
| | Initial (milliseconds) | 0 | 50 |
| | Secondary (milliseconds) | 5000 | 200 |
| | max (milliseconds) | 5 | 5 |
| timers lsa arrival | | | |
| | milliseconds | 1000 | 100 |

The following is the sample output of **show ip ospf** command for OSPFv2 with the default-optimize values.

```

Device# show ip ospf
Routing Process "ospf 10" with ID 1.1.1.1
Start time: 00:00:01.471, Time elapsed: 03:00:34.706
Supports only single TOS(TOS0) routes
Supports opaque LSA
Supports Link-local Signaling (LLS)
Supports area transit capability
Supports NSSA (compatible with RFC 3101)
Supports Database Exchange Summary List Optimization (RFC 5243)
Event-log enabled, Maximum number of events: 1000, Mode: cyclic
Router is not originating router-LSAs with maximum metric
Initial SPF schedule delay 50 msec
Minimum hold time between two consecutive SPF's 200 msec
Maximum wait time between two consecutive SPF's 5000 msec
Incremental-SPF disabled
Initial LSA throttle delay 50 msec
Minimum hold time for LSA throttle 200 msec
Maximum wait time for LSA throttle 5000 msec
Minimum LSA arrival 100 msec
LSA group pacing timer 240 secs
Interface flood pacing timer 33 msec
Retransmission pacing timer 66 msec
EXCHANGE/LOADING adjacency limit: initial 300, process maximum 300
Number of external LSA 18. Checksum Sum 0x075EB2
Number of opaque AS LSA 0. Checksum Sum 0x000000
Number of DCbitless external and opaque AS LSA 0
Number of DoNotAge external and opaque AS LSA 0
Number of areas in this router is 1. 1 normal 0 stub 0 nssa
Number of areas transit capable is 0
External flood list length 0
IETF NSF helper support enabled
Cisco NSF helper support enabled
Reference bandwidth unit is 100 mbps
  Area BACKBONE(0)
    Number of interfaces in this area is 4 (2 loopback)
    Area has RRR enabled
    Area has no authentication
    SPF algorithm last executed 02:27:23.736 ago
    SPF algorithm executed 20 times
    Area ranges are
    Number of LSA 94. Checksum Sum 0x321DCF
    Number of opaque link LSA 0. Checksum Sum 0x000000
    Number of DCbitless LSA 0

```

```

Number of indication LSA 0
Number of DoNotAge LSA 0
Flood list length 0

```

The following is the sample output of **show ospf** command for OSPFv3 with the default-optimize values.

```

Device# show ospfv3
  OSPFv3 10 address-family ipv6
    Router ID 11.11.11.11
    Supports NSSA (compatible with RFC 3101)
    Supports Database Exchange Summary List Optimization (RFC 5243)
    Event-log enabled, Maximum number of events: 1000, Mode: cyclic
    Router is not originating router-LSAs with maximum metric
    Initial SPF schedule delay 50 msec
    Minimum hold time between two consecutive SPF's 200 msec
    Maximum wait time between two consecutive SPF's 5000 msec
    Initial LSA throttle delay 50 msec
    Minimum hold time for LSA throttle 200 msec
    Maximum wait time for LSA throttle 5000 msec
    Minimum LSA arrival 100 msec
    LSA group pacing timer 240 secs
    Interface flood pacing timer 33 msec
    Retransmission pacing timer 66 msec
    Retransmission limit dc 24 non-dc 24
    EXCHANGE/LOADING adjacency limit: initial 300, process maximum 300
    Number of external LSA 0. Checksum Sum 0x000000
    Number of areas in this router is 1. 1 normal 0 stub 0 nssa
    Graceful restart helper support enabled
    Reference bandwidth unit is 100 mbps
    RFC1583 compatibility enabled
      Area BACKBONE(0)
        Number of interfaces in this area is 2
        SPF algorithm executed 7 times
        Number of LSA 3. Checksum Sum 0x012426
        Number of DCbitless LSA 0
        Number of indication LSA 0
        Number of DoNotAge LSA 0
        Flood list length 0

```

Additional References for Fast Convergence Default Optimize

Related Documents

| Related Topic | Document Title |
|--------------------|---|
| Cisco IOS Commands | Cisco IOS Master Command List, All Releases |

Feature Information for Fast Convergence Default Optimize

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for Fast Convergence Default Optimize

| Feature Name | Releases | Feature Information |
|-----------------------------------|------------------------------|---|
| Fast Convergence Default Optimize | Cisco IOS XE Everest 16.5.1b | The fast convergence default optimize feature modifies the default settings of all the protocols to recommended defaults for fast convergence. No new commands were added or modified. |

