



WebEx Telepresence Media Support Over Single SIP Session

The WebEx Telepresence Media Support over Single SIP Session feature provides support for end-to-end negotiation of up to 6 m-lines or media lines over a single Session Initiation Protocol (SIP) session. The media types can be audio, video, or application.

- [Feature Information for WebEx Telepresence Media Support Over Single SIP Session, on page 1](#)
- [Restrictions for WebEx Telepresence Media Support Over Single SIP Session, on page 2](#)
- [Information About WebEx Telepresence Media Support Over Single SIP Session, on page 2](#)
- [Monitoring WebEx Telepresence Media Support Over Single SIP Session, on page 2](#)

Feature Information for WebEx Telepresence Media Support Over Single SIP Session

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to <https://cfngng.cisco.com/>. An account on Cisco.com is not required.

Table 1: Feature Information for WebEx Telepresence Media Support Over Single SIP Session

Feature Name	Releases	Feature Information
WebEx Telepresence Media Support Over Single SIP Session	Baseline Functionality	The WebEx Telepresence Media Support over Single SIP Session feature provides support for end-to-end negotiation of up to 6 m-lines or media lines over a single Session Initiation Protocol (SIP) session. The media types can be audio, video, or application.

Restrictions for WebEx Telepresence Media Support Over Single SIP Session

- High availability is not supported with multiple m-lines.
- Only single dynamic payload type in the m-line for H.224 protocol is supported.
- Payload type interworking for Aggregation Service Routers (ASR) is not supported, so dynamic payload type is negotiated end-to-end.

Information About WebEx Telepresence Media Support Over Single SIP Session

The WebEx Telepresence Media Support over Single SIP Session feature provides the following support:

- End-to-end negotiation of multiple m-lines.
- Negotiation of Binary Floor Control Protocol (BFCP), IX, and H.224 protocol m-lines (m=application) and creation of Real-time Transport Protocol (RTP) or UDP streams for the same.
- Early-Offer (EO-EO) and Delayed-Offer (DO-DO) calls' support by the Cisco Unified Border Element (Cisco UBE) with multiple m-lines.
- End-to-end negotiation of multiple m-lines of same media type for video and application (but not audio).
- Mid-call escalation and de-escalation for multiple application and video m-lines.
- Secure RTP (SRTP) passthrough for all RTP streams (audio, video, and application).
- SRTP-RTP interworking for video (ASR only).
- Multiple dynamic payload types in the same m-line for the H.264 codec.

You can use the **show voip rtp connections** and **show call active video compact** commands to see the details about additional video and application streams.

Monitoring WebEx Telepresence Media Support Over Single SIP Session

Perform this task to see the details about additional video and application streams. The **show** commands can be entered in any order.

SUMMARY STEPS

1. **enable**
2. **show call active video compact**
3. **show voip rtp connections**

4. show sip-ua calls

DETAILED STEPS

Procedure

Step 1 enable

Enables privileged EXEC mode.

Example:

```
Device> enable
```

Step 2 show call active video compact

Displays a compact version of call information for Skinny Call Control Protocol (SCCP), SIP, and H.323 video calls in progress. The codec type, negotiated codec, and remote media ports are displayed.

Example:

```
Device# show call active video compact
```

```
<callID>  A/O FAX T<sec> Codec      type      Peer Address      IP R<ip>:<udp>
Total call-legs: 2
           1 ANS   T5    H264      VOIP-VIDEO P332211          9.45.38.39:2448
           6 ORG   T5    H264      VOIP-VIDEO P1111           9.45.38.39:2438
```

Step 3 show voip rtp connections

Displays RTP named event packets. In the following sample output, two RTP connections are displayed for each m-line and a total of 10 RTP connections are displayed for 5 m-lines.

Example:

```
Device# show voip rtp connections
```

```
VoIP RTP active connections :
No. CallId      dstCallId  LocalRTP  RmtRTP   LocalIP      RemoteIP
1      1          6         16384    54024        192.0.2.123  192.0.2.39
2      2          7         16386    2448         192.0.2.123  192.0.2.39
3      3          8         16400    5070         192.0.2.123  192.0.2.39
4      4          9         16388    2450         192.0.2.123  192.0.2.39
5      5          10        16402    2452         192.0.2.123  192.0.2.39
6      6          1         16390    58121        192.0.2.123  192.0.2.39
7      7          2         16392    2438         192.0.2.123  192.0.2.39
8      8          3         16394    5070         192.0.2.123  192.0.2.39
9      9          4         16396    2440         192.0.2.123  192.0.2.39
10     10         5         16398    2442         192.0.2.123  192.0.2.39
Found 10 active RTP connections
```

Step 4 show sip-ua calls

Displays active user agent client (UAC) and user agent server (UAS) information on Session Initiation Protocol (SIP) calls.

Example:

```
Device# show sip-ua calls
```

```
Total SIP call legs:2, User Agent Client:1, User Agent Server:1
```

SIP UAC CALL INFO

Call 1

SIP Call ID : 72B6C784-753E11E2-FFFFFFFF8008B555-FFFFFFFFE340699E@9.45.47.123
 State of the call : STATE_ACTIVE (7)
 Substate of the call : SUBSTATE_NONE (0)
 Calling Number : 332211
 Called Number : 1111
 Bit Flags : 0xC04018 0x10000100 0x80
 CC Call ID : 6
 Source IP Address (Sig) : 9.45.47.123
 Destn SIP Req Addr:Port : [9.45.38.39]:5267
 Destn SIP Resp Addr:Port: [9.45.38.39]:5267
 Destination Name : 9.45.38.39
 Number of Media Streams : 5
 Number of Active Streams: 5
 RTP Fork Object : 0x0
 Media Mode : flow-through

Media Stream 1

State of the stream : STREAM_ACTIVE
 Stream Call ID : 6
 Stream Type : voice-only (0)
 Stream Media Addr Type : 1
 Negotiated Codec : g711ulaw (160 bytes)
 Codec Payload Type : 0
 Negotiated Dtmf-relay : inband-voice
 Dtmf-relay Payload Type : 0
 QoS ID : -1
 Local QoS Strength : BestEffort
 Negotiated QoS Strength : BestEffort
 Negotiated QoS Direction : NoneLocal QoS Status : None
 Media Source IP Addr:Port: [9.45.47.123]:16390
 Media Dest IP Addr:Port : [9.45.38.39]:58121

Media Stream 2

State of the stream : STREAM_ACTIVE
 Stream Call ID : 7
 Stream Type : video (7)
 Stream Media Addr Type : 1
 Negotiated Codec : h263 (0 bytes)
 Codec Payload Type : 97
 Negotiated Dtmf-relay : inband-voice
 Dtmf-relay Payload Type : 0
 QoS ID : -1
 Local QoS Strength : BestEffort
 Negotiated QoS Strength : BestEffort
 Negotiated QoS Direction : None
 Local QoS Status : None
 Media Source IP Addr:Port: [9.45.47.123]:16392
 Media Dest IP Addr:Port : [9.45.38.39]:2438

Media Stream 3

State of the stream : STREAM_ACTIVE
 Stream Call ID : 8
 Stream Type : application (8)
 Stream Media Addr Type : 1
 Negotiated Codec : No Codec (0 bytes)
 Codec Payload Type : 255 (None)
 Negotiated Dtmf-relay : inband-voice
 Dtmf-relay Payload Type : 0
 QoS ID : -1
 Local QoS Strength : BestEffort
 Negotiated QoS Strength : BestEffort
 Negotiated QoS Direction : None
 Local QoS Status : None
 Media Source IP Addr:Port: [9.45.47.123]:16394
 Media Dest IP Addr:Port : [9.45.38.39]:5070

Media Stream 4

State of the stream : STREAM_ACTIVE
Stream Call ID : 9
Stream Type : video (7)
Stream Media Addr Type : 1
Negotiated Codec : h263 (0 bytes)
Codec Payload Type : 97
Negotiated Dtmf-relay : inband-voice
Dtmf-relay Payload Type : 0
QoS ID : -1
Local QoS Strength : BestEffort
Negotiated QoS Strength : BestEffort
Negotiated QoS Direction : None
Local QoS Status : None
Media Source IP Addr:Port: [9.45.47.123]:16396
Media Dest IP Addr:Port : [9.45.38.39]:2440

Media Stream 5

State of the stream : STREAM_ACTIVE
Stream Call ID : 10
Stream Type : application (8)
Stream Media Addr Type : 1
Negotiated Codec : H.224 (0 bytes)
Codec Payload Type : 107
Negotiated Dtmf-relay : inband-voice
Dtmf-relay Payload Type : 0
QoS ID : -1
Local QoS Strength : BestEffort
Negotiated QoS Strength : BestEffort
Negotiated QoS Direction : None
Local QoS Status : None
Media Source IP Addr:Port: [9.45.47.123]:16398
Media Dest IP Addr:Port : [9.45.38.39]:2442

Options-Ping ENABLED:NO ACTIVE:NO
Number of SIP User Agent Client(UAC) calls: 1
