



# Configuring SGCP RSIP and AUEP Enhancements

---

**Last Updated: December 14, 2011**

This section provides information on configuring the Simple Gateway Control Protocol (SGCP) Restart In Progress (RSIP) and Audit Endpoint (AUEP) Enhancements feature. The feature provides enhancements to SGCP for disconnected RSIP and audit endpoints requested by call agents.

Feature benefits include the following:

- Provides SGCP 1.5 gateways with the ability to synchronize endpoints with call agents after the disconnected procedure has occurred.

For more information about this and related Cisco IOS voice features, see the following:

- "Overview of MGCP and Related Protocols" on page 3
- Entire Cisco IOS Voice Configuration Library--including library preface and glossary, other feature documents, and troubleshooting documentation--at [http://www.cisco.com/en/US/docs/ios/12\\_3/vvf\\_c/cisco\\_ios\\_voice\\_configuration\\_library\\_glossary/vcl.htm](http://www.cisco.com/en/US/docs/ios/12_3/vvf_c/cisco_ios_voice_configuration_library_glossary/vcl.htm)

## Feature History for SGCP RSIP and AUEP Enhancements

Release	Modification
12.2(11)T	This feature was introduced on the following platforms: Cisco IAD2420 series, Cisco 2600 series, and Cisco MC3810.

- [Finding Feature Information, page 2](#)
- [Prerequisites for SGCP RSIP and AUEP Enhancements, page 2](#)
- [Restrictions for SGCP RSIP and AUEP Enhancements, page 2](#)
- [Information About SGCP RSIP and AUEP Enhancements, page 2](#)
- [How to Configure SGCP RSIP and AUEP Enhancements, page 3](#)
- [Configuration Examples for SGCP RSIP and AUEP Enhancements, page 4](#)



---

**Americas Headquarters:**  
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

## Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the Feature Information Table at the end of this document.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.

## Prerequisites for SGCP RSIP and AUEP Enhancements

- Configure SGCP 1.5 on the gateway.

## Restrictions for SGCP RSIP and AUEP Enhancements

- This feature applies only to SGCP 1.5 gateways.
- This feature does not apply to MGCP gateways.

## Information About SGCP RSIP and AUEP Enhancements

The SGCP RSIP and AUEP Enhancements feature provides additional messaging capabilities that allow an endpoint on a Simple Gateway Control Protocol (SGCP) 1.5 gateway to synchronize with a call agent after the endpoint returns to service from the disconnected procedure. The additional messaging capabilities provide the following:

- A special disconnected Restart In Progress (RSIP) message that the gateway sends to the call agent as a result of the disconnected procedure.
- Additional fields in the Audit Endpoint (AUEP) command that the call agent uses to query the endpoint's status when contact is reestablished.

Media Gateway Control Protocol (MGCP) provides this ability automatically, but it must be explicitly configured for SGCP networks, as described in the [How to Configure SGCP RSIP and AUEP Enhancements, page 3](#).

An endpoint may lose contact with its call agent because the call agent is temporarily off line or because of faults in the network. When a gateway recognizes that an endpoint has lost its communication with the call agent, it initiates the disconnected procedure. The disconnected procedure requires the endpoint to send RSIPs to the call agent and also to guarantee that the first message that the call agent sees from the endpoint is an RSIP command. The endpoint continues to attempt to send RSIPs at the intervals prescribed by the disconnected procedure until an attempt is successful. The RSIP identifies itself as an RSIP that was generated from a disconnected procedure rather than from a restart. The following output is seen on the gateway:

```
Disconnected RSIP sent from gateway
00:04:27:RSIP 7 ds1-3/2@RouterA SGCP 1.5
RM:disconnected
```

On receipt of a disconnected RSIP message, the call agent may decide to send an AUEP command to query the status of endpoints and synchronize endpoints. The SGCP RSIP and AUEP Enhancements feature provides the following additional fields of information in the AUEP:

- I--List of connection identifiers for current connections on the endpoint
- ES--Event state of the endpoint (off-hook or on-hook)
- RM--Restart method for the endpoint, which is one of the following:
  - Graceful--Endpoints are being taken out of service after a delay; the call agent should not make new connections.
  - Forced--Endpoints were abruptly taken out of service; connections were lost.
  - Restart--Endpoints with no connections will be returned to service after a delay.
  - Disconnected--Endpoints are being returned to service after the disconnected procedure.

## How to Configure SGCP RSIP and AUEP Enhancements

- [Configuring SGCP RSIP and AUEP Enhancements, page 3](#)
- [Verifying SGCP RSIP Configuration, page 3](#)

### Configuring SGCP RSIP and AUEP Enhancements

To configure enhanced restart and endpoint audit messaging capabilities on an SGCP gateway, use the following command in global configuration mode:

Command	Purpose
Router(config)# <b>mgcp sgcp disconnect notify</b>	Enables enhanced endpoint synchronization with a call agent after a disconnected procedure. The command is disabled by default.

### Verifying SGCP RSIP Configuration

To verify your configuration, enter the **show mgcp** command. The following example shows that disconnected RSIP is enabled.

```
Router# show mgcp
MGCP Admin State ACTIVE, Oper State ACTIVE - Cause Code NONE
MGCP call-agent:172.16.193.148 Initial protocol service is SGCP 1.5
MGCP block-newcalls DISABLED
MGCP send SGCP RSIP:forced/restart/graceful DISABLED, disconnected ENABLED
MGCP quarantine mode discard/step
MGCP quarantine of persistent events is ENABLED
MGCP dtmf-relay for VoIP disabled for all codec types
MGCP dtmf-relay for VoAAL2 disabled for all codec types
MGCP voip modem passthrough mode:NSE, codec:g711ulaw, redundancy:DISABLED,
MGCP voaal2 modem passthrough mode:NSE, codec:g711ulaw
MGCP TSE payload:0
MGCP Named Signalling Event (NSE) response timer:200
MGCP Network (IP/AAL2) Continuity Test timer:200
MGCP 'RTP stream loss' timer:5
MGCP request timeout 500
MGCP maximum exponential request timeout 4000
```

```

MGCP gateway port:2427, MGCP maximum waiting delay 3000
MGCP restart delay 0, MGCP vad DISABLED
MGCP rtrcac DISABLED
MGCP system resource check DISABLED
MGCP xpc-codec:DISABLED, MGCP persistent hookflash:DISABLED
MGCP persistent offhook:ENABLED, MGCP persistent onhook:DISABLED
MGCP piggyback msg ENABLED, MGCP endpoint offset DISABLED
MGCP simple-sdp DISABLED
MGCP undotted-notation DISABLED
MGCP codec type g711ulaw, MGCP packetization period 20
MGCP JB threshold lwm 30, MGCP JB threshold hwm 150
MGCP LAT threshold lwm 150, MGCP LAT threshold hwm 300
MGCP PL threshold lwm 1000, MGCP PL threshold hwm 10000
MGCP CL threshold lwm 1000, MGCP CL threshold hwm 10000
MGCP playout mode is adaptive 60, 4, 200 in msec
MGCP IP ToS low delay disabled, MGCP IP ToS high throughput disabled
MGCP IP ToS high reliability disabled, MGCP IP ToS low cost disabled
MGCP IP RTP precedence 5, MGCP signaling precedence:3
MGCP default package:line-package
MGCP supported packages:gm-package dtmf-package trunk-package line-package
                        hs-package atm-package ms-package dt-package res-package
                        mt-package
MGCP Digit Map matching order:shortest match
SGCP Digit Map matching order:always left-to-right
MGCP VoAAL2 ignore-lco-codec DISABLED

```

## Configuration Examples for SGCP RSIP and AUPE Enhancements

- [Disconnected RSIP Messaging Example, page 4](#)

### Disconnected RSIP Messaging Example

The following example shows the configuration of disconnected RSIP messaging on a Cisco MC3810.

```

version 12.2
no parser cache
no service pad
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname Router2
!
boot system tftp smithj/mc3810-r3j1l 172.16.206.10
logging buffered 2000000 debugging
no logging console
enable password lab
!
network-clock base-rate 56k
ip subnet-zero
!
no ip domain-lookup
ip host corona 172.16.206.10
ip host redlands 172.31.140.33
ip host rialto 172.16.193.147
!
voice service voip
  fax protocol t38 ls-redundancy 0 hs-redundancy 0
!
no voice confirmation-tone
voice-card 0
!
controller T1 0

```

```
mode cas
framing esf
clock source internal
linecode ami
ds0-group 0 timeslots 1-24 type fxs-ground-start
!
interface Ethernet0
 ip address 172.16.193.162 255.255.255.0
 no ip mroute-cache
!
interface Serial0
 no ip address
 no ip route-cache
 no ip mroute-cache
 shutdown
!
interface Serial1
 no ip address
 no ip route-cache
 no ip mroute-cache
 shutdown
!
interface FR-ATM20
 no ip address
 shutdown
 ip classless
 ip route 10.0.0.0 10.0.0.0 172.16.193.1
 ip route 172.16.0.0 255.255.0.0 172.16.193.1
 no ip http server
!
!
call rsvp-sync
!
voice-port 0:0
!
voice-port 1/1
!
voice-port 1/2
 description package
!
mgcp
mgcp call-agent 172.16.193.148 service-type sgcp version 1.5
mgcp sgcp disconnect notify
!
mgcp profile default
!
dial-peer cor custom
!
dial-peer voice 1 pots
 application mgcpapp
 port 1/1
!
dial-peer voice 2 pots
 application mgcpapp
 port 1/2
!
dial-peer voice 3 pots
 application mgcpapp
 port 0:0
!
gatekeeper
 shutdown
!
line con 0
 exec-timeout 0 0
line aux 0
line 2 3
line vty 0 4
 exec-timeout 0 0
 password hemet
 login
!
end
```

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2011 Cisco Systems, Inc. All rights reserved.