



Configuring ISG Policies for Automatic Subscriber Logon

First Published: March 20, 2006

Last Updated: May 13, 2010

Intelligent Services Gateway (ISG) is a Cisco IOS and Cisco IOS XE software feature set that provides a structured framework in which edge devices can deliver flexible and scalable services to subscribers. This module contains information on how to configure ISG to use specified identifiers in place of the username in authorization requests, enabling a user profile to be downloaded from an authentication, authorization, and accounting (AAA) server as soon as packets are received from a subscriber.

Finding Feature Information

For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the “[Feature Information for ISG Automatic Subscriber Logon](#)” section on page 11.

Use Cisco Feature Navigator to find information about platform support and Cisco IOS XE software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

Contents

- [Prerequisites for ISG Automatic Subscriber Logon, page 2](#)
- [Restrictions for ISG Automatic Subscriber Logon, page 2](#)
- [Information About ISG Automatic Subscriber Logon, page 2](#)
- [How to Configure ISG Policies for Automatic Subscriber Logon, page 4](#)
- [Configuration Examples for ISG Automatic Subscriber Logon, page 8](#)



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

■ Prerequisites for ISG Automatic Subscriber Logon

- [Additional References, page 9](#)
- [Feature Information for ISG Automatic Subscriber Logon, page 11](#)

Prerequisites for ISG Automatic Subscriber Logon

For information about release and platform support, see the “[Feature Information for ISG Automatic Subscriber Logon](#)” section on page 11.

Depending on your AAA implementation, you may need to configure one of the following identifiers in the password field of the user profile: source IP address, MAC address, remote ID, circuit ID. You may also need to configure a global address in the password field.

To use circuit ID and remote ID for authorization for IP sessions, the DSLAM must insert the circuit ID and remote ID in the DHCP Option 82 information.

To use remote ID for authorization of PPPoE sessions, the PPPoE client must provide the remote ID information in the PPPoE Tag ID or line ID.

Restrictions for ISG Automatic Subscriber Logon

The username field in an authorization request has a limit of 253 characters.

Information About ISG Automatic Subscriber Logon

Before you configure ISG automatic subscriber logon, you should understand the following concepts:

- [Overview of ISG Automatic Subscriber Logon, page 2](#)
- [Supported Identifiers for ISG Automatic Subscriber Logon, page 3](#)
- [Authorization Based on Circuit ID and Remote ID, page 3](#)
- [Accounting Behavior When ISG Automatic Subscriber Logon Is Configured, page 3](#)

Overview of ISG Automatic Subscriber Logon

Service providers commonly implement a policy at the start of IP sessions that redirects all subscriber packets to a logon portal for authentication. Following successful authentication, per-subscriber authorization data is typically returned from a AAA server. For some deployments, usually in subscriber networks that are well protected against spoofing and denial-of-service (DoS) attacks, service providers are willing to forgo authentication and trust subscriber identity. ISG automatic subscriber logon allows service providers to grant certain subscribers access to services without requiring the subscribers to log on.

ISG automatic subscriber logon enables a specified identifier to be used in place of the username in authorization requests. Enabling the AAA server to authorize subscribers on the basis of a specified identifier allows subscriber profiles to be downloaded from the AAA server as soon as packets are received from subscribers.

The event that triggers automatic subscriber logon is session-start. For IP sessions, session-start occurs when a DHCP DISCOVER request is received or when an unrecognized source IP address is detected. For PPPoE sessions, session-start occurs when a client attempts to initiate a session by sending a PPPoE Active Discovery Initiation (PADI) packet.

Supported Identifiers for ISG Automatic Subscriber Logon

For IP sessions, an ISG device can be configured to use the following identifiers in place of the username in authorization requests: IP address, MAC address, circuit ID, remote ID, or a combination of the circuit ID and remote ID.

For PPPoE sessions, an ISG device can be configured to use the remote ID in place of the username in authorization requests.

Authorization Based on Circuit ID and Remote ID

The circuit ID and remote ID fields are part of the DHCP relay agent information option (also referred to as Option 82) and the PPPoE Tag VSA. These fields are inserted into DHCP and PPPoE messages by a DSLAM. An ISG device can be configured to use the circuit ID, remote ID, or a combination of circuit ID and remote ID as the username in authorization requests.

By default, the ISG device will use the circuit ID and remote ID that are provided by the Layer 2 edge access device for authorization. If the **ip dhcp relay information option** command is configured, the ISG device will use the circuit ID and remote ID that are received in a DHCP message.

Accounting Behavior When ISG Automatic Subscriber Logon Is Configured

Accounting Behavior for MAC-Address-Based Authorization

If the MAC address is sent as the username in authorization requests, the MAC address will also be sent as the Calling Station ID in accounting records.

Accounting Behavior for Remote-ID- and Circuit-ID-Based Authorization

For IP sessions that use DHCP Option 82 authorization, accounting messages are sent to the AAA server with the Circuit ID and Remote ID Cisco VSAs. Although you can configure a combination of circuit ID and remote ID as the username for authorization, the attributes are sent individually in accounting records. You can also configure the circuit ID and remote ID to be sent together in accounting records as the NAS Port ID.

For PPPoE sessions, the Remote ID VSA is sent in accounting records, and the remote ID is also sent as the NAS Port ID.

If the **radius-server attribute 31 remote-id** command is configured, the remote ID is sent in accounting records as the Calling Station ID.

How to Configure ISG Policies for Automatic Subscriber Logon

To configure ISG policies to automatically log on subscribers, perform the following tasks:

- [Identifying Traffic for Automatic Logon in a Control Policy Class Map, page 4](#)
- [Configuring an ISG Control Policy for Automatic Subscriber Logon, page 5](#)
- [Enabling the Remote-ID to Be Sent as the Calling-Station-ID, page 7](#)
- [Verifying ISG Automatic Subscriber Logon, page 7](#)

Identifying Traffic for Automatic Logon in a Control Policy Class Map

Perform this task to configure a control policy class map that specifies the traffic to which ISG automatic subscriber logon will apply.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **class-map type control match-all *class-map-name***
4. **match source-ip-address *ip-address subnet-mask***
or
match nas-port circuit-id *name*
or
match nas-port remote-id *name*
5. **end**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
	Example: Router> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example: Router# configure terminal	
Step 3	class-map type control match-all <i>class-map-name</i>	Creates a control class map, which defines the conditions under which the actions of a control policy map will be executed.
	Example: Router(config)# class-map type control match-all TAL-subscribers	

Command or Action	Purpose
Step 4 <pre>match source-ip-address ip-address subnet-mask or match nas-port circuit-id name or match nas-port remote-id name</pre> <p>Example: Router(config-control-classmap) # match source-ip-address 10.1.1.0 255.255.255.0 or</p> <p>Example: Router(config-control-classmap) # match nas-port circuit-id circuit1 or</p> <p>Example: Router(config-control-classmap) # match nas-port remote-id remote1 </p>	Creates a condition that will evaluate true if a subscriber's source IP address matches the specified IP address. or Creates a condition that will evaluate true if a subscriber's circuit ID matches the specified value. or Creates a condition that will evaluate true if a subscriber's remote ID matches the specified value.
Step 5 <pre>end</pre> <p>Example: Router(config-control-classmap) # end</p>	(Optional) Returns to privileged EXEC mode.

Configuring an ISG Control Policy for Automatic Subscriber Logon

Perform this task to configure an ISG control policy that initiates subscriber authorization and inserts a specified identifier into the username field of the authorization request.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **policy-map type control *policy-map-name***
4. **class type control {*class-map-name* | always} event session-start**
5. ***action-number authorize [aaa {*list-name* | list {*list-name* | default}}] [password *password*] [upon network-service-found {continue | stop}] [use method *authorization-type*] identifier *identifier-type* [plus *identifier-type*]***
6. **end**

DETAILED STEPS

	Command or Action	Purpose
Step 1	<code>enable</code>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
	Example: Router> enable	
Step 2	<code>configure terminal</code>	Enters global configuration mode.
	Example: Router# configure terminal	
Step 3	<code>policy-map type control policy-map-name</code>	Creates or modifies a control policy map, which is used to define a control policy.
	Example: Router(config)# policy-map type control TAL	
Step 4	<code>class type control {class-map-name always} event session-start</code>	Specifies a control class, which defines the conditions that must be met in order for an associated set of actions to be executed. <ul style="list-style-type: none"> • Specify the control class-map that was configured in the task “Identifying Traffic for Automatic Logon in a Control Policy Class Map”.
	Example: Router(config-control-policymap)# class type control TAL-subscribers event session-start	
Step 5	<code>action-number authorize [aaa {list-name list {list-name default}} [password password]] [upon network-service-found {continue stop}] [use method authorization-type] identifier identifier-type [plus identifier-type]</code>	Inserts the specified identifier into the username field of authorization requests.
	Example: Router(config-control-policymap-class-control)# 1 authorize aaa list TAL_LIST password cisco identifier source-ip-address	
Step 6	<code>end</code>	Exits the current configuration mode and returns to privileged EXEC mode.
	Example: Router(config-control-policymap-class-control)# end	

What to Do Next

You must apply the control policy to a context by using the **service-policy type control** command. For information about applying control policies, see the module “[Configuring ISG Control Policies](#)”.

You may want to configure policies to determine what should happen for autologon subscribers whose IP address or MAC address authorization fails; for example, you may want to redirect the subscriber to the policy server for authentication.

Enabling the Remote-ID to Be Sent as the Calling-Station-ID

Perform this task to enable the ISG device to send the remote ID in the Calling-Station-ID (attribute 31) field of accounting records and access requests.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **radius-server attribute 31 remote-id**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode. • Enter your password if prompted.
	Example: Router> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example: Router# configure terminal	
Step 3	radius-server attribute 31 remote-id	Enables the ISG device to send the remote ID in the Calling Station ID (attribute 31) field of accounting records and access requests.
	Example: Router#(config) radius-server attribute 31 remote-id	

Verifying ISG Automatic Subscriber Logon

Perform this task to determine whether or not automatic subscriber logon was successful.

SUMMARY STEPS

1. **enable**
2. **show subscriber session**

DETAILED STEPS

Step 1	enable	Enables privileged EXEC mode.
Step 2	show subscriber session	Use the show subscriber session command to display information about ISG subscriber sessions. If the output shows that a session was brought up in the state “authen”, automatic subscriber authorization was successful. If automatic subscriber authorization was not successful, the session will still be brought up, but in the state “unauthen”.

■ Configuration Examples for ISG Automatic Subscriber Logon

The following sample output shows information for a session for which automatic subscriber authorization was successful:

```
Router# show subscriber session all

Current Subscriber Information: Total sessions 1
-----
Unique Session ID: 3
Identifier: aabb.cc01.3000
SIP subscriber access type(s): IP
Current SIP options: Req Fwding/Req Fwded
Session Up-time: 00:00:24, Last Changed: 00:00:21

Policy information:
  Authentication status: authen
  Rules, actions and conditions executed:
    subscriber rule-map DEFAULT
      condition always event session-start
        1 authorize identifier mac-address

Session inbound features:
  Feature: IP Idle Timeout
    Timeout value is 600
    Idle time is 00:00:21
Configuration sources associated with this session:
Interface: GigabitEthernet0/0/0, Active Time = 00:00:24
```

Configuration Examples for ISG Automatic Subscriber Logon

This section contains the following example:

- [Automatic Subscriber Logon Based on IP Address: Example, page 8](#)

Automatic Subscriber Logon Based on IP Address: Example

In the following example, if the client is from the 1.1.1.0 subnet, the ISG sends an authorization request to the list “TAL_LIST” with the subscriber’s source IP address as the username. If the authorization request is successful, any automatic-activation services specified in the returned user profile are activated for the session, and the execution of rules within the control policy stops. If the authorization is not successful, the rule execution proceeds, and the subscriber is redirected to the policy server to log in. If the subscriber does not log in within five minutes, the session is disconnected.

ISG Configuration

```
subscriber service password cisco

interface GigabitEthernet0/0/0
  service-policy type control RULEA

  aaa authorization network TAL_LIST group radius
  aaa authentication login LOCAL local
  access-list 100 permit ip any any

  class-map type traffic match-any all-traffic
    match access-group input 100
```

```

match access-group output 100

policy-map type service redirectprofile
  class type traffic all-traffic
    redirect to ip 10.0.0.148 port 8080

class-map type control match-all CONDA
  match source-ip-address 10.1.1.0 255.255.255.0

!
class-map type control match-all CONDF
  match timer TIMERB
  match authen-status unauthenticated

policy-map type control RULEA
  class type control CONDA event session-start
    1 authorize aaa list TAL_LIST password cisco identifier source-ip-address
    2 service-policy type service aaa list LOCAL name redirectprofile
    3 set-timer TIMERB 5 minutes
!
class type control CONDF event timed-policy-expiry
  1 service disconnect

```

User Profile Configuration

```

1.1.1.1 Password = "cisco"
Service-Type = Outbound,
Cisco:Account-Info = "AAuto-Internet;proxy-user;cisco"

```

Service Profile Configuration

```

Auto-Internet Password = "cisco"
Cisco:Service-Info = "IAuto-Internet",
Cisco-Avpair = "traffic-class=input access-group 100"

proxy-user Password = "cisco"
Idle-Timeout = 5

```

Additional References

The following sections provide references related to ISG automatic subscriber logon.

Related Documents

Related Topic	Document Title
ISG commands	<i>Cisco IOS Intelligent Services Gateway Command Reference</i>

Standards

Standard	Title
No new or modified standards are supported by this feature.	—

■ Additional References

MIBs

MIB	MIBs Link
No new or modified MIBs are supported by this feature.	To locate and download MIBs for selected platforms, Cisco IOS XE releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

Technical Assistance

Description	Link
The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.	http://www.cisco.com/techsupport
To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.	
Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.	

Feature Information for ISG Automatic Subscriber Logon

Table 1 lists the features in this module and provides links to specific configuration information. For information about a feature in this technology that is not documented here, see the “[Intelligent Services Gateway Features Roadmap](#).”

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS XE software images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.



Note **Table 1** lists only the Cisco IOS XE software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS XE software release train also support that feature.

Table 1 *Feature Information for ISG Automatic Subscriber Logon*

Feature Name	Releases	Feature Configuration Information
ISG: Session: Authentication (MAC, IP)	Cisco IOS XE Release 2.2	<p>ISG automatic subscriber logon enables an IP address or MAC address to be used in place of the username in authorization requests. This functionality allows subscriber profiles to be downloaded from the AAA server as soon as packets are received from subscribers.</p> <p>This module provides information about this feature.</p>
ISG: Authentication: DHCP Option 82 Line ID - AAA Authorization Support	Cisco IOS XE Release 2.2	<p>This feature enhances ISG automatic subscriber logon by providing support for authorization on the basis of the circuit-id and remote-id.</p> <p>The following sections provide information about this feature:</p> <ul style="list-style-type: none"> • Supported Identifiers for ISG Automatic Subscriber Logon, page 3 • Authorization Based on Circuit ID and Remote ID, page 3 • Accounting Behavior When ISG Automatic Subscriber Logon Is Configured, page 3 • How to Configure ISG Policies for Automatic Subscriber Logon, page 4

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2006–2010 Cisco Systems, Inc. All rights reserved.

■ Feature Information for ISG Automatic Subscriber Logon