



Configuring RMON Features Roadmap

First Published: February 27, 2009
Last Updated: December 15, 2009

This feature roadmap lists the Remote Monitoring (RMON) features documented in the RMON Support section of the *Cisco IOS Network Management Configuration Guide* and maps them to the documents in which they appear. The roadmap is organized so that you can select your release train and see the features in that release. Find the feature name you are searching for and click on the URL in the “Where Documented” column to access the document containing that feature.

Many legacy features have been incorporated into the configuration files, and these features may not have entries in this roadmap. In addition, information in this roadmap supports other software releases or platforms. For the latest feature information and caveats, see the release notes for your platform and software release.

Feature and Release Support

Table 1 lists RMON feature support for the following Cisco IOS software release trains:

- [Cisco IOS Release 12.2SR](#)
- [Cisco IOS Release 12.2SX](#)
- [Cisco IOS Releases 11.2, 12.2T, 12.3, 12.3T, 12.4 and 12.4T](#)

Use Cisco Feature Navigator to find information about platform support and software image support. Cisco Feature Navigator enables you to determine which Cisco IOS and Catalyst OS images support a specific software release, feature set, or platform. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.



Note

Table 1 lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

Table 1 lists the most recent release of each software train first and the features in alphabetical order within the release.



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Table 1 Supported Configuring RMON Features

Release	Feature Name	Feature Description	Where Documented
Cisco IOS Release 12.2SR			
12.2(33)SRE	HC Alarm MIB	The HC Alarm MIB feature provides an extension to the RMON-1 Alarm group table objects which was used to support counter 32 objects for threshold capabilities. The HC Alarm MIB adds support to threshold capabilities for counter 64 objects.	Configuring RMON Support
12.2(33)SRE	RMON MIB enhancement to support 64 bit counters	RMON MIB enhancement to support 64 bit counters features provides support for the ability to poll 64 bit counters.	Configuring RMON Support
Cisco IOS Release 12.2SX			
12.2(33)SXI	HC Alarm MIB	The HC Alarm MIB feature provides an extension to the RMON-1 Alarm group table objects which was used to support counter 32 objects for threshold capabilities. The HC Alarm MIB adds support to threshold capabilities for counter 64 objects.	Configuring RMON Support
12.2(33)SXI	RMON MIB enhancement to support 64 bit counters	RMON MIB enhancement to support 64 bit counters features provides support for the ability to poll 64 bit counters.	Configuring RMON Support
Cisco IOS Releases 11.2, 12.2T, 12.3, 12.3T, 12.4 and 12.4T			
12.4(5)T	Remote Monitoring MIB Update	The RMON Rewrite feature updated the Remote Monitoring MIB to improve performance and available features.	Configuring RMON Support
11.2	RMON Events and Alarms	The RMON Events and Alarms feature introduces the ability to combine RMON alarms and events (classes of messages that indicate traffic violations and various unusual occurrences over a network) with existing MIBs allows you to choose where proactive monitoring will occur.	Configuring RMON Support
11.2	RMON Full	Remote Monitoring (RMON) is a standard monitoring specification that enables various network monitors and console systems to exchange network-monitoring data. RMON provides network administrators with more freedom in selecting network-monitoring probes and consoles with features that meet their particular networking needs. The RMON Full feature identifies activity on individual nodes and helps monitor all nodes and their interaction on a LAN segment. Used in conjunction with the SNMP agent in a router, RMON can be used to view both traffic that flows through the router and segment traffic not necessarily destined for the router.	Configuring RMON Support

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco:Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0910R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2009 Cisco Systems, Inc. All rights reserved.

