



BGP-based VPWS Autodiscovery

Table 1: Feature History Table

Feature Name	Release Information	Feature Description
BGP-Based VPWS Infrastructure	Release 7.3.1	This feature is now supported on routers that have Cisco NC57 line cards installed and operate in the native mode.

An important aspect of VPN technologies is the ability of network devices to automatically signal to other devices about an association with a particular VPN. Autodiscovery refers to the process of finding all the provider edge routers that participates in a given VPWS instance.

The two primary functions of the VPWS control plane are: auto-discovery and signaling. Both of these functions are accomplished with a single BGP Update advertisement.

When a VPWS cross-connect is configured with BGP auto-discovery and signaling enabled, BGP needs to distribute NLRI for the xconnect with the PE as the BGP next-hop and appropriate CE-ID. Additionally, the cross-connect is associated with one or more BGP export Route Targets (RTs) that are also distributed (along with NLRI).

- [Configuring VPWS with BGP Autodiscovery and Signaling, on page 1](#)
- [VPWS with BGP Autodiscovery and BGP Signaling, on page 3](#)

Configuring VPWS with BGP Autodiscovery and Signaling

Perform this task to configure BGP-based autodiscovery and signaling.

Procedure

Step 1 **configure**

Example:

```
RP/0/RP0/CPU0:router# configure
```

Enters the global configuration mode.

Step 2 **l2vpn**

Example:

```
RP/0/RP0/CPU0:router(config)# l2vpn
```

Enters L2VPN configuration mode.

Step 3 xconnect group *group name***Example:**

```
RP/0/RP0/CPU0:router(config-l2vpn)# xconnect group gr1
```

Enters configuration mode for the named xconnect group.

Step 4 mp2mp *vpws-domain name***Example:**

```
RP/0/RP0/CPU0:router(config-l2vpn-xc)# mp2mp mp1
```

Enters configuration mode for the named vpws domain.

Step 5 vpn-id *vpn-id***Example:**

```
RP/0/RP0/CPU0:router(config-l2vpn-xc-m2mp)# vpn-id 100
```

Specifies the identifier for the VPWS service.

Step 6 l2 encapsulation vlan**Example:**

```
RP/0/RP0/CPU0:router(config-l2vpn-xc-mp2mp)#l2-encapsulation vlan
```

Configure the L2 encapsulation for this L2VPN MP2MP Instance.

Step 7 autodiscovery bgp**Example:**

```
RP/0/RP0/CPU0:router(config-l2vpn-xc-mp2mp)#autodiscovery bgp
```

Enters BGP autodiscovery configuration mode where all BGP autodiscovery parameters are configured.

Step 8 rd { *as-number:nn* | *ip-address:nn* | **auto }****Example:**

```
RP/0/RP0/CPU0:router(config-l2vpn-xc-mp2mp-ad)# rd auto
```

Specifies the route distinguisher (RD).

Step 9 **route-target { as-number:nn | ip-address:nn | export | import }**

Example:

```
RP/0/RP0/CPU0:router(config-l2vpn-xc-mp2mp-ad)# route-target 500:99
```

Specifies the route target (RT).

Step 10 **signaling-protocol bgp**

Example:

```
RP/0/RP0/CPU0:router(config-l2vpn-xc-mp2mp-ad)# signaling-protocol bgp
```

Enables BGP signaling, and enters the BGP signaling configuration submode where BGP signaling parameters are configured.

Step 11 **ce-id { number}**

Example:

```
RP/0/RP0/CPU0:router(config-l2vpn-xc-mp2mp-ad-sig)# ce-id 10
```

Specifies the local Customer Edge Identifier.

Step 12 Use the **commit** or **end** command.

commit - Saves the configuration changes and remains within the configuration session.

end - Prompts user to take one of these actions:

- **Yes** - Saves configuration changes and exits the configuration session.
- **No** - Exits the configuration session without committing the configuration changes.
- **Cancel** - Remains in the configuration mode, without committing the configuration changes.

VPWS with BGP Autodiscovery and BGP Signaling

The following figure illustrates an example of configuring and verifying VPWS with BGP autodiscovery (AD) and BGP Signaling.

Figure 1: VPLS with BGP autodiscovery and BGP signaling



Configuration at PE1:

```
12vpn
  xconnect group gr1
    mp2mp mp1
    vpn-id 100
    12 encapsulation vlan
      autodiscovery bgp
      rd auto
      route-target 2.2.2.2:100
      ! Signaling attributes
      signaling-protocol bgp
      ce-id 1
    interface GigabitEthernet0/1/0/1.1 remote-ce-id 2
```

Configuration at PE2:

```
12vpn
  xconnect group gr1
    mp2mp mp1
    vpn-id 100
    12 encapsulation vlan
      autodiscovery bgp
      rd auto
      route-target 2.2.2.2:100
      ! Signaling attributes
      signaling-protocol bgp
      ce-id 2
    interface GigabitEthernet0/1/0/2.1 remote-ce-id 1
```

Verification:**PE1:**

```
PE1# show 12vpn discovery xconnect

Service Type: VPWS, Connected

List of VPNs (1 VPNs):

XC Group: gr1, MP2MP mp1

List of Local Edges (1 Edges):

Local Edge ID: 1, Label Blocks (1 Blocks)

  Label base Offset  Size  Time Created
  -----  -----  -----  -----
  16030      1       10  01/24/2009 21:23:04

  Status Vector: 9f ff

List of Remote Edges (1 Edges):

Remote Edge ID: 2, NLRIs (1 NLRIs)

  Label base Offset  Size  Peer ID  Time Created
  -----  -----  -----  -----

```

```

16045      1          10      1.1.1.1      01/24/2009 21:29:35
Status Vector: 7f ff

PE1# show l2vpn xconnect mp2mp detail
Group gr1, MP2MP mp1, state: up
VPN ID: 100
VPN MTU: 1500
L2 Encapsulation: VLAN
Auto Discovery: BGP, state is Advertised (Service Connected)
Route Distinguisher: (auto) 3.3.3.3:32770
Import Route Targets:
2.2.2.2:100
Export Route Targets:
2.2.2.2:100
Signaling protocol:BGP
CE Range:10
...
Group gr1, XC mp1.1:2, state is up; Interworking none
Local CE ID: 1, Remote CE ID: 2, Discovery State: Advertised
AC: GigabitEthernet0/1/0/1.1, state is up
Type VLAN; Num Ranges: 1
VLAN ranges: [1, 1]
MTU 1500; XC ID 0x2000013; interworking none
PW: neighbor 1.1.1.1, PW ID 65538, state is up ( established )
PW class not set, XC ID 0x2000013
Encapsulation MPLS, Auto-discovered (BGP), protocol BGP
MPLS          Local          Remote
-----
Label        16031        16045
MTU         1500         1500
Control word enabled           enabled
PW type     Ethernet VLAN      Ethernet VLAN
CE-ID       1             2

```

VPWS with BGP Autodiscovery and BGP Signaling

```
PE1# show bgp l2vpn vpws

BGP router identifier 3.3.3.3, local AS number 100
BGP generic scan interval 60 secs
BGP table state: Active
Table ID: 0x0
BGP main routing table version 913
BGP NSR converge version 3
BGP NSR converged
BGP scan interval 60 secs
Status codes: s suppressed, d damped, h history, * valid, > best
               i - internal, S stale
Origin codes: i - IGP, e - EGP, ? - incomplete
```

Network	Next Hop	Rcvd Label	Local Label
Route Distinguisher: 1.1.1.1:32775			
*>i2:1/32	1.1.1.1	16045	nolabel
*>i3:1/32	1.1.1.1	16060	nolabel
Route Distinguisher: 3.3.3.3:32770 (default for vrf gr1:mp1)			
*> 1:1/32	0.0.0.0	nolabel	16030
*>i2:1/32	1.1.1.1	16045	nolabel
*>i3:1/32	1.1.1.1	16060	nolabel

Processed 5 prefixes, 5 paths

PE2:

```
PE2# show l2vpn discovery xconnect
Service Type: VPWS, Connected
List of VPNs (1 VPNs):
XC Group: gr1, MP2MP mp1
List of Local Edges (2 Edges):
Local Edge ID: 2, Label Blocks (1 Blocks)
```

```

Label base Offset  Size  Time Created
----- -----  -----
16045      1       10   01/24/2009 21:09:14

Status Vector: 7f ff

Local Edge ID: 3, Label Blocks (1 Blocks)

Label base Offset  Size  Time Created
----- -----  -----
16060      1       10   01/24/2009 21:09:14

Status Vector: 7f ff

List of Remote Edges (1 Edges):

Remote Edge ID: 1, NLRIs (1 NLRIs)

Label base Offset  Size  Peer ID  Time Created
----- -----  -----  -----
16030      1       10   3.3.3.3   01/24/2009 21:09:16

Status Vector: 9f ff

PE2# show l2vpn xconnect mp2mp detail

Group gr1, MP2MP mp1, state: up

VPN ID: 100

VPN MTU: 1500

L2 Encapsulation: VLAN

Auto Discovery: BGP, state is Advertised (Service Connected)

Route Distinguisher: (auto) 1.1.1.1:32775

Import Route Targets:

2.2.2.2:100

Export Route Targets:

2.2.2.2:100

Signaling protocol:BGP

CE Range:10

...

Group gr1, XC mp1.2:1, state is up; Interworking none

Local CE ID: 2, Remote CE ID: 1, Discovery State: Advertised

```

VPWS with BGP Autodiscovery and BGP Signaling

```

AC: GigabitEthernet0/1/0/2.1, state is up

Type VLAN; Num Ranges: 1

VLAN ranges: [1, 1]

MTU 1500; XC ID 0x2000008; interworking none

PW: neighbor 3.3.3.3, PW ID 131073, state is up ( established )

PW class not set, XC ID 0x2000008

Encapsulation MPLS, Auto-discovered (BGP), protocol BGP

```

MPLS	Local	Remote
<hr/>		
Label	16045	16031
MTU	1500	1500
Control word enabled		enabled
PW type	Ethernet VLAN	Ethernet VLAN
CE-ID	2	1
<hr/>		
...		

```

PE2# show bgp l2vpn vpws

BGP router identifier 1.1.1.1, local AS number 100

BGP generic scan interval 60 secs

BGP table state: Active

Table ID: 0x0

BGP main routing table version 819

BGP NSR converge version 7

BGP NSR converged

BGP scan interval 60 secs

Status codes: s suppressed, d damped, h history, * valid, > best
               i - internal, S stale

Origin codes: i - IGP, e - EGP, ? - incomplete

Network          Next Hop        Rcvd Label     Local Label
Route Distinguisher: 1.1.1.1:32775 (default for vrf gr1:mp1)
*->i1:1/32           3.3.3.3       16030         nolabel

```

```
*> 2:1/32          0.0.0.0        nolabel      16045
*> 3:1/32          0.0.0.0        nolabel      16060
Route Distinguisher: 3.3.3.3:32770
*>i1:1/32          3.3.3.3       16030        nolabel
```

Processed 4 prefixes, 4 paths

