



MACsec Using EAP-TLS Authentication

This chapter describes how to achieve MACSec encryption between two Routers using the 802.1X port-based authentication with Extensible Authentication Protocol-Transport Layer Security (EAP-TLS).

For more information on 802.1X port-based authentication, see the *802.1X Port-Based Authentication* chapter.

Table 1: Feature History

Release	Modification
Release 6.6.3	This feature was introduced.

- [MACSec Using EAP-TLS Authentication, on page 1](#)
- [Configure MACSec Encryption Using EAP-TLS Authentication, on page 1](#)

MACSec Using EAP-TLS Authentication

This chapter describes how to achieve MACSec encryption between two Routers using the 802.1X port-based authentication with Extensible Authentication Protocol-Transport Layer Security (EAP-TLS). EAP-TLS allows mutual authentication using certificates, between the authentication server and the client, and generates the Master Session Key (MSK). This MSK is used to derive the Connectivity Association Key (CAK), and the corresponding Connectivity Association Key Name (CKN) is derived from the EAP session ID.

Configure MACSec Encryption Using EAP-TLS Authentication

The system supports certificate-based MACsec encryption using both local and remote EAP-TLS authentications.

Restrictions for MACSec Using EAP-TLS Authentication

- The system does not support certificate-based (EAP-TLS) MACsec encryption on sub-interfaces.
- The system does not support MACSec using EAP-TLS authentication in **multi-auth** host mode.

You must also follow the guidelines and restrictions applicable to EAP-TLS session. For details, see the [#unique_307](#) section in the *802.1X Port-Based Authentication* chapter.

Prerequisites

For MACSec using EAP-TLS authentication, you must first configure a EAP-TLS session. For more information on configuring EAP-TLS session, see the following topics in the *802.1X Port-Based Authentication* chapter:

- [802.1X with Remote RADIUS Authentication](#)
- [802.1X with Local EAP Authentication](#)
- [Router as 802.1X Supplicant](#)

The MKA participant with 802.1X PAE role as **authenticator** acts as the key server and the **supplicant** acts as the non-key server.

When the 802.1X PAE role for the interface is configured as **authenticator** or **both**, then you must configure the dot1x **host-mode** under the authenticator sub mode as **single-host** or **multi-host** in order to bring up the MACsec EAP session. For details, see [802.1X host-modes](#).

Configure MACSec EAP on an Interface

The following section describes the steps to configure MACSec EAP on an interface.

Configuration Example

```
Router#configure
Router(config)#interface HundredGigE 0/1/1/2
Router(config-if)#macsec eap
Router(config-if)#commit
```

Running Configuration

```
Router#show run interface HundredGigE 0/1/1/2
interface HundredGigE 0/1/1/2
    macsec eap
!
```

You can also configure MACSec EAP on an interface by specifying the configured MACSec policy name.

Configuration Example

```
Router(config-if)#macsec eap policy test-macsec-policy
```

Running Configuration

```
Router#show run interface HundredGigE 0/1/1/2
interface HundredGigE 0/1/1/2
    macsec eap policy test-macsec-policy
!
```

Verify MACSec EAP Configuration on an Interface

You can use these commands to verify the MACSec EAP configuration:

- **show macsec mka session interface**

Sample output:

```
Router# show macsec mka session interface HundredGigE 0/1/1/2
=====
Interface-Name   Local-TxSCI      #Peers Status  Key-Server PSK/EAP CKN
=====
Hu0/1/12         0201.9ab0.85af/0001  1   Secured YES      EAP      A94399 ...
```

• **show macsec mka session interface detail**

Sample output:

```
Router# show macsec mka session interface HundredGigE 0/1/1/2 detail

MKA Detailed Status for MKA Session
=====
Status                                     : SECURED - Secured MKA Session with MACsec

Local Tx-SCI                             : 0201.9ab0.85af/0001
Local Tx-SSCI                             : 2
Interface MAC Address                     : 0201.9ab0.85af
MKA Port Identifier                       : 1
Interface Name                           : Hu0/1/1/2
CAK Name (CKN)                           : A94399EE68B2A455F85527A4309485DA
CA Authentication Mode                    : EAP
Keychain                                 : NA (EAP mode)
Member Identifier (MI)                    : 3222A4A7678A6BDA553FDB54
Message Number (MN)                      : 114
Authenticator                            : YES
Key Server                               : YES
MKA Cipher Suite                          : AES-128-CMAC
Configured MACSec Cipher Suite            : GCM-AES-XPB-256
Latest SAK Status                         : Rx & Tx
Latest SAK AN                             : 1
Latest SAK KI (KN)                       : 3222A4A7678A6BDA553FDB5400000001 (1)
Old SAK Status                           : No Rx, No Tx
Old SAK AN                               : 0
Old SAK KI (KN)                          : RETIRED (0)
SAK Transmit Wait Time                    : 0s (Not waiting for any peers to respond)
SAK Retire Time                           : 0s (No Old SAK to retire)
Time to SAK Rekey                         : NA
MKA Policy Name                           : *DEFAULT POLICY*
Key Server Priority                        : 16
Delay Protection                          : FALSE
Replay Window Size                        : 64
Include ICV Indicator                     : FALSE
Confidentiality Offset                    : 0
Algorithm Agility                         : 80C201
SAK Cipher Suite                          : 0080C20001000004 (GCM-AES-XPB-256)
MACsec Capability                         : 3 (MACsec Integrity, Confidentiality, &
Offset)
MACsec Desired                           : YES

# of MACsec Capable Live Peers            : 1
# of MACsec Capable Live Peers Responded : 1
```

Live Peer List:

MI	MN	Rx-SCI (Peer)	SSCI	KS-Priority
86B47DE76B42D9D7AB6805F7	113	0257.3fae.5cda/0001	1	16

Potential Peer List:

MI	MN	Rx-SCI (Peer)	SSCI	KS-Priority
----	----	---------------	------	-------------

Peers Status:

```

Last Tx MKPDU      : 2018 Mar 01 13:36:56.450
Peer Count         : 1
RxSCI              : 02573FAE5CDA0001
MI                 : 86B47DE76B42D9D7AB6805F7
Peer CAK           : Match
Latest Rx MKPDU    : 2018 Mar 01 13:36:56.450

```

- **show macsec mka summary**

Sample output:

```
Router#show macsec mka summary
```

```

=====
Interface-Name Status  Cipher-Suite  KeyChain      PSK/EAP  CKN
=====
Hu0/1/12       Secured  GCM-AES-XPN-256 NA (EAP mode) EAP       A94399 ...

```

```

Total MACSec Sessions : 1
Secured Sessions      : 1
Pending Sessions      : 0

```