



Configure Segment Routing for BGP

Border Gateway Protocol (BGP) is an Exterior Gateway Protocol (EGP) that allows you to create loop-free inter-domain routing between autonomous systems. An autonomous system is a set of routers under a single technical administration. Routers in an autonomous system can use multiple Interior Gateway Protocols (IGPs) to exchange routing information inside the autonomous system and an EGP to route packets outside the autonomous system.

This module provides the configuration information used to enable Segment Routing for BGP.



Note For additional information on implementing BGP on your router, see the *BGP Configuration Guide for Cisco NCS 5500 Series Routers*.

- [Segment Routing for BGP, on page 1](#)
- [Configure BGP Prefix Segment Identifiers, on page 2](#)
- [Segment Routing Egress Peer Engineering, on page 3](#)
- [Configure BGP Link-State, on page 9](#)
- [BGP-LS Northbound API on LSLIB server, on page 13](#)
- [Configurable Filters for IS-IS Advertisements to BGP-Link State, on page 24](#)
- [Use Case: Configuring SR-EPE and BGP-LS, on page 26](#)
- [Configure BGP Proxy Prefix SID, on page 28](#)
- [BGP Best Path Computation using SR Policy Paths, on page 35](#)
- [Optimal Utilization of ECMP FEC Resources, on page 41](#)
- [SRv6 double recursion for multilayer BGP underlay , on page 44](#)

Segment Routing for BGP

In a traditional BGP-based data center (DC) fabric, packets are forwarded hop-by-hop to each node in the autonomous system. Traffic is directed only along the external BGP (eBGP) multipath ECMP. No traffic engineering is possible.

In an MPLS-based DC fabric, the eBGP sessions between the nodes exchange BGP labeled unicast (BGP-LU) network layer reachability information (NLRI). An MPLS-based DC fabric allows any leaf (top-of-rack or border router) in the fabric to communicate with any other leaf using a single label, which results in higher packet forwarding performance and lower encapsulation overhead than traditional BGP-based DC fabric.

However, since each label value might be different for each hop, an MPLS-based DC fabric is more difficult to troubleshoot and more complex to configure.

BGP has been extended to carry segment routing prefix-SID index. BGP-LU helps each node learn BGP prefix SIDs of other leaf nodes and can use ECMP between source and destination. Segment routing for BGP simplifies the configuration, operation, and troubleshooting of the fabric. With segment routing for BGP, you can enable traffic steering capabilities in the data center using a BGP prefix SID.



Note BGP flowspec support with SRv6 - Limitations

List of BGP address families interacts with SRv6. There are some supported and unsupported BGP address family for the interaction with SRv6.

Supported address family:

- address-families ipv6.

Unsupported address families:

- address-families ipv4
 - vpv4
 - vpv6
-

Configure BGP Prefix Segment Identifiers

Segments associated with a BGP prefix are known as BGP prefix SIDs. The BGP prefix SID is global within a segment routing or BGP domain. It identifies an instruction to forward the packet over the ECMP-aware best-path computed by BGP to the related prefix. The BGP prefix SID is manually configured from the segment routing global block (SRGB) range of labels.

Each BGP speaker must be configured with an SRGB using the **segment-routing global-block** command. See the [About the Segment Routing Global Block](#) section for information about the SRGB.



Note You must enable SR and explicitly configure the SRGB before configuring SR BGP. The SRGB must be explicitly configured, even if you are using the default range (16000 – 23999). BGP uses the SRGB and the index in the BGP prefix-SID attribute of a learned BGP-LU advertisement to allocate a local label for a given destination.

If SR and the SRGB are enabled after configuring BGP, then BGP is not aware of the SRGB, and therefore it allocates BGP-LU local labels from the dynamic label range instead of from the SRGB. In this case, restart the BGP process in order to allocate BGP-LU local labels from the SRGB.



Note Because the values assigned from the range have domain-wide significance, we recommend that all routers within the domain be configured with the same range of values.

To assign a BGP prefix SID, first create a routing policy using the **set label-index** *index* attribute, then associate the index to the node.



Note A routing policy with the **set label-index** attribute can be attached to a network configuration or redistribute configuration. Other routing policy language (RPL) configurations are possible. For more information on routing policies, refer to the "Implementing Routing Policy" chapter in the *Routing Configuration Guide for Cisco NCS 5500 Series Routers*.

Example

The following example shows how to configure the SRGB, create a BGP route policy using a \$SID parameter and **set label-index** attribute, and then associate the prefix-SID index to the node.

```
RP/0/RSP0/CPU0:router(config)# segment-routing global-block 16000 23999

RP/0/RSP0/CPU0:router(config)# route-policy SID($SID)
RP/0/RSP0/CPU0:router(config-rpl)# set label-index $SID
RP/0/RSP0/CPU0:router(config-rpl)# end policy

RP/0/RSP0/CPU0:router(config)# router bgp 1
RP/0/RSP0/CPU0:router(config-bgp)# bgp router-id 10.1.1.1
RP/0/RSP0/CPU0:router(config-bgp)# address-family ipv4 unicast
RP/0/RSP0/CPU0:router(config-bgp-af)# network 10.1.1.3/32 route-policy SID(3)
RP/0/RSP0/CPU0:router(config-bgp-af)# allocate-label all
RP/0/RSP0/CPU0:router(config-bgp-af)# commit
RP/0/RSP0/CPU0:router(config-bgp-af)# end

RP/0/RSP0/CPU0:router# show bgp 10.1.1.3/32
BGP routing table entry for 10.1.1.3/32
Versions:
  Process          bRIB/RIB   SendTblVer
  Speaker          74         74
  Local Label: 16003
Last Modified: Sep 29 19:52:18.155 for 00:07:22
Paths: (1 available, best #1)
  Advertised to update-groups (with more than one peer):
    0.2
  Path #1: Received by speaker 0
  Advertised to update-groups (with more than one peer):
    0.2
  3
  99.3.21.3 from 99.3.21.3 (10.1.1.3)
    Received Label 3
    Origin IGP, metric 0, localpref 100, valid, external, best, group-best
    Received Path ID 0, Local Path ID 1, version 74
    Origin-AS validity: not-found
    Label Index: 3
```

Segment Routing Egress Peer Engineering

Segment routing egress peer engineering (EPE) uses a controller to instruct an ingress provider edge, or a content source (node) within the segment routing domain, to use a specific egress provider edge (node) and

a specific external interface to reach a destination. BGP peer SIDs are used to express source-routed inter-domain paths.

Below are the BGP-EPE peering SID types:

- **PeerNode SID**—To an eBGP peer. Pops the label and forwards the traffic on any interface to the peer.
- **PeerAdjacency SID**—To an eBGP peer via interface. Pops the label and forwards the traffic on the related interface.
- **PeerSet SID**—To a set of eBGP peers. Pops the label and forwards the traffic on any interface to the set of peers. All the peers in a set might not be in the same AS.

Multiple PeerSet SIDs can be associated with any combination of PeerNode SIDs or PeerAdjacency SIDs.

The controller learns the BGP peer SIDs and the external topology of the egress border router through BGP-LS EPE routes. The controller can program an ingress node to steer traffic to a destination through the egress node and peer node using BGP labeled unicast (BGP-LU).

EPE functionality is only required at the EPE egress border router and the EPE controller.

Usage Guidelines and Limitations

- When enabling BGP EPE, you must enable MPLS encapsulation on the egress interface connecting to the eBGP peer. This can be done by enabling either BGP labeled unicast (BGP-LU) address family or MPLS static for the eBGP peer.

For information about BGP-LU, refer to the “[Implementing BGP](#)” chapter in the *BGP Configuration Guide for Cisco NCS 5500 Series Routers*.

For information about MPLS static, refer to the “[Implementing MPLS Static Labeling](#)” chapter in the *MPLS Configuration Guide for NCS 5500 Series Routers*.

- When configuring SRv6 BGP with stitching and non-stitching VRFs between the same peers, you must enable the CLI knob **label mode per-nexthop-received-label** to avoid GRID full memory error while scaling the non-stitching VRFs. The stitching-VRF is used in SRv6 Interworking Gateway case (IW-GW)
- Note the following points related to the Ip-lookup backup support for EPEs:
 - This feature works only when you enable the **epe backup enable**, under the Global Address Family ID (AFI).
 - With this feature, an IP-Lookup backup is installed for each Egress Peer Engineering. This means, when all the paths of that EPE go down, the Forwarding Information Base (FIB) table searches in the IP table for the destination IP address in the data packet and forwards them accordingly.
 - The peer-set EPEs have a backup installed only when the mentioned CLI knob is enabled.

Configure Segment Routing Egress Peer Engineering

This task explains how to configure segment routing EPE on the EPE egress node.

SUMMARY STEPS

1. **router bgp** *as-number*
2. **neighbor** *ip-address*
3. **remote-as** *as-number*
4. **egress-engineering**
5. **exit**
6. **mpls static**
7. **interface** *type interface-path-id*
8. Use the **commit** or **end** command.

DETAILED STEPS

Procedure

	Command or Action	Purpose
Step 1	router bgp <i>as-number</i> Example: RP/0/RSP0/CPU0:router(config)# router bgp 1	Specifies the BGP AS number and enters the BGP configuration mode, allowing you to configure the BGP routing process.
Step 2	neighbor <i>ip-address</i> Example: RP/0/RSP0/CPU0:router(config-bgp)# neighbor 192.168.1.3	Places the router in neighbor configuration mode for BGP routing and configures the neighbor IP address as a BGP peer.
Step 3	remote-as <i>as-number</i> Example: RP/0/RSP0/CPU0:router(config-bgp-nbr)# remote-as 3	Creates a neighbor and assigns a remote autonomous system number to it.
Step 4	egress-engineering Example: RP/0/RSP0/CPU0:router(config-bgp-nbr)# egress-engineering	Configures the egress node with EPE for the eBGP peer.
Step 5	exit Example: RP/0/RSP0/CPU0:router(config-bgp-nbr)# exit RP/0/RSP0/CPU0:router(config-bgp)# exit RP/0/RSP0/CPU0:router(config)#	

	Command or Action	Purpose
Step 6	mpls static Example: RP/0/RSP0/CPU0:router(config)# mpls static	Configure MPLS static on the egress interface connecting to the eBGP peer.
Step 7	interface type interface-path-id Example: RP/0/RSP0/CPU0:router(config-mpls-static)# interface GigabitEthernet0/0/1/2	Specifies the egress interface connecting to the eBGP peer.
Step 8	Use the commit or end command.	commit —Saves the configuration changes and remains within the configuration session. end —Prompts user to take one of these actions: <ul style="list-style-type: none"> • Yes — Saves configuration changes and exits the configuration session. • No —Exits the configuration session without committing the configuration changes. • Cancel —Remains in the configuration session, without committing the configuration changes.

Example**Running Config:**

```

router bgp 1
  neighbor 192.168.1.3
    remote-as 3
    egress-engineering
  !
!
mpls static
  interface GigabitEthernet0/0/1/2
  !
!

```

Configuring Manual BGP-EPE Peering SIDs

Configuring manual BGP-EPE Peer SIDs allows for persistent EPE label values. Manual BGP-EPE SIDs are advertised through BGP-LS and are allocated from the Segment Routing Local Block (SRLB). See [Configure Segment Routing Global Block and Segment Routing Local Block](#) for information about the SRLB.

Each PeerNode SID, PeerAdjacency SID, and PeerSet SID is configured with an index value. This index serves as an offset from the configured SRLB start value and the resulting MPLS label (SRLB start label + index) is assigned to these SIDs. This label is used by CEF to perform load balancing across the individual

BGP PeerSet SIDs, BGP PeerNode SID, or ultimately across each first-hop adjacency associated with that BGP PeerNode SID or BGP PeerSet SID.

Configuring Manual PeerNode SID

Each eBGP peer will be associated with a PeerNode SID index that is configuration driven.

```
RP/0/0/CPU0:PE1(config)# router bgp 10
RP/0/0/CPU0:PE1(config-bgp)# neighbor 10.10.10.2
RP/0/0/CPU0:PE1(config-bgp-nbr)# remote-as 20
RP/0/0/CPU0:PE1(config-bgp-nbr)# egress-engineering
RP/0/0/CPU0:PE1(config-bgp-nbr)# peer-node-sid index 600
```

Configuring Manual PeerAdjacency SID

Any first-hop for which an adjacency SID is configured needs to be in the resolution chain of at least one eBGP peer that is configured for egress-peer engineering. Otherwise such a kind of “orphan” first-hop with regards to BGP has no effect on this feature. This is because BGP only understands next-hops learnt by the BGP protocol itself and in addition only the resolving IGP next-hops for those BGP next-hops.

```
RP/0/0/CPU0:PE1(config)# router bgp 10
RP/0/0/CPU0:PE1(config-bgp)# adjacencies
RP/0/0/CPU0:PE1(config-bgp-adj)# 10.1.1.2
RP/0/0/CPU0:PE1(config-bgp-adj)# adjacency-sid index 500
```

Configuring Manual PeerSet SID


The PeerSet SID is configured under global Address Family. This configuration results in the creation of a Peer-Set SID EPE object.

```
RP/0/0/CPU0:PE1(config)# router bgp 10
RP/0/0/CPU0:PE1(config-bgp)# address-family ipv4 unicast
RP/0/0/CPU0:PE1(config-bgp-afi)# peer-set-id 1
RP/0/0/CPU0:PE1(config-bgp-peer-set)# peer-set-sid 300
```

Example

Topology

The example in this section uses the following topology.



In this example, BGP-EPE peer SIDs are allocated from the default SRLB label range (15000 – 15999). The BGP-EPE peer SIDs are configured as follows:

- PeerNode SIDs to 10.10.10.2 with index 600 (label 15600), and for 20.10.10.2 with index 700 (label 15700)
- PeerAdj SID to link 10.1.1.2 with index 500 (label 15500)
- PeerSet SID 1 to load balance over BGP neighbors 10.10.10.1 and 20.10.10.2 with SID index 300 (label 15300)
- PeerSet SID 2 to load balance over BGP neighbor 20.10.10.2 and link 10.1.1.2 with SID index 400 (label 15400)

Configuration on R1

```
router bgp 10
address-family ipv4 unicast
  peer-set-id 1
  peer-set-sid index 300
  !
  peer-set-id 2
  peer-set-sid index 400
  !
!
adjacencies
10.1.1.2
  adjacency-sid index 500
  peer-set 2
  !
!
neighbor 10.10.10.2
remote-as 20
egress-engineering
peer-node-sid index 600
peer-set 1
!
neighbor 20.10.10.2
egress-engineering
peer-node-sid index 700
peer-set 1
```

```
peer-set 2  
!
```

To further show the load balancing of this example:

- 15600 is load balanced over {10.1.1.1 and 2.1.1.1}
- 15700 is load balanced over {3.1.1.1 and 4.1.1.1}
- 15500 is load balanced over {10.1.1.1}
- 15300 is load balanced over {10.1.1.1, 2.1.1.1, 3.1.1.1 and 4.1.1.1}
- 15400 is load balanced over {10.1.1.1, 3.1.1.1 and 4.1.1.1}


Configure BGP Link-State

BGP Link-State (LS) is an Address Family Identifier (AFI) and Sub-address Family Identifier (SAFI) originally defined to carry interior gateway protocol (IGP) link-state information through BGP. The BGP Network Layer Reachability Information (NLRI) encoding format for BGP-LS and a new BGP Path Attribute called the BGP-LS attribute are defined in [RFC7752](#). The identifying key of each Link-State object, namely a node, link, or prefix, is encoded in the NLRI and the properties of the object are encoded in the BGP-LS attribute.

The BGP-LS Extensions for Segment Routing are documented in [RFC9085](#).

BGP-LS applications like an SR Path Computation Engine (SR-PCE) can learn the SR capabilities of the nodes in the topology and the mapping of SR segments to those nodes. This can enable the SR-PCE to perform path computations based on SR-TE and to steer traffic on paths different from the underlying IGP-based distributed best-path computation.

The following figure shows a typical deployment scenario. In each IGP area, one or more nodes (BGP speakers) are configured with BGP-LS. These BGP speakers form an iBGP mesh by connecting to one or more route-reflectors. This way, all BGP speakers (specifically the route-reflectors) obtain Link-State information from all IGP areas (and from other ASes from eBGP peers).



Usage Guidelines and Limitations

- BGP-LS supports IS-IS and OSPFv2.
- The identifier field of BGP-LS (referred to as the Instance-ID) identifies the IGP routing domain where the NLRI belongs. The NRIs representing link-state objects (nodes, links, or prefixes) from the same IGP routing instance must use the same Instance-ID value.
- When there is only a single protocol instance in the network where BGP-LS is operational, we recommend configuring the Instance-ID value to **0**.
- Assign consistent BGP-LS Instance-ID values on all BGP-LS Producers within a given IGP domain.
- NRIs with different Instance-ID values are considered to be from different IGP routing instances.
- Unique Instance-ID values must be assigned to routing protocol instances operating in different IGP domains. This allows the BGP-LS Consumer (for example, SR-PCE) to build an accurate segregated multi-domain topology based on the Instance-ID values, even when the topology is advertised via BGP-LS by multiple BGP-LS Producers in the network.
- If the BGP-LS Instance-ID configuration guidelines are not followed, a BGP-LS Consumer may see duplicate link-state objects for the same node, link, or prefix when there are multiple BGP-LS Producers deployed. This may also result in the BGP-LS Consumers getting an inaccurate network-wide topology.

- The following table defines the supported extensions to the BGP-LS address family for carrying IGP topology information (including SR information) via BGP. For more information on the BGP-LS TLVs, refer to [Border Gateway Protocol - Link State \(BGP-LS\) Parameters](#).

Table 1: IOS XR Supported BGP-LS Node Descriptor, Link Descriptor, Prefix Descriptor, and Attribute TLVs

TLV Code Point	Description	Produced by IS-IS	Produced by OSPFv2	Produced by BGP
256	Local Node Descriptors	X	X	—
257	Remote Node Descriptors	X	X	—
258	Link Local/Remote Identifiers	X	X	—
259	IPv4 interface address	X	X	—
260	IPv4 neighbor address	X		
261	IPv6 interface address	X	—	—
262	IPv6 neighbor address	X	—	—
263	Multi-Topology ID	X	—	—
264	OSPF Route Type	—	X	—
265	IP Reachability Information	X	X	—
266	Node MSD TLV	X	X	—
267	Link MSD TLV	X	X	—
512	Autonomous System	—	—	X
513	BGP-LS Identifier	—	—	X
514	OSPF Area-ID	—	X	—
515	IGP Router-ID	X	X	—
516	BGP Router-ID TLV	—	—	X
517	BGP Confederation Member TLV	—	—	X
1024	Node Flag Bits	X	X	—
1026	Node Name	X	X	—
1027	IS-IS Area Identifier	X	—	—
1028	IPv4 Router-ID of Local Node	X	X	—
1029	IPv6 Router-ID of Local Node	X	—	—
1030	IPv4 Router-ID of Remote Node	X	X	—
1031	IPv6 Router-ID of Remote Node	X	—	—
1034	SR Capabilities TLV	X	X	—
1035	SR Algorithm TLV	X	X	—
1036	SR Local Block TLV	X	X	—

TLV Code Point	Description	Produced by IS-IS	Produced by OSPFv2	Produced by BGP
1039	Flex Algo Definition (FAD) TLV	X	X	—
1044	Flex Algorithm Prefix Metric (FAPM) TLV	X	X	—
1088	Administrative group (color)	X	X	—
1089	Maximum link bandwidth	X	X	—
1090	Max. reservable link bandwidth	X	X	—
1091	Unreserved bandwidth	X	X	—
1092	TE Default Metric	X	X	—
1093	Link Protection Type	X	X	—
1094	MPLS Protocol Mask	X	X	—
1095	IGP Metric	X	X	—
1096	Shared Risk Link Group	X	X	—
1099	Adjacency SID TLV	X	X	—
1100	LAN Adjacency SID TLV	X	X	—
1101	PeerNode SID TLV	—	—	X
1102	PeerAdj SID TLV	—	—	X
1103	PeerSet SID TLV	—	—	X
1114	Unidirectional Link Delay TLV	X	X	—
1115	Min/Max Unidirectional Link Delay TLV	X	X	—
1116	Unidirectional Delay Variation TLV	X	X	—
1117	Unidirectional Link Loss	X	X	—
1118	Unidirectional Residual Bandwidth	X	X	—
1119	Unidirectional Available Bandwidth	X	X	—
1120	Unidirectional Utilized Bandwidth	X	X	—
1122	Application-Specific Link Attribute TLV	X	X	—
1152	IGP Flags	X	X	—
1153	IGP Route Tag	X	X	—
1154	IGP Extended Route Tag	X	—	—
1155	Prefix Metric	X	X	—
1156	OSPF Forwarding Address	—	X	—
1158	Prefix-SID	X	X	—
1159	Range	X	X	—

TLV Code Point	Description	Produced by IS-IS	Produced by OSPFv2	Produced by BGP
1161	SID/Label TLV	X	X	—
1170	Prefix Attribute Flags	X	X	—
1171	Source Router Identifier	X	—	—
1172	L2 Bundle Member Attributes TLV	X	—	—
1173	Extended Administrative Group	X	X	—

Exchange Link State Information with BGP Neighbor

The following example shows how to exchange link-state information with a BGP neighbor:

```
Router# configure
Router(config)# router bgp 1
Router(config-bgp)# neighbor 10.0.0.2
Router(config-bgp-nbr)# remote-as 1
Router(config-bgp-nbr)# address-family link-state link-state
Router(config-bgp-nbr-af)# exit
```

IGP Link-State Database Distribution

A given BGP node may have connections to multiple, independent routing domains. IGP link-state database distribution into BGP-LS is supported for both OSPF and IS-IS protocols in order to distribute this information on to controllers or applications that desire to build paths spanning or including these multiple domains.

To distribute IS-IS link-state data using BGP-LS, use the **distribute link-state** command in router configuration mode.

```
Router# configure
Router(config)# router isis isp
Router(config-isis)# distribute link-state instance-id 32
```

To distribute OSPFv2 link-state data using BGP-LS, use the **distribute link-state** command in router configuration mode.

```
Router# configure
Router(config)# router ospf 100
Router(config-ospf)# distribute link-state instance-id 32
```

BGP-LS Northbound API on LSLIB server

BGP-LS Northbound API on LSLIB server is an API that facilitates the collection and sharing of the following information with the external components

- Link state information from IGP,
- Link state AF and Egress peer engineering information from BGP, and

- SR Policy information from PCE and Headend Nodes.

The Cisco Crosswork Optimization Engine is an application that makes use of BGP-LS northbound API to provide services such as topology visualizer and policy provisioning. For more information, refer to the [Cisco Crosswork Optimization Engine User Guides](#).

Table 2: Feature History Table

Feature Name	Release Information	Feature Description
gRPC based North Bound API for BGP-LS objects	Release 25.2.1	<p>Introduced in this release on: NCS 5500 fixed port routers; NCS 5700 fixed port routers; NCS 5500 modular routers (NCS 5500 line cards; NCS 5700 line cards [Mode: Native])</p> <p>This gRPC-based API exports BGP-LS topology objects, which include Nodes, Links, IPv4 and IPv6 Prefixes, SRv6 SIDs, and SR Policy Candidate Paths. The API is designed to provide real-time updates to external controllers and applications, enabling them to perform tasks such as re-optimization, service placement, and network visualization.</p> <p>For more information, refer to the Cisco Crosswork Optimization Engine User Guides.</p>

The LSLIB Server is a newly introduced component in Cisco IOS XR Release 25.2.1, designed to act as a centralized cache and service backend for all BGP Link-State (BGP-LS) information. It plays a pivotal role in enabling scalable, secure, and efficient northbound APIs (NB-APIs) for topology data distribution.

Configure BGP-LS Northbound API on LSLIB server

Use this procedure to enable the LSLIB server.

Before you begin

Ensure the router is running a compatible version of Cisco IOS-XR Release 25.2.1 and later versions that support the NB-API for BGP-LS feature.

Procedure

-
- Step 1** Run the **service-layer** command under the gRPC sub-mode to enable BGP-LS Topology Service. The BGP-LS topology service, which is part of the service-layer, is disabled by default.

Example:

```
Router# configure
Router(config)# grpc
Router(config-grpc)# service-layer
Router(config-grpc)# commit
```

Step 2 Run the **lslib-server** command under configuration mode to enable LSLIB server.

The LSLIB server process is disabled by default.

Example:

```
Router# config
Router(config)# lslib-server
Router(config-lslib)# commit
```

Verify BGP-LS Northbound API on LSLIB server

The purpose of this task is to verify the configured northbound API details.

Procedure

Step 1 Run the **show lslib** command to provide details on the LSLIB server.

Example:

```
Router#show lslib ?
  cache  Show cache data for the LSLIB Client processes
  server  Show LSLIB Server process related info
  trace   Show trace data for the LSLIB

Router#show lslib server ?
  connection  gRPC Clients connection information
  memory      Show memory information of the LSLIB Server process
  producer    Show producers information of the LSLIB Server process
  topology-db Show topology data in the LSLIB Server process
  trace       Show trace data for the LSLIB Server
  |           Output Modifiers
  <cr>
Router#
```

Step 2 Run the **show lslib server topology-db** command to list NLRIs and their lengths in bits. The length helps you to efficiently fetch the matching NLRI from the radix tree.

Example:

```
Router#show lslib server topology-db

Prefix codes: E link, V node, T IP reachable route, S SRv6 SID, SP SRTE Policy, u/U unknown
               I Identifier, N local node, R remote node, L link, P prefix, S SID, C candidate path
               L1/L2 ISIS level-1/level-2, O OSPF, D direct, ST static/peer-node, SR Segment Routing
               a area-ID, l link-ID, t topology-ID, s ISO-ID,
               c confed-ID/ASN, b bgp-identifier, r router-ID, te te-router-ID, sd SID
```

```

i if-address, n nbr-address, o OSPF Route-type, p IP-prefix
d designated router address, po protocol-origin, f flag
e endpoint-ip, cl color, as originator-asn oa originator-address
di discriminator
[V] [L1] [I0x0] [N[c100] [b192.168.0.1] [s0000.0000.0001.00]]/328
[V] [L1] [I0x0] [N[c100] [b192.168.0.1] [s0000.0000.0002.00]]/328
[V] [L2] [I0x0] [N[c100] [b192.168.0.1] [s0000.0000.0002.00]]/328
[V] [L2] [I0x0] [N[c100] [b192.168.0.1] [s0000.0000.0003.00]]/328
...
[E] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.1]] [R[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.2d10.10.10.2]] [L[i10.10.10.1] [n10.10.10.2]]/824
[E] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.1]] [R[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.2d11.11.11.2]] [L[i11.11.11.1] [n11.11.11.2]]/824
...
[T] [L2] [I0x0] [N[c100] [b192.168.0.1] [s0000.0000.0003.00]] [P[p192.168.1.4/32]]/400
[T] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.1]] [P[o0x01] [p192.168.0.1/32]]/488
[T] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.2]] [P[o0x01] [p192.168.0.2/32]]/488
[T] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.4d14.14.14.4]] [P[o0x01] [p14.14.14.0/24]]/512
[T] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.4d15.15.15.4]] [P[o0x01] [p15.15.15.0/24]]/512
...
Retrieved 66 entries

```

Step 3 Run the `show lslib server topology-db <nlri/len>` command to display details of a single NLRI and its attributes.

Example:

```

Router#show lslib server topology-db
[T] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.2d10.10.10.2]] [P[o0x01] [p10.10.10.0/24]]/512

NLRI:
[T] [O] [I0x0] [N[c100] [b192.168.0.1] [a0.0.0.0] [r192.168.0.2d10.10.10.2]] [P[o0x01] [p10.10.10.0/24]]/512
NLRI Length: 64 bytes
Attribute Length: 8 bytes
Producers:
  0, ospf
  0, bgp
NLRI Type: Prefix
Protocol: OSPF
Identifier: 0x0
Local Node Descriptor:
  AS Number: 100
  BGP Identifier: 192.168.0.1
  Area ID: 0.0.0.0
  Router ID IPv4: 192.168.0.2
  Designated Router Address: 10.10.10.2
Prefix Descriptor:
  OSPF Route Type: 0x01
  Prefix: 10.10.10.0/24

Attributes: Metric: 0

```

Step 4 Run the `show lslib server connection` command to list all the active gRPC client connections with the LSLIB server.

Example:

```

Router# show lslib server connection

LSLIB Server - Client Information
C - Connected, E - EOD Sent, S - SOD Sent

ID      Status  Up-Time  Statistics
5       CES     00:17:42 326/8/0

```

6 CES 00:08:57 119/0/0

Router# **show lslib server connection detail**
 LSLIB Server - Client Information

Client Channel Identifier: 5
 VRF Name: default
 Subscribed: Oct 28 12:35:13
 Connected: Yes
 Up Time: 00:18:38
 EOD added: Yes
 SOD sent at: Oct 28 12:35:13.258
 EOD sent at: Oct 28 12:35:13.259
 Number of Match Filters: 0
 Initial Data Statistics:

NLRI	Filter Matched			Filter Unmatched		
	Update	Delete	Error	Update	Delete	Error
Node	13	0	0	0	0	0
Link	24	0	0	0	0	0
Prefix	269	0	0	0	0	0
SRv6 SID	1	0	0	0	0	0
SR Policy	7	0	0	0	0	0
Unknown	-	-	0	-	-	0
Total	314	0	0	0	0	0

Statistics:

Markers

SOD 1
 EOD 1

NLRI	Filter Matched			Filter Unmatched		
	Update	Delete	Error	Update	Delete	Error
Node	14	1	0	0	0	0
Link	32	4	0	0	0	0
Prefix	272	3	0	0	0	0
SRv6 SID	1	0	0	0	0	0
SR Policy	7	0	0	0	0	0
Unknown	-	-	0	-	-	0
Total	326	8	0	0	0	0

Client Channel Identifier: 6
 VRF Name: default
 Subscribed: Oct 28 12:43:58
 Connected: Yes
 Up Time: 00:09:53
 EOD added: Yes
 SOD sent at: Oct 28 12:43:58.415
 EOD sent at: Oct 28 12:43:58.415
 Number of Match Filters: 1
 Match Filter: #1
 Identifier: 0
 Protocol: OSPF

Initial Data Statistics:

NLRI	Filter Matched			Filter Unmatched		
	Update	Delete	Error	Update	Delete	Error
Node	7	0	0	0	0	0
Link	16	0	0	0	0	0
Prefix	96	0	0	0	0	0
SRv6 SID	0	0	0	0	0	0
SR Policy	0	0	0	0	0	0
Unknown	-	-	0	-	-	0
Total	119	0	0	0	0	0

Statistics:

Markers						
SOD	1					
EOD	1					
	Filter Matched			Filter Unmatched		
NLRI	Update	Delete	Error	Update	Delete	Error
Node	7	0	0	6	0	0
Link	16	0	0	8	0	0
Prefix	96	0	0	173	0	0
SRv6 SID	0	0	0	1	0	0
SR Policy	0	0	0	7	0	0
Unknown	-	-	0	-	-	0
Total	119	0	0	195	0	0

Step 5 Run the `show lslib server producer` command to list all the active BGP-LS producers in the LSLIB server.

Example:

```
Router#show lslib server producer
LSLIB Server - Producer Informatio
  Producer Instance-Id Up-Time Statistics
  bgp      0           2d03h  615/256/0
  xtc-agent 0           2d03h  18/5/0
  bgp-epe  0           2d03h  0/0/0
  ospf     0           2d03h  457/98/0
  isis     0           2d03h  543/154/0
Router#
```

```
Router#show lslib server producer detail
LSLIB Server - Producer Information
```

```
Producer: bgp
Instance Identifier: 0
Local Identifier: 1
Connected at: Oct 26 09:25:00
Up Time: 2d03h
SOD received at: Oct 26 09:25:00.524
EOD received at: Oct 26 09:25:00.525
EOD Pending: No
EOD Timer running: No
Checkpointed: Yes
Statistics:
  Markers
  SOD      1
  EOD      1
  InitialData
  NLRI     Update Delete Error Cumulative
  Node    13      0      0      41      1      0
  Link    24      0      0      38      8      0
  Prefix  29      0      0      517     242    0
  SRv6 SID 0      0      0      1       0      0
  SR Policy 1      0      0      18      5      0
  Unknown  -       -       0      -       -       0
  Total   67      0      0      615     256    0
```

```
Producer: xtc-agent
Instance Identifier: 0
Local Identifier: 2
Connected at: Oct 26 09:25:00
Up Time: 2d03h
SOD received at: Oct 26 09:25:00.681
EOD received at: Oct 26 09:25:00.681
EOD Pending: No
EOD Timer running: No
```

Checkpointed: Yes

Statistics:

Markers

SOD 1
EOD 1

NLRI	InitialData			Cumulative		
	Update	Delete	Error	Update	Delete	Error
Node	0	0	0	0	0	0
Link	0	0	0	0	0	0
Prefix	0	0	0	0	0	0
SRv6 SID	0	0	0	0	0	0
SR Policy	0	0	0	18	5	0
Unknown	-	-	0	-	-	0
Total	0	0	0	18	5	0

Producer: bgp-epe

Instance Identifier: 0

Local Identifier: 4

Connected at: Oct 26 09:25:01

Up Time: 2d03h

SOD received at: Oct 26 09:25:01.211

EOD received at: Oct 26 09:25:01.211

EOD Pending: No

EOD Timer running: No

Checkpointed: Yes

Statistics:

Markers

SOD 1
EOD 1

NLRI	InitialData			Cumulative		
	Update	Delete	Error	Update	Delete	Error
Node	0	0	0	0	0	0
Link	0	0	0	0	0	0
Prefix	0	0	0	0	0	0
SRv6 SID	0	0	0	0	0	0
SR Policy	0	0	0	0	0	0
Unknown	-	-	0	-	-	0
Total	0	0	0	0	0	0

Producer: ospf

Instance Identifier: 0

Local Identifier: 5

Connected at: Oct 26 09:37:59

Up Time: 2d03h

SOD received at: Oct 26 09:37:59.155

EOD received at: Oct 26 09:37:59.168

EOD Pending: No

EOD Timer running: No

Checkpointed: Yes

Statistics:

Markers

SOD 5
EOD 1

NLRI	InitialData			Cumulative		
	Update	Delete	Error	Update	Delete	Error
Node	7	0	0	27	2	0
Link	16	0	0	113	4	0
Prefix	7	0	0	317	92	0
SRv6 SID	0	0	0	0	0	0
SR Policy	0	0	0	0	0	0
Unknown	-	-	0	-	-	0
Total	30	0	0	457	98	0

Producer: isis

```

Instance Identifier: 0
Local Identifier: 3
Connected at: Oct 26 09:38:52
Up Time: 2d03h
SOD received at: Oct 26 09:38:52.288
EOD received at: Oct 26 09:38:52.298
EOD Pending: No
EOD Timer running: No
Checkpointed: Yes
Statistics:
  Markers
  SOD      4
  EOD      1
      InitialData
  NLRI     Update   Delete   Error
  Node     6           0         0       38        0         0
  Link     8           0         0       64         4         0
  Prefix   19          0         0      440       150        0
  SRv6 SID 0           0         0         1          0         0
  SR Policy 0           0         0         0          0         0
  Unknown  -           -         0         -          -         0
  Total    33          0         0      543       154        0
Router#

```

Step 6 Run the **show service-layer bgp-ls** command to list all the gRPC clients subscribed for BGP-LS topology service plugin.

Example:

```

Router#show service-layer bgp-ls connection
BGP-LS - Connection Information

  C - Connected, E - EOD Sent, S - SOD Sent

ID   Client-IP      Port  Status  Up-Time  Statistics
5    127.0.0.1      51372 CES     00:30:30 326/8/0
6    127.0.0.1      57610 CES     00:21:45 119/0/0
Router#

```

```

Router#show service-layer bgp-ls connection detail
BGP-LS - Connection Information

```

```

Client Channel Identifier: 5
Address: 127.0.0.1:51372
VRF Name: default
Subscribed: Oct 28 12:35:13
Connected: Yes
Up Time: 00:30:58
SOD received at: Oct 28 12:35:13.259
EOD received at: Oct 28 12:35:13.260
Flow control: Status: Off Paused: 0 Resumed: 0
Number of Match Filters: 0
Decode Error Statistics:
      InitialData  Cumulative
  Node           0           0
  Link           0           0
  Prefix         0           0
  SRv6 SID       0           0
  SR Policy      0           0
  Unknown        0           0

Stream Statistics:
  SOD sent at: Oct 28 12:35:13.259
  EOD sent at: Oct 28 12:35:13.264
  Initial Data sent in: 00:00:00.004
  Data sent: 24 KB

```

```

Markers
SOD      1
EOD      1
          InitialData
NLRI     Update   Delete   Error    Cumulative
Node     13          0        0        Update   Delete   Error
Link     24          0        0        14       1        0
Prefix   269         0        0        32       4        0
SRv6 SID 1           0        0        272      3        0
SR Policy 7           0        0        1        0        0
Unknown  -           -        0        -         -        0
Total    314         0        0        326      8        0
Client Channel Identifier: 6
Address: 127.0.0.1:57610
VRF Name: default
Subscribed: Oct 28 12:43:58
Connected: Yes
Up Time: 00:22:13
SOD received at: Oct 28 12:43:58.415
EOD received at: Oct 28 12:43:58.415
Flow control: Status: Off Paused: 0 Resumed: 0
Number of Match Filters: 1
  Match Filter: #1
    Identifier: 0
    Protocol: OSPF

Decode Error Statistics:
          InitialData  Cumulative
Node     0                0
Link     0                0
Prefix   0                0
SRv6 SID 0                0
SR Policy 0                0
Unknown  0                0

Stream Statistics:
SOD sent at: Oct 28 12:43:58.415
EOD sent at: Oct 28 12:43:58.417
Initial Data sent in: 00:00:00.001
Data sent: 7 KB

Markers
SOD      1
EOD      1
          InitialData
NLRI     Update   Delete   Error    Cumulative
Node     7          0        0        Update   Delete   Error
Link     16         0        0        7        0        0
Prefix   96         0        0        16       0        0
SRv6 SID 0           0        0        96       0        0
SR Policy 0           0        0        0        0        0
Unknown  -           -        0        -         -        0
Total    119         0        0        119      0        0
Router#

```

```

Router#show service-layer bgp-ls connection history
BGP-LS - Connection History Information

```

C - Connected, E - EOD Sent, S - SOD Sent

```

Unsubscribed-At  ID      Client-IP      Port  Status  Up-Time  Statistics

```

```

Oct 28 12:32:10 2 127.0.0.1 37304 ES 2d15h 603/248/0
Oct 28 12:32:04 3 127.0.0.1 38982 ES 2d15h 28/2/0
Router#

```

Router#**show service-layer bgp-ls connection history detail**

BGP-LS - Connection History Information

```

Client Channel Identifier: 2
Address: 127.0.0.1:37304
VRF Name: default
Subscribed: Oct 26 09:35:39
Unsubscribed: Oct 28 12:32:10
Up Time: 2d15h
SOD received at: Oct 26 09:35:39.519
EOD received at: Oct 26 09:35:39.519
Flow control: Status: Off Paused: 0 Resumed: 0
Number of Match Filters: 0
Decode Error Statistics:

```

	InitialData	Cumulative
Node	0	0
Link	0	0
Prefix	0	0
SRv6 SID	0	0
SR Policy	0	0
Unknown	0	0

```

Stream Statistics:
SOD sent at: Oct 26 09:35:39.519
EOD sent at: Oct 26 09:35:39.521
Initial Data sent in: 00:00:00.001
Data sent: 57 KB

```

Markers

```

SOD 1
EOD 1

```

	InitialData			Cumulative		
NLRI	Update	Delete	Error	Update	Delete	Error
Node	0	0	0	40	0	0
Link	0	0	0	30	4	0
Prefix	0	0	0	514	239	0
SRv6 SID	0	0	0	1	0	0
SR Policy	0	0	0	18	5	0
Unknown	-	-	0	-	-	0
Total	0	0	0	603	248	0

```

Client Channel Identifier: 3
Address: 127.0.0.1:38982
VRF Name: default
Subscribed: Oct 26 09:36:02
Unsubscribed: Oct 28 12:32:04
Up Time: 2d15h
SOD received at: Oct 26 09:36:02.088
EOD received at: Oct 26 09:36:02.088
Flow control: Status: Off Paused: 0 Resumed: 0
Number of Match Filters: 3
Match Filter: #1
  Identifier: 0
  Protocol: IS-IS-L1
  NLRI Type: Node

Match Filter: #2
  Identifier: 0
  Protocol: IS-IS-L1
  NLRI Type: Link

```

```
Match Filter: #3
Identifier: 0
Protocol: IS-IS-L1
NLRI Type: IPv4 Prefix
```

```
Decode Error Statistics:
InitialData Cumulative
Node 0 0
Link 0 0
Prefix 0 0
SRv6 SID 0 0
SR Policy 0 0
Unknown 0 0
```

```
Stream Statistics:
SOD sent at: Oct 26 09:36:02.088
EOD sent at: Oct 26 09:36:02.088
Initial Data sent in: 00:00:00.000
Data sent: 3 KB
```

```
Markers
SOD 1
EOD 1
InitialData Cumulative
NLRI Update Delete Error Update Delete Error
Node 0 0 0 14 0 0
Link 0 0 0 6 2 0
Prefix 0 0 0 8 0 0
SRv6 SID 0 0 0 0 0 0
SR Policy 0 0 0 0 0 0
Unknown - - 0 - - 0
Total 0 0 0 28 2 0
```

Router#

Router#show service-layer bgpls memory chunk

Thu Oct 10 17:08:46.712 IST

LSLIB SL Client - Chunk Memory Information

Chunk Name	Frees	Count	Fails	Elements/ Num of	Elements	Element	Chunk	Total	Allocs
				Chunk Chunks	Inuse	Size(B)	Size(kB)	Size(kB)	
Notification				51 1	0	16	1	1	1969
1969	0		0						
Notif Entry				46 1	0	24	2	2	1927
1927	0		0						
Node Id				34 1	0	56	2	2	540
540	0		0						
Link Id				17 1	0	168	3	3	1010
1010	0		0						
Prefix Id				26 1	0	88	2	2	377
377	0		0						
SRTE Id				22 1	0	120	3	3	0
0	0		0						
SRv6 Id				28 1	0	80	2	2	0
0	0		0						
Node Attribute				22 1	0	120	3	3	348
348	0		0						
Link Attribute				13 1	0	232	3	3	1010
1010	0		0						
Prefix Attribute				22 1	0	120	3	3	377
377	0		0						
STRE Attribute				30 1	0	72	2	2	0
0	0		0						

```

SRv6 Attribute          39      1      0      40      2      2      0
0      0      0
Resume Notif           60      1      0      16      2      2      0
0      0      0

```

```

Router#show service-layer bgpls memory heap
LSLIB SL Client - Heap Memory Information

```

```

Mem Name           Allocs   Frees   Count   Fails   TotalBytes
Subscribe Notif    9        9        0        0        0
Unsubscribe Notif  4        4        0        0        0
Connection         9        0        9        0      2664
Match Filter       40       16       24       0      1928
Request Message    25       25       0        0        0
Connection Bag     16       16       0        0        0
Misc               0        0        0        0        0
Router#

```

Configurable Filters for IS-IS Advertisements to BGP-Link State

Table 3: Feature History Table

Feature Name	Release Information	Feature Description
Configurable Filters for IS-IS Advertisements to BGP-Link State	Release 7.10.1	<p>Introduced in this release on: NCS 5500 fixed port routers; NCS 5700 fixed port routers; NCS 5500 modular routers (NCS 5500 line cards; NCS 5700 line cards [Mode: Compatibility; Native])</p> <p>This feature allows you to configure a route map to filter IS-IS route advertisements to BGP-Link State (LS). It also provides a per-area configuration knob to disable IS-IS advertisements for external and propagated prefixes. This configuration of filters hence reduces the amount of redundant data for external and interarea prefixes sent to the BGP - LS clients.</p> <p>The feature introduces exclude-external, exclude-interarea, and route-policy <i>name</i> optional keywords in the distribute link-state command.</p>

In a large IS-IS network, there are multiple routers in different areas distributing their link-state databases through BGP-LS. In addition, other protocols, such as OSPF do their own BGP-LS reporting and have routes that are redistributed into IS-IS. This can result in substantial amounts of redundant data for external and interarea prefixes which are sent to the BGP-LS clients only to be discarded.

Rather than sending redundant information, this feature provides the option of limiting the prefixes for which IS-IS TLV information is sent to BGP-LS.

There are three options to filter prefix Type-Length-Values (TLVs) that are reported in BGP-LS and the operators can specify these options on a per-level basis:

- **exclude-external**: Omits information for external prefixes that are redistributed from a different protocol or instance. These are identified by the “X” bit set in its Extended Reachability Attribute Flags or the ‘X’ bit of TLVs 236 and 237.

- **exclude-interarea**: Omits information for interarea prefixes and summaries. These are identified by the 'R' bit set in their Extended Reachability Attribute Flags or the 'up or down' bit set in TLVs 135, 235, 236, and 237.
- **route-policyname**: Allows specification of a route-policy to provide filtering based on a set of destination prefixes.

The filtering is implemented at the point where the individual prefix TLVs are read from a label-switched path to generate updates to BGP-LS. It does not affect the advertisement of a node or the link information.

Configure Filters for IS-IS Advertisements to BGP-LS

Configuration Example

You can configure any of these filters for IS-IS advertisements to BGP-LS:

```
Router#config
Router(config)#router isis 1
Router(config-isis)#distribute link-state exclude-external
Router(config-isis)#commit
```

```
Router#config
Router(config)#router isis 1
Router(config-isis)#ddistribute link-state exclude-interarea
Router(config-isis)#commit
```

```
Router# config
Router(config)# router isis 1
Router(config-isis)#distribute link-state route-policy isis-rp-1
Router(config-isis)#commit
```



Note This feature does not introduce any new failure modes to IS-IS.

Running Configuration

To check the filter for IS-IS advertisements to BGP-LS, you can run the following command:

```
Router# show running-config
router isis 1
  distribute link-state exclude-external
  commit
  !
  !

router isis 1
  distribute link-state exclude-interarea
  commit
  !
  !

router isis 1
  distribute link-state route-policy isis-rp-1
```

```


commit
!
!

```

Use Case: Configuring SR-EPE and BGP-LS

In the following figure, segment routing is enabled on autonomous system AS1 with ingress node A and egress nodes B and C. In this example, we configure EPE on egress node C.

Figure 1: Topology



Procedure

Step 1 Configure node C with EPE for eBGP peers D and E.

Example:

```

RP/0/RSP0/CPU0:router_C(config)# router bgp 1
RP/0/RSP0/CPU0:router_C(config-bgp)# neighbor 192.168.1.3
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# remote-as 3
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# description to E
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# egress-engineering
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# address-family ipv4 unicast
RP/0/RSP0/CPU0:router_C(config-bgp-nbr-af)# route-policy bgp_in in
RP/0/RSP0/CPU0:router_C(config-bgp-nbr-af)# route-policy bgp_out out
RP/0/RSP0/CPU0:router_C(config-bgp-nbr-af)# exit
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# exit
RP/0/RSP0/CPU0:router_C(config-bgp)# neighbor 192.168.1.2
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# remote-as 2
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# description to D
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# egress-engineering
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# address-family ipv4 unicast
RP/0/RSP0/CPU0:router_C(config-bgp-nbr-af)# route-policy bgp_in in
RP/0/RSP0/CPU0:router_C(config-bgp-nbr-af)# route-policy bgp_out out
RP/0/RSP0/CPU0:router_C(config-bgp-nbr-af)# exit
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# exit

```

Step 2 Configure node C to advertise peer node SIDs to the controller using BGP-LS.

Example:

```

RP/0/RSP0/CPU0:router_C(config-bgp)# neighbor 172.29.50.71
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# remote-as 1

```

```
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# description to EPE_controller
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# address-family link-state link-state
RP/0/RSP0/CPU0:router_C(config-bgp-nbr)# exit
RP/0/RSP0/CPU0:router_C(config-bgp)# exit
```

Step 3 Configure MPLS static on the egress interfaces connecting to the eBGP peer.

Example:

```
RP/0/RSP0/CPU0:router_C(config)# mpls static
RP/0/RSP0/CPU0:router_C(config-mpls-static)# interface TenGigE 0/3/0/0
RP/0/RSP0/CPU0:router_C(config-mpls-static)# interface TenGigE 0/1/0/0
RP/0/RSP0/CPU0:router_C(config-mpls-static)# exit
```

Step 4 Commit the configuration.

Example:

```
RP/0/RSP0/CPU0:router_C(config)# commit
```

Step 5 Verify the configuration.

Example:

```
RP/0/RSP0/CPU0:router_C# show bgp egress-engineering

Egress Engineering Peer Set: 192.168.1.2/32 (10b87210)
  Nexthop: 192.168.1.2
  Version: 2, rn version: 2
  Flags: 0x00000002
  Local ASN: 1
  Remote ASN: 2
  Local RID: 10.1.1.3
  Remote RID: 10.1.1.4
  First Hop: 192.168.1.2
  NHID: 3
  Label: 24002, Refcount: 3
  rpc_set: 10b9d408

Egress Engineering Peer Set: 192.168.1.3/32 (10be61d4)
  Nexthop: 192.168.1.3
  Version: 3, rn version: 3
  Flags: 0x00000002
  Local ASN: 1
  Remote ASN: 3
  Local RID: 10.1.1.3
  Remote RID: 10.1.1.5
  First Hop: 192.168.1.3
  NHID: 4
  Label: 24003, Refcount: 3
  rpc_set: 10be6250
```

The output shows that node C has allocated peer SIDs for each eBGP peer.

Example:

```
RP/0/RSP0/CPU0:router_C# show mpls forwarding labels 24002 24003
Local  Outgoing  Prefix          Outgoing      Next Hop      Bytes
Label  Label       or ID          Interface     Interface     Switched
-----
24002  Pop         No ID         Te0/3/0/0    192.168.1.2  0
```

```
24003 Pop          No ID          Te0/1/0/0      192.168.1.3    0
```

The output shows that node C installed peer node SIDs in the Forwarding Information Base (FIB).

Configure BGP Proxy Prefix SID

To support segment routing, Border Gateway Protocol (BGP) requires the ability to advertise a segment identifier (SID) for a BGP prefix. A BGP-Proxy-SID is the segment identifier of the BGP prefix segment in a segment routing network. BGP proxy SID attribute is a BGP extension to signal BGP proxy-SIDs. However, there may be routers which do not support BGP extension for segment routing. Hence, those routers also do not support BGP proxy SID attribute and an alternate approach is required.

BGP proxy prefix SID feature allows you to attach BGP proxy SID attributes for remote prefixes learnt from BGP labeled unicast (LU) neighbours which are not SR-capable and propagate them as SR prefixes. This allows an LSP towards non SR endpoints to use segment routing global block in a SR domain. Since BGP proxy prefix SID uses global label values it minimizes the use of limited resources such as ECMP-FEC and provides more scalability for the networks.

BGP proxy prefix SID feature is implemented using the segment routing mapping server (SRMS). SRMS allows the user to configure SID mapping entries to specify the prefix-SIDs for the prefixes. The mapping server advertises the local SID-mapping policy to the mapping clients. BGP acts as a client of the SRMS and uses the mapping policy to calculate the prefix-SIDs.

Configuration Example:

This example shows how to configure the BGP proxy prefix SID feature for the segment routing mapping server.

```
RP/0/RSP0/CPU0:router(config)# segment-routing
RP/0/RSP0/CPU0:router(config-sr)# mapping-server
RP/0/RSP0/CPU0:router(config-sr-ms)# prefix-sid-map
RP/0/RSP0/CPU0:router(config-sr-ms-map)# address-family ipv4
RP/0/RSP0/CPU0:router(config-sr-ms-map-af)# 10.1.1.1/32 10 range 200
RP/0/RSP0/CPU0:router(config-sr-ms-map-af)# 192.168.64.1/32 400 range 300
```

This example shows how to configure the BGP proxy prefix SID feature for the segment-routing mapping client.

```
RP/0/RSP0/CPU0:router(config)# router bgp 1
RP/0/RSP0/CPU0:router(config-bgp)# address-family ip4 unicast
RP/0/RSP0/CPU0:router(config-bgp-af)# segment-routing prefix-sid-map
```

Verification

These examples show how to verify the BGP proxy prefix SID feature.

```
RP/0/RSP0/CPU0:router# show segment-routing mapping-server prefix-sid-map ipv4 detail
Prefix
10.1.1.1/32
  SID Index:      10
  Range:          200
  Last Prefix:    10.1.1.200/32
  Last SID Index: 209
```

```
Flags:
Number of mapping entries: 1
```

```
RP/0/RSP0/CPU0:router# show bgp ipv4 labeled-unicast 192.168.64.1/32
```

```
BGP routing table entry for 192.168.64.1/32
```

```
Versions:
```

```
Process          bRIB/RIB  SendTblVer
Speaker          117      117
Local Label: 16400
```

```
Last Modified: Oct 25 01:02:28.562 for 00:11:45Paths: (2 available, best #1)
```

```
Advertised to peers (in unique update groups):
```

```
201.1.1.1
```

```
Path #1: Received by speaker 0 Advertised to peers (in unique update groups):
```

```
201.1.1.1
```

```
Local
```

```
20.0.101.1 from 20.0.101.1 (20.0.101.1) Received Label 61
```

```
Origin IGP, localpref 100, valid, internal, best, group-best, multipath, labeled-unicast
```

```
Received Path ID 0, Local Path ID 0, version 117
```

```
Prefix SID Attribute Size: 7
```

```
Label Index: 1
```

```
RP/0/RSP0/CPU0:router# show route ipv4 unicast 192.68.64.1/32 detail
```

```
Routing entry for 192.168.64.1/32
```

```
Known via "bgp 65000", distance 200, metric 0, [ei]-bgp, labeled SR, type internal
```

```
Installed Oct 25 01:02:28.583 for 00:20:09
```

```
Routing Descriptor Blocks
```

```
20.0.101.1, from 20.0.101.1, BGP multi path
```

```
Route metric is 0
```

```
Label: 0x3d (61)
```

```
Tunnel ID: None
```

```
Binding Label: None
```

```
Extended communities count: 0
```

```
NHID:0x0(Ref:0)
```

```
Route version is 0x6 (6)
```

```
Local Label: 0x3e81 (16400)
```

```
IP Precedence: Not Set
```

```
QoS Group ID: Not Set
```

```
Flow-tag: Not Set
```

```
Fwd-class: Not Set
```

```
Route Priority: RIB_PRIORITY_RECURSIVE (12) SVD Type RIB_SVD_TYPE_LOCAL
```

```
Download Priority 4, Download Version 242
```

```
No advertising protos.
```

```
RP/0/RSP0/CPU0:router# show cef ipv4 192.168.64.1/32 detail
```

```
192.168.64.1/32, version 476, labeled SR, drop adjacency, internal 0x5000001 0x80 (ptr 0x71c42b40) [1], 0x0 (0x71c11590), 0x808 (0x722b91e0)
```

```
Updated Oct 31 23:23:48.733
```

```
Prefix Len 32, traffic index 0, precedence n/a, priority 4
```

```
Extensions: context-label:16400
```

```
gateway array (0x71ae7e78) reference count 3, flags 0x7a, source rib (7), 0 backups [2 type 5 flags 0x88401 (0x722eb450) ext 0x0 (0x0)]
```

```
LW-LDI[type=5, refc=3, ptr=0x71c11590, sh-ldi=0x722eb450]
```

```
gateway array update type-time 3 Oct 31 23:49:11.720
```

```
LDI Update time Oct 31 23:23:48.733
```

```
LW-LDI-TS Oct 31 23:23:48.733
```

```
via 20.0.101.1/32, 0 dependencies, recursive, bgp-ext [flags 0x6020]
```

```
path-idx 0 NHID 0x0 [0x7129a294 0x0]
```

```
recursion-via-/32
```

```
unresolved
```

```
local label 16400
```

```

labels imposed {ExpNullv6}

RP/0/RSP0/CPU0:router# show bgp labels
BGP router identifier 2.1.1.1, local AS number 65000
BGP generic scan interval 60 secs
Non-stop routing is enabled
BGP table state: Active
Table ID: 0xe0000000 RD version: 245
BGP main routing table version 245
BGP NSR Initial initsync version 16 (Reached)
BGP NSR/ISSU Sync-Group versions 245/0
BGP scan interval 60 secs

Status codes: s suppressed, d damped, h history, * valid, > best
               i - internal, r RIB-failure, S stale, N Nexthop-discard
Origin codes: i - IGP, e - EGP, ? - incomplete
   Network        Next Hop        Rcvd Label        Local Label
*>i10.1.1.1/32    10.1.1.1        3                  16010
*> 2.1.1.1/32    0.0.0.0        no-label          3
*> 192.68.64.1/32 20.0.101.1     2                  16400
*> 192.68.64.2/32 20.0.101.1     2                  16401

```

BGP-LU Inter-AS Option-C Interworking with LDP and IGP SR-MPLS using Proxy BGP-SR

Table 4: Feature History Table

Feature Name	Release	Description
BGP-LU Inter-AS Option-C Interworking with LDP and IGP SR-MPLS using Proxy BGP-SR	Release 7.3.2	<p>This feature extends the current Proxy BGP-SR functionality by allowing the BGP-LU ASBR router with Proxy BGP-SR configured to also interconnect attached LDP domains.</p> <p>The Proxy BGP-SR feature allows interconnection of IGP SR-MPLS domains and legacy domains via BGP-LU Inter-AS option-C. It provides a prefix-to-SID mapping for BGP-LU prefixes that are learned without a Prefix-SID.</p>


The Proxy BGP-SR feature allows interconnection of IGP SR-MPLS domains and legacy domains via BGP-LU Inter-AS option-C. It provides a prefix-to-SID mapping for BGP-LU prefixes that are learned without a Prefix-SID. This new feature extends the current functionality by allowing the BGP-LU ASBR router (configured with Proxy BGP-SR) to also interconnect attached LDP domains.

With this enhancement, when performing redistribution from BGP into IGP, LDP would use the same local label assigned by BGP for a prefix learned by BGP-LU. The local label value is based on the SR mapping server configuration (Proxy-BGP SR feature). This behavior allows incoming LDP traffic destined to a redistributed prefix to be switched over to the BGP-LU Inter-AS LSP.

Use Case

In the following figure, Router A does the following:

- Is an ASBR for BGP AS 100 running BGP-LU with BGP AS 200
- Interconnects two IS-IS processes: one running LDP and another running Segment Routing
- Redistributes prefixes learned by BGP-LU from AS 200 into both IS-IS instances
- Runs SR Mapping Server (SRMS) in order to assign mappings to prefixes learned by BGP LU from AS 200 without a prefix SID (proxy BGP-SR) and prefixes learned from the LDP domain



Configuration on Router A - ASBR for AS100

```

prefix-set pfxset-bgplu
 100.1.1.8/32 // The Prefix under test
end-set
!
prefix-set LOOPBACKS
 192.168.0.1,
 192.168.0.2,
 192.168.0.3,
 192.168.0.4,
 192.168.0.8
end-set
!
route-policy Pass
 pass
end-policy
!
route-policy rpl-bgplu
 if destination in pfxset-bgplu then
  pass
 else

```

```

        drop
    endif
end-policy
!
route-policy MATCH_LOOPBACKS
    if destination in LOOPBACKS then
        pass
    else
        drop
    endif
end-policy
!
router static
    address-family ipv4 unicast
        10.10.10.2/32 GigabitEthernet0/2/0/0
    !
!
router isis 50
    is-type level-2-only
    net 49.0001.0000.0000.0001.00
    address-family ipv4 unicast
    metric-style wide
    redistribute bgp 100 route-policy rpl-bgplu // Redistribute prefixes learned by BGP-LU
into IS-IS LDP domain
!
interface Loopback0
    passive
    address-family ipv4 unicast
    !
!
interface GigabitEthernet0/2/0/1
    address-family ipv4 unicast
    !
!
!
router isis 100
    is-type level-2-only
    net 49.0001.0000.0000.0011.00
    distribute link-state
    address-family ipv4 unicast
    metric-style wide
    mpls traffic-eng level-2-only
    mpls traffic-eng router-id Loopback0
    redistribute bgp 100 route-policy rpl-bgplu // Redistribute prefixes learned by BGP-LU
into IS-IS SR domain
    segment-routing mpls
    segment-routing prefix-sid-map advertise-local
!
interface Loopback0
    passive
    address-family ipv4 unicast
    prefix-sid index 1
    !
!
interface GigabitEthernet0/2/0/2
    address-family ipv4 unicast
    !
!
!
router bgp 100
    bgp router-id 192.168.0.1
    address-family ipv4 unicast
    segment-routing prefix-sid-map // SR Proxy SID Configuration
    network 192.168.0.1/32

```

```

redistribute isis 50 route-policy MATCH_LOOPBACKS
redistribute isis 100 route-policy MATCH_LOOPBACKS
allocate-label all
!
neighbor 10.10.10.2
  remote-as 200
  address-family ipv4 labeled-unicast
    route-policy Pass in
    route-policy Pass out
!
!
!
mpls ldp
  router-id 192.168.0.1
  interface GigabitEthernet0/2/0/1
!
!
segment-routing
  global-block 16000 23999
mapping-server
  prefix-sid-map // SRMS configuration
  address-family ipv4
    100.1.1.8/32 108 range 1 // SRMS mapping - LU prefix 100.1.1.8/32 assigned prefix index
  108
    192.168.0.3/32 3 range 1 // SRMS mapping - LDP prefix Router C assigned prefix index
  3
!
!
!
!

```

Configuration on Router B - ASBR for AS200

```

route-policy Pass
  pass
end-policy
!
router static
  address-family ipv4 unicast
    10.10.10.1/32 GigabitEthernet0/0/0/0
!
!
router bgp 200
  bgp router-id 192.168.0.2
  address-family ipv4 unicast
    network 100.1.1.8/32 // Import/Inject route into BGP
    network 192.168.0.2/32
    allocate-label all
!
neighbor 10.10.10.1
  remote-as 100
  address-family ipv4 labeled-unicast
    route-policy Pass in
    route-policy Pass out
!
!
!

```

Configuration on Router C in the LDP Domain

```

router isis 50
  is-type level-2-only
  net 49.0001.0000.0000.0003.00

```

```

address-family ipv4 unicast
metric-style wide
!
interface Loopback0
passive
address-family ipv4 unicast
!
!
interface GigabitEthernet0/0/0/0
address-family ipv4 unicast
!
!
!
mpls ldp
router-id 192.168.0.3
interface GigabitEthernet0/0/0/0
!
!

```

Configuration on Router D in the SR IS-IS Domain

```

router isis 100
is-type level-2-only
net 49.0001.0000.0000.0004.00
address-family ipv4 unicast
metric-style wide
mpls traffic-eng level-2-only
mpls traffic-eng router-id Loopback0
segment-routing mpls
!
interface Loopback0
passive
address-family ipv4 unicast
prefix-sid index 4
!
!
interface GigabitEthernet0/0/0/0
address-family ipv4 unicast
!
!
!
segment-routing
!

```

BGP Best Path Computation using SR Policy Paths

Table 5: Feature History Table

Feature Name	Release Information	Feature Description
BGP Best Path Computation using SR Policy Paths	Release 7.5.2 Release 7.3.4	<p>BGP best-path selection is modified for a prefix when at least one of its paths resolves over the next hop using SR policies (SR policy in “up” state). Under this condition, paths not steered over an SR policy (those using native next-hop resolution) are considered ineligible during best-path selection.</p> <p>You can thus control the best path selection in order to steer traffic, preferably or exclusively, over SR policies with the desired SLA.</p> <p>This feature introduces the bgp bestpath sr-policy {force prefer} command.</p>

BGP selects the best path from the available pool of paths such as iBGP, eBGP, color, or noncolor paths with native next hop and SR policy next hop. BGP uses either native next hop or an SR policy next hop for best path computation. However, BGP might not consider SR policy next hop for best path computation due to other factors in best path selection. By default, BGP considers a native next hop for the best path computation during the failure.

For more information, see [Best path calculation algorithm](#).

When multiple advertisements of the same BGP prefix are received where some have extended community color, SRTE headend with BGP multi-path enabled installs multiple routes with or without extended community color. It may be required to exclude the path resolving over native next hop SR policy paths from BGP best path selection when a prefix has multiple paths in the presence of one BGP path with the extended community color that is resolved over the SR policy.

You may want to use the egress PE to exit a domain using local preference or other attributes before the next hop metric selection. In such scenarios, when SR policy of the primary path fails, the best path is resolved over a regular IGP next hop that is the default mode of operation. Traffic doesn't select the backup path with SR policy, instead traffic moves to native LSP on the primary path.

The BGP Best Path Computation using SR Policy Paths feature allows the BGP to use the path with SR policy as the best-path, backup, and multipath.

When this feature is enabled, some paths are marked as an ineligible path for BGP best path selection. Existing BGP best path selection order is applied to the eligible paths.

Use either of the following modes for the BGP to select the SR policy path as the best path for the backup path:

- Force mode: When force mode is enabled, only SR policy paths are considered for best path calculation. Use the **bgp bestpath sr-policy force** command to enable this mode.

In a network, when at least one path has an active SR policy, the following paths are marked as ineligible for best path selection:

- iBGP paths with noncolor or color paths with SR policy that isn't active.
- eBGP with color and SR policy isn't active.
- eBGP noncolor paths



Note Local and redistributed BGP paths are always eligible for best path selection.

- Prefer mode: When prefer mode is enabled, SR policy paths and eBGP noncolor paths are eligible for best path calculation.

Use the **bgp bestpath sr-policy prefer** command to enable this mode.

In a network, when at least one path has an active SR policy, the following paths are marked as ineligible for best path selection:

- iBGP paths with noncolor or color paths with SR policy that isn't active.
- eBGP with color and SR policy isn't active.



Note Local and redistributed BGP paths are always eligible for best path selection.

Configure BGP Best Path Computation using SR Policy Paths

To enable the feature, perform the following tasks on the ingress PE router that is the head-end of SR policy:

- Configure route policy.
- Configure SR policy.
- Configure BGP with either prefer or force mode.

Configuration Example

Configure route policies on the egress PE router:

```
Router(config)#extcommunity-set opaque color9001
Router(config-ext)#9001 co-flag 01
Router(config-ext)#end-set
Router(config)#extcommunity-set opaque color9002
Router(config-ext)#9002 co-flag 01
Router(config-ext)#end-set
Router(config)#commit

Router(config)#route-policy for9001
Router(config-rpl)#set extcommunity color color9001
```

```

Router(config-rpl) # pass
Router(config-rpl) #end-policy

Router(config) #route-policy for9002
Router(config-rpl) #set extcommunity color color9002
Router(config-rpl) #pass
Router(config-rpl) #end-policy
Router(config) #commit

Router#configure
Router(config) #route-policy add_path
Router(config-rpl) #set path-selection backup 1 install multipath-protect advertise
multipath-protect-advertise
Router(config-rpl) #end-policy

Router(config) #route-policy pass-all
Router(config-rpl) #pass
Router(config-rpl) #end-policy
Router(config) #commit

```

Configure SR policy on the egress PE router:

```

Router#configure
Router(config) #segment-routing
Router(config-sr) #traffic-eng
Router(config-sr-te) #segment-list SL201
Router(config-sr-te-sl) #index 1 mpls label 25000
Router(config-sr-te-sl) #policy POLICY_9001
Router(config-sr-te-policy) #binding-sid mpls 47700
Router(config-sr-te-policy) #color 9001 end-point ipv6 ::
Router(config-sr-te-policy) #candidate-paths
Router(config-sr-te-policy-path) #preference 10
Router(config-sr-te-policy-path-pref) #explicit segment-list SL201
Router(config-sr-te-sl) #policy POLICY_9002
Router(config-sr-te-policy) #binding-sid mpls 47701
Router(config-sr-te-policy) #color 9002 end-point ipv6 ::
Router(config-sr-te-policy) #candidate-paths
Router(config-sr-te-policy-path) #preference 10
Router(config-sr-te-policy-path-pref) #explicit segment-list SL201
Router(config-sr-te-policy-path-pref) #commit

```

Configure BGP on the Egress PE router:

```

Router(config) #router bgp 100
Router(config-bgp) #nsr
Router(config-bgp) #bgp router-id 10.1.1.2
Router(config-bgp) #bgp best-path sr-policy force
Router(config-bgp) #address-family ipv6 unicast
Router(config-bgp-af) #maximum-paths eibgp 25
Router(config-bgp-af) #additional-paths receive
Router(config-bgp-af) #additional-paths send
Router(config-bgp-af) #additional-paths selection route-policy add_path
Router(config-bgp-af) #redistribute connected
Router(config-bgp-af) #redistribute static
Router(config-bgp-af) #allocate-label all
Router(config-bgp-af) #commit
Router(config-bgp-af) #exit
Router(config-bgp) #neighbor 31::2
Router(config-bgp-nbr) #remote-as 2
Router(config-bgp-nbr) #address-family ipv6 unicast
Router(config-bgp-nbr-af) #route-policy for9001 in
Router(config-bgp-nbr-af) #route-policy pass-all out

```

```

Router(config-bgp-nbr-af)#commit
Router(config-bgp-nbr-af)#exit
Router(config-bgp)#neighbor 32::2
Router(config-bgp-nbr)#remote-as 2
Router(config-bgp-nbr)#address-family ipv6 unicast
Router(config-bgp-nbr-af)#route-policy for9002 in
Router(config-bgp-nbr-af)#route-policy pass-all out
Router(config-bgp-nbr-af)#commit

```

Verification

The following show output shows that when the **force** option is enabled, the configured SR policy path is selected as the best path instead of the default best path.

```

Router#show bgp ipv6 unicast 2001:DB8::1 brief
Status codes: s suppressed, d damped, h history, * valid, > best
              i - internal, r RIB-failure, S stale, N Nexthop-discard
Origin codes: i - IGP, e - EGP, ? - incomplete
   Network          Next Hop          Metric LocPrf Weight Path
* 2001:DB8::1      10:1:1::55              100     0 2 i
* i                 10:1:1::55              100     0 2 i

*                  30::2                      0 2 I
*>                 31::2 C:9001              0 2 I
*                  32::2 C:9002              0 2 I
Router#

```

Use the following command to compare the best paths:

```

Router#show bgp ipv6 unicast 2001:DB8::1 bestpath-compare
BGP routing table entry for 2001:DB8::1
Versions:
  Process          bRIB/RIB  SendTblVer
  Speaker          7641      7641
  Flags: 0x240232b2+0x20050000; multipath; backup available;
Last Modified: Dec  7 03:43:57.200 for 00:34:48
Paths: (24 available, best #4)
  Advertised IPv6 Unicast paths to update-groups (with more than one peer):
    0.3 0.4
  Advertised IPv6 Unicast paths to peers (in unique update groups):
    10.1.1.55
  Path #1: Received by speaker 0
  Flags: 0x2000000000020005, import: 0x20
  Flags2: 0x00
  Not advertised to any peer
  2
    10:1:1::55 (metric 30) from 10.1.1.55 (10.1.1.55), if-handle 0x00000000
      Origin IGP, localpref 100, valid, internal
      Received Path ID 1, Local Path ID 0, version 0
      Extended community: Color[CO-Flag]:8001[01]
      Non SR-policy path is ignored due to config knob
  Path #2: Received by speaker 0
  Flags: 0x2000000000020005, import: 0x20
  Flags2: 0x00
  Not advertised to any peer
  2
    10:1:1::55 (metric 30) from 10.1.1.55 (10.1.1.55), if-handle 0x00000000
      Origin IGP, localpref 100, valid, internal
      Received Path ID 3, Local Path ID 0, version 0
      Extended community: Color[CO-Flag]:8002[01]
      Non SR-policy path is ignored due to config knob
  Path #3: Received by speaker 0
  Flags: 0x3000000000060001, import: 0x20

```

```

Flags2: 0x00
Advertised IPv6 Unicast paths to update-groups (with more than one peer):
  0.4
Advertised IPv6 Unicast paths to peers (in unique update groups):
  10.1.1.55
  2
  30::2 from 30::2 (198.51.100.1), if-handle 0x00000000
    Origin IGP, localpref 100, weight 65534, valid, external, backup, add-path
    Received Path ID 0, Local Path ID 2, version 7641
    Origin-AS validity: (disabled)
    Non SR-policy path is ignored due to config knob
Path #4: Received by speaker 0
Flags: 0xb000000001070001, import: 0x20
Flags2: 0x00
Advertised IPv6 Unicast paths to update-groups (with more than one peer):
  0.3 0.4
Advertised IPv6 Unicast paths to peers (in unique update groups):
  10.1.1.55
  2
  31::2 C:9001 (bsid:48900) from 31::2 (198.51.100.2), if-handle 0x00000000
    Origin IGP, localpref 100, valid, external, best, group-best, multipath
    Received Path ID 0, Local Path ID 1, version 7641
    Extended community: Color[CO-Flag]:9001[01]
    Origin-AS validity: (disabled)
    SR policy color 9001, ipv6 null endpoint, up, not-registered, bsid 48900

    best of AS 2, Overall best
Path #5: Received by speaker 0
Flags: 0xb000000000030001, import: 0x20
Flags2: 0x00
Not advertised to any peer
  2
  32::2 C:9002 (bsid:48901) from 32::2 (198.51.100.3), if-handle 0x00000000
    Origin IGP, localpref 100, valid, external, multipath
    Received Path ID 0, Local Path ID 0, version 0
    Extended community: Color[CO-Flag]:9002[01]
    Origin-AS validity: (disabled)
    SR policy color 9002, up, not-registered, bsid 48901
    Higher router ID than best path (path #4)

```

Use the **show bgp process** command to verify which mode is enabled.

In the following example, you see that the **force** mode is enabled.

```

Router#show bgp process
BGP Process Information:
BGP is operating in STANDALONE mode
Autonomous System number format: ASPLAIN
Autonomous System: 100
Router ID: 10.1.1.2 (manually configured)
Default Cluster ID: 10.1.1.2
Active Cluster IDs: 10.1.1.2
Fast external fallover enabled
Platform Loadbalance paths max: 64
Platform RLIMIT max: 8589934592 bytes
Maximum limit for BMP buffer size: 1638 MB
Default value for BMP buffer size: 1228 MB
Current limit for BMP buffer size: 1228 MB
Current utilization of BMP buffer limit: 0 B
Neighbor logging is enabled
Enforce first AS enabled
Use SR-Policy admin/metric of color-extcomm Nexthop during path comparison: disabled
SR policy path force is enabled
Default local preference: 100

```

```

Default keepalive: 60
Non-stop routing is enabled
Slow peer detection enabled
ExtComm Color Nexthop validation: RIB

Update delay: 120
Generic scan interval: 60
Configured Segment-routing Local Block: [0, 0]
In use Segment-routing Local Block: [15000, 15999]
Platform support mix of sr-policy and native nexthop: Yes

Address family: IPv4 Unicast
Dampening is not enabled
Client reflection is enabled in global config
Dynamic MED is Disabled
Dynamic MED interval : 10 minutes
Dynamic MED Timer : Not Running
Dynamic MED Periodic Timer : Not Running
Scan interval: 60
Total prefixes scanned: 33
Prefixes scanned per segment: 100000
Number of scan segments: 1
Nexthop resolution minimum prefix-length: 0 (not configured)
IPv6 Nexthop resolution minimum prefix-length: 0 (not configured)
Main Table Version: 12642
Table version synced to RIB: 12642
Table version acked by RIB: 12642
IGP notification: IGP notified
RIB has converged: version 2
RIB table prefix-limit reached ? [No], version 0
Permanent Network Unconfigured

Node          Process      Nbrs Estb Rst Upd-Rcvd Upd-Sent Nfn-Rcv Nfn-Snt
node0_RSP1_CPU0 Speaker      53   3   2    316    823     0     53

```

Optimal Utilization of ECMP FEC Resources

Table 6: Feature History Table

Feature Name	Release Information	Feature Description
Optimal Utilization of ECMP FEC Resources	Release 7.5.2	<p>BGP-SR multipath ECMP FEC optimization is enhanced to support 32k BGP-LU prefixes (from the earlier 4k BGP-LU prefixes) on multipath with the same outgoing label. This results in the consumption of lesser ECMP FEC resources, thus avoiding out-of-resource (OOR) situations for your router.</p> <p>In earlier releases, all 4k BGP-LU prefixes consumed all the 4k ECMP FEC resources.</p> <p>Use the hw-module fib mpls bgp-sr lsr-optimized command to enable BGP-SR multipath ECMP FEC optimization.</p>

The BGP-SR multipath ECMP FEC optimization solution minimizes the ECMP FEC resource consumption during underlay programming for an SR-MPLS network. BGP-LU prefix consumes one FEC resource for every path and one ECMP FEC resource for multipath. When you configure BGP-LU multipath, each BGP-LU prefix consumes one ECMP FEC resource for programming the prefix. This limits the BGP-LU prefix scale to only 4k. To support higher BGP-LU prefix scales of upto 32k, you need to conserve the ECMP FEC resources. With BGP-SR multipath ECMP FEC optimization feature, you can conserve the ECMP FEC resource usage when BGP-LU multipath is configured.

Enable the **hw-module fib mpls bgp-sr lsr-optimized** command, and ensure that all BGP-LU prefix paths advertise the same `out_label`. You can achieve this with BGP-SR or proxy BGP-SR by using same **prefix-sid-map** on the next hop routers.

After you enable ECMP FEC optimization, all BGP-LU prefix is assigned the same ECMP FEC key by conserving the ECMP FEC resources and supports scale of upto 32k BGP-LU prefixes.



Note If the paths for BGP-LU prefixes don't have the same `out_label`, then each prefix whose `out_label` isn't the same, starts to consume ECMP FEC resources and may result in out-of-resource (OOR) when it exceeds 4k, and you may observe traffic drops. Also, the successive prefixes starts to consume FEC resources, which affect multipath support.

Usage Guidelines and Limitations

- BGP-SR multipath ECMP FEC optimization feature isn't supported on Cisco NCS 5700 series fixed port routers or Cisco NCS 5500 series routers that have the Cisco NC57 line cards installed and operating in the native or compatible modes.
- All the prefixes advertised must be /32 (IPv4 only) and to enable optimization, all prefixes must have the same outgoing label.
- eBGP is always interface peering and iBGP is always loopback peering.
- Supports 32k LU prefix scale (IPv4 only) for loopback peering and 24k LU prefix scale for interface peering.
 - For eBGP interface peering, the maximum BGP next hops possible is only 2.
 - For iBGP loopback peering, the maximum BGP next hops possible is only 4.
- You can't configure the **hw-module fib mpls bgp-sr lsr-optimized** command, if **hw-module fib mpls label lsr-optimized** command is already configured.
- No ECMP FEC optimization is supported for L3VPN services over BGP-LU loopback peering.

Enable BGP-SR Multipath ECMP FEC Optimization

To enable BGP-SR multipath ECMP FEC optimization, you must configure the **hw-module fib mpls label lsr-optimized** command in global configuration mode. After enabling this feature, reload the chassis.

```
Router(config)#hw-module fib mpls bgp-sr lsr-optimized
Tue Nov 16 22:27:42.360 UTC
In order to activate this MPLS profile, you must manually reload the chassis/all line cards
Router(config)#commit

Router# reload location 0/0/CPU0

Proceed with reload? [confirm]
Reloading node 0/0/CPU0
```

Verification

The following example shows NPU ECMP FEC resource before enabling BGP-SR multipath ECMP FEC optimization, shows the OOR state and the ECMP FEC resource consumption.

```
RP/0/RP0/CPU0:PE1#show controllers npu resources ecmpfec location all
Tue Nov 16 21:43:01.219 UTC
HW Resource Information For Location: 0/7/CPU0
HW Resource Information
  Name                : ecmp_fec
  Asic Type            : Jericho
NPU-0
OOR Summary
  Estimated Max Entries : 4096
  Red Threshold          : 95 %
  Yellow Threshold      : 80 %
  OOR State              : Red
  OOR State Change Time : 2021.Nov.16 21:39:21 UTC
  Bank Info              : ECMP
```

```

OFA Table Information
(May not match HW usage)
    ipnhgroup           : 3916
    ip6nhgroup          : 178

Current Hardware Usage
Name: ecmp_fec
    Estimated Max Entries      : 4096
    Total In-Use             : 4094    (99 %)
    OOR State                  : Red
    OOR State Change Time     : 2021.Nov.16 21:39:21 UTC
    Bank Info                   : ECMP
Name: hier_0
    Total In-Use               : 4094
    OOR State                   : Red
    OOR State Change Time     : 2021.Nov.16 21:39:21 UTC
    Bank Info                   : ECMP

```

The following example shows NPU usage after enabling BGP-SR multipath ECMP FEC optimization, shows improvement in the OOR state and the ECMP FEC resource consumption.

```

RP/0/RP0/CPU0:PE1#show controllers npu resources ecmpfec location all
Wed Nov 17 19:49:08.978 UTC
HW Resource Information
    Name                   : ecmp_fec
    Asic Type               : Jericho
NPU-0
OOO Summary
    Estimated Max Entries   : 4096
    Red Threshold           : 95 %
    Yellow Threshold        : 80 %
    OOO State                 : Green
    Bank Info                : ECMP
OFA Table Information
(May not match HW usage)
    ipnhgroup           : 185
    ip6nhgroup          : 178
Current Hardware Usage
Name: ecmp_fec
    Estimated Max Entries      : 4096
    Total In-Use             : 363    (8 %)
    OOR State                  : Green
    Bank Info                   : ECMP
Name: hier_0
    Total In-Use               : 363
    OOR State                   : Green
    Bank Info                   : ECMP

```

SRv6 double recursion for multilayer BGP underlay

Table 7: Feature History Table

Feature Name	Release Information	Feature Description
SRv6 double recursion for multilayer BGP underlay	Release 24.4.1	<p>Introduced in this release on; NCS 5700 fixed port routers; NCS 5500 modular routers (NCS 5500 line cards; NCS 5700 line cards [Mode: Compatibility; Native])</p> <p>The feature introduces support for SRv6 double recursion, where network services such as BGP VPNs (Layer 2 and Layer 3) require multiple resolution layers. Specifically, one routing layer resolves over another before reaching the final destination. Double recursion is achieved by collapsing the underlay, typically involving protocols like IGP or BGP in the packet forwarding chain. This enables three-level load balancing and an even distribution of traffic across multiple layers of the network stack.</p> <p>The feature is supported on the ingress Provider Edge (PE) router.</p> <p>The feature introduces these changes:</p> <p>CLI:</p> <ul style="list-style-type: none"> • tag-map tag <value> map forwarding-hierarchy level-2-used-as-nexthop • The show cef ipv6 and show cef ipv4 commands now include the Layer 2 prefix information, which resolve as nexthop Layer 3 prefixes. <p>YANG Data Models:</p> <ul style="list-style-type: none"> • Cisco-IOS-XR-un-router-rib-cfg:router (see GitHub, Yang Data Models Navigator) data model.

SRv6 double recursion and load balancing

SRv6 double recursion refers to scenarios where network service such as BGP VPN (Layer 2/Layer 3) requires multiple layers of resolution, specifically where one routing layer resolves over another before reaching its final destination.

The SRv6 double recursion feature is designed to support three-level load balancing by collapsing the underlay, which typically involves protocols like IGP or BGP in the forwarding chain. This involves specific configurations in RIB, BGP, and static routes to indicate IPv4 and IPv6 unicast routes with Layer 2 prefixes, which resolve as nexthop Layer 3 prefixes.

Without this feature, the traffic drops the Layer 3 prefixes leading to packet loss.

Key benefits of SRv6 double recursion

- Support for complex network scenarios: In traditional service provider (SP) networks, BGP VPN services typically resolve directly over IGP reachability, meaning there is a straightforward, single-level resolution path from the service to the IGP underlay. However, with the evolution of networking, especially in data centers, new architectures have emerged where BGP underlay networks are used. In these scenarios, BGP VPN services resolve over a BGP underlay, which in turn resolves over IGP or directly connected routes.
- Support for enhanced load balancing: SRv6 double recursion allows the routing platform to balance traffic more efficiently across all available paths, enhancing overall network performance and reducing congestion. Proper load balancing at each level of recursion helps in distributing traffic evenly, avoiding bottlenecks, and ensuring that packets take optimal paths even in complex topologies.
- Improved network flexibility: Double recursion allows advanced routing solutions in SP and data center networks, accommodating complex use cases beyond single-layer limitations.

Single and double recursion in BGP VPN services

To optimize the network routing efficiency, it is important to understand the resolution processes of BGP VPN services.

- Single Recursion: BGP VPN service → IGP reachability. In a single recursion, the BGP VPN service directly resolves to IGP (Interior Gateway Protocol) reachability. Single recursion is required when a BGP VPN service can directly resolve to an IGP route without any intermediary steps.
- Double Recursion: BGP VPN service → BGP underlay reachability → IGP reachability. In double recursion, the BGP VPN service first resolves over a BGP underlay, which then leads to IGP reachability. Double recursion is necessary in cases where a BGP VPN service cannot resolve directly to an IGP route but instead must traverse a BGP underlay first. This creates a layered resolution process that standard single-level load balancing cannot handle effectively.

Usage guidelines and limitations for SRv6 double recursion

Limitations

You cannot use a combination of BGP-SU (BGP Service Unicast) and BGP-IP paths at Layer 2.

Usage guidelines

The usage guidelines that are listed apply:

- Configure the locator prefix for IPv6 prefixes that are Layer 2 prefixes.
- If the collapsed BGP paths are a combination of IGP IPv6 and SRv6, the router filters out only the IPv6 paths.
- In a collapsed chain scenario with SRv6 as the IGP, the router configures the encapsulation (Encap) ID, provided it supports SRv6 and BGP extensions for SRv6.

Configure SRv6 double recursion for multilayer BGP underlay

Before you begin

- For Layer 2 IPv6 prefixes, set the locator prefix using the **prefix-set** command in RIB.
- Configure the set of IPv4 and IPv6 Layer 2 prefixes, which resolve as nexthop Layer 3 prefixes using the **prefix-set** command.

Procedure

Step 1 Enable the hardware support for BGP-LU to allow the ingress PE router to advertise and forward the MPLS-labelled unicast routes.

Example:

```
Router#config
Router(config)#hw-module profile cef bgplu enable
```

Step 2 Configure the IPv4 and IPv6 unicast routes in the RIB to ensure that the Layer 2 prefixes can be used as nexthop for Layer 3 prefixes.

Example:

```
Router#config
Router(config)#router bgp 100
Router(config-bgp)#address-family ipv4 unicast
Router(config-bgp-af)#table-policy level2-ipv4-policy
Router(config-bgp-af)#exit
Router(config-bgp)#address-family ipv6 unicast
Router(config-bgp-af)#table-policy level2-ipv6-policy
Router(config-bgp-af)#commit
```

Step 3 Assign the required tag to the IPv4 and IPv6 unicast routes to forward the route information to the Forwarding Information Base (FIB).

For the IPv4 and IPv6 routes, the RIB assigns the tags and forwards the route information to the FIB, indicating that these Layer 2 prefixes resolve as nexthop for Layer 3 prefixes.

Example:

IPv4 Layer 2 prefixes:

```
Router(config)#route-policy level2-ipv4-policy
Router(config-rpl)#if destination in level2_prefixes-ipv4 then
```

```

Router(config-rpl-if)#set tag 100
Router(config-rpl-if)#else
Router(config-rpl-else)#pass
Router(config-rpl-else)#endif
Router(config-rpl)#end-policy
Router(config)#commit

```

Example:

IPv6 Layer 2 prefixes:

```

Router(config)#route-policy level2-ipv6-policy
Router(config-rpl)#if destination in level2_prefixes-ipv6 then
Router(config-rpl-if)#set tag 100
Router(config-rpl-if)#endif
Router(config-rpl)#if destination in level2_locators then
Router(config-rpl-if)#set locator-prefix
Router(config-rpl-if)#else
Router(config-rpl-else)#pass
Router(config-rpl-else)#endif
Router(config-rpl)#end-policy

```

- Step 4** Map the tags in the RIB for the IPv4 and IPv6 unicast routes to ensure that the routes resolve as nexthop for Layer 3 prefixes.

In the following example, the RIB maps all the IPv4 and IPv6 routes tagged with the value 100, which indicates that these routes resolve as nexthop for Layer 3 prefixes. The RIB adds the *FIB_UPDATE_ROUTE_FLAG_EXTN_LVL2_HAS_DEPENDENT* flag when it sends the route update to the FIB.

Example:

```

Router#config
Router(config)#router rib
Router(config-rib)#tag-map tag 100 map forwarding-hierarchy level-2-used-as-nexthop
Router(config-rib)#commit

```

- Step 5** Run the **show running-config** command to verify the running configuration.

Example:

```

hw-module profile cef bgplu enable
!
router bgp 100
  address-family ipv4 unicast
    table-policy level2-ipv4-policy
  !
  address-family ipv6 unicast
    table-policy level2-ipv6-policy
  !
!
router rib
  tag-map tag 100 map forwarding-hierarchy level-2-used-as-nexthop
  !
!

```

- Step 6** Run the **show cef ipv4** and **show cef ipv6** commands to verify the Layer 2 collapsed prefixes.

In the show output command example, the IPv6 Layer 2 prefixes, which resolve as nexthop for Layer 3 prefixes are collapsed. This is indicated by the **collapsed** keyword in the output. The SRv6 SID lists indicate the different encapsulation layers or hierarchy.

Example:

```

Router#show cef ipv6 2001:DB8:A:B::1/64
Thu Jun  6 12:48:52.399 EDT

```

```

2001:DB8:A:B::1/64, version 8, SRv6 Headend, internal 0x1000001 0x0 (ptr 0x63851c98) [1], 0x1400
(0x63851da0), 0x0 (0x638b2128)
Updated Jun  6 12:41:10.589
Prefix Len 64, traffic index 0, precedence n/a, priority 0, encap-id 0x11deadbeef
gateway array (0x61e1a798) reference count 1, flags 0x10, source rib (7), 0 backups
    [2 type 3 flags 0x40008501 (0x63853e38) ext 0x0 (0x0) (collapsed)]
    LW-LDI[type=3, refc=1, ptr=0x63851da0, sh-ldi=0x63853e38]
    gateway array update type-time 1 Jun  6 12:41:10.589
    LDI Update time Jun  6 12:41:10.629
    LW-LDI-TS Jun  6 12:41:10.629
    Accounting: Disabled
    via 2001:DB8::1/128, 1 dependency, recursive [flags 0x3000000]
    path-idx 0 NHID 0x0 [0x63a2c098 0x0]
    next hop 2001:DB8::1/128 via 2001:DB8::1
    SRv6 H.Encaps.Red SID-list {2001:DB8:1:e002::}
    SRv6 H.Insert.Red SID-list {}
    SRv6 H.Insert.Red SID-list {bbbb:bbb:3:: bbbb:bbb:4::}
    via 2001:DB8::1/128, 1 dependency, recursive [flags 0x3000000]
    path-idx 1 NHID 0x0 [0x63a2c270 0x0]
    next hop 2001:DB8::1/128 via 2001:DB8::1
    SRv6 H.Encaps.Red SID-list {bbbb:bbb:2:e002::}
    SRv6 H.Insert.Red SID-list {}

    Load distribution: 0 1 2 2 (refcount 2)

    Hash  OK  Interface                Address
    0     Y   UNKNOWN intf 0x00000013    10::2
    1     Y   UNKNOWN intf 0x00000014    20::2
    2     Y   UNKNOWN intf 0x00000013    10::2
    3     Y   UNKNOWN intf 0x00000013    10::2

```

The described show output indicates that the IPv4 Layer 2 prefixes, which resolve as nexthop for Layer 3 prefixes are collapsed.

Example:

```

Router#show cef 209.165.201.1 detail
Output received:
Mon Dec  2 08:31:43.765 UTC
209.165.201.1/27, version 47031, internal 0x5000001 0x40 (ptr 0x98246ad8) [1], 0x0 (0x0), 0x0 (0x0)
Updated Dec  2 08:27:35.523
Prefix Len 32, traffic index 0, precedence n/a, priority 4
gateway array (0x98099098) reference count 1, flags 0x2010, source rib (7), 0 backups
    [1 type 3 flags 0x40441 (0x98134438) ext 0x0 (0x0)]
    LW-LDI[type=0, refc=0, ptr=0x0, sh-ldi=0x0]
    gateway array update type-time 1 Dec  2 08:27:35.523
    LDI Update time Dec  2 08:31:14.951

Level 1 - Load distribution: 0 1
[0] via 209.165.200.225/27, recursive
[1] via 209.165.200.226/27, recursive

via 209.165.200.225/27, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
path-idx 0 NHID 0x0 [0x982355c8 0x0]
next hop 209.165.200.225/27 via 209.165.200.225/27

Load distribution: 0 1 2 2 (refcount 1)

Hash  OK  Interface                Address
0     Y   HundredGigE0/0/0/0/2    fe80::2
1     Y   Bundle-Ether1201        fe80::2
2     Y   Bundle-Ether1301        fe80::3
3     Y   Bundle-Ether1301        fe80::3

```

```
via 209.165.200.226/27, 3 dependencies, recursive, bgp-multipath [flags 0x6080]
path-idx 1 NHID 0x0 [0x98235678 0x0]
next hop 209.165.200.226/27 via 209.165.200.226/27
```

```
Load distribution: 0 1 2 2 (refcount 1)
```

Hash	OK	Interface	Address
4	Y	HundredGigE0/0/0/0/2	fe80::2
5	Y	Bundle-Ether1201	fe80::2
6	Y	Bundle-Ether1301	fe80::3
7	Y	Bundle-Ether1301	fe80::3

Step 7 Run the **router static** command to configure and map the tags in RIB for IPv6 or IPv4 static routes.

Example:

```
Router#config
Router(config)#router static
Router(config-static)#address-family ipv6 unicast
Router(config-static-afi)#2001:DB8:8::/48 4::4 tag 100
Router(config-static-afi)#commit
```

Step 8 Run the **show route** command to view the configuration for IPv4 or IPv6 static routes.

Example:

The below show output displays the IPv4 static route configuration.

```
Router#show route 209.165.201.30

Tue Dec 3 18:22:39.579 UTC

Routing entry for 209.165.201.30/27
Known via "bgp 100", distance 200, metric 0, lvl2 has dependent
Tag 100, type internal
Installed Dec 3 18:22:35.820 for 00:00:03
Routing Descriptor Blocks
1::2, from 1::2, BGP multi path
Nexthop in Vrf: "default", Table: "default", IPv6 Unicast, Table Id: 0xe0800000
Route metric is 0
1::3, from 1::3, BGP multi path
Nexthop in Vrf: "default", Table: "default", IPv6 Unicast, Table Id: 0xe0800000
Route metric is 0
No advertising protos.
```

Example:

The below show output displays the IPv6 static route configuration.

```
Router#show route ipv6 2001:DB8:A:B::1 detail
Tue Dec 3 18:23:55.390 UTC

Routing entry for 2001:DB8:A:B::1/64
Known via "bgp 100", distance 200, metric 0, lvl2 has dependent
Tag 100, type internal
Installed Dec 3 18:22:45.835 for 00:01:09
Routing Descriptor Blocks
1::2, from 1::2
Route metric is 0
Label: None
Tunnel ID: None
Binding Label: None
Extended communities count: 0
NHID: 0x0 (Ref: 0)
Path Grouping ID: 100
SRv6 Headend: H.Encaps.Red [f3216], SID-list {fccc:bb01:2:e002::}
```

```
Route version is 0x1c (28)
No local label
IP Precedence: Not Set
QoS Group ID: Not Set
Flow-tag: Not Set
Fwd-class: Not Set
Route Priority: RIB_PRIORITY_RECURSIVE (12) SVD Type RIB_SVD_TYPE_LOCAL
Download Priority 4, Download Version 17265
No advertising protos.
```
