



Establish a Model-Driven Telemetry Session from a Collector to a Router

Streaming telemetry is a new paradigm in monitoring the health of a network. It provides a mechanism to efficiently stream configuration and operational data of interest from Cisco IOS XR routers. This streamed data is transmitted in a structured format to remote management stations for monitoring and troubleshooting purposes.

With telemetry data, you create a data lake. Analyzing this data, you proactively monitor your network, monitor utilization of CPU and memory, identify patterns, troubleshoot your network in a predictive manner, and devise strategies to create a resilient network using automation.

Telemetry works on a [subscription](#) model where you subscribe to the data of interest in the form of [sensor paths](#). The sensor paths describes [OpenConfig data models](#) or native Cisco data models. You can access the [OpenConfig](#) and [Native](#) data models for telemetry from Github, a software development platform that provides hosting services for version control. You choose who initiates the subscription by establishing a telemetry session between the router and the receiver. The session is established using either a [dial-out mode](#) or [dial-in mode](#), described in the [Scale-Up Your Network Monitoring Strategy Using Telemetry](#) article.




Note Watch this [video](#) to discover the power of real-time network management using model-driven telemetry.

This article describes the dial-in mode where a receiver dials in to the router to establish a telemetry session. In this mode, the receiver dials in to the router, and subscribes dynamically to one or more sensor paths specified in a subscription. The router streams telemetry data through the same session that is established by the receiver. The dial-in mode of subscriptions is dynamic. This dynamic subscription terminates when the receiver cancels the subscription or when the session terminates.

The following image shows a high-level overview of the dial-in mode:

Figure 1: Dial-In Mode



This article describes, with a use case that illustrates the simultaneous monitoring of various parameters in the network, how streaming telemetry data helps you gain better visibility of the network, and make informed decisions to stabilize it.



YANG Data Model

You can programmatically configure a dial-in telemetry session using `openconfig-telemetry.yang` OpenConfig data model. To get started with using data models, see the *Programmability Configuration Guide*.

- [Monitor Network Parameters Using Telemetry Data for Proactive Analysis, on page 2](#)

Monitor Network Parameters Using Telemetry Data for Proactive Analysis

The use case illustrates how, with the [dial-in mode](#), you can use telemetry data to stream various parameters about your network. You use this data for predictive analysis where you monitor patterns, and proactively troubleshoot issues. This use case describes the tools used in the open-sourced collection stack to store and analyse telemetry data.



Note Watch this [video](#) to see how you configure model-driven telemetry to take advantage of data models, open source collectors, encodings and integrate into monitoring tools.

Telemetry involves the following workflow:

- **Define:** You define a subscription to stream data from the router to the receiver. To define a subscription, you create a sensor-group.

- **Deploy:** The receiver initiates a session with the router and establishes a subscription-based telemetry session. The router streams data to the receiver. You verify subscription deployment on the router.
- **Operate:** You consume and analyse telemetry data using open-source tools, and take necessary actions based on the analysis.

Before you begin

Ensure you meet these dependancies:

- Make sure you have L3 connectivity between the router and the receiver.
- Enable gRPC server on the router to accept incoming connections from the receiver.

```
Router#configure
Router(config)#grpc
Router(config-grpc)#port <port-number>
Router(config-grpc)#commit
```

The port-number ranges from 57344 to 57999. If a port number is unavailable, an error is displayed.

- Configure a third-party application (TPA) source address. This address sets a source hint for Linux applications, so that the traffic originating from the applications can be associated to any reachable IP on the router.

```
Router(config)#tpa
Router(config)#address-family ipv4
Router(config-af)#update-source dataports TenGigE0/6/0/0/1
```

A default route is automatically gained in the Linux shell.

The following example shows the output of the gRPC configuration with TLS enabled on the router.

```
Router#show grpc
Address family : ipv4
Port : 57350
DSCP : Default
VRF : global-vrf
TLS : enabled
TLS mutual : disabled
Trustpoint : none
Maximum requests : 128
Maximum requests per user : 10
Maximum streams : 32
Maximum streams per user : 32
TLS cipher suites
Default : none
Enable : none
Disable : none
Operational enable : ecdhe-rsa-chacha20-poly1305
: ecdhe-ecdsa-chacha20-poly1305
: ecdhe-rsa-aes128-gcm-sha256
: ecdhe-ecdsa-aes128-gcm-sha256
: ecdhe-rsa-aes128-sha
Operational disable : none
```

Define a Subscription to Stream Data from Router to Receiver

Create a subscription to define the data of interest to be streamed from the router to the destination.

Procedure

- Step 1** Specify the subset of the data that you want to stream from the router using sensor paths. The [sensor path](#) represents the path in the hierarchy of a YANG data model. This example uses the native data model `Cisco-IOS-XR-um-telemetry-model-driven-cfg.yang`. Create a sensor-group to contain the sensor paths.

Example:

```
sensor-group health
  sensor-path Cisco-IOS-XR-wdsysmon-fd-oper:system-monitoring/cpu-utilization
  sensor-path Cisco-IOS-XR-nto-misc-oper:memory-summary/nodes/node/summary
  sensor-path Cisco-IOS-XR-shellutil-oper:system-time/uptime
  !
sensor-group interfaces
  sensor-path
Cisco-IOS-XR-infra-statsd-oper:infra-statistics/interfaces/interface/latest/generic-counters
  sensor-path Cisco-IOS-XR-pfi-im-cmd-oper:interfaces/interface-summary
  !
sensor-group optics
  sensor-path Cisco-IOS-XR-controller-optics-oper:optics-oper/optics-ports/optics-port/optics-info
  !
sensor-group routing
  sensor-path Cisco-IOS-XR-clns-isis-oper:isis/instances/instance/levels/level/adjacencies/adjacency

  sensor-path Cisco-IOS-XR-clns-isis-oper:isis/instances/instance/statistics-global
  sensor-path
Cisco-IOS-XR-ip-rib-ipv4-oper:rib/vrfs/vrf/afs/af/safs/saf/ip-rib-route-table-names/ip-rib-route-table-name/protocol/isis/as/information

  sensor-path Cisco-IOS-XR-ipv4-bgp-oper:bgp/instances/instance/instance-active/default-vrf/process-info
  !
sensor-group mpls-te
  sensor-path Cisco-IOS-XR-mpls-te-oper:mpls-te/tunnels/summary
  sensor-path Cisco-IOS-XR-ip-rsvp-oper:rsvp/interface-briefs/interface-brief
  sensor-path Cisco-IOS-XR-ip-rsvp-oper:rsvp/counters/interface-messages/interface-message
  !
```

- Step 2** Subscribe to telemetry data that is streamed from a router. A [subscription](#) binds the sensor-group, and sets the streaming method. The streaming method can be [cadence-driven](#) or [event-driven](#). Separating the sensor-paths into different subscriptions enhances the efficiency of the router to retrieve operational data at scale.

Example:

Note

The configuration for event-driven telemetry is similar to cadence-driven telemetry, with only the sample interval as the differentiator. Configuring the sample interval value to 0 (zero), sets the subscription for event-driven telemetry, while configuring the interval to any non-zero value sets the subscription for cadence-driven telemetry.

To receive telemetry data from the router to the receiver, see the *Define a Subscription to Stream Data from Router to Third Party Application (TPA)* section for the configuration details. Provide the client IP and port information according to your setup or requirements.

```
subscription health
  sensor-group-id health strict-timer
```

```

    sensor-group-id health sample-interval 30000
    !
  subscription interfaces
    sensor-group-id interfaces strict-timer
    sensor-group-id interfaces sample-interval 30000
    !
  subscription optics
    sensor-group-id optics strict-timer
    sensor-group-id optics sample-interval 30000
    !
  subscription routing
    sensor-group-id routing strict-timer
    sensor-group-id routing sample-interval 30000
    !
  subscription mpls-te
    sensor-group-id mpls-te strict-timer
    sensor-group-id mpls-te sample-interval 30000
    !

```

Verify Deployment of the Subscription

The receiver dials into the router to establish a dynamic session based on the subscription. After the session is established, the router streams data to the receiver to create a data lake.

You can verify the deployment of the subscription on the router.

Procedure

Verify the state of the subscription. An `Active` state indicates that the router is ready to stream data to the receiver based on the subscription.

Example:

```

Router#show telemetry model-driven subscription
Thu Jan 16 09:48:14.293 UTC
Subscription:  health                               State: Active
-----
  Sensor groups:
  Id            Interval(ms)      State
  health        30000              Resolved

Subscription:  optics                               State: NA
-----
  Sensor groups:
  Id            Interval(ms)      State
  optics        30000              Resolved

Subscription:  mpls-te                               State: NA
-----
  Sensor groups:
  Id            Interval(ms)      State
  mpls-te       30000              Resolved

Subscription:  routing                               State: NA
-----

```

```

Sensor groups:
Id              Interval(ms)      State
routing        30000             Resolved

Subscription: interfaces          State: NA
-----
Sensor groups:
Id              Interval(ms)      State
interfaces     30000             Resolved

Subscription: CPU-Utilization     State: NA
-----
Sensor groups:
Id              Interval(ms)      State
Monitor-CPU    30000             Resolved

Destination Groups:
Id              Encoding      Transport  State  Port  Vrf  IP
CPU-Health     self-describing-gpb tcp        NA    57500  Vrf  172.0.0.0
No TLS

```

The router streams data to the receiver using the subscription-based telemetry session and creates a data lake in the receiver.

Operate on Telemetry Data for In-depth Analysis of the Network

You can start consuming and analyzing telemetry data from the data lake using an open-sourced collection stack. This use case uses the following tools from the collection stack:

- Pipeline is a lightweight tool used to collect data. You can download [Network Telemetry Pipeline](#) from Github. You define how you want the collector to interact with routers, and where you want to send the processed data using `pipeline.conf` file.
- Telegraph or InfluxDB is a time series database (TSDB) that stores telemetry data, which is retrieved by visualization tools. You can download [InfluxDB](#) from Github. You define what data you want to include into your TSDB using the `metrics.json` file.
- [Grafana](#) is a visualization tool that displays graphs and counters for data streamed from the router.

In summary, Pipeline accepts TCP and gRPC telemetry streams, converts data and pushes data to the InfluxDB database. Grafana uses the data from InfluxDB database to build dashboards and graphs. Pipeline and InfluxDB may run on the same server or on different servers.

Consider that the router is monitored for the following parameters:

- Memory and CPU utilization
- Interface counters and interface summary
- Transmitter and receiver power levels from optic controllers
- ISIS route counts and ISIS interfaces
- BGP neighbours, path count, and prefix count
- MPLS-TE tunnel summary
- RSVP control messages and bandwidth allocation for each interface

Procedure

Step 1 Start Pipeline from the shell, and enter your router credentials.

Example:

```
$ bin/pipeline -config pipeline.conf
```

```
Startup pipeline
```

```
Load config from [pipeline.conf], logging in [pipeline.log]
```

```
CRYPT Client [grpc_in_myndtrouter], [http://172.0.0.0:5432]
```

```
Enter username: <username>
```

```
Enter password: <password>
```

```
Wait for ^C to shutdown
```

The streamed telemetry data is stored in InfluxDB.


Step 2 Use Grafana to create a dashboard and visualize the streamed data.

Figure 2: Visual Analysis of Network Health using Telemetry Data



369765

Figure 3: Visual Analysis of System Monitoring using Telemetry Data



In conclusion, telemetry data shows that various parameters of the network can be monitored simultaneously. This data is streamed in near real-time without affecting the performance of the network. With this data, you gain better visibility into your network.