



Newly Added Properties

NewScale.Properties

The below table lists the newly added *newscale.properties* that can control settings on other modules.

Table A-1 *newscale.properties introduced in patch releases*

Property	Description
Serviceformelement.display.instructional.helpertext	Enables the legacy display style for non-grid Dictionary field help texts by setting the property to true.
Serviceform.simtask.validation.skip	Bypasses the validation check that prevents the removal of Active Form Components, containing 1 or more service item based Dictionaries, from the service when 1 or more service item tasks are defined based on these dictionaries by setting the property to true.
MAX_ALLOWED_SERVICE_ITEM_EXPORT_RECORD_SIZE	Controls the service item records that can be exported to a .csv file from the My Stuff page and the Service Item Manager module by setting the parameter (Default is 1000).
servicecatalog.display.direct.category.service.association	Enables this to view the direct category associated with the service from Service Catalog by setting the property to true. Note This feature supports the display of only three levels of category hierarchy (excluding the placeholder category meant to occupy the Browse Category - All Showcase Location).
serviceform.add.attachment	Add attachments to a requisition at the time of ordering from Service Catalog module by setting the property to true.
ObjectCache.Environment.Name	You can assign name to the CPSC environment by using the property. This property can be referenced in the application with the namespace Site.ENV. For example, this namespace is used in the email templates to identify the source environment from which the email has originated, you can use the pound character (#) as delimiter to resolve the namespace.
localization.languages.export.limit=<export_count> localization.languages.import.limit=<import_count>	You can specify the limit on the number of languages (Default is 10) to be imported and exported by editing the two properties.
servicecatalog.display.req.percentage.completion	You can enable the percentage display in Service Catalog > My Stuff > Open Orders page by setting the property to true.

Table A-1 *newscale.properties introduced in patch releases*

Property	Description
nsapi.directory.person.hide.secure.information	You can hide the encrypted value of the password attribute and the cleartext value of the cloudpassword attribute by setting the property to true.
localization.languages.column.display.limit = <count>	You can specify the limit on the number of language columns (Default is 4) to be displayed in the grid by editing the property.
modules.ordermanagement.disable	You can disable Order Management for end user from being able to access the module directly from service catalog or service manager by editing the property to true.
serviceform.element.serverside.editable.disable	You can disable Editable on Server–Side only by editing the property to true.
deployment.service.authtask.agent.parameters.override	Overridden parameter values for external Authorization and Review tasks could be made to persist after deployment by editing the property to true.
servicecatalog.orderonbehalf.enable	Enables the new Order on Behalf functionality by setting the property to true.
serviceitem.remove.nextline	Enable this to convert multi–line service item field values to single–line value when exported to <i>.csv</i> by setting the property to true.
nsapi.person.create.trigger.email.enable	Enables an email on creation of new user account using nsAPI by setting the property to true.
ldap.enabled.prevent.user.password.update	You can disable the visibility of password related fields when the Directory Integration is enabled by setting the property to true.
enable.legacy.cr.isfjs.show.hide	Enable this to get back to the legacy functionality of Show/Hide CR and ISF JS by setting the property to true.
serviceitem.update.customer.details	You can update the subscription information for the Service Item instance while performing update operation by setting the property to true.
serviceform.ddr.null.value.as.empty	Enables the rendering of blank values as such on the Service Form for all dictionary fields by setting the property to true.
Serviceform.helpicon.clickable	Enables ‘?’ icon to be clicked on to close the help text popup by setting the property to true.
showAllTransactionsMessages	You can disable the default filter on the messages tab in Service Link during page load by setting the property to true.
prevent.queue.task.self.perform	You can disable the queue performers to access Authorization, Review, and Monitor Plan tasks for their own Requisitions, from Service Manager or Order Management modules by setting the property to true.
admin.setlocale.global	Enables the default language setting a global one, affecting both new and existing users in the system by setting the property to true.
session.token.nsapisc.validation	Enables token-based validation for nsAPI calls from Service Catalog by setting the property to 1.
htmlscan.enable	Enables the system to scan and remove the nonconforming content from the user input by setting the property to 1.
serviceitem.nsapi.rbac.check	You can disable the RBAC check for the service item based nsAPI’s by setting the property to false.