



MWTM Ports

The Cisco Mobile Wireless Transport Manager (MWTM) uses the following default ports to provide services:

Port Name or Number	Port Type	Description
1774	tcp	Apache web server
1775	tcp	TOMCAT Java Server Pages (JSP) server
44742	tcp	Java Remote Method Invocation (RMI) naming service
dynamic port 1	tcp	Java RMI service for Login Service. A network or system administrator can specify a fixed port using the LOGINSERVER_PORT parameter in the <i>System.properties</i> file. Note If you installed the MWTM in the default directory, <i>/opt</i> , then the location of the <i>System.properties</i> file is <i>/opt/CSCOsgm/properties/System.properties</i> . If you installed the MWTM in a different directory, then the <i>System.properties</i> file resides in that directory.
dynamic port 2	tcp	Java RMI service for the MWTM Data Server. A network or system administrator can specify a fixed port using the DATASERVER_PORT parameter in the <i>System.properties</i> file. Note If you installed the MWTM in the default directory, <i>/opt</i> , then the location of the <i>System.properties</i> file is <i>/opt/CSCOsgm/properties/System.properties</i> . If you installed the MWTM in a different directory, then the <i>System.properties</i> file resides in that directory.
162	udp	Simple Network Management Protocol (SNMP) trap listener
dynamic ports 1-25	udp	SNMP request senders. These ports are used by the SNMP stack for sending SNMP requests. A maximum of 25 can be opened in the MWTM. You can customize the number of ports by changing the SNMP_SOCKET_NUMBER parameter in the <i>Server.properties</i> file. Note If you installed the MWTM in the default directory, <i>/opt</i> , then the location of the <i>Server.properties</i> file is <i>/opt/CSCOsgm/properties/Server.properties</i> . If you installed the MWTM in a different directory, then the <i>Server.properties</i> file resides in that directory.

