



Support for REST API in Cisco Prime Access Registrar

This appendix provides information about the REpresentational State Transfer (REST) APIs supported in Cisco Prime Access Registrar. The purpose of this appendix is to provide a developer, system or network administrator, or system integrator with basic guidelines for using the outlined REST APIs within the Prime Access Registrar deployment.

REST API Framework

REST is a resource-based architectural style to create web services. A resource is an object, which could be a user, address, and so on. Each resource is identified by a Unique Resource Identifier (URI) and is manipulated by representations that pass back and forth between client and server. Representations can be in the form of XML, JSON, Plain, TEXT, or HTML. However, Prime Access Registrar supports only the JSON format.

[Table D-1](#) lists the common operations supported in Prime Access Registrar for REST APIs.

Table D-1 Common Operations Used in REST APIs

Method	Crud Operation
ADD	Create a resource
GET	Read and retrieve a representation of a resource
EDIT	Update an existing representation
DELETE	Delete a resource

REST API Services

You can use any client for creating the APIs and must pass the following information as inputs for the APIs:

- Content-Type—application/json
- username—username to access the service
- password—password to access the service

[Table D-1](#) lists the REST APIs used in Prime Access Registrar.

Table D-2 REST API Services

Object -> Type ID	ADD	EDIT	GET	DELETE
Script -> 1	<p><code>http://<hostname>:8080/RESTAPI/service/addobject</code></p> <p>Pass the object and the object name as data.</p> <p>Example:</p> <pre>{ "Script": { "Name": "test", .. } }</pre>	<p><code>http://<hostname>:8080/RESTAPI/service/editobject?typeid=1&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/getobject?typeid=1&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=1&name=<object name></code></p>
Client -> 2	<p><code>http://<hostname>:8080/RESTAPI/service/addobject</code></p> <p>Pass the object and the object name as data.</p>	<p><code>http://<hostname>:8080/RESTAPI/service/editobject?typeid=2&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/getobject?typeid=2&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=2&name=<object name></code></p>
Service -> 3	<p><code>http://<hostname>:8080/RESTAPI/service/addobject</code></p> <p>Pass the object and the object name as data.</p>	<p><code>http://<hostname>:8080/RESTAPI/service/editobject?typeid=3&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/getobject?typeid=3&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=3&name=<object name></code></p>
Policy -> 4	<p><code>http://<hostname>:8080/RESTAPI/service/addobject</code></p> <p>Pass the object and the object name as data.</p>	<p><code>http://<hostname>:8080/RESTAPI/service/editobject?typeid=4&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/getobject?typeid=4&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=4&name=<object name></code></p>
ResourceManager -> 5	<p><code>http://<hostname>:8080/RESTAPI/service/addobject</code></p> <p>Pass the object and the object name as data.</p>	<p><code>http://<hostname>:8080/RESTAPI/service/editobject?typeid=5&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/getobject?typeid=5&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=5&name=<object name></code></p>
Administrator -> 6	<p><code>http://<hostname>:8080/RESTAPI/service/addobject</code></p> <p>Pass the object and the object name as data.</p>	<p><code>http://<hostname>:8080/RESTAPI/service/editobject?typeid=6&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/getobject?typeid=6&name=<object name></code></p>	<p><code>http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=6&name=<object name></code></p>

Table D-2 REST API Services (continued)

Object -> Type ID	ADD	EDIT	GET	DELETE
RemoteServer -> 7	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=7&name=<object name>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=7&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=7&name=<object name>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=7&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=7&name=<object name>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=7&name=<object name></p>
UserGroup -> 8	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=8&name=<object name>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=8&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=8&name=<object name>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=8&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=8&name=<object name>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=8&name=<object name></p>
Profile -> 9	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=9&name=<object name>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=9&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=9&name=<object name>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=9&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=9&name=<object name>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=9&name=<object name></p>
Replication -> 10	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=10&name=<name of Repmember>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=10&name=<name of Repmember></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=10&name=<name of Repmember>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=10&name=<name of Repmember></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=10&name=Replication/Rep+Members/<name of Repmember>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=10&name=Replication/Rep+Members/<name of Repmember></p>
Rule -> 11	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=11&name=<object name>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=11&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=11&name=<object name>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=11&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=11&name=<object name>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=11&name=<object name></p>
SessionManager -> 12	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=12&name=<object name>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=12&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=12&name=<object name>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=12&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=12&name=<object name>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=12&name=<object name></p>
Snmp -> 13	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	—	—	—

Table D-2 REST API Services (continued)

Object -> Type ID	ADD	EDIT	GET	DELETE
RemoteODBCSession Server -> 14	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	—	—	—
UserList -> 16	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=16&name=<object name>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=16&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=16&name=<object name>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=16&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=16&name=<object name>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=16&name=<object name></p>
EncryptedIMSI-PrivateKeys -> 18	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=18&name=<name of key>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=18&name=<name of key></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=18&name=<name of key>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=18&name=<name of key></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=18&name=EncryptedIMSI-PrivateKeys/keys/<name of key>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=18&name=EncryptedIMSI-PrivateKeys/keys/<name of key></p>
ODBCDataSource -> 44	<p><a href="http://<hostname>:8080/RESTAPI/service/addobject">http://<hostname>:8080/RESTAPI/service/addobject</p> <p>Pass the object and the object name as data.</p>	<p><a href="http://<hostname>:8080/RESTAPI/service/editobject?typeid=44&name=<object name>">http://<hostname>:8080/RESTAPI/service/editobject?typeid=44&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/getobject?typeid=44&name=<object name>">http://<hostname>:8080/RESTAPI/service/getobject?typeid=44&name=<object name></p>	<p><a href="http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=44&name=<object name>">http://<hostname>:8080/RESTAPI/service/deleteobject?typeid=44&name=<object name></p>

Table D-3 provides a list of other REST APIs used in Prime Access Registrar.

Table D-3 Other APIs used in Prime Access Registrar

Operation	URL
Tacacs Statistics	<a href="http://<hostname>:8080/RESTAPI/service/Tacacsstatistics">http://<hostname>:8080/RESTAPI/service/Tacacsstatistics
Diameterstatistics	<a href="http://<hostname>:8080/RESTAPI/service/Diameterstatistics">http://<hostname>:8080/RESTAPI/service/Diameterstatistics
Statistics	<a href="http://<hostname>:8080/RESTAPI/service/Statistics">http://<hostname>:8080/RESTAPI/service/Statistics
RemoteServerStats	<a href="http://<hostname>:8080/RESTAPI/service/RemoteServerStats">http://<hostname>:8080/RESTAPI/service/RemoteServerStats
DiameterPeerStats	<a href="http://<hostname>:8080/RESTAPI/service/DiameterPeerStats">http://<hostname>:8080/RESTAPI/service/DiameterPeerStats
DiaRemoteServerStats	<a href="http://<hostname>:8080/RESTAPI/service/DiaRemoteServerStats">http://<hostname>:8080/RESTAPI/service/DiaRemoteServerStats
ClientStats	<a href="http://<hostname>:8080/RESTAPI/service/ClientStats">http://<hostname>:8080/RESTAPI/service/ClientStats
Reload	<a href="http://<hostname>:8080/RESTAPI/service/Reload">http://<hostname>:8080/RESTAPI/service/Reload
AddUser	<a href="http://<hostname>:8080/RESTAPI/service/adduser?UserListName=<nameofUserList>">http://<hostname>:8080/RESTAPI/service/adduser?UserListName=<nameofUserList>
GetUser	<a href="http://<hostname>:8080/RESTAPI/service/getuser?name=<nameofuser>&UserListName=<nameofuserlist>">http://<hostname>:8080/RESTAPI/service/getuser?name=<nameofuser>&UserListName=<nameofuserlist>

Table D-3 Other APIs used in Prime Access Registrar (continued)

Operation	URL
EditUser	http://<hostname>:8080/RESTAPI/service/edituser?name=< nameof user >&UserListName=<nameofuserlist>
DeleteUser	http://<hostname>:8080/RESTAPI/service/deleteuser?name=< nameof user>&UserListName=<nameofuserlist>

Example for adding a user using REST interface:

```
curl http://hostname:8080/RESTAPI/service/adduser?UserListName=new -H "Content-Type: application/json" -H "Authorization: Basic YWRtaW46YW1jdXNlcg==" --data '{"User\":{"Name\":"TestUser\","\Description\":"\","\Password\":"testuser\","\Enabled\":"TRUE\","\AllowNullPassword\":"FALSE\","\Attributes\":{"User-Name\":"joe\","\Nas-Port\":"3\"}}'
```

Always the JSON input must start with name of the objects while editing sub objects. A sample is given below:

```
curl -k -X PUT -H "Authorization: Basic YWRtaW46YW1jdXNlcg==" -H "Content-Type: application/json" 'https://<hostname>:8443/RESTAPI/service/editobject?typeid=18&name=key1' -data '{"AllowedKeyIdentifiers\":"hello\","\keys\":[{"Name\":"key1\","\identifier\":"100\","\PrivateKey\":"test456\"}]}'
```



Note

REST interface can also be accessed using HTTPS through the 8443 port.

CoA and PoD REST APIs

The Change of Authorization (CoA) and Packet of Disconnect (PoD) API calls allow you to send session reauthentication and session disconnect commands for a specified session.

You can use any client for creating the APIs and must pass the following information as inputs for the APIs:

- URL—URL to access the PoD/CoA service. Example:
 - For PoD—http://<hostname>:8080/RESTAPI/service/PoD
 - For CoA—http://<hostname>:8080/RESTAPI/service/CoA
- Content-Type—application/json
- username—username to access the service
- password—password to access the service
- data—API body with syntax as listed in [Table D-4](#)

Example

The following example shows a sample API written using cURL client.

```
http://ar-lnx-vm054:8080/RESTAPI/service/PoD -H "Content-Type: application/json" -H "username:admin -H "password:aicuser --data '{"parameter":"S21", "value":"","type":"with-id}"
```

Prime Access Registrar supports basic authentication with Base64 encoding support for username and password.

A sample header on encryption is provided in the example below:

```
-H "Authorization: Basic YWRtaW46YWljdXNlcg=="
```

**Note**

REST interface can also be accessed using HTTPS through the 8443 port.

Table D-4 Parameter and Data Syntax for APIs

Parameter	Data Syntax/Example
with-id	"{"parameter":"S21","value":"","type":"with-id"}"
with-user	"{"parameter":"bob","value":"","type":"with-user"}"
with-key	"{"parameter":"bob","value":"","type":"with-key"}"
with-nas	"{"parameter":"localhost","value":"","type":"with-nas"}"
with-ip-address	"{"parameter":"192.168.0.4","value":"","type":"with-ip-address"}"
with-ipx-network	"{"parameter":"0x6","value":"","type":"with-ipx-network"}"
with-age	"{"parameter":"1S","value":"","type":"with-age"}"
with-usr-vpn	"{"parameter":"1","value":"","type":"with-usr-vpn"}"
with-attribute	"{"parameter":"Framed-IP-Address","value":"192.168.0.1","type":"with-attribute"}"
with-Home-Agent	"{"parameter":"","value":"","type":"with-Home-Agent"}"
with-IP-Subnet	"{"parameter":"","value":"","type":"with-IP-Subnet"}"

REST API Support for Query and Release Sessions

The REST interface allows you to perform the following:

- Query the server about the currently active user sessions
- Release the currently active user sessions

You can request information about those sessions that match a specified filter type, which could be one of the following:

- with-id
- with-user
- with-key
- with-nas
- with-ip-address
- with-ipx-network
- with-age
- with-usr-vpn
- with-attribute

- with-Home-Agent
- with-IP-Subnet

Table D-5 lists the details of REST APIs for query and release session services.

Table D-5 REST APIs for Query and Release Sessions

Service	URL	Inputs	Sample API
Query Session	<code>http://<hostname>:8080/RESTAPI/service/querySessions?path=/r&filterType=with-user&filterValue=bob</code>	<ul style="list-style-type: none"> • Content-Type—application/json • username—username to access the services • password—password to access the service • filterType—as listed above 	<pre>curl -H "username:admin" -H "password:aicuser" 'http://ar-lnx-vm038:8080/RESTAPI/service/querySessions?path=/r&filterType=with-user&filterValue=bob' {"session-mgr-1":{"S3":{"Username":"bob","Key":"localhost:1","Nas":"localhost","IP":"192.168.0.0","IPX":"0x1","GSL":"1","USL":"1","UserVPN":"1","Nas-port":"1","Time":"00:01:17","User-Name":"bob"}}} [root@ar-lnx-vm049 ~]#</pre>
Release Session	<code>http://<hostname>:8080/RESTAPI/service/releasesessions?path=/r&filterType=with-user&filterValue=bob</code>		<pre>curl -X GET -H "username:admin" -H "password:aicuser" -H "Content-Type:application/json" 'http://ar-lnx-vm041:8080/RESTAPI/service/releasesessions?path=/r/SessionManagers/&filterType=with-user&filterValue=bob' Released 1 session(s) Successfully in /Radius/SessionManagers</pre>

