



Uninstalling Cisco Prime Network Registrar

You must have administrator or superuser privileges to uninstall Cisco Prime Network Registrar, just as you must to install it.

To back up your database before uninstalling Cisco Prime Network Registrar, see the *Cisco Prime Network Registrar 11.2 Administration Guide* for the procedure.



Note Uninstallation stops the Cisco Prime Network Registrar server agents first. If you find that the server processes are not shutting down, see [Starting and Stopping Servers](#).

- [Uninstalling Cisco Prime Network Registrar, on page 1](#)

Uninstalling Cisco Prime Network Registrar

To uninstall Cisco Prime Network Registrar, run any of the following commands:

```
# rpm -e kitname
```

OR

```
# yum remove kitname
```

OR

```
# dnf remove kitname
```

where *kitname* is either `cpnr-local`, `cpnr-regional`, or `cpnr-client`.

For example, to uninstall the regional cluster, use any of the following commands:

```
# rpm -e cpnr-regional
```

OR

```
# yum remove cpnr-regional
```

OR

```
# dnf remove cpnr-regional
```

Certain configuration and data files that are created during installation and operation remain deliberately after uninstallation. Optionally, delete the data files that are associated with Cisco Prime Network Registrar, as mentioned in the instructions at the end of the uninstallation message.