



CHAPTER 6

Managing Policies

This chapter provides information about managing policies.

This chapter includes the following sections:

- [Working With Core File Policies, page 6-1](#)
- [Working With Fault Policies, page 6-5](#)
- [Working With Log Policies, page 6-9](#)
- [Working With Syslog Policies, page 6-14](#)

Working With Core File Policies

This section includes the following topics:

- [Creating a Core File Policy, page 6-1](#)
- [Displaying Core File Policies, page 6-2](#)
- [Deleting a Core File Policy, page 6-4](#)

Creating a Core File Policy

You can create core file policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect** `policy-mgr`
2. **scope** `org`
3. **scope** `policy`
4. **create** `corefile` *<policy-name>* *<transfer-host-name>* *<file-path>* { **disabled** | **enabled** }

5. commit-buffer

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnm# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnm(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnm(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	create corefile Example vnm(policy-mgr) /org/policy # create corefile EaCoreP12 hostname /test enabled	Creates a core file policy. For the policy name, the maximum number of characters is 32.
Step 5	commit-buffer Example: vnm(policy-mgr) /org/policy/corefile* # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to create a core file policy:

```
vnm# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnm(policy-mgr)# scope org
vnm(policy-mgr) /org # scope policy
vnm(policy-mgr) /org/policy # create corefile EaCoreP12 hostname /test enabled
vnm(policy-mgr) /org/policy/corefile* # commit-buffer
vnm(policy-mgr) /org/policy/corefile #
```

Displaying Core File Policies

You can display core file policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **show corefile**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnm# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnm(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnm(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	show corefile Example vnm(policy-mgr) /org/policy # show corefile	Displays core file policies.

EXAMPLES

This example shows how to display all core file policies in list form:

```
vnm# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnm(policy-mgr)# scope org
vnm(policy-mgr) /org # scope policy
```

```

vnmcli(policy-mgr) /org/policy # show corefile

Core File Policy:
  Core File Policy Name: local
  Core File Transfer Host Name: nexthost
  Core File Policy Path: /test
  Core File Policy Admin State: Enabled

  Core File Policy Name: host
  Core File Transfer Host Name: nexthost
  Core File Policy Path: /test
  Core File Policy Admin State: Enabled
vnmcli(policy-mgr) /org/policy #

```

Deleting a Core File Policy

You can delete core file policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **delete corefile** *<policy-name>*
5. **commit-buffer**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnmcli# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnmcli(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnmcli(policy-mgr) /org # scope policy	Places you in policy mode.

	Command	Purpose
Step 4	delete corefile Example vnmc(policy-mgr) /org/policy # delete corefile EaCoreP12	Deletes a core file policy.
Step 5	commit-buffer Example: vnmc(policy-mgr) /org/policy * # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to delete the core file:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr)# scope org
vnmc(policy-mgr)# scope policy
vnmc(policy-mgr) /org/policy # delete corefile EaCoreP12
vnmc(policy-mgr) /org/policy* # commit-buffer
vnmc(policy-mgr) /org/policy #
```

Working With Fault Policies

This section includes the following topics:

- [Creating a Fault Policy, page 6-5](#)
- [Displaying Fault Policies, page 6-7](#)
- [Deleting a Fault Policy, page 6-8](#)

Creating a Fault Policy

You can create fault policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **create faultpolicy** *<policy-name>* *<flap-interval>* { **delete** | **retain** } { *<number-of-days>* | **forever** } { **disabled** | **enabled** }
5. **commit-buffer**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnm# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnm(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnm(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	create faultpolicy Example vnm(policy-mgr) /org/policy # create faultpolicy EaFaultPA13 10 retain forever enabled	Creates a fault policy. For the policy name, the maximum number of characters is 32.
Step 5	commit-buffer Example: vnm(policy-mgr) /org/policy/faultpolicy* # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to create a fault policy named EaFaultPA13:

```
vnm# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnm(policy-mgr)# scope org
```

```

vnmcli(policy-mgr) /org # scope policy
vnmcli(policy-mgr) /org/policy # create faultpolicy EaFaultPA13 10 retain forever enabled
vnmcli(policy-mgr) /org/policy/faultpolicy* # commit-buffer
vnmcli(policy-mgr) /org/policy/faultpolicy #

```

Displaying Fault Policies

You can display fault policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. connect policy-mgr
2. scope org
3. scope policy
4. show faultpolicy

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnmcli# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnmcli(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnmcli(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	show faultpolicy Example vnmcli(policy-mgr) /org/policy # show faultpolicy	Displays fault policies.

EXAMPLES

This example shows how to display all fault policies in list form:

```

vnmcli# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac

```

Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
 The copyrights to certain works contained in this software are owned by other third parties and used and distributed under license. Certain components of this software are licensed under the GNU General Public License (GPL) version 2.0 or the GNU Lesser General Public License (LGPL) Version 2.1. A copy of each such license is available at
<http://www.opensource.org/licenses/gpl-2.0.php> and
<http://www.opensource.org/licenses/lgpl-2.1.php>

```
vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope policy
vnmc(policy-mgr) /org/policy # show faultpolicy
```

```
Fault Policy:
  Fault Policy Name: default
  Fault Policy Clear Action: Retain
  Fault Policy Flap Interval (dd:hh:mm:ss): 00:00:00:10
  Fault Policy Retention Interval (dd:hh:mm:ss): 10:00:00:00
  Fault Policy Admin State: Enabled

  Fault Policy Name: EaFaultPA13
  Fault Policy Clear Action: Retain
  Fault Policy Flap Interval (dd:hh:mm:ss): 00:00:00:05
  Fault Policy Retention Interval (dd:hh:mm:ss): 100:00:00:00
  Fault Policy Admin State: Enabled
```

Deleting a Fault Policy

You can delete fault policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **delete faultpolicy** *<policy-name>*
5. **commit-buffer**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnm# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnm(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnm(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	delete faultpolicy Example vnm(policy-mgr) /org/policy # delete faultpolicy EaFaultPA13	Deletes a fault policy.
Step 5	commit-buffer Example: vnm(policy-mgr) /org/policy* # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to delete a fault policy named sysfault:

```
vnm# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnm(policy-mgr)# scope org
vnm(policy-mgr) /org # scope policy
vnm(policy-mgr) /org/policy # delete faultpolicy EaFaultPA13
vnm(policy-mgr) /org/policy* # commit-buffer
vnm(policy-mgr) /org/policy #
```

Working With Log Policies

This section includes the following topics:

- [Creating a Log Policy, page 6-10](#)
- [Displaying Log Policies, page 6-11](#)

- [Deleting a Log Policy, page 6-12](#)

Creating a Log Policy

You can create log policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **create log** *<policy-name>* *<log-policy-backup-count>* {**critical** | **debug0** | **debug1** | **debug2** | **debug3** | **debug4** | **info** | **major** | **minor** | **warning**} *<log-policy-size>*
5. **commit-buffer**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnm# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnm(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnm(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	create log Example vnm(policy-mgr) /org/policy # create log EaLogP13 9 critical 10000000	Creates a log policy. For the policy name, the maximum number of characters is 32.
Step 5	commit-buffer Example: vnm(policy-mgr) /org/policy/log* # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to create a log policy named EaLogP13:

```
vnm# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnm(policy-mgr)# scope org
vnm(policy-mgr) /org # scope policy
vnm(policy-mgr) /org/policy # create log EaLogP13 9 critical 10000000
vnm(policy-mgr) /org/policy/log* # commit-buffer
vnm(policy-mgr) /org/policy/log #
```

Displaying Log Policies

You can display log policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **show log**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnm# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnm(policy-mgr)# scope org	Places you in organization mode.

	Command	Purpose
Step 3	scope policy Example: vnm (policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	show log Example vnm (policy-mgr) /org/policy # show log	Displays log policies.

EXAMPLES

This example shows how to display all log policies in list form:

```
vnm# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnm(policy-mgr)# scope org
vnm(policy-mgr) /org # scope policy
vnm(policy-mgr) /org/policy # show log

Logging Policy:
  Logging Policy Name: LogPA1
  Logging Policy Backup Count: 2
  Logging Policy Level: Debug1
  Logging Policy Size: 10000000
  Logging Policy Admin State: Enabled

  Logging Policy Name: LogPA2
  Logging Policy Backup Count: 1
  Logging Policy Level: critical
  Logging Policy Size: 1000000
  Logging Policy Admin State: Enabled
vnm(policy-mgr) /org/policy #
```

Deleting a Log Policy

You can delete fault policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **delete log <policy-name>**
5. **commit-buffer**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnmcli# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnmcli(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnmcli(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	delete log Example vnmcli(policy-mgr) /org/policy # delete log EaLogP13	Deletes a log policy.
Step 5	commit-buffer Example: vnmcli(policy-mgr) /org/policy* # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to delete a log policy named EaLogP13:

```
vnmcli# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php
```

```

vnmc(policy-mgr) # scope org
vnmc(policy-mgr) /org # scope policy
vnmc(policy-mgr) /org/policy # delete log EaLogP13
vnmc(policy-mgr) /org/policy* # commit-buffer
vnmc(policy-mgr) /org/policy #

```

Working With Syslog Policies

This section includes the following topics:

- [Creating a Syslog Policy, page 6-14](#)
- [Displaying Syslog Policies, page 6-15](#)
- [Deleting a Syslog Policy, page 6-16](#)

Creating a Syslog Policy

You can create syslog policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **create syslog <policy-name>**
5. **commit-buffer**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnmc# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnmc(policy-mgr)# scope org	Places you in organization mode.

	Command	Purpose
Step 3	scope policy Example: vnmcli(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	create syslog Example vnmcli(policy-mgr) /org/policy # create syslog EaSysPA13	Creates a syslog policy. For the policy name, the maximum number of characters is 32.
Step 5	commit-buffer Example: vnmcli(policy-mgr) /org/policy/syslog* # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to create a log policy named EaSysPA13:

```
vnmcli# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmcli(policy-mgr) # scope org
vnmcli(policy-mgr) /org # scope policy
vnmcli(policy-mgr) /org/policy # create syslog EaSysPA13
vnmcli(policy-mgr) /org/policy/syslog* # commit-buffer
vnmcli(policy-mgr) /org/policy/syslog #
```

Displaying Syslog Policies

You can display syslog policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**

3. **scope policy**
4. **show syslog**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnm# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnm(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnm(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	show syslog Example vnm(policy-mgr) /org/policy # show syslog	Displays syslog policies.

EXAMPLES

This example shows how to display all log policies in list form:

```
vnm# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnm(policy-mgr)# scope org
vnm(policy-mgr) /org # scope policy
vnm(policy-mgr) /org/policy # show syslog

name: default
description: Syslog Service
name: EaSysPA13
description: Syslog Service
vnm(policy-mgr) /org/policy #
```

Deleting a Syslog Policy

You can delete syslog policies.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-8](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope policy**
4. **delete syslog** *<policy-name>*
5. **commit-buffer**

DETAILED STEPS

	Command	Purpose
Step 1	connect policy-mgr Example: vnmc# connect policy-mgr	Places you in the policy manager CLI.
Step 2	scope org Example: vnmc(policy-mgr)# scope org	Places you in organization mode.
Step 3	scope policy Example: vnmc(policy-mgr) /org # scope policy	Places you in policy mode.
Step 4	delete syslog Example vnmc(policy-mgr) /org/policy # delete syslog EaSysPA13	Deletes a syslog policy.
Step 5	commit-buffer Example: vnmc(policy-mgr) /org/policy* # commit-buffer	Commits (saves) the configuration.

EXAMPLES

This example shows how to delete a log policy named EaSysPA13:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
```

Lesser General Public License (LGPL) Version 2.1. A copy of each such license is available at <http://www.opensource.org/licenses/gpl-2.0.php> and <http://www.opensource.org/licenses/lgpl-2.1.php>

```
vnmc(policy-mgr)# scope org
vnmc(policy-mgr)# scope policy
vnmc(policy-mgr) /org/policy # delete syslog EaSysPA13
vnmc(policy-mgr) /org/policy* # commit-buffer
vnmc(policy-mgr) /org/policy #
```