



Cisco Nexus Data Broker Configuration Guide, Release 3.2

First Published: 2016-12-07

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <http://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)



The Java logo is a trademark or registered trademark of Sun Microsystems, Inc. in the U.S. or other countries.

© 2016 Cisco Systems, Inc. All rights reserved.



Cisco Nexus Data Broker Overview

This chapter contains the following sections:

- [About Cisco Nexus Data Broker, page 1](#)
- [Supported Web Browsers, page 5](#)
- [Guidelines and Limitations, page 5](#)
- [Prerequisites for Cisco Nexus Series Switches, page 6](#)

About Cisco Nexus Data Broker

Visibility into application traffic has traditionally been important for infrastructure operations to maintain security, troubleshooting, and compliance and perform resource planning. With the technological advances and growth in cloud-based applications, it has become imperative to gain increased visibility into the network traffic. Traditional approaches to gain visibility into network traffic are expensive and rigid, making it difficult for managers of large-scale deployments.

Cisco Nexus Data Broker with Cisco Nexus Switches provides a software-defined, programmable solution to aggregate copies of network traffic using Switched Port Analyzer (SPAN) or network Test Access Point (TAP) for monitoring and visibility. As opposed to traditional network taps and monitoring solutions, this packet-brokering approach offers a simple, scalable and cost-effective solution that is well-suited for customers who need to monitor higher-volume and business-critical traffic for efficient use of security, compliance, and application performance monitoring tools.

With the flexibility to use a variety of Cisco Nexus Switches and the ability to interconnect them to form a scalable topology provides the ability to aggregate traffic from multiple input TAP or SPAN ports, and replicate and forward traffic to multiple monitoring tools which may be connected across different switches. Combining the use of Cisco plugin for OpenFlow and the Cisco NX-API agent to communicate to the switches, Cisco Nexus Data Broker provides advance features for traffic management.

Cisco Nexus Data Broker provides management support for multiple disjointed Cisco Nexus Data Broker networks. You can manage multiple Cisco Nexus Data Broker topologies that may be disjointed using the same application instance. For example, if you have 5 data centers and want to deploy an independent Cisco Nexus Data Broker solution for each data center, you can manage all 5 independent deployments using a single application instance by creating a logical partition (network slice) for each monitoring network.

**Note**

Starting with Cisco Nexus Data Broker Release 3.1, the user strings for Cisco Nexus Data Broker can contain alphanumeric characters including the following special characters: period (.), underscore (_), or hyphen (-). These are the only special characters that are allowed in the user strings.

**Note**

The hostname string for Cisco Nexus Data Broker can contain between 1 and 256 alphanumeric characters including the following special characters: period (.), underscore (_), or hyphen (-). These are the only special characters that are allowed in the user strings.

Cisco Nexus Data Broker provides the following:

- Support for the OpenFlow mode or the NX-API mode of operation.

**Note**

The OpenFlow mode and the NX-API mode are supported on both Cisco Nexus 3000 Series and Cisco Nexus 9000 Series switches. Cisco Nexus 9500, 9200, and 9300-EX switches support only NX-API mode of deployment. Cisco Nexus 3500 supports only Openflow mode of deployment. You can enable only one mode, either OpenFlow or NX-API mode, at a time.

In order to start or stop the Cisco Nexus Data Broker application in embedded mode, you should activate or de-activate the ofa file. Do not use ./runxnc.sh as it is not the right way to start the application.

You can enable only one mode, either OpenFlow or NX-API mode, at a time.

When using OpenFlow mode, NX-API is available for auxiliary configurations only, for example, Enabling Q-in-Q on the SPAN and TAP ports.

Cisco NX-OS Release 7.0(3)I5(1) supports only Cisco Nexus Data Broker 3.2 embedded version.

Cisco Nexus 9300-EX Series switches support only Cisco NX-OS Release 7.0(3)I5(1).

The configuration that is supported in the AUX mode is:

- Pull and push of interface description
- Q-in-Q configuration
- Redirection
- Port Channel load balancing
- MPLS Stripping

**Note**

Starting with Cisco Nexus 3000 Release 7.x, the NX-API configuration is supported on the following Cisco Nexus Series switches:

- Cisco Nexus 3172 switches
- Cisco Nexus 3132 switches
- Cisco Nexus 3164 switches
- Cisco Nexus 31128 switches
- Cisco Nexus 3232 switches
- Cisco Nexus 3264 switches
- Cisco Nexus 3100-V switches

- The features that are supported with the Cisco Nexus 9500 Series switches are:
 - The NX-API feature is supported. (OpenFlow is not supported.)
 - The MPLS strip feature is supported.
 - The label age CLI feature is not supported.
- Support for Layer-7 filtering for the HTTP traffic using the HTTP methods.
- Support for VLAN and MPLS tag stripping.
- A scalable topology for TAP and SPAN port aggregation.
- Support for Q-in-Q to tag input source TAP and SPAN ports.
- Symmetric load balancing.
- Rules for matching monitoring traffic based on Layer 1 through Layer 4 information.
- The ability to replicate and forward traffic to multiple monitoring tools.
- Time stamping using Precision Time Protocol (PTP).
- Packet truncation beyond a specified number of bytes to discard payload.
- Reaction to changes in the TAP/SPAN aggregation network states.
- Security features, such as role-based access control (RBAC), and integration with an external Active Directory using RADIUS or TACACS for authentication, authorization, and accounting (AAA) functions.
- End-to-end path visibility, including both port and flow level statistics for troubleshooting.
- Robust Representational State Transfer (REST) API and a web-based GUI for performing all functions
- Support for Cisco plugin for Open Flow, version 1.0
- Cisco Nexus Data Broker adds NX-API plugin to support Cisco Nexus 9000 Series switches as TAP/SPAN aggregation. The NX-API supports JSON-RPC, XML, and JSON. Cisco Nexus Data Broker interacts with Cisco Nexus 9000 Series using the NX-API in JSON message formats.
- Beginning with Cisco Nexus Data Broker, Release 3.1, Cisco Nexus Data Broker is certified with Cisco Nexus 9200 Series and Cisco Nexus 9300-EX Series switches.

The following features are supported on the Cisco Nexus 9300-EX Series switches:

- Symmetric Load Balancing
- Q-in-Q
- Switch Port Configuration
- MPLS Stripping
- BlockTx

The following features are not supported on the Cisco Nexus 9300-EX Series switches:

- Timestamp Tagging
- Truncate

- Beginning with Cisco Nexus Data Broker, Release 3.1, Cisco Nexus Data Broker is shipped with a certificate for the HTTPS connection between the Cisco Nexus Data Broker and a browser. Now with this feature, you can change to a different certificate than the shipped certificate.

The script **generateWebUICertificate.sh** is available in the **xnc/configuration** folder. If you execute this script, it moves the shipped certificate to **old_keystore** and the new certificate is generated in **keystore**. On the next Cisco Nexus Data Broker restart, this new certificate is used.

With Cisco Nexus Data Broker, you can:

- Classify Switched Port Analyzer (SPAN) and Test Access Point (TAP) ports.
- Integrate with Cisco ACI through Cisco APIC to configure SPAN destinations and SPAN sessions.
- Add monitoring devices to capture traffic.
- Filter which traffic should be monitored.
- Redirect packets from a single or multiple SPAN or TAP ports to multiple monitoring devices through delivery ports.
- Restrict which users can view and modify the monitoring system.
- If Cisco Nexus 9000 Series switch is using 7.0(3)I4(1) or later version in NX-API mode and if a flow is installed using a VLAN filer, then the device goes through an IP access list and it does not match on the Layer 2 packet.
- Configure these additional features, depending upon the type of switch:
 - Enable MPLS Tag stripping.
 - Set VLAN ID on Cisco Nexus 3000 Series switches.
 - Symmetric load balancing on Cisco Nexus 3100 Series switches and Cisco Nexus 9000 Series switches.
 - Q-in-Q on Cisco Nexus 3000 Series switches, 3100 Series switches, and Cisco Nexus 9000 Series switches.
 - Timestamp tagging and packet truncation on Cisco Nexus 3500 Series switches.
 - You can now configure the **watchdog_timer** configuration parameter in the **config.ini** file. If the value of the parameter is set to 0, the watchdog timer functionality is not available. The value of

30 seconds is a minimum value of the parameter and if the value of the parameter is set to a value more the 30 seconds, the watchdog timer monitors the JAVA process for the configured time interval.

Supported Web Browsers

The following web browsers are supported for Cisco Nexus Data Broker:

- Firefox 18.x and later versions
- Chrome 24.x and later versions

**Note**

JavaScript 1.5 or a later version must be enabled in your browser.

Guidelines and Limitations

Cisco Nexus Data Broker runs in a Java Virtual Machine (JVM). As a Java-based application, Cisco Nexus Data Broker can run on any x86 server. For best results, we recommend the following:

- One 8-core CPU at 2 GHz or higher.
- A minimum of 16 GB of memory.
- A minimum of 40 GB of free hard disk space must be available on the partition where you will be installing the Cisco Nexus Data Broker application.
- A 64-bit Linux distribution with Java, such as the following:
 - Ubuntu Linux
 - Red Hat Enterprise (RHEL) Linux
 - Fedora Linux
- You can skip JAVA check while running Cisco Nexus Data Broker. When you enter the **./runxnc.sh -skipjavacheck** command, it skips the JAVA check and Cisco Nexus Data Broker runs irrespective of the JAVA version.
- Java Virtual Machine 1.8.0_45 and higher.
- Python 2.7.3 and a higher version is required for the backup and restore script. This is also required to do the TLS configuration if Cisco Nexus Data Broker needs to use TLS for the device communication.
- A \$JAVA_HOME environment variable in your profile that is set to the path of the JVM.
- JConsole and VisualVM that are both part of JDK are the recommended (but not required) additions for troubleshooting.

- During OpenFlow configuration for Cisco NXOS Release 7.0(3)I5(1) software image, virtual service ofa should not be installed and the following configuration should be used:

```
switch#
conf t
feature openflow
openflow
switch 1 pipeline 201
controller ipv4 10.16.206.162 port 6653 vrf management security none
of-port interface ethernet1/1
of-port interface ethernet1/2
```

See the following link for further details on NXOS configuration for OpenFlow: http://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus/openflow/b_openflow_agent_nxos_1_3/Cisco_Plug_in_for_OpenFlow.html#reference_B6284F508CC6461B8EF30DCF870C809F

- You should not configure the same name for more than one switch in the topology to avoid unpredictable behavior in the link discovery by Cisco Nexus Data Broker.
- When the domain name is enabled in the switch, it does not reflect the change in the LLDP neighbors and the links get removed for that particular switch. The workaround for this issue is to disable the LLDP feature and then to enable it again by using **no feature lldp** and **feature lldp** CLI commands respectively.

Global Updates with Cisco Nexus Data Broker, Release 3.2

See the following global updates that are available with Cisco Nexus Data Broker, Release 3.2:

- The ports in the Graphical User Interface (GUI) are listed in a sorted order.
- A new field, **Row Count** is added in the GUI to display the rows in the multiples of 10, 25, 50, and 100.

Prerequisites for Cisco Nexus Series Switches

Cisco Nexus Data Broker is supported on Cisco Nexus 3000, 3100, 3200, 3500, and 9000 series switches. Before you deploy the software, you must do the following:

- Ensure that you have administrative rights to log in to the switch.
- Verify that the management interface of the switch (mgmt0) has an IP address configured by running the switch# **show running-config interface mgmt0** command.
- Add the VLAN range in the database that is to be used in Cisco Nexus Data Broker for tap aggregation and inline monitoring redirection to support VLAN filtering. For example, the syntax is **vlan <range of VLAN IDs>**. For example, the VLAN range is <1-3967>.

For running the OpenFlow and NX-API mode on the Cisco Nexus Series switches, see the following pre-requisites.

Device Models	OpenFlow Mode	NX-API Mode
Cisco Nexus 3000 Series switches	Enter the # hardware profile openflow command at the prompt.	With Cisco Nexus 3000 Series switches, only Openflow mode is supported.

Device Models	OpenFlow Mode	NX-API Mode
Cisco Nexus 3164Q switches	The OpenFlow mode is not supported on the Nexus 3164Q switches.	Enter the following commands at the prompt: <ul style="list-style-type: none"> • # hardware profile tcam region qos 0 • # hardware profile tcam region racl 0 • # hardware profile tcam region vACL 0 • # hardware profile tcam region ifacl 1024 double-wide • # hardware access-list tcam region mac-ifacl 512
Cisco Nexus 3172 Series switches	Enter the # hardware profile openflow command at the prompt.	Use the hardware profile mode tap-aggregation [l2drop] CLI command to enable tap aggregation and to reserve entries in the interface table that are needed for VLAN tagging. The l2drop option drops non-IP traffic ingress on tap interfaces.
Cisco Nexus 3200 Series switches	Enter the hardware access-list tcam region openflow 256 command at the prompt.	Enter the following commands at the prompt: <ul style="list-style-type: none"> • # hardware access-list tcam region e-racl 0 • # hardware access-list tcam region span 0 • # hardware access-list tcam region redirect 0 • # hardware access-list tcam region vpc-convergence 0 • # hardware access-list tcam region racl-lite 256 • # hardware access-list tcam region l3qos-intra-lite 0 • # hardware access-list tcam region ifacl 256 double-wide • # hardware access-list tcam region mac-ifacl 512

Device Models	OpenFlow Mode	NX-API Mode
Cisco Nexus 9300 Series switches	<p>Enter the hardware access-list tcam region openflow 512 double-wide command at the prompt to configure the MAC filters.</p> <p>For other scenarios, enter the hardware access-list tcam region openflow 512 command.</p>	<p>Enter the following commands at the prompt:</p> <ul style="list-style-type: none"> • # hardware access-list tcam region qos 0 • # hardware access-list tcam region vacl 0 • # hardware access-list tcam region racl 0 • # hardware access-list tcam region redirect 0 • # hardware access-list tcam region vpc-convergence 0 • # hardware access-list tcam region ifacl 1024 double-wide • # hardware access-list tcam region mac-ifacl 512
Cisco Nexus 9200 and 9300-EX switches	The OpenFlow mode is not supported on the 9200 and 9300-EX switches.	<p>Enter the following commands at the prompt:</p> <ul style="list-style-type: none"> • # hardware access-list tcam region ing-racl 256 • # hardware access-list tcam region ing-l3-vlan-qos 256 • # hardware access-list tcam region egr-racl 256 • # hardware access-list tcam region ing-ifacl 1024



Deploying Cisco Nexus Data Broker

This chapter contains the following sections:

- [Installing Cisco Nexus Data Broker, page 9](#)

Installing Cisco Nexus Data Broker

Installing or Upgrading the Cisco Nexus Data Broker Software



Important

Direct upgrade path to Cisco Nexus Data Broker Release 3.2 is available from Cisco Nexus Data Broker release 3.0 or above. If you are running a previous release, upgrade to Release 3.0 first before upgrading to Release 3.2.

- To complete a new installation of Cisco Nexus Data Broker, see the *Installing the Cisco Nexus Data Broker Software* section.

Installing the Cisco Nexus Data Broker Software

- Step 1** In a web browser, navigate to **www.cisco.com**.
- Step 2** Under **Support**, click **All Downloads**.
- Step 3** In the center pane, click **Cloud and Systems Management**.
- Step 4** If prompted, enter your Cisco.com **username** and **password** to log in.
- Step 5** In the right pane, click **Network Controllers and Applications**, and then click **Cisco Nexus Data Broker**. The file information for Release 3.2.0 is displayed: Cisco Nexus Data Broker Software Application: ndb1000-sw-app-k9-3.2.0.zip

- Step 6** Download the Cisco Nexus Data Broker application bundle.
- Step 7** Create a directory in your Linux machine where you plan to install Cisco Nexus Data Broker. For example, in your Home directory, create `CiscoNDB`.
- Step 8** Copy the Cisco Nexus Data Broker zip file into the directory that you created.
- Step 9** Unzip the Cisco Nexus Data Broker zip file.
The Cisco Nexus Data Broker software is installed in a directory called `xnc`. The directory contains the following:
- `runxnc.sh` file—The file that you use to launch Cisco Nexus Data Broker.
 - `version.properties` file—The Cisco Nexus Data Broker build version.
 - `captures` directory—The directory that contains output dump files from analytics run in Cisco Nexus Data Broker.
- Note** The `captures` directory is created after you execute the Cisco Nexus Data Broker analytics tool.
- `configuration` directory—The directory that contains the Cisco Nexus Data Broker initialization files. This directory also contains the `startup` subdirectory where configurations are saved.
 - `bin` directory—The directory that contains the following script:
 - `xnc` file—This script contains the Cisco Nexus Data Broker common CLI.
 - `etc` directory—The directory that contains profile information.
 - `lib` directory—The directory that contains the Cisco Nexus Data Broker Java libraries.
 - `logs` directory—The directory that contains the Cisco Nexus Data Broker logs.
- Note** The `logs` directory is created after the Cisco Nexus Data Broker application is started.
- `plugins` directory—The directory that contains the OSGi plugins.
 - `work` directory—The webserver working directory.
- Note** The `work` directory is created after the Cisco Nexus Data Broker application is started.
-

Upgrading the Application Software

Use the **upgrade** command to upgrade to Cisco Nexus Data Broker Release 3.2.0. When you are upgrading from Release 2.2.0 and/or Release 2.2.1, you first need to upgrade to Release 3.0.0 or Release 3.1.0 and only then you can upgrade to Cisco Nexus Data Broker Release 3.2.0. This upgrade is an in-place upgrade, which means that the product bits are replaced. A backup archive is created to restore your original installation, if necessary.

**Note**

Once you upgrade to Cisco Nexus Data Broker Release 3.2.0, you cannot use the downgrade option to rollback to 3.1.0 or 3.0.0. You have to use the configuration archive that is created during the upgrade process to rollback the software.

**Note**

When you upgrade the software, the hostname should not be changed during the upgrade process. While upgrading to Cisco Nexus Data Broker Release 3.2.0, user should not allowed to change the hostname. If the hostname is changed during the upgrade, the upgrade process is not done successfully.

When you execute the **upgrade** command, the installation and the configuration are upgraded. However, any changes you made to the shell scripts or configuration files, for example, `runxnc.sh` and `config.ini`, are overwritten. After you complete the upgrade process, you must manually reapply your changes to those files.

Before You Begin

- Stop all controller instances that use the Cisco Nexus Data Broker installation. This will avoid conflicts with the file system, which is updated during the upgrade.
- If you are using high availability clustering, stop all application instances in the cluster to ensure that there are no inconsistencies.
- Back up your `config.ini` and `runxnc.sh` files.

**Important**

You should manually backup your `config.ini` and `runxnc.sh` files before upgrading, because the backup process does not back them up for you. If you do not backup your files before upgrading, any changes you made will be lost.

**Note**

When you run `runxnc.sh` script after upgrading from Cisco Nexus Data Broker, make sure that you upgrade your current Java version and you have set `JAVA_HOME` to point to the correct JAVA version. If the current Java version used is lower than 1.8.0_45, the Java process does not start and it does not get the Web access.

**Note**

When you run `runxnc.sh` script, there is a thread in the script that monitors the log and the Cisco Nexus Data Broker JAVA process to monitor the health of the Cisco Nexus Data Broker. The default value for this option is 30 Seconds.

- Step 1** In a web browser, navigate to [Cisco.com](https://www.cisco.com).
- Step 2** Under **Support**, click **All Downloads**.
- Step 3** In the center pane, click **Cloud and Systems Management**.
- Step 4** In the right pane, click **Network Controllers and Applications**, and then click **Cisco Nexus Data Broker**.
- Step 5** Download the Cisco Nexus Data Broker Release 3.2.0 application bundle: Cisco Nexus Data Broker Software Application—ndb1000-sw-app-k9-3.2.0.zip
- Step 6** Create a temporary directory in your Linux machine where you plan to upgrade to Cisco Nexus Data Broker. For example, in your Home directory, create `CiscoNDB_Upgrade`.
- Step 7** Extract the Cisco Nexus Data Broker Release 3.2.0 zip file into the temporary directory that you created.
- Step 8** Navigate to the `xnc` directory that was created when you installed the Cisco Nexus Data Broker release earlier.
- Step 9** Backup your Cisco Nexus Data Broker release installation using your standard backup procedures.
- Step 10** Stop running all Cisco Nexus Data Broker release processes.
- Step 11** Navigate to the `xnc/bin` directory in the temporary directory that you created for the Cisco Nexus Data Broker Release 3.2.0 upgrade software.
- Step 12** Upgrade the application by entering the `./xnc upgrade --perform --target-home {xnc_directory_to_be_upgraded} [--verbose] [--backupfile {xnc_backup_location_and_zip_filename}]` command.
You can use one of the following options:

Option	Description
<code>--perform --target-home {xnc_directory_to_be_upgraded}</code>	Upgrades the Cisco XNC Monitor Manager installation to Cisco Nexus Data Broker.
<code>--perform --target-home {xnc_directory_to_be_upgraded} --backupfile {xnc_backup_location_and_zip_filename}</code>	Upgrades the Cisco XNC Monitor Manager installation to Cisco Nexus Data Broker and creates a backup .zip file in the directory path that you set. Note You must provide the name of the backup file and the .zip extension.
<code>--rollback --target-home {xnc_directory_to_be_upgraded}</code>	Rolls back to the previous Cisco XNC Monitor Manager installation.
<code>--rollback --target-home {xnc_directory_to_be_upgraded} --backupfile {xnc_backup_location_and_zip_filename}</code>	Rolls back to the previous Cisco XNC Monitor Manager installation using the backup file in the absolute path that you set.
<code>--verbose</code>	Displays detailed information to the console. This option can be used with any other option and is disabled by default.

Option	Description
--validate --target-home <i>{xnc_directory_to_be_upgraded}</i>	Validates the installation.
./xnc help upgrade	Displays the options for the upgrade command.

Step 13 Navigate to the `xnc` directory where you originally installed Cisco XNC Monitor Manager.

Step 14 Start the application processes that you previously stopped.

Note Press Ctrl-F5, or press the Cmd, Shift, and R keys simultaneously when you access Cisco Nexus Data Broker through a web UI following an upgrade.

Step 15 If you have any upgrade-related issues, perform the following tasks:

- Stop all application processes.
- Navigate to the temporary directory that you created in Step 6.
- Enter the **./xnc upgrade --rollback --target-home** *{xnc_directory_to_be_downgraded}* **--backupfile** *{xnc_backup_location_and_zip_filename}* **[--verbose]** command.
- Restart the application processes.

Note Press Ctrl-F5, or press the Cmd, Shift, and R keys simultaneously when you access Cisco XNC Monitor Manager through a web UI following a rollback.

Starting the Application

Step 1 (Optional) Change the default password supplied with Cisco Nexus Data Broker by entering the **reset-admin-password** **[--wait-seconds** *{wait_time}* **--password** *{password}***]** command.

The *{password}* variable resets the administrator password to the value that you specify by restarting the user manager. The *{wait_time}* is the number of seconds to wait while the user manager restarts. The minimum *{wait_time}* value is 5 seconds and the maximum is 60 seconds.

- Note**
- If double ENTER is used instead of entering a value for the password, the password is set to the default vales, for example, **admin/admin**.
 - The password must be from 8 to 256 characters, contain both uppercase and lowercase characters, and have at least one number and one nonalphanumeric character.
 - If you leave the password blank, it is reset to the factory default of "admin".
 - Each time that you reset the administrative password, make sure that the new password meets these requirements or you will not be able to log in to Cisco Nexus Data Broker.

Step 2 Navigate to the `xnc` directory and start Cisco Nexus Data Broker by entering the **./runxnc.sh** command.

Note When you are running `xnc` for the first time, the URL that you need to connect to and the port that it is listening on are displayed on the screen. For example, when you run the `./runxnc.sh` script, the following message is displayed on the screen: Web GUI can be accessed using below URL: *[https://<IP_address>: 8443]*.

You can use one of the following options:

Option	Description
no option	Starts Cisco Nexus Data Broker with the -start option.
-jmx	Enables Java Management Extensions (JMX) remote access on the Cisco Nexus Data Broker JVM, which can be used to troubleshoot performance issues.
-jmxport <i>port_number</i>	Enables JMX remote access on the specified JVM port.
-debug	Enables debugging on the Cisco Nexus Data Broker JVM.
-debugsuspend	Suspends the Cisco Nexus Data Broker startup until a debugger is connected.
-debugport <i>port_number</i>	Enables debugging on the specified JVM port.
-start	Starts Cisco Nexus Data Broker and provides Secure Shell (SSH) access on port 2400. Note The SSH server can be accessed by any Cisco Nexus Data Broker user with the network-administrator role.
-start <i>port_number</i>	Starts Cisco Nexus Data Broker and provides SSH access to the controller on the specified port number. Note The SSH server can be accessed by any Cisco Nexus Data Broker user with the network-administrator role. The valid range of values for <i>port_num</i> is 1024 through 65535.
-stop	Stops Cisco Nexus Data Broker.
-status	Displays the status of Cisco Nexus Data Broker.
-console	Starts Cisco Nexus Data Broker with the OSGi console.
-help	Displays the options for the ./runxnc.sh command.
-tls	Enables TLS secure connections between Cisco Nexus Data Broker and OpenFlow switches. To enable TLS, start the controller by entering the ./runxnc.sh -tls -tlskeystore keystore_file_location -tlstruststore truststore_file_location command.
-osgiPasswordSync	To set the OSGi web console password same as the XNC password if the XNC password is changed. Note This step is optional. If the application is started without this option, the OSGi console can be accessed through the default credentials.

Note Use `runxnc.sh` script to start Cisco Nexus Data Broker. You have to set a path variable named `JAVA_HOME`. It sets the path variables that are used for startup and launches the OSGi framework with the specified options. If a user attempts to start the Cisco Nexus Data Broker application with Java version lower than 1.7, an error message is displayed and the application aborts. To resolve the issue, upgrade your current Java version and restart Cisco Nexus Data Broker. If the current Java Version used is lower than 1.8.0_45, a warning message is issued before the start that Upgrade to 1.8.0_45 or above is recommended.

Verifying That The Application is Running

-
- Step 1** Open a command window where you installed Cisco Nexus Data Broker.
- Step 2** Navigate to the `xnc` directory that was created when you installed the software.
- Step 3** Verify that the application is running by entering the `./runxnc.sh -status` command. The controller outputs the following, which indicates that the controller is running the Java process with PID 21680:

```
Controller with PID:21680 -- Running!
```

Note Nexus Data Broker can be accessed via Web browser
at:
`https://Nexus_data_broker_ip:8443`

What to Do Next

Connect the switches to the controller. For more information, see the configuration guide for your switches.



Managing TLS Certificate, KeyStore, and TrustStore Files

This chapter contains the following sections:

- [About the TLS Certificate, KeyStore, and TrustStore Files, page 17](#)
- [Preparing to Generate the TLS Credentials, page 18](#)
- [Creating a Public Certificate Using SSL Certification, page 22](#)

About the TLS Certificate, KeyStore, and TrustStore Files



Note

When Cisco Nexus Data Broker is started in a normal way, the connection to the device is HTTP. When Cisco Nexus Data Broker is started using the TLS protocol, the connection to the device is in HTTPS.



Note

To configure High Availability clusters in TLS mode, you need to run Cisco Nexus Data Broker in TLS mode for each instance of Cisco Nexus Data Broker.

Enabling the TLS connections between Cisco Nexus Data Broker and the OpenFlow switches requires TLS KeyStore and TrustStore files. The TLS KeyStore and TLS TrustStore files are password protected.

Cisco Nexus Series switches connecting to Cisco Nexus Data Broker over OpenFlow require additional credentials, including Private Key, Certificate, and Certificate Authority (CA).

- The TLS KeyStore file contains the private key and certificate information used by Cisco Nexus Data Broker.
- The TLS TrustStore file contains the Certification Authority (CA) certificates used to sign the certificates on the connecting switches.

If TLS connections are required in your Cisco Nexus Data Broker implementation, all of the connections in the network must be TLS encrypted, and you must run Cisco Nexus Data Broker with TLS enabled. After

Cisco Nexus Data Broker is started with TLS, you must run the TLS KeyStore password configuration command to provide the passwords for Cisco Nexus Data Broker to unlock the KeyStore files.

Preparing to Generate the TLS Credentials

OpenFlow switches require cryptographic configuration to enable TLS.

The NX-API protocol plugin now supports TLS for secure communication to the devices. You can connect to the NX-API protocol plugin on the secure port 443. All configuration, discovery, and statistics collection is done using secure communication. Cisco Nexus Data Broker should be configured with the required certificates and it should be started in the secure mode. When Cisco Nexus Data Broker is started in TLS mode, all devices support the TLS connection. The normal unencrypted connection to the switches is not accepted.



Caution

Self-signed certificates are appropriate only for testing in small deployments. For additional security and more granular controls over individual certificate use and revocation, you should use certificates generated by your organization's Certificate Authority. In addition, you should never use the keys and certificates generated by this procedure in a production environment.

Before You Begin

Ensure that OpenSSL is installed on the Linux host where these steps will be performed.

SUMMARY STEPS

1. Create a TLS directory using **mkdir -p TLS** command and then navigate to it using **cd TLS** command:
2. Set up the directories for your CA system to function within. Create three directories under `mypersonalca` using **mkdir -p mypersonalca/<directory name>** command. To initialize the `serial` file and the `index.txt` file, enter **echo "01" > mypersonalca/serial** command and **touch mypersonalca/index.txt** command respectively.
3. Create the CA configuration file (`ca.cnf`). Before saving the `ca.cnf` file, some changes need to be made that are specific to the devices. One critical change is to change the `[alt_names]` section in the `ca.cnf` file to be relevant to the device IP address, because these IP addresses should be specified in the configuration file. If you need more or fewer IP/DNS names, you can add or remove the lines.
4. Once the directory structure is created and the configuration file (`ca.cnf`) is saved on your disk, create the TLS certificate file.
5. Copy **server.key** and **server.crt** into respective devices and install by using the following commands:
6. Creating the TLS KeyStore File
7. Creating the TLS TrustStore File
8. Starting application with TLS

DETAILED STEPS

- Step 1** Create a TLS directory using **mkdir -p TLS** command and then navigate to it using **cd TLS** command:
- ```
mkdir -p TLS
cd TLS
```

**Step 2** Set up the directories for your CA system to function within. Create three directories under `mypersonalca` using `mkdir -p mypersonalca/<directory name>` command. To initialize the `serial` file and the `index.txt` file, enter `echo "01" > mypersonalca/serial` command and `touch mypersonalca/index.txt` command respectively.

```
mkdir -p mypersonalca/certs
```

```
mkdir -p mypersonalca/private
```

```
mkdir -p mypersonalca/crl
```

```
echo "01" > mypersonalca/serial
```

```
touch mypersonalca/index.txt
```

The `serial` file and the `index.txt` file are used by the CA to maintain its database of the certificate files.

**Step 3** Create the CA configuration file (`ca.cnf`). Before saving the `ca.cnf` file, some changes need to be made that are specific to the devices. One critical change is to change the `[alt_names]` section in the `ca.cnf` file to be relevant to the device IP address, because these IP addresses should be specified in the configuration file. If you need more or fewer IP/DNS names, you can add or remove the lines.

**Note** This step is applicable to NX-API only.

The following is an example of the content of the `ca.cnf` file:

```
[ca]
default_ca = CA_default

[CA_default]
dir = .
serial = $dir/serial
database = $dir/index.txt
new_certs_dir = $dir/newcerts
certs = $dir/certs
certificate = $certs/cacert.pem
private_key = $dir/private/cakey.pem
default_days = 365
default_md = sha1
preserve = no
email_in_dn = no
nameopt = default_ca
certopt = default_ca
policy = policy_match
copy_extensions = copy

[policy_match]
countryName = match
stateOrProvinceName = match
organizationName = match
organizationalUnitName = optional
commonName = supplied
emailAddress = optional

[req]
```

```

default_bits = 2048 # Size of keys
default_keyfile = example.key # name of generated keys
default_md = sha1 # message digest algorithm
string_mask = nombstr # permitted characters
distinguished_name = req_distinguished_name
req_extensions = v3_req
x509_extensions = v3_req

```

```

[req_distinguished_name]
Variable name Prompt string
#-----
0.organizationName = Organization Name (company)
organizationalUnitName = Organizational Unit Name (department, division)
emailAddress = Email Address
emailAddress_max = 40
localityName = Locality Name (city, district)
stateOrProvinceName = State or Province Name (full name)
countryName = Country Name (2 letter code)
countryName_min = 2
countryName_max = 2
commonName = Common Name (hostname, IP, or your name)
commonName_max = 64

```

# Default values for the above, for consistency and less typing.

```

Variable name Value
#-----
commonName_default = www.cisco.com
0.organizationName_default = Cisco
localityName_default = San Jose
stateOrProvinceName_default = CA
countryName_default = US
emailAddress_default = webmaster@cisco.com

```

```

[v3_ca]
basicConstraints = CA:TRUE
subjectKeyIdentifier = hash
authorityKeyIdentifier = keyid:always,issuer:always

```

```

[v3_req]
Extensions to add to a certificate request
basicConstraints = CA:FALSE
keyUsage = nonRepudiation, digitalSignature, keyEncipherment

```

```

Some CAs do not yet support subjectAltName in CSRs.
Instead the additional names are form entries on web
pages where one requests the certificate...
subjectAltName = @alt_names

```

```
[alt_names]
IP.1 = 1.1.1.1
IP.2 = 2.2.2.2
IP.3 = 3.3.3.3
IP.4 = 4.4.4.4

[server]
Make a cert with nsCertType set to "server"
basicConstraints=CA:FALSE
nsCertType = server
nsComment = "OpenSSL Generated Server Certificate"
subjectKeyIdentifier=hash
authorityKeyIdentifier=keyid,issuer:always

[client]
Make a cert with nsCertType set to "client"
basicConstraints=CA:FALSE
nsCertType = client
nsComment = "OpenSSL Generated Client Certificate"
subjectKeyIdentifier=hash
authorityKeyIdentifier=keyid,issuer:always
```

**Step 4** Once the directory structure is created and the configuration file (ca.cnf) is saved on your disk, create the TLS certificate file.

Generate the TLS private key and Certification Authority (CA) files by entering the **openssl req -x509 -nodes -days 3650 -newkey rsa:2048 -out mypersonalca/certs/ca.pem -outform PEM -keyout mypersonalca/private/ca.key** command. This step generates the TLS private key in PEM format with a key length of 2048 bits and the CA file.

Generate the certificates (**server.key** and **server.crt**) file by entering **openssl req -new -x509 -days 365 -nodes -out server.crt -keyout server.key -config Example.conf**

**Step 5** Copy **server.key** and **server.crt** into respective devices and install by using the following commands:

**configure terminal** to enter the configure terminal mode.

**nxapi certificate httpskey keyfile bootflash:///server.key** where bootflash:/// is a file location of **server.key**.

**nxapi certificate https crt certfile bootflash:///server.crt** where bootflash:/// is a file location of **server.crt**.

**nxapi certificate enable**

**Step 6** Creating the TLS KeyStore File

**Note** The TLS KeyStore file should be placed in the configuration directory of Cisco Nexus Data Broker.

Copy **server.key** to **xnc-privatekey.pem**. This command copies the **server.key** file that was generated in step 5. For example, use the command **cp server.key xnc-privatekey.pem**.

Copy **server.crt** to **xnc-cert.pem**. This command makes a copy of the **server.crt** file that was generated in step 5. For example, use the command **cp server.crt xnc-cert.pem**.

Create the **xnc.pem** file, that contains the private key and certificate, by entering the **cat xnc-privatekey.pem xnc-cert.pem > xnc.pem** command.

Convert the PEM file **xnc.pem** file to the file **xnc.p12** file by entering the **openssl pkcs12 -export -out xnc.p12 -in xnc.pem** command. Enter a password at the prompt. This is the Export password. The password must contain at least 6 characters, for example, *cisco123*. You must use the same password for this step and for Step 7. The *xnc.pem* file is converted to a password-protected *.p12* file.

Convert the *xnc.p12* to a Java KeyStore (tlsKeyStore) file by entering the **keytool -importkeystore -srckeystore xnc.p12 -srcstoretype pkcs12 -destkeystore tlsKeyStore -deststoretype jks** command. This command converts the *xnc.p12* file to a password-protected *tlsKeyStore* file. Enter a password at the prompt. Use the same password that you entered in previous step.

### Step 7 Creating the TLS TrustStore File

The TLS TrustStore file should be placed in the application configuration directory.

Copy the **mypersonalca/certs/ca.pem** file to **sw-cacert.pem**.

Convert the **sw-cacert.pem** file to a Java TrustStore (tlsTrustStore) file by entering the **keytool -import -alias swca1 -file sw-cacert.pem -keystore tlsTrustStore** command.

Enter a password at the prompt. The **sw-cacert.pem** file is converted into a password-protected Java TrustStore (tlsTrustStore) file. The password must be at least six characters long, for example, *cisco123*

### Step 8 Starting application with TLS

When Cisco Nexus Data Broker is running in TLS mode and if you restart Cisco Nexus Data Broker with the saved configuration, the **./runxnc.sh -start** command starts the application in TLS mode again. If you do not want to restart Cisco Nexus Data Broker in TLS mode, then delete the **configuration/startup/tlsconf.conf** file and start the application using the **./runxnc.sh -start** command again.

You do not need to provide the TLS KeyStore and TrustStore passwords when Cisco Nexus Data Broker is restarted with the saved configuration.

## Creating a Public Certificate Using SSL Certification

Complete the following steps to create a public certificate using the SSL certification:

### Step 1 Create a certificate service request using the command: **openssl req -newkey rsa:2048 -sha256 -keyout cert.key -keyform PEM -out cert.req -outform PEM**

#### Example:

```
[root@RHEL-VM-NDB-ACI newcert]# openssl req -newkey rsa:2048 -sha256 -keyout cert.key
-keyform PEM -out cert.req -outform PEM
```

```
Generating a 2048 bit RSA private key
.....+++
.....+++
writing new private key to 'cert.key'
Enter PEM pass phrase: => ciscoxnc
Verifying - Enter PEM pass phrase: => ciscoxnc
```



-----

You are about to be asked to enter information that will be incorporated into your certificate request.  
What you are about to enter is what is called a Distinguished Name or a DN.  
There are quite a few fields but you can leave some blank  
For some fields there will be a default value,  
If you enter '.', the field will be left blank.

-----

Country Name (2 letter code) [GB]:US  
State or Province Name (full name) [Berkshire]:CA  
Locality Name (eg, city) [Newbury]:SJ  
Organization Name (eg, company) [My Company Ltd]:cisco  
Organizational Unit Name (eg, section) []:insbu  
Common Name (eg, your name or your server's hostname) []:RHEL-VM-NDB-ACI.cisco.com  
Email Address []:bosellap@cisco.com

Please enter the following 'extra' attributes  
to be sent with your certificate request

A challenge password []:

An optional company name []:

```
[root@RHEL-VM-NDB-ACI newcert]# ls
cert.key cert.req
[root@RHEL-VM-NDB-ACI newcert]#
```

## Step 2

Create the public certificates using Cisco internal certification Website, [sslcerts.cisco.com](https://sslcerts.cisco.com).

a) Enter the command: **cat cert.req**

### Example:

```
[root@RHEL-VM-NDB-ACI newcert]# cat cert.req
```

-----BEGIN CERTIFICATE REQUEST-----

```
MIIC1DCCAbwCAQAwY4xCzAJBgNVBAYTAlVTMQswCQYDVQQIEwJDQTELMakGA1UE
BxMCU0oxODJAMBgNVBAoTBWNpc2NvM0Q4wDAYDVQQLEwVpbNidTEiMCAgA1UEAxMZ
UkhFTClWTS1OREItQUNJLmNpc2NvLmNvbTEhMB8GCSqGSIb3DQEJARYSYm9zZWxs
YXBAY2lzY28uY29tMIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAg2k+
c3p8FBGyxFvLBNjpLBvOk9OABk/gCVQWZIWgM0W5gF29S1jGTAVhK1zGZukSycjT
5mV2Or9VfiffT3/2tps7IBY97NsIyj5Rc+KGBKMSpEXqyCylLdMy+LMAiYPt4Nn8
k7HI8gGlvthH5snusqm/jnp7HBH0tZjd3IUQOE8UGtGRB1SKFCr7UymKpDfCVzsz
dF+gB15TaG9vMKTUBPLjzLuZatZDKIVXWCpkzbwsRd5d4jHvzK5uftHJ/lScqWHs
gN0872McqtNmmQjclSEmpilDvQkBgSdE+8s0jaIVd/WS+w3lu7goSK91vBoLxTdb
ypJAtql06b2qYI4bwIDAQABoAAwDQYJKoZIhvcNAQELBQADggEBAFYOk/pxfoLG
4ba1J0BP6pEa88z2um53xVitVegmBv4Chb/yd87/ucn7CW/x9GPdgHqVn8Y0K71G
xkZI6S34cklaSf4VSA7qtQ/8rStLwA+HZ/qptebwer0k32lWcbqG1DZRhSuVF4/3
sYSUqnDYpE+ZY0iQHhX8Bk1/GIIBEbXl+uYyvC8S6cr7rCd3Nnel574Da2PK+pu3
GJEn811iXr6pylYqRX52jqkNbCSfy+czrC/oiBWjZZ3wTIos6uAgQTiCWqDip/sJ
1kAsNWVA9koZ32HXDPXZ3mQXImla1162FEFpyJfLJ7v5DEwDh7edkSoKphLGDIP7
/ICkW4Si5rA=
```

-----END CERTIFICATE REQUEST-----

```
[root@RHEL-VM-NDB-ACI newcert]#
```

b) Copy the certificate request from **-----BEGIN CERTIFICATE REQUEST-----** to **-----END CERTIFICATE REQUEST-----** from the output.

c) Use the CSR file to request a signed certificate from an external certificate authority.

**Step 3** Copy the certificates to the Cisco Nexus Data Broker server.  
There are 3 certificate files: root, intermediate, and domain.

**Step 4** Import the keys in to the keystore file.

**Step 5** Use the command **openssl pkcs12 -export -in <domain certificate> -inkey <gen key> > inter\_keystore** to import the key. The input files are domain certificate and cert.key and store it in inter\_keystore file:

**Example:**

```
[root@RHEL-VM-NDB-ACI Demo]#openssl pkcs12 -export -in RHEL-VM-NDB-ACI.cisco.com.cer -inkey
../cert.key > inter_keystore

Enter pass phrase for ../cert.key:
Enter Export Password:
Verifying - Enter Export Password:
[root@RHEL-VM-NDB-ACI Demo]#
[root@RHEL-VM-NDB-ACI Demo]#
[root@RHEL-VM-NDB-ACI Demo]# ls
inter_keystore RHEL-VM-NDB-ACI.cisco.com.cer RHEL-VM-NDB-ACI.cisco.com.zip test-root-ca-2048.cer
test-ssl-ca.cer

[root@RHEL-VM-NDB-ACI Demo]#
```

**Step 6** Import all the certificates in to the inter\_keystore file

a) Import the root certificate file.

**Example:**

```
[root@RHEL-VM-NDB-ACI Demo]# keytool -import -trustcacerts -alias root -file test-root-ca-2048.cer
-keystore inter_keystore

Enter keystore password:
Owner: CN=TEST Root CA 2048, O=Cisco Systems
Issuer: CN=TEST Root CA 2048, O=Cisco Systems
Serial number: 228afc0c5220cda94e298af8cdad4243
Valid from: Thu Feb 19 13:01:38 PST 2004 until: Fri Aug 11 13:29:31 PDT 2034
Certificate fingerprints:
 MD5: 90:73:67:6A:03:B4:38:85:CA:48:3E:AB:6C:25:74:77
 SHA1: 91:AD:ED:70:CB:E0:1A:D5:9A:18:DC:EF:82:B2:1C:A9:60:7D:3C:2D
 SHA256:
A0:1E:1E:A7:D1:47:59:63:B1:0F:E9:DF:71:A6:5A:2B:12:DC:C0:BF:F8:07:B4:FA:52:3E:95:3A:0D:8D:29:DC
 Signature algorithm name: SHA1withRSA
 Version: 3

Extensions:

#1: ObjectId: 1.3.6.1.4.1.311.21.1 Criticality=false
0000: 02 01 02 ...

#2: ObjectId: 1.3.6.1.4.1.311.21.2 Criticality=false
0000: 04 14 10 81 B3 88 0A C1 E3 2F 9E 28 DC 61 A0 D8/.(a..
0010: B8 18 45 F2 16 8B ..E...

#3: ObjectId: 2.5.29.19 Criticality=true
BasicConstraints:[
 CA:true
 PathLen:2147483647
]
```

```
#4: ObjectId: 2.5.29.15 Criticality=false
KeyUsage [
 DigitalSignature
 Key_CertSign
 Crl_Sign
]

#5: ObjectId: 2.5.29.14 Criticality=false
SubjectKeyIdentifier [
KeyIdentifier [
0000: CA 1C 01 A4 F7 5F A6 C2 18 1C BD 82 16 09 86 FB _.....
0010: 1B FA BA 7A ...Z
]
]

Trust this certificate? [no]: yes
Certificate was added to keystore

[root@RHEL-VM-NDB-ACI Demo]#
```

b) Import the intermediate certificate file.

**Example:**

```
[root@RHEL-VM-NDB-ACI Demo]# keytool -import -trustcacerts -alias intermediate -file test-ssl-ca.cer
-keystore inter_keystore

Enter keystore password:
Certificate was added to keystore

[root@RHEL-VM-NDB-ACI Demo]#
```

c) Import the domain certificate file.

**Example:**

```
[root@RHEL-VM-NDB-ACI Demo]# keytool -import -trustcacerts -alias cisco -file
RHEL-VM-NDB-ACI.cisco.com.cer -keystore inter_keystore

Enter keystore password:
Certificate already exists in keystore under alias <l>
Do you still want to add it? [no]: yes
Certificate was added to keystore

[root@RHEL-VM-NDB-ACI Demo]#
```

**Step 7** Copy the inter\_keystore file as keystore file under xnc/configuration.

**Example:**

```
[root@RHEL-VM-NDB-ACI configuration]# cp ../../cert/Demo/inter_keystore keystore

[root@RHEL-VM-NDB-ACI configuration]# ls
cert.key context.xml keystore logback.xml org.eclipse.osgi
tomcat-logging.properties web.xml xncjgroups.xml
config.ini generateWebUICertificate.sh keystore_old
org.eclipse.equinox.console.authentication.config startup tomcat-server.xml
xncinfinispan.xml
```

**Step 8** Stop and start the controller.

**Example:**

```
[root@RHEL-VM-NDB-ACI configuration]# cd ..

[root@RHEL-VM-NDB-ACI xnc]#
[root@RHEL-VM-NDB-ACI xnc]#
[root@RHEL-VM-NDB-ACI xnc]#

[root@RHEL-VM-NDB-ACI xnc]# ./runxnc.sh -stop
Controller with PID: 10383 -- Stopped!

[root@RHEL-VM-NDB-ACI xnc]# ./runxnc.sh -status
Doesn't seem any Controller daemon is currently running
[root@RHEL-VM-NDB-ACI xnc]#
[root@RHEL-VM-NDB-ACI xnc]#
[root@RHEL-VM-NDB-ACI xnc]#
[root@RHEL-VM-NDB-ACI xnc]#

[root@RHEL-VM-NDB-ACI xnc]# ./runxnc.sh -start
Running controller in background with PID: 11172, to connect to it please SSH to this host on port
2400
NDB GUI can be accessed using below URL:
[https://10.16.206.160:8443]
[root@RHEL-VM-NDB-ACI xnc]#

[root@RHEL-VM-NDB-ACI xnc]# ./runxnc.sh -status
Controller with PID: 11172 -- Running!

[root@RHEL-VM-NDB-ACI xnc]#
```

**Step 9**

In the user interface, click **Add Exception...** in the message window to connect to the Website. Completing the procedure outlined above creates a public certificate using the SSL certification.

---



## Logging in and Managing Cisco Nexus Data Broker

---

This chapter contains the following sections:

- [Configuring Cisco Nexus Data Broker, page 27](#)
- [Logging in to the Cisco Nexus Data Broker GUI, page 31](#)
- [Changing the Controller Access to HTTP, page 31](#)
- [Cisco Nexus Data Broker GUI Overview, page 32](#)
- [Saving Configuration Changes , page 34](#)

## Configuring Cisco Nexus Data Broker

### Configuring High Availability Clusters

Cisco Nexus Data Broker supports high availability clustering in active/active mode with up to five controllers. To use high availability clustering with Cisco Nexus Data Broker, you must edit the `config.ini` file for each instance of Cisco Nexus Data Broker.

#### Before You Begin

- All IP addresses must be reachable and capable of communicating with each other.
- All switches in the cluster must connect to all of the controllers.
- All controllers must have the same HA clustering configuration information in the `config.ini` files.
- All controllers must have the same information in the `xnc/configuration/startup` directory.

- If using cluster passwords, all controllers must have the same password configured in the `xncjgroups.xml` file. See [Password Protecting the High Availability Clusters](#), on page 28.

- 
- Step 1** Ensure that Cisco Nexus Data Broker is not running on any of the instances in the cluster.
- Step 2** Open a command window on one of the instances in the cluster.
- Step 3** Navigate to the `xnc/configuration` directory that was created when you installed the software.
- Step 4** Use any text editor to open the `config.ini` file.
- Step 5** Locate the following text:
- ```
# HA Clustering configuration (colon-separated IP addresses of all controllers that are part of the
cluster.)
# supernodes=<ip1>:<ip2>:<ip3>:<ipn>
```
- Step 6** Remove the comments on the `# supernodes` line, and replace `<ip1>:<ip2>:<ip3>:<ipn>` with the IP addresses for each instance of Cisco Nexus Data Broker in the cluster. You can enter from two to five IP addresses.
- Example:**
- ```
HA Clustering configuration (colon-separated IP addresses of all controllers that are part of the
cluster.)
supernodes=10.1.1.1:10.2.1.1:10.3.1.1:10.4.1.1:10.5.1.1
```
- Step 7** Save the file and exit the editor.
- Step 8** Repeat Step 3 through Step 7 for each instance of Cisco Nexus Data Broker in the cluster.
- Step 9** Restart Cisco Nexus Data Broker.
- 

## Password Protecting the High Availability Clusters

You can password protect your HA clusters with the `xncjgroups.xml` file. This file must be exactly the same for each instance of Cisco Nexus Data Broker.

- 
- Step 1** Ensure that Cisco Nexus Data Broker is not running on any of the instances in the cluster.
- Step 2** Open a command window on one of the instances in the cluster.
- Step 3** Navigate to the `xnc/configuration` directory.
- Step 4** Use any text editor to open the `xncjgroups.xml` file.
- Step 5** Locate the following text:
- ```
<!-- <AUTH auth_class="org.jgroups.auth.MD5Token" auth_value="ciscoXNC" token_hash="MD5"></AUTH> -->
```
- Step 6** Remove the comments from the AUTH line.
- Example:**
- ```
<AUTH auth_class="org.jgroups.auth.MD5Token" auth_value="ciscoXNC" token_hash="MD5"></AUTH>
```
- Step 7** (Optional) Change the password in the `auth_value` attribute.

By default, the cluster is protected with the password "ciscoXNC". You can change this password to whatever value you want, if you make the same change on all machines in the cluster.

**Step 8** Save the file and exit the editor.

**Step 9** Repeat Step 4 through Step 8 for each instance of Cisco Nexus Data Broker in the cluster.

**Step 10** Restart Cisco Nexus Data Broker.

## Editing the Configuration Files for Cisco Nexus Switches

Cisco Nexus Data Broker has the ability to periodically rediscover Cisco Nexus switch inventory and the topology so that the topology and inventory is in sync. Cisco Nexus data broker periodically rediscovers the switch inventory and the topology interconnection and status. This information is updated in the GUI depending on the status. You can configure the rediscovery interval and the default value is 60 seconds.

### DETAILED STEPS

|        | Command or Action                                                                                          | Purpose                          |                             |                          |                              |
|--------|------------------------------------------------------------------------------------------------------------|----------------------------------|-----------------------------|--------------------------|------------------------------|
| Step 1 | Navigate to the <code>xnc/configuration</code> directory that was created when you installed the software. |                                  |                             |                          |                              |
| Step 2 | Use any text editor to open the <code>config.ini</code> file.                                              |                                  |                             |                          |                              |
| Step 3 | Update the following parameters:                                                                           | Name                             | Predefined Value in Seconds | Minimum Value in Seconds | Recommended Value in Seconds |
|        |                                                                                                            | of.messageResponseTimer          | 60                          | 2                        | 60                           |
|        |                                                                                                            | of.switchLivenessTimeout         | 120.5                       | 60.5                     | 120.5                        |
|        |                                                                                                            | of.flowStatsPollInterval         | 240                         | 10                       | 240                          |
|        |                                                                                                            | of.portStatsPollInterval         | 240                         | 5                        | 240                          |
|        |                                                                                                            | of.descStatsPollInterval         | 240                         | 60                       | 240                          |
|        |                                                                                                            | of.barrierMessagePriorCount      | 50                          | 100                      | 50                           |
|        |                                                                                                            | of.discoveryInterval             | 300                         | 30                       | 300                          |
|        |                                                                                                            | of.discoveryTimeoutMultiple      | 2                           | 2                        | 2                            |
|        |                                                                                                            | NX-API related system parameters |                             |                          |                              |

|               | Command or Action                  | Purpose                                                                                                                                                                                                                                                                           |                             |                          |                              |
|---------------|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|--------------------------|------------------------------|
|               |                                    | Name                                                                                                                                                                                                                                                                              | Predefined Value in Seconds | Minimum Value in Seconds | Recommended Value in Seconds |
|               |                                    | nx.connectionDelayTimer                                                                                                                                                                                                                                                           | 300                         | —                        | 300                          |
|               |                                    | nx.flowStatsPollInterval                                                                                                                                                                                                                                                          | 120                         | —                        | 120                          |
|               |                                    | nx.tableStatsPollInterval                                                                                                                                                                                                                                                         | 120                         | —                        | 120                          |
|               |                                    | nx.portStatsPollInterval                                                                                                                                                                                                                                                          | 120                         | —                        | 120                          |
|               |                                    | nx.descStatsPollInterval                                                                                                                                                                                                                                                          | 120                         | —                        | 120                          |
|               |                                    | nx.lldpPollingTimer                                                                                                                                                                                                                                                               | 10                          | —                        | 10                           |
|               |                                    | nx.portPollingTimer                                                                                                                                                                                                                                                               | 20                          | —                        | 20                           |
|               |                                    | <b>Note</b> Predefined values are the values that Cisco includes in the <code>config.ini</code> file that is shipped with Cisco Nexus Data Broker. A em dash ("—") in this column of the table means that unless you explicitly update the value, the minimum value will be used. |                             |                          |                              |
| <b>Step 4</b> | Save the file and exit the editor. |                                                                                                                                                                                                                                                                                   |                             |                          |                              |
| <b>Step 5</b> | Restart Cisco Nexus Data Broker.   |                                                                                                                                                                                                                                                                                   |                             |                          |                              |

## Configuring User Roles for Edge Ports

To manage which edge ports a Cisco Nexus Data Broker application user can use for creating rules for edge ports, you must modify the App-User role settings in the `config.ini` file to enable role-based access control (RBAC) for application users. After you make your changes and restart Cisco Nexus Data Broker, note these restrictions:

- Cisco Nexus Data Broker App-User role users will be able to create rules only for source ports which are part of the resource group or groups assigned to that role .
- Only Cisco Nexus Data Broker App-Admin role users will be able create rules with no source.



To enable RBAC for the App-User role, follow these steps:

- 
- Step 1** Open the `config.ini` file for editing.
- Step 2** Locate the line `# Enforce restriction on edge/tap ports user can capture` (default `false`).
- Step 3** Remove the comment character from the following line:  
`monitor.strictAuthorization=true`
- Step 4** Save your work and close the file.
- Step 5** If Cisco Nexus Data Broker is running, restart the application to enable the change.
- 

## Logging in to the Cisco Nexus Data Broker GUI

You can log into the Cisco Nexus Data Broker using HTTPS. The default HTTPS web link for the Cisco Nexus Data Broker GUI is `https://Nexus_Data_Broker_IP:8443/monitor`.



**Note**

You must manually specify the `https://` protocol in your web browser. The controller must also be configured for HTTPS.

---

- 
- Step 1** In your web browser, enter the Cisco Nexus Data Broker web link.
- Step 2** On the launch page, do the following:
- a) Enter your username and password.  
The default username and password is `admin/admin`.
  - b) Click **Log In**.
- 

## Changing the Controller Access to HTTP

Starting with Cisco Nexus Data Broker Release 2.1, an unencrypted (HTTP) access to the GUI and the API to the controller access is disabled by default. You cannot access the controller with the URL `http://<host>:8080`.

If you want to change the controller access to HTTP, complete the following steps:

## DETAILED STEPS

|               | Command or Action                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Purpose |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| <b>Step 1</b> | <p>Remove the comment character from the connector for port 8080 in the tomcat-server.xml file in the configuration directory as displayed in the following example:</p> <p><b>Example:</b></p> <pre>&lt;Service name="Catalina"&gt;   &lt;!--     &lt;Connector port="8080" protocol="HTTP/1.1"       connectionTimeout="20000"       redirectPort="8443" server="Cisco XNC" enableLookups="false" /&gt;   --&gt;   &lt;Connector port="8443" protocol="HTTP/1.1" SSLEnabled="true"     scheme="https" secure="true"     clientAuth="false" sslProtocol="TLS"     keystoreFile="configuration/keystore"     keystorePass="ciscoxnc" server="Cisco XNC"     connectionTimeout="60000" enableLookups="false" /&gt;</pre> <p><b>Example:</b></p> <p>Remove the comment character as displayed in the following example:</p> <pre>&lt;Service name="Catalina"&gt;   &lt;Connector port="8080" protocol="HTTP/1.1"     connectionTimeout="20000"     redirectPort="8443" server="Cisco XNC" enableLookups="false" /&gt;    &lt;Connector port="8443" protocol="HTTP/1.1" SSLEnabled="true"     scheme="https" secure="true"     clientAuth="false" sslProtocol="TLS"     keystoreFile="configuration/keystore"     keystorePass="ciscoxnc" server="Cisco XNC"     connectionTimeout="60000" enableLookups="false" /&gt;</pre> |         |
| <b>Step 2</b> | Restart the controller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |         |

## Cisco Nexus Data Broker GUI Overview

The Cisco Nexus Data Broker Release GUI contains the following tabs:

- Cisco Nexus Data Broker, Release Version
- **Configuration** tab at the top of the screen
- **Administration** tab at the top of the screen
- **Default** tab displaying the switches in use
- **Save** button—Enables you to save any additions or changes you make in Cisco Nexus Data Broker.


**Note**

You should always click **Save** after making any configuration changes.

- The **Online help** button—Provides access to the online help for the current page.

- Bookmarks
- Administrator Details

The **Configuration** tab contains the following items:

- Topology
- Port Definitions
- Port Groups
- Monitoring Devices
- Service Nodes
- Filters
- Connections
- Redirections
- Statistics
- SPAN Sessions

The **Administration** tab contains the following items:

- Device Management
- Devices
- Flows
- Troubleshoot
- Consistency Check
- System Management
- User Management
- System

### Topology Tools

The left side of the topology pane contains a zoom slider that allows you increase or decrease the size of the topology diagram. You can also increase or decrease the size of the topology diagram by scrolling up or down, respectively, with your mouse wheel.

You can move the entire topology diagram, a single topology element, or a node group. To move the diagram, an element, or a node group, click it and drag it.

To view information about a node or an edge port, hover over the node or edge port icon with your mouse. The information displayed depends on the device you choose.

To view information about a path, hover over the path in the topology diagram.

To view information about a filter, hover over the **Name** of the filter in the **Filters** tab.

## Saving Configuration Changes

In Cisco Nexus Data Broker, Release 3.2.0 the auto-save configuration option is added. You can save the configuration changes, but it is not required. For example, if you configure Edge-SPAN, monitor the device, or configure any other functionality in Cisco Nexus Data Broker, it is saved automatically.

---

On the menu bar, click **Save**.

---



## Viewing and Adding Devices

This chapter contains the following sections:

- [Viewing and Adding Devices](#) , page 35

## Viewing and Adding Devices

On the **Devices** screen, the following tabs are displayed:

- Nodes Learned
- Device Connections
- Device Groups
- SPAN Management
- Subnet Gateway Configuration

On the **Nodes Learned** tab, the following details are displayed for each node:

- The name of the node
- The ID of the node
- The hardware on the node
- The number of ports on the node

When you click the node name under the tab **Node Name**, the **Update Node Information** window is displayed. Update the following fields in the window:

- **Node ID:** Enter the node ID.
- **Node Name:** The name of the node.
- **Tier:** Select the tier of the node from the following options in the drop-down list: Unknown, Access, Distribution, and Core.
- **Operation Mode:** Choose how the traffic is handled based on the flows. This can be one of the following:

Allow reactive forwarding—No default flows are programmed. How traffic that does not match a flow is treated depends upon the switch implementation.

Proactive forwarding only—The following default flows are programmed on the switch:

- Punt Address Resolution Protocol (ARP) packets.
- Punt Link Layer Discovery Protocol (LLDP) packets.
- Drop all other traffic.

On the **Device Connections** tab, click **Add Device** to add a device, click **Remove Devices** to remove a device, or click **Rediscover Devices** to rediscover a device. When you click **Rediscover Devices** tab, the **Rediscover Device** window is displayed. Click **Rediscover Device** so that the device gets deleted and rediscovered again.

In each device window, click **View**, **Edit**, or **Delete** to add a device, edit an existing device, or delete a device. The following details are displayed for each device in each device window:

- The name of the device and its IP address
- The username on the device
- The type of the mode, for example, NX-API
- The uptime on the device, for example, date and time
- The hardware on the node

On the **Device Groups** tab, click + **Group** to add a group of devices. In each group window, click **View**, **Edit**, or **Delete** to add a group of devices, edit an existing group of devices, or delete a group of devices respectively. The following details are displayed in each group window:

- The name of the node group, for example, Node Group Name One
- The names of the nodes in the group, for example, nx-tap-agg-sw1 and nx-tap-agg-sw2

On the **SPAN Management** tab, click + **Add Device** to add an APIC device or the production switch to the network. Click **Remove Devices** to delete the devices or click **Rediscover Devices** to rediscover the devices. The production switch should be a Cisco Nexus 9000 Series switch or Cisco Nexus 3000 Series switch in NXOS mode. The feature NXAPI has to be enabled on these production switches.

The following columns are displayed on the **SPAN Management** tab to display the information about the devices:

- IP Address
- Username
- Type: The APIC device is listed as AC and the production switch will belated here is listed as PS.
- Active IP
- Secondary IP Address
- Tertiary IP Address
- Action

You must add an APIC controller before you can set up SPAN session and SPAN destination.



## Configuring Cisco Nexus 9000 Series Switches

This chapter contains the following sections:

- [Guidelines and Limitations, page 37](#)
- [Configuring TCAM Hardware Sizing on Cisco Nexus 9000 Series Switches, page 38](#)
- [Enabling Cisco NX-API on Cisco Nexus 9000 Series Switches Using CLI, page 39](#)
- [Enabling Switch Port Mode as Trunk on the Inter-switch Ports and Port Channels, page 39](#)

### Guidelines and Limitations

See the following guidelines and limitations for configuring Cisco Nexus 9000 Series switches through Cisco Nexus Data Broker.

- Cisco Nexus Data Broker supports NX-API protocol for Cisco Nexus 9000 series family of devices starting with Release 7.x.
- The NX-API device Edit option is not supported in the current release.
- The devices that are going to be provisioned by Cisco Nexus Data Broker are assumed to have LLDP enabled and the LLDP feature should not be disabled during the device association with Cisco Nexus Data Broker. If the LLDP feature is disabled, there might be an inconsistency in Cisco Nexus Data Broker that cannot be fixed without device deletion and re-addition.
- Cisco Nexus Data Broker assumes that the device interfaces configured by the port definitions are L2 switch ports and these interfaces have device configurations as switchport trunk by default.
- Cisco Nexus 9000 series devices do not support VLAN ID for the Edge Port, SPAN and Edge port, and the TAP interfaces.
- If the devices that are added in the Cisco Nexus Data Broker are to be removed, the devices associated with the port definitions and the connections should be removed first.
- For Cisco Nexus 9000 Series switches, upgrade the Cisco NX-OS software to Cisco NX-OS Release 7.x or above.
- You can now add a Cisco Nexus 9000 Series switch to the Cisco Nexus Data Broker that can be discovered through NX-API protocol. Once the connection is successful, all the line card information for chassis model 9500 is discovered.

- Cisco Nexus Data Broker uses the TAP aggregation feature and the NX-API support for JSON-RPC.
- Prior to deploying the Cisco Nexus 9000 Series switches for Tap/SPAN aggregation through Cisco Nexus Data Broker with NX-API mode, the following configurations should be completed:
  - Configure the ACL TCAM region size for IPV4 port ACLs or MAC port ACLs using the **hardware access-list tcam region {ifacl | mac-ifacl} 1024 double-wide** command on the switch.
  - Enable NX-API with **feature manager** CLI command on the switch.
  - Configure **switchport mode trunk** on all the inter-switch ports and the port-channels.
- Prior to deploying the Cisco Nexus 9000 Series switches for Tap/SPAN aggregation through Cisco Nexus Data Broker with OpenFlow mode, enter the command **hardware access-list tcam region openflow 512** at the prompt.
- Cisco Nexus data broker periodically rediscovers the switch inventory, the topology interconnection, and the status. This information is updated in the GUI depending on the status. The rediscovery interval can be configured and the default value for the rediscovery interval is every 10 seconds.

# Configuring TCAM Hardware Sizing on Cisco Nexus 9000 Series Switches

## SUMMARY STEPS

1. Use the **hardware access-list tcam region <region> <tcam-size>** command to configure the following TCAM regions:

## DETAILED STEPS

|               | Command or Action                                                                                                                 | Purpose                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Step 1</b> | Use the <b>hardware access-list tcam region &lt;region&gt; &lt;tcam-size&gt;</b> command to configure the following TCAM regions: | <ul style="list-style-type: none"> <li>• IPV4 PACL [ifacl] size = 1024</li> <li>• IPV6 PACL [ipv6-ifacl] size = 0</li> <li>• MAC PACL [mac-ifacl] size = 512</li> <li>• Egress IPV4 RACL [e-racl] size = 256</li> <li>• Egress IPV6 RACL [e-ipv6-racl] size = 0</li> <li>• Ingress System size = 256</li> <li>• Egress System size = 256</li> <li>• SPAN [span] size = 256</li> <li>• Ingress COPP [copp] size = 256</li> </ul> <p>See the <i>Cisco Nexus 9000 Series NX-OS Security Configuration Guide</i> for the step-by-step TCAM hardware sizing configuration on Cisco Nexus 9000 Series Switches.</p> |



|  | Command or Action | Purpose |
|--|-------------------|---------|
|--|-------------------|---------|

## Enabling Cisco NX-API on Cisco Nexus 9000 Series Switches Using CLI

You can now manage multiple Cisco Nexus 9000 Series switches that are connected in a topology. Cisco Nexus Data Broker plugin can discover the switch interconnections using LLDP and update the topology services within Cisco Nexus Data Broker. The switch interconnections can be a physical link or a port-channel interface. The topology displays only the interconnections between Cisco Nexus 9000 Series switches that are added to the Cisco Nexus Data Broker device list. The topology interconnection is displayed in the GUI.

Complete the following steps for enabling Cisco NX-API on Cisco Nexus 9000 Series switches:

### DETAILED STEPS

|               | Command or Action                             | Purpose                                                                                                                                                                                                                   |
|---------------|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Step 1</b> | Enable the management interface.              | Enable the management interface on the switch.                                                                                                                                                                            |
| <b>Step 2</b> | switch# <b>conf t</b>                         | Enter the configuration mode.                                                                                                                                                                                             |
| <b>Step 3</b> | switch (config) # <b>feature nxapi</b>        | Enable the NX-API feature.                                                                                                                                                                                                |
| <b>Step 4</b> | switch (config) # <b>nxapi http port 80</b>   | Configure the HTTP port.                                                                                                                                                                                                  |
| <b>Step 5</b> | switch (config) # <b>nxapi https port 443</b> | Configure the HTTPS port.<br><br>For the step-by-step configuration information for enabling the NX-API feature on Cisco Nexus 9000 Series switches, see the <i>Cisco Nexus 9000 Series NX-OS Programmability Guide</i> . |

## Enabling Switch Port Mode as Trunk on the Inter-switch Ports and Port Channels

Complete the following steps to enable the switch port mode on the inter-switch ports and port-channels:

### DETAILED STEPS

|               | Command or Action               | Purpose                         |
|---------------|---------------------------------|---------------------------------|
| <b>Step 1</b> | switch(config)# <b>config t</b> | Enables the configuration mode. |

|               | Command or Action                                                    | Purpose                                                                                            |
|---------------|----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| <b>Step 2</b> | switch(config)# interface {{type slot/port}   {port-channel number}} | Specifies an interface to configure.                                                               |
| <b>Step 3</b> | switch(config-if)# <b>switchport mode</b> {access   trunk}           | Configures the switchport mode as access or trunk on the inter-switch ports and the port-channels. |
| <b>Step 4</b> | switch(config)# <b>exit</b>                                          | Exits the configuration mode.                                                                      |



## Configuring the Nexus Data Broker

---

This chapter contains the following sections:

- [Viewing Topology, page 41](#)
- [Configuring Port Definition, page 41](#)
- [Configuring Port Groups, page 45](#)
- [Configuring a Monitoring Device, page 46](#)
- [Adding a Service Node, page 47](#)
- [Configuring Symmetric Load Balancing and MPLS Tag Stripping , page 48](#)
- [Adding Filters, page 48](#)
- [Adding Connections, page 54](#)
- [Adding Redirections, page 57](#)
- [Viewing Statistics, page 61](#)
- [Adding SPAN Sessions, page 63](#)

### Viewing Topology

Click the **Topology** tab in the left frame to view the topology in the network.

### Configuring Port Definition

When you click **Port Definition** tab in the GUI, the **Port Definition** screen is displayed. Select the switch from the drop-down list to configure the ports.

On the **Port Definition** screen, the following two tabs are displayed:

- Port Configuration
- SPAN Destination

Click the **Port Configuration** tab, the following tabs are displayed:

- Configure Multiple Ports
- Remove port Configuration
- Add Service Node
- Add Monitoring Device

When you click **Configure Multiple Ports** tab, the **Configure Multiple Ports** window is displayed. The following details are displayed on the screen: Number, Status, Port Name, Type, In Use, Port ID, and Action.



**Note**

Beginning with Cisco Nexus Data Broker, Release 3.1, the interface description is updated from the Cisco Nexus Data Broker GUI to the switch and the interface description is also available from the switch into the Cisco Nexus Data Broker GUI. When using in Openflow mode, the NX-API auxiliary connection is required for this functionality to work.



**Note**

On the Port Configuration tab, the port name and the interface are displayed as hyperlinks. When you click the port name, you can view the running configuration for that interface on the tab.

If you want to remove any ports, select the port and click **Remove port Configuration** tab.

Click **Add Service Node** to add a service node.

Click **Add Monitoring Device** to add a monitoring device.

On the **Port Configuration** screen, the following port details are displayed for the selected node:

- Serial Number
- Status
- Port name
- Type
- In Use
- Port ID
- Action—When you click **Configure**, the **Configure Ports** window is displayed.

On the **SPAN Destination** tab, the following details are displayed:

- SPAN Destination Name
- SPAN Destinations
- Node Connector
- Monitor Port Type
- Description

## Configuring Ports

- Step 1** Select the switch for which you want to configure the port details on the **Port Configuration** screen.
- Step 2** Click **Configure** under **Action**.  
The **Configure Ports** window is displayed.
- Step 3** In the **Configure Ports** window, configure the port type from the **Select a port type** drop-down list by selecting one of the following options:

- **Add Monitoring Device**
- **Edge Port-SPAN**
- **Edge Port-TAP**
- **Production Port**

**Monitoring Device**—Creates a monitoring device for capturing traffic and configures the corresponding delivery port.

**Edge Port-SPAN**—Creates an edge port for incoming traffic connected to an upstream switch that is configured as a SPAN destination.

**Edge Port-TAP**—Creates an edge port for incoming traffic connected to a physical TAP port.

**Production Port**—Creates a production port for the ingress and egress traffic.

**Note** To receive the traffic from the production network, the production ingress port is configured. After entering the service nodes (multiple security tools), the traffic exits the data center through the production egress port.

**Note** Starting with Cisco Nexus Data Broker, Release 3.2, when Edge-SPAN, Edge-TAP, monitoring device, or production port is defined in NX-API mode of configuration, the CLI command, **spanning-tree bpdudfilter enable** is automatically configured in the interface mode on the ports to filter the BPDU packets. This configuration is applicable for all Cisco Nexus 3000 and 9000 Series switches. The sample configuration is displayed in the example:

```
switch#
show run interface eth1/1
interface ethernet1/1
switchport mode trunk
mode tap-aggregation
spanning-tree bpdudfilter enable
```

**Note** Production port has been enabled for Q-in-Q in Cisco Nexus Data Broker and a unique VLAN should be assigned for each production port. This VLAN should not overlap with any production VLAN numbers.

**Note** The **spanning-tree bpdudfilter enable** CLI command should be configured by the user on all the inter-switch ports for all Cisco Nexus series switches and Cisco Nexus Data Broker does not configure this command.

**Note** Once an interface is configured with Q-in-Q, do not configure multiple VLAN filters for the Q-in-Q configured interface.

When you select the port type, the title of the window changes to **Manage Configure Ports**.

- Step 4** (Optional) In the **Port Description** field, enter the port description.

Beginning with Cisco Nexus Data Broker, Release 3.1, the interface description is updated from the Cisco Nexus Data Broker GUI to the switch and the interface description is also available from the switch into the Cisco Nexus Data Broker GUI. When using in Openflow mode, the NX-API auxiliary connection is required for this functionality to work.

- Step 5** Enter VLAN ID for the port.  
The port is configured as dot1q to preserve any production VLAN information. The VLAN ID is used to identify the port that the traffic is coming from.
- Step 6** (Optional) If APIC is available, you can select the ACI side port and designate it as the SPAN destination port.
- Step 7** In the **Enable Packet Truncation** field, enter the packet length.
- Step 8** A check box is added for **Block Tx** and it is applicable only for Edge-SPAN where you can block the traffic that is being transmitted out of Edge-SPAN interface.
- Step 9** Click **Submit** to save the settings or click **Clear** to clear the details.  
Once you configure a port, you can click **Edit** under **Action** on the **Port Configuration** screen to edit the port details. You can click **Remove** under **Action** on the **Port Configuration** screen to clear the port details.

## Adding SPAN Destination

When you configure a port as an edge SPAN port and the port is connected to the API side, you can select the pod, node, and port from the ACI side and set the port as SPAN destination.



### Note

You can add SPAN destination only after APIC has been successfully added to the network.

- Step 1** Select the switch for which you want to configure the port details on the **Port Configuration** screen.
- Step 2** Click **Configure** under **Action**.  
The **Configure Ports** window is displayed.
- Step 3** In the **Configure Ports** window, configure the port type from the **Select a port type** drop-down list by selecting one of the following options:
- **Add Monitoring Device**
  - **Edge Port-SPAN**
  - **Edge Port-TAP**
  - **Production Port**

**Monitoring Device**—Creates a monitoring device for capturing traffic and configures the corresponding delivery port.

**Edge Port-SPAN**—Creates an edge port for incoming traffic connected to an upstream switch that is configured as a SPAN destination.

**Edge Port-TAP**—Creates an edge port for incoming traffic connected to a physical TAP port.

**Production Port**—Creates a production port for the ingress and egress traffic.

When you select the port type, the title of the window changes to **Manage Configure Ports**.

- Step 4** In the SPAN DESTINATION pane, select the pod from the **Pod** drop-down list.
  - Step 5** Select the ACI leaf from the **Leaf** drop-down list.
  - Step 6** Select the port from the ACI side from the **Port** drop-down list and set the interface as SPAN destination.
  - Step 7** Click **Submit** to save the settings.  
The port is now configured as SPAN destination part and it is displayed on the Port Definition screen.
- 

## Configuring Multiple Ports

You can configure multiple ports for a node.

- 
- Step 1** Click **Configure Multiple Ports** on the **Port Configuration** screen. The **Configure Multiple Ports** window is displayed.
  - Step 2** Use **CTRL/SHIFT** to select multiple ports in the **Select Ports** field.
  - Step 3** Select port type from the drop-down list in the **Select Port Type** field.
  - Step 4** Click **Submit** to save the settings.
- 

## Configuring Port Groups

You can create a port group and add the ports to the connection.



### Note

Starting with Cisco Nexus Data Broker, Release 3.2, you can create port groups for different source ports. The port groups can be a combination of the edge-span and the edge-tap ports across different switches. You can select ports, define port groups, provide a name to the port group, select the port group in a connection screen (only one port group per connection), and use the ports defined in the port group as source ports for creating a connection. Selecting individual ports is disabled when using a port group.

You cannot edit the port group even if it is part of a connection. The connection is automatically updated with the new port group. Deleting a port group is not allowed when the port group is in use.

---

Complete the following steps to configure port groups:

## Before You Begin

- 
- Step 1** Select the switch for which you want to configure the port details on the Port Configuration screen.
- Step 2** Click **Port Groups** tab in the left frame.
- Step 3** Click + **Add Group** to create a port group.
- Step 4** In the **Create Port Group** window, enter the group name in the **Group Name** field.
- Step 5** In the **Select Node** field, select a node, for example, N9K-116.
- Step 6** In the **Select Port** field, select a port, for example, Ethernet1/1 (Ethernet1/1).  
You can add only edge-span and edge-tap ports and you cannot add production ports to the port groups.
- Step 7** Click + **Add To Group** to add the port to the group.  
You can add multiple ports to the group.
- Step 8** Click **Apply**.  
The port group is displayed on the **Port Groups** screen with the following information for the group, for example, **Name**, **Connection Name**, **Ports** and **Action**.
- 

## Configuring a Monitoring Device

- 
- Step 1** Navigate to the **Monitoring Device** tab under **Configuration**.
- Step 2** Click + **Monitoring Device**.
- Step 3** In the **Monitoring Device** window, complete the following fields:

| Name                          | Description                                                                                                                                                                                                                              |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Monitoring Device Name</b> | Add the service node name.<br><b>Note</b> The valid characters for the monitoring devices are the alphanumeric characters and the special characters: colon (":"), underscore ("_"), hyphen ("-"), vertical bar (" "), and period ("."). |
| <b>Select Switch Node</b>     | Select the switch node.                                                                                                                                                                                                                  |
| <b>Select Port</b>            | Select the port.                                                                                                                                                                                                                         |
| <b>Icons</b>                  | Select a Monitoring Device Icon.                                                                                                                                                                                                         |
| <b>Block Rx</b>               | Block any traffic from being received from the monitoring tools. This option is selected by default. You can turn this option off by unchecking the box.                                                                                 |



| Name                            | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Enable Timestamp Tagging</b> | <p>You can configure timestamp tagging only on the Cisco Nexus 3500 Series switches that are running Release 6.0(2)A8(1) or later and the mode is NX-API auxiliary.</p> <p>When you enable timestamp tagging, the TS-tag field is displayed next to the switch on the tab. With this option enabled, the <b>ttag</b> and <b>ttag-marker enable</b> CLIs are available for use.</p> <p>The <b>ttag-marker-interval</b> is a global option that is available on the Cisco Nexus 3500 Series switches. The default interval for this option is 3 Seconds.</p> |

**Step 4** Click **Save**.

## Adding a Service Node

**Step 1** Navigate to the **Service Nodes** tab under **Configuration** and click + **Service Node**.

**Step 2** In the **Add Service Node** window, enter the name of the service node.

**Step 3** Select the ingress port for the service node from the **Service Node Ingress Port** drop-down list.

**Step 4** Select the egress port for the service node from the **Service Node Egress Port** drop-down list.

**Step 5** Enable health check on a service node by selecting the **Service Node Health Check** option. Beginning with Cisco Nexus Data Broker, Release 3.2, you can configure the wait interval in the **config.ini** file before the health check is up. The **ServiceNodeHealthCheckWaitInterval** is the variable in the **config.ini** file to set the wait interval. If you do not specify a value or if the value is 0 for the wait interval in the **config.ini** file, the default value of 5 Seconds is used. The wait interval is not applicable if the port is in shutdown state.

This option works only in the OpenFlow mode. The controller or the NDB injects a packet in the service node ingress port and the packet is received at the egress port. The packets are checked at the interval of every 5 seconds. If five packets are not received in 5 seconds, the health of the service node is considered as down.

For the service node, a new field is displayed in the details: Service Node Status. This field displays the status of the service node.

**Step 6** Select a service node icon from the available options.

**Step 7** Click **Save**.

# Configuring Symmetric Load Balancing and MPLS Tag Stripping

From the Cisco Nexus Data Broker GUI and the REST API interfaces, you can now configure symmetric load balancing and enable MPLS tag stripping on the Cisco Nexus 3000 Series and Cisco Nexus 9000 Series switches using NX-API as the configuration mode.

## Before You Begin

Add device to Cisco Nexus Data Broker using NX-API.

- 
- Step 1** In the topology diagram, click the node for which you wish to configure MPLS tag stripping.
- Step 2** In the **Port Configuration** window, click **Configure Node**. The **Node Configuration** window is displayed.
- Step 3** In the **Symmetric Load Balancing on Port Channel** drop-down list, select the **Hashing Option**.
- Step 4** In the **MPLS Strip Configuration** drop-down list, choose one of the following:
- Enable MPLS Strip.
  - Disable MPLS Strip.
- Step 5** When you select **Enable MPLS Strip** option, the **Label Age** field is displayed. In the field, enter a value for the MPLS strip label age. The range for MPLS strip label age configuration is 61-31622400.
- Step 6** Click **Submit**.
- 

# Adding Filters

## Before You Begin

The hardware command that is a pre-requisite for the IPv6 feature is **hardware access-list tcam region ipv6-ifacl 512 double-wide**.

- 
- Step 1** On the **Filters** tab, click + **Filter** to add a filter. The **Add Filter** window is displayed.
- Step 2** In the **Filter Description** section of the **Add Filter** window, complete the following fields:

| Name       | Description                                                    |
|------------|----------------------------------------------------------------|
| Name field | The name of the filter.                                        |
|            | <b>Note</b> The name cannot be changed once you have saved it. |

| Name                           | Description                                                                                                                                                                                                                                                                                                      |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Bidirectional check box</b> | Check this box if you want the filter to capture traffic information from a source IP, source port, or source MAC address to a destination IP, destination port, or destination MAC address, and from a destination IP, destination port, or destination MAC to a source IP, source port, or source MAC address. |

**Step 3**

In the **Layer 2** section of the **Add Filter** window, complete the following fields:

|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ethernet Type</b> field              | <p>Required. The Ethernet type of the Layer 2 traffic. The default value displayed is IPv4, or you can choose one of the following:</p> <ul style="list-style-type: none"> <li>• IPv6</li> <li>• ARP</li> <li>• LLDP</li> <li>• Predefined EtherTypes</li> <li>• All EtherTypes</li> <li>• Enter Ethernet Type—If you choose Enter Ethernet Type as the type, enter the Ethernet type in hexadecimal format. If you choose Predefined EtherTypes, all predefined Ethernet types contained in the config.in file are associated with the rule, and you should not configure any other parameters.</li> </ul> <p><b>Note</b> You can now configure more than 1 user-defined Ethernet type per filter. You can apply an arbitrary number of Ethernet types that are separated by "," so that a single filter can be setup for the different traffic types.</p> |
| <b>VLAN Identification Number</b> field | <p>The VLAN ID for the Layer 2 traffic. You can enter a single VLAN ID, a range of VLAN ID values, or comma-separated VLAN ID values and VLAN ID ranges, for example, 1-4,6,8,9-12.</p> <p><b>Note</b> For NX-API, a VLAN ID with Layer 3 address is not supported. If a VLAN ID with Layer 3 address is configured, it results in the inconsistent flows. You have to troubleshoot and fix the flows.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>VLAN Priority</b> field              | The VLAN priority for the Layer 2 traffic.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Source MAC Address</b> field         | The source MAC address of the Layer 2 traffic.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

|                                      |                                                     |
|--------------------------------------|-----------------------------------------------------|
| <b>Destination MAC Address</b> field | The destination MAC address of the Layer 2 traffic. |
|--------------------------------------|-----------------------------------------------------|

**Step 4** In the **Layer 3** section of the **Add Filter** window, update the following fields:

| Name                           | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Source IP Address</b> field | <p>The source IP address of the Layer 3 traffic. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• The host IP address, for example, 10.10.10.10</li> <li>• Discontiguous source IP address, for example, 10.10.10.10, 10.10.10.11, 10.10.10.12</li> <li>• An IPv4 address range, for example, 10.10.10.10-10.10.10.15</li> <li>• An IPv4 subnet, for example, 10.1.1.0/24</li> <li>• The host IP address in IPv6 format, for example, 2001::0</li> </ul> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>• When a switch is used in NX-API mode, you can now select an IPv6 filter and setup a connection. You can enter a single IPv6 address, comma separated multiple IPv6 addresses, an IPv6 address range, and/or IPv6 subnet in the <b>Source IP Address</b> field.</li> <li>• If you configure a range of Layer 3 source IP addresses, you cannot configure ranges of Layer 4 source or destination ports.</li> <li>• If you configure a range of Layer 3 source IP addresses, you cannot configure ranges of Layer 2 VLAN identifiers.</li> </ul> <p><b>Note</b> When using IPv6 address in the filter, the <b>Ethernet Type</b> should be set to IPv6.</p> |

| Name                                | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Destination IP Address</b> field | <p>The destination IP address of the Layer 3 traffic. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• The host IP address, for example, 10.10.10.11</li> <li>• An IPv4 address range, for example, 10.10.10.11-10.10.10.18</li> <li>• An IPv4 subnet, for example, 10.1.1.0/24</li> <li>• The host IP address in IPv6 format, for example, 2001::4</li> <li>• The subnet, for example, 10.0.0.0/25</li> </ul> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>• When a switch is used in NX-API mode, you can now select a IPv6 filter and setup a connection. You can enter a single IPv6 address only in the <b>Destination IP Address</b> field. The comma separated multiple IPv6 addresses, an IPv6 address range, and/or IPv6 subnets are not supported. The hardware command that is a pre-requisite is for using the IPv6 feature is <b>hardware access-list tcam region ipv6-ifacl 512</b>.</li> <li>• If you configure a range of Layer 3 source IP addresses, you cannot configure ranges of Layer 4 source or destination ports.</li> <li>• If you configure a range of Layer 3 source IP addresses, you cannot configure ranges of Layer 2 VLAN identifiers.</li> </ul> |
| <b>Protocol</b> drop-down list      | <p>Choose the Internet protocol of the Layer 3 traffic. This can be one of the following: If you choose Enter Protocol as the type, enter the protocol number in decimal format.</p> <ul style="list-style-type: none"> <li>• ICMP</li> <li>• TCP</li> <li>• UDP</li> <li>• Enter Protocol</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>ToS Bits</b> field               | <p>The Type of Service (ToS) bits in the IP header of the Layer 3 traffic. Only the Differentiated Services Code Point (DSCP) values are used.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

**Step 5** In the **Layer 4** section of the **Add Filter** dialog box, complete the following fields:

| Name                       | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Source Port drop-down list | <p>Choose the source port of the Layer 4 traffic. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• FTP (Data)</li> <li>• FTP (Control)</li> <li>• SSH</li> <li>• TELNET</li> <li>• HTTP</li> <li>• HTTPS</li> <li>• Enter Source Port</li> </ul> <p><b>Note</b> Beginning with Cisco Nexus Data Broker Release 3.2 , you can enter comma separated single port numbers and a range of the source port numbers in the <b>Enter Source Port</b> field.</p> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>• If you configure a range of Layer 4 source ports, you cannot configure ranges of Layer 3 IP source or destination addresses.</li> <li>• If you configure a range of Layer 4 source ports, you cannot configure ranges of Layer 2 VLAN identifiers</li> </ul> |

| Name                                   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Destination Port</b> drop-down list | <p>Choose the destination port of the Layer 4 traffic. This can be one of the following:</p> <ul style="list-style-type: none"><li>• FTP (Data)</li><li>• FTP (Control)</li><li>• SSH</li><li>• TELNET</li><li>• HTTP</li><li>• HTTPS</li><li>• Enter Destination Port</li></ul> <p><b>Note</b> Beginning with Cisco Nexus Data Broker Release 3.2 , you can enter comma separated single port numbers and a range of the source port numbers in the <b>Enter Destination Port</b> field.</p> <p><b>Note</b></p> <ul style="list-style-type: none"><li>• If you configure a range of Layer 4 destination ports, you cannot configure ranges of Layer 3 IP source or destination addresses.</li><li>• If you configure a range of Layer 4 destination ports, you cannot configure ranges of Layer 2 VLAN identifiers</li></ul> |

**Step 6** In the **Layer 7** section of the **Add Filter** dialog box, complete the following fields:

| Name                    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HTTP Method field       | <p>You can configure matching on the HTTP methods and redirect the traffic based on that method. Select one or more methods to match within a single filter. This option is available only when the destination port is HTTP or HTTPS.</p> <ul style="list-style-type: none"> <li>• Connect</li> <li>• Delete</li> <li>• Get</li> <li>• Head</li> <li>• Post</li> <li>• Put</li> <li>• Trace</li> </ul> <p><b>Note</b> Layer 7 match is supported only with the NX-API mode only and it is not supported in OpenFlow.</p> <p><b>Note</b> The TCP option length is enabled when you select any one of the methods from Layer 7 traffic.</p> |
| TCP Option Length field | <p>You can extend the filter configuration to specify the TCP option length in the text box. The default value on the text box is 0. All methods within the filter have the same option length.</p> <p>Enter the TCP option length in a decimal format.</p> <p><b>Note</b> The value on the text box should be in the multiples of 4 and it can range from 0-40.</p>                                                                                                                                                                                                                                                                       |

**Step 7** Click **Add Filter**.

## Adding Connections

### Before You Begin

- Add a filter to be assigned to the connection.
- Configure a monitoring device (optional).



- Configure an edge port or multiple edge ports (optional).

**Step 1**

On the **Connections** tab, click **+ Connection**. The **Add Connections** window is displayed.

**Step 2**

In the **Add Connections** window, you can add the **Connection Name** and the **Priority** of the connection in the **Connection Details** area:

| Field                  | Description                                                                                                                                          |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Connection Name</b> | The name of the connection.                                                                                                                          |
| <b>Description</b>     | Enter the description when creating a new connection.                                                                                                |
| <b>Priority</b>        | The priority that you want to set for the connection.<br><br>Connection by default has priority of 100. It can be changed in the range of <1-10000>. |

**Step 3**

In the **Allow Matching Traffic** area, modify the following fields:

| Field                                        | Description                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Allow Filters</b> drop-down list          | Choose a filter to use to allow matching traffic.<br><br><b>Note</b> You cannot choose the same filter for Allow Filters that you choose for Drop Filters.                                                                                                                                                                     |
| <b>Set VLAN</b> field                        | The VLAN ID that you want to set for the connection.<br><br><b>Note</b> This functionality is available only in Openflow mode.                                                                                                                                                                                                 |
| <b>Strip VLAN at delivery port</b> check box | Check this box to strip the VLAN tag from the packet before it reaches the delivery port.<br><br><b>Note</b> The Strip VLAN at delivery port action is only valid for connections with a single edge port and one or more delivery devices for a single, separate node. This functionality is available only in Openflow mode. |
| <b>Destination Devices</b> list              | The monitoring devices that you want to associate with the filter. You can choose one or more devices by checking the boxes next to their names.                                                                                                                                                                               |
| <b>Drop Filters</b> drop-down list           | <b>Note</b>                                                                                                                                                                                                                                                                                                                    |

**Step 4**

In the **Drop Matching Traffic** area, complete the following fields:

| Field        | Description                                                                                                                                                                                                    |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Drop Filters | Choose the default filter <b>Default-Match-all</b> or use other filters to drop the matching traffic.<br><br><b>Note</b> You cannot choose the same filter for Drop Filters that you choose for Allow Filters. |

**Step 5**

In the **Source Ports (Optional)** area, complete the following fields:

| Field                                                                                                                                                           | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Select Source Node drop-down list                                                                                                                               | Choose the source node that you want to assign.<br><br><b>Note</b> If you do not choose a source node, the any-to-multipoint loop-free forwarding path option is used, and traffic from all nondelivery ports is evaluated against the filter.<br><br><b>Note</b> When setting up a new redirection, you can see the number of flows that are part of each input port. When you click the port number, the flow details are displayed.                                                                                                                                                        |
| Select Source Port drop-down list                                                                                                                               | Choose the port on the source node that you want to assign.<br><br><b>Note</b> Only edge ports can be used as source ports.<br><br><b>Note</b> If you do not select a source port while adding a new connection, the following warning message is displayed: No source port is selected. Connection will be setup from all configured Edge-SPAN and Edge-TAP ports. Click OK to continue with the connection installation/creation. It ensures that you do not install any to multi point connection and disrupt any existing traffic. Click Cancel to take you to the connection setup page. |
| In the <b>Source Ports (Optional)</b> area, select <b>Port Group</b> instead of <b>Source Ports</b> .                                                           | Select port group.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Select a port group from <b>Select Port Group</b> drop-down list. If you do not have any port groups configured, click + <b>Port Group</b> to add a port group. | Select a port group.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

**Note** Similar to the number of Edge-Tap or SPAN ports are displayed on top of each switch in the topology, the number of forwarding rules that a particular monitoring tool is part of are displayed when you hover the mouse over a switch. A popup table displays the rule (connection) names within which the monitoring tool is being used.

**Note** In Cisco Nexus Data Broker, Release 3.2.0, you can also select a port group in which case the individual ports cannot be selected.

**Step 6** Do one of the following:

- Click **Save Connection** to save the connection, but not to install it until later.
- Click **Install Connection** to save the connection and install it at the same time.
- Click **Close** to exit the connection without saving it.

The following fields are displayed on the **Connection Setup** screen:

- Name
- Allow Filters
- Drop Filters
- Source Ports
- Devices
- Priority
- Last Modified By
- Description

---

The following fields are displayed In the Connections tab: **Status, Name, Allow Filters, Drop Filters, Source Ports/Port Group, Devices, Priority, Last modified by, Description, and Action.**



**Note**

Beginning with Cisco Nexus Data Broker, Release 3.2, if you have added two or more interfaces (source ports) using the Connections tab, two interfaces (source ports) are displayed by default. If you have more than two interfaces (source ports) in the **Connections** tab, you can expand or collapse the source ports by using **more...** or **less...** options that are provided in the GUI.

Click **i Search Connections** tab in the Connections screen to search for the connections using the keywords, **Success, Installing, Creating, Partial, and Failed.**

## Adding Redirections



**Note**

The redirection setup feature is supported on Cisco Nexus 3000 Series switches running Release 6.0(2)U5(2) only and on Cisco Nexus 9300 switches with Release 7.x and OpenFlow.

Cisco Nexus Data Broker lets you configure redirection policies that match specific traffic, redirecting it through multiple security tools before it enters or exits your data center using redirection.

### Before You Begin

- Add a filter to be assigned to the redirection.
- Configure a monitoring device (optional).

- Configure an edge port or multiple edge ports (optional).
- The production ingress port, the production egress port, and the service node should be on the same redirection switch.

**Step 1**

On the **Redirections** tab, click + **Redirection**. The **Add Redirection** window is displayed.

**Step 2**

In the **Add Redirection** window, you can add the **Redirection Name** and the **Priority** of the redirection in the **Redirection Details** area:

| Field                               | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Redirection Name</b>             | The name of the redirection.<br><b>Note</b> The name of the redirection cannot be changed once you have saved it.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Description</b>                  | Enter the description when creating a new redirection.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Set Auto Priority</b> checkbox   | Check this option to enable the auto-priority for redirection. The priority of the redirection is set based on the existing redirections that are installed on the selected ingress ports.<br><br>If auto-priority is enabled, redirection has a default priority of 10000. Next redirection with auto-priority enabled will have the priority value as the last priority minus 1.<br><br>Without the auto-priority feature, the default value is 100. It can be changed in the range of <2-10000>.<br><br>Priority value 1 is reserved for the backup bypass flows.<br><b>Note</b> The priority of the redirection should not be configured as 1. Also, if the last priority is configured as 2, you cannot clone the redirection with auto-priority enabled. You have to manually clone the redirection. |
| <b>Priority</b>                     | The priority that you want to set for the redirection. The valid range of the values is 0–10000. The default is 100.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Automatic Fail-safe</b> checkbox | Check this option to enable the fail-safe feature of redirection. When you enable this feature, the direct flow from the production ingress port and the egress port is created that matches all ethertype traffic of low priority.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

**Step 3**

In the **Matching Traffic** area, modify the following fields:

| Field                         | Description                                                                                                             |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>Filters</b> drop-down list | Choose a filter to use to allow matching traffic.<br><b>Note</b> You cannot choose the same redirection for the filter. |

**Step 4**

In the **Redirection Switch** area, modify the following fields:

| Field                                    | Description                                            |
|------------------------------------------|--------------------------------------------------------|
| Select Redirection Switch drop-down list | Select the redirection switch that you want to assign. |

**Note** You can have only one ingress port and one egress port per one redirection switch.

**Step 5**

In the **Service Nodes (OPTIONAL)** area, complete the following fields:

| Field                              | Description                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------------------|
| Select Service Node drop-down list | Select the redirection service node that you want to assign and click <b>Add Service Node</b> . |

**Note** If you want to add multiple service nodes, you should add them in an order in which you want the packets to travel.

Starting with Cisco Nexus Data Broker, Release 3.2.0, the order of the service nodes is maintained. For example, if you have added the service nodes s1, s2, and s3 to redirection in an order. The service nodes become operationally down and therefore, they get removed from the redirection. Once the nodes become operationally up, they are added to the redirection in the same order.

**Step 6**

Select the **Reverse ServiceNode Direction** option to enable reverse direction on the service node.

When you enable this option and click **Submit**, the ingress and egress ports of the service node are swapped and reverse redirection is enabled on the service node. The option is also displayed as enabled in the **Redirections** tab.

**Step 7**

In the **Production Ports** area, complete the following fields:

| Field                                         | Description                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Select Production Ingress Port drop-down list | <p>Select the production ingress port that you want to assign.</p> <p><b>Note</b> You can select only one ingress port. Multiple ingress ports are not allowed. You cannot use the same ports as the ingress and the egress ports.</p> <p><b>Note</b> When setting up a new redirection, you can see the number of flows that are part of each input port. When you click the port number, the flow details are displayed.</p> |
| Select Production Egress Port drop-down list  | Select the production egress port that you want to assign.                                                                                                                                                                                                                                                                                                                                                                     |

**Step 8**

In the **Delivery Devices to copy traffic (OPTIONAL)** area, complete the following fields:

| Field                        | Description                                                                                                                                                                                                  |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Select Device drop-down list | <p>Select a device, for example, a switch from the drop-down list, that you want to assign and click <b>Add Device</b>.</p> <p><b>Note</b> You can select multiple delivery devices for the redirection.</p> |

| Field                                 | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Select Monitor Traffic drop-down list | <p>When creating inline redirection with copy, the monitoring port receives one flow from the production ingress port and another from the egress port of service node.</p> <p>Starting with Cisco Nexus Data broker Release 3.2, a filtering mechanism is added in the GUI to filter out the traffic. Use the drop down list to select the traffic to copy device in redirection.</p> <p>The following options are displayed in the drop-down list:</p> <ul style="list-style-type: none"> <li>• Production Ingress-- Flow from the production ingress port</li> <li>• Production Egress-- Flow from the egress port of the service node</li> <li>• Both-- Flow from both the ports (the ingress and the egress ports)</li> </ul> |

**Step 9** Do one of the following:

- Click **Save Redirection** to save the redirection, but not to install it until later.
- Click **Install Redirection** to save the redirection and install it at the same time.
- Click **Close** to exit the redirection without saving it.

**Step 10** When you click **Install Redirection** to save the redirection and install it at the same time, the redirection path on the redirection switch is displayed on the production ingress ports, service nodes, and the production egress ports.**Step 11** Click **Flow Statistics** to view the flow statistics for the redirection switch.

The following fields provide information on the flow statistics:

- In Port field—The Input port(s) from which the traffic is matched. An asterisk ("\*") indicates any input port.
- DL Src field—The source MAC address to be matched for the incoming traffic. An asterisk ("\*") indicates any source MAC address.
- DL Dst field—The destination MAC address to be matched for the incoming traffic. An asterisk ("\*") indicates any destination MAC address.
- DL Type field—The Ethertype to be matched for the incoming traffic. For example, "IPv4" or "IPv6" is used for all IP traffic types.
- DL VLAN field—The VLAN ID to be matched for the incoming traffic. An asterisk ("\*") indicates any VLAN ID.
- VLAN PCP field—The VLAN priority to be matched for the incoming traffic. An asterisk ("\*") is almost always displayed in this field.
- NW Src field—The IPv4 or IPv6 source address for the incoming traffic. An asterisk ("\*") indicates any source address based on IPv4 or IPv6 Ethertypes.

- NW Dst field—The IPv4 or IPv6 destination address for the incoming traffic. An asterisk ("\*") indicates any destination address based on IPv4 or IPv6 Ethertypes.
- NW Proto field—The network protocol to be matched for the incoming traffic. For example, "6" indicates the TCP protocol.
- TP Src field—The source port associated with the network protocol to be matched for the incoming traffic. An asterisk ("\*") indicates any port value.
- TP Dst field—The destination port associated with the network protocol to be matched for the incoming traffic. An asterisk ("\*") indicates any port value.
- Actions field—The output action to be performed for the traffic matching the criteria specified, for example, "OUTPUT = OF|2".
- Byte Count field—The aggregate traffic volume shown in bytes that match the specified flow connection.
- Packet Count field—The aggregate traffic volume shown in packets that match the specified flow connection.
- Duration Seconds field—The amount of time, in milliseconds, that the specific flow connection has been installed in the switch.
- Idle Timeout field—The amount of time, in milliseconds, that the flow can be idle before it is removed from the flow table.
- Priority field—The priority assigned to the flow. The flows with higher priority numbers take precedence.

**Step 12** Click **Close** to close the flow statistics display window.

---

## Viewing Statistics

View the flow and port statistics for the switches on the Statistics tab.



**Note**

When you select a switch on the statistics page, the **Auto Refresh** tab for the switch is ON by default. Click **Auto Refresh: Off** to disable auto refresh on the Statistics tab. The screen is refreshed every 30 seconds and the updated statistics for the switch are displayed on the screen.

---

**Step 1** Navigate to the **Statistics** tab under **Configuration** and click a node from the drop-down list to check and view the flow and port statistics of that node.

You can also navigate to the statistics of another switch by selecting the switch in the drop down box.

You can view the flow statistics, for example:

- Flow Name
- In Port
- DL Source

- DL Destination
- DL Type
- DL VLAN
- VLAN PCP
- NW Source
- NW Destination
- NW Proto
- TP Source
- TP Destination
- AP HttpMd
- AP TcpOptLn
- Actions
- Byte Count
- Packet Count
- Duration Seconds
- Idle Timeout
- Priority

**Step 2**

Click the **Ports** tab to check the ports statistics.

You can view the ports statistics as displayed in the following fields.

**Note** If you are programming the switches with OpenFlow, when you navigate to the **Statistics** tab, select a switch, and select **Ports** tab, the statistics gathered from the switches for the **Rx Frame Errs** and **Collisions** are not supported. The value of -1 is displayed rather than N/A because the variable needs to be an integer.

- Port Name
- Rx Packets
- Tx Packets
- Rx Bytes
- Tx Bytes
- Rx Rate (kbps)
- Tx rate (kbps)
- Rx Drops
- Tx Drops
- Rx Errors
- Tx Errors



- Rx Frame Errors
  - Rx Overrun Errors
  - Rx CRC Errors
  - Collisions
- 

## Adding SPAN Sessions

On the SPAN Sessions tab, the following fields are displayed:

- SPAN Session
- Filter
- Devices
- SPAN Source
- SPAN Destination

You can add a SPAN session in ACI.

- 
- Step 1** Click + **SPAN Session** to add a SPAN session. The **Add SPAN Session** window is displayed.
- Step 2** In the **Add SPAN Session** window, add a session name in the **SPAN Session Name** field.
- Step 3** (Optional) Select a connection in the **Select Connections** field.
- Step 4** In the **Action** pane, select a priority for the SPAN session.
- Step 5** Select a rule using the drop-down list in the **Rule Filter** field. You can select the default filter rule, **Default-Match-IP** or select another filter from the drop-down list.  
The available filter rules are **Default-Match-IP**, **Match-HTTP**, **Match-vlan**, and **Default-Match-all**.
- Step 6** Select a destination device to which the traffic is sent.
- Step 7** In the **SPAN SOURCES** pane, select the device type as ACI or NXOS in the **Select Device Type** field. When you select ACI device and click +Add SPAN Source, the **Add Leaf Ports** or +**Add EPG** tabs are displayed.
- In the **Add Leaf Ports** window, select a pod using the drop-down list in the **POD** field.
  - Select a node using the drop-down list in the **Node** field.
  - Select a port using the drop-down list in the **Port** field.
  - Click **Add Leaf Ports**.
  - In the **SPAN SOURCES** pane, select a direction from the **Incoming**, **Outgoing**, or **Both** options.  
The selected Span source is displayed in the **Span Source** field.
  - If you select +**Add EPG** to add EPG source, select a tenant using the drop-down list in the **Tenant** field in the **Add EPG** window.

- Note**
- All EPG interfaces work only when all the ports are within the same leaf switch.
  - If same EPG is across multiple switches, you have to select the leaf switch and the associated ports. One SPAN session needs to be setup for each leaf switch.

- g) Select a profile using the drop-down list in the **Profile** field.
- h) Select EPG associated with the tenant using the drop-down list in the **EPG** field.  
The selected **SPAN Source** is displayed.
- i) Select **Include All EPG Interfaces** option.  
When you enable this option, the statically configured interfaces are added to the EPG.

**Note** This option can be used only when all EPG sources are within the same leaf switch.

If the EPG is selected, by default, Cisco Nexus Data Broker listens for the changes in the statically configured interfaces of the selected EPG. If there is any change, it is applied to the SPAN session. The web socket connection is not secured with the certificates. To disable the event listening, add **enableWebSocketHandle=false** in the **config.ini** file under **xnc/configuration** folder.

- j) Click **Add EPG**.

**Step 8** In the **SPAN SOURCES** pane, when you select the device type as NXOS in the **Select Device Type** field and click **+Add SPAN Source**, the **Add Interface** or **Add VLAN** tabs are displayed.  
This field allows to add NXOS SPAN session via NXAPI. It allows to add 2 types of SPAN sources. If you need to add interface as source, click **+ ADD SPAN Source** and click **Interface**. If you need to allow traffic of a particular VLAN, click **VLAN**.

**Note** You cannot add interfaces and VLAN as SPAN source for the same NXOS SPAN session.

You cannot have ACI and NXOS SPAN sources in the same SPAN session.

**Step 9** When you click **+Add Interface**, the **Add Production Switch Interface** window is displayed.  
You can select a node, select an interface, and click **Submit**.

**Step 10** When you click **+Add VLAN**, the **Add Production Switch VLAN** window is displayed.  
You can select a node, enter a VLAN, and click **Submit**.

**Step 11** In the **SPAN Destination** field, you can select the SPAN destination.  
This field displays SPAN destination for ACI in the ACI SPAN session or SPAN destination for NXOS in the NXOS SPAN session.

**Note** The SPAN destination should be the same leaf where the SPAN sources are being selected.

SPAN destination and SPAN source interface of ACI should be in the same node. If both are in different nodes, the SPAN session cannot be created.

**Step 12** Click **Add SPAN Session**.  
A message box is displayed asking you to confirm, **Are you sure you want to add SPAN session?**, if you want to add the SPAN session.

**Step 13** Click **OK**.  
As a result, a SPAN session is set up in ACI. It also sets up a connection automatically on the Cisco Nexus Data Broker with the same SPAN session name and this connection redirects the traffic from that source port to the monitoring device.

**Note** Each leaf can have a maximum of 4 SPAN sessions.

You can set up additional SPAN sessions. You can append a new SPAN session to the existing connection. In that case, you can select the new SPAN session in the Add SPAN Session window, use the same connection that is previously created, select new SPAN sources from different leaf ports, select the SPAN destination, and add the SPAN session.

It creates a new session in ACI, but it appends an existing connection to include the new traffic on the Cisco Nexus Data Broker side.

You can edit or clone the existing SPAN sessions. If you want to remove a SPAN session, click the session and click **Remove SPAN Session(s)**. A message box is displayed asking you to confirm, **Remove the following sessions?**, if you want to remove the displayed SPAN session. Click **Remove SPAN Sessions** to confirm. If the SPAN session is using an existing connection, the connection is updated automatically with the changes. If it is the last connection associated with the SPAN session, the connection is deleted.

---





# Integrating Cisco Nexus Data Broker With Cisco ACI

---

This chapter contains the following sections:

- [Viewing the SPAN Management Tab, page 67](#)
- [Viewing the SPAN Destination Tab, page 68](#)
- [Adding SPAN Destination, page 68](#)
- [Creating Copy Devices Using Copy Sessions \(BETA\), page 70](#)
- [Adding SPAN Sessions, page 71](#)

## Viewing the SPAN Management Tab

The **SPAN Management** tab is displayed on the **Devices** screen under the **Administration** tab in the GUI.

On the **SPAN Management** tab, click + **Add Device**. The **Connect to Device** window is displayed. Complete the following steps to connect to the device:

### Before You Begin

For APIC and production switches, the centralized deployment of Cisco Nexus Data Broker is mandatory.

- 
- |               |                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Step 1</b> | Choose <b>ACI</b> device to add an APIC device.                                                                                                                                                                                                                                                                                                                                                               |
| <b>Step 2</b> | In the <b>APIC IP Addresses</b> panel, add the <b>APIC IP Address (Primary)</b> , <b>APIC IP address (Secondary)</b> , and <b>APIC IP address (Tertiary)</b> .                                                                                                                                                                                                                                                |
| <b>Step 3</b> | In the <b>User Details</b> panel, add <b>Username</b> and <b>Password</b> .                                                                                                                                                                                                                                                                                                                                   |
| <b>Step 4</b> | After an ACI device has been added, the ACI radio button is disabled. Then you can add a NXOS production switch. Click <b>NXOS</b> in the first step to add a NXOS production switch.<br>The NX-API feature has to be enabled for the NXOS production switch to be added. To add a NXOS production switch in the <b>SPAN Management</b> tab, one NX-API device should already exist. This is a pre-requisite. |

**Step 5** Click **Connect**.

The NXOS production switch is displayed with the **Type** as **PS** in the **SPAN Management** tab. The **APIC IP Address (Primary)**, **APIC IP address (Secondary)**, and **APIC IP address (Tertiary)** do not apply to the NXOS production switch. Therefore, those fields are blank. You can also edit the credentials of the NXOS production switch. Once the production switch is added, it is displayed in the Configuration tab in green. In the Port Configuration window, you can configure SPAN Destination in the production Nexus switches that are NX-API enabled.

## Viewing the SPAN Destination Tab

When you click **Port Definition** tab in the GUI, the **Port Definition** screen is displayed. Select the switch from the drop-down list to configure the ports.

On the **Port Definition** screen, the following two tabs are displayed:

- Port Configuration
- SPAN Destination

On the **SPAN Destination** tab, the following details are displayed:

- SPAN Destination Name
- SPAN Destinations
- Node Connector
- Monitor Port Type
- Description

## Adding SPAN Destination

When you configure a port as an edge SPAN port and the port is connected to the API side, you can select the pod, node, and port from the ACI side and set the port as SPAN destination. SPAN destination can now be configured on the Cisco Nexus 9000 or Cisco Nexus 3000 Series production switches.

**Note**

For APIC SPAN destination, when you configure a port as an Edge SPAN port and the port is connected to the API side, you can select the pod, the node, and the port from the ACI side and set the port as SPAN destination. For production switch SPAN destination, when you configure a port as an Edge SPAN port and the port is connected to the production switch side, you can select the node and the port from the production switch side and set the port as SPAN destination.

You can add SPAN destination only after either an APIC or the production switch has been successfully added to the network.

---

**Step 1** Select the switch for which you want to configure the port details on the **Port Configuration** screen.

**Step 2** Click **Configure** under **Action**.  
The **Configure Ports** window is displayed.

**Step 3** In the **Configure Ports** window, configure the port type from the **Select a port type** drop-down list by selecting one of the following options:

- **Add Monitoring Device**
- **Edge Port-SPAN**
- **Edge Port-TAP**
- **Production Port**

**Monitoring Device**—Creates a monitoring device for capturing traffic and configures the corresponding delivery port.

**Edge Port-SPAN**—Creates an edge port for incoming traffic connected to an upstream switch that is configured as a SPAN destination.

**Edge Port-TAP**—Creates an edge port for incoming traffic connected to a physical TAP port.

**Production Port**—Creates a production port for the ingress and egress traffic.

When you select the port type, the title of the window changes to **Manage Configure Ports**.

**Step 4** In **Manage Configure Ports** window, the details of the selected node are displayed.

**Step 5** In the **Destination** panel, if the APIC device is added, it is listed in the drop-down list. Select the **Node Type** as **APIC** from the drop-down list.  
The **SPAN Destination** and **Copy Device** tabs are displayed.

**Step 6** When you click the **SPAN Destination** tab, the **Select SPAN Destination** window is displayed. It contains the following fields: **Select Pod**, **Select Node**, **Select Port**, and **SPAN Destination**.

**Step 7** Select the values for the fields and click **Apply**.  
The port is now configured as SPAN destination part and it is displayed on the Port Definition screen.

---

# Creating Copy Devices Using Copy Sessions (BETA)

When you configure a port as an edge-SPAN port, you can create copy devices using Copy Sessions (BETA) functionality.



## Note

You can add SPAN destination and copy devices only after an APIC device has been successfully added to the network.

- 
- Step 1** Select the switch for which you want to configure the port details using the **Port Configuration** screen.
- Step 2** Click **Configure** under **Action**.  
The **Configure Ports** window is displayed.
- Step 3** In the **Configure Ports** window, configure the port type from the **Select a port type** drop-down list by selecting one of the following options:
- **Add Monitoring Device**
  - **Edge Port-SPAN**
  - **Edge Port-TAP**
  - **Production Port**
- Monitoring Device**—Creates a monitoring device for capturing traffic and configures the corresponding delivery port.
- Edge Port-SPAN**—Creates an edge port for incoming traffic connected to an upstream switch that is configured as a SPAN destination.
- Edge Port-TAP**—Creates an edge port for incoming traffic connected to a physical TAP port.
- Production Port**—Creates a production port for the ingress and egress traffic.
- When you select the port type, the title of the window changes to **Manage Configure Ports**.
- Step 4** In **Manage Configure Ports** window, the details of the selected node are displayed.
- Step 5** In the **Destination** panel, if the APIC device is added, it is listed in the drop-down list. Select the **Node Type** as **APIC** from the drop-down list.  
The **SPAN Destination** and **Copy Device** tabs are displayed. See *Adding SPAN Destination* section for adding SPAN destination.
- Step 6** When you click the **Copy Device** tab in the same window, the **Create Copy Device (BETA)** window is displayed.
- Step 7** In the General panel, enter the name of the device in the **Name** field. The values for the fields, **Device Type** and **Physical Domain** are hard-coded.
- Step 8** In the Device Interface panel, enter the details in the following fields: **Name**, **Pod**, **Node**, and **Port**. The value for the field, **Path Type** is hard-coded.
- Step 9** In the Cluster panel, enter the details in the following fields, **Name** and **VLAN Encap**. The value for the field, **Interface** is hard-coded.
- Step 10** Click **Submit** to save the settings.  
The name and the path of the copy device is displayed in the destination panel.



- Step 11** When you click **Submit** in **Manage Configure Ports** window, the device is displayed in the **Destination** column in the **Port Configuration** screen. When you hover over the device name in the GUI, the name of the **Copy Device** is displayed.
- Step 12** Once the **Copy Device** is added, it is displayed in the **APIC Copy Session (BETA)** screen under the **Copy Device** tab. The following fields are displayed under the **Copy Device** tab: **Cluster Name**, **Managed**, **Device Type**, and **Service Type**.
- Step 13** In the **APIC Copy Session (BETA)** screen, the **Service Graph** tab is displayed. When you click **+Add Service Graph**, the **Add Service Graph (BETA)** window is displayed.
- Step 14** Add name for the service graph in the **Name** field.
- Step 15** Select the copy device for the service graph in the **Copy Device** field.  
The copy devices that are created by Cisco Nexus Data Broker are listed in the **Copy Device** field.
- Step 16** Click **Submit** to save the settings.  
Once the service graph is added, it is displayed in the **APIC Copy Session (BETA)** screen under the **Service Graph** tab. The fields that are displayed on the tab are **Name**, **Copy Device**, **Function Nodes**, and **Action**. The parameters that can be edited for the service graph are **Name** and **Copy Device** only. You can click **Remove** under **Action** column in the **APIC Copy Session (BETA)** screen to remove the service graph.
- Note** By default, the copy device and the service graph get created under the common tenant.

## Adding SPAN Sessions

On the SPAN Sessions tab, the following fields are displayed:

- SPAN Session
- Filter
- Devices
- SPAN Source
- SPAN Destination

You can add a SPAN session in ACI.

- Step 1** Click **+ SPAN Session** to add a SPAN session. The **Add SPAN Session** window is displayed.
- Step 2** In the **Add SPAN Session** window, add a session name in the **SPAN Session Name** field.
- Step 3** (Optional) Select a connection in the **Select Connections** field.
- Step 4** In the **Action** pane, select a priority for the SPAN session.
- Step 5** Select a rule using the drop-down list in the **Rule Filter** field. You can select the default filter rule, **Default-Match-IP** or select another filter from the drop-down list.  
The available filter rules are **Default-Match-IP**, **Match-HTTP**, **Match-vlan**, and **Default-Match-all**.

- Step 6** Select a destination device to which the traffic is sent.
- Step 7** In the **SPAN SOURCES** pane, click + **Add SPAN Source**. In the pane, click + **Add Leaf Ports** to add a leaf port to capture the traffic from multiple leaf ports. OR optionally, you can click +**Add EPG** to add an EPG source. Enter the values in the following fields:
- In the **Add Leaf Ports** window, select a pod using the drop-down list in the **POD** field.
  - Select a node using the drop-down list in the **Node** field.
  - Select a port using the drop-down list in the **Port** field.
  - Click **Add Leaf Ports**.
  - In the **SPAN SOURCES** pane, select a direction from the **Incoming**, **Outgoing**, or **Both** options.  
The selected Span source is displayed in the **Span Source** field.
  - If you select +**Add EPG** to add EPG source, select a tenant using the drop-down list in the **Tenant** field in the **Add EPG** window.
 

**Note**

    - All EPG interfaces work only when all the ports are within the same leaf switch.
    - If same EPG is across multiple switches, you have to select the leaf switch and the associated ports. One SPAN session needs to be setup for each leaf switch.
  - Select a profile using the drop-down list in the **Profile** field.
  - Select EPG associated with the tenant using the drop-down list in the **EPG** field.  
The selected **SPAN Source** is displayed.
  - Select **Include All EPG Interfaces** option.  
When you enable this option, the statically configured interfaces are added to the EPG.
 

**Note** This option can be used only when all EPG sources are within the same leaf switch.

If the EPG is selected, by default, Cisco Nexus Data Broker listens for the changes in the statically configured interfaces of the selected EPG. If there is any change, it is applied to the SPAN session. The web socket connection is not secured with the certificates. To disable the event listening, add **enableWebSocketHandle=false** in the **config.ini** file under **xnc/configuration** folder.
  - Click **Add EPG**.
- Step 8** In the **SPAN Destination** field, select SPAN destination.  
If you install ACI SPAN session, it lists the SPAN destination that is created in ACI.  
If you install NXOS SPAN session, it lists the SPAN destination that is created in NXOS.
- Note** The SPAN destination should be the same leaf where the SPAN sources are being selected.
- Step 9** Click **Add SPAN Session**.  
A message box is displayed asking you to confirm, **Are you sure you want to add SPAN session?**, if you want to add the SPAN session.
- Step 10** Click **OK**.  
As a result, a SPAN session is set up in ACI. It also sets up a connection automatically on the Cisco Nexus Data Broker with the same SPAN session name and this connection redirects the traffic from that source port to the monitoring device.
- Note** Each leaf can have a maximum of 4 SPAN sessions.
- You can set up additional SPAN sessions. You can append a new SPAN session to the existing connection. In that case, you can select the new SPAN session in the Add SPAN Session window, use the same connection that is previously created, select new SPAN sources from different leaf ports, select the SPAN destination, and add the SPAN session.

It creates a new session in ACI, but it appends an existing connection to include the new traffic on the Cisco Nexus Data Broker side.

You can edit or clone the existing SPAN sessions. If you want to remove a SPAN session, click the session and click **Remove SPAN Session(s)**. A message box is displayed asking you to confirm, **Remove the following sessions?**, if you want to remove the displayed SPAN session. Click **Remove SPAN Sessions** to confirm. If the SPAN session is using an existing connection, the connection is updated automatically with the changes. If it is the last connection associated with the SPAN session, the connection is deleted.

---





## Viewing and Adding Flows

This chapter contains the following sections:

- [Viewing Flows, page 75](#)
- [Adding a Flow, page 75](#)

### Viewing Flows



**Note**

This functionality is applicable only for OpenFlow mode of deployment.

On the **Flows** tab, the following fields are displayed:

- Serial Number
- Status
- Flow Name
- Node

**What to Do Next**

Click + **Flow** to add a flow.

### Adding a Flow

**Step 1** Navigate to the **Flows** tab under **Administration**, click + **Flow** to add a flow.

**Step 2** On the **Add Flow Description** window, update the following fields:

| Name                                    | Description                                                                                                                                                                                                                                                                                           |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b> field                       | The name that you want to assign to the flow.<br><b>Note</b> You cannot change the name of the flow entry after it is saved.                                                                                                                                                                          |
| <b>Select a Node</b> drop-down list     | Select a node name for the device.<br><b>Note</b> The node you choose cannot be changed once you save the flow entry.                                                                                                                                                                                 |
| <b>Input Port</b> drop-down list        | Choose the port on the node where traffic enters the flow.                                                                                                                                                                                                                                            |
| <b>Priority</b> field                   | The priority that you want to apply to the flow. The default priority is 500. Flows with a higher priority are given precedence over flows with a lower priority.<br><b>Note</b> The priority is considered only when all of the Layer 2, Layer 3, and Layer 4 match fields are equal.                |
| <b>Hard Timeout</b> field               | The amount of time in milliseconds for the flow to be installed before it is removed from the flow table.                                                                                                                                                                                             |
| <b>Idle Timeout</b> field               | The amount of time in milliseconds that the flow can be idle before it is removed from the flow table.                                                                                                                                                                                                |
| <b>Layer 2</b>                          |                                                                                                                                                                                                                                                                                                       |
| <b>Ethernet Type</b> field              | The Ethernet type for the Layer 2 traffic. The Ethernet type for IPv4, in hexadecimal format, is displayed by default. Either accept the default value, or enter one of the following, in hexadecimal format: <ul style="list-style-type: none"> <li>• IPv6</li> <li>• ARP</li> <li>• LLDP</li> </ul> |
| <b>VLAN Identification Number</b> field | The VLAN ID for the Layer 2 traffic.                                                                                                                                                                                                                                                                  |
| <b>VLAN Priority</b> field              | The VLAN priority for the Layer 2 traffic.                                                                                                                                                                                                                                                            |
| <b>Source MAC Address</b> field         | The source MAC address for the Layer 2 traffic.                                                                                                                                                                                                                                                       |
| <b>Destination MAC Address</b> field    | The destination MAC address for the Layer 2 traffic.                                                                                                                                                                                                                                                  |
| <b>Layer 4</b>                          |                                                                                                                                                                                                                                                                                                       |
| <b>Source Port</b> field                | The source port of the Layer 4 traffic.                                                                                                                                                                                                                                                               |

| Name                          | Description                                                                                                                 |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>Destination Port</b> field | The destination port of the Layer 4 traffic.                                                                                |
| <b>Protocol</b> field         | The Internet protocol number of the Layer 4 traffic. Enter the IP protocol number in decimal, hexadecimal, or octal format. |
| <b>Actions</b> drop-down list | Select an action from the drop-down list.                                                                                   |

**Step 3**

Click **Install Flow** to install the flow into the device OR click **Save Flow** to save the flow to the **Flow Entries** table, but the system does not install the flow in the flow table of the device.

---







## Viewing Consistency Check

---

This chapter contains the following sections:

- [Viewing Consistency Check, page 79](#)

## Viewing Consistency Check

On the **Consistency Check** tab, the following details are displayed:

- Node ID
- Inconsistent Controller Flow
- Inconsistent Node Flow
- Statistics: Click **Flows & Ports** for the node statistics.

- 
- |               |                                                                                                                                                                                                                             |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Step 1</b> | Select the node name from the list of available nodes in the <b>Node Name</b> field.<br>The ID for the selected node is displayed in the <b>Node ID</b> field.                                                              |
| <b>Step 2</b> | Click the value in the <b>Inconsistent Controller Flow</b> field to view the inconsistent controller flows that display the following fields, <b>Switch</b> , <b>Priority</b> , <b>Hard Timeout</b> , <b>Idle Timeout</b> . |
| <b>Step 3</b> | Click the value in the <b>Inconsistent Node Flow</b> field to view the inconsistent node flows.                                                                                                                             |
| <b>Step 4</b> | Click <b>Statistics</b> to view the flow and port statistics.                                                                                                                                                               |
-





# Managing Users

This chapter contains the following sections:

- [Adding a User, page 81](#)
- [Adding a Role, page 82](#)
- [Adding a Group, page 83](#)

## Adding a User

After creating a user, you can change the password, but you cannot change the roles assigned to the user.

- Step 1

Step 2
- Navigate to the **User Management** tab under **Administration** and click + **User** to add a user.  
In the **Add User** window, complete the following fields:

| Name                  | Description                                                                                                                                                                                                              |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Username field        | The name that you want to assign to the user.                                                                                                                                                                            |
| Password field        | The password for the user.<br><br>Passwords must be between 8 and 256 characters long, contain uppercase and lowercase characters, have at least one numeric character, and have at least one nonalphanumeric character. |
| Verify Password field | Verify the password by re-entering it.                                                                                                                                                                                   |

| Name                          | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Choose Role(s) drop-down list | <p>Choose the role that you want to assign to the user. You can assign more than one role. It can be one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Application User</b>—Provides privileges that are defined in the specified application.</li> <li>• <b>Security</b>—Provides privileges that are defined in the security application.</li> <li>• <b>Network Administrator</b>—Provides full administrative privileges to all applications.</li> <li>• <b>Network Operator</b>—Provides read-only privileges to all applications.</li> <li>• <b>Slice User</b>—Provides access to a specified slice.</li> </ul> |
| Enter a Role Name field       | If you choose <b>Application User</b> , enter the name that you want to assign to the role.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

**Step 3** Click **Save** in the **User Management** window or click **Cancel** to cancel the action.

## Adding a Role

**Step 1** Navigate to the **User Management** tab under **Administration** and click + **Role**.

**Step 2** In the **Add Role** window, complete the following fields:

| Field                | Description                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name field           | The name of the role.                                                                                                                                                                                                                                                                                                                                                                                             |
| Level drop-down list | <p>Choose the level that you want to assign to the role. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• <b>App-Administrator</b>—Has full access to all Cisco Nexus Data Broker resources.</li> <li>• <b>App-User</b>—Has full access to resources that are assigned to his resource group and resources that are created by another user who has similar permissions.</li> </ul> |
| Assign Group(s)      | Assign groups to the selected role.                                                                                                                                                                                                                                                                                                                                                                               |

**Step 3** Click save.

---

## Adding a Group

**Step 1** Navigate to the **User Management** tab under **Administration** and click **+ Groups**.

**Step 2** In the **Add Group** window, complete the following field:

| Field                            | Description                                   |
|----------------------------------|-----------------------------------------------|
| <b>Resource Group Name</b>       | The name of the resource group.               |
| <b>Select Switch Node</b>        | Select a switch node from the drop-down list. |
| <b>+ Assign Switch and Ports</b> | Click + to add a new switch to the group.     |
| <b>Select Ports</b>              | Select the ports associated with the switch.  |
| <b>Assign Group to Roles</b>     | Assign a role to the group.                   |

**Step 3** Click Save.

---





## Configuring the Setup for a Use Case in the Centralized Mode

This chapter contains the following sections:

- [Configuring Cisco Nexus Data Broker For Centralized Mode Using The CLI, page 85](#)
- [Configuring Cisco Nexus Data Broker in Centralized Mode Using The GUI, page 88](#)

## Configuring Cisco Nexus Data Broker For Centralized Mode Using The CLI

Complete the following steps to configure

### SUMMARY STEPS

1. Create two connections.
2. Run Cisco Nexus Data Broker in Linux server.
3. Verify that the ofa package is there.
4. Install ofa.
5. Configure OpenFlow switch.

### DETAILED STEPS

|        | Command or Action                            | Purpose |
|--------|----------------------------------------------|---------|
| Step 1 | Create two connections.                      |         |
| Step 2 | Run Cisco Nexus Data Broker in Linux server. |         |
| Step 3 | Verify that the ofa package is there.        |         |
| Step 4 | Install ofa.                                 |         |
| Step 5 | Configure OpenFlow switch.                   |         |

## Run Cisco Nexus Data Broker in Linux server.

```
[root@rhel64-ndb-nxapi NDB3.0.0]#
[root@rhel64-ndb-nxapi NDB3.0.0]# ls
ndb1000-sw-app-k9-3.0.0.zip xnc
[root@rhel64-ndb-nxapi NDB3.0.0]#
[root@rhel64-ndb-nxapi NDB3.0.0]# cd xnc/
[root@rhel64-ndb-nxapi xnc]# ls
bin configuration etc lib logs plugins runxnc.cmd runxnc.sh version.properties
work
[root@rhel64-ndb-nxapi xnc]# ./runxnc.sh -start
Running controller in background with PID: 11987, to connect to it please SSH to this host
on port 2400
[root@rhel64-ndb-nxapi xnc]#
```

## Verify that the ofa package is installed.

```
switch-1 - Switch
=====
```

```
switch-1#
switch-1# dir
4096 Jun 01 23:55:07 2016 .patch/
1044 Aug 13 00:15:17 2014 20140813_001215_poap_3799_init.log
16 Aug 13 00:30:15 2014 cert.err
9255 Jun 01 23:38:11 2016 clean_config
2885642 May 12 22:11:57 2014 lltormtc-dplug-mzg.6.0.2.A3.0.23.bin
4194304 Sep 08 19:24:42 2014 messages
3752 Mar 18 00:48:03 2014 mts.log
36825088 Apr 19 18:47:44 2016 n3500-uk9-kickstart.6.0.2.A6.5a.bin
37472256 Jun 01 23:43:34 2016 n3500-uk9-kickstart.6.0.2.A8.0.15.bin
180349300 Apr 19 18:49:37 2016 n3500-uk9.6.0.2.A6.5a.bin
190244286 Jun 01 23:42:07 2016 n3500-uk9.6.0.2.A8.0.15.bin
54343680 Apr 24 05:27:43 2016 ofa_mmemb-1.1.5-r3-n3000-SPA-k9.ova
4096 Mar 18 06:08:07 2014 oneP/
3314 Apr 25 18:14:18 2014 sercert.p12
1024 Apr 19 18:58:37 2016 sprom_cstruct_2_0_0
1024 Apr 19 18:59:22 2016 sprom_cstruct_3_0_0
4096 Jan 01 03:25:17 2011 vdc_2/
4096 Jan 01 03:25:17 2011 vdc_3/
4096 Jan 01 03:25:17 2011 vdc_4/
4096 Jun 01 23:31:49 2016 virt_strg_pool_bf_vdc_1/
4096 Jun 01 23:31:49 2016 virtual-instance/
4096 Aug 09 02:20:14 2014 virtual-instance-stby-sync/
243671040 May 09 20:55:18 2016 xnclite_ofa_jdk1877.ova
243732480 May 10 21:51:52 2016 xnclite_ofa_jdk1892.ova
```

```
Usage for bootflash://
1124974592 bytes used
770195456 bytes free
1895170048 bytes total
switch-1#
```

## Install ofa.

```
switch-1#
switch-1# virtual-service install name ofa package ofa_mmemb-1.1.5-r3-n3000-SPA-k9.ova
Note: Installing package 'bootflash:/ofa_mmemb-1.1.5-r3-n3000-SPA-k9.ova' for virtual service
'ofa'. Once the install has finished, the VM may be activated. Use 'show virtual-service
list' for progress.
```

```
switch-1# sh virtual-service list
```

```
Virtual Service List:
```

| Name | Status    | Package Name                        |
|------|-----------|-------------------------------------|
| ofa  | Installed | ofa_mmemb-1.1.5-r3-n3000-SPA-k9.ova |



```

switch-1# configure
Enter configuration commands, one per line. End with CNTL/Z.
switch-1(config)# virtual-service ofa
switch-1(config-virt-serv)# activate
Note: Activating virtual-service 'ofa', this might take a few minutes. Use 'show
virtual-service list' for progress.
switch-1(config-virt-serv)# show virtual-service list

```

Virtual Service List:

| Name | Status    | Package Name                        |
|------|-----------|-------------------------------------|
| ofa  | Activated | ofa_mmemb-1.1.5-r3-n3000-SPA-k9.ova |

```
switch-1(config-virt-serv)#
```

### Configure OpenFlow switch.

```

switch-1(config-virt-serv)# openflow
switch-1(config-ofa)# switch 1
switch-1(config-ofa-switch)# pipeline 203
switch-1(config-ofa-switch)# controller ipv4 10.16.206.161 port 6653 vrf management security
none
switch-1(config-ofa-switch)# sh int br

```

| Ethernet Interface | VLAN | Type | Mode   | Status | Reason           | Speed  | Port Ch # |
|--------------------|------|------|--------|--------|------------------|--------|-----------|
| Eth1/1             | 1    | eth  | access | up     | none             | 10G(D) | --        |
| Eth1/2             | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/3             | 1    | eth  | access | up     | none             | 10G(D) | --        |
| Eth1/4             | 1    | eth  | access | up     | none             | 10G(D) | --        |
| Eth1/5             | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/6             | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/7             | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/8             | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/9             | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/10            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/11            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/12            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/13            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/14            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/15            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/16            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/17            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/18            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/19            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/20            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/21            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/22            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/23            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/24            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/25            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/26            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/27            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/28            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/29            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/30            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/31            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/32            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/33            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/34            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/35            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/36            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/37            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/38            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/39            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/40            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/41            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |
| Eth1/42            | 1    | eth  | access | down   | SFP not inserted | 10G(D) | --        |

```

Eth1/43 1 eth access down SFP not inserted 10G(D) --
Eth1/44 1 eth access down SFP not inserted 10G(D) --
Eth1/45 1 eth access down SFP not inserted 10G(D) --
Eth1/46 1 eth access down SFP not inserted 10G(D) --
Eth1/47 1 eth access up none 10G(D) --
Eth1/48 1 eth access down SFP not inserted 10G(D) --

```

```

Port VRF Status IP Address Speed MTU

mgmt0 -- up 10.16.206.129 1000 1500
switch-1(config-ofa-switch)#
switch-1(config-ofa-switch)#
switch-1(config-ofa-switch)#
switch-1(config-ofa-switch)# of-port interface ethernet1/1-4
switch-1(config-ofa-switch)# of-port interface ethernet1/47
switch-1(config-ofa-switch)#

```

```

Switch-2
=====

```

```

switch-2(config-ofa-switch)# show virtual-service list

```

```

Virtual Service List:

```

```

Name Status Package Name

ofa Activated ofa_mmemb-1.1.5-r3-n3000-SPA-k9.ova

```

```

switch-2(config-ofa-switch)#

```

### What to Do Next

For centralized mode, complete the steps for configuring Cisco Nexus Data Broker using the GUI as outlined in the next section.

## Configuring Cisco Nexus Data Broker in Centralized Mode Using The GUI

After configuring the Cisco Nexus Data Broker using the CLI, complete the following steps:

- 
- Step 1** Open a new browser window and type *https://<NDB-IP>:8443*.
- a)
- Step 2** Configure the TAP and SPAN ports using the GUI.

- Step 3** Select switch 2 and configure the delivery ports.
- Step 4** Add switch 1 and switch 2 in NX-API as in auxiliary mode by enabling the **Set Auxiliary Node** option in the **Add Device** window.
- Step 5** Click **Nodes Learned** to configure the mode.
- Step 6** For switch 1, click on the OpenFlow device ID and change the **Operation Mode** in the **Update Node Information** window to **Proactive forwarding only** option.
- Step 7** For switch 2, click on the OpenFlow device ID and change the **Operation Mode** in the **Update Node Information** window to **Proactive forwarding only** option.
- Step 8** In the **Port Definition** window, click **Edit** for delivery port 1/1.
- Step 9** Check the **Enable Timestamp Tagging** option in the **Configure Ports** window and click **Submit**.
- Step 10** In the **Port Definition** window, click **Edit** for delivery port 1/2.
- Step 11** Check the **Enable Timestamp Tagging** option in the **Configure Ports** window and click **Submit**.  
After you configure the timestamp, the **TS-Tag** field is displayed next to the port under the **Port Configuration** tab. You can view the monitoring devices in the **Monitoring Devices** tab.
- Step 12** Add different traffic filters under the **Filters** tab.
- Step 13** Click **Topology** to understand how the devices are learned.
- Step 14** Click **Connections** to create a connection.
- Step 15** Click **Add Connection** and add filters and the monitoring devices for connection 1.
- Step 16** Add connection 2 in a similar way.  
After the connections are created, view the connections in the **Connections** tab.
- Step 17** View the final topology.

### Example of the configuration on switch 1 and switch 2:

Switch 1 Configuration: switch-1

```

hardware profile tcam region racl 512
hardware profile tcam region ifacl 1024 double-wide
hardware profile forwarding-mode openflow-only
hardware internal mtc-usd ttag-eth-type 0x88b5
snmp-server user admin network-admin auth md5 0x188749ba5e1c6af881227235b1b14d04 priv
0x188749ba5e1c6af881227235b1b14d04 localizedkey

vlan 1
vrf context management
 ip route 0.0.0.0/0 10.16.206.1

interface Ethernet1/1
 no lldp transmit
 spanning-tree bpdufilter enable
 mode openflow
 no shutdown

interface Ethernet1/2
 no lldp transmit
 spanning-tree bpdufilter enable
 mode openflow
 no shutdown

interface Ethernet1/3
 no lldp transmit
 switchport mode trunk
 spanning-tree bpdufilter enable

```

```
mode openflow
no shutdown

interface Ethernet1/4
no lldp transmit
switchport mode trunk
spanning-tree bpdufilter enable
mode openflow
no shutdown

interface Ethernet1/5
no shutdown

interface Ethernet1/6
no shutdown

interface Ethernet1/7
no shutdown

interface Ethernet1/8
no shutdown

interface Ethernet1/9
no shutdown

interface Ethernet1/10
no shutdown

interface Ethernet1/11
no shutdown

interface Ethernet1/12
no shutdown

interface Ethernet1/13
no shutdown

interface Ethernet1/14
no shutdown

interface Ethernet1/15
no shutdown

interface Ethernet1/16
no shutdown

interface Ethernet1/17
no shutdown

interface Ethernet1/18
no shutdown

interface Ethernet1/19
no shutdown

interface Ethernet1/20
no shutdown

interface Ethernet1/21
no shutdown

interface Ethernet1/22
no shutdown

interface Ethernet1/23
no shutdown

interface Ethernet1/24
no shutdown

interface Ethernet1/25
no shutdown
```

```
interface Ethernet1/26
 no shutdown

interface Ethernet1/27
 no shutdown

interface Ethernet1/28
 no shutdown

interface Ethernet1/29
 no shutdown

interface Ethernet1/30
 no shutdown

interface Ethernet1/31
 no shutdown

interface Ethernet1/32
 no shutdown

interface Ethernet1/33
 no shutdown

interface Ethernet1/34
 no shutdown

interface Ethernet1/35
 no shutdown

interface Ethernet1/36
 no shutdown

interface Ethernet1/37
 no shutdown

interface Ethernet1/38
 no shutdown

interface Ethernet1/39
 no shutdown

interface Ethernet1/40
 no shutdown

interface Ethernet1/41
 no shutdown

interface Ethernet1/42
 no shutdown

interface Ethernet1/43
 no shutdown

interface Ethernet1/44
 no shutdown

interface Ethernet1/45
 no shutdown

interface Ethernet1/46
 no shutdown

interface Ethernet1/47
 no lldp transmit
 spanning-tree bpdufilter enable
 mode openflow
 no shutdown

interface Ethernet1/48
 no shutdown

interface mgmt0
```

```

vrf member management
ip address 10.16.206.129/24
line console
line vty
boot kickstart bootflash:/n3500-uk9-kickstart.6.0.2.A8.0.15.bin
boot system bootflash:/n3500-uk9.6.0.2.A8.0.15.bin
openflow
switch 1
 pipeline 203
 controller ipv4 10.16.206.161 port 6653 vrf management security none
 of-port interface ethernet1/1-4
 of-port interface ethernet1/47
virtual-service ofa
activate
=====

Switch 2 Configuration : switch-2

hardware profile tcam region racl 512
hardware profile tcam region ifacl 1024 double-wide
hardware profile forwarding-mode openflow-only
hardware internal mtc-usd ttag-eth-type 0x88b5
snmp-server user admin network-admin auth md5 0xb7289bc7f348c5044b495f93bac10137 priv
0xb7289bc7f348c5044b495f93bac10137 localizedkey

vlan 1
vrf context management
ip route 0.0.0.0/0 10.16.206.1

interface Ethernet1/1
no lldp transmit
ttag
switchport mode trunk
spanning-tree bpdudfilter enable
mode openflow
no shutdown

interface Ethernet1/2
no lldp transmit
ttag
switchport mode trunk
spanning-tree bpdudfilter enable
mode openflow
no shutdown

interface Ethernet1/3
no shutdown

interface Ethernet1/4
no shutdown

interface Ethernet1/5
no shutdown

interface Ethernet1/6
no shutdown

interface Ethernet1/7
no shutdown

interface Ethernet1/8
no shutdown

interface Ethernet1/9
no shutdown

interface Ethernet1/10
no shutdown

interface Ethernet1/11
no shutdown

```

```
interface Ethernet1/12
 no shutdown

interface Ethernet1/13
 no shutdown

interface Ethernet1/14
 no shutdown

interface Ethernet1/15
 no shutdown

interface Ethernet1/16
 no shutdown

interface Ethernet1/17
 no shutdown

interface Ethernet1/18
 no shutdown

interface Ethernet1/19
 no shutdown

interface Ethernet1/20
 no shutdown

interface Ethernet1/21
 no shutdown

interface Ethernet1/22
 no shutdown

interface Ethernet1/23
 no shutdown

interface Ethernet1/24
 no shutdown

interface Ethernet1/25
 no shutdown

interface Ethernet1/26
 no shutdown

interface Ethernet1/27
 no shutdown

interface Ethernet1/28
 no shutdown

interface Ethernet1/29
 no shutdown

interface Ethernet1/30
 no shutdown

interface Ethernet1/31
 no shutdown

interface Ethernet1/32
 no shutdown

interface Ethernet1/33
 no shutdown

interface Ethernet1/34
 no shutdown

interface Ethernet1/35
 no shutdown

interface Ethernet1/36
```

```

 no shutdown

interface Ethernet1/37
 no shutdown

interface Ethernet1/38
 no shutdown

interface Ethernet1/39
 no shutdown

interface Ethernet1/40
 no shutdown

interface Ethernet1/41
 no shutdown

interface Ethernet1/42
 no shutdown

interface Ethernet1/43
 no shutdown

interface Ethernet1/44
 no shutdown

interface Ethernet1/45
 no shutdown

interface Ethernet1/46
 no shutdown

interface Ethernet1/47
 no lldp transmit
 spanning-tree bpdufilter enable
 mode openflow
 no shutdown

interface Ethernet1/48
 no shutdown

interface mgmt0
 vrf member management
 ip address 10.16.206.130/24
line console
line vty
boot kickstart bootflash:/n3500-uk9-kickstart.6.0.2.A8.0.15.bin
boot system bootflash:/n3500-uk9.6.0.2.A8.0.15.bin
openflow
 switch 1
 pipeline 203
 controller ipv4 10.16.206.154 port 6653 vrf management security none
 controller ipv4 10.16.206.161 port 6653 vrf management security none
 of-port interface ethernet1/1-2
 of-port interface ethernet1/47
virtual-service ofa
 activate

```





## Managing System

---

This chapter contains the following sections:

- [About Slices, page 95](#)
- [Adding a Slice, page 96](#)
- [Adding a Flow Specification, page 97](#)
- [About AAA Servers, page 97](#)
- [Adding an AAA Server, page 98](#)
- [Installing the TACACS+ Server, page 98](#)
- [Configuring the TACACS+ Server Required for Cisco Nexus Data Broker, page 99](#)
- [Configuring User Authentication for RADIUS Server, page 100](#)
- [Viewing Cluster Information, page 100](#)
- [Viewing the OSGi Console, page 101](#)
- [Viewing the Northbound API Content, page 101](#)
- [Downloading the System Log Files, page 102](#)
- [Downloading the System Configuration Files, page 102](#)
- [Uploading the System Configuration Files, page 102](#)
- [Scheduling Configuration Backup, page 103](#)
- [Backing Up or Restoring the Configuration, page 104](#)
- [Recovering the Administrative Password, page 104](#)
- [Uninstalling the Application Software, page 105](#)

## About Slices

The slices screen provides a way for you, as a network administrator, to partition networks into many logical networks. This feature allows you to create multiple disjoint networks and assign different roles and access

levels to each one. Each logical network can be assigned to departments, groups of individuals, or applications. Multiple disjoint networks can be managed using the Cisco Nexus Data Broker application.

The slices are created based on the following criteria:

- Network devices—The devices that can be used in the slice.  
Network devices can be shared between slices.
- Network device interfaces—The device interfaces that can be used in the slice.  
Network device interfaces can be shared between slices.
- Flow Specification—A combination of source and destination IP, protocol, and source and destination transport ports used to identify the traffic that belongs to the slice.  
Flow specifications can be assigned to different slices if the associated network devices and interfaces are disjointed.


**Note**

You can also use VLAN IDs to segregate the slice traffic.

Slices must be created by a Cisco Nexus Data Broker user with the Network Administrator role. After creation, the slices can be managed by a user with the Slice Administrator role.

Slices can overlap if each slice has at least one unique attribute. For example, a slice can share the same physical switches and ports, but be differentiated by the type of traffic it receives.

## Adding a Slice

**Step 1** Navigate to the **System** tab under **Administration** and click + **Slice**.  
The **Add Slice** window is displayed.

**Step 2** In the **Add Slice** window, complete the following fields:

| Name           | Description                                                   |
|----------------|---------------------------------------------------------------|
| Name           | The name that you want to assign to the slice.                |
| Select Devices | Select the devices that you want to associate with the slice. |

**Step 3** Click **Save**.

# Adding a Flow Specification

## Before You Begin

Create a slice before you add a flow specification.



**Note** Be default, a flow specification is bidirectional.

**Step 1** Navigate to the **System** tab under **Administration** and click + **Flow Spec** to add a flow specification for the selected slice.

**Step 2** In the **Add Flow Spec** dialog box, complete the following fields:

| Name                   | Description                                                                               |
|------------------------|-------------------------------------------------------------------------------------------|
| Name field             | The name that you want to use for the flow specification.                                 |
| VLAN field             | The VLAN ID or the range of VLAN IDs that you want to use for the flow specification.     |
| Source IP field        | The source IP address that you want to use for the flow specification.                    |
| Destination IP field   | The destination IP address that you want to use for the flow specification.               |
| Protocol field         | The IP protocol number in decimal format that you want to use for the flow specification. |
| Source Port field      | The source port that you want to use for the flow specification.                          |
| Destination Port field | The destination port that you want to use for the flow specification.                     |

**Step 3** Click **Save**.  
OR you can click **Cancel** to cancel the action.

## About AAA Servers

AAA enables the security appliance to determine who the user is (authentication), what the user can do (authorization), and what the user did (accounting). Cisco Nexus Data Broker uses Remote Authentication

Dial-In User Service (RADIUS) or Terminal Access Controller Access-Control System Plus (TACACS+) to communicate with an AAA server.

Remote authentication and authorization is supported using the AAA server. To authenticate each user, Cisco Nexus Data Broker uses both the login credentials and an attribute-value (AV) pair that assigns the authorized role for the user as part of the user administration. After successful authentication, the Cisco AV pair is returned to Cisco Nexus Data Broker for resource access authorization.

## Adding an AAA Server



### Note

When the configured AAA server(s) are not reachable, the user request is authenticated locally. If the AAA server is reachable and the user authentication fails, the user request is not authenticated locally.

**Step 1** Navigate to the **AAA** tab under **System** and click **+ Server**.  
The **Add AAA Server** window is displayed.

**Step 2** In the **Add AAA Server** window, complete the following fields:

| Name                        | Description                                                                                                                                                            |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Server Address</b> field | The IP address of the AAA server.                                                                                                                                      |
| <b>Secret</b> field         | The shared secret configured on the AAA server.                                                                                                                        |
| <b>Protocol</b> field       | Choose the protocol for the AAA server. This can be one of the following: <ul style="list-style-type: none"> <li>• <b>Radius+</b></li> <li>• <b>TACACS+</b></li> </ul> |

**Step 3** Click **Save**.

### What to Do Next

If you chose RADIUS as the protocol for the AAA server, you need to configure user authentication for RADIUS.

## Installing the TACACS+ Server

Execute the following steps to setup the TACACS+ server in Linux platform. To make the authentication to work, you need to create the user in the Linux machine and install TACAS+ server with PAM support.

Complete the following steps to install the TACACS+ server:

- 
- |               |                                                                                                                                               |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Step 1</b> | <code>sudo su</code>                                                                                                                          |
| <b>Step 2</b> | <code>apt-get update &amp;&amp; apt-get install -y gcc make flex bison libwrap0-dev</code>                                                    |
| <b>Step 3</b> | <code>apt-get install libpam-dev</code>                                                                                                       |
| <b>Step 4</b> | <code>wget ftp://ftp.shrubby.net/pub/tac_plus/tacacs+-F4.0.4.26.tar.gz &amp;&amp; tar zxvf tacacs+-F4.0.4.26.tar.gz</code>                    |
| <b>Step 5</b> | <code>cd tacacs+-F4.0.4.26</code>                                                                                                             |
| <b>Step 6</b> | <code>./configure --prefix=/usr --enable-acls --enable-uenable --enable-maxsess --enable-finger --enable-debug &amp;&amp; make install</code> |
- 

## Configuring the TACACS+ Server Required for Cisco Nexus Data Broker

Complete the following steps to configure the TACACS+ server:

### Before You Begin

- 
- |               |                                                                                                                                                                                                                                                                                                       |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Step 1</b> | Insert the line, <code>vi /etc/ld.so.conf</code> in the <code>ld.so.conf</code> file.                                                                                                                                                                                                                 |
| <b>Step 2</b> | <code>/usr/lib</code>                                                                                                                                                                                                                                                                                 |
| <b>Step 3</b> | <code>ldconfig</code>                                                                                                                                                                                                                                                                                 |
| <b>Step 4</b> | <code>mkdir /etc/tacacs</code>                                                                                                                                                                                                                                                                        |
| <b>Step 5</b> | <code>cd /etc/tacacs</code>                                                                                                                                                                                                                                                                           |
| <b>Step 6</b> | <b><code>touch tac_plus.conf</code></b><br>A sample <b><code>tac_plus.conf</code></b> file is displayed in the example. You can ignore the lines while adding it to a file. Create user in Linux machine and the password should be the same as configured in <b><code>tac_plus.conf</code></b> file. |

```

-----START-----
accounting syslog;
accounting file = /var/log/tac_plus.acct
key = "cisco123"
group = admin {
default service = permit
service = exec {
 priv-lvl = 15
 shell:roles="Network-Admin"
}
}
user = ndb {
login = ndb
member = admin
}

```

```
default authentication = file /etc/passwd
-----END-----
```

- Step 7**      **chmod 755 tac\_plus.conf**
  - Step 8**      **mkdir /var/log/tac\_plus**
  - Step 9**      **touch /var/log/tac\_plus/tac\_plus.acct**
  - Step 10**     **adduser ndb**
  - Step 11**     **tac\_plus -C /etc/tacacs/tac\_plus.conf**  
To start the TACACS+ server, use this command.
  - Step 12**     **kill -9 (Process id)**  
To stop the TACACS+ service, use this command.
- 

## Configuring User Authentication for RADIUS Server

User authorization on a RADIUS server must conform to the Cisco Attribute-Value (av-pair) format.

---

In the RADIUS server, configure the Cisco av-pair attribute for a user as follows:

```
shell:roles="Network-Admin Slice-Admin"
```

**Note**      This is applicable for both RADIUS and TACACS servers.

---

## Viewing Cluster Information

---

Navigate to the **Cluster** tab under **System** to view information about the clusters.

The cluster management dialog boxes are read-only. The dialog box lists the IP addresses of all of the Cisco Nexus Data Broker instances in the cluster.

**Note**      For the backup and upload features to work properly, all the servers in the cluster should be stopped and then they should be restarted. You should not configure any functionality during this time. Once the upload configuration is done, you should not configure anything from any other nodes in the cluster as it might lead to few inconsistencies in the data.

---

## Viewing the OSGi Console

You can view all of Cisco Nexus Data Broker bundles that comprise the application by viewing the OSGi Web Console.

**Note**

This procedure does not provide a step-by-step guide to everything you can do in the OSGi Web Console for **Cisco XNC Bundles** list. It guides you in opening the OSGi Web Console and viewing bundle information.

- 
- Step 1** Navigate to the **System** tab under **Administration**.  
A new browser tab opens.
- Step 2** Click **OSGI**.
- Step 3** Enter your username and password, and then press **Enter**.  
The **Cisco – XNC Bundles** list is displayed. In this page you can view all of the active packages, filter on the package name to specify bundle names, and complete other tasks.
- Step 4** When you are finished viewing the list, close the **Cisco – XNC Bundles** browser tab.
- 

## Viewing the Northbound API Content

You can view all of Cisco Nexus Data Broker northbound API content for the application by opening a browser tab using the **Northbound API** tool (book icon) in the menu bar.

- 
- Step 1** From the menu bar, click the **Northbound API** button.  
A new browser tab (Swagger UI) is opened and the complete list of northbound API content used in Cisco Nexus Data Broker is displayed.
- From this tab, you can do the following:
- Show or hide the operations for an API.
  - List the operations for an API.
  - Expand the operations for an API.
- Step 2** When you are finished viewing northbound API content, close the browser tab.
-

## Downloading the System Log Files

You can download log files for Cisco Nexus Data Broker to use for analysis. Log files are saved as a .zip archive.

- 
- Step 1** Navigate to the **System** tab under **Administration**.
- Step 2** Click **Download Logs**.  
A dialog box opens in the browser prompting you to either open or save the .zip file.
- Step 3** Do one of the following:
- Save the archive to a location of your choosing, for example, `home/ndbconfig`.
  - Open the archive to view the contents, and then save it.
- 

## Downloading the System Configuration Files

You can download the system configuration files for Cisco Nexus Data Broker to save them in case you need to restore the system after an upgrade or other change. System configuration files are saved in a zipped archive.

- 
- Step 1** Navigate to the **System** tab under **Administration**.
- Step 2** Click **Download Configuration**.  
A dialog box opens in the browser prompting you to either open or save the file.
- Step 3** Do one of the following:
- Save the archive to a location of your choosing, for example, `home/ndbconfig`.
  - Open the archive to view the contents, and then save it.
- 

## Uploading the System Configuration Files

You can upload the saved system configuration files for Cisco Nexus Data Broker to restore the Cisco Nexus Data Broker application in the case of a failure or other event. After restoring your configuration, you will need to restart Cisco Nexus Data Broker.

Direct upload path to Cisco Nexus Data Broker, Release 3.2 is available from Cisco Nexus Data Broker, Release 3.0 or above. If you are running a previous release, upload it to Release 3.0 first before uploading to Release 3.2.



### Before You Begin

You must download the system configuration files and save them in a zipped archive.

- 
- Step 1** Navigate to the **System** tab under **Administration** and click **Upload Configuration**.
  - Step 2** Navigate to the location of the file `configuration_startup.zip`.
  - Step 3** Click on the archive file.  
The system configuration is uploaded and the browser displays a message informing you that you need to restart the server.
  - Step 4** Restart the server, and then log back in to the Cisco Nexus Data Broker GUI.
- 

## Scheduling Configuration Backup

Beginning with Cisco Nexus Data Broker, Release 3.2, you can schedule automatic configuration backup with a start date and an end date. The backup is saved at a server location that is set with the variable **scheduler.backup.path=/home** in **config.ini** file with default value as **/home**. When any configuration is performed in Cisco Nexus Data Broker, it can be saved automatically.

**Note**

Beginning with Cisco Nexus Data Broker, Release 3.2, you do not need to use the **Save** option to save the Cisco Nexus Data Broker configurations. Even after you restart the server, the configuration is autosaved.

### Before You Begin

- 
- Step 1** Navigate to **Administration -> System -> Configuration** and click **Schedule**.
  - Step 2** Click **Start Date** and **End Date**.
  - Step 3** (Optional) Or you can select **No End Date**.
  - Step 4** Choose the start time of the backup using the **Start Time** field in the AM/PM format.
  - Step 5** Choose the pattern as **Daily**, **Weekly**, or **Monthly**.
  - Step 6** Choose the days of the week for the scheduled backup.
  - Step 7** Click **Enable**.
  - Step 8** Click **Apply**.
- 

After you click **Enable** and click **Apply**, your scheduled backup starts. If you do not click **Enable** but only click **Apply**, the values are saved. The scheduled backup is triggered only after clicking **Enable** and then clicking **Apply**. The scheduled backup is saved and it is displayed under the **Recovery** tab as per the scheduled backup time.

The information for the scheduled backup is displayed using the following columns: **Item** (scheduled backup date and time), **Backup Status**, **Description**, **Restore Triggers**, and **Action**. If you click **Restore** under **Action**, the configuration that is present at the scheduled backup time is restored.

You can search for a particular backup that is taken on a particular start date by adding a date in the **Filter by** field.

### What to Do Next

## Backing Up or Restoring the Configuration

The backup and restore commands allow you to back up your Cisco Nexus Data Broker configurations and restore them.

- 
- Step 1** Open a command window where you installed Cisco Nexus Data Broker.
  - Step 2** Navigate to the `xnc/bin` directory that was created when you installed the software.
  - Step 3** Back up the configuration by entering the `./xnc config --backup` command.  
The `--backup` option creates a backup archive (in .zip format) of the startup configuration in the current `xnc` distribution. The backup archive is stored in `{xncHome}/backup/`. A new archive is created each time that the backup command is entered using a filename with the current timestamp.
  - Step 4** Restore the configuration by entering the `./xnc config --restore --backupfile {zip_filename}` command.  
The `--restore` option restores the startup configuration of the current `xnc` distribution from an existing backup archive. The restore action requires the absolute path of the backup archive.
  - Step 5** If you are restoring a configuration, stop and restart Cisco Nexus Data Broker for the restored configuration to take effect.
- 

## Recovering the Administrative Password

The Cisco Nexus Data Broker network administrator user can return the administrative password to the factory default.



### Note

The software may or may not be running when this command is used. If the software is not running, the password reset takes effect the next time that it is run.

- 
- Step 1** Open a command window where you installed Cisco Nexus Data Broker.
  - Step 2** Navigate to the `xnc/bin` directory that was created when you installed the software.
  - Step 3** Reset the administrative password by entering the `./xnc reset-admin-password [--wait-seconds {wait_time}] --password {password}` command.  
Resets the admin password to the default or specified password by restarting the user manager.

- The **wait-seconds** is the length of time, in seconds, to wait for the user manager to restart. The minimum is 5 seconds and the maximum is 60 seconds.
- The **password** is the administrative password.

- Note**
- The password must be from 8 to 256 characters, contain both uppercase and lowercase characters, and have at least one number and one non-alphanumeric character.
  - If you leave the password blank, it is reset to the factory default of "admin".
  - Each time that you reset the administrative password, make sure that the new password meets these requirements or you will not be able to log in to Cisco Nexus Data Broker.
- 

## Uninstalling the Application Software

### Before You Begin

Ensure that your Cisco Nexus Data Broker application is stopped before proceeding.

- 
- Step 1**      Navigate to the directory where you created the Cisco Nexus Data Broker installation.  
For example, if you installed the software in `Home/CiscoNDB`, navigate to the `Home` directory.
- Step 2**      Delete the `CiscoNDB` directory.
-

