



CHAPTER 2

APPLY Commands

This chapter provides apply (APPLY) commands for the Cisco ONS 15454 SDH, Cisco ONS 15454 M2, and Cisco ONS 15454 M6.



Note

All commands supported on the Cisco ONS 15454 SDH platform are also supported on Cisco ONS 15454 M2 and Cisco ONS 15454 M6 platforms.

2.1 APPLY

(Cisco ONS 15454 SDH) The Apply (APPLY) command activates or reverts a software load during a software upgrade or downgrade process.

Usage Guidelines

An error will be generated if you attempt to activate an older software load or attempt to revert to a newer software load.

Category

File Transfer

Security

Superuser

Input Format

APPLY:[<TID>]::<CTAG>[::<MEM_SW_TYPE>];

Input Example

APPLY:CISCO::123::ACT;

Table 2-1 *APPLY Commands - Parameter Support*

Input Parameters	Description
<MEM_SW_TYPE>	(Optional) Memory switch action during the software upgrade. The parameter type is DL_TYPE, which indicates the software download type. The default value is ACT.
<ul style="list-style-type: none">• ACPT	Activates to a newer software load on the active controller card and resets the active card.
<ul style="list-style-type: none">• CANC	Cancels the software download.
<ul style="list-style-type: none">• RVRT	Reverts to an older software load during software download.
<ul style="list-style-type: none">• ACT	Activates to a new software load.