



Wrapper

- [create vnic, on page 2](#)

create vnic

QA Test Sprint 9 CSCta77961: Test that each Command appears in its own page.

karthik has inserted part of sprint6-round1 build

karthik added this to check wan bridge issue in sprint12

To create a VNIC (Virtual Network Interface Card), use the **create vnic** command.

```
create vnic name {fabric {a | a-b | b | b-a} | eth-if eth-if} *
```

Syntax Description

<i>name</i>	VNIC template name. The range of valid values is 1 to 16.
<i>fabric</i>	Specifies the fabric switch identification number.
<i>a</i>	Specifies switch A.
<i>a-b</i>	Specifies redundant, with switch A as primary.
<i>b</i>	Specifies switch B.
<i>b-a</i>	Specifies redundant, with switch B as primary.
<i>eth-if</i>	Specifies a Ethernet interface.
<i>eth-if</i>	Ethernet interface name. The range of valid values is 1 to 16.

Command Default

None

Command Modes

Service profile (/org/service-profile)

Command History

Release	Modification
1.0(1)	This command was introduced.

Usage Guidelines

Use this command to create a vNIC with the specified name, and enters organization virtual NIC mode.

Examples

This example shows how to create a vNIC:

```
switch-A# scope org org3
switch-A /org # scope service-profile spl
switch-A /org/service-profile # create vnic vnic110
switch-A /org/service-profile/vnic* # commit-buffer
switch-A /org/service-profile/vnic #
```

Related Commands

QA Test: CSCtd06182 Check that the shortdescriptions appear on the dfescription column below. Also click on the first cross chapter link and see that it works in html and pdf chapters

Command	Description
create vsan-Sathish	This is short description for vsan command
create vnic-egress-policy	This is short dfescription for create vnic-egress-policy command

