



# Configure a Network

**Table 1: Feature History**

Feature Name	Release Information	Feature Description
MOLS 2.0 Support	Cisco ONP Release 25.1.1	<p>CONP now supports the latest Metro DCI Open Line System, MOLS 2.0, which is hosted on the NCS 1014 chassis. This includes support for:</p> <ul style="list-style-type: none"> <li>• new EDFA amplifier that hosts               <ul style="list-style-type: none"> <li>• a new OTDR pluggable (ONS-QSFP-OTDR),</li> <li>• a new coherent probe pluggable (DP01QSDD-ZT5-A1), and</li> <li>• an existing OSC pluggable (ONS-SC-PTP-1510), and</li> </ul> </li> <li>• a pair of new 32-channel colored add/drop passive modules               <ul style="list-style-type: none"> <li>• NCS1K-MD-32O-CE</li> <li>• NCS1K-MD-32E-CE</li> </ul> </li> </ul> <p>Select the NCS 1014 platform during network creation to create MOLS 2.0 networks. You can design the new MOLS 2.0 networks through the properties.</p> <ul style="list-style-type: none"> <li>• Probe Channel and OTDR Pluggable at the network level,</li> <li>• OSC Pluggable property at the edge level,</li> <li>• the MOLS 2.0 colored add/drop modules (default option is odd + even cards) at add/drop level, and</li> <li>• noneditable Pre Amp, Pre PSD, Second Booster, Second Booster PSD at the C-band amplifier level.</li> </ul>

Feature Name	Release Information	Feature Description
Transponder Aggregation Service	Cisco ONP Release 25.1.1	<p>This release introduces the transponder aggregation service, which provides comprehensive support for transponder service aggregation across NCS 1000 line cards on all L0 platforms. Key features include:</p> <ul style="list-style-type: none"> <li>• Support for transponder service creation and network-wide analysis, considering transponder services in both greenfield and brownfield deployments.</li> <li>• Compatibility with NCS 2000, NCS 1001, NCS 1010, and NCS 1014 platforms, with specific add/drop support for each platform.</li> <li>• Force update the transponder properties, with support for service control, property override, and UI configurations.</li> <li>• Update Optical, Traffic, BOM, Installation Parameters, and Cabling Reports to include transponder parameters.</li> <li>• Placement of transponder cards in NCS1004 and NCS1014 chassis, with NFV view including Transponder connections.</li> <li>• Draw services between ROADM/Terminal/Traffic sites, force transponder properties, and view updated BOM and reports after network analysis.</li> </ul>

This chapter describes the various ways of configuring the network designed through Cisco ONP.

- [Configure an NCS 2000 network for contentionless functionality, on page 2](#)
- [Configure an NCS 2000 network for colorless functionality, on page 3](#)
- [Configure an NCS 2000 network for colored functionality, on page 4](#)
- [Configure a network with mixed Add/Drop multiplexers and demultiplexers, on page 5](#)
- [Configure an NCS 1010 network for colorless functionality, on page 10](#)
- [Configure an NCS 1010 network for colored functionality, on page 11](#)
- [Configure an NCS 1010 network with mixed add/drop multiplexers and demultiplexers, on page 12](#)
- [Configure an NCS 1010 C+L-Band network with mixed Add/Drop multiplexers and demultiplexers, on page 12](#)
- [Configure an NCS 1010 network for Omnidirectional functionality, on page 13](#)
- [Configure an NCS 1001 network for colored functionality, on page 13](#)
- [Configure an NCS 1014 network for colored functionality, on page 14](#)
- [Configure an NCS 1001/1010/1014 network with NCS 1000 transponders, on page 15](#)
- [Configure an NCS 2000 network with NCS 1000 transponders, on page 16](#)

## Configure an NCS 2000 network for contentionless functionality

Use this procedure to configure contentionless functionality in a network.

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

## Procedure

---

- Step 1** Create a network design. See [#unique\\_227](#).
- Step 2** Add contentionless sides to the required sites. See [Add contentionless side to a site](#).
- Step 3** Set the channel type for the demands:
- In the **Entity Editor** window, click the **Services** tab.
  - Click the service connecting the site and set the **Src Channel Type** property as *Auto* or *Contentionless*. Then, click the trail under the wave (for non-SSON) or Media Channel (for SSON) and set the **Src Channel Type** property to *Auto* or *Contentionless*.
- Note**  
Contentionless is the default option when you select *Auto*.
- Click **Update**.
- Step 4** Analyze the network by choosing **Network > Analyze**.
- 

# Configure an NCS 2000 network for colorless functionality

This procedure guides you through the process of configuring colorless functionality in an NCS 2000 optical network.

## Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

## Procedure

---

- Step 1** Create a network design. See [#unique\\_227](#).
- Step 2** Set the channel type for the demands:
- In the **Entity Editor** window, click the **Services** tab.
  - Click the service connecting the site. Set the **Src Channel Type** property as *Colorless*. For non-SSON click the trail under the wave. For SSON, click the Media Channel (for SSON). Set the **Src Channel Type** property as *Colorless*.
  - Under the **Site > Side** properties, choose the Line type side from which you want to create the colorless demand, and enter the number of **Colorless Ports**.
- From Release 24.3.1, you can select the colorless ports for the SMR-9 card.
- The number of colorless ports for MF-6AD-CFS depends on the **Scalable Upto Degree** property. See [Colorless ports for SSON and Non-SSON networks, on page 4](#).
- Click **Update**.
- Step 3** Under the **C-Band** properties, choose *MF-6AD-CFS* or *Direct SMR* as the **Colorless Add/Drop**.
- Step 4** Click **Update**.
- Step 5** Analyze the network by choosing **Network > Analyze**.

You can see the colorless Add/Drop unit getting added in the layout and BOM.

## Colorless ports for SSON and Non-SSON networks

This table explains the maximum number of colorless ports that can be added based on the **Scalable Upto Degree** property for the MF-6AD-CFS card.

*Table 2: Colorless ports for SSON and Non-SSON networks*

Site type	Scalable upto degree	Maximum number of colorless ports for SSON	Maximum number of colorless ports for non-SSON
SMR-20	4	72	72
SMR-20	8	72	72
SMR-20	12	24	24
SMR-20	16	24	24
SMR-20	Line	96	96
SMR-20	Terminal	120	96

### Configure an NCS 2000 network for colorless functionality

## Configure an NCS 2000 network for colored functionality

This procedure guides you through the process of configuring colored functionality in an NCS 2000 optical network.

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

### Procedure

- Step 1** Create a network design. See [#unique\\_227](#) .
- Step 2** Set the channel type for the demands:
- In the **Entity Editor** window, click the **Services** tab.
  - Click the service connecting the site and set the **Src Channel Type** property as **Colored**. For non-SSON click the trail under the wave. For SSON, click the Media Channel (for SSON). Set the **Src Channel Type** property as **Colored**.
  - Click **Update**.
- Step 3** For an SSON network, complete these steps.
- Under the **C-Band** properties, choose **MD-64-C** as the **Colored Add/Drop**.

### Note

MD-64-C is supported from NCS 2000 Release 12.x.

b) Click **Update**.

By default, the system adds **MD-48-ODD** or **MD-48-EVEN** as the **Colored Add/Drop** when **Share SMR Port** is not enabled.

**Note**

If you choose **MD-48-EVEN** or **MD-48-ODD**, select an even wavelength for the **Wavelength** property under **Trail**.

**Step 4** When **Share SMR Port** port is enabled, you can select the **Colored Add/Drop** by using these steps:

a) Under the **C-Band** properties, choose **MD-48-ODD**, **MD-48-EVEN**, or **MD-48-ODD+MD-48-EVEN** as the **Colored Add/Drop**.

**Note**

These Add/Drop units are supported from NCS 2000 Release 11.x.

b) Click **Update**.

**Step 5** Analyze the network by choosing **Network > Analyze**.

The colored Add/Drop unit appears in the layout and BOM.

---

## Configure a network with mixed Add/Drop multiplexers and demultiplexers

Use the following procedure to configure mixed wavelengths in a network:

**Before you begin**

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

Table 3: Feature History

Feature Name	Release Information	Feature Description
Support for Mixed Add/Drop Configuration	Cisco ONP Release 4.2	<p>You can configure different functionalities in the network created in Cisco ONP. Mixed wavelengths such as colorless and contentionless, colored and contentionless, can be added/dropped on the same side or direction. The following mixed configurations are supported:</p> <ul style="list-style-type: none"> <li>• Colored (MD-48-ODD/MD-48-EVEN) and Contentionless (16-AD-CCOFS) without shared SMR port</li> <li>• Colored and Contentionless (MD-64-C and 16-AD-CCOFS)</li> <li>• Colored (MD-64-C) and Colorless (Direct SMR)</li> <li>• Colored (MD-48) and Contentionless (16-AD-CCOFS) with Shared SMR Port</li> <li>• Colorless and MD-48-ODD/MD-48-EVEN</li> <li>• Colorless and 16-AD-CCOFS</li> </ul>

### Procedure

---

**Step 1** Create a network design. See [#unique\\_227](#).

**Step 2** Set the properties of the network under the **Entity Editor** for different combinations of the functionalities, as described in [Supported and unsupported mixed configurations, on page 6](#).

**Note**

You cannot mix the MF-6AD-CFS colorless configuration with any other configuration.

---

## Supported and unsupported mixed configurations

This section describes the list of mixed configurations that are supported and unsupported by Cisco ONP.

Table 4: Supported mixed Configurations

Supported network type	Possible mixed configurations	Properties to be set
Non-SSON	Colored (MD-48-ODD/MD-48-EVEN) and Contentionless (16-AD-CCOFS) without shared SMR port	<ul style="list-style-type: none"> <li>• Add required number of contentionless sides.</li> <li>• <b>Channel Type</b>—Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Colored</b> for one wave. Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Contentionless</b> for the second wave created on the same site. Both wavelengths must add/drop in the same side or direction.</li> <li>• By default, MD-48-ODD or MD_48-EVEN is added as the Colored Add/Drop in the BOM and layout when you set the <b>Channel Type</b> as <b>Colored</b> and when <b>Shared SMR Port</b> is disabled.  By default, 16-AD-CCOFS is added in the BOM and layout when you set the <b>Channel Type</b> as <b>Contentionless</b>.</li> </ul>
SSON	Colored and Contentionless (MD-64-C and 16-AD-CCOFS)	<ul style="list-style-type: none"> <li>• Add required number of contentionless sides.</li> <li>• <b>Channel Type</b>—Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Colored</b> for one media channel. Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Contentionless</b> for the second media channel created on the same site. Both channels must add/drop in the same side or direction.</li> <li>• <b>Colored Add/Drop</b>—MD-64-C under the side.</li> </ul>

Supported network type	Possible mixed configurations	Properties to be set
SSON	Colored (MD-64-C) and Colorless (Direct SMR)	<ul style="list-style-type: none"> <li>• <b>Channel Type</b>—Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Colored</b> for one media channel. Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Colorless</b> for the second media channel created on the same site. Both channels must add/drop in the same side or direction.</li> <li>• Enter the number of <b>Colorless Ports</b> under the <b>Line Side</b> properties.</li> <li>• <b>Colored Add/Drop</b>—MD-64-C <b>Colorless Add/Drop</b>—Direct SMR</li> </ul>
Non-SSON	Colored (MD-48) and Contentionless (16-AD-CCOFS) with Shared SMR Port	<ul style="list-style-type: none"> <li>• Add required number of contentionless sides.</li> <li>• <b>Channel Type</b>—Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Colored</b> for one wave. Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Contentionless</b> for the second wave created on the same site. Both wavelengths must add/drop in the same side or direction.</li> <li>• Check the <b>Shared SMR Port</b> check box, under the <b>Site</b> properties.</li> <li>• <b>Colored Add/Drop</b>—MD-48-ODD, MD-48-EVEN, or MD-48-ODD and MD-48-EVEN</li> <li>• If you choose <b>MD-48-EVEN</b>, make sure to select an even wavelength for the <b>Wavelength</b> property under <b>Trail</b>.</li> </ul>

Supported network type	Possible mixed configurations	Properties to be set
Non-SSON	Colorless and MD-48-ODD/MD-48-EVEN	<ul style="list-style-type: none"> <li>• <b>Channel Type</b>—Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Colorless</b> for the wave.</li> <li>• Enter the number of <b>Colorless Ports</b> under the <b>Line Side</b> properties.</li> <li>•</li> <li>•</li> <li>• By default, MD-48-ODD/MD-48-EVEN is added as colored Add/Drop in the BOM and layout, when any colored demand is added in the non-SSON network.</li> </ul>
SSON	Colorless and Contentionless (16-AD-CCOFS)	<ul style="list-style-type: none"> <li>• Add required number of contentionless sides.</li> <li>• <b>Channel Type</b>—Set the <b>Src Channel Type</b> and <b>Dst Channel Type</b> to be <b>Colorless</b> for the wave or media channel.</li> <li>• <b>Channel Type</b>—<b>Colorless</b> for one wave and <b>Contentionless</b> for another wave created on the same site. Both wavelengths must add/drop in the same side or direction.</li> </ul>

**Table 5: Unsupported mixed configurations**

Network type	Mixed configurations
SSON	Colored (MD-64-C) and Colorless (MF-6AD-CFS)
SSON	Contentionless and Colorless (MF-6AD-CFS)
SSON	Colored (MD-64-C), Contentionless, and Colorless (MF-6AD-CFS)
SSON	Colored (MD-64-C) and Layer-2 Contentionless
Non-SSON	Contentionless and Colorless (MF-6AD-CFS)
Non-SSON	Colored (MD-48) and Colorless (MF-6AD-CFS)
Non-SSON	Colorless (Direct SMR) and Colorless (MF-6AD-CFS)
Non-SSON	Colored, Contentionless, and Colorless (MF-6AD-CFS)



---

**Note** Different Add/drop functionalities (Colored, Colorless, or Contentionless) at Source and Destination is not supported.

---

## Configure an NCS 1010 network for colorless functionality

Use this procedure to configure the colorless functionality in an NCS 1010 network.

### Before you begin

Log in to the [Cisco ONP web interface](#) as a user with the admin role.

### Procedure

---

**Step 1** Create a network design. See [#unique\\_227](#).

**Step 2** Set the channel type for the demands.

- a) In the **Entity Editor** window, click the **Services** tab.
- b) Click the trail under the circuit, set the **Src Channel Type** property to *Colorless*.
- c) Click **Update**.

**Step 3** Under the **C-Band** properties, choose *BRK-8*, *BRK-16*, or *BRK-24* as the **Colorless Add/Drop**.

The Maximum number of colorless ports depends on the scalable upto degree. See [Colorless ports for NCS 1010 networks, on page 10](#).

#### Note

Colorless configuration is not supported for scalable upto degree 31.

#### Note

NCS1K14-CCMD-16 add/drop is not supported with OLT standard faceplate.

Enhanced OLT add/drop ports *AD-2* and *AD-3* are not used for Direct LC (Direct Optical Source or Transponder) connection. MD-32-ODD connects to *AD-2* and MD-32-EVEN connects to *AD-3* ports.

**Step 4** Click **Update**.

**Step 5** Analyze the network by choosing **Network > Analyze**.

The colorless Add/Drop unit is added in the layout and BOM.

---

## Colorless ports for NCS 1010 networks

This section describes the maximum number of colorless ports based on the scalable up to degree.

Table 6: Colorless ports for NCS 1010 networks

Scalable upto degree	MPO port used for degree interconnect	Maximum number of colorless ports supported		
		BRK-24	BRK-16	BRK-8
7	4	72	48	24
9	1	66	44	22
15	3, 4	48	32	16
17	1, 2	42	28	14
23	2, 3, 4	24	16	8
25	1, 2, 3	18	12	6
31	1, 2, 3, 4	0	0	0
Terminal	NA	90	60	30
Line	4	72	48	24

## Configure an NCS 1010 network for colored functionality

Use this procedure to configure the colored functionality in an NCS 1010 network.

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

### Procedure

- 
- Step 1** Create a network design. See [#unique\\_227](#).
- Step 2** Set the channel type for the demands:
- In the **Entity Editor** window, click the **Services** tab.
  - Click the trail under the circuit and set the **Src Channel Type** property as *Colored*.
  - Click **Update**.
- Step 3** Under the **C-Band** properties, choose *MD-32-EVEN*, *MD-32-ODD*, or *MD-32- ODD+MD-32-EVEN* as the **Colored Add/Drop**.
- Step 4** Click **Update**.
- Step 5** Analyze the network by choosing **Network > Analyze**.
- The colored Add/Drop unit appears in the layout and the BOM.
-

## Configure an NCS 1010 network with mixed add/drop multiplexers and demultiplexers

Use this procedure to configure mixed wavelengths in an NCS 1010 network:

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

### Procedure

---

**Step 1** Create a network design. See [#unique\\_227](#).

**Step 2** Set the properties under the **Entity Editor** for different combinations of the functionalities.

For example, set the source **Add/Drop Type** and destination **Add/Drop Type** to *Colored* for one circuit. Set the **Src Channel Type** and **Dst Channel Type** to *Colorless* for the second circuit created on the same site. Both channels must add or drop in the same side or direction.

You can select any combination of colored or colorless add/drop channels.

### Note

When the **Scalable Upto Degree** is 31, you cannot use the colorless configuration. Therefore, you cannot use mixed configuration when **Scalable Upto Degree** is set to 31.

---

## Configure an NCS 1010 C+L-Band network with mixed Add/Drop multiplexers and demultiplexers

Use this procedure to configure mixed wavelengths in an NCS 1010 C+L-Band network:

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

### Procedure

---

**Step 1** Create a network design. See [#unique\\_227](#).

**Step 2** Set the properties under the **Entity Editor** for different combinations of the functionalities.

For example, set the source **Add/Drop Type** and destination **Add/Drop Type** to **Colored** or **Colorless** for the C-band circuit. Set **Band Type** to **L-band** for the second circuit that is created on the same site. Both channels must add/drop on the same side or in the same direction.

You can choose any combination of colored or colorless add/drop for C-band circuits. However, for L-band circuits, colorless add/drop is the default value.

### Note

When **Scalable Upto Degree** is 31, only C-band colored configuration is supported. You cannot create colorless if all colorless ports are exhausted, so a mixed configuration is not supported for **Scalable Upto Degree** 31.

---

## Configure an NCS 1010 network for Omnidirectional functionality

Use this procedure to configure colored and colorless omnidirectional functionalities in an NCS 1010 network:

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

### Procedure

---

- Step 1** Create a network design. See [#unique\\_227](#).
- Step 2** Add Omnidirectional sides to the required sites. See [Add omni-directional sides to a site](#). You can also use the **Max Auto Omni Allowed** property under the network properties. When you enter a number, Cisco ONP automatically generates the same number of Omni Edges and runs the analysis.
- Step 3** Select the Omni variant and type of omnidirectional add/drop stage.
- In the **Entity Editor** window, click the **Sites** tab.
  - Choose the omnidirectional side under the required site, and set these properties.  
**Omni Variant:** Select the type of omni variant as **Dual OLT** or **4x4 COFS**. The available options are:  
**Omni Directional Ports:** Enter the number of omnidirectional ports.
- Step 4** Select the type of omnidirectional add/drop stage.
- In the **Entity Editor** window, click the **Services** tab.
  - Choose the required service and set the **Src Add/Drop Type** and **Dst Add/Drop Type** as *omni-colored* or *omni-colorless*.
  - Choose the trail under the service, and set the **Add/Drop Type** as *omni-colored* or *omni-colorless*.
- Step 5** Click **Update**.
- Step 6** Analyze the network by choosing **Network > Analyze**.  
You can see the Omni Add/Drop unit getting added in the layout and BOM.
- 

## Configure an NCS 1001 network for colored functionality

This procedure guides you through the process of configuring colored functionality in an NCS 1001 optical network.

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.



---

**Note** Deployment of more than two OLA nodes between two Terminal Sites is not supported.

---

### Procedure

---

- Step 1** Create a network design. See [#unique\\_227](#) .
- Step 2** Set the channel type for the demands:
- In the **Entity Editor** window, click the **Services** tab.
  - Click the trail under the circuit and set the **Src Add/Drop Type** property as *Colored*.
  - Click **Update**.
- Step 3** Under the **C-Band** properties, choose *MD-32-EVEN*, *FLD-4*, *MD-48-ODD*, *MD-48-EVEN*, *MD-48-ODD+MD-48-EVEN*, or *MD-64* as the **Colored Add/Drop**.
- Step 4** Click **Update**.
- Step 5** Analyze the network by choosing **Network > Analyze**.
- The layout and BOM display the added colored Add/Drop unit.
- 

## Configure an NCS 1014 network for colored functionality

Use this procedure to configure colored functionality in an NCS 1014 optical network.

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.



---

**Note** Deployment of more than two OLA nodes between two terminal sites is not supported.

---

### Procedure

---

- Step 1** Create a network design. See [#unique\\_227](#) .
- Step 2** Set the channel type for each demand:
- In the **Entity Editor** window, click the **Services** tab.
  - Click the trail under the circuit and set the **Src Add/Drop Type** property as *Colored*.
  - Click **Update**.
- Step 3** Under the **C-Band** properties, select *MD-32-EVEN*, *MD-32-ODD*, or *MD-32- ODD+MD-32-EVEN* as the **Colored Add/Drop**.
- Step 4** Click **Update**.
- Step 5** Analyze the network by choosing **Network > Analyze**.

The colored Add/Drop unit is added in the layout and BOM.

## Configure an NCS 1001/1010/1014 network with NCS 1000 transponders

Use this procedure to add NCS 1000 transponders to an NCS 1001, NCS 1010, or NCS 1014 optical network.



**Note** NCS 1000 transponders with colored add/drop functionality do not support all trunk and baud rate combination.

### Before you begin

Log in to the [Cisco ONP web interface](#) as a user with the admin role.

### Procedure

**Step 1** Create a network design. See [#unique\\_227](#).

**Step 2** Set the TXP Chassis and Card type for the transponders.

- a) In the **Entity Editor** window, click the **Service** tab.
- b) At the service level, set the **Client Type**.
- c) Select the **Band Type**.
- d) At the circuit or media channel level, set **Traffic Type** as **Transponder Card**.  
At the trail level, **Card Type** and **TXP Chassis** properties appear.
- e) Click the trail under the sections, and then set the **TXP Chassis** and **Card Type** properties.
- f) Click the service and set the **TXP Chassis** and **Card Type** properties.

Refer to this table for the required chassis and card type.

**Table 7: Supported transponders**

TXP Chassis	Card Type
NCS 1014	<ul style="list-style-type: none"> <li>• <b>Auto</b></li> <li>• <b>NCS1K14-2.4T-K9</b></li> <li>• <b>NCS1K14-2.4T-X-K9</b></li> <li>• <b>NCS1K4-QXP-K9</b></li> <li>• <b>NCS1K14-1.2T-K9</b></li> <li>• <b>NCS1K14-2.4T-A-K9</b></li> <li>• <b>NCS1K42-QDD-C-K9</b></li> </ul>

TXP Chassis	Card Type
NCS 1004	<ul style="list-style-type: none"> <li>• Auto</li> <li>• NCS1K4-QXP-K9</li> <li>• NCS1K4-OTN-XP</li> <li>• NCS1K14-1.2T-K9</li> <li>• NCS1K42-QDD-C-K9</li> </ul>

- g) Set the relevant properties. See [Supported transponders and their trunk modes](#).  
h) Click **Update**.

- Step 3** Under the **C-Band** properties, select the required multiplexer and demultiplexer.  
**Step 4** Click **Update**.  
**Step 5** Analyze the network by choosing **Network > Analyze**.

## Configure an NCS 2000 network with NCS 1000 transponders

Use this procedure to add NCS 1000 transponders to an NCS 2000 optical network.

### Before you begin

[Log in to the Cisco ONP web interface](#) as a user with the admin role.

### Procedure

- Step 1** Create a network design. See [#unique\\_227](#).
- Enable the **SSON Network** check box and choose **Traffic type** as **NCS (4K\_1K\_2K)**.
  - In the design palette, use the drawing tool to add traffic sites to the network.
- Step 2** Set Traffic Site and Traffic Type.
- In the **Entity Editor** window, click the **Site** tab and expand the sites.
  - Select a site.  
On the right pane, the **General** tab opens.
  - Under the **General** tab, set **Type** as **Traffic** and **Traffic Type** as **1K-2K**.
- Step 3** Set the TXP Chassis and Card type for the transponders.
- In the **Entity Editor** window, click the **Service** tab.
  - At the circuit or media channel level, set **Traffic Type** as **Transponder Card**.  
At the trail level, **Card Type** and **TXP Chassis** properties appear.
  - Click the trail under the sections, and then set the **TXP Chassis** and **Card Type** properties.
  - Click the service and set the **TXP Chassis** and **Card Type** properties.
- Select the required chassis and card type as mentioned in this table.

**Table 8: Supported transponders**

<b>TXP Chassis</b>	<b>Card Type</b>
NCS 1014	<ul style="list-style-type: none"><li>• Auto</li><li>• NCS1K14-1.2T-K9</li><li>• NCS1K14-24T-A-K9</li><li>• NCS1K42QDD-C-K9</li><li>• NCS1K14-2.4T-K9</li><li>• NCS1K14-24T-X-K9</li><li>• NCS1K4-QXP-K9</li></ul>
NCS 1004	<ul style="list-style-type: none"><li>• Auto</li><li>• NCS1K4-QXP-K9</li><li>• NCS1K4-OTN-K9</li><li>• NCS1K14-1.2T-K9</li><li>• NCS1K42QDD-C-K9</li></ul>

e) Click **Update**.

**Step 4** Under the **C-Band** properties, choose the required multiplexer and demultiplexer.

**Step 5** Click **Update**.

**Step 6** Analyze the network by choosing **Network > Analyze**.

---

