# Performance Monitoring

Performance monitoring (PM) parameters are used by service providers to gather, store, set thresholds for, and report performance data for early detection of network issues. You can configure and retrieve PM counters for the various controllers in 30-second, 15-minute, or 24-hour intervals. These parameters simplify troubleshooting operations and enhance data that can be collected directly from the equipment.


- Configuring PM Parameters, on page 1


# Configuring PM Parameters

You can configure and view the performance monitoring parameters for the Optics, Ethernet, and coherent DSP controllers.

To configure PM parameters, use the following commands.

**configure**

**controller** *controllertype R/S/I/P* { **pm** { **15-min** | **30-sec** | **24-hour** } { **optics** | **ether** | **pcs** | **fec** | **otn**} { **report** | **threshold** } *value* }

**commit**

### Examples

The following is a sample in which the performance monitoring parameters of the Optics controller are configured at 24-hour intervals.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#controller optics 0/0/1/5 pm 24-hour optics threshold osnr max
345
RP/0/RP0/CPU0:ios(config)#commit
```

The following is a sample in which the performance monitoring parameters of the Ethernet controller are configured at 15-minute intervals.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#controller HundredGigECtrlr 0/3/0/0 pm 15-min pcs report bip
enable
RP/0/RP0/CPU0:ios(config)#commit
```

The following is a sample in which performance monitoring parameters of a Coherent DSP controller are configured 30-second intervals.

```
RP/0/RP0/CPU0:ios#configure
RP/0/RP0/CPU0:ios(config)#controller coherentDSP 0/0/1/1 pm 30-sec fec threshold post-fec-ber
 max OE-15
RP/0/RP0/CPU0:ios(config)#commit
```

### Viewing PM Parameters

To view the performance monitoring parameters for Optics, Ethernet, and Coherent DSP controllers, use this command:

**show controllers** *controllertype R/S/I/P* **{ pm { current | history } { 30 sec | 15-min | 24-hour } { optics | ether | fec | otn | prbs}** *linenumber* }

**Example 1:** Displays the current performance monitoring parameters of the Optics controller at 15-minute intervals. Client optics have four lanes.

```
RP/0/RP0/CPU0:ios#show controller optics 0/1/0/3 pm current 15-min optics 3

Sat Feb 9 19:33:42.480 UTC

Optics in the current interval [19:30:00 - 19:33:42 Sat Feb 9 2019]

Optics current bucket type : Valid
            MIN       AVG       MAX      Operational      Configured      TCA   Operational
      Configured     TCA
                                          Threshold(min)   Threshold(min) (min) Threshold(max)
   Threshold(max) (max)
LBC[% ]      : 0.0       0.0       0.0      0.0              NA              NO   100.0
          NA              NO
OPT[dBm]     : -40.00    -40.00    -40.00   -30.00           NA              NO   63.32
          NA              NO
OPR[dBm]     : -40.00    -40.00    -40.00   -30.00           NA              NO   63.32
          NA              NO
FREQ_OFF[Mhz]: 0         0         0        0                NA              NO   0
          NA              NO
```

**Example 2:** Displays the current performance monitoring parameters of the Optics controller 15-minute intervals. Trunk optics have one lane.

```
RP/0/RP0/CPU0:ios#show controller optics 0/2/0/1  pm  current 15-min optics 1


Sat Feb  9 11:19:15.234 UTC

Optics in the current interval [11:15:00 - 11:19:15 Sat Feb 9 2019]

Optics current bucket type : Valid
            MIN       AVG       MAX      Operational      Configured      TCA   Operational
      Configured     TCA
                                          Threshold(min)   Threshold(min) (min) Threshold(max)
   Threshold(max) (max)
LBC[% ]      : 0.0       0.0       0.0      0.0              NA              NO   100.0
          NA              NO

OPT[dBm]     : -1.51     -1.49     -1.48    -30.00           NA              NO   63.32
          NA              NO

OPR[dBm]     : -9.11     -9.07     -9.03    -30.00           NA              NO   63.32
          NA              NO

CD[ps/nm]    : 13        15        18       -180000          NA              NO   180000
          NA              NO
```

```
DGD[ps ]     : 2.00      2.33      3.00     0.01             NA             NO   21474836.46
      NA              NO

SOPMD[ps^2]  : 5.00      33.02     79.00    0.01             NA             NO   21474836.46
      NA              NO

OSNR[dB]     : 31.50     31.97     32.50    0.01             NA             NO   21474836.46
      NA              NO

PDL[dB]      : 0.20      0.34      0.50     0.01             NA             NO   21474836.46
      NA              NO

PCR[rad/s]   : 0.00      19.92     93.00    0.01             NA             NO   21474836.46
      NA              NO

RX_SIG[dBm]  : -9.05     -9.02     -8.99    -30.00             NA               NO   63.32
          NA               NO

FREQ_OFF[Mhz]: -302      -178      -74      -1500              NA               NO   1500
          NA               NO
```

**Example 3:** Displays the current performance monitoring parameters of the Ethernet controller 15-minute intervals.

```
RP/0/RP0/CPU0:ios#show controller HundredGigECtrlr 0/1/0/2 pm current 15-min ether
Fri Aug 30 00:37:53.527 UTC

ETHER in the current interval [00:30:00 - 00:37:53 Fri Aug 30 2019]

ETHER current bucket type : Valid
RX-UTIL[%]                : 100.00              Threshold : 0.00         TCA(enable) : NO
TX-UTIL[%]                : 10.00               Threshold : 0.00         TCA(enable) : NO
RX-PKT                    : 3852414442          Threshold : 0            TCA(enable) : NO
STAT-PKT                  : 0                   Threshold : 0            TCA(enable) : NO
OCTET-STAT                : 5847965122956       Threshold : 0            TCA(enable) : NO
OVERSIZE-PKT              : 0                   Threshold : 0            TCA(enable) : NO
FCS-ERR                   : 0                   Threshold : 0            TCA(enable) : NO
LONG-FRAME                : 0                   Threshold : 0            TCA(enable) : NO
JABBER-STATS              : 0                   Threshold : 0            TCA(enable) : NO
64-OCTET                  : 0                   Threshold : 0            TCA(enable) : NO
65-127-OCTET              : 0                   Threshold : 0            TCA(enable) : NO
128-255-OCTET             : 0                   Threshold : 0            TCA(enable) : NO
256-511-OCTET             : 0                   Threshold : 0            TCA(enable) : NO
512-1023-OCTET            : 0                   Threshold : 0            TCA(enable) : NO
1024-1518-OCTET           : 0                   Threshold : 0            TCA(enable) : NO
IN-UCAST                  : 0                   Threshold : 0            TCA(enable) : NO
IN-MCAST                  : 0                   Threshold : 0            TCA(enable) : NO
IN-BCAST                  : 0                   Threshold : 0            TCA(enable) : NO
OUT-UCAST                 : 0                   Threshold : 0            TCA(enable) : NO
OUT-BCAST                 : 0                   Threshold : 0            TCA(enable) : NO
OUT-MCAST                 : 0                   Threshold : 0            TCA(enable) : NO
TX-PKT                    : 7053588067          Threshold : 0            TCA(enable) : NO
OUT-OCTET                 : 451429636288        Threshold : 0            TCA(enable) : NO
IFIN-ERRORS               : 0                   Threshold : 0            TCA(enable) : NO
IFIN-OCTETS               : 0                   Threshold : 0            TCA(enable) : NO
STAT-MULTICAST-PKT        : 0                   Threshold : 0            TCA(enable) : NO
STAT-BROADCAST-PKT        : 0                   Threshold : 0            TCA(enable) : NO
STAT-UNDERSIZED-PKT       : 0                   Threshold : 0            TCA(enable) : NO
IN_GOOD_BYTES             : 5847965122956       Threshold : 0            TCA(enable) : NO
IN_GOOD_PKTS              : 3852414442          Threshold : 0            TCA(enable) : NO
IN_DROP_OTHER             : 0                   Threshold : 0            TCA(enable) : NO
```

```
OUT_GOOD_BYTES            : 451429636288        Threshold : 0            TCA(enable) : NO
OUT_GOOD_PKTS             : 7053588067          Threshold : 0            TCA(enable) : NO
IN_PKT_64_OCTET           : 0                   Threshold : 0            TCA(enable) : NO
IN_PKTS_65_127_OCTETS     : 0                   Threshold : 0            TCA(enable) : NO
IN_PKTS_128_255_OCTETS    : 0                   Threshold : 0            TCA(enable) : NO
IN_PKTS_256_511_OCTETS    : 0                   Threshold : 0            TCA(enable) : NO
IN_PKTS_512_1023_OCTETS   : 0                   Threshold : 0            TCA(enable) : NO
IN_PKTS_1024_1518_OCTETS  : 3852414442          Threshold : 0            TCA(enable) : NO
OUT_PKT_64_OCTET          : 7053588067          Threshold : 0            TCA(enable) : NO
OUT_PKTS_65_127_OCTETS    : 0                   Threshold : 0            TCA(enable) : NO
OUT_PKTS_128_255_OCTETS   : 0                   Threshold : 0            TCA(enable) : NO
OUT_PKTS_256_511_OCTETS   : 0                   Threshold : 0            TCA(enable) : NO
OUT_PKTS_512_1023_OCTETS  : 0                   Threshold : 0            TCA(enable) : NO
OUT_PKTS_1024_1518_OCTETS : 0                   Threshold : 0            TCA(enable) : NO
TX_UNDERSIZED_PKT         : 0                   Threshold : 0            TCA(enable) : NO
TX_OVERSIZED_PKT          : 0                   Threshold : 0            TCA(enable) : NO
TX_JABBER                 : 0                   Threshold : 0            TCA(enable) : NO
TX_BAD_FCS                : 0                   Threshold : 0            TCA(enable) : NO
```

**Note** Performance monitoring statistics are not supported for IN-UCAST and OUT-UCAST counters for Ethernet clients.

**Example 4:** Displays the current *FEC* performance monitoring parameters of the Coherent DSP controller at 15-minute intervals.

```
RP/0/RP0/CPU0:ios#show controller coherentDSP 0/2/0/1 pm current 15-min  fec


Sat Feb  9 11:23:42.196 UTC

g709 FEC in the current interval [11:15:00 - 11:23:42 Sat Feb 9 2019]

FEC current bucket type : Valid
    EC-BITS   : 291612035786            Threshold : 903330                 TCA(enable)  :
YES
    UC-WORDS  : 0                       Threshold : 5                      TCA(enable)  :
YES

                MIN       AVG        MAX    Threshold   TCA     Threshold   TCA
                                              (min)    (enable)   (max)    (enable)
PreFEC BER  : 7.1E-03   7.2E-03   8.1E-03     0E-15        NO     0E-15       NO
PostFEC BER :   0E-15     0E-15     0E-15     0E-15        NO     0E-15       NO
```

**Example 5:** Displays the current *PRBS* performance monitoring parameters of the Coherent DSP controller 15-minute intervals.

```
RP/0/RP0/CPU0:ios#show controllers coherentDSP 0/0/0/1 pm current 15-min prbs


Mon Feb 13 00:58:48.327 UTC
PRBS in the current interval [00:45:00 - 00:58:48 Mon Feb 13 2019]
PRBS current bucket type : Valid
EBC : 40437528165
FOUND-COUNT : 1 FOUND-AT-TS : 00:51:22 Mon Feb 13 2019
LOST-COUNT : 1 LOST-AT-TS : 00:52:52 Mon Feb 13 2019
CONFIG-PTRN : PRBS_PATTERN_PN31
Last clearing of "show controllers OTU" counters never
```

**Example 6:** Displays the current PCS performance monitoring parameters of the Coherent DSP controller 30-second intervals.

```
RP/0/RP0/CPU0:ios#show controllers hundredGigECtrlr 0/0/0/2 pm current 30-sec pcs
Tue Nov 19 09:17:26.684 UTC

Ethernet PCS in the current interval [09:17:00 - 09:17:26 Tue Nov 19 2019]

Ethernet PCS current bucket type : Valid
BIP[00] : 0 Threshold : 0 TCA(enable) : NO
BIP[01] : 0 Threshold : 0 TCA(enable) : NO
BIP[02] : 0 Threshold : 0 TCA(enable) : NO
BIP[03] : 0 Threshold : 0 TCA(enable) : NO
BIP[04] : 0 Threshold : 0 TCA(enable) : NO
BIP[05] : 0 Threshold : 0 TCA(enable) : NO
BIP[06] : 0 Threshold : 0 TCA(enable) : NO
BIP[07] : 0 Threshold : 0 TCA(enable) : NO
BIP[08] : 0 Threshold : 0 TCA(enable) : NO
BIP[09] : 0 Threshold : 0 TCA(enable) : NO
BIP[10] : 0 Threshold : 0 TCA(enable) : NO
BIP[11] : 0 Threshold : 0 TCA(enable) : NO
BIP[12] : 0 Threshold : 0 TCA(enable) : NO
BIP[13] : 0 Threshold : 0 TCA(enable) : NO
BIP[14] : 0 Threshold : 0 TCA(enable) : NO
BIP[15] : 0 Threshold : 0 TCA(enable) : NO
BIP[16] : 0 Threshold : 0 TCA(enable) : NO
BIP[17] : 0 Threshold : 0 TCA(enable) : NO
BIP[18] : 0 Threshold : 0 TCA(enable) : NO
BIP[19] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[00] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[01] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[02] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[03] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[04] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[05] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[06] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[07] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[08] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[09] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[10] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[11] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[12] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[13] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[14] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[15] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[16] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[17] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[18] : 0 Threshold : 0 TCA(enable) : NO
FRM-ERR[19] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[00] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[01] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[02] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[03] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[04] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[05] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[06] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[07] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[08] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[09] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[10] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[11] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[12] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[13] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[14] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[15] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[16] : 0 Threshold : 0 TCA(enable) : NO
```

```
BAD-SH[17] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[18] : 0 Threshold : 0 TCA(enable) : NO
BAD-SH[19] : 0 Threshold : 0 TCA(enable) : NO
ES : 0 Threshold : 0 TCA(enable) : NO
SES : 0 Threshold : 0 TCA(enable) : NO
UAS : 0 Threshold : 0 TCA(enable) : NO
ES-FE : 0 Threshold : 0 TCA(enable) : NO
SES-FE : 0 Threshold : 0 TCA(enable) : NO
UAS-FE : 0 Threshold : 0 TCA(enable) : NO

Last clearing of "show controllers ETHERNET " counters never
RP/0/RP0/CPU0:BH1_P2A4#
```

**Example 7:** Displays the history *PCS* performance monitoring parameters of the 100GE controller at 30-second intervals.

```
RP/0/RP0/CPU0:ios#show controllers hundredGigECtrlr 0/0/0/2 pm history 30-sec pcs 1
Tue Nov 19 09:27:49.169 UTC

Ethernet PCS in the current interval [09:27:00 - 09:27:30 Tue Nov 19 2019]

Ethernet PCS current bucket type : Valid
BIP[00] : 0
BIP[01] : 0
BIP[02] : 0
BIP[03] : 0
BIP[04] : 0
BIP[05] : 0
BIP[06] : 0
BIP[07] : 0
BIP[08] : 0
BIP[09] : 0
BIP[10] : 0
BIP[11] : 0
BIP[12] : 0
BIP[13] : 0
BIP[14] : 0
BIP[15] : 0
BIP[16] : 0
BIP[17] : 0
BIP[18] : 0
BIP[19] : 0
FRM-ERR[00] : 0
FRM-ERR[01] : 0
FRM-ERR[02] : 0
FRM-ERR[03] : 0
FRM-ERR[04] : 0
FRM-ERR[05] : 0
FRM-ERR[06] : 0
FRM-ERR[07] : 0
FRM-ERR[08] : 0
FRM-ERR[09] : 0
FRM-ERR[10] : 0
FRM-ERR[11] : 0
FRM-ERR[12] : 0
FRM-ERR[13] : 0
FRM-ERR[14] : 0
FRM-ERR[15] : 0
FRM-ERR[16] : 0
FRM-ERR[17] : 0
FRM-ERR[18] : 0
FRM-ERR[19] : 0
BAD-SH[00] : 0
BAD-SH[01] : 0
```

```
BAD-SH[02] : 0
BAD-SH[03] : 0
BAD-SH[04] : 0
BAD-SH[05] : 0
BAD-SH[06] : 0
BAD-SH[07] : 0
BAD-SH[08] : 0
BAD-SH[09] : 0
BAD-SH[10] : 0
BAD-SH[11] : 0
BAD-SH[12] : 0
BAD-SH[13] : 0
BAD-SH[14] : 0
BAD-SH[15] : 0
BAD-SH[16] : 0
BAD-SH[17] : 0
BAD-SH[18] : 0
BAD-SH[19] : 0
ES : 0
SES : 0
UAS : 0
ES-FE : 0
SES-FE : 0
UAS-FE : 0

Last clearing of "show controllers ETHERNET " counters never
RP/0/RP0/CPU0:BH1_P2A4#
```

**Example 8:** Displays the current performance monitoring parameters of the optics controller at 10-second intervals as flexi-bin.

```
RP/0/RP0/CPU0:ios#show controllers optics 0/0/0/0 pm current flex-bin optics 1
Thu May 21 07:43:38.964 UTC

Optics in the current interval [07:43:30 - 07:43:38 Thu May 21 2020]

Flexible bin interval size: 10 seconds

Optics current bucket type : Valid
            MIN       AVG       MAX      Operational      Configured      TCA   Operational
      Configured     TCA
                                          Threshold(min)   Threshold(min)  (min) Threshold(max)
   Threshold(max)  (max)
LBC[% ]       : 0.0       0.0       0.0      0.0              NA              NO    0.0
          NA               NO
OPT[dBm]      : -0.13     -0.10     -0.06    0.00             NA              NO    0.00
          NA               NO
OPR[dBm]      : -3.01     -2.96     -2.92    0.00             NA              NO    0.00
          NA               NO
CD[ps/nm]     : -3        -2        -1       0                NA              NO    0
          NA               NO
DGD[ps ]      : 1.00      1.67      2.00     0.00             NA              NO    0.00
          NA               NO
SOPMD[ps^2]   : 17.00     37.00     81.00    0.00             NA              NO    0.00
          NA               NO
OSNR[dB]      : 37.60     37.60     37.60    0.00             NA              NO    0.00
          NA               NO
PDL[dB]       : 0.60      0.66      0.70     0.00             NA              NO    0.00
          NA               NO
PCR[rad/s]    : 0.00      29.11     80.00    0.00             NA              NO    0.00
          NA               NO
RX_SIG[dBm]   : -3.49     -3.41     -3.36    0.00             NA              NO    0.00
          NA               NO
```

```
FREQ_OFF[Mhz]: 191       241       301       0                 NA                NO   0
          NA                NO
SNR[dB]      : 14.50     14.62     14.70     0.00              NA                NO   0.00
          NA                NO
SNR-AX[dB]   : 17.10     17.19     17.30     0.00              NA                NO   0.00
          NA                NO
SNR-AY[dB]   : 11.90     12.06     12.10     0.00              NA                NO   0.00
          NA                NO
SNR-BX[dB]   : 0.00      0.00      0.00      0.00              NA                NO   0.00
          NA                NO
SNR-BY[dB]   : 0.00      0.00      0.00      0.00              NA                NO   0.00
          NA                NO
SOP-S1       : 0.50      0.55      0.59      0.00              NA                NO   0.00
          NA                NO
SOP-S2       : -0.59     -0.52     -0.48     0.00              NA                NO   0.00
          NA                NO
SOP-S3       : -0.67     -0.64     -0.60     0.00              NA                NO   0.00
          NA                NO

Last clearing of "show controllers OPTICS" counters never
```

**Example 9:** Displays the history performance monitoring parameters of the optics controller at 10-second intervals as flexi-bin.

```
RP/0/RP0/CPU0:ios#show controllers optics 0/0/0/0 pm history flex-bin optics 1 bucket 1
Thu May 21 07:45:44.358 UTC

Optics in interval 1 [07:45:30 - 07:45:40 Thu May 21 2020]

Flexible bin interval size: 10 seconds

Optics history bucket type : Valid
              MIN       AVG       MAX
LBC[% ]    : 0.0       0.0       0.0
OPT[dBm]   : -0.12     -0.10     -0.04
OPR[dBm]   : -3.01     -2.97     -2.91
CD[ps/nm]  : -5        -4        -3
DGD[ps ]   : 1.00      1.50      2.00
SOPMD[ps^2]: 28.00     43.10     66.00
OSNR[dB]   : 37.60     37.60     37.60
PDL[dB]    : 0.60      0.65      0.70
PCR[rad/s] : 0.00      25.70     75.00
RX_SIG[dBm] : -3.49     -3.44     -3.37
FREQ_OFF[Mhz]: 235       272       330
SNR[dB]   : 14.60     14.64     14.80
SNR-AX[dB]: 17.20     17.25     17.30
SNR-AY[dB]: 11.90     12.02     12.20
SNR-BX[dB]: 0.00      0.00      0.00
SNR-BY[dB]: 0.00      0.00      0.00
SOP-S1    : 0.50      0.53      0.57
SOP-S2    : -0.58     -0.53     -0.49
SOP-S3    : -0.69     -0.65     -0.61
```

### Clearing PM Parameters

To clear the performance monitoring parameters for Ethernet and Coherent DSP controllers, use this command:

**clear controller** *controllertype R/S/I/P* **pm**

**Example 1:** Clears the PM parameters on the Coherent DSP controller.

```
RP/0/RP0/CPU0:ios#show controller CD 0/0/0/0 pm current 15-min fec
```

```
Mon Jun 10 11:43:39.981 UTC

g709 FEC in the current interval [11:30:00 - 11:43:40 Mon Jun 10 2019]

FEC current bucket type : Invalid
    EC-BITS   : 308360273               Threshold : 903330                TCA(enable)  :
YES
    UC-WORDS  : 131108352               Threshold : 5                     TCA(enable)  :
YES

                MIN       AVG        MAX    Threshold   TCA     Threshold   TCA
                                              (min)    (enable)   (max)    (enable)
PreFEC BER  : 3.44E-02   3.45E-02   3.45E-02     0E-15        NO     0E-15       NO
PostFEC BER :   0E-15     0E-15     0E-15     0E-15        NO     0E-15       NO
Q           :    0.51      0.51      0.51    0.00        NO      0.00       NO
Q_Margin    :    0.00      0.00      0.00    0.00        NO      0.00       NO

Last clearing of "show controllers OTU" counters never
RP/0/RP0/CPU0:ios#clear controller coherentDSP 0/0/0/0 pm
Mon Jun 10 11:44:31.650 UTC
RP/0/RP0/CPU0:ios#show controller CD 0/0/0/0 pm current 15-min fec
Mon Jun 10 11:44:38.804 UTC

g709 FEC in the current interval [11:30:00 - 11:44:38 Mon Jun 10 2019]

FEC current bucket type : Invalid
    EC-BITS   : 0                       Threshold : 903330                TCA(enable)  :
YES
    UC-WORDS  : 0                       Threshold : 5                     TCA(enable)  :
YES

                MIN       AVG        MAX    Threshold   TCA     Threshold   TCA
                                              (min)    (enable)   (max)    (enable)
PreFEC BER  : 3.44E-02   3.44E-02   3.45E-02     0E-15        NO     0E-15       NO
PostFEC BER :   0E-15     0E-15     0E-15     0E-15        NO     0E-15       NO
Q           :    0.51      0.51      0.51    0.00        NO      0.00       NO
Q_Margin    :    0.00      0.00      0.00    0.00        NO      0.00       NO

Last clearing of "show controllers OTU" counters 00:00:07
```

**Example 2:** Clears the PM parameters on the Ethernet controller.

```
RP/0/RP0/CPU0:ios#clear controller HundredGigECtrlr 0/0/0/2 pm
```

### Viewing PM Statistics

To view PM statistics for the Ethernet controllers, use this command:

```
RP/0/RP0/CPU0:ios#show controllers HundredGigECtrlr 0/0/0/2 stats
Fri Aug 30 13:10:33.123 IST
Statistics for interface HundredGigECtrlr0/0/0/2 (cached values):

Ingress:
    Input total bytes           = 1702197139760640
    Input good bytes            = 1702197139760640

    Input total packets         = 13298415154380
    Input 802.1Q frames         = 0
    Input pause frames          = 0
    Input pkts 64 bytes         = 0
    Input pkts 65-127 bytes     = 0
    Input pkts 128-255 bytes    = 13298415154380
    Input pkts 256-511 bytes    = 0
```

```
    Input pkts 512-1023 bytes   = 0
    Input pkts 1024-1518 bytes  = 0
    Input pkts 1519-Max bytes   = 0

    Input good pkts             = 13298415154380
    Input unicast pkts          = 0
    Input multicast pkts        = 0
    Input broadcast pkts        = 0

    Input drop overrun          = 0
    Input drop abort            = 0
    Input drop invalid VLAN     = 0
    Input drop invalid DMAC     = 0
    Input drop invalid encap    = 0
    Input drop other            = 0

    Input error giant           = 0
    Input error runt            = 0
    Input error jabbers         = 0
    Input error fragments       = 0
    Input error CRC             = 0
    Input error collisions      = 0
    Input error symbol          = 0
    Input error other           = 0

    Input MIB giant             = 0
    Input MIB jabber            = 0
    Input MIB CRC               = 0

Egress:
    Output total bytes          = 1702197139760640
    Output good bytes           = 1702197139760640

    Output total packets        = 13298415154380
    Output 802.1Q frames        = 0
    Output pause frames         = 0
    Output pkts 64 bytes        = 0
    Output pkts 65-127 bytes    = 0
    Output pkts 128-255 bytes   = 13298415154380
    Output pkts 256-511 bytes   = 0
    Output pkts 512-1023 bytes  = 0
    Output pkts 1024-1518 bytes = 0
    Output pkts 1519-Max bytes  = 0

    Output good pkts            = 13298415154380
    Output unicast pkts         = 0
    Output multicast pkts       = 0
    Output broadcast pkts       = 0

    Output drop underrun        = 0
    Output drop abort           = 0
    Output drop other           = 0

    Output error other          = 0

RP/0/RP0/CPU0:ios#
```

**Note** Performance monitoring statistics are not supported for the input unicast packets, output unicast packets, and input error fragments counters for Ethernet clients.